Predicting the retinotopic organization of human visual cortex from

anatomy using geometric deep learning

Fernanda L. Ribeiro[a,b], Steffen Bollmann[c], Alexander M. Puckett[a,b]

[a]School of Psychology, The University of Queensland; Brisbane QLD 4072; Australia

[b]Queensland Brain Institute, The University of Queensland; Brisbane QLD 4072; Australia

[c]School of Information Technology and Electrical Engineering, The University of Queensland; Brisbane

QLD 4072; Australia

Corresponding author:

Fernanda L. Ribeiro

School of Psychology

University of Queensland

St. Lucia QLD 4072

Australia

Email: fernanda.ribeiro@uq.edu.au

Phone: +61432643672

Abstract

Whether it be in a single neuron or a more complex biological system like the human

brain, form and function are often directly related. The functional organization of

human visual cortex, for instance, is tightly coupled with the underlying anatomy with

cortical shape having been shown to be a useful predictor of the retinotopic

organization in early visual cortex. Although the current state-of-the-art in predicting

retinotopic maps is able to account for gross individual differences, such models are

unable to account for any idiosyncratic differences in the structure-function relationship

from anatomical information alone due to their initial assumption of a template. Here

we developed a geometric deep learning model capable of exploiting the actual

structure of the cortex to learn the complex relationship between brain function and

anatomy in human visual cortex such that more realistic and idiosyncratic maps could

be predicted. We show that our neural network was not only able to predict the

functional organization throughout the visual cortical hierarchy, but that it was also

able to predict nuanced variations across individuals. Although we demonstrate its

utility for modeling the relationship between structure and function in human visual

cortex, our approach is flexible and well-suited for a range of other applications

involving data structured in non-Euclidean spaces.

Keywords

human connectome project, fMRI, 7T, vision, cortical surface, manifold, neural

network, machine learning, retinotopy, visual hierarchy

Introduction

Introduction

The modern-day study of visual perception has led to an unprecedented

understanding of the neurobiological mechanisms underlying sensory information

processing in the brain. Although first being of interest to those pursuing basic science,

this understanding has since translated to more practical applications, notably by

inspiring the development of convolutional neural networks (CNNs) (Fukushima, 1980)

which have revolutionized the field of artificial intelligence (Lecun et al., 2015). In the

human visual system, light reaches the retina where it is converted into electrical

impulses that are transferred to the lateral geniculate nucleus and then through a

hierarchy of cortical areas (Figure 1) (Felleman and Van Essen, 1991; Hubel and

Wiesel, 1962; Mishkin et al., 1983). At the bottom level of the hierarchy (primary visual

cortex), neurons with small receptive fields (i.e., the coverage area in the visual field

to which a neuron is responsive) capture simple visual features such as spatial

orientation (Hubel and Wiesel, 1962). As those signals travel through higher order

visual areas (comprised of neurons with increasing receptive field sizes) those simple

visual features are combined, enabling complex features to be mapped from the visual

input. These more complex features range from contours and textures (low to mid-

level) to complete faces near the top of the hierarchy (Kanwisher et al., 1997). This

type of hierarchical processing is imitated by CNNs by using filters with learnable

parameters which are convolved across data representations with the aim of capturing

common features in the input (Seeliger et al., 2018). At early layers of CNNs, those

filters capture simple features, while in deeper layers more complex features are

detected due to the complex combination of the inputs of previous layers. Here, we

report that the story has – in a sense – come full circle. By leveraging recent advances

in the application of CNNs to non-Euclidean spaces (Bronstein et al., 2017), we show

that deep learning can be used to predict the functional organization of the very brain

regions that inspired them (i.e., the areas of the visual cortical hierarchy).

Figure 1 - Hierarchical organization of the visual cortex. The 21 atlas-based (Wang et al.,
2015) visual areas in both left (LH) and right (RH) hemispheres displayed on spherical surface
and fiducial surface (lateral and posterior views) models. Different colors represent different
visual areas. Central legend indicates the name of each visual area.

The visual hierarchy is comprised of a number of functionally specialized cortical visual

areas (Zeki et al., 1991), nearly all of which are organized retinotopically (Grill-Spector

and Malach, 2004; Van Essen, 2004). That is, the spatial organization of the retina

(and hence the visual field) is maintained in each of these cortical visual areas - albeit

in a distorted fashion due to properties such as cortical magnification (i.e., there are

more neurons dedicated to processing foveal vs. peripheral information) (Cohen,

2011; Cowey and Rolls, 1974). Although distorted, this retinotopic mapping is known

to be similar across individuals and the mapping functions between the visual field and

the brain, at least in early visual cortex, can be described by relatively simple

mathematical models (Balasubramanian et al., 2002; Schira et al., 2007). However,

considerable inter-individual variation does exist (Van Essen and Glasser, 2018), and

this variation has been shown to be directly related to variability in gross anatomical

properties like brain size as well as variability in cortical folding patterns and other

anatomical features such as the degree of myelination (Abdollahi et al., 2014; Benson

et al., 2014, 2012; Benson and Winawer, 2018; Hinds et al., 2009; Rajimehr and

Tootell, 2009; Wu et al., 2012). Note, for instance, that the size of primary visual cortex

(V1) and hence its corresponding retinotopic maps vary by a factor of 2-3 between

individuals (Dougherty et al., 2003).

Given the variability in retinotopically organized cortex across individuals, it has

previously been held that obtaining an accurate estimate of a particular individual's

retinotopic maps requires a dedicated empirical experiment. These experiments,

whether done using a conventional phase-encoded design (Deyoe et al., 1996; Engel

et al., 1997; Sereno et al., 1995) or a more modern population receptive field (pRF)

approach (Carvalho et al., 2020; Dumoulin and Wandell, 2008; Zeidman et al., 2018),

are capable of producing robust and detailed estimates of these maps by stimulating

different visual field locations while an individual undergoes an fMRI scan – and then

subsequently examining the elicited cortical activation with respect to the known

spatiotemporal properties of the visual stimulus. These empirically derived maps can

be used specifically to examine the functional organization of the visual cortex or for

more general purposes such as defining visual area boundaries, which is instrumental

for any visual experiment aiming to isolate or compare cortical area specific signals.

Despite being a well-established and reliable approach, collecting the retinotopic

mapping data needed to construct these empirical maps still requires significant

resources (e.g., scan time is usually between 15-60 minutes) and can be impractical

or even impossible in certain circumstances (e.g., some clinical populations). As such,

considerable effort has been dedicated to developing an alternative method for

estimating these maps at the individual level.

As mentioned, the functional organization of the visual hierarchy is tightly associated

with its underlying structure. Given that structural data is easier and less time

consuming (requiring only 5-15 minutes) to collect than functional data, the notion of

predicting the retinotopic maps directly from the underlying structure has been

attractive – and cortical shape has, in fact, been shown to be a useful predictor of

retinotopic organization in early visual cortex (Benson et al., 2014, 2012; Hinds et al.,

2009; Schira et al., 2012; Wang et al., 2015). The current state-of-the-art in predicting

retinotopic maps uses mathematical templates that are warped to an individual's

cortical anatomy and is able to account for gross individual differences in the functional

organization of early visual cortex (Benson et al., 2014, 2012). While becoming widely

used instead of empirical retinotopic mapping and of clear utility (Albers et al., 2018;

Alvarez et al., 2019; Isherwood et al., 2017; Storrs et al., 2020), such models are

unable to account for any idiosyncratic differences in the structure-function relationship

from anatomical information alone – due to their initial assumption of a template. Here,

it was our aim to develop a predictive model capable of capturing the intricate

structure-function relationship of the visual cortex without enforcing a spatially

consistent mapping (i.e., a template), such that more realistic and idiosyncratic maps

could be predicted. To this end, we set out to train a CNN using the most

comprehensive and detailed retinotopy dataset openly available – that from the

Human Connectome Project (HCP) (Benson et al., 2018). Note that this dataset

includes ultra-high field (7T) fMRI retinotopic mapping data of a large number of

participants along with their anatomical data, serving as an ideal dataset for this

endeavor.

Convolutional neural networks are conventionally applied to data represented in two-

or three-dimensional Euclidean space (Figure 2a). A great deal of data, however, is

not best represented in such a simple and regular domain (Bronstein et al., 2017). In

the field of neuroscience, and for retinotopic mapping in particular, data are often

represented on surface models of the brain as many cortical properties only make

sense considering their specific location with respect to the various sulci and gyri (Van

Essen et al., 1998). Indeed, the HCP 7T retinotopy dataset being used here was made

available with the functional and structural data already mapped onto surface-based

representations of the cortex (Benson et al., 2018). These surface models are

essentially sheet-like meshes that are intricately folded in three-dimensional space,

maintaining the geometrical structure of the brain (Borne et al., 2020; Dale et al., 1999;

Van Essen and Glasser, 2018). Importantly, two points on the surface model might be

close to one another in Euclidean space but far apart in terms of cortical distance

following the surface (e.g., on opposing banks in a sulcus). To account for this and

other non-Euclidean properties, techniques have recently been developed that

generalize deep neural network models to non-Euclidean spaces such as surfaces

(Figure 2b) and graphs – with these techniques collectively being referred to as

geometric deep learning (Bronstein et al., 2017).

Figure 2 - Predicting brain function with geometric deep learning. a, Convolution in 3D
Euclidean space involves convolving a conventional 3D kernel across multiple slices of 2D
images. **b,** Convolution on a surface, a non-Euclidean space, involves convolving a B-spline

kernel directly on the surface, in which the kernel is able to aggregate information in local
neighborhoods. **c**, Geometric convolutional neural network architecture. Input data included
curvature and myelin values (vertex features) as well as the connectivity among the ROI
surface vertices (i.e., the surface topology) and their spatial disposition (i.e., their 3D
coordinates) in a template cortical surface (implicit feature). The output data is the vertex-wise
polar angle/eccentricity values. Network parameters were optimized to reduce the difference
between prediction and ground truth using a smooth L1 loss function.

Here, we leveraged these recent advances in machine learning to achieve our aim of

developing a framework capable of learning the complex relationship between the

functional organization of visual cortex and the underlying anatomy using the surface-

based HCP 7T retinotopy dataset. That is, using geometric deep learning we

developed a neural network capable of predicting the retinotopic organization of the

human visual hierarchy (Figure 2c). Our model was not only able to predict the

functional organization of human visual cortex from anatomical properties alone, but

remarkably it was also able to predict nuanced variations across individuals. Although

we show its utility for retinotopic mapping, geometric deep learning is flexible and well-

suited for an abundance of other applications in the field of neuroscience (Gopinath et

al., 2018; Seong et al., 2018; Zhao et al., 2019).

Results

Retinotopic mapping with deep learning

Retinotopic mapping typically involves empirical data collection performed by showing

visual stimuli, which are temporally and spatially controlled, to a participant lying in an

MRI scanner (DeYoe et al., 1996; Dumoulin and Wandell, 2008). Analysis of the fMRI

signals elicited by such stimuli allows the visual field location encoded by each

responsive voxel to be estimated. The visual field locations are usually defined in polar

coordinates resulting in two retinotopic maps: one representing the polar angle (or

clock position) and the other representing the eccentricity (or distance away from

fixation). An example of these empirically derived retinotopic maps for a single

individual is shown in Figure 3 (top row). From these, it can be seen that the polar

angle and eccentricity maps are organized roughly orthogonal to one another – most

easily discerned in early visual cortex (V1, V2, and V3). Since the human visual system

is comprised of multiple retinotopically organized cortical areas, these maps are also

used to demarcate the boundaries of the various areas. The polar angle maps are

particularly useful for this as the boundaries between areas can be identified by

reversals in the progression of the polar angle values. In Figure 3, for example, the

superior boundary between V1 and V2 is found by locating the band at which the polar

angle reverses from progressing from red to yellow, back to red. Likewise the inferior

boundary between V1 and V2 is found where the polar angle representation reverses

from progressing from red to purple, back to red.

To map retinotopically organized areas without the need to collect functional data, we

built a geometric convolutional neural network by stacking spline-based convolution

layers (Fey et al., 2018) to compute convolutions on a manifold (i.e., the cortical

surface model) (Figure 2c). The data serving as input to the network included

curvature and myelin values (determined by the ratio of T1w/T2w images) as well as

the connectivity among vertices forming the surface (i.e., the surface topology) and

their spatial disposition (i.e., their 3D coordinates) in the HCP 32k fs_LR standard

surface space. The output of the model was either the polar angle or eccentricity value

for each vertex of the cortical surface model. Developing the neural network involved

three main steps: (1) *training* the neural network, (2) hyperparameter *tuning*, and (3)

testing the model. Prior to the training step, the 181 participants from the HCP dataset

were randomly separated into three datasets: training (161 participants), development

(10 participants) and test (10 participants). These datasets were used in each of the

above three steps, respectively. During *training*, the network learned the

correspondence between the retinotopic maps and the anatomical features by

exposing the network to each example in the training dataset. Hence, the empirically-

derived retinotopic maps served as the ground truth and the parameters of the neural

network were optimized to minimize the difference between the predicted and

empirical retinotopic maps. Note that the objective function, smooth L1 loss, was

weighted by explained variance from the population receptive field (pRF) modeling

procedure used to generate the retinotopic maps (Benson et al., 2018). Model

hyperparameters, such as the number of layers, were *tuned* (i.e., optimized) by

inspecting model performance using the development dataset. Finally, once the final

model was selected, the network was *tested* by assessing the predicted maps for each

participant in the test dataset. This procedure was followed for each hemisphere and

each type of retinotopic mapping data separately, resulting in four predictive models.

Figure 3 illustrates the predicted retinotopic maps with their corresponding ground truth

(i.e., empirically measured retinotopic maps) for a single participant in the test dataset.

Qualitatively, the predicted maps bear a remarkable resemblance to the ground truth,

appearing to accurately predict the main features of both polar angle and eccentricity

maps. To aid comparison between the empirical and predicted maps a grid of isopolar

angle and isoeccentricity lines has been overlaid upon the maps in early visual cortex.

The grid was drawn based on the ground truth data and then positioned identically on

the predicted maps. Note how well the visual area boundaries (i.e., the isopolar angle

contours) match the predicted maps, running directly through the polar angle

reversals. A similar quality of fit can be seen for the isoeccentricity lines.

Figure 3 - Retinotopic mapping with geometric deep learning. Upper row shows empirical (ground truth) polar angle and eccentricity maps for both left (LH) and right (RH) hemispheres of a single individual from the test dataset (*Participant 1*). Lower row shows the predicted polar angle and eccentricity maps for each hemisphere of the same participant. Polar angles vary from 0º to 360º, while eccentricity values varied from 0º to 12º as indicated by the color wheels. The white grid illustrates isoeccentricity (dashed) and isopolar angle (solid) lines associated with early visual cortex (V1, V2, and V3). Note that V2 and V3 are split around V1 and are comprised of dorsal and ventral components.

Although the grid is focused on early visual areas (due to their organization being most

well understood and hence most reliable to outline), it is important to note that the

neural networks are able to predict the retinotopic organization far beyond early visual

cortex, throughout the visual hierarchy (Figure 4). Being smaller in size, it is difficult to

see the finer retinotopic details in these areas, however, the predicted maps in these

areas do appear to reflect the general organizational features present in the empirical

data. Figure 4 shows the average empirical polar angle maps (left and right

hemispheres) of the test dataset as well as the average predicted maps. On these, we

have explicitly drawn isopolar angle lines (dashed white lines) at phase reversals

based on the average empirical maps and then positioned the grid identically on the

predicted maps as well as on the visual hierarchy parcels as defined by the Wang et

al. (2015) atlas. Note that visual areas boundaries are delineated by reversals in polar

angle representation, near the horizontal meridian (0º - left hemisphere; 180º - right

hemisphere), upper vertical meridian (90º) and lower vertical meridian (270º). As can

be seen in Figure 4, our model was able to capture polar angle reversals beyond early

visual cortex, as seen for IPS0 and IPS1 boundaries in the parietal portion of the visual

cortex, hV4 ventrally, and TO2 in the lateral visual cortex. Notably, despite being

unclear in the average empirical polar angle map, the polar angle reversal between

IPS1 and IPS2 can be seen clearly in the average predicted map (solid black line, left

hemisphere) further demonstrating that our model is able to predict legitimate

retinotopic details beyond early visual cortex. Note, however, that this difference could

also be simply due to our model learning the mean retinotopic organization between

IPS1 and IPS2 from the training dataset rather than reflecting an accurate prediction

at the individual subject level. Additionally, the polar angle reversal between V3b and

LO1 seen in the average empirical map of the left hemisphere was absent in the

average predicted map, suggesting that our model failed to capture this boundary.

264
265

Figure 4 - Polar angle reversals throughout the visual hierarchy. Upper row shows the
average empirical polar angle map from the test dataset, the average predicted map, and the
visual hierarchy parcels for the left hemisphere. Lower row shows the same maps for the right
hemisphere. The dashed white grid illustrates isopolar angle lines associated with boundaries
of visual areas that were drawn based on the average empirical maps. Solid black line

indicates an extra polar angle reversal between IPS1 and IPS2 seen in the average predicted
map of the left hemisphere.

Individual variability in predicted maps

It is clear that the geometric deep learning models can predict the basic retinotopic

organization of human visual cortex and that the predicted maps appear to be in line

with the empirically measured maps for one participant, but are these models capable

of predicting individual variability across participants? Figure 5 shows the results for 4

additional participants from the test dataset. For brevity, we only show the polar angle

maps from the left hemisphere, but all the predicted maps for each test dataset

participant are included as supplementary material (Supplementary Figures 1 and 2).

In Figure 5a, the empirical polar angle maps are marked by unusual and/or

discontinuous polar angle reversals. In the first three maps (Figure 5a, Participants 2-

4), a discontinuous representation of the lower vertical meridian (that is, the

boundaries between V1 and dorsal V2 as well as at the anterior border of dorsal V3)

can be observed – indicated by the gray lines. Importantly, these unique variations

were correctly predicted by our model. Perhaps even more striking, we see that these

borders have merged to form a Y-shape for Participant 5, which was also observed in

the predicted map. Importantly, a simple average map is unable to capture these clear

examples of individual variability (Figure 5a, bottom row).

Figure 5 - Individual variability in retinotopic maps. a, First row shows empirical (ground truth) polar angle maps and second row shows their respective predicted polar angle maps for four participants in the test dataset. The third row shows the average polar angle map from the training dataset. Grey lines indicate unique polar angle representations that were predicted by our model. **b**, Upper row shows the prediction error of each individual map and lower row shows how variable the same given map is from all the other predicted maps in the test dataset. White arrows indicate regions that differed the most among predicted maps.

To further assess the performance of our models, the difference (given by the smallest

difference between two angles – Equation 2) between the predicted and the empirical

(ground truth) polar angle values was determined in a vertex-wise manner (upper row,

Figure 5b). This error estimate was then displayed on a template cortical surface mesh

to inspect where our models perform well and where they suffer. Predictions differed

most from the ground truth near the foveal confluence (i.e., where the V1, V2, and V3

foveal representations merge), at the most peripheral eccentricities, and in some of

the higher order visual areas (particularly those located dorsally in the intraparietal

sulcus). Notably, each of these regions are known to be problematic when measuring

retinotopic maps empirically. For example, it has been shown that retinotopic

measurements within the foveal confluence are often not well represented due to

instrumental and measurement limitations (Wandell and Winawer, 2010). The errors

seen at the most peripheral eccentricities likely manifest from the suppressive effects

seen in the cortex for retinotopic locations immediately outside the most peripheral

limit of the visual stimuli (Puckett et al., 2014; Shmuel et al., 2002). Finally, the higher

order areas are also known to be more difficult to map empirically using conventional

procedures due to their smaller size and their higher degree of selectivity to specific

types of stimuli (Wandell and Winawer, 2010). This brings us to an important caveat:

the empirical maps, although treated as ground truth, may themselves misrepresent

the underlying retinotopic organization. Accordingly, Figure 6 shows the average

explained variance (R^2) associated with the original pRF analysis of the empirical

retinotopic mapping data (Benson et al., 2018) and as such, can be seen as a proxy

for the quality of our ground truth. Pertinently, it shows that quality of the empirical data

is indeed lowest in the regions where our model predictions were most error-prone –

e.g., in the foveal confluence (Figure 6, arrow a), at the most peripheral eccentricities

(Figure 6, arrow b), and in some of the higher-order areas (Figure 6, arrow c). Despite

being a reasonable estimate of the quality of the data, the explained variance is an

indirect and somewhat noisy measure. For example, the explained variance can be

systematically high even when the pRF estimate is wrong – depending on details such

as vessel location. Because the explained variance is systematically high in some

parts of the visual cortex and systematically low in others, it can essentially be

considered another visual field map. Here we use these maps to weight our loss

function (see Methods); however, it would also be possible to train the network to

predict these maps in addition to the eccentricity and polar angle maps.

Figure 6 - Quality of the empirical retinotopic mapping data. Average explained variance
(R^2) map of pRF modeling (Benson et al., 2018) from all participants in the test dataset. Arrows
indicate the foveal confluence (a), peripheral eccentricities (b), and some of the higher-order
areas (c) where explained variance is lowest.

Similar to the error estimates, we were interested in quantifying the extent to which

each individual's predicted map within the test dataset varied from the others. For this

we computed an individual variability estimate as the difference (Equation 2) between

a particular predicted map and each of the other predicted maps in the test dataset in

a vertex-wise manner and averaged across all comparisons. Results are shown in

Figure 5b, lower row. As expected, locations that more prominently differed among

predicted maps in early visual cortex were the areas in and near the unique

discontinuities seen around the lower vertical meridian lines in the polar angle maps

(Figure 5, white arrows).

To further assess the accuracy of our individual predictions, we compared the

performance of our model to a simple average of the retinotopic maps (computed

using the training dataset, see Supplementary Figure 3) in predicting polar angle,

eccentricity, and pRF center location. To this end, we quantified the mean error over

vertices within the range of 1-8º of eccentricity within a few regions of interest: (1)

dorsal V1-3 (Wang et al., 2015), where we see most of the unique variation in the early

visual cortex (Figure 5 and Supplementary Figure 1), (2) the entire early visual cortex,

and (3) higher order visual areas (Figure 7). Figure 7a shows a diagram of the three

different error metrics used to quantify the vertex-wise difference between predicted

and empirical (1) polar angle, (2) eccentricity, and (3) pRF center location values. The

pRF center location is determined by both the polar angle and eccentricity values for

each vertex, and as such, the mislocalization of the pRF center is not independent but

rather a composite of the other two error measures. Note that the difference (i.e.,

distance in the visual field) between the predicted and empirical pRF center location

was then divided by the empirical eccentricity value from each participant to prevent

errors at high eccentricity from dominating the error metric (Benson and Winawer,

2018).

The reduction in the mean error afforded by our model in the dorsal portion of V1-3

(Figure 7b) indicates that the variations generated by our model more accurately

represent an individual's polar angle map ($p < 0.01$, two-sided repeated measures t-

test). However, this is less prominently seen at the entire early visual cortex ($p = 0.11$,

two-sided repeated measures t-test), likely due the lower variability of the ventral

portion of V1-3, and even less in higher order areas ($p = 0.46$, two-sided repeated

measures t-test), where there is no clear improvement/deterioration in prediction

accuracy with our model. Interestingly, while our approach did not generate more

accurate eccentricity maps than a simple average map at the dorsal portion of V1-3

and the entire early visual cortex, we found a significant improvement with our model's

predictions at higher order visual areas ($p < 0.01$, two-sided repeated measures t-test).

Finally, we found that using both the eccentricity and polar angle maps generated by

our approach to estimate pRF center location was significantly more accurate than

only using average maps in both the dorsal portion of V1-3 ($p < 0.01$, two-sided

repeated measures t-test) and higher order visual areas ($p < 0.001$, two-sided

repeated measures t-test). The mean prediction error averaged over the test dataset

of the four predictive models in comparison to the average maps are summarized in

Supplementary Table 1. The mean vertex-wise explained variance of the four

predictive models are in Supplementary Table 2. Finally, we also compared our polar

angle predictions for the left hemisphere at the dorsal portion of V1-3 with different

pRF fits (split halves, see Methods), and we found they were consistently more

accurate than the average map (Supplementary Table 3 and Supplementary Table 4).

Figure 7 - Prediction error based on predicting individual's retinotopic map using our model and using an average retinotopic map. a, Diagram of the three different error metrics used to quantify the vertex-wise difference between predicted (by either our model or an average map) and empirical polar angle (left), eccentricity (middle) and pRF center location (right) values. **b,** Vertex-wise errors were averaged over vertices within the range of 1-8° of eccentricity within the dorsal portion of V1-3, early visual cortex, and higher order visual areas

for each individual from the test dataset (10 individuals). Dark red points illustrate the mean
prediction error of average maps based predictions for each individual, while light red points
illustrate the mean prediction error of our models' predicted maps. *p < 0.01

Variability guided by anatomical features

To demonstrate the importance of the anatomical features in shaping individual

differences in the functional organization of the visual cortex, we predicted three new

sets of retinotopic maps using the previously trained model for each participant after

manipulating the input by (1) rotating the anatomical feature maps, (2) randomly

shuffling the anatomical input features, and (3) setting the input features equal to a

constant value (equal to the mean curvature and myelin values) (see Figure 8a for

examples of these manipulated feature maps). Generally, we expected that disrupting

the input features in these ways would result in higher error across predicted maps.

More specifically, (1) rotating the feature maps results in a set of statistically intact

input features; however, the anatomical information is from outside of visual cortex

and hence should not be predictive of the functional organization therein. (2) Random

shuffling of the anatomical features produces inputs that retain the same set of values

from within visual cortex; however, the statistical structure among this information will

be destroyed. Hence, if the spatial disposition of anatomical features on the cortical

surface is important for predicting individual variability in retinotopic maps, this too

should lack predictive power compared to using intact anatomical features. Finally, (3)

by completely removing the variability present in the input features it was expected

that not only would prediction accuracy suffer due to the lack of intact, patterned

anatomical features, but so would the model's ability to predict any individual

variability.

Contrasting the four sets of maps (Figure 8b) confirms the expectation that

manipulating the input features generally leads to less accurate predictions compared

to those generated using intact input values – especially in the dorsal portion of the

early visual cortex where most of the variability was seen across individuals (Figure 5

and Supplementary Figure 4). As expected, using anatomical information from outside

visual cortex (i.e., rotated input features) produced maps that are largely disrupted,

with nearly no retinotopic structure matching the ground truth. Randomly shuffling

anatomical features similarly led to less accurate predictions; however, the predicted

maps are not nearly as disrupted as for the rotated input patterns. Without a structured

input, it appears the model predictions tend toward the mean of the retinotopic

organization learned by the network from the shape of the cortical surface template.

This likely reflects the fact that shuffled input features resemble constant input feature

maps with the addition of unstructured noise, such that input values vary around the

mean without any additional coherent spatial organization. Indeed, this can be further

appreciated by examining the predictions associated with the constant inputs, which

led to maps similar to those generated with shuffled input features. Here, again in a

case where the statistical structure of the input data is lacking and is in no way

biologically plausible, the model predictions contain recognizable retinotopic structure

that tends toward the mean. However, it is important to note that despite these

predictions being relatively accurate in some regions, they completely lack the

nuanced differences seen across participants when using the intact anatomical feature

patterns (or any differences at all in the case of using a constant input). Together,

these results suggest that our model is relying on the spatial pattern of anatomical

features to tune the general retinotopic organization learned from the shape of the

cortical surface (i.e., surface topology) to generate accurate predictions at the

individual level.

Figure 8 - Individual variability in predicted maps is determined by the spatial arrangement and variability of anatomical features. a, An example of the new set of input features generated for each participant after (1) rotating the features maps (second column), (2) randomly shuffling the anatomical input features (third column), and (3) setting the input

447 features equal to a constant value (fourth column). **b,** Top row shows empirical polar angle
448 maps (ground truth), followed by the predicted polar angle maps using the empirical
449 anatomical features (second row) and each of the three new sets of retinotopic maps
450 generated using rotated feature maps (third row), shuffled features (fourth row), and input
451 features equal to a constant value (fifth row).

Individual variability and genetic dependency

Although the HCP 7T retinotopy dataset contained mapping data for 181 different

participants, not all datasets were strictly independent due to the presence of a large

number of twin pairs (50 pairs of monozygotic and 34 pairs of dizygotic twins). For the

previous results, we used data from all the participants to maximize the number of

training examples seen by our network. However, given the genetic dependency

among participants in our training and test data (all 10 of our test participants had a

twin in the training set), we repeated the model training with a reduced training sample

by excluding the twins of the participants in the test dataset from the training dataset.

Importantly, the resulting model was still able to predict the retinotopic organization of

visual cortex as well as unique variations in polar angle maps without exposure to the

genetically-related mapping data (Supplementary Figure 5).

Discussion

This study shows that deep learning can be used to predict the functional organization

of visual cortex from anatomical features alone by building neural networks able to

predict retinotopic maps throughout the visual cortical hierarchy. Remarkably the

networks were able to predict unique features in these maps, showing sensitivity to

individual differences. Practically, these predictions can be used to demarcate cortical

visual areas within individuals according to known retinotopic mapping principles

(Amano et al., 2009; Arcaro et al., 2009; DeYoe et al., 1996; Engel et al., 1997; Hansen

et al., 2007; Sereno et al., 1995, 2001; Silver and Kastner, 2009; Swisher et al., 2007;

Wandell et al., 2007; Wandell and Winawer, 2010). However, it is important to note

that the utility of our current models extends well beyond finding area boundaries as

the models were not trained to simply predict visual areas but to predict detailed,

vertex-wise retinotopic maps across the visual areas. Hence, our predictions can also

be used to examine cortical responses as a function of eccentricity and polar angle –

all without empirical data collection.

Individual variability in retinotopic maps

Visual cortex has long been known to be organized retinotopically, and understanding

the nature of the relationship between the spatial pattern on the retina and its cortical

representation has been an active area of research. It has been shown that this

relationship can be described using relatively simple mathematics, at least for early

visual cortex (Balasubramanian et al., 2002; Schira et al., 2010; Schwartz, 1977). It

was then shown that these analytic models can serve as templates to be subsequently

warped to an individual's cortical anatomy to predict the functional organization of early

visual cortex (Benson et al., 2014, 2012). Similar to our approach, these predictions

are based on individual's anatomical structure. However, this previous approach

assumes a rigid structure-function relationship through the use of the template, and

hence despite being able to account for gross structural differences across

participants, it is unable to account for any idiosyncratic differences in the structure-

function relationship. The dependency on the template also prevents the application

of this approach to areas outside early visual cortex where mathematical models of

the retinotopic organization are lacking. Following this work, Benson and Winawer

(2018) built a Bayesian model for predicting retinotopic maps that addressed these

shortcomings through the addition of a small amount of empirical mapping data

(Benson and Winawer, 2018). That is, the interpolated template map is used as a prior

that can be further adjusted based on collected functional data. Critically, while this

approach is able to predict some of the idiosyncratic differences seen across

individuals, it is unable to do so from anatomical information alone. See

Supplementary Table 5 for a further comparison of our approach to these others.

Differently from the current state-of-art models of retinotopic maps, our model was

capable of capturing the intricate structure-function relationship of the visual cortex

without enforcing a spatially consistent mapping (i.e., a template). It is often assumed

that the dorsal third tier visual cortex is occupied by a single continuous area (V3) that

extends all the way along the dorsal border of V2 (Benson et al., 2014; Benson and

Winawer, 2018; Wang et al., 2015). However, research suggests that there may be a

more complicated organization of the dorsal third tier visual cortex in non-human

primates (Angelucci and Rosa, 2015; Zhu and Vanduffel, 2019) as well as in humans

(Arcaro et al., 2015). In fact, the same Y-shaped (or forked) lower vertical meridian

that our model was able to predict in dorsal visual cortex of Participant 5 (Fig 5 and 8)

has been reported by other researchers and in multiple individuals (Van Essen and

Glasser, 2018). Electrophysiological recording from a multiunit electrode study in

macaques suggests that the dorsal third tier visual cortex is not comprised of a single

continuous area, but rather two visual areas, with a discontinuity at the lower vertical

meridian representation at the anterior border of dorsal V3 (Gattass et al., 1988).

Although the organization of the dorsal third tier visual cortex remains to be further

investigated in humans, the discontinuous representation of the anterior border of

dorsal V3 has been seen in some individuals in published work from different labs

(Allen et al., 2021; Arcaro and Kastner, 2015; Benson and Winawer, 2018; Van Essen

and Glasser, 2018). Therefore, the ability of our model to predict the discontinuous

representation of the lower vertical meridian at the anterior border of dorsal V3

suggests that this discontinuity is most likely a real structure-related variation, worthy

of further investigation.

Finally, to show the importance of the anatomical features in shaping individual

differences in the functional organization of the visual cortex, we investigated how

different manipulation strategies of the input features would impact our model's

predictions (Figure 8). We found that spatially structured input features (i.e. intact

anatomical information) from outside visual cortex (rotated input features) produced

maps that were largely disrupted, with nearly no retinotopic structure matching the

ground truth. On the other hand, spatially unstructured input features (randomly

shuffled or constant features) also led to less accurate predictions, although predicted

maps were not nearly as disrupted as for the rotated input patterns. These results

suggest that our model is relying on the spatial pattern of anatomical features to tune

the general retinotopic organization learned from the shape of the cortical surface (i.e.,

surface topology) to generate accurate predictions at the individual level. In other

words, the ventral V1/V2 boundary, for instance, is highly conserved in its relative

position across individuals, which is determined by the anatomical features. This

suggests that our model has learned that this boundary goes in a particular absolute

position on the cortical surface template, which explains why it was intact even in maps

generated with shuffled, constant, and to some extent rotated input features. For areas

with higher individual variability (i.e. dorsal portion of V1-3), the spatial arrangement

of anatomical features seems to more directly inform the positioning of polar angle

reversals, explaining their absence in maps generated with shuffled, constant, and

rotated input features. While these analyses were exploratory, our findings make

provision for hypothesis-driven interpretability investigations.

Limitations and Future Directions

Although our neural network was able to predict the main features of retinotopic maps

as well as nuanced differences across individuals, there were regions where prediction

accuracy suffered. The highest errors were seen near the foveal confluence, at the

most peripheral eccentricities, and in some of the higher order visual areas. Amongst

the possible reasons for this discrepancy, we have already mentioned one: the

network's ability to generate accurate predictions is determined largely by the quality

of the training data. The quality of the training data is reflected to some extent in the

explained variance associated with the original pRF analysis (Benson et al., 2018),

which suggests that the retinotopic mapping values given by the pRF analysis are

least reliable (i.e., lowest explained variance) in exactly the same regions where our

model predictions were most error-prone (Figure 6). Considering the intrinsic difficulty

of mapping these regions and the fact that fMRI data cannot offer perfect

representations of the underlying neuronal activity, we weighted the loss function by

the fraction of explained variance from the pRF solution of each vertex (Benson et al.,

2018; Benson and Winawer, 2018) (see Methods), and hence by design, our model

was trained to generate better predictions in regions with more reliable pRF estimates.

Future work using stimuli tailored for the activation of these regions could be

performed to test the assertion that the predictions would improve by providing the

neural network with higher quality training data.

Another possible reason for less accurate predictions in some regions of visual cortex,

especially the higher-order areas, is that the functional organization of these regions

may simply not be as strongly coupled with the underlying anatomical properties. The

location and organization of many visual areas outside early visual cortex (V1/V2/V3)

remain controversial, and this can be attributed to a variety of reasons, ranging from

instrumental and measurement limitations (Wandell and Winawer, 2010) to data pre-

processing steps (e.g., inaccurate cortical surface alignment). Hence, it has proven

difficult to study the particular structure-function relationship in these areas compared

to early visual cortex. A systematic assessment of the effects of training data on

predictions may provide insight into the degree to which the functional organization is

coupled to the underlying anatomical properties. For example, if model accuracy does

not improve in the higher-order areas despite better training data, it may indicate that

the functional organization is less tightly coupled with the underling anatomical

properties – at least the ones used here (i.e., curvature and myelin). Note that in such

case, and even for the regions that are well-predicted, another future direction to

improve the model predictions might be to include different input features. Although

we tested two anatomical features known to be related to retinotopic organization,

other anatomical parameters can be drawn from T1-weighted images, such as cortical

thickness, which can easily be incorporated as input features to train new models.

Additionally, it remains to be further investigated if using individual-specific surfaces

(Gopinath et al., 2018) as opposed to interpolating individual's anatomical features

onto a template surface affords an increment in prediction accuracy of retinotopic

maps. Moreover, one could also include non-anatomical features known to vary

according to retinotopic organization such as functional connectivity measures (Griffis

et al., 2017; Park et al., 2018) in order to improve prediction accuracy.

Besides reducing the amount of resources required to obtain high-quality and

idiosyncratic retinotopic maps, there are many other potential uses for CNNs as

implemented here. Having successfully been able to predict vertex-wise retinotopic

maps that can subsequently be used to identify individual visual areas, presumably

our approach could be modified to infer the visual area parcellations directly by training

the network to classify each vertex with respect to its known visual area rather than

visual field location. Pertinently, the HCP dataset has recently been annotated with

individual-specific boundaries for V1, V2, and V3 (Benson et al., 2021), which could

be integrated directly into our geometric deep learning framework for this purpose.

There are also a number of disorders with known correlates in their visual field map

properties/activity patterns across the visual areas (e.g., prosopagnosia and dyslexia)

(Demb et al., 1997; Witthoft et al., 2016). Accordingly, the learning objective of our

model could be altered to predict disease state from appropriate data. And finally,

although we have primarily been discussing visual cortex, this approach can easily be

deployed to achieve similar goals in other topographically organized areas in the brain,

including somatosensory (Puckett et al., 2020; Sanchez Panchuelo et al., 2018) and

auditory cortices (Da Costa et al., 2015; Saenz and Langers, 2014).

Geometric deep learning in neuroscience

A key aspect of this work was the use of a geometric approach, which permitted deep

learning to be performed directly on the cortical surface model. Doing so, we were able

to take advantage of the actual structure of the brain and hence more appropriately

represent the data to the neural network. Geometric deep learning provides tools that

facilitate the filtering of features along the surface representation. Importantly, such an

approach avoids the mixing of information across inappropriate spatial domains by

allowing convolutions only along the cortical sheet. This stands in stark contrast to

conventional deep learning approaches, which operate through convolution across

Euclidean space. Although it would be possible to employ a more traditional form of

deep learning using the volumetric MRI data (i.e., a stack of 2D slices), this would

result in the convolutions being performed such that information would be mixed

across regions that are not spatially contiguous in the actual brain (e.g., across sulci

or even hemispheres) and across regions containing data that are irrelevant for the

given task (e.g., white matter and cerebral spinal fluid). With this respect, it is important

to note that it was not the goal of our study to demonstrate the superiority of geometric

deep learning over more traditional forms of convolutional neural networks. Rather, it

was our aim to demonstrate an apposite application of geometric deep learning in

neuroscience (i.e., for a task associated with spatially patterned information distributed

across the cortical surface).

Here, the geometric deep learning approach was used to model the relationship

between structural brain data and functional brain data; however, the potential for this

technique transcends this particular use case as a similar approach can be applied to

model relationships among task-based activation patterns, functional connectivity,

structural information, sensory spaces, behavioral measures, and much more.

Importantly, it is not at all rare for data to better be represented in a non-Euclidean

space than in the Euclidean one. For example, also within the field of neuroscience,

brain functional networks are often represented as graphs (i.e., connectomes) in which

connections between two brain regions do not necessarily represent the physical

distance between them. Geometric deep learning, being also well-suited for graph

data (Bronstein et al., 2017; Zhang and Bellec, 2019), offers the field a powerful tool

given the growing interest in predicting aspects of human behavior from these

functional connectivity graphs (Cai et al., 2020; Dadi et al., 2019; Finn et al., 2015;

Fountain-Zaragoza et al., 2019; Gao et al., 2019; Shen et al., 2017).

Methods

Participant information and data overview

Comprehensive information about the HCP 7T retinotopy dataset is given elsewhere

(Benson et al., 2018). Briefly, complete retinotopic mapping and structural data were

acquired for 181 participants (109 females, age 22-35) following the HCP protocol

(Benson et al., 2018; Van Essen et al., 2013). All participants had normal or corrected-

to-normal visual acuity. Among these participants, 100 individuals are genetically

confirmed monozygotic twins (50 pairs), 68 individuals are dizygotic twins (34 pairs),

4 individuals are non-twin siblings (2 pairs), and 9 individuals whose twin/siblings were

not included and/or were not genetically tested. Structural image acquisition included

T1w and T2w structural scans at 0.7 mm isotropic resolution at a customized Siemens

3T Connectome scanner (Van Essen et al., 2013). White and pial cortical surfaces

were reconstructed from the structural scans using FreeSurfer

(http://surfer.nmr.mgh.harvard.edu/) and were aligned across participants to the HCP

32k fs_LR standard surface space (Glasser et al., 2013). Myelin maps were

determined by the ratio of T1w/T2w images (Glasser and Van Essen, 2011) and

appropriately normalized to account for B1+ transmit effects (Glasser et al., 2013).

Whole-brain fMRI data were acquired using a Siemens 7T Magnetom scanner at a

resolution of 1.6mm isotropic and 1s TR. The data were processed using the HCP

pipeline (Glasser et al., 2013), which involved correction for head motion and EPI

spatial distortion, alignment of the fMRI data with the HCP standard surface space,

and denoising for spatially specific structured noise. The data produced (in CIFTI

format) by the pipeline consists of 91,282 grayordinates: 32,492 cortical vertices per

hemisphere and 26,298 subcortical voxels with approximately 2mm spatial resolution.

All data are publicly available on the ConnectomeDB database
(https://db.humanconnectome.org).

Retinotopic mapping details

To build our deep learning model, we used previously analyzed retinotopic mapping
data (Benson et al., 2018) – made available at
https://balsa.wustl.edu/study/show/9Zkk as scene files. These files can be visualized
using Connectome Workbench and are efficiently handled using the MATLAB GIFTI
library and Fieldtrip toolbox. For complete details on the experimental design and
analysis procedure used to produce the maps, please refer to Benson et al. (2018)
(Benson et al., 2018). In brief, retinotopic stimuli were constrained to a circular region
with a diameter of 16º. They consisted of slowly moving apertures of achromatic pink-
noise background with dynamic colorful texture object, which was designed to elicit
strong neural responses throughout the visual hierarchy – including in higher order
visual areas. The experiment consisted of 6 runs with different set of apertures:
wedges, rings and bars. Each aperture was presented twice, changing the direction of
movement between runs, except for bar stimuli runs which were identical. Ring stimuli
consisted of 8 cycles of a ring expanding away from the center or contracting towards
the center with a period of 32s. Wedges stimuli consisted of 8 cycles of 90º wedges
rotating across the visual field counterclockwise or clockwise with a period of 32s.
Finally, each bar stimuli run consisted of bars with different orientations (4 orientations)
moving across different directions in visual field. During each condition, participants
were to attend to a semitransparent dot located at the center of the display and report
whenever the color of the dot changed (via a button press) to ensure their gaze were
fixed at the center of the display.

A pRF modeling procedure was then used to construct the retinotopic maps (Benson

et al., 2018; Kay et al., 2013). Essentially, this modeling procedure estimates the

spatial sensitivity profile within the visual field to which a grayordinate is responsive

(i.e., its receptive field). For this, the fMRI time series elicited by the retinotopic

mapping stimuli described above are modeled as the sum of a stimulus-related time

series and a baseline time series. The stimulus-related response is then obtained by

computing the dot product between the stimulus aperture time series and a 2D

isotropic Gaussian (representing the pRF), applying a non-linearity component and

rescaling the result by a gain factor, and then convolving it with a canonical

hemodynamic response function. The modeled fMRI time series is optimized in order

to best match the real fMRI time series by changing the 2D isotropic Gaussian

parameters, such as its center position (x and y coordinates) and size, as well as the

gain factor. Once the best parameters are determined, it is possible to construct

retinotopic maps using each grayordinate's preferred location in the visual field (i.e.,

its pRF's center location). Polar angle maps reflect the polar angle in visual field to

which a grayordinate is most responsive, while eccentricity maps reflect the distance

from the center of the visual field (i.e., the fixation point) to which a grayordinate is

most responsive. Note that the pRF modeling procedure is fully described in Benson

et al. (2018).

Definition of the region of interest

As mentioned, the data files consisted of 91,282 grayordinates: 32,492 cortical surface

vertices per hemisphere and 26,298 subcortical voxels. Here, we restricted the

analysis to the cortical surface, hence ignoring the subcortical voxels. We further

restricted our region of interest (ROI) to only include vertices within visual cortex using

a surface-based probabilistic atlas (Wang et al., 2015). We modified the atlas slightly

by extending the early visual cortex (V1, V2, V3) ROIs to include the foveal confluence

(Schira et al., 2009) as well as combining ventral and dorsal components which are

labelled separately in the original atlas (Figure 1). We also excluded the frontal eye

fields (FEF) due to its discontinuity with the remaining areas. After selecting only

vertices within this region of interest, we were left with 3,267 vertices for the left

hemisphere (3,219 vertices of the right hemisphere), adding up to 19,024 connections

(edges) between pairs of vertices (18,760 edges for the right hemisphere).

Data for deep learning

Our goal was to develop and train a deep neural network to predict the functional

organization of the visual cortex (i.e., the retinotopic maps) from underlying anatomical

properties (Figure 2). The anatomical data serving as input to the neural network

included the mean curvature and myelin values (both of which have been shown to be

related to the functional organization of visual cortex), which are explicit features, as

well as the connectivity among the ROI surface vertices (i.e., the surface topology)

and their spatial disposition (i.e., their 3D coordinates) in the HCP 32k fs_LR standard

surface space, implicit features. The output of the model was either the polar angle or

eccentricity value for each vertex of the cortical surface model. Note that polar angle

values are cyclical (i.e., $360^\circ = 0^\circ$). To avoid issues with the discontinuity in values, we

shifted the polar angle values so that each hemisphere was trained with the point of

wrap-around (from 360° to 0°) positioned at the horizontal meridian in the contralateral

hemifield. After training, the values were shifted back to their original range.

For the modeling procedure, the data was represented on the midthickness cortical

surface model (S1200_7T_Retinotopy181.L(R).midthickness_MSMAll.32k_fs_LR.

surf.gii). Importantly, this model is a fiducial surface that maintains the actual geometry

of the brain. Our results are, however, displayed using a spherical surface model

(S1200_7T_Retinotopy181.L(R).sphere.32k_fs_LR.surf.gii)   for   visualization

purposes. This permits all visual areas to be displayed in a single view.

Developing the neural network

Developing the neural network involved three main steps: (1) *training* the neural

network, (2) hyperparameter *tuning*, and (3) *testing* the model. Prior to the training

step, the 181 participants from the HCP dataset were randomly separated into three

datasets: training (161 participants), development (10 participants) and test (10

participants) datasets (Supplementary Table 6). These datasets were used in each of

the above three steps, respectively. During *training*, the network learned the

correspondence between the retinotopic maps and the anatomical features by

exposing the network to each example in the training dataset. Hence, the empirically-

derived retinotopic maps served as the "ground truth" and the parameters of the neural

network were optimized to minimize the difference between the predicted and

empirical retinotopic maps. Model hyperparameters, such as the number of layers,

were *tuned* (i.e., optimized) by inspecting model performance using the development

dataset. Finally, once the final model was selected, the network was *tested* by

assessing the predicted maps for each participant in the test dataset. This procedure

was followed for each hemisphere and each type of retinotopic mapping data (i.e.,

polar angle and eccentricity) separately, resulting in four predictive models.

Model architecture and training

We implemented a spline-based convolutional neural network (SplineCNN) (Fey et al.,

2018) on cortical surfaces using PyTorch Geometric (Fey and Lenssen, 2019), a

geometric deep learning extension of PyTorch. Among the broad range of methods

defining convolution operations on irregular structured data, such as graphs and

surfaces, spline-based convolution is amidst the spatial filtering approaches. In these

approaches, filters aggregate information locally, around a vertex's neighborhood.

These filters exploit information given by relative positions of the neighbor vertices with

respect to the reference vertex in addition to the information encoded in the

connectivity, edge weights, and vertex features. Thus, SplineCNN aggregates vertex

features in local neighborhoods weighted by learnable parameters of a continuous

kernel function (Fey et al., 2018).

Following the original study, we denote spline-based convolutional layers as

SConv(k,M_{in},M_{out}) of which k is the kernel size, M_{in} is the number of input feature maps,

and M_{out} is the number of output feature maps (Figure 2). Our final model architecture

included 12 convolutional layers with the number of feature maps increasing to a

maximum of 32 feature maps per layer, and then decreasing back to one final feature

map. We fixed the kernel size (k) to 25 for all layers, as predicted maps looked

smoother than the ones generated with smaller kernel sizes. A non-linear activation

function, the exponential linear unit (ELU), was used after each convolution layer.

Batch normalization and dropout (p=0.10) were applied to all layers, except the last.

Batch normalization is an approach commonly used in the field of machine learning to

automatically normalize each layer's input data, preventing the shift of the input data

distribution during training, which results in faster training and lower variability among

models (Frankle et al., 2020; Ioffe and Szegedy, 2015). Dropout refers to a

regularization method used to prevent model overfitting (Srivastava et al., 2014). In

our model, we only used Cartesian coordinates to compute relative distance between

vertices and the degree of B-spline basis m = 1, due to the fact that models with those

parameters showed better performance than the models using higher degree of B-

spline basis or using spherical coordinates in previous experiments (Fey et al., 2018).

Training was carried out for 200 epochs with a batch size of 1 and a learning rate at

0.01 for 100 epochs that was then adjusted to 0.005, using Adam optimizer. Our

models' learning objective was to reduce the difference between predicted retinotopic

map and ground truth (i.e., the empirical retinotopic map). This mapping objective is

measured by the smooth L1 loss function (Equation 1).

795
$$loss(\hat{y}^*, y^*) = \frac{1}{n} \sum_i z_i \tag{1}$$

796 where y^* and $\hat{y}^*$ are, respectively, the empirical and predicted value weighted by

797 individual-specific explained variance (R^2) from the pRF modeling procedure (Benson

798 et al., 2018), n is the total number of vertices, and z_i is given by:

799
$$z_i = \begin{cases} 0.5(\hat{y}^*_i - y^*_i)^2, if \left|\hat{y}^*_i - y^*_i\right| < 1 \\ \left|\hat{y}^*_i - y^*_i\right| - 0.5, \quad otherwise \end{cases}$$

Models were implemented using Python 3.7.3 and Pytorch 1.2.0. Surface plots were

generated using Nilearn, a Python module for fast statistical learning on neuroimaging

data (Abraham et al., 2014).Training was performed on a high-performance computing

cluster using NVIDIA Tesla V100 Accelerator units.

Hyperparameter tuning

Hyperparameter tuning was conducted by considering the performance of the model

on predicting retinotopic maps of participants within the development dataset. We

used the mean absolute error to compute the difference between predicted and

expected values (ground truth). During the training stage, we monitored the decrease

of the loss function (i.e., the prediction error on the training dataset) and the decrease

of the mean absolute error (i.e., the prediction error on the development dataset). We

also visually monitored predicted retinotopic maps using the development dataset, as

we observed that despite the prediction error within the development dataset reaching

a plateau around 100 epochs, some of the details in the predicted retinotopic maps

continued to vary with additional training. To allow for some of this additional fine

tuning, we fixed our training to 200 epochs.

To find the most appropriate number of layers, we trained five different models per

number of layers, varying from 1 to 20 layers, as the performance of the final model

fluctuated due to random initialization of the learnable parameters. We selected the

number of layers based on the performance of the trained network, which was

estimated by the smallest difference between two angles, given by:

821                    $$\text{MIN}(|\widehat{\theta} - \theta|, |\widehat{\theta} - \theta + 2\pi|, |\widehat{\theta} - \theta - 2\pi|) \qquad \textbf{(2)}$$

for $0 < \theta < 2\pi$. To this end, we considered two factors: (1) how well model prediction

matched the ground truth (error) and (2) how much a predicted map differed from the

others (individual variability). To estimate the error, we computed the difference (given

by Equation 2) between the predicted and the empirical (ground truth) polar angle

values in a vertex-wise manner and averaged across all participants in the

development dataset and within the various ROIs. The other factor, individual

variability, was determined by the difference between a specific predicted map and

each other predicted map in the development dataset in a vertex-wise manner and

averaged across all combinations (there are 10 participants in the development

dataset, hence 9 combinations), and then averaged across participants and within the

various ROIs. This was performed for all models (5 models per number of layers) and

we selected the number of layers that resulted in the best performance across all the

ROIs in both metrics (12 layers; see Supplementary Figure 6). This selection was

based on mapping polar angle values in the left hemisphere; however, we tested a

range of layers using the right hemisphere data and found similar results. Finally, once

the appropriate number of layers was established, we chose the best model among

the 5 models that were trained with the same hyperparameters but with different

learnable parameters (due to the random initialization) to evaluate on the test dataset.

For the eccentricity models (left and right hemispheres), we kept the same

hyperparameters as optimized for polar angle models.

Model testing and evaluation metric

The selected models were evaluated based on their performance on the test dataset

considering the same two factors, error and individual variability. Importantly, the test

dataset was never seen by the network nor by the researchers until the deep learning

architecture was finalized and the final model selected. Again, the error was

determined by the difference between the predicted and the empirical polar angle

values in a vertex-wise manner and averaged across all participants – this time in the

test dataset. Individual variability was determined by the difference between a specific

predicted map and each other predicted map in the test dataset in a vertex-wise

manner and averaged across all combinations (9 combinations), and then averaged

across participants.

Model performance in comparison to an average map

To assess the accuracy of our individual predictions, we compared the performance

of our model to a simple average of the retinotopic maps in predicting polar angle,

eccentricity, and pRF center location. We quantified the mean error over vertices

within the range of 1-8º of eccentricity, which was selected using the group-average

eccentricity map over the training dataset. This range of values was chosen because,

in the original pRF mapping experiment of the HCP, the visual stimulus extended to

8° of eccentricity. Additionally, due to the inherent difficulty in mapping the foveal

confluence (Wandell and Winawer, 2010), we constrained our comparison to

eccentricity values above 1°. Polar angle and eccentricity prediction errors were

determined as described previously. PRF center location prediction error was

determined by the Euclidean distance between two points in polar coordinates, given

by:

$\Delta(\text{pRF center location}) =$

$$\sqrt{r_{\text{predicted}}^2 + r_{\text{empirical}}^2 - 2r_{\text{predicted}}r_{\text{empirical}}\cos(\theta_{\text{predicted}} - \theta_{\text{empirical}})} \quad (3)$$

where $r_{\text{predicted}}$ and $\theta_{\text{predicted}}$ are the predicted eccentricity and polar angle values, and

$r_{\text{empirical}}$ and $\theta_{\text{empirical}}$ are the empirical eccentricity and polar angle values. Then, the

pRF center location errors were divided by the empirical eccentricity values from each

participant to prevent errors at high eccentricity from dominating the error metric

(Benson and Winawer, 2018).

After computing the vertex-wise prediction error, errors were averaged within a few

regions of interest for each participant: (1) dorsal V1-3 - not including the foveal

confluence (Wang et al., 2015), (2) the entire early visual cortex, and (3) higher order

visual areas. The mean error across participants was determined to evaluate the

performance of our model in comparison to a simple average map (Supplementary

Table 1). We performed statistical comparisons with repeated measure t-test using

Scipy (Virtanen et al., 2020). Additionally, we determined the vertex-wise explained

variance of our model over the test dataset (Supplementary Table 2). First, individuals'

predicted and empirical maps were concatenated, which resulted in two matrices of

size 'number of vertices' × 10. Then, we calculated the square of the correlation

coefficient between each vertex's (rows) predicted values and its corresponding

empirical values.

Finally, we also compared our predictions with different pRF fits provided by the HCP.

For each individual subject, Benson et al. (2018) performed three separate model fits:

one fit used all data from six runs of retinotopic mapping stimuli (used here as our

ground truth – fit 1), the second fit (fit 2) and the third fit (fit 3) used only the first half

and only the second half of each of the six runs (i.e., split halves), respectively.

Prediction error was determined between our model and pRF fits 1 to 3, and between

the average map and pRF fits 1 to 3. We report the mean vertex-wise prediction error

within the dorsal portion of V1-3 averaged over the test dataset (Supplementary Table

3). Statistical comparison was performed with two-way (prediction X pRF fit) repeated

measures ANOVA using Jamovi (The jamovi project, 2021) (Supplementary Table 4).

Assessing spatial organization of the anatomical features

To evaluate the importance of the spatial organization of the anatomical features and

their variability for the prediction of individual differences in retinotopic maps, we tested

the effects of modifying the input data in three ways using the previously trained model:

(1) rotating the feature maps, (2) randomly shuffling the anatomical features, and (3)

setting the input features equal to a constant value. (1) To rotate the feature maps,

AFNI's ConvertSurface was used with the flag '-xmat_1D NegXY' (which flips the sign

of X and Y coordinates), followed by the SurfToSurf command that interpolates the

rotated surface nodes onto the original surface. This procedure essentially replaces

the intact curvature and myelin patterns in visual cortex with intact (but inappropriate)

patterns from elsewhere in the brain. (2) Random shuffling of the input features, in

contrast, uses the values from the intact feature maps in visual cortex; however, the

values are permuted across the ROI vertices such that the spatial organization of the

anatomical information was completely disrupted. (3) To test the effect of completely

removing the variability present in the input features, all curvature and myelin values

of each participant in the test dataset was set equal to the mean curvature (0.027) and

the mean myelin (1.439) values, respectively. Note that the mean values were

computed using all participants from the training dataset.

Data and code availability

The data used in this study in publicly available at BALSA

(https://balsa.wustl.edu/study/show/9Zkk). All pre-trained models will be available on

the Open Science Framework (https://osf.io/95w4y/) and all accompanying Python

source code will be available upon publication. Moreover, an executable code

notebook hosted on Google Collab is currently available that allows anyone to load

the trained models and to generate predictions on the test dataset

(https://colab.research.google.com/drive/1zXrK5HK806iXkJ6IIKeg0ePKm1SCTQlB?

usp=sharing).

Acknowledgments

This work was supported by the Australian Research Council (DE180100433). Data

were provided by the Human Connectome Project, WU-Minn Consortium (Principal

Investigators: David Van Essen and Kamil Ugurbil; 1U54MH091657) funded by the 16

NIH Institutes and Centers that support the NIH Blueprint for Neuroscience Research;

and by the McDonnell Center for Systems Neuroscience at Washington University.

The authors acknowledge Jake Carroll and Irek Porebski for their great support with

the high-performance computing facilities of the Research Computing Centre at the

University of Queensland.

Author contributions

F.L.R., S.B., and A.M.P. conceptualized the study. F.L.R. and A.M.P. designed the

study and analyses. F.L.R. carried out the modeling procedure and analyses. F.L.R.

and A.M.P. wrote the manuscript. All authors reviewed the manuscript.

Competing financial interests

The authors declare no competing financial interests.

References

Abdollahi, R.O., Kolster, H., Glasser, M.F., Robinson, E.C., Coalson, T.S., Dierker,
D., Jenkinson, M., Van Essen, D.C., Orban, G.A., 2014. Correspondences
between retinotopic areas and myelin maps in human visual cortex. Neuroimage
99, 509–524. https://doi.org/10.1016/j.neuroimage.2014.06.042

Abraham, A., Pedregosa, F., Eickenberg, M., Gervais, P., Mueller, A., Kossaifi, J.,
Gramfort, A., Thirion, B., Varoquaux, G., 2014. Machine learning for
neuroimaging with scikit-learn. Front. Neuroinform. 8, 1–10.
https://doi.org/10.3389/fninf.2014.00014

Albers, A.M., Meindertsma, T., Toni, I., de Lange, F.P., 2018. Decoupling of BOLD
amplitude and pattern classification of orientation-selective activity in human
visual cortex. Neuroimage 180, 31–40.
https://doi.org/10.1016/j.neuroimage.2017.09.046

Allen, E.J., St-Yves, G., Wu, Y., Breedlove, J.L., Dowdle, L.T., Caron, B., Pestilli, F.,
Charest, I., Hutchinson, J.B., Naselaris, T., Kay, K., 2021. A massive 7T fMRI
dataset to bridge cognitive and computational neuroscience. bioRxiv 1–70.
https://doi.org/10.1101/2021.02.22.432340

Alvarez, I., Parker, A.J., Bridge, H., 2019. Normative cerebral cortical thickness for
human visual areas. Neuroimage 201, 116057.
https://doi.org/10.1016/j.neuroimage.2019.116057

Amano, K., Wandell, B.A., Dumoulin, S.O., 2009. Visual field maps, population
receptive field sizes, and visual field coverage in the human MT+ complex. J.
Neurophysiol. 102, 2704–2718. https://doi.org/10.1152/jn.00102.2009

Angelucci, A., Rosa, M.G.P., 2015. Resolving the organization of the third tier visual
cortex in primates: A hypothesis-based approach. Vis. Neurosci. 32.
https://doi.org/10.1017/S0952523815000073

Arcaro, M.J., Honey, C.J., Mruczek, R.E.B., Kastner, S., Hasson, U., 2015.
Widespread correlation patterns of fMRI signal across visual cortex reflect
eccentricity organization. Elife 2015, 1–28. https://doi.org/10.7554/eLife.03952

Arcaro, M.J., Kastner, S., 2015. Topographic organization of areas V3 and V4 and its
relation to supra-areal organization of the primate visual system. Vis. Neurosci.
https://doi.org/doi:10.1017/S0952523815000115

Arcaro, M.J., McMains, S.A., Singer, B.D., Kastner, S., 2009. Retinotopic
organization of human ventral visual cortex. J. Neurosci. 29, 10638–10652.
https://doi.org/10.1523/JNEUROSCI.2807-09.2009

Balasubramanian, M., Polimeni, J., Schwartz, E.L., 2002. The V1-V2-V3 complex:
quasiconformal dipole maps in primate striate and extra-striate cortex. Neural
Networks 15, 1157–1163.

Benson, N.C., Butt, O.H., Brainard, D.H., Aguirre, G.K., 2014. Correction of
Distortion in Flattened Representations of the Cortical Surface Allows Prediction
of V1-V3 Functional Organization from Anatomy. PLoS Comput. Biol. 10.
https://doi.org/10.1371/journal.pcbi.1003538

Benson, N.C., Butt, O.H., Datta, R., Radoeva, P.D., Brainard, D.H., Aguirre, G.K.,
2012. The retinotopic organization of striate cortex is well predicted by surface
topology. Curr. Biol. 22, 2081–2085. https://doi.org/10.1016/j.cub.2012.09.014

Benson, N.C., Jamison, K.W., Arcaro, M.J., Vu, A.T., Glasser, M.F., Coalson, T.S.,
Van Essen, D.C., Yacoub, E., Ugurbil, K., Winawer, J., Kay, K., 2018. The
Human Connectome Project 7 Tesla retinotopy dataset : Description and
population receptive field analysis. J. Vis. 18, 1–22.

Benson, N.C., Winawer, J., 2018. Bayesian analysis of retinotopic maps. Elife 7, 1–
29. https://doi.org/10.7554/elife.40224

Benson, N.C., Yoon, J.M.D., Forenzo, D., Kay, K.N., Engel, S.A., Winawer, J., 2021.
Surface area and cortical magnification of V1, V2, and V3 in a large sample of
human observers. bioRxiv. https://doi.org/10.1101/2020.12.30.424856

Borne, L., Rivière, D., Mancip, M., Mangin, J.F., 2020. Automatic labeling of cortical
sulci using patch- or CNN-based segmentation techniques combined with
bottom-up geometric constraints. Med. Image Anal. 62.
https://doi.org/10.1016/j.media.2020.101651

Bronstein, M.M., Bruna, J., Lecun, Y., Szlam, A., Vandergheynst, P., 2017.
Geometric Deep Learning: Going beyond Euclidean data. IEEE Signal Process.
Mag. 34, 18–42. https://doi.org/10.1109/MSP.2017.2693418

Cai, H., Chen, J., Liu, S., Zhu, J., Yu, Y., 2020. Brain functional connectome-based
prediction of individual decision impulsivity. Cortex 125, 288–298.
https://doi.org/10.1016/j.cortex.2020.01.022

Carvalho, J., Invernizzi, A., Ahmadi, K., Hoffmann, M.B., Renken, R.J., Cornelissen,
F.W., 2020. Micro-probing enables fine-grained mapping of neuronal
populations using fMRI. Neuroimage 209, 116423.
https://doi.org/10.1016/j.neuroimage.2019.116423

Cohen, R.A., 2011. Cortical Magnification, in: Kreutzer, J.S., DeLuca, J., Caplan, B.
(Eds.), Encyclopedia of Clinical Neuropsychology. Springer New York, New
York, NY, pp. 718–719. https://doi.org/10.1007/978-0-387-79948-3_1355

Cowey, A., Rolls, E.T., 1974. Human cortical magnification factor and its relation to
visual acuity. Exp. Brain Res. 21, 447–454. https://doi.org/10.1007/BF00237163

Da Costa, S., Saenz, M., Clarke, S., van der Zwaag, W., 2015. Tonotopic Gradients
in Human Primary Auditory Cortex: Concurring Evidence From High-Resolution
7 T and 3 T fMRI. Brain Topogr. 28, 66–69. https://doi.org/10.1007/s10548-014-
0388-0

Dadi, K., Rahim, M., Abraham, A., Chyzhyk, D., Milham, M., Thirion, B., Varoquaux,
G., 2019. Benchmarking functional connectome-based predictive models for
resting-state fMRI. Neuroimage 192, 115–134.
https://doi.org/10.1016/j.neuroimage.2019.02.062

Dale, A.M., Fischl, B., Sereno, M.I., 1999. Cortical surface-based analysis: I.
Segmentation and surface reconstruction. Neuroimage 9, 179–194.
https://doi.org/10.1006/nimg.1998.0395

Demb, J.B., Boynton, G.M., Heeger, D.J., 1997. Brain activity in visual cortex
predicts individual differences in reading performance. Proc. Natl. Acad. Sci. U.
S. A. 94, 13363–13366. https://doi.org/10.1073/pnas.94.24.13363

Deyoe, E.A., Carman, G.J., Bandettini, P., Glickman, S., Wieser, J., Cox, R., Miller,
D., Neitz, J., 1996. Mapping striate and extrastriate visual areas in human
cerebral cortex. Proc. Natl. Acad. Sci. U. S. A. 93, 2382–2386.
https://doi.org/10.1073/pnas.93.6.2382

DeYoe, E.A., Carman, G.J., Bandettini, P., Glickman, S., Wieser, J., Cox, R., Miller,
D., Neitz, J., 1996. Mapping striate and extrastriate visual areas in human
cerebral cortex. Proc. Natl. Acad. Sci. 93, 2382–2386.

Dougherty, R.F., Koch, V.M., Brewer, A.A., Fischer, B., Modersitzki, J., Wandell,
B.A., 2003. Visual field representations and locations of visual areas v1/2/3 in
human visual cortex. J. Vis. 3, 586–598. https://doi.org/10.1167/3.10.1

Dumoulin, S.O., Wandell, B.A., 2008. Population receptive field estimates in human
visual cortex. Neuroimage 39, 647–660.
https://doi.org/10.1016/j.neuroimage.2007.09.034

Engel, S.A., Glover, G.H., Wandell, B.A., 1997. Retinotopic organization in human
visual cortex and the spatial precision of functional MRI. Cereb. Cortex 7, 181–
192. https://doi.org/10.1093/cercor/7.2.181

Felleman, D.J., Van Essen, D.C., 1991. Distributed hierarchical processing in the
primate cerebral cortex. Cereb. Cortex 1, 1–47.

Fey, M., Lenssen, J.E., 2019. Fast Graph Representation Learning with PyTorch
Geometric. arXiv 1–9.

Fey, M., Lenssen, J.E., Weichert, F., Muller, H., 2018. SplineCNN: Fast Geometric
Deep Learning with Continuous B-Spline Kernels. Proc. IEEE Comput. Soc.
Conf. Comput. Vis. Pattern Recognit. 869–877.
https://doi.org/10.1109/CVPR.2018.00097

Finn, E.S., Shen, X., Scheinost, D., Rosenberg, M.D., Huang, J., Chun, M.M.,
Papademetris, X., Constable, R.T., 2015. Functional connectome fingerprinting:
identifying individuals using patterns of brain connectivity. Nat. Neurosci. 18,
1664–1671. https://doi.org/10.1038/nn.4135

Fountain-Zaragoza, S., Samimy, S., Rosenberg, M.D., Prakash, R.S., 2019.
Connectome-based models predict attentional control in aging adults.
Neuroimage 186, 1–13. https://doi.org/10.1016/j.neuroimage.2018.10.074

Frankle, J., Schwab, D.J., Morcos, A.S., 2020. Training BatchNorm and Only
BatchNorm: On the Expressive Power of Random Features in CNNs. ArXiv 1–
14.

Fukushima, K., 1980. Neocognition: A Self-organizing Neural Network Model for a
Mechanism of Pattern Recognition Unaffected by Shift in Position. Biol. Cybern.
36, 193–202. https://doi.org/10.1007/BF00344251

Gao, S., Greene, A.S., Constable, R.T., Scheinost, D., 2019. Combining multiple connectomes improves predictive modeling of phenotypic measures. Neuroimage 201, 116038. https://doi.org/10.1016/j.neuroimage.2019.116038

Gattass, R., Sousa, A.P.B., Gross, C.G., 1988. Visuotopic organization and extent of V3 and V4 of the macaque. J. Neurosci. 8, 1831–1845. https://doi.org/10.1523/jneurosci.08-06-01831.1988

Glasser, M.F., Sotiropoulos, S.N., Wilson, J.A., Coalson, T.S., Fischl, B., Andersson, J.L., Xu, J., Jbabdi, S., Webster, M., Polimeni, J.R., Van Essen, D.C., Jenkinson, M., 2013. The minimal preprocessing pipelines for the Human Connectome Project. Neuroimage 80, 105–124. https://doi.org/10.1016/j.neuroimage.2013.04.127

Glasser, M.F., Van Essen, D.C., 2011. Mapping human cortical areas in vivo based on myelin content as revealed by T1- and T2-weighted MRI. J. Neurosci. 31, 11597–11616. https://doi.org/10.1523/JNEUROSCI.2180-11.2011

Gopinath, K., Desrosiers, C., Lombaert, H., 2018. Graph Convolutions on Spectral Embeddings for Cortical Surface Parcellation. Med. Image Anal. 54, 297–305. https://doi.org/10.1016/j.media.2019.03.012

Griffis, J.C., Elkhetali, A.S., Burge, W.K., Chen, R.H., Bowman, A.D., Szaflarski, J.P., Visscher, K.M., 2017. Retinotopic patterns of functional connectivity between V1 and large-scale brain networks during resting fixation. Neuroimage 176, 1071–1083. https://doi.org/10.1016/j.physbeh.2017.03.040

Grill-Spector, K., Malach, R., 2004. The Human Visual Cortex. Annu. Rev. Neurosci. 27, 649–677. https://doi.org/10.1146/annurev.neuro.27.070203.144220

Hansen, K.A., Kay, K.N., Gallant, J.L., 2007. Topographic organization in and near human visual area V4. J. Neurosci. 27, 11896–11911. https://doi.org/10.1523/JNEUROSCI.2991-07.2007

Hinds, O.P., Rajendran, N., Polimeni, J.R., Augustinack, J.C., Wiggins, G., Wald, L.L., Rosas, H.D., Potthast, A., Schwarts, E.L., Fischl, B., 2009. Accurate prediction of V1 location from cortical folds in a surface coordinate system. Neuroimage 39, 1585–1599.

Hubel, D.H., Wiesel, T.N., 1962. Receptive fields, binocular interaction and functional architecture in the cat's visual cortex. J. Physiol. 160, 106–154. https://doi.org/10.1113/jphysiol.1962.sp006837

Ioffe, S., Szegedy, C., 2015. Batch Normalization: Accelerating Deep Network Training by Reducing Internal Covariate Shift, in: International Conference on Machine Learning. pp. 448–456. https://doi.org/10.1080/17512786.2015.1058180

Isherwood, Z.J., Schira, M.M., Spehar, B., 2017. The tuning of human visual cortex to variations in the $1/f\alpha$ amplitude spectra and fractal properties of synthetic noise images. Neuroimage 146, 642–657. https://doi.org/10.1016/j.neuroimage.2016.10.013

Kanwisher, N., McDermott, J., Chun, M.M., 1997. The Fusiform Face Area: A Module in Human Extrastriate Cortex Specialized for Face Perception. J.

Neurosci. 17, 4302–4311. https://doi.org/10.1109/CDC.2005.1583375

Kay, K.N., Winawer, J., Mezer, A., Wandell, B.A., 2013. Compressive spatial
summation in human visual cortex. J. Neurophysiol. 110, 481–494.
https://doi.org/10.1152/jn.00105.2013

Lecun, Y., Bengio, Y., Hinton, G., 2015. Deep learning. Nature 521, 436–444.
https://doi.org/10.1038/nmeth.3707

Mishkin, M., Ungerleider, L.G., Macko, K.A., 1983. Object vision and spatial vision:
two cortical pathways. Trends Neurosci. 6, 414–417.
https://doi.org/10.1016/0166-2236(83)90190-X

Park, B.Y., Tark, K.J., Shim, W.M., Park, H., 2018. Functional connectivity based
parcellation of early visual cortices. Hum. Brain Mapp. 39, 1380–1390.
https://doi.org/10.1002/hbm.23926

Puckett, A.M., Bollmann, S., Junday, K., Barth, M., Cunnington, R., 2020. Bayesian
population receptive field modeling in human somatosensory cortex.
Neuroimage 208, 116465. https://doi.org/10.1016/j.neuroimage.2019.116465

Puckett, A.M., Mathis, J.R., Deyoe, E.A., 2014. An investigation of positive and
inverted hemodynamic response functions across multiple visual areas. Hum.
Brain Mapp. 35, 5550–5564. https://doi.org/10.1002/hbm.22569

Rajimehr, R., Tootell, R.B.H., 2009. Does retinotopy influence cortical folding in
primate visual cortex? J. Neurosci. 29, 11149–11152.
https://doi.org/10.1523/JNEUROSCI.1835-09.2009

Saenz, M., Langers, D.R.M., 2014. Tonotopic mapping of human auditory cortex.
Hear. Res. 307, 42–52. https://doi.org/10.1016/j.heares.2013.07.016

Sanchez Panchuelo, R.M., Besle, J., Schluppeck, D., Humberstone, M., Francis, S.,
2018. Somatotopy in the Human Somatosensory System. Front. Hum. Neurosci.
12, 1–14. https://doi.org/10.3389/fnhum.2018.00235

Schira, M.M., Tyler, C.W., Breakspear, M., Spehar, B., 2009. The foveal confluence
in human visual cortex. J. Neurosci. 29, 9050–9058.
https://doi.org/10.1523/JNEUROSCI.1760-09.2009

Schira, M.M., Tyler, C.W., Rosa, M.G.P., 2012. Brain mapping: The (un)folding of
striate cortex. Curr. Biol. 22, R1051–R1053.
https://doi.org/10.1016/j.cub.2012.11.003

Schira, M.M., Tyler, C.W., Spehar, B., Breakspear, M., 2010. Modeling magnification
and anisotropy in the primate foveal confluence. PLoS Comput. Biol. 6, 1–10.
https://doi.org/10.1371/journal.pcbi.1000651

Schira, M.M., Wade, A.R., Tyler, C.W., 2007. Two-Dimensional Mapping of the
Central and Parafoveal Visual Field to Human Visual Cortex. J. Neurophysiol.
97, 4284–4295. https://doi.org/10.1152/jn.00972.2006

Schwartz, E.L., 1977. Spatial mapping in the primate sensory projection: Analytic
structure and relevance to perception. Biol. Cybern. 25, 181–194.
https://doi.org/10.1007/BF01885636

Seeliger, K., Fritsche, M., Güçlü, U., Schoenmakers, S., Schoffelen, J.M., Bosch,
S.E., van Gerven, M.A.J., 2018. Convolutional neural network-based encoding
and decoding of visual object recognition in space and time. Neuroimage 180,
253–266. https://doi.org/10.1016/j.neuroimage.2017.07.018

Seong, S.-B., Pae, C., Park, H.-J., 2018. Geometric Convolutional Neural Network
for Analyzing Surface-Based Neuroimaging Data. Front. Neuroinform. 12, 1–13.
https://doi.org/10.3389/fninf.2018.00042

Sereno, M., Dale, A., Reppas, J., Kwong, K., Belliveau, J., Brady, T., Rosen, B.,
Tootell, R., 1995. Borders of multiple visual areas in humans revealed by
functional magnetic resonance imaging. Science (80-.). 268, 889–893.

Sereno, M.I., Pitzalis, S., Martinez, A., 2001. Mapping of contralateral space in
retinotopic coordinates by a parietal cortical area in humans. Science (80-.).
294, 1350–1354. https://doi.org/10.1126/science.1063695

Shen, X., Finn, E.S., Scheinost, D., Rosenberg, M.D., Chun, M.M., Papademetris,
X., Constable, R.T., 2017. Using connectome-based predictive modeling to
predict individual behavior from brain connectivity. Nat. Protoc. 12, 506–518.
https://doi.org/10.1038/nprot.2016.178

Shmuel, A., Yacoub, E., Pfeuffer, J., Van de Moortele, P.F., Adriany, G., Hu, X.,
Ugurbil, K., 2002. Sustained negative BOLD, blood flow and oxygen
consumption response and its coupling to the positive response in the human
brain. Neuron 36, 1195–1210. https://doi.org/10.1016/S0896-6273(02)01061-9

Silver, M.A., Kastner, S., 2009. Topographic maps in human frontal and parietal
cortex. Trends Cogn. Sci. 13, 488–495.
https://doi.org/10.1016/j.tics.2009.08.005.Topographic

Srivastava, N., Hinton, G., Krizhevsky, A., Sutskever, I., Salakhutdinov, R., 2014.
Dropout: A simple way to prevent neural networks from overfitting. J. Mach.
Learn. Res. 15, 1929–1958.

Storrs, K.R., Kietzmann, T.C., Walther, A., Mehrer, J., Kriegeskorte, N., 2020.
Diverse deep neural networks all predict human IT well, after training and fitting.
bioRxiv 2020.05.07.082743. https://doi.org/10.1101/2020.05.07.082743

Swisher, J.D., Halko, M.A., Merabet, L.B., McMains, S.A., Somers, D.C., 2007.
Visual topography of human intraparietal sulcus. J. Neurosci. 27, 5326–5337.
https://doi.org/10.1523/JNEUROSCI.0991-07.2007

The jamovi project (2021), n.d.

Van Essen, D.C., 2004. Organization of visual areas in macaque and human
cerebral cortex, in: Chapula, L., Werner, J. (Eds.), The Visual Neuroscience.
Cambridge: MIT, pp. 507–521.

Van Essen, D.C., Drury, H.A., Joshi, S., Miller, M.I., 1998. Functional and structural
mapping of human cerebral cortex: solutions are in the surfaces. Proc. Natl.
Acad. Sci. U. S. A. 95, 788–795.

Van Essen, D.C., Glasser, M.F., 2018. Parcellating Cerebral Cortex: How Invasive
Animal Studies Inform Noninvasive Mapmaking in Humans. Neuron 99, 640–
663. https://doi.org/10.1016/j.neuron.2018.07.002

Van Essen, D.C., Smith, S.M., Barch, D.M., Behrens, T.E.J., Yacoub, E., Ugurbil, K.,
2013. The WU-Minn Human Connectome Project: An overview. Neuroimage 80,
62–79. https://doi.org/10.1016/j.neuroimage.2013.05.041

Virtanen, P., Gommers, R., Oliphant, T.E., Haberland, M., Reddy, T., Cournapeau,
D., Burovski, E., Peterson, P., Weckesser, W., Bright, J., van der Walt, S.J.,
Brett, M., Wilson, J., Millman, K.J., Mayorov, N., Nelson, A.R.J., Jones, E., Kern,
R., Larson, E., Carey, C.J., Polat, İ., Feng, Y., Moore, E.W., VanderPlas, J.,
Laxalde, D., Perktold, J., Cimrman, R., Henriksen, I., Quintero, E.A., Harris,
C.R., Archibald, A.M., Ribeiro, A.H., Pedregosa, F., van Mulbregt, P.,
Vijaykumar, A., Bardelli, A. Pietro, Rothberg, A., Hilboll, A., Kloeckner, A.,
Scopatz, A., Lee, A., Rokem, A., Woods, C.N., Fulton, C., Masson, C.,
Häggström, C., Fitzgerald, C., Nicholson, D.A., Hagen, D.R., Pasechnik, D. V.,
Olivetti, E., Martin, E., Wieser, E., Silva, F., Lenders, F., Wilhelm, F., Young, G.,
Price, G.A., Ingold, G.L., Allen, G.E., Lee, G.R., Audren, H., Probst, I., Dietrich,
J.P., Silterra, J., Webber, J.T., Slavič, J., Nothman, J., Buchner, J., Kulick, J.,
Schönberger, J.L., de Miranda Cardoso, J.V., Reimer, J., Harrington, J.,
Rodríguez, J.L.C., Nunez-Iglesias, J., Kuczynski, J., Tritz, K., Thoma, M.,
Newville, M., Kümmerer, M., Bolingbroke, M., Tartre, M., Pak, M., Smith, N.J.,
Nowaczyk, N., Shebanov, N., Pavlyk, O., Brodtkorb, P.A., Lee, P., McGibbon,
R.T., Feldbauer, R., Lewis, S., Tygier, S., Sievert, S., Vigna, S., Peterson, S.,
More, S., Pudlik, T., Oshima, T., Pingel, T.J., Robitaille, T.P., Spura, T., Jones,
T.R., Cera, T., Leslie, T., Zito, T., Krauss, T., Upadhyay, U., Halchenko, Y.O.,
Vázquez-Baeza, Y., 2020. SciPy 1.0: fundamental algorithms for scientific
computing in Python. Nat. Methods 17, 261–272.
https://doi.org/10.1038/s41592-019-0686-2

Wandell, B.A., Dumoulin, S.O., Brewer, A.A., 2007. Visual field maps in human
cortex. Neuron 56, 366–383. https://doi.org/10.1016/j.neuron.2007.10.012

Wandell, B.A., Winawer, J., 2010. Imaging retinotopic maps in the human brain.
Vision Res. 51, 718–737. https://doi.org/10.1016/j.visres.2010.08.004.Imaging

Wang, L., Mruczek, R.E.B., Arcaro, M.J., Kastner, S., 2015. Probabilistic maps of
visual topography in human cortex. Cereb. Cortex 25, 3911–3931.
https://doi.org/10.1093/cercor/bhu277

Witthoft, N., Poltoratski, S., Nguyen, M., Golarai, G., Liberman, A., LaRocque, K.F.,
Smith, M.E., Grill-Spector, K., 2016. Reduced spatial integration in the ventral
visual cortex underlies face recognition deficits in developmental prosopagnosia
Nathan. bioRxiv 1–26.

Wu, J., Yan, T., Zhang, Z., Jin, F., Guo, Q., 2012. Retinotopic mapping of the
peripheral visual field to human visual cortex by functional magnetic resonance
imaging. Hum. Brain Mapp. 33, 1727–1740. https://doi.org/10.1002/hbm.21324

Zeidman, P., Silson, E.H., Schwarzkopf, D.S., Baker, C.I., Penny, W., 2018.
Bayesian population receptive field modelling. Neuroimage 180, 173–187.
https://doi.org/10.1016/j.neuroimage.2017.09.008

Zeki, S., Watson, J.D.G., Lueck, C.J., Friston, K.J., Kennard, C., Frackowiak, R.S.J.,
1991. A direct demonstration of functional specialization in human visual cortex.
J. Neurosci. 11, 641–649. https://doi.org/10.1523/jneurosci.11-03-00641.1991

Zhang, Y., Bellec, P., 2019. Functional Annotation of Human Cognitive States using
Graph Convolution Networks. NeurIPS 1–6.

Zhao, F., Xia, S., Wu, Z., Duan, D., Wang, L., Lin, W., Gilmore, J.H., Shen, D., Li, G.,
2019. Spherical U-Net on Cortical Surfaces: Methods and Applications 1–12.

Zhu, Q., Vanduffel, W., 2019. Submillimeter fMRI reveals a layout of dorsal visual
cortex in macaques, remarkably similar to New World monkeys. Proc. Natl.
Acad. Sci. U. S. A. 116, 2306–2311. https://doi.org/10.1073/pnas.1805561116