Creative destruction: Sparse activity emerges on the mammal connectome under a simulated communication strategy with collisions and redundancy

Yan Hao (hao@hws.edu)
Department of Mathematics and Computer Science, Hobart & William Smith Colleges
Geneva, NY 14456 USA

Daniel Graham (graham@hws.edu)
Department of Psychology, Hobart & William Smith Colleges
Geneva, NY 14456 USA

ABSTRACT

Signal interactions in brain network communication have been little studied. We describe how nonlinear collision rules on simulated mammal brain networks can result in sparse activity dynamics characteristic of mammalian neural systems. We tested the effects of collisions in "information spreading" (IS) routing models in comparison to standard random walk (RW) routing models. Simulations employed synchronous agents on tracer-based mesoscale mammal connectomes at a range of signal loads. We find that RW models have high average activity that increases with load. Activity in RW models is also densely distributed over nodes: a substantial fraction is highly active in a given time window, and this fraction increases with load. Surprisingly, while IS models make many more attempts to pass signals, they show lower net activity due to collisions compared to RW, and activity in IS increases relatively little over with load. Activity in IS also shows greater sparseness than RW, and sparseness decreases slowly with load. Results hold on two networks of the monkey cortex and one of the mouse whole-brain. We also find evidence that activity is lower and more sparse for empirical networks compared to degree-matched randomized networks under IS, suggesting network topology supports IS-like routing strategies.

Keywords: connectome; communication systems; collisions; redundancy; routing; sparseness

Introduction

How does the mammal brain manage the communication of signals across its network? At the level of mesoscale mammal brain network structure, comprising connectivity of tens to hundreds of brain areas over thousands to hundreds of thousands of connections, an increasingly detailed picture of network connectivity is emerging (Markov et al., 2014; Oh et al., 2016; Gămănuț et al., 2018). Researchers are now aiming to "animate" these networks in order to understand patterns of whole-brain signaling dynamics (a research area termed *dynomics*; Kopell et al., 2014).

However, a given topology can support a wide range of observable dynamics (see, e.g., Friston, 2011; Knoblauch et al., 2016). Adding to the challenge is that activity on the whole network is poorly understood, with severe limitations in sampling at the single neuron level, and in spatial and temporal precision for imaging methods. Moreover, though single-neuron spiking dynamics for some neuron

classes are well understood, global activity will not necessarily be a linear summation of single-neuron dynamics.

One approach to understanding brain network dynamics is to consider the system of intercommunication among nodes as a bridge between network topology and network dynamics. Using imaging data, communication dynamics can serve as a linkage between structural connectivity and functional connectivity (Avena-Koenigsberger et al., 2018). More generally, nodes in the network can be considered as communicators that attempt to pass signals or messages to other nodes according to routing rules (Graham, 2014).

Communication demands such as flexibility and reliability place important constraints on the system (Poggio, 1984; Hahn et al., 2018). Effective and robust routing strategies are especially important on the mammal connectome because the topology is such that there are paths of just a few synapses between any node and practically any other node. Brain networks also need to dynamically exchange multimodal information among a large number of nodes in real time without appreciably changing network topology. In addition, routing in the brain lacks central control.

To begin to understand what routing strategy is in use in the brain, one can look to design strategies in engineered systems (Graham and Rockmore, 2010; Graham 2014; 2017; Navlakha et al., 2015; 2017; Fornito et al., 2016). A fundamental engineering goal for any large-scale communication system is the management of signal interactions. Signal interactions could take many forms such as summation, thresholding, collision, and duplication. As we describe in the Discussion, brain-like networks with signal interactions involving summations/thresholds tend to produce undesirable behavior such as activity die-off or overload (Kaiser et al., 2007; Kaiser and Hilgetag, 2010). Here we perform initial simulations of two interactions that have received little attention: signal collision and signal duplication (i.e., redundancy).

Collisions occur when signals from different sources converge on the same target at the same time. They are the price paid for the ability to route signals selectively to many possible destinations on a fixed network. Collision dynamics are emergent: they are a nonlinear effect of topology, node dynamics, and current traffic. All large-scale engineered communication systems have means for managing collisions, through redress, arbitration, and other strategies (see e.g., Kleinrock, 1976; Mišić and Mišić, 2014).

Given the *a priori* likelihood of collisions on small world-like brain networks (compared to, for example, lattice networks), we argue that it is in the interest of brain networks to establish dynamic interactions that manage collisions successfully across the entire brain. Management of collisions is especially important in mesoscale brain networks since behavior-related information must be exchanged dynamically among a large number of subsystems.

However, collisions introduce nonlinearities, which are difficult to study analytically. Nonlinear signal interactions are increasingly investigated with explicit agent-based models in the study of other communication networks (e.g., epidemics: Min et al. 2020), but little work in network neuroscience has used explicit approaches. For example, most random walk models (e.g., Noh and Rieger, 2004; Abdelnour et al., 2014), which route signals to randomly chosen outgoing edges (either with uniform probability, in proportion to edge weight, or in other ways) use analytical methods that cannot account for signal interactions such as collisions.

An exception is Mišić et al. (2014a,b). In this pair of studies, buffers (node memory allocations, a form of nonlinearity) were employed to manage collisions in a random walk routing model. In this scheme, colliding signals at the inputs of a node are lined up in a queue and stored in node memory until they can be directed to a randomly chosen outgoing edge. Buffers are ubiquitous on the Internet and may be useful in brains. But though several neurobiological mechanisms for buffering have been proposed, they remain hypothetical (see, e.g., Goldman-Rakic, 1996; Graham, 2014; Funahashi, 2015).

An alternative to random walk models is shortest path routing, which invokes the logic of evolved optimality (e.g., Bullmore and Sporns, 2009; Rubinov and Sporns, 2010; Goñi et al., 2013, 2014). Shortest path strategies also have parallels in engineered systems like the Internet (e.g., OSPF: open shortest-path first routing, see, e.g., Sosnovich et al., 2017). However, shortest path models typically ignore signal interactions such as collisions, again because these models are studied analytically. Yet signal interactions are especially important in a shortest path context. Though it has not been well recognized, successful shortest path routing requires knowledge of current network traffic: a short path is not necessarily short if there is congestion. Even when short path models include small buffers, they show substantial message loss due to collisions (Graham and Hao, 2018). In any case, shortest path routing is considered implausible because it requires global knowledge of network architecture to select shortest paths for all signals (Seguin et al., 2018; but see Mišić et al., 2015).

In the present work, we investigate a strategy of fully destructive collisions. The brain may in fact use a less punitive strategy than this but neurophysiological evidence increasingly supports the notion that signals in the brain regularly collide and are destroyed. For example, Sardi et al. (2017) demonstrated the failure of coincident signals above threshold to elicit spikes. They also showed that excitatory signals can cancel each other when they collide "head on" (Sardi et al., 2017; this is also predicted by the Hodgkin-Huxley model: Scott, 1977). Gidon et al. (2020) have shown exclusive-OR activity in single *ex vivo* human pyramidal cortical neurons, a behavior that effectively destroys some colliding signals. At the circuit level, gating circuits (e.g., Steriade and Paré, 2007; Gollisch and Meister, 2010), when closed, can also be conceived as destructive collisions between signals. If collisions need to be managed at the single cell level and the level of circuits, the same logic applies at the level of mesoscale brain networks (see Discussion).

However, collisions need not incapacitate a communication network. They may be useful in establishing stable and robust dynamics with locally-implemented routing rules. In particular, we suggest that collisions could—almost paradoxically—help promote system efficiency.

First, destructive collisions may on average help ensure a low level of energy use. Energy efficiency is imperative given that the dynamic connectome of mammals has strong metabolic constraints (Bullmore and Sporns, 2012, Goñi et al., 2013). Destructive collisions may also promote homeostasis, which appears desirable for maintaining relatively constant activity in the face of changing system demands (e.g., Aeschbach et al., 1997; Turrigiano, 1999).

But the brain cannot achieve efficiency simply by using as little energy as possible (Poldrack, 2015). The brain instead operates in sparse fashion, in part because the environment is sparse. To avoid confusion, we note that *sparseness* (or, equivalently, sparsity) in the present context refers to the distribution of activity across nodes and over time, rather than to the topology of the network (on a scale from "sparse" to "dense" connectivity). Sparse operation of a system is defined by the achievement of low average activity ratios (see, e.g., Foldiak, 2002).

Although sparse activity can confer low average energy usage, it does not necessarily imply minimal energy use. Instead, it involves a characteristically non-Gaussian distribution of activity across units, in particular a distribution with a strong peak near zero activity (most units are "off" at a given time) and heavy tails (a small number of units are likely to be highly active).

In the brain, it has been understood for decades that only a small fraction of units—10% or less—in a given part of the network can be highly active at a given time (Levy and Baxter 1997; Lennie, 2000; Attwell and Laughlin, 2003); this is known as population sparseness. In addition, it is estimated that a unit can only be highly active over a small fraction of its lifetime; this is known as lifetime sparseness (see Willmore and Tolhurst, 2001; Graham and Field, 2006). Sparse activity in the visual system for example is thought to be in part a result of sparse physical environments (Field, 1994; Olshausen and Field 1996; Bell and Sejnowski, 1997), in addition to metabolic constraints and other factors (Graham and Field, 2009). We suggest here that collision dynamics that result in emergent sparse activity are good candidates for how the mammal brain routes information.

If collisions are destructive, it may be necessary for the brain to adopt strategies to generate redundancy in order to promote reliability. Brain network communication models increasingly include not just a pathfinding dimension (stretching from random walks to shortest paths: Avena-Koenigsberger et al., 2019), but a second dimension that can be seen as redundancy (Avena-Koenigsberger et al., 2017; Bettinardi et al., 2017; Tipnis et al., 2018).

A simple way to promote redundancy is to produce duplicate copies of messages at each node. Based on this idea, we introduce an *information spreading* (IS) model of brain network communication. Signal interactions in a system with collisions and information spreading will produce nonlinear, emergent behavior. For example, as more signals and copies of those signals propagate on the network, the influence of collisions is increasingly important. Using numerical simulations, we investigate emergent behavior of the IS model, in comparison to a standard random walk (RW) model.

We show that mammal brain networks using IS can achieve a balance between collisions and redundancy, producing sparse activity. In particular, we show that, across a range of signal loads, low activity and high sparseness are emergent properties of network-wide communication under an IS model. Performance of the IS model contrasts with RW models, which exhibits high and increasing energy use with increasing signal loads, and lower and decreasing sparseness across loads. To investigate whether empirical topology in the mammal connectome supports sparse, efficient activity patterns, we also compare dynamics of the anatomical network to randomized networks with matched degree distributions.
`

Methods

Overview

Using a Markovian agent-based model on monkey and mouse tracer-based connectomes, we implemented an information spreading (IS) model wherein nodes pass copies of incoming signals to all output edges. Simulations utilized a nonlinear collision rule whereby all colliding messages are destroyed. We compared the IS model to a standard random walk (RW) model following the same collision rule. In RW, each message is passed from one node to another through a randomly chosen outgoing edge. At each time step, a set number of messages, which we term the *load* is injected to randomly chosen nodes; this is the primary independent variable in this study.

Connectomes

We utilized three mesoscale mammal connectomes: two of the macaque monkey (Markov et al., 2014,
termed *monkey1* in the present study as shorthand; and the CoCoMac database, see Bakker et al. 2012,
termed *monkey2*), and one for the mouse (Oh et al., 2014, termed *mouse*). All edges are directed and have
a weight of 1.

The *monkey1* connectome comprises 91 cortical nodes and 1615 edges, primarily in the visual system
(ipsilateral). Of these nodes, 29 have in- and out-degree > 0, while the remainder are source nodes (in-
degree = 0). This means that 62 nodes in *monkey1* are not reachable from the rest of the network, and only
pass messages injected at those nodes. This limitation is a result of the retrograde tracing method used by
Markov et al. (2014), and is the reason we included the *monkey2* network as well. For *monkey2*, we used
only nodes that had an in-degree and an out-degree of at least 1. This set comprised 163 nodes
corresponding to cortical regions and 5093 edges. The *mouse* connectome spans the entire mouse brain
(ipsilateral), comprising 213 nodes and 16954 edges (all have in- and out-degree > 0). For all connectomes,
isolated nodes with no incoming or outgoing edges (present only in *monkey2*) were removed. Both *mouse*
and *monkey2* contain self-loops (i.e., nodes with edges to themselves) but removing these edges did not
change the outcome of the experiments so self-loops are therefore included in the presented data. Including
nodes with in-degree or out-degree of 0 also did not affect the outcome. Adjacency matrices for the data
sets are shown in Figure 1.

Figure 1. Adjacency matrices of the connectomes tested. *Mouse* includes the ipsilateral whole brain of
the mouse (Oh et al., 2014), while *monkey1* (Markov et al., 2014) and *monkey2* (Bakker et al., 2012)
include monkey cortex. All edges (blue) are directed and have weight 1. Non-zero entries are shown in
numerical and percentage terms below each matrix.

Message-passing Models

In our models, time is discretized and message-passing at each node is synchronous. During a time step,
a node can be active or inactive. Each time step t, L new messages are injected into the system at randomly
chosen nodes, representing load. Variable loads are to be expected in brain networks, but are most likely
restricted to a relatively low range given metabolic constraints. Because the three connectomes have
different numbers of nodes N, load is expressed as a percentage of the number of nodes in the network.

We also report the case of 1 new message injected per time step in each case. We restrict simulations to
the load regime with a number of messages less than or equal to 50% of N.

During each time step, a node looks to all incoming messages, including messages that are already in the
system and new messages that are scheduled to be injected; if there is more than one message coming in,
all are deleted. The full set of operations in the model is given as pseudocode in Supplemental Box 1. We
are also making code to generate these models available on GitHub.

Measures of Dynamic Network Activity

Simulations consist of 500 runs of 1000 time steps each. Data from the first 500 time steps is excluded to
allow the analysis of equilibrium dynamics (see, e.g., Schrubin and Margolin, 1978). However, we note
that data for the full test run produce the same overall pattern of results.

First, we measured the fraction of nodes active on a given time step. We measured both attempted activity
before accounting for collisions, and actual (net) activity after collisions.

We also measured the sparseness over time in 5-time step bins using the Treves-Rolls measure of
sparseness (Treves and Rolls, 1991; Rolls and Tovee, 1994); recall that sparseness here relates to network
activity rather than to network structure. The Treves-Rolls measure is sensitive to higher-order statistical
regularities in data (see Willmore and Tolhurst, 2001). We calculate population sparseness by
constructing a histogram of the frequency of firing x_n within a time window per node, then sum over i
nodes. The Treves-Rolls measure S divides the square of the sum of the distribution by the sum of the
squares of the distribution:

$$S = \frac{(\frac{1}{N} \sum_i x_n)^2}{\frac{1}{N} \sum_i x_n^2}$$

This measure ranges between maximal sparseness at N^{-1} if one unit is active per window, and all other
units are inactive; minimal sparseness is 1.0 for uniformly-distributed activity (sparseness of standard
normal distribution by this measure is 0.64). See Figure S1. Thus, lower values of Treves-Rolls sparseness
indicate more sparse activity. We note that tests of 10-time step windows for the sparseness measure
produced similar results. We also calculated lifetime sparseness as above, summing over time instead of
over nodes.

Comparison to Randomized Networks

To investigate the dependency of network dynamics on the specific wiring patterns of the mammal
connectome, we compared network activity under our models to the same models implemented on
randomized networks. Randomized networks have the same distribution of in- and out-degree as the
empirical networks. This amounts to shuffling the in- and outgoing edges of nodes in a given network
(Maslov and Sneppen, 2002).

However, the nature of the connectomes in this study complicates the randomization process. When a
network is dense (in a topological sense; except for the present discussion of randomization, all references
to density and sparseness refer to network activity rather than topology), as in the *mouse* connectome and
the 29-node core of *monkey1*, network topology changes little after randomization. We therefore

thresholded the *mouse* connectome to make it less dense for randomization. Since edge weights in the
mouse are known (corresponding to tracer volumes) we thresholded the network to exclude edges with a
weight below 0.0136 (a value close to the modal weight, and one implied as meaningful by Oh et al.,
2014), then randomized the resulting network. Thresholding of the *mouse* network reduced degree in a
way that brought edge density to a level comparable to that of *monkey2* (but interestingly, the global
topology changed relatively little after removing more than half of the edges, suggesting self-similarity).
The density problem is compounded in *monkey1* because the full 91-node network is low-density as
compared to the other two networks. Therefore, we have omitted randomization of *monkey1*; results of
randomized network comparison in the monkey are for the *monkey2* connectome, which has intermediate
connectivity. Note that each trial in the randomized network simulations corresponds to a different
randomized network.

Results

Qualitative differences in network dynamics are apparent in visualizations of node activity over time. In
Figure 2, we show attempted and actual (net) activity through a representative simulation of the *mouse*
connectome, with nodes shown along the vertical axis and the last 500 time steps of the simulation running
from left to right ($L = 10\%$).

A

B

**Figure 2. (A) Attempted activity (before collisions) and (B) actual activity (net, following collisions)
under IS and RW models in the *mouse* connectome at 10% load.** Vertical axis corresponds to nodes
and time runs left to right. Colors indicated in the vertical axis in attempted activity plots (top) represent
the number of colliding messages at a given node and time step. Net activity per node per time step (below)
is binary (black=off, white=active).

The top row of Figure 2 shows attempted message-passing per node according to the color scale shown (i.e., the number of messages colliding). In general, attempted (i.e., simultaneous) messages are distributed in unimodal, roughly Gaussian fashion in RW whereas attempted messages are bimodally distributed in IS with a high peak at zero (not shown).

The bottom row of Figure 2 shows actual (net) activity (black=off, white=active). In the left-hand column is shown the IS model, and in the right-hand column is shown the RW model. From inspection, the net activity is more "bursty" and sparse in IS while activity is more uniformly distributed across nodes and time in RW.

We can quantify these observations by calculating the average net activity and the sparseness of activity across simulations. Figure 3 shows average activity (expressed as a fraction of the number of nodes active in a given model, averaged over time and trials) as a function of load L (expressed as a percentage of nodes creating new messages on each time step, except for the left-most tick, which represents injection of one new message per time step). IS models are shown with solid lines and RW models are shown with dashed lines. Though RW models have lower net activity with $L = 1$ message, net activity increases rapidly and monotonically as load increases. In contrast, IS models show relatively uniform activity across loads.

Figure 4 shows sparseness of activity (population sparseness) as a function of load. As with net activity across nodes, population sparseness of activity in a given network is greater (closer to zero) for IS compared to RW at all loads except the minimum load. As a function of load, we observed the same pattern for sparseness over time within a simulation (lifetime sparseness of activity) as was seen for population sparseness, namely that sparseness over time in a given network is greater (closer to zero) for IS compared to RW except at the lowest loads. (See Supplementary Figure 2). We note that, like attempted activity, net activity over time within simulation runs for IS is bimodally distributed with a high peak at zero, whereas net activity under RW is distributed in roughly Gaussian fashion (See Supplemental Figure 3).

332
Figure 3. Mean of net simulated activity on the mammal connectome as a function of load under IS
(solid lines) and RW (dashed lines) models for *mouse* **(circles),** *monkey1* **(stars) and** *monkey2*
(triangles) networks. In IS, activity remains mostly constant across load and is lower compared to the
corresponding value for RW at all load levels except 1 message per time step. Activity in RW increases
by more than two octaves across loads tested. Shaded areas represent 2 standard deviations of variability
from the mean across simulations (note that in some cases this dispersion is smaller than the width of the
markers/lines). Data points show significant differences (t-test, p<0.01) for corresponding IS and RW
measurements at all loads.

Figure 4. Population sparseness of activity as a function of load under IS (solid lines) and RW (dashed lines) models for *mouse* (circles), *monkey1* (stars) and *monkey2* (triangles) networks. As with net activity, IS models show relatively constant sparseness of activity across load, with greater sparseness of activity (closer to zero) than RW models at all loads except 1 message per time step. Sparseness in RW decreases by more than a factor of 2. Shaded areas represent 2 standard deviations of variability from the mean of population sparseness across simulations. Data points show significant differences (t-test, p<0.01) for corresponding IS and RW measurements at all loads.

366   **A**   **B**

Figure 5. (A) Net activity and (B) population sparseness for empirical and randomized networks of the *monkey2* and the (thresholded) *mouse* under IS and RW models. In IS models, both the empirical *monkey2* and the (thresholded) *mouse* networks show lower activity and greater sparseness (albeit by a small margin) compared to corresponding randomized networks. Randomized RW models show essentially the same behavior as the empirical networks (except in the case of 5% load in the *mouse*, wherein the empirical network is less active). Filled symbols indicate significant differences (t-test, p<0.01) between empirical and corresponding randomized networks, whereas open symbols indicate no significant difference.

Results of comparison to randomized networks (Figure 5) in the thresholded *mouse* and in *monkey2* show that IS models have lower net activity and greater sparseness in the empirical network at almost all loads tested, whereas RW models on empirical networks generally show slight increases in activity compared to randomized networks (*mouse*) or very small decreases (*monkey2*).

In particular, empirical *mouse* and *monkey2* networks under IS differ significantly (t-test, p<0.01) at all loads compared to corresponding randomized networks. Under IS, the mean net activity of the empirical networks across loads is lower by 0.0039 (*mouse*) and 0.13 (*monkey2*) units compared to corresponding randomized networks. The mean sparseness of the empirical network across loads under IS is greater (closer to zero) by 0.0092 (*mouse*) and 0.262 (*monkey2*) units compared to corresponding randomized networks. Empirical *mouse* and *monkey2* networks under RW also differ significantly (t-test, p<0.01) at

all but 2 load values compared to corresponding randomized networks. However, compared to
corresponding randomized networks, the mean net activity of the empirical networks across loads under
RW is greater by 0.0027 (*mouse*) or marginally lower by 0.00074 (*monkey2*) units. Likewise, the mean
sparseness of the empirical network across loads under IS is lower (closer to one) by 0.0012 (*mouse*) or
marginally greater by 0.0013 (*monkey2*) units compared to corresponding randomized networks. Although
the differences between empirical and randomized networks are not large, this evidence is consistent with
the notion that empirical network topology in mammals promotes sparse, efficient activity under an
information spreading routing strategy.

Discussion

In the context of collision interactions among signals, we used numerical simulations to show how the
mammal brain can exploit mesoscale network structure by spreading information widely, and in particular
by sending multiple copies of an incoming signal. Under an information spreading (IS) strategy for
routing, the network achieves globally low net activity and high sparseness of activity like what is found
in real mammal brains. Net activity and sparseness of activity change relatively little as load increases
under the IS model. This result suggests a way that the brain could achieve ongoing sparse activity spread
across the entire system using local protocol, but without deviating too far from globally homeostatic
operation. In contrast, random walk (RW) models with the same collision rule produce substantially higher
summed activity. In RW, substantial numbers of nodes are active in a given time window, resulting in less
sparse activity. Net activity and sparseness of activity under RW change substantially as load increases
over the same range, with activity increasing more than four-fold, and sparseness decreasing by around a
factor of two. Our findings hold in both the monkey cortex and mouse whole brain. In addition, empirical
networks under IS models show lower activity and greater sparseness of activity than randomized
networks with the same degree distributions.

Together, these results suggest that nonlinear collision protocol and mammal connectome topology could
promote sparse, efficient routing of communication traffic across the mammal brain network. This
protocol is biologically plausible, and does not require centralized control.

Taking a wider perspective, the management of signals arising from different sources that impinge on the
same target is a critical problem in network neuroscience. In the mesoscale mammal connectome, where
all nodes are only a few hops from each other (and where signals are excitatory), the system would seem
to need a strategy for managing coincident excitations in order to route signals appropriately.

This conception stands in contrast to models of dynamics of the mesoscale connectome (particularly
cortex) inspired by integrate-and-fire spiking neuron models, wherein the goal of the system is to have
many excitatory signals arrive at the same time in order for the unit to be highly activated. Collisions—in
the sense of multiple coincident efferents—are seen as signals to be integrated. However, studies such as
Kaiser et al. (2007) and Kaiser and Hilgetag (2010) that approach dynamics from this perspective confirm
the necessity of keeping global activity at a low and relatively constant level. Kaiser and colleagues tested
a threshold routing model on surrogate hierarchical networks with biologically plausible parameters, and
suggested that brain networks must seek regimes of "limited sustained activity." Using a "spreading"
model that is somewhat similar to our IS model, their simulations indicated that specific parameters of
activity likelihood promoted limited sustained activity of around 10-20% of nodes. However, many if not
most parameter settings led to "dying-out" activity or overload (Kaiser et al. 2007; Kaiser and Hilgetag,
2010). We have shown here that limited sustained activity of around 10-20% of nodes is robustly achieved

on mammal connectomes under a nonlinear routing approach employing destructive collisions and
information spreading. However, in contrast to Kaiser and Hilgetag (2010), our model shows that this
pattern of activity is distributed across the entire network over time, rather than concentrated in a minority
of nodes, and this behavior is demonstrated on all simulation runs.

In separate tests, we found that the structure of mammal brain networks is such that collisions that sum or
threshold signals lead to very high activity and very low sparseness in both RW and IS models. This was
suggested by tests of a "let one pass" collision rule whereby exactly one message in a collision of k
messages is allowed to pass on a randomly chosen outgoing edge. Even at low load values, the network
quickly overloads (especially under IS) with this collision rule producing data that are not meaningful,
and therefore not reported here.

Our results show that strategies with nonlinear, self-organizing mechanisms that align with basic
physiology can generate network activity that offsets collisions, requires no central agent, operates
sparsely in time and over nodes, and maintains relatively uniform global activity despite large increases
in signal load. However, automatic deletion is not the only or necessarily the best solution for managing
collisions. There are many other possible strategies and combinations of strategies that could be at play
including buffering (Misic et al. 2014a), resending (Graham and Rockmore, 2011), and deflection routing
(Fornito, Zalesky and Bullmore, 2016).

We find some evidence for one alternative strategy, which is to reduce load almost to zero. In this regime,
redundancy may not be needed because collisions are rare, and a given path is unlikely to be congested.
This is suggested in the finding that RW models achieve lower net activity and higher sparseness of
activity than IS models at the lowest load (1 message per time step) in all cases. It remains possible that
the brain could adopt this kind of extremely sparse strategy (see e.g., Ovsepian, 2015). However, such a
system, being so close to floor values, would be restricted to low activity ranges and would be vulnerable
to large changes in dynamics if load varies more than a small amount. In any case, if collisions are indeed
very rare, this is also a major problem for models based on integrate-and-fire strategies and linear
approaches.

We note that redundancy in the brain such as correlated firing among neighboring neurons (see e.g.,
Meytlis, Nichols and Nirenberg, 2012) is typically thought to be something that the system should
minimize (Wainwright, 1999; Barlow, 2001). Following Shannon's theory of information, parallel
communication channels should seek to reduce mutual information to theoretical minima. However, the
brain's network topology is not parallel but rather small world-like (see, e.g., Achard et al., 2006; see also
Knoblauch et al., 2016). In this situation, there is no straightforward way to apply Shannon's theory for
arbitrary node-to-node communication (El Gamal and Kim, 2011). Our results suggest that redundancy of
signals may allow brain networks to strike a dynamic balance between signal creation and destruction.

However, copying all incoming signals has its drawbacks. It may be more efficient to send redundant
signals only on some fraction of outgoing edges. Tests exploring this parameter are underway; we predict
a smooth transition in dynamics between the observed extremes of RW and IS conditions. In any case, the
purpose of the present investigation is not to find the optimal solution for intrabrain communication but
rather to address the question, what would be a reasonable way for the brain to route signals on the
mammalian network architecture, given the likelihood of collisions, the need for distributed protocol, and
a demand for low, sparse activity levels? Much as vision scientists have gained knowledge from asking
what a good retinal code would be given the statistical regularities of the environment (e.g., Field, 1994;

Graham and Field, 2009), we aim to advance model building by asking what a good routing protocol would be in the brain given its architecture and operational demands.

We note that collisions cannot be ignored by assuming that signals arriving at a node at the same time do not interact. Of course, at the mesoscale, inputs arising in different nodes that travel to a target node do not necessarily synapse with the same population within the target node. But if there were dedicated links from sending nodes via a target node to destinations one edge away, this would imply a different network topology (i.e. the target node would not be considered a node). If the brain performs dynamic routing at nodes—and functional demands appear to necessitate this (Olshausen et al., 1993; Graham and Rockmore, 2011)—collisions must be managed.

Nevertheless, the brain probably does not annihilate all colliding signals at all nodes. The rules governing collisions may vary in time and space from those that are fully punitive for coincident signals to those that require greater coincidence. This is a limitation of our study. Collision rules are a dimension worth exploring but as an initial study, we adopted a simplified model that promotes interpretability.

The difficulty of studying nonlinear interactions of brain network communication is due in part to the problem of simulating dynamics explicitly. The challenge lies in tracking every signal's path and interactions. Random walk models and shortest path models admit analytical solutions that capture the likelihood of a set of states of the network. But this is generally possible only when collisions and other nonlinear interactions are ignored. As a result, explicit models capable of accounting for collisions have been relatively little studied to date (see Graham and Hao, 2018). With further study of explicit models we may be able to understand fine-grained activity patterns such as regional differences and correlations in activity.

However, though we were able to model signal interactions explicitly, the lack of tracking of messages is another limitation of this study. For example, we would like to know how many messages are delivered, and how quickly. We have identified a way to infer message "age" in our simulations and will present results of this work in a subsequent report.

This study has other limitations including idiosyncrasies of connectomes studied. For example, the CoCoMac network is known to be incomplete (Chen et al., 2020), and the Markov et al. (2014) data are limited by retrograde tracing procedures. In addition, we have not constrained or tailored activity in terms of functional demands.

We conclude that the mammal brain network appears capable of striking a balance between activity and collisions such that sparse activity is robustly maintained across a wide range of loads. At present we cannot say what properties of network structure are necessary for supporting this behavior. But we argue that some strategy for managing collisions is necessary, and whatever solution the mammal brain has adopted, it must generate low, stable net activity that is sparsely distributed across the network.

Acknowledgments

We thank Barbara Finlay, David Field, Marc-Thorsten Hütt, and Ao Tang for helpful discussions.

Author Contributions

YH and DG conceptualized the study, designed the framework, performed analyses, interpreted the results, and wrote the manuscript.

Code Availability

Matlab code for performing simulations under IS and RW models will be posted to GitHub.

References

Abdelnour, F., Voss, H. U., and Raj, A. (2014). Network diffusion accurately models the relationship between structural and functional brain connectivity networks. Neuroimage, 90, 335-347.

Achard, S., Salvador, R., Whitcher, B., Suckling, J., & Bullmore, E. D. (2006). A resilient, low-frequency, small-world human brain functional network with highly connected association cortical hubs. Journal of Neuroscience, 26(1), 63-72.

Aeschbach, D., Matthews, J. R., Postolache, T. T., Jackson, M. A., Giesen, H. A., & Wehr, T. A. (1997). Dynamics of the human EEG during prolonged wakefulness: evidence for frequency-specific circadian and homeostatic influences. Neuroscience Letters, 239(2-3), 121-124.

Attwell, D., and Laughlin, S. B. (2001). An energy budget for signaling in the grey matter of the brain. Journal of Cerebral Blood Flow and Metabolism, 21(10), 1133-114.

Avena-Koenigsberger, A., Mišić, B., Hawkins, R. X., Griffa, A., Hagmann, P., Goñi, J., & Sporns, O. (2017). Path ensembles and a tradeoff between communication efficiency and resilience in the human connectome. Brain Structure and Function, 222(1), 603-618.

Avena-Koenigsberger, A., Misic, B., & Sporns, O. (2018). Communication dynamics in complex brain networks. Nature Reviews Neuroscience, 19(1), 17.

Avena-Koenigsberger, A., Yan, X., Kolchinsky, A., van den Heuvel, M., Hagmann, P., and Sporns, O. (2019). A spectrum of routing strategies for brain networks. PLoS Computational Biology, 15(3), e1006833.

Bakker, R., Wachtler, T. and Diesmann, M. (2012), CoCoMac 2.0 and the future of tract-tracing databases, Frontiers in Neuroinformatics, doi: 10.3389/fninf.2012.00030

Barlow, H. (2001). Redundancy reduction revisited. Network: Computation in Neural Systems, 12(3), 241-253.

Bell, A. J. and Sejnowski, T. J. (1997). The 'independent components' of natural scenes are edge filters. Vision Research 37, 3327-3338.

Bettinardi, R. G., Deco, G., Karlaftis, V. M., Van Hartevelt, T. J., Fernandes, H. M., Kourtzi, Z., ... & Zamora-López, G. (2017). How structure sculpts function: unveiling the contribution of anatomical connectivity to the brain's spontaneous correlation structure. Chaos: An Interdisciplinary Journal of Nonlinear Science, 27(4), 047409.

Bullmore, E., and Sporns, O. (2009). Complex brain networks: graph theoretical analysis of structural and functional systems. Nature Reviews Neuroscience, 10(3), 186.

Bullmore, E., & Sporns, O. (2012). The economy of brain network organization. Nature Reviews Neuroscience, 13(5), 336-349.

Chen, Y., Zhang, Z. K., He, Y., & Zhou, C. (2020). A Large-Scale High-Density Weighted Structural Connectome of the Macaque Brain Acquired by Predicting Missing Links. Cerebral Cortex. https://doi.org/10.1093/cercor/bhaa060

El Gamal, A., & Kim, Y. H. (2011). Network Information Theory. Cambridge University Press.

Field, D. J. (1994). What is the goal of sensory coding? Neural Computation, 6(4), 559-601.

Foldiak, P. (2002). Sparse coding in the primate cortex. The Handbook of Brain Theory and Neural Networks, ed. M.A. Arbib. Cambridge, Ma.: MIT Press.

Fornito, A., Zalesky, A., and Bullmore, E. (2016). Fundamentals of Brain Network Analysis. Academic Press.

Friston, K. J. (2011). Functional and effective connectivity: a review. Brain Connectivity, 1(1), 13-36.

Funahashi, S. (2015). Functions of delay-period activity in the prefrontal cortex and mnemonic scotomas revisited. Frontiers in Systems Neuroscience, 9, 2.

Gămănuţ, R., Kennedy, H., Toroczkai, Z., Ercsey-Ravasz, M., Van Essen, D. C., Knoblauch, K., & Burkhalter, A. (2018). The mouse cortical connectome, characterized by an ultra-dense cortical graph, maintains specificity by distinct connectivity profiles. Neuron, 97(3), 698-715.

Gidon, A., Zolnik, T. A., Fidzinski, P., Bolduan, F., Papoutsi, A., Poirazi, P., ... & Larkum, M. E. (2020). Dendritic action potentials and computation in human layer 2/3 cortical neurons. Science, 367(6473), 83-87.

Goldman-Rakic, P. S. (1996). Regional and cellular fractionation of working memory. Proceedings of the National Academy of Sciences, 93(24), 13473-13480.

Gollisch, T., & Meister, M. (2010). Eye smarter than scientists believed: neural computations in circuits of the retina. Neuron, 65(2), 150-164.

Goñi, J., Avena-Koenigsberger, A., de Mendizabal, N. V., van den Heuvel, M. P., Betzel, R. F., & Sporns, O. (2013). Exploring the morphospace of communication efficiency in complex networks. PLoS One, 8(3).

Goñi, J., van den Heuvel, M. P., Avena-Koenigsberger, A., de Mendizabal, N. V., Betzel, R. F., Griffa, A., ... & Sporns, O. (2014). Resting-brain functional connectivity predicted by analytic measures of network communication. Proceedings of the National Academy of Sciences, 111(2), 833-838.

Graham, D. J. (2014). Routing in the brain. Frontiers in Computational Neuroscience 8:44.

Graham, D. J. (2017). Commentary: Building brains that communicate like machines. Behavioral and Brain Sciences e266, 37-38.

Graham, D. J. and Field, D. J. (2006). Sparse coding in the neocortex. In: Evolution of Nervous Systems Vol. III, ed. Jon H. Kaas and Leah A. Krubitzer. Elsevier, pp. 181-187. doi: 10.1016/B0-12-370878-8/00064-1

Graham, D. J., and Field, D. J. (2009). Natural images: Coding efficiency. Encyclopedia of Neuroscience, Vol. VI, ed. Larry R. Squire. Oxford: Academic Press, pp. 19-27.

Graham, D. J. and Hao, Y. (2018). A selective diffusion model of brain network activity. Proceedings of the Conference on Cognitive Computational Neuroscience, 1195. https://ccneuro.org/2018/proceedings/1195.pdf

Graham, D. J. and Rockmore, D. N. (2011). The packet switching brain. Journal of Cognitive Neuroscience 23 (2), 267-276.

Hahn, G., Ponce-Alvarez, A., Deco, G., Aertsen, A., and Kumar, A. (2019). Portraits of communication in neuronal networks. Nature Reviews Neuroscience, 20(2), 117-127.

Hancock, J. T. (2017). Cell Signalling. Oxford: Oxford University Press.

Kaiser, M., Görner, M., and Hilgetag, C. C. (2007). Functional criticality in clustered networks without inhibition. New Journal of Physics 9, 110.

Kaiser, M., and Hilgetag, C. C. (2010). Optimal hierarchical modular topologies for producing limited sustained activation of neural networks. Frontiers in Neuroinformatics, 4, 8.

Kleinrock, L. (1976) Queueing Systems, Vol II: Computer Applications. New York: Wiley.

Knoblauch, K., Ercsey-Ravasz, M., Kennedy, H., & Toroczkai, Z. (2016). The brain in space. In Micro-, meso-and macro-connectomics of the brain (pp. 45-74). Springer, Cham.

Kopell, N. J., Gritton, H. J., Whittington, M. A., and Kramer, M. A. (2014). Beyond the connectome: the dynome. Neuron, 83(6), 1319-1328.

Lennie, P. (2003). The cost of cortical computation. Current Biology, 13(6), 493-497.

Levy, W. B., and Baxter, R. A. (1996). Energy efficient neural codes. Neural computation, 8(3), 531-543.

Maslov, S., and Sneppen, K. (2002). Specificity and stability in topology of protein networks. Science 296, 910–913

Meytlis, M., Nichols, Z., and Nirenberg, S. (2012). Determining the role of correlated firing in large populations of neurons using white noise and natural scene stimuli. Vision Research, 70, 44-53.

Min, B., & Castellano, C. (2020). Message-passing theory for cooperative epidemics. Chaos: An Interdisciplinary Journal of Nonlinear Science, 30(2), 023131.

Mišić, B., Sporns, O., and McIntosh, A. R. (2014a). Communication efficiency and congestion of signal traffic in large-scale brain networks. PLoS Computational Biology 10(1), e1003427.

Mišić, B., Goñi, J., Betzel, R. F., Sporns, O., and McIntosh, A. R. (2014b). A network convergence zone in the hippocampus. PLoS Computational Biology 10(12), e1003982.

Mišić, B., Betzel, R. F., Nematzadeh, A., Goñi, J., Griffa, A., Hagmann, P. and Sporns, O. (2015). Cooperative and competitive spreading dynamics on the human connectome. Neuron, 86(6), 1518-1529.

Mišić, V. B., & Mišić, J. (2014). Machine-to-machine Communications: Architectures, Technology, Standards, and Applications. CRC Press.

Navlakha, S., Barth, A. L., and Bar-Joseph, Z. (2015). Decreasing-rate pruning optimizes the construction of efficient and robust distributed networks. PLoS Computational Biology, 11(7), e1004347.

Navlakha, S., Bar-Joseph, Z., and Barth, A. L. (2017). Network Design and the Brain. Trends in Cognitive Sciences.

Noh, J. D., & Rieger, H. (2004). Random walks on complex networks. Physical review letters, 92(11), 118701.

Olshausen, B. A., Anderson, C. H., and Van Essen, D. C. (1993). A neurobiological model of visual attention and invariant pattern recognition based on dynamic routing of information. Journal of Neuroscience, 13(11), 4700-4719.

Olshausen, B. A., and Field, D. J. (1996). Emergence of simple-cell receptive field properties by learning a sparse code for natural images. Nature, 381(6583), 607.

Ovsepian, S. V. (2019). The dark matter of the brain. Brain Structure and Function, 224(3), 973-983.

Poggio, T. (1984). Routing thoughts. Massachusetts Institute of Technology Artificial Intelligence Laboratory Working Paper 258.

Poldrack, R. A. (2015). Is "efficiency" a useful concept in cognitive neuroscience? Developmental Cognitive Neuroscience, 11, 12-17.

Rolls, E. T. and Tovee, M. J. (1995). Sparseness of the neuronal representation of stimuli in the primate temporal visual cortex. Journal of Neurophysiology 73, 713-726.

Rubinov, M., and Sporns, O. (2010). Complex network measures of brain connectivity: uses and interpretations. Neuroimage, 52(3), 1059-1069.

Sardi, S., Vardi, R., Sheinin, A., Goldental, A., & Kanter, I. (2017). New types of experiments reveal that a neuron functions as multiple independent threshold units. Scientific reports, 7(1), 1-17.

Schruben, L. W., & Margolin, B. H. (1978). Pseudorandom number assignment in statistically designed simulation and distribution sampling experiments. Journal of the American Statistical Association, 73(363), 504-520.

Scott, A. (1977). Neurophysics. John Wiley and Sons.

Seguin, C., Razi, A., and Zalesky, A. (2019). Inferring neural signalling directionality from undirected structural connectomes. Nature Communications, 10(1), 1-13.

Sosnovich, A., Grumberg, O., and Nakibly, G. (2017). Formal Black-Box Analysis of Routing Protocol
Implementations. arXiv preprint arXiv:1709.08096.
Steriade, M., & Paré, D. (2007). Gating in Cerebral Networks. Cambridge University Press.
Tipnis, U., Amico, E., Ventresca, M., & Goni, J. (2018). Modeling communication processes in the human
connectome through cooperative learning. IEEE Transactions on Network Science and Engineering.
Treves A and Rolls E T 1991 What determines the capacity of autoassociative memories in the brain?
Network: Computation in Neural Systems 2, 371–97.
Turrigiano, G. G. (1999). Homeostatic plasticity in neuronal networks: the more things change, the more
they stay the same. Trends in Neurosciences, 22(5), 221-227.
Wainwright, M. J. (1999). Visual adaptation as optimal information transmission. Vision Research,
39(23), 3960-3974.
Waxman, S. G. (1972). Regional differentiation of the axon: a review with special reference to the concept
of the multiplex neuron. Brain Research, 47(2), 269-288.
Willmore, B., and Tolhurst, D. J. (2001). Characterizing the sparseness of neural codes. Network:
Computation in Neural Systems, 12(3), 255-270.

690
691

Supplemental Material

693
694

Algorithm 1 Information Spreading

```
 1: procedure MESSAGE FEED
 2:     N ← the number of states in the network
 3:     Adj ← the adjacency matrix of the networks
 4:     n_batch ← how many batches of messages will be fed to the network
 5:     load ← number of messages in each batch
 6:     Msg ← load random sender and receiver node pairs
 7:     Senders ← all sender nodes in Msg
 8:     Activity ← n_batch × N matrix of 0
 9:     Activity(1, Senders) ← 1
10:     Attempts(1, Senders) ← 1
11: end procedure
12: procedure MESSAGE DISTRIBUTION
13: loop:
14:     for i ← 2, n_batch do
15:         Activity(i, :) ← Activity(i − 1, :) × Adj
16:         Msg ← load random sender and receiver node pairs
17:         Senders ← all sender nodes in Msg
18:         NewActivity ← 1 × N vector of 0
19:         NewActivity(Senders) ← 1
20:         Activity(i, :) ← Activity(i, :) + NewActivity
21:         Attempts(i, :) ← Activity(i, :)
22:         Where ← where entries of Activity(i, :) are ≥ 1
23:         Activity(i, Where) ← 0
24:         Attempts(i, Where) ← 1
25:     end for
26: end procedure
```

Algorithm 2 RandomWalk

```
 1: procedure MESSAGE FEED
 2:     n_batch ← how many batches of messages will be fed to the network
 3:     load ← number of messages in each batch
 4:     Msg ← load random sender and receiver node pairs
 5:     Activity(1, :) ← all sender nodes in Msg
 6:     Attempts(1, :) ← all sender nodes in Msg
 7: end procedure
 8: procedure MESSAGE DISTRIBUTION
 9: loop:
10:     for i ← 2, n_batch do
11:         for j ← 1, length of Activity(i − 1, :) do
12:             PossibNext ← all nodes reachable from Activity(i − 1, j)
13:             NextMsg(j) ← a randsample from PossibNext
14:         end for
15:         Msg ← load random sender and receiver node pairs
16:         Activity(i, :) ← [NextMsg, Msg]
17:         Attempts(i, :) ← all unique entries in Activity(i, :)
18:         Jams ← all repeated elements in Activity(i, :)
19:         if Jams ≠ ∅ then
20:             for k = 1, length of Jams do
21:                 Where ← positions of entries in Activity that equal to Jams(k)
22:                 Activity(i, Where) ← 0
23:             end for
24:         end if
25:     end for
26: end procedure
```

696
Box S1. (A) Pseudocode of information spreading (IS) model. (B) Pseudocode of random walk (RW) model.

$$S = \frac{\left(\frac{1}{N} \sum_i x_n\right)^2}{\frac{1}{N} \sum_i x_n^2}$$

Figure S1. Illustration of the Treves-Rolls measure of sparseness S for hypothetical histograms of activity data. Maximal sparseness (S closest to zero) equal to $1/N$ is achieved for a histogram where activities of x_n are all zero except for one non-zero entry (indicated here by "high"). Histograms that are well approximated by other common functions are shown with corresponding sparseness values: Pareto ($S \approx 0.33$); Exponential ($S \approx 0.5$); and Gaussian ($S \approx 0.64$). A uniform histogram (not shown) has minimal sparseness of $S = 1.0$.

Figure S2. Mean lifetime sparseness of IS (solid lines) and RW (dashed lines) models as a function of load. As with population sparseness, lifetime sparseness is greater (closer to 0) for IS models compared to RW at loads above 1 message per time step. Shaded areas indicate 2 standard deviations from the mean. Filled symbols indicate significant differences (t-test, p<0.01) between corresponding IS and RW data, whereas open symbol indicates no significant difference.

Frequency of net activity across time under IS

750   B

751
752   **Figure S3. Relative frequency of net activity under IS models (A) and under RW models (B) at**
753   **different loads.** Results are for the *mouse* network. Tildes in A indicate a contracted vertical axis.