Prediction of the receptorome for the human-infecting virome

Zheng Zhang[1,#], Sifan Ye[1,#], Aiping Wu[2], Taijiao Jiang[2],Yousong Peng[1,*]

[1] College of Biology, Hunan Provincial Key Laboratory of Medical Virology, Hunan University,

Changsha 410082, China

[2] Center for Systems Medicine, Institute of Basic Medical Sciences, Chinese Academy of Medical

Sciences & Peking Union Medical College, Beijing 100005, Suzhou Institute of Systems

Medicine, Suzhou, Jiangsu 215123, China;

[#] These authors contributed equally to this work

* Corresponding author: Yousong Peng, pys2013@hnu.edu.cn

Abstract

The virus receptors are key for the viral infection of host cells. Identification of the

virus receptors is still challenging at present. Our previous study has shown that

human virus receptor proteins have some unique features including high

N-glycosylation level, high number of interaction partners and high expression level.

Here, a random-forest model was built to identify human virus receptorome from

human cell membrane proteins with an accepted accuracy based on the combination

of the unique features of human virus receptors and protein sequences. A total of 1380

human cell membrane proteins were predicted to constitute the receptorome of the

human-infecting virome. In addition, the combination of the random-forest model

with protein-protein interactions between human and viruses predicted in previous

studies enabled further prediction of the receptors for 693 human-infecting viruses,

such as the Enterovirus, Norovirus and West Nile virus. As far as we know, this study

is the first attempt to predict the receptorome for the human-infecting virome and

would greatly facilitate the identification of the receptors for viruses.

Inroduction

Receptor-binding is the first step for viral infection of host cells. Proteins are

considered to be the more ideal receptors for viruses due to their higher binding

affinity and specificity than carbohydrate and lipid (Baranowski et al., 2001;

Casasnovas, 2013; Dimitrov, 2004; Li, 2015; Wang, 2002). Lots of human virus

receptors have been identified. In addition, it is not a random process for viruses to

choose proteins as their receptors. Previous studies have shown that the proteins that

are abundant in the surface of host cells or have relatively low affinity for their natural

ligands are the preferred receptors for viruses (Dimitrov, 2004; Wang, 2002).

Moreover, based on a collection of 119 mammalian virus receptors, our recent study

has further revealed that human virus receptor proteins have higher level of

N-glycosylation, higher number of interaction partners in the human protein-protein

interaction (PPI) network and higher expression level in 32 common human tissues

compared to other cell membrane proteins (Zhang et al., 2019). The results obtained

from these studies could facilitate the identification of human virus receptors.

Identification of virus receptors in host cells is challenging. Currently, several

experimental methods have been developed for identifying virus receptors. The first

approach is to select candidate membrane proteins that can bind to the virus

receptor-binding proteins (RBPs) by affinity purification and mass spectroscopy (Free

et al., 2009; Ryu, 2016). The second approach is firstly to identify monoclonal

antibodies which can block the virus entry, and then take the membrane proteins to

which the monoclonal antibodies bind as candidate receptor proteins (Minor et al.,

1984; Ryu, 2016). The third approach is to identify virus receptors by functional

cloning selection based on the cDNA expression library (Ryu, 2016). The proteins

that can enable viral infection of the non-susceptible cells after transfection are

considered as the receptor candidates. However, the identification of virus receptors is

still time-consuming and difficult at present. Besides, the limitations on scalability

have hampered the large-scale identification of viral receptors. Therefore, it is urgent

to develop the computational methods for the identification of the human virus

receptors.

Previous studies have developed several computational models for predicting the PPIs

between viruses and hosts which can help identify virus receptors (Lasso et al., 2019;

Yan et al., 2019). For example, Lasso et al. developed an in silico computational

framework (P-HIPSTer) that employed the structural information to predict more than

280,000 PPIs between 1,001 human-infecting viruses and humans, and made a series

of new findings about human-virus interactions (Lasso et al., 2019). The predicted

PPIs between viral RBPs and human cell membrane proteins can be used to identify

virus receptors. Here, a computational model was developed to predict the

receptorome of the human-infecting virome based on the features of human virus

receptors and protein sequences. Furthermore, the combination of this computational

model with the PPIs predicted in Lasso's work was further used to predict the

receptors for 693 human-infecting viruses. The results of this study would greatly

facilitate the identification of human virus receptors.

Materials and Methods

Human virus receptors, human cell membrane proteins and human membrane

proteins

A total of 91 human virus protein receptors were obtained from the viralReceptor

database (available at http://www.computationalbiology.cn:5000/viralReceptor) that

was developed in our previous study (Zhang et al., 2019). Human cell membrane

proteins and human membrane proteins were obtained from the

UniProtKB/Swiss-Prot database on February 21, 2020. The human proteins with the

words of "cell membrane" and "cell surface" in the field of "Subcellular location"

were considered to be human cell membrane proteins. The human proteins with the

words of "membrane" and "cell surface" in the field of "Subcellular location" were

considered to be human membrane proteins. A total of 3,642 human cell membrane

proteins and 7,663 human membrane proteins were obtained.

Features of the human virus protein receptors and protein sequences

The N-glycosylation sites of the human proteins mentioned above were obtained from

the UniprotKB/Swiss-Prot database. For those proteins without the annotation of

N-glycosylation sites in the UniprotKB/Swiss-Prot database, their N-glycosylation

sites were predicted with NetNGlyc 1.0 (available at

http://www.cbs.dtu.dk/services/NetNGlyc/) (Gupta et al., 2004). The N-glycosylation

level of these proteins was defined as the number of N-glycosylation sites per 100

amino acids.

To calculate the node degree of the human proteins in the human PPI network, firstly,

the human PPIs with the combined scores greater than 400 were extracted from the

STRING database (version 10.5) (Szklarczyk et al., 2015) and were used to form the

human PPI network. Then, the node degree was calculated with the function of *degree*

in the R package igraph (version 1.2.4.2) (Csardi and Nepusz, 2006).

The expression level of the human genes in 32 common human tissues was obtained

from the Expression Atlas database (Petryszak et al., 2016) on February 6, 2018.

Since there were strong correlations between the gene expression level in different

tissues, the principal component analysis (PCA) method was used to reduce the

correlations with the function of *PCA* in the package scikit-learn (version 0.21.3)

(Pedregosa et al., 2011) in Python (version 3.6.7). Only the first principal component

was used to measure the expression level of human genes, which explained 95% of

the total variance.

The frequencies of k-mers with one or two amino acids were calculated for each

human protein with a Python script.

Machine learning modeling

To distinguish human virus receptors from other human cell membrane proteins using

machine learning models, the human virus receptors were chosen as positive samples.

Since the human cell membrane proteins may contain virus receptors unidentified yet,

the human membrane proteins were taken as negative samples after excluding the

human cell membrane proteins.

Because not all human proteins were observed in the used human PPI network or

showed the observed expressions in the available data, only the human proteins that

possess all the three protein features, i.e., the N-glycosylation level, node degree and

expression in common human tissues, were used in the modeling. Besides, the

sequence redundancy in both human virus receptor proteins and human membrane

proteins was removed using CD-HIT (version 4.8.1) (Fu et al., 2012) at 70% identity

level. Finally, a total of 88 human virus receptors and 1,743 human membrane

proteins were used in the machine learning modeling.

The random-forest (RF) model is an ensemble machine learning technique using

multiple decision trees and can handle data with high variance and high bias, while

the risk of over-fitting can be significantly reduced by averaging multiple trees.

Therefore, the RF model was chosen to distinguish human virus receptors from other

human cell membrane proteins. Since the number of positive samples (human viral

receptors) was much smaller than that of negative samples (human membrane

proteins), the function of BalanceRandomForest in the package imbalanced-learn

(version 0.5.0) (Chen et al., 2004) in Python was used to deal with the imbalanced

positive and negative samples with the parameter of n_estimators set to be 100.

Five times of five-fold cross-validations were conducted to evaluate the predictive

performances of the RF model with the function of StratifiedKFold in the package

scikit-learn in Python. The predictive performances of the RF model were evaluated

by the area under receiver operating characteristics curve (AUC), accuracy, sensitivity

and specificity.

Validation of the RF model by ranking the receptor candidates

The predicted PPIs between human-infecting viruses and human were obtained from

the database of P-HIPSTer (available at http://phipster.org/) (Lasso et al., 2019) on

November 1, 2019. A total of 9,395 pairs of interactions between viral RBPs and

human cell membrane proteins with the likelihood ratio (LR) $\geq$ 100 were extracted

for further analysis, which included 718 viral RBPs and 314 human cell membrane

proteins. The RBPs of human-infecting viruses were compiled from three sources: the

ViralZone database (Masson et al., 2012), the UniprotKB database in which viral

proteins were annotated with GO terms "viral entry into host cell" or "virion

attachment the host cell", and the literatures related to viral RBPs. The viruses

belonging to the same viral family were supposed to use the same RBPs. For example,

all coronaviruses were supposed to take the spike protein as RBPs.

To evaluate the ability of the RF model in identification of virus receptors, 25 pairs of

experimentally validated interactions between viral RBPs and receptors, and the

predicted PPIs between these viral RBPs and human cell membrane proteins were

extracted from the P-HIPSTer database. For each viral RBP, the predicted

RBP-interacting human cell membrane proteins were ranked by either the LR

provided in Lasso's work, or the predicted score provided by the RF model. Then, the

ranks of the real receptors were analyzed, and the rank percentage of each real

receptor was calculated by dividing the rank by the number of RBP-interacting human

cell membrane proteins.

When ranking the RBP-interacting proteins by the RF model, the performance of the

RF model may be over-estimated due to the sequence similarity between the

RBP-interacting proteins and human proteins in the modeling. To reduce the above

effect, for each pair of viral RBP and receptor, the predicted RBP-interacting human

cell membrane proteins were clustered with human proteins used in the modeling

using CD-HIT at 50% identity level. All the proteins which were clustered with

RBP-interacting proteins were excluded in the modeling.

Data availability

All data used in this study were obtained from public databases as mentioned above.

Results

Development of random-forest models for predicting the receptorome of the

human-infecting virome

Our previous studies have shown that human virus protein receptors have unique

features including high N-glycosylation level, high number of interaction partners in

the human PPI network, and high expression level in 32 common human tissues

(Zhang et al., 2019). To identify the potential receptors of the human-infecting virome,

firstly, a RF model was built to distinguish the human virus receptor proteins from

other human membrane proteins based on the above features. The RF model built

based on individual protein feature achieved an AUC ranging from 0.51 to 0.61 in

five-fold cross-validations (Table 1). The combination of all three features greatly

improved the RF model with both the AUC and the prediction accuracy equaling to

0.70 (Table 1).

For comparison, we also developed RF models to distinguish the human virus

receptors from other human membrane proteins based on protein sequences. The

frequencies of k-mers with length of one and two amino acids were used as features in

the modeling. The RF model built based on the combination of 20 amino-acid

frequencies achieved an AUC of 0.70. When using the frequencies of k-mers with two

amino acids as features, only the top N (N = 1 to 400) most important features were

used in the modeling to reduce over-fitting. Figure S1 showed that the AUC of the RF

models increased rapidly as the increase of N from 1 to 10. Then, it increased slowly

or even decreased when more than ten features were used. Therefore, only top ten

features were used in the modeling to balance the performance and complexity of the

model. The RF model based on top ten features achieved an AUC of 0.71.

To further improve the model for predicting the receptorome of the human-infecting

virome, the protein features and the top ten most important k-mers of two amino acids

were incorporated in the modeling. The RF model achieved an AUC of 0.75. The

prediction accuracy, sensitivity and specificity of the model were 0.76, 0.73 and 0.76,

respectively (Table 1). The model combining both the protein features and k-mers was

used for further analysis.

Table 1. The predictive performances of RF models using different sets of features.

N-gly, N-glycosylation; PPI, node degree in human PPI network; Expression,

expressions in 32 human tissues. Acc, accuracy; Sen, Sensitivity; Spe, Specificity.

Model with different sets of features	Acc	Sen	Spe	AUC
N-gly	0.59	0.58	0.59	0.59
PPI	0.62	0.60	0.62	0.61
Expression	0.50	0.51	0.50	0.51
N-gly+PPI+Expression	0.72	0.68	0.72	0.70
Top 10 k-mers	0.70	0.71	0.70	0.71
N-gly+PPI+Expression + Top 10 k-mers	0.76	0.73	0.76	0.75

Prediction of the receptorome for the human-infecting virome

Based on the RF model, the receptorome was predicted from human cell membrane

proteins. A score ranging from 0 to 1 was assigned to each human cell membrane

protein. The proteins with high scores are more likely to be virus receptors. A total of

1380 proteins with scores greater than 0.5 were considered to constitute the

receptorome of the human-infecting virome. Table 2 listed top 20 human cell

membrane proteins and the relevant scores (for all human cell membrane proteins,

please see Table S1).

Table 2. Top 20 human cell membrane proteins and their scores assigned by the RF model.

Gene Name	Protein name	RF score	Gene Name	Protein name	RF score
LAMP1	Lysosome-associated membrane glycoprotein 1	0.968	LAMP2	Lysosome-associated membrane glycoprotein 2	0.913
ITGAV	Integrin alpha-V	0.961	TYRO3	Tyrosine-protein kinase receptor TYRO3	0.911
PVR	Poliovirus receptor	0.955	HSPA8	Heat shock cognate 71 kDa protein	0.907
FGFR3	Fibroblast growth factor receptor 3	0.953	GPNMB	Transmembrane glycoprotein NMB	0.899
NECTIN1	Nectin-1	0.946	NCAM1	Neural cell adhesion molecule 1	0.895
TNFRSF14	Tumor necrosis factor receptor superfamily member 14	0.928	CD86	T-lymphocyte activation antigen CD86	0.893
DPP4	Dipeptidyl peptidase 4	0.928	EGFR	Epidermal growth factor receptor	0.893
CD55	Complement decay-accelerating factor	0.922	LDLR	Low-density lipoprotein receptor	0.892
ITGB1	Integrin beta-1	0.918	CD44	CD44 antigen	0.891
CR2	Complement receptor type 2	0.915	FGFR2	Fibroblast growth factor receptor 2	0.889

Prediction of virus-receptor interactions for human-infecting viruses

Then, the prediction of virus-receptor interactions was investigated. In the previous study, Lasso et al. predicted 282,528 pairs of PPIs between human and 1,001 human-infecting viruses (Lasso et al., 2019). Based on the study, 9,395 pairs of PPIs between 718 viral RBPs from 693 human-infecting viruses, and 314 human cell membrane proteins were extracted for further analysis (see Table S2). A viral RBP was predicted to interact with 1 to 65 human cell membrane proteins, with a median of 10. For each viral RBP, the RBP-interacting cell membrane proteins were ranked by the score provided by the RF model to select the most likely receptor (Table S2).

To validate the accuracy of the ranking by the RF model, 25 pairs of experimentally

validated interactions between viral RBPs and receptors were extracted. For each pair

of viral RBP and its receptor, the rank of the real receptor among the predicted

RBP-interacting proteins was obtained, and then the related rank percentage was

calculated (Materials and Methods). Ten real receptors were ranked in top one by the

RF model (Table 3). Besides, nearly 60% (14/25) of real receptors were ranked in top

three. On average, the real receptors had a rank percentage of 0.20 among all the

RBP-interacting human cell membrane proteins, suggesting that the real receptors

would be ranked in the top 20% of all candidates by the RF model.

The LR provided in Lasso's work can also be used to rank the RBP-interacting

proteins. 12 of 25 pairs of experimentally validated viral RBP-receptor interactions

had LRs available from Lasso's work. For comparison, the viral RBP-interacting

human cell membrane proteins were ranked by LR. No real receptor was ranked in

top one, and only two real receptors were ranked in top three when ranking

RBP-interacting human cell membrane proteins by using LR. On average, the median

rank percentage of real receptors was 0.43 when ranking was conducted by the LR,

while that was 0.10 by the RF model (Table 3).

Table 3. The ranks of real virus receptors among the RBP-interacting human cell

membrane proteins by LR and RF score.

Virus name	RBP	Real viral receptor	Num of RBP-interacting proteins	Rank by LR	Rank by RF score
SARS-CoV	S	ACE2	31	-[*]	21
MERS-CoV	S	DPP4	8	-	2
Echovirus E6	VP1	CD55	13	5	1
Echovirus E11	VP1	CD55	9	4	1

Echovirus E7	VP1	CD55	7	-	1
Echovirus E13	VP1	CD55	11	4	1
Echovirus E20	VP1	CD55	12	5	1
Echovirus E29	VP1	CD55	13	6	1
Echovirus E33	VP1	CD55	13	6	1
Enterovirus C	VP1	PVR	5	-	1
Hepacivirus C	E1	EGFR	17	10	1
MACV	GPC	TFRC	2	-	1
Measles virus	H	NECTIN4	18	-	13
Measles virus	H	SLAMF1	18	2	4
Hendra virus	G	EFNB2	5	-	4
Nipah virus	G	EFNB2	5	-	5
HAdV-A	L5	CXADR	25	-	22
HAdV-C	L5	CXADR	5	4	5
HAdV-E	L5	CXADR	33	3	20
HAdV-D	L5	CXADR	28	4	24
HSV-1	US6	TNFRSF14	28	-	2
HSV-1	US6	NECTIN1	28	-	3
HSV-2	US6	NECTIN1	34	-	2
HSV-2	US6	TNFRSF14	34	23	6
HIV-1	env	CD4	21	-	5
Top 1				0	10 (7)[#]
Top 3				2	14 (7)[#]
Top 5				8	19 (9)[#]
Median rank percentage				0.43	0.20 (0.10)[#]

The median rank percentage of real virus receptors among RBP-interacting human

cell membrane proteins, and the number of real virus receptors among top one, three

and five ranks were summarized at the bottom. [#]The number in brackets referred to

those when only considering 12 pairs of viral RBP-receptor interaction with LRs

available from Lasso's work. * No LR was provided in Lasso's work since there were

resolved complex structures between the RBP and the receptor. MACV, Machupo

mammarenavirus; HAdV-A, Human mastadenovirus A; HAdV-C, Human

mastadenovirus C; HAdV-E, Human mastadenovirus E;HAdV-D, Human

mastadenovirus D; HSV-1, Human alphaherpesvirus 1; HSV-2, Human

alphaherpesvirus 2; HIV-1, Human immunodeficiency virus 1.

Discussion

The identification of receptors for human-infecting viruses is critical for

understanding the interactions between viruses and human. Our previous studies have

shown that human virus receptor proteins have some unique features compared to

other cell membrane proteins, including high N-glycosylation level, high number of

interaction partners and high expression level. This study further built a RF model for

identifying human virus receptors from human cell membrane proteins with an

accepted accuracy. Based on the RF model, the receptorome for the human-infecting

virome was predicted, which included a total of 1380 human cell membrane proteins.

The results could facilitate the identification of human virus receptors.

In the previous study, Lasso et al. developed a computational model for predicting

PPIs between human-infecting viruses and human (Lasso et al., 2019). A variable

number of human cell membrane proteins were predicted to interact with viral RBPs.

To further select the potential receptors for viruses, both the LR and the RF model

were used to rank the viral RBP-interacting human cell membrane proteins. The RF

model was found to rank the real receptors better than the LR in a small validation

dataset, suggesting that the performance of the RF model may be superior to that of

the LR in selecting the real receptors from the predicted RBP-interacting human cell

membrane proteins. The combination of the RF model and the RBP-interacting

human cell membrane proteins predicted in Lasso's work enabled the prediction of

receptors for 693 human-infecting viruses (Table S2). Nevertheless, more efforts are

needed to validate these candidate receptors in future studies.

There are some limitations to this study. Firstly, the number of human virus receptor

proteins was much smaller than that of human membrane proteins in the modeling,

which may hinder accurate modeling. Thus, the under-sampling method was used to

deal with the imbalance problem. Secondly, the performance of the RF model was

modest in discriminating human virus receptor proteins from human membrane

proteins. More efforts are still needed to improve the model. Thirdly, although the RF

model can be used to predict the receptorome of human-infecting virome, it is not

feasible to use the model to identify the receptors for a specific human-infecting virus.

The combination of the RF model with the model of PPI predictions such as Lasso's

work can help identify virus-receptor interactions.

In conclusion, this study for the first time built a computational model for predicting

the receptorome of the human-infecting virome. The results can facilitate the

identification of human virus receptors in either computational or experimental

studies.

Acknowledgements

This work was supported by the National Key Plan for Scientific Research and

Development of China (2016YFD0500300), Hunan Provincial Natural Science

Foundation of China (2018JJ3039), and the Chinese Academy of Medical Sciences

(2016-I2M-1-005).

The authors have declared that no competing interests exist.

Ethical Statement

No ethical approval was required because no human or animal samples were collected

in this study.

References

Baranowski E, Ruiz-Jarabo CM, Domingo E (2001) Evolution of cell recognition by viruses Science 292:1102-1105

Casasnovas JM (2013) Virus-receptor interactions and receptor-mediated virus entry into host cells. In: Structure and Physics of Viruses. Springer, pp 441-466

Chen C, Liaw A, Breiman L (2004) Using random forest to learn imbalanced data University of California, Berkeley 110:24

Csardi G, Nepusz T (2006) The igraph software package for complex network research InterJournal, complex systems 1695:1-9

Dimitrov DS (2004) Virus entry: molecular mechanisms and biomedical applications Nature Reviews Microbiology 2:109-122

Free RB, Hazelwood LA, Sibley DR (2009) Identifying novel protein-protein interactions using co-immunoprecipitation and mass spectroscopy Current protocols in neuroscience 46:5.28. 21-25.28. 14

Fu L, Niu B, Zhu Z, Wu S, Li W (2012) CD-HIT: accelerated for clustering the next-generation sequencing data Bioinformatics 28:3150-3152

Gupta R, Jung E, Brunak S (2004) Prediction of N-glycosylation sites in human proteins

Lasso G et al. (2019) A structure-informed atlas of human-virus interactions Cell 178:1526-1541. e1516

Li F (2015) Receptor recognition mechanisms of coronaviruses: a decade of structural studies Journal of virology 89:1954-1964

Masson P et al. (2012) ViralZone: recent updates to the virus knowledge resource Nucleic acids research 41:D579-D583

Minor P, Pipkin P, Hockley D, Schild G, Almond J (1984) Monoclonal antibodies which block cellular receptors of poliovirus Virus research 1:203-212

Pedregosa F et al. (2011) Scikit-learn: Machine learning in Python Journal of machine learning research 12:2825-2830

Petryszak R et al. (2016) Expression Atlas update—an integrated database of gene and protein expression in humans, animals and plants Nucleic acids research 44:D746-D752

Ryu, W-S (2016) Molecular virology of human pathogenic viruses. Academic Press

Szklarczyk D et al. (2015) STRING v10: protein–protein interaction networks, integrated over the tree of life Nucleic acids research 43:D447-D452

Wang J-h (2002) Protein recognition by cell surface receptors: physiological receptors versus virus interactions Trends in biochemical sciences 27:122-126

Yan C, Duan G, Wu F-X, Wang J (2019) IILLS: predicting virus-receptor interactions based on similarity and semi-supervised learning BMC bioinformatics 20:651

Zhang Z et al. (2019) Cell membrane proteins with high n-glycosylation, high expression and multiple interaction partners are preferred by mammalian viruses as receptors Bioinformatics 35:723-728