HLA-class II specificity assessed by high-density peptide microarray interactions

Thomas Osterbye[1], Morten Nielsen[2,5], Nadine L. Dudek[3], Sri H. Ramarathinam[3], Anthony

W. Purcell[3], Claus Schafer-Nielsen[4], and Soren Buus[1]

[1]*Department of Immunology and Microbiology, University of Copenhagen, Denmark*

[2]*Department of Health Technology, Technical University of Denmark, Lyngby, Denmark*

[3]*Department of Biochemistry & Molecular Biology and Infection and Immunity Program,*

Biomedicine Discovery Institute, Monash University, Clayton VIC 3800, Australia

[4] *Schafer-N, Copenhagen, Denmark*

[5]*Instituto de Investigaciones Biotecnológicas, Universidad Nacional de San Martín, San*

Martín, Argentina

Abstract

The ability to predict and/or identify MHC binding peptides is an essential component

of T cell epitope discovery; something that ultimately should benefit the development of

vaccines and immunotherapies. In particular, MHC class I (MHC-I) prediction tools have

matured to a point where accurate selection of optimal peptide epitopes is possible for

virtually all MHC-I allotypes; in comparison, current MHC class II (MHC-II) predictors are

less mature. Since MHC-II restricted CD4+ T cells control and orchestrate most immune

responses, this shortcoming severely hampers the development of effective immunotherapies.

The ability to generate large panels of peptides and subsequently large bodies of peptide-

MHC-II interaction data is key to the solution of this problem; a solution that also will

support the improvement of bioinformatics predictors, which critically relies on the

availability of large amounts of accurate, diverse and representative data. Here, we have used

recombinant HLA-DRB1*01:01 and HLA-DRB1*03:01 molecules to interrogate high-

density peptide arrays, *in casu* containing 70,000 random peptides in triplicates. We

demonstrate that the binding data acquired contains systematic and interpretable information

reflecting the specificity of the HLA-DR molecules investigated. Collectively, with a cost per

peptide reduced to a few cents combined with the flexibility of recombinant HLA

technology, this poses an attractive strategy to generate vast bodies of MHC-II binding data

at an unprecedented speed and for the benefit of generating peptide-MHC-II binding data as

well as improving MHC-II prediction tools.

1   **Introduction**

The binding of peptides to major histocompatibility complex class II (MHC-II)

molecules is one of the most selective events in antigen presentation. Expressed by

professional antigen presenting cells and presenting exogenous peptides to CD4+ T cells,

MHC-II is central to adaptive immunity. Since CD4+ T cells, restricted to MHC-II, are

recognized for their orchestrating role in shaping both humoral and cellular immune

responses, much effort has been put into understanding the specificity of MHC-II. The human

MHC (human leucocyte antigen) HLA loci is one of the most polymorphic gene families

known (1), and as of September 2019, the number of HLA class II HLA-II alleles amounts to

7,065 according to hla.alleles.org, not considering the additional diversity created by the

combinatorial HLA-DPA/DPB and HLA-DQA/DQB pairing. Further, considering the

number of peptides that can be presented and the huge diversity of T cell receptors that can

recognize peptide-HLA-II (pHLAII) complexes, the combinations of peptides, HLA-II and

TcRs that should be evaluated to characterize this interaction system are staggering. This

calls for high-throughput and bioinformatics-based approaches. Indeed, bioinformatics has

been a driving force in describing MHCII specificity. Based on binding and affinity data,

several different algorithms have been developed capable of predicting peptide MHC-II

interactions (e.g. the NetMHC suite) as an efficient approach to address the vast number of

peptides and MHC allotypes. Prediction algorithms powered by artificial neural networks

(ANNs) are dependent on large bodies of data which are costly to generate since each peptide

conventionally needs to be individually synthesized and handled before conducting binding

experiments. More recently, proteomics-driven, high-throughput identification of peptides

eluted off MHC-II molecules has become possible and used to improve the performance of

MHC-II prediction algorithms (2).

While the prediction tools available today have improved significantly over the years, they are still impaired by a high false positive rate (3) making it difficult to select true T cell epitopes. This is recognized as a major current problem in the development of personalized medicine and immunotherapies, in particular those modes that are based on real-time discovery of tumor neo-antigens (4, 5). The recent advances within the field of cancer immunotherapy have suggested that immunization with tumor derived neo-antigens is a very promising strategy and growing evidence suggests that MHC-II-restricted neo-antigens should be included (4, 6, 7). Hence, there is an increasing demand for more accurate and efficient predictors of peptide MHC-II interactions, underscored by the pharmaceutical industry now focusing on developing MHC-II prediction tools (8).

We have for years chosen a biochemical approach to study peptide MHC interactions (9). This has resulted in the generation of a large collection of recombinant HLA molecules, which have been used to generate tens of thousands of data points subsequently used to develop the NetMHC suite of prediction algorithms (10-12), which continues to be updated. While high-throughput assays have been developed to study peptide-MHC interactions, classical orthogonal peptide synthesis remains a very costly and time-consuming bottleneck. However, within the last decade, high-density peptide microarray platforms, potentially containing up to millions individual peptides/array, have become available at a cost as low as a few cents/peptide. We have recently developed and used high-density peptide microarrays to characterize linear sequence motifs such as enzyme cleavage sites and B cell epitopes in great detail (13-18). Such peptide microarrays containing C-terminally anchored 15-mer peptides should in theory be able to interact with MHC-II molecules due to its open-ended peptide-binding cleft allowing peptides to protrude through the ends of the cleft; something that should allow C-terminal tethering.

The ability to acquire millions of peptide-MHC-II binding data in a single experiment

could potentially transform CD4+ T cell epitope discovery. In particular, the combination of

such data with machine-learning methods has the potential to transform the development of

peptide-MHC-II predictors. Here, we have investigated the binding of HLA-

DRA1*01:01/HLA-DRB1*01:01 and HLA-DRA1*01:01/HLA-DRB1*03:01 to high-density

peptide microarrays containing ~70k random peptides in triplicate; used the binding data to

train ANNs, validated these using peptides eluted off HLA-DRA1*01:01/HLA-DRB1*01:01

and HLA-DRA1*01:01/HLA-DRB1*03:01, and compared the prediction power to ANNs

trained on public available binding affinity data from the IEDB (19).

Results

We investigated the binding of HLA-DR molecules to peptides, synthesized *in situ* on microscope glass slides (17), by *de novo* folding of recombinant HLA-DR molecules (20) followed by staining with a monoclonal mouse anti-HLA-DR antibody known to react with a conformational HLA-DR alpha epitope, exclusively expressed by correctly folded HLA-DR alpha-beta hetero-dimers (21) and finally stained with Cy3-labeled polyclonal goat anti-mouse IgG. Only in the presence of both HLA-DRA and HLA-DRB did we obtain a staining pattern corresponding to the location, geometry and size of relevant peptides synthesized *in situ* (figure 1) confirming that conformationally intact peptide-HLA-DR complexes were obtained. We found no binding of the Cy3-goat anti-mouse IgG to the peptide arrays in absence of HLA-DRA, HLA-DRB, or L243 (figure 1) showing that the signals obtained was dependent on the presence of *on chip* generated peptide-HLA-DR complexes.

We determined the optimal peptide length to be synthesized on these peptide microarrays by synthesizing peptides with lengths from 9-15 amino acid residues and using the binding data to train artificial neural networks. Initially, NNAlign-1.4, was used to evaluate the effect of peptide length on network performance expressed as PCC and RMSE. with an optimal performance identified as maximizing the PCC in combination with the lowest RMSE. This identified a peptide length of 13 as being optimal for developing efficient predictors with a combination of high PPC and low RMSE. It should be noted that later versions of the algorithm such as NNAlign-2.1, which allows the incorporation of insertions and deletions in the analysis, can handle longer length (at least up to 15 aa) without loss of performance (suppl. figure 1).

A list containing 63,802 peptides was generated from random sampling 13-mer peptides originating from an in-house database of human pathogens and synthesized in triplicate on a microscope slide with a randomly distributed localization. The microscope

slide was incubated with HLA-DRA1*01:01 / HLA-DRB1*03:01 and stained with L243 /

Cy3-goat anti-mouse IgG before obtaining a laser scanning image at 1μm resolution (figure

2). The individual peptide fields (20x20 μm) are clearly distinct in the zoomed section (figure

2, insert) and present themselves with varying intensities reflecting the amounts of peptide-

HLA-DR complexes present on each field.

Each individual peptide field was quantified with a proprietary software (PepArray,

Schafer-N, Denmark), and the mean signal and the coefficient of variance (cv) based on

triplicate values was calculated for each peptide. For both HLA-DRB1*01:01 and HLA-

DRB1*03:01, we found a high concordance between triplicate signal values generally

showing cv<0.25 for peptides with mean signal values > 50% of the max signal. Peptides

with mean signal in the lower 10% of max value showed a marked increase in cv suggesting

that these lower signals approached the noise level of detection (figure 3A). Inclusion criteria

for downstream ANN training was chosen at cv < 0.5, which almost exclusively filtered away

weak and non-binding signals. The mean signal of the remaining (cv<0.5) peptides were, for

both HLA-DR allotypes, displaying a log-normal distribution (figure 3B); for ANN training

signal values were log-transformed to bring the signal in the range [0-1] and reduce the

distribution skewness, figure 3C.

By comparing the log-transformed signals of HLA-DRB1*01:01 against HLA-

DRB1*03:01 peptide by peptide we found, as expected, the two molecules to bind to very

different peptides (figure 4, Left), confirming that a particular HLA-DR molecule has

preference towards different subset of peptides. This is further confirmed when considering

only the subset of data with log-transformed signal > 0.5 (figure 4, left red square) for both

molecules. Here the Spearman rank correlation was SRC = 0.11 suggesting a very limited

specificity overlap between the two molecules for strong binding peptides. The

reproducibility of the HLA-II/peptide microarray binding assay was examined by repeating

the peptide array synthesis (i.e. the peptide design and layout was identical to the first peptide

microarray) and repeating the binding of DRA/HLA-DRB1*01:01 and DRA/HLA-

DRB1*03:01. Plotting the log-transformed signals from duplicate binding experiments

against each other by HLA, we found a Pearson correlation coefficient (PCC = 0.92) for both

HLA-DRB1*01:01, HLA-DRB1*03:01(figure 4, middle and right) suggesting that the

binding of each HLA-DR molecule was highly reproducible. To assess whether the binding

data possessed peptide sequence-based information of a quality sufficient to support the

development of ANN predictors, we submitted the data-sets from HLA-DRB1*01:01 and

HLA-DRB1*03:01 to the publicly available NNAlign server with the network architecture

parameters specified in table 1. As a reference and comparison to the peptide microarray

data, we used the original data sets (originating from IEDB binding data) used to train the

NetMHCII prediction algorithms (available at

https://services.healthtech.dtu.dk/service.php?NetMHCII-2.3) and subjected them to

NNAlign with the exact same network architecture as the peptide array data sets (table 1).

For both HLA-DRB1*01:01 and HLA-DRB1*03:01, ANN training with the relevant peptide

microarray data-sets returned prediction models with a very high internal correlation (PCC >

0.95) between predicted and observed data (figure 5). The results, summarized in table 2,

suggests that the peptide microarray data-set of the respective HLA-DR molecules contains a

distinct and recognizable pattern that can be extracted by the NNAlign algorithm.

20   The sequence logo representations of the final NNAlign network ensembles trained

on peptide microarray data sets revealed motifs with distinct anchor residues in positions P1,

P4, P6 and P9 for both HLA-DRB1*01:01 and HLA-DRB1*03:01 (figure 6). Although P1 in

HLA-DRB1*01:01 did not appear to be as prominent an anchor position (reflected by a

relatively low bit score) as normally observed for P1 in many HLA-II motifs, we found the

motifs and anchor positions to be comparable to the commonly accepted motifs of the

respective molecules. A head to head comparison of the final DRB1*01:01 ANN network

ensembles trained on peptide microarray versus network ensembles trained on IEDB data,

showed overall that the peptide microarray generated motif appeared more blurred with less

distinct anchor positions (P1 in particular). In contrast, the motif for HLA-DRB1*03:01 as

derived from the microarray data appeared sharper and with higher information context

compared to the motif derived from the IEDB data.

To benchmark the prediction power of the final network ensembles, we evaluated the

prediction of HLA-DRB1*01:01 and HLA-DRB1*03:01 epitopes extracted from IEDB with

selection criteria outlined in table 3 (note that epitopes were curated for cases where the

epitope sequence not being present in the corresponding source antigen). To benchmark the

peptide microarray driven models which operates in a 13-mer peptide space, each source

antigen was *in silico* digested into overlapping peptides with the length of the epitope; within

each of these peptides, the highest predicted score of the underlying overlapping 13-mers was

assigned to the peptide. Similarly, for each epitope was the highest predicted 13-mer within

each epitope assigned to the epitope. The IEDB data set driven models were trained on

peptides with varying lengths, hence predictions were made on the epitope sequence, and

overlapping peptides from the source antigen with same lengths of the epitope. By comparing

the prediction of each epitope against the predictions of the overlapping source antigen

peptides, an AUC was calculated for each epitope; AUC values of each epitope and models

are shown in figure 7. The overall performance (mean AUC values) of each model,

summarized in table 2, shows that the prediction power of IEDB data driven networks is

higher ($p<0.05$), AUC=0.821 as compared to AUC=0.722 of peptide microarray driven

networks, with respect to predicting HLA-DRB1*01:01 epitopes. In contrast. was the power

to predict HLA-DRB1*03:01 epitopes higher ($p<0.05$) by the peptide microarray driven

networks AUC = 0.817 compared to IEDB driven networks predicting with an AUC = 0.753.

As a further validation, we evaluated the prediction of peptides eluted off HLA-DRB1*01:01

or HLA-DRB1*03:01, and sequenced by mass spectrometry (22) and as described here

(eluted peptide sequences provided in Suppl. Table 1). Peptides (5515) of different lengths

eluted off HLA-DRB1*01:01 were in silico digested to length 13 amino acids and subjected

to prediction, the highest predicted 13-mer within each eluted peptide were used in the

evaluation against 5000 randomly generated 13-mer peptides. An identical strategy was

applied for the (5713) eluted HLA-DRB1*03:01 peptides evaluated against the same 5000

randomly generated peptides. Density plots (figure 8) of the predicted scores confirmed that

all four network ensembles are assigning higher scores to peptides eluted off relevant MHC-

II allotypes than to random peptides, resulting in a clear skewness of the score distribution.

The AUC values, summarized in table 2, of the evaluation of eluted peptides against random

peptides were comparable to AUC values obtained for the evaluation of epitopes. Using a

student's t-test to compare the performances of the peptide microarray driven models against

the IEDB driven models, we found no statistical difference (p=0.17, p=0.31, HLA-

DRB1*01:01 and HLA-B1*03:01, respectively) of the combined mean AUC of epitopes and

eluted peptides. A direct comparison of the prediction scores of eluted peptides between the

peptide microarray driven models and IEDB models (fig 9) reveals that, the peptide

microarray and IEDB model performances are comparable, with Spearman rank correlations

(HLA-DRB1*01:01) SRC=0.66 and (HLA-DRB1*03:01) SRC=0.71. There is a tendency

towards agreement between the models in particular for peptides with high prediction scores.

It is possible that the nature of the binding data, which is obtained from two different assays,

chip binding and traditional affinity data (IEDB), contributes to the differences. For all data

sets, the peptide with the strongest measured binding is transformed to a value of 1 in the

training sets. Hence, the differences in distribution of the transformed data originating from

the different data sets may in part explain some of the differences observed for prediction

scores < 0.8; which in any case translates into weak to non-binders and thus less relevant.

Collectively, the high internal performance of the peptide microarray driven models

and a prediction power comparable to prediction models based on traditional binding data

(IEDB), suggests that high-density peptide microarrays can be used to generate relevant

peptide-HLA-II binding data. As a final examination of the prediction models, we calculated

the distance between the models one-by-one and their individual distances to NetMHC-2.3,

summarized in table 4. Briefly, the distance is calculated as $1-SRC^2$, where SRC is the

Spearman rank coefficient found by comparing prediction scores of 100,000 random peptides

from two prediction models. We found the distances of network ensembles to be closer

within allotypes (HLA-DRB1*01:01 distance = 0.31 and HLA-DRB12*03:01 distance =

0.43) than between allotypes (0.49 < distance < 0.85) underscoring that the training data

contains allotype specific binding data.

In conclusion, the binding data obtained from HLA-II-peptide microarray assays

produced comparable HLA-II peptide prediction models compared to models trained on

peptide-HLA-II affinity data available at IEDB, and as such represents an attractive way

forward to generate large amounts of peptide-MHC-II binding data and to improve existing

prediction models.

Discussion

CD4+ T cells arguably perform the most important function of the immune system; by controlling and coordinating the responses of most immune cells they essentially orchestrate the overall specificity and reactivity of the immune system. To this end, they survey peptide-MHC class II complexes and determine whether these peptides are of self or non-self-origin. This essential process of peptide sampling and display is diversified immensely by the polymorphism of the MHC system, which assures that no two individuals will perform self-non-self-discrimination in an identical manner thereby avoiding the evolution of pathogen variants that can escape the immune systems of the entire species. An in-depth understanding of which peptides bind to MHC-II and how this interaction is affected by MHC polymorphism is of paramount importance for our ability to understand and manipulate the immune system. Many autoimmune diseases (e.g. type I diabetes, multiple sclerosis, rheumatoid arthritis, narcolepsy and many more) are tightly associated with specific MHC-II allotypes, which obviously make these allotypes interesting in their own right. More recently, the field of personalized immunotherapy - emerging as promising cancer treatments – increasingly rely on a better understanding and prediction of immune specificities in a much broader representative coverage of the "MHC space" underscoring the relevance of pan-specific predictors.

A need for experimental coverage became apparent when pan-specific predictors were applied to MHC allotypes lacking experimental data and it could be shown that these pan-predictors are more accurate when they have been trained on experimental data from a closely related allotype rather than a more distant allotype (23). The development of these bioinformatics methods requires large-bodies of data that are representative of peptide-MHC-II interactions. In other words, it requires access to large panels of natural and/or synthetic peptides representing peptide-MHC-II binding events. By combining recombinant MHC-II

molecules with high-density peptide array technology, it is be possible to generate the large

bodies of binding data representing many different allotypes, and do so at significant cost

reductions compared to generating the same amount of data using more traditional binding

experiments.

Here, we have demonstrated that MHC-II can interact with *in situ* synthesized

peptides in a high-density array format; that the peptide MHC-II interaction is specific; that

there is a systematic binding pattern which is interpretable by ANNs, here exemplified by

NNAlign training (24, 25); furthermore the resulting prediction models are able to predict

peptide MHC-II binding at a level comparable to that of models trained on traditional binding

data deposited at the IEDB which have been used to develop NetMHCII models (25). We

also found the binding motifs revealed by the models trained on peptide microarray data

comparable with the motifs obtained by training on IEDB binding data.

The capacity of this high-density peptide microarray technology should enable large-

scale analyses of any MHC-II allotype of interest even including all post-translational

modifications that are available for solid-phase peptide synthesis (SPPS). Without the

limitations inherent to conventional SPPS, peptides could be selected entirely based on the

scientific and/or practical merits of the question at hand. A completely random selection of

peptides, as applied here, would ensure a truly unbiased approach to define MHC-II

specificity. Alternatively, one could randomly extract peptides from the proteomes of

organism(s) of interest (microbiomes for infectious diseases, the human proteome for

autoimmune disease, onco-proteomes for cancer etc.). Other "peptide-intensive" strategies

could also be pursued e.g. using an initial random screen to generate a primary predictor and

use that to enrich for binders in a secondary experiment. In contrast, the current cost of

obtaining peptides for such mapping projects tend to be prohibitive and may lead to the use

of existing prediction tools to downsize sampling with the inherent risk of introducing bias

leading to an incomplete representation of the relevant sequence space.

The prediction models developed using peptide microarray binding data are at

performance levels comparable to prediction models trained on traditional binding (affinity)

data. Thus, peptide microarrays could be used to develop large bodies of peptide-MHC-II

binding data and/or to complement other methods capable of generating large amounts of

binding data (e.g peptide elution and mass spectrometry) (2, 23). This could even include

non-standard amino acids representing post-translational modifications that otherwise are

scarcer and/or more difficult to obtain. The massive amounts of representative peptide-MHC-

II data that can be generated should allow an exhaustive scanning of both the peptide and

MHC spaces. This should support the generation of improved pan-MHC-II predictors, which

should allow peptide-MHC-II interactions to be evaluated *in silico* cheaper, faster and at an

even higher capacity than any experimental approach, even one enabled by the high-density

peptide microarray technology, could do. One area may always benefit from an experimental

approach: the binding of epitopes derived from cancer neoepitopes identified by genomics or

proteomics sequencing of tumor cells vs normal cells. Here, all mutations and corresponding

wildtype sequences could potentially be synthesized in multiple length variants and tested

experimentally against all the MHC-II allotypes of a given patient.

One current disadvantage of the present peptide microarray technology is the inability

– at least with current technologies – to validate the identity and quality of the peptides. Thus,

some of the experimental peptide-MHC-II data points might be erroneous. We surmise that

as long as such errors are the exception, rather than the rule, then the predictors should ignore

these experimental errors. Notwithstanding, it would be a major advance if the quality of the

individual peptides on a microarray could be validated through independent physical means

e.g. by mass spectrometry.

Other recent technologies have emerged as possible ways of generating large-scale

peptide-MHC-II data. One approach is phage expression of peptide libraries followed by

MHC-II selection and sequencing (26) . This technology does not offer the same degree of

control of the peptides expressed; it requires DNA sequencing to identify the peptides

involved rather than the simple "identification by look-up" used by the peptide microarray

technology; it does not readily allow the incorporation of post-translational modifications;

nor does it allow the identification of non-binders which are important for ANN training.

Another recent approach, "immunopeptidomics", involves sequencing of natural peptides

eluted of MHC-II by liquid chromatography followed by mass spectrometry (27). Sequencing

natural peptides has the huge qualitative advantage that it includes events of antigen

processing and includes post-translational modification. Otherwise, it shares some of the

same disadvantage of the phage display approach: lack of control of which peptides and post-

translational modification are interrogated; and lack of non-binders. Ideally, one should

include data obtained from both synthetic and natural peptide, and generate immune-

bioinformatics predictors incorporating both kinds of input.

In conclusion, we have demonstrated that high-density peptide microarrays can be

used to generate very large numbers of discrete peptide-MHC-II interaction data; something

that represents a major advance in the analysis of peptide-MHC-II interactions, and should

become instrumental in developing improved bioinformatics methods representing these

important interactions.

Methods

Production of recombinant HLA-DR molecules HLA-DRA1*01:01, -DRB1*01:01,

DRB1*03:01

4   HLA-DR molecules were produced and purified according to (20). Briefly, this

5   entailed separate *E. coli* expression of each recombinant HLA-DR chain followed by a

6   multiple liquid chromatography purification steps. The purified HLA-DR molecules were

7   stored in 8M Urea, 25 mM TRIS, 15 mM NaCl at -80°C.

9   *High-density peptide arrays*

Nexterion-E microscope slides (Schott, Jena, Germany) were amino-functionalized

with a 2% w/v linear copolymer of N,N′-dimethylacrylamide (Sigma-Aldrich) and

aminoethyl methacrylate (Sigma-Aldrich) and used as substrate for solid-phase peptide

synthesis. High-density peptide arrays were then synthesized on the surface of the amino-

functionalized microscope glass slides using a principle of maskless photolithographic

synthesis (17, 28) combined with standard Fmoc peptide synthesis modified with the

photolabile NPPOC (2-(2-nitrophenyl)propyl oxycarbonyl). A detailed description of the

peptide synthesis has been described elsewhere (13).

HD peptide array design

The array designs were all made with a proprietary software (PepArray, Schafer-N,

Denmark) by importing peptide sequences and randomly distributing the sequences across 12

virtual sectors. A design to analyze the effect of peptide length on MHC-II binding ~2300 15-

mer peptides with random sequences were generated *in silico* and subsequently chopped into

overlapping 8-14 mers and randomly distributed across the peptide array.

1    For the generation of peptide MHC-II binding data, 500k 13-mer peptides were

2  generated from a list of pathogen proteins from which 72,000 peptide sequences were

3  randomly sampled and distributed across the peptide array in triplicates.

5    *Binding of HLA-class II molecules to peptide microarray:*

6    The peptide arrays synthesised on microscope glass slides were hydrated in

7  Lockmailer microscope jars containing 15 ml PBS prior to incubation with HLA-DR

8  molecules.

9    HLA-DR molecules (DRA1*01:01, DRB1*01:01, DRB1*03:01, immunAware,

10 Denmark) dissolved in storage buffer (8M Urea, 25 mM Tris pH 8, 25 mM NaCl) were

11 diluted in 12 ml re-folding buffer (PBS pH 7.4 suppl. with 0.01% Lutrol F68, Glycerol 20%

12 (vol/vol), TPCK, TLCK, PMSF, TCEP) to a final concentration of 500 nM HLA-DRA and

13 HLA-DRB and transferred to the incubation jar containing the hydrated peptide array and

14 allowed to re-fold at 18°C for 48 hours. Following incubation, the incubation jars were

15 drained and the peptide arrays washed 5x in PBS-T (PBS pH 7.4, 1% Tween-20) followed by

16 incubation with 1 µg/ml of monoclonal mouse anti-HLA-DR antibody (clone #L243) in PBS-

17 T for 2 hours. The peptide arrays were washed 5 times in 15 ml PBS-T before a final

18 incubation with 1 µg/ml Cy3-conjugated goat anti-mouse IgG (Bethyl Lab., TX) in PBS-T. A

19 final wash with 5x PBS-T was conducted before transferring the peptide array to PBS for 20-

20 30 min before drying the microscope slide in a spin centrifuge dryer.

22    *Data acquisition*

23    The peptide arrays were scanned in a microscope slides laser scanner (INNOSCAN

24 900, Innopsys, France) at 534 nm, resolution 1µm and stored as TIFF-format images. Prior to

25 qualification of the image scans, each image was cropped to include only the peptide array

area surrounded by a thin border, subsequently, the cropped images were rescaled to (10000

x 6000 pixels) and saved in PNG-format.

Quantification of signals (proprietary software, Schafer-N)

The processed images were quantified with a proprietary software (PepArray,

Schafer-N, Denmark) by positioning a virtual grid corresponding to the peptide fields on top

of the scanned images and quantifying each peptide field. The quantified signals (8-bit) were

stored in a text-file format containing corresponding peptide sequence information, peptide

field id, quantified signal, row, column and (virtual) sector information. The quantified data

were prepared for ANN (NNAlingn) training by calculating the mean value SD and CV

(based on triplicate measurements). Inclusion criteria for ANN training set were set at a

threshold of cv < 0.5. The NNAlign server (2.1)

https://services.healthtech.dtu.dk/service.php?NNAlign-2.1 accepts columns of a text strings

and corresponding numerical values [0-1] with a limit of 50,000 inputs, hence the data-sets

were reduced to 50,000 by selecting, based on signal strength, the top 2000 peptides and

random sampling of the remaining peptides.

Data transformation

The data were transformed from the 8-bit format [0-255] to [0-1] using a log-

transformation optimized by a BoxCox algorithm written in R using the EnvStats package

(29)

ANN Training

Log-transformed data with corresponding peptide sequences (one letter code) were

uploaded to the NNAling 2.1 server and trained with the parameters indicated in Table 2.

ANN model evaluation

Peptide sequences used to evaluate the ANN models were obtained by selecting IEDB

epitopes restricted to HLA-DRB1*01:01 or HLA-DRB1*03:01 and selecting only peptide

sequences with a positive multimer/tetramer assay (see list of filters applied in Table 3

Evaluation data). The remaining epitopes were further filtered for inconsistencies between

the peptides sequence and reported source antigen and subsequent *in silico* digested into 13-

per peptide sequences. The source antigen for each epitope were also retrieved based on the

Genbank id and *in silico* chopped into peptides with the length of the relevant epitope in

question; each of these peptides were further digested into 13-mer peptides where the highest

predicted score of each derived overlapping 13-mer were assigned to the epitope or source

antigen peptide. The applied filters and number of epitopes and antigens are summarized in

Table 3.

Isolation of HLA DR-bound peptides

Cell pellets from International Histocompatibility Workshop B-LCLs 9022 (COX:

DRA*01:02-DRB1*03:01:01) and 9087 (STEINLEN: HLA DRA*01:02-DRB1*03:01:01)

(30) were lysed in a mild detergent. Following lysis, peptide-HLA complexes were affinity

purified by anti-HLA-DR antibody (LB3.1). Affinity purified HLA molecules and their

peptide cargo were separated using reversed-phase chromatography and peptides were

subsequently analyzed using mass spectrometry as described (31). In brief, cells were

expanded in RPMI-10% FCS and pellets of 109 cells snap frozen in liquid nitrogen. Cells

were ground under cryogenic conditions and resuspended in lysis buffer (0.5% IGEPAL, 50

mM Tris pH 8, 150 mM NaCl and protease inhibitors) and cleared lysates passed over a

protein A pre-column followed by an affinity column cross-linked with a monoclonal

antibody specific for HLA-DR (LB3.1). Peptide-MHC complexes were eluted from the

column by acidification with 10% acetic acid. Peptides were isolated using reversed-phase

HPLC (Chromolith C18 Speed Rod, Merck) on an Akta Ettan HPLC system (GE

HealthCare). Fractions were concentrated and run on an AB SCIEX 5600+ TripleTOF high

resolution mass spectrometer. Acquired data was searched against the human proteome

(Uniprot/Swissprot v2012_7) using ProteinPilot™ (v5; SCIEX) using following parameters:

database: Human proteins from UniProt/SwissProt v2016_12, no cysteine alkylation, no

enzyme digestion (considers all peptide bond cleavages), instrument-specific settings for

TripleTOF 5600+ (MS tolerance 0.05 Da, MS/MS tolerance 0.1 Da, charge state +2 to +5),

biological modification probabilistic features on, thorough ID algorithm, detected protein

threshold 0.05. The resulting peptide identities were subject to strict bioinformatic criteria

including the use of a decoy database to calculate the false discovery rate (FDR). A 5% FDR

cut-off was applied and the filtered dataset was further analyzed manually to exclude

redundant peptides and known contaminants.

Figure legends

Figure 1.

Peptide microarray incubated with HLA-DRA1*01:01 / HLA-DRB1*03:01 stained

with monoclonal anti-HLA-DR (L243) and Cy3-conjugated goat anti-mouse in combinations

indicated in the figure heading. A fluorescent signal was only detectable in presence of HLA-

DRA, HLA-DRB, mouse anti HLA-DR and Cy3-goat anti-mouse suggesting that the binding

assay reveals HLA-DR molecules bound to specific peptides.

Figure 2.

A full view of HD peptide array with 217,000 individual peptides (Area 20x11 mm)

divided in 12 virtual sectors. Zoomed inserts of sector 6 and a further zoom of a subsection of

sector 6 with individual peptide fields visible. The size of each peptide field is 20x20 μm

with a 10 μm pitch scanned with a resolution of 1μm/pixel.

Figure 3.

A) Raw data, Mean Signal versus coefficient of variation (cv) calculated from

triplicate signal values. B) Signal distribution of the calculated Mean Signal. C) Signal

distribution after Log transformation of the mean signal calculated after optimization with a

BoxCox transformation (R package EnvStats Version 2.3.1).

Figure 4.

Left: Log transformed signals of DRB1*01:01 plotted against DRB1*03:01 by

peptide sequence show a weak correlation (PCC = 0.47). Considering peptides with a

predicted score>0.5 returns a SRC=0.11, suggesting HLA-DR specificity. Middle and Right:

Log transformed signals obtained by replica experiments of DRB1*03:01 and DRB1*01:01,

respectively, correlates well (PCC = 0.92) conferring an acceptable reproducibility.

Figure 5.

Scatter plots of predicted versus observe values (log transformed signals) of

NNAlign-2.1 models trained on ~50k peptide sequences obtained from peptide microarrays

with SPARSE encoding. IEDB train sets (downloaded as pairs of peptides sequences and log

transformed binding data from https://services.healthtech.dtu.dk/service.php?NetMHCII-2.3)

encoded with SPARSE. The internal model performances are listed in table 2. BLOSUM

encoding rendered network ensembles with comparable performances (data not shown). The

neural network architecture is disseminated in table 1.

Figure 6.

LOGO representation of the final NNAlign network ensemble based one the peptide

microarray data set and IEDB data sets trained with the neural network architecture listed in

table 1.

Figure 7.

AUC values of HLA-DRB1*01:01 (light grey) and HLA-DRB1*03:01 (white)

epitopes based on predictions by network ensembles trained on peptide micro array data (left)

and IEDB binding data (right). Neural network architecture is listed in table 1 and the mean

AUC values are listed in table 2. In general, all four models assign high prediction scores to

peptide sequences which can be identified as HLA-II tetramer validated epitopes as expected

if the input data reflects the peptide HLA-DR interaction. The prediction performances

reported as AUC values are comparable between the models with respect to allotype. This

indicates that the data obtained by peptide microarray binding studies contain specific

peptide-HLA-DR information comparable to traditional binding data and suitable to ANN

training.

Figure 8.

Predicted scores of peptides eluted off HLA-DRB1*01:01 and HLA-DRB1*03:01

and compared to random peptides. Left, the peptide microarray model prediction of eluted

peptides (grey density) are clearly skewed towards high scores while random peptides (white

density) primarily are skewed towards low scores for both HLA-DR allotypes. Right,

predicted scores by the models trained in IEDB data presents a similar pattern of eluted

peptides (grey density) and random peptides (white density). The model performances are

summarized in table 2 showing that HLA-DRB1*03:01 models performed at par while the

HLA-DRB1*01:01 model based on IEDB data sets had a better prediction power compared

to the model trained on peptide microarray data.

Figure 9.

Scatter plots of eluted peptide scores (Left: HLA-DRB1*01:01, Right: HLA-

DRB1*03:01) predicted by peptide microarray models versus IEDB models. The Spearman

rank correlation of the respective data-set are inserted.

Table 1.

Summary of NNAlign architecture and encoding applied to all four models. Data sets

were reduced to 50,000 peptide sequences according to the maximum accepted number of

inputs by the server.

Table 2.

Summary of the final network ensemble for all models listing the number of data

points, prediction performance reported as Pearson correlation coefficient (PCC) and Root

mean square error (RMSE). The mean AUC values are Area under the curve reported by a

ROC analysis of predicted scores of IEDB epitopes versus epitope source antigens.

Table 3.

Evaluation data sets (epitopes) extracted from IEDB after selecting positive assays

(tetramer /multimer staining).

Table 4.

Table of calculated distances between the models trained on peptide microarray data,

IEDB binding data and NetMHC-2.3. The distance is calculated as $1-R^2$, where R is the

Spearman rank correlation calculated on the prediction scores of 100,000 random peptides.

Acknowledgements

Funded by European commission (HIPAD project no. 278832), the Independent

Research Fund Denmark award DFF – 6110-00644 and the Danish MS Society award

A31444)

Mass spec and DRB1*03:01 elution work was supported by grants and a Principal

Research Fellowship from the National Health and Medical Research Council of Australia to

AWP (NHMRC) (1165490, 1137739). The authors acknowledge the provision of

instrumentation, training and technical support by the Monash Biomedical Proteomics

Facility. Computational resources were supported by the R@CMon/Monash Node of

the NeCTAR Research Cloud, an initiative of the Australian Government's Super Science

Scheme and the Education Investment Fund.

Conflicts of interests.

C. S-N. is affiliated with Schafer-N, provider of HD peptide arrays

T.O. and S.B. (immunAware ApS, commercial provider of HLA monomers and

tetramers)

Bibliography

1.   Reche PA, Reinherz EL. Sequence variability analysis of human class I and class II

MHC molecules: functional and structural correlates of amino acid polymorphisms. J Mol

Biol. 2003;331(3):623-41.

2.   Garde C, Ramarathinam SH, Jappe EC, Nielsen M, Kringelum JV, Trolle T, et al.

Improved peptide-MHC class II interaction prediction through integration of eluted ligand

and peptide affinity data. Immunogenetics. 2019;71(7):445-54.

3.   Lin HH, Zhang GL, Tongchusak S, Reinherz EL, Brusic V. Evaluation of MHC-II

peptide binding prediction servers: applications for vaccine research. BMC Bioinformatics.

2008;9 Suppl 12:S22.

4.   Sahin U, Tureci O. Personalized vaccines for cancer immunotherapy. Science.

2018;359(6382):1355-60.

5.   The problem with neoantigen prediction. Nat Biotechnol. 2017;35(2):97.

6.   Kreiter S, Vormehr M, van de Roemer N, Diken M, Lower M, Diekmann J, et al.

Mutant MHC class II epitopes drive therapeutic immune responses to cancer. Nature.

2015;520(7549):692-6.

7.   Tran E, Turcotte S, Gros A, Robbins PF, Lu YC, Dudley ME, et al. Cancer

immunotherapy based on mutation-specific CD4+ T cells in a patient with epithelial cancer.

Science. 2014;344(6184):641-5.

8.   Abelin JG, Harjanto D, Malloy M, Suri P, Colson T, Goulding SP, et al. Defining

HLA-II Ligand Processing and Binding Rules with Mass Spectrometry Enhances Cancer

Epitope Prediction. Immunity. 2019;51(4):766-79 e17.

9.   Buus S. Description and prediction of peptide-MHC binding: the 'human MHC

project'. Curr Opin Immunol. 1999;11(2):209-13.

10.   Buus S, Lauemoller SL, Worning P, Kesmir C, Frimurer T, Corbet S, et al. Sensitive

quantitative predictions of peptide-MHC binding by a 'Query by Committee' artificial neural

network approach. Tissue Antigens. 2003;62(5):378-84.

11.   Nielsen M, Lundegaard C, Blicher T, Lamberth K, Harndahl M, Justesen S, et al.

NetMHCpan, a method for quantitative predictions of peptide binding to any HLA-A and -B

locus protein of known sequence. PLoS One. 2007;2(8):e796.

12.   Nielsen M, Lundegaard C, Lund O. Prediction of MHC class II binding affinity using

SMM-align, a novel stabilization matrix alignment method. BMC Bioinformatics.

2007;8:238.

13.   Hansen LB, Buus S, Schafer-Nielsen C. Identification and mapping of linear antibody

epitopes in human serum albumin using high-density Peptide arrays. PLoS One.

2013;8(7):e68902.

14.   Zandian A, Forsstrom B, Haggmark-Manberg A, Schwenk JM, Uhlen M, Nilsson P,

et al. Whole-Proteome Peptide Microarrays for Profiling Autoantibody Repertoires within

Multiple Sclerosis and Narcolepsy. J Proteome Res. 2017;16(3):1300-14.

15.   Hecker M, Fitzner B, Wendt M, Lorenz P, Flechtner K, Steinbeck F, et al. High-

Density Peptide Microarray Analysis of IgG Autoantibody Reactivities in Serum and

Cerebrospinal Fluid of Multiple Sclerosis Patients. Mol Cell Proteomics. 2016;15(4):1360-

80.

16.   Hecker M, Lorenz P, Steinbeck F, Hong L, Riemekasten G, Li Y, et al.

Computational analysis of high-density peptide microarray data with application from

systemic sclerosis to multiple sclerosis. Autoimmun Rev. 2012;11(3):180-90.

17.   Buus S, Rockberg J, Forsstrom B, Nilsson P, Uhlen M, Schafer-Nielsen C. High-

resolution mapping of linear antibody epitopes using ultrahigh-density peptide microarrays.

Mol Cell Proteomics. 2012;11(12):1790-800.

18.   Andreatta M, Schafer-Nielsen C, Lund O, Buus S, Nielsen M. NNAlign: a web-based

prediction method allowing non-expert end-user discovery of sequence motifs in quantitative

peptide data. PLoS One. 2011;6(11):e26781.

19.   Vita R, Mahajan S, Overton JA, Dhanda SK, Martini S, Cantrell JR, et al. The

Immune Epitope Database (IEDB): 2018 update. Nucleic Acids Res. 2019;47(D1):D339-

D43.

20.   Justesen S, Harndahl M, Lamberth K, Nielsen LL, Buus S. Functional recombinant

MHC class II molecules and high-throughput peptide-binding assays. Immunome Res.

2009;5:2.

21.   Moro M, Cecconi V, Martinoli C, Dallegno E, Giabbai B, Degano M, et al.

Generation of functional HLA-DR*1101 tetramers receptive for loading with pathogen- or

tumour-derived synthetic peptides. BMC Immunol. 2005;6:24.

22.   Ooi JD, Petersen J, Tan YH, Huynh M, Willett ZJ, Ramarathinam SH, et al.

Dominant protection from HLA-linked autoimmunity by antigen-specific regulatory T cells.

Nature. 2017;545(7653):243-7.

23.   Racle J, Michaux J, Rockinger GA, Arnaud M, Bobisse S, Chong C, et al. Robust

prediction of HLA class II epitopes by deep motif deconvolution of immunopeptidomes. Nat

Biotechnol. 2019;37(11):1283-6.

24.   Nielsen M, Andreatta M. NNAlign: a platform to construct and evaluate artificial

neural network models of receptor-ligand interactions. Nucleic Acids Res.

2017;45(W1):W344-W9.

25.   Nielsen M, Lund O. NN-align. An artificial neural network-based alignment

algorithm for MHC class II peptide binding prediction. BMC Bioinformatics. 2009;10:296.

26.   Somasundaram R, Satyamoorthy K, Caputo L, Yssel H, Herlyn D. Detection of HLA

class II-dependent T helper antigen using antigen phage display. Clin Exp Immunol.

2004;135(2):247-52.

27.   Dudek NL, Croft NP, Schittenhelm RB, Ramarathinam SH, Purcell AW. A Systems

Approach to Understand Antigen Presentation and the Immune Response. Methods Mol Biol.

2016;1394:189-209.

28.   Singh-Gasson S, Green RD, Yue Y, Nelson C, Blattner F, Sussman MR, et al.

Maskless fabrication of light-directed oligonucleotide microarrays using a digital micromirror

array. Nat Biotechnol. 1999;17(10):974-8.

29.   Millard SP. EnvStats : an R package for environmental statistics. 2013.

30.   Robinson J, Barker DJ, Georgiou X, Cooper MA, Flicek P, Marsh SGE. IPD-

IMGT/HLA Database. Nucleic Acids Res. 2020;48(D1):D948-D55.

31.   Purcell AW, Ramarathinam SH, Ternette N. Mass spectrometry-based identification

of MHC-bound peptides for immunopeptidomics. Nat Protoc. 2019;14(6):1687-707.

Figure 1

DRA / DRB	DRA / DRB	DRA / -	- / DRB
L243	-	L243	L243
Goat anti-mouse IgG-Cy3			

Peptide stained with Primary and/or secondary antibody after incubation with MHC class II (DRA/DRB)

Figure 2

Figure 3

Figure 4

Specificity

Spearman = 0. 48

Replica experiments

PCC = 0. 92   PCC = 0. 92

Figure 5

Peptide micro array train set

IEDB train set

DRB*1*01:01

DRB*1*03:01

DRB*1*01:01

DRB*1*03:01

Figure 6

Peptide micro array train sets

IEDB train sets

DRB1*01:01

DRB1*03:01

DRB1*01:01

DRB1*03:01

Figure 7

Figure 8

Peptide micro array train set

DRB*1*01:01

AUC=0.832

density

0.00 0.25 0.50 0.75
Prediction

DRB*1*03:01

AUC=0.835

density

0.00 0.25 0.50 0.75
Prediction

IEDB train set

DRB*1*01:01

AUC=0.923

density

0.00 0.25 0.50 0.75 1.00
Prediction

DRB*1*03:01

AUC=0.845

density

0.0 0.2 0.4 0.6 0.8
Prediction

Figure 9

Tables

Table 1 - ANN summary.

NEURAL NETWORK ARCHITECTURE
· Motif length: 9
· Flanking region (PFR) size: 3
· PFR length encoding type: 0
· PFR encoding: SPARSE OR BLOSUM
· Number of hidden neurons: 2,10,20
· Burn-in period without insertions or deletions: 10
· Impose amino acid preference during burn-in: ILVMFYW
· Amino acid numerical encoding: SPARSE OR BLOSUM
· Number of training cycles: 500
· Number of random seeds: 10
• Number of networks in final ensemble: 150

CROSS VALIDATION
· Folds for cross-validation : 5
· Method to create subsets: Common motif with maximum overlap of 9 amino acids
· Cross-validation setup: Simple
· Stop training on best test-set performance: No

Table 2 - ANN output and Performance

Allotype	Peptide micro array data					IEDB data				
		ANN Performance		TMR+ Evaluation	Eluted peptides Evaluation		ANN Performance		TMR+ Evaluation	Eluted Peptides Evaluation
	# data points	PCC	RMSE	AUC	AUC	# data points	PCC	RMSE	AUC	AUC
DRB1*01:01	49,507	0.954	0.065	0.722	0.832	5,166	0.671	0.199	0.821	0.923
DRB1*03:01	49,508	0.952	0.086	0.817	0.835	1,020	0.511	0.204	0.753	0.845

Table 3 - Evaluation data

Source	HLA	Applied filters	# of Epitopes	# of Epitopes curated	# of Source Antigens
IEDB	DRB1*01:01	• Positive Assays Only • Qualitative binding (MMR/TMR) • No B cell Assays • No MHC ligand assays • MHC restriction - ID MRO_0001279 HLA-DRB1*01:01	266	235	80
IEDB	DRB1*03:01	• Positive Assays Only • Qualitative binding (MMR/TMR) • No B cell Assays • No MHC ligand assays • MHC restriction - ID MRO_0001284 HLA-DRB1*03:01	114	105	49

Table 4. Distances between predictions models

		DRB1*01:01		DRB1*03:01	
MODEL		micro array	IEDB	micro array	IEDB
DRB1*01:01	micro array	0.00	0.31	0.49	0.85
	IEDB	-	0.00	0.68	0.68
DRB1*03:01	micro array	-	-	0.00	0.43
	IEDB	-	-	-	0.00

Scanning through different peptide lengths - ANN training (2.0d and 1.4)

Optimizing the peptide length. Peptides of lengths 9-15 were synthesised on a peptide array and incubated with HLA-DRB1*03:01. Data from each peptide length were used to train ANNs and the internal correlation and RMSE output from the networks were used to find the optimal peptide length. NNAlign_2.0d (open) shows little or no response to the peptide length input in contrast to NNAlign_1.4 (solid) which clearly show optimal performance at peptide length = 13 (Pearson to RMSE).