1

Active Vision in Immersive, 360° Real-World Environments

Amanda J. Haskins[1], Jeff Mentch[1,2], Thomas L. Botch[1], Caroline E. Robertson[1]

[1] *Department of Psychological and Brain Sciences, Dartmouth College, Hanover, NH 03755, USA*
[2] *Department of Brain and Cognitive Sciences, Massachusetts Institute of Technology, Cambridge, MA 02139, USA*

Correspondence:

Address: 3 Maynard Street, Moore Hall, Hanover NH 03755
Phone: +1 (603) 646 9129

Abstract

How do we construct a sense of place in a real-world environment? Real-world environments are actively explored via saccades, head turns, and body movements. Yet, little is known about how humans process real-world scene information during active viewing conditions. Here, we exploited recent developments in virtual reality (VR) and in-headset eye-tracking to test the impact of active vs. passive viewing conditions on gaze behavior while participants explored novel, real-world, 360º scenes. In one condition, participants actively explored 360º photospheres from a first-person perspective via self-directed motion (saccades and head turns). In another condition, photospheres were passively displayed to participants while they were head-restricted. We found that, relative to passive viewers, active viewers displayed increased attention to semantically meaningful scene regions, suggesting more exploratory, information-seeking gaze behavior. We also observed signatures of exploratory behavior in eye movements, such as quicker, more entropic fixations during active as compared with passive viewing conditions. These results show that active viewing influences every aspect of gaze behavior, from the way we move our eyes to what we choose to attend to. Moreover, these results offer key benchmark measurements of gaze behavior in 360º, naturalistic environments.

Introduction

Constructing a sense of place in a complex, dynamic environment is an active process. Humans actively sample their sensory environment to build an understanding of their surroundings and gain information relevant to their behavioral goals[1,2]. Yet, much of what we know about how people encode real-world environments comes from paradigms that severely limit participants' active affordances: paradigms in which head-restricted participants view images that are passively displayed on a computer screen. In this context, the participant's behavioral repertoire is limited to eye movements, and the displayed portion of an environment is typically limited to a single field of view. In contrast, everyday visual environments are actively explored. We gain rich information about a place by shifting our eyes, turning our heads, and moving our bodies. This is because real-world scenes are immersive, extending 360º around us and beyond any single field of view. How does scene understanding unfold in immersive, active viewing conditions?

It has long been understood that active viewing conditions impact perceptual processing. Neurons in early stages of the visual system are sensitive to the distinction between self- and world-generated motion under conditions that are carefully matched for equivalent retinal stimulation and attentional engagement[3,4]. Further, active vision is thought to be necessary for typical visual development: even basic visual functions, such as depth perception and contrast sensitivity, suffer when animals are denied self-motion in a visual environment, but are passively exposed to equivalent visual stimuli[5]. Studies in humans also suggest that perceptual systems differentially represent stimuli that are encountered via active vs. passive viewing[1]. For example, an object's spatial location is better recalled when it has been actively reached for rather than passively moved toward[6]. Yet, to date, no studies have explored how active viewing conditions impact the way that humans process complex visual stimuli, such as real-world scenes.

Here, we used a novel experimental design to study real-world scene processing during active and passive viewing conditions. We exploited recent developments in virtual reality (VR) to immerse participants in real-world, 360º scenes. Meanwhile, we monitored participants' gaze using in-headset eye-tracking as they explored these environments, revealing which scene regions they prioritized over others as they built an understanding of the scene. In one condition, participants explored scenes from an active, first-person perspective. In the other condition, scenes were passively displayed to participants while they were head-restricted in a chin rest. In both conditions, diverse, real-world scenes were displayed with the same wide-angle field of view (100 DVA), and participants were exposed to comparable portions of the display over the course of the trial. Thus, this paradigm enabled us to perform quantitative, in-depth comparisons of gaze behavior and attentional deployment as subjects encoded a diverse set of novel, real-world scenes during active vs. passive exploration.

Our central hypothesis was that active viewing conditions would increase a viewer's exploratory, information-seeking behavior in a real-world scene. We tested this by

measuring the degree to which participants' overt attention was dominantly predicted by the spatial distribution of scene features that are semantically informative (e.g., objects, faces, doors)[7,8], as compared with scene regions that are rich in salient visual features (e.g., luminance, contrast, color, and orientation)[9,10]. Previous studies have shown that these information sources compete for participants' top-down vs. bottom-up attention as scene understanding unfolds, although attention is predominantly predicted by the distribution of semantic information[8,11].

In brief, we observed that participants' attention was dominantly guided by semantic meaning as compared low-level visual features in both active and passive conditions, replicating previous findings[8,11]. Crucially, this effect tripled during active viewing, reflecting an increase in signatures of top-down attentional guidance when participants were free to actively view their environment. Moreover, in service of this information-seeking behavior, active viewers made shorter, more exploratory fixations as compared to passive viewers. These results have broad implications for studies of visual cognition, suggesting that active viewing influences every aspect of gaze behavior – from the way we move our eyes to what we choose to attend to – as we construct a sense of place in a real-world environment.

Results

To test whether active viewing conditions modulate attentional guidance in real-world scenes, we designed a novel eye-tracking paradigm to directly compare eye movements while participants viewed immersive, 360° environments in two experimental conditions. During the passive condition, participants' heads were fixed in a chin rest, and the scene panned across the HMD screen (Figure 1A). In the active condition, participants could actively explore the environment via self-directed motion (i.e., saccades, head, and body turns) (Figure 1B). We observed high-quality eye-tracking in the HMD, comparable with that reported in fixed display studies at screen center (accuracy: 0.79 DVA, precision, 0.11 DVA; see Supplemental Figure 1).

Figure 1. Passive viewing condition vs. active viewing condition. On each trial, participants viewed immersive, 360° real-world scenes via a headmounted VR display while gaze position was monitored using an in-headset eye-tracker**. A)** In the passive condition, participants were head-restricted using a chin rest, and scenes panned across the display. **B)** In the active condition, participants explored scenes from a first-person perspective through movement of their eyes, head, and body.

Our central hypothesis was that active viewing conditions would increase exploratory, information-seeking behavior in a real-world scene. To test this hypothesis, we first constructed two models of the visual content in each environment (Figure 2, Methods). First, we computed a traditional "salience map", which reflects the distribution of low-level visual features in a scene (e.g., contrast, color, orientation, etc.)[12]. Prominent low-level visual features in a scene are known to predict a significant portion of gaze behavior[9,13]. However, as attention is drawn on the basis of visual salience, rather than semantically meaningful scene regions, the degree to which such maps predict gaze behavior is not related to information-seeking behavior, thus providing a good baseline model for our hypothesis.

Second, we computed a "meaning map" for each scene, which reflects the distribution of high-level semantic features in an environment (e.g., faces, objects, doors, etc.)[8]. "Meaning maps", a recently proposed "conceptual analogue" of salience maps[8], reflect the spatial distribution of features that are relevant to understanding the semantic content and affordances available to the viewer in a scene. Recent studies have shown that attentional deployment in novel scene images is dominantly predicted by the spatial distribution of scene features that are semantically informative (meaning maps) as compared with low-level features (salience maps) [8,11]. Consistent with cognitive guidance theories of attention[14,15], these studies emphasize the notion that overt attention primarily reflects information-seeking behavior on the part of a viewer.

Figure 2. Comparing salience and meaning maps to gaze behavior. A) Each photosphere was first decomposed into smaller undistorted image tiles. Next, we created two models of the content in each real-world environment. **B)** "Salience maps" were generated by modeling low-level visual features for each tile using the GBVS Toolbox[12]. Each tile was then projected onto a two-dimensional salience map. **C)** "Meaning maps" were generated via online participants who rated the semantic content, or "meaning" of each image tile. Each tile's rating was then projected onto a two-dimensional meaning map. **D)** Group gaze maps were trimmed (vertically) to match the passive condition field of view. **E)** Points are sampled evenly on a sphere and used to account for photosphere distortion in two-dimensional maps. **F)** A linear mixed effects model was used to compare the degree to which each model predicted attentional guidance in our two conditions.

We specifically hypothesized that active viewing conditions would increase exploratory,
information-seeking behavior, and therefore increase the degree to which meaning-maps
predict gaze behavior. One of the few existing observations from eye-tracking in VR is
the tendency for viewers to fixate near the equator[16]; therefore to test our hypothesis, we
first generated a map of the equator to serve as a baseline prediction for 360º viewing
behavior. Then, for each condition, we compared the additional predictive contribution of
each map of environmental content (salience map, meaning map) using a linear mixed-
effects model. Specifically, we included three spatial maps (i.e., salience maps, meaning
maps, and our baseline map of the equator) and viewing condition as fixed effects and
individual scenes as random effects in the model. All results are summarized in Table 1.
141
Overall, we observed that overt attention in real-world scenes primarily reflects
information-seeking behavior in both active and passive conditions, confirming previous
results[8,11]. Both salience and meaning maps significantly predicted participants' overt
attention (salience estimated marginal effect: 0.15 +/- 0.03 STE, CI: [0.09,0.21]; $p < 0.001$;
meaning estimated marginal effect: 0.31 +/- 0.03 STE, CI: [0.25, 0.36]; $p < 0.001$).
However, in both active and passive conditions, meaning was significantly more
predictive of which scene regions participants explored than salience (meaning:salience
interaction: $p < 0.001$; post-hoc corrected t-tests for meaning vs. salience: $p < 0.001$ for
both conditions).
151

Figure 3. Active viewing increases top-down attentional allocation. Estimated marginal effects of salience and meaning maps on predicting overt attention in each condition (active vs. passive). We found that viewing condition (active vs. passive) significantly modulated gaze behavior (salience*meaning*condition: $p < 0.001$). Specifically, active viewers disproportionately directed their attention to meaningful, over salient, scene regions. Individual points represent random item effects (i.e., individual scenes). Error bars represent prediction intervals (+/- 1 STE). *** denotes $p < 0.001$.

Critically, however, this advantage for meaningful scene regions nearly tripled in the
active as compared with the passive condition (salience*meaning*condition: $p < 0.001$;
Figure 3). Post-hoc analyses revealed that the estimated marginal effect of meaning (i.e.,
its predictive contribution, holding other factors constant) was significantly greater for
active as compared with passive viewers (passive: 0.25 +/- 0.03 STE; active: 0.31 +/-
0.03 STE; $p < 0.001$). Conversely, the estimated marginal effect of salience was greater
in the passive condition than in the active condition (passive estimate: 0.20 +/- 0.03 STE;
active estimate: 0.15 +/- 0.03 STE; $p < 0.001$). Taken together, these results show that
active viewing conditions specifically increase attentional allocation to semantically
relevant regions of a visual environment.
162
163 **Table 1: Linear mixed effects model results summary.**
164

	numDF	denDF	*F* value	*p* value
condition	1	6163960	8818.25	< 0.001
meaning	1	6163907	71586.82	< 0.001
salience	1	6163982	19920.19	< 0.001
condition:meaning	1	6163960	21579.7	< 0.001
condition:salience	1	6163960	212.22	< 0.001
meaning:salience	1	6163997	64200.96	< 0.001
condition:equator	2	6163980	485605.49	< 0.001
condition:meaning:salience	1	6163960	71.36	< 0.001

165
Control analyses confirmed that these results could be attributed to active affordances
rather than passive viewers' limitations. First, we restricted our analysis to the fields of
view containing regions ranked in the top 50th percentile for meaning. The
disproportionate advantage for meaning-guided attention in the active condition remained
significant even after eliminating less meaningful scene regions that passive viewers were
required to scan as a result of the panning image presentation (Supplemental Table 1).
Second, due to the consistent image motion, participants in the passive condition were
unable to revisit scene regions; however, we found that participants in the active condition
rarely fixated on a region for longer than it would have been displayed during the passive
condition, even when accounting for return fixations (< 3% of fixations). Thus, as
predicted, in the active condition, when participants were free to move their head and
body, participants' attention was disproportionately directed towards semantically
relevant regions of a visual environment.
179
We further characterized gaze behavior during active viewing using two measures of
spatial distribution that are independent of individual scene content: 1) deviation from
center bias and 2) entropy. Prior to the observation of an equator bias in 360°
environments[16], studies of visual attention using traditional fixed displays also commonly
observed a bias to fixate near the center of an image[17,18]. Although the precise source of
this bias is disputed[13,19,20], deviation from "center bias" has been used to describe the
degree of visual exploration[21]. On average, we found that fixations made in the active

condition had less center bias, or were further from the equator[16], (17.13 degrees +/- 0.54
STE) than fixations made in the passive condition (12.53 degrees +/- 0.23 STE) (t(39) =
9.98, $p < 0.001$; Figure 4). Of course, this result could reflect a systematic, non-central
bias (e.g., active viewers could have routinely looked toward the poles), rather than more
exploratory gaze behavior per se. To address that possibility, we used a second measure,
entropy, a measure of homogeneity (or lack thereof) in the probability distribution of
fixations[22], to test whether any systematic biases occurred in each viewing condition. We
found that gaze behavior in the active condition was more entropic (3.49 +/- 0.07 STE)
than gaze in the passive condition (2.88 +/- 0.02 STE) (t(39) = 8.63, $p < 0.001$). Taken
together, these results further demonstrate that active viewers prioritize rapid exploration
of new scene regions that are rich in semantic content, relative to passive viewers.
198
Finally, we sought to characterize the eye movements participants made in service of this
increase in information-seeking behavior (Figure 4). Participants made shorter (0.27s +/-
0.004 STE) and more frequent (29.45 +/- 0.34 STE) fixations in the active as compared
with the passive condition (size: 0.39s +/- 0.008 STE, t(39) = -14.52, $p < 0.001$; frequency:
26.60 +/- 0.31 STE, t(39) = 7.53, $p < 0.001$. Further, active viewing conditions impacted
the magnitude of gaze shifts (i.e., the combined movement of eyes and head between
two fixations) participants made while exploring their environment. Gaze shifts were
significantly larger in the active condition (29.17 DVA +/- 0.48 STE) as compared with the
passive condition (19.08 DVA +/- 0.23 STE: t(39) = 23.11, $p < 0.001$). Indeed, it was not
uncommon for active viewers to make gaze shifts as large as 150 DVA, exceeding
previous saccade length estimates from fixed display studies (5-10 DVA) by an order of
magnitude[23,24]. Notably, our headmounted display subtended a wider field of view (100
DVA) than typically afforded by fixed display studies. Importantly, this wide display was
matched for both active and passive conditions; thus, the differences we observed cannot
be attributed to the size or content of our stimuli, which is known to impact the size of
gaze shifts[25]. Instead, our results demonstrate that active viewing conditions
fundamentally impact the size of gaze shifts a viewer will routinely choose to make when
exploring a real-world visual environment: people make faster fixations and larger gaze
shifts, once more suggesting more exploratory gaze behavior.

Figure 4. Active viewing impacts eye movements. A) Relative to fixations made in the passive viewing condition, fixations in the active viewing condition were shorter B) and more frequent. C) Gaze shifts in the active viewing condition were also larger, and D) the spatial distribution of gaze in the active viewing condition was less centrally tending. E) Sample duration-weighted fixations and gaze shifts made by a single participant (top) and group fixation map for participants (bottom) per condition. *** denotes $p < 0.001$.

Discussion

Our results provide novel insights into the process by which we actively construct representations of immersive, real-world visual environments. We found that, when participants are unconstrained and free to choose their field of view, their behavior is most guided by meaningful, semantic properties of the environment, as compared with passive viewers. Moreover, in service of this information-seeking behavior, active viewers employ shorter, more entropic fixations. All in all, we demonstrate that active viewing conditions impact nearly all features of gaze behavior, from gaze mechanics (how we move our eyes) to gaze dynamics (what we choose to attend to). These findings lay the foundation for future studies of gaze behavior in immersive, real-world environments using VR.

The recent development of eye-tracking in immersive VR is a critical advance for investigating real-world scene processing in the context of natural behavioral affordances. VR frees the subject from the limitations typically imposed by head-restricted display studies, allowing for eye, head, and body movements[1]. Moreover, it does so without sacrificing experimental control. Active participants in our study were not only free to naturally explore an environment from a first-person perspective; they were also shown a large, diverse set of stimuli within precise trial structures in a counterbalanced design. Such stimulus diversity and controlled presentation is an essential ingredient for quantitative, model-based insights into active human gaze behavior. This opportunity for experimental control and diverse stimulus presentation stands in contrast to mobile eye-

tracking paradigms, where participants might only traverse a single, extended
environment (e.g., a university campus) in which the low-level visual features (e.g., the
lighting/contrast) as well as high-level visual features (e.g., people walking down the
street) inevitably vary between participants. Previous approaches comparing active
versus passive viewing have relied on a combination of fixed-display and mobile
paradigms[26,27], which inherently differ in terms of task demands (e.g., watching a video
vs. navigating) and displayed field of view. All in all, eye-tracking in immersive VR is an
exciting opportunity for novel insight into active human gaze behavior.

Our findings have multiple implications for active, real-world vision. Recent studies have
proposed a dominant role for semantically meaningful scene regions in guiding attention
even during passive viewing of fixed-display images, suggesting that gaze behavior
primarily reflects high-level information-seeking priority as scene understanding
unfolds[7,8,11]. Our results extend these findings in three key ways. First, we demonstrate
that semantically relevant features guide attention in immersive, naturalistic
environments. This is an important demonstration if semantically guided attention is
indeed a feature of real-world vision. Second, we show that active viewing conditions
increase the advantage for semantics over low-level visual salience in guiding gaze
behavior. Again, this finding has important implications for real-world vision; our results
suggest that when participants are free to seek out information and choose their field of
view, their behavior is most guided by meaningful, semantic properties of the stimulus, or
scene. Finally, our findings provide key benchmark measurements of gaze behavior in
diverse, real-world scenes during active viewing conditions, demonstrating that active
viewers make quick, entropic fixations and shift their gaze nearly twice per second.

We attribute the observed increase in exploratory, information-seeking behavior in active
viewing conditions to differences in the *affordances* available to active viewers, not
differences in their *action goals*. Our experiment manipulated self- vs. image-generated
motion, but not participants' task, a factor long understood to impact gaze behavior[28–30].
Participants in the active condition had no objective to physically interact with meaningful
scene regions, such as objects; nor was this a possibility. Yet, access to a naturalistic
behavioral repertoire – a broader capacity for self-generated action – nonetheless
impacted how participants moved their eyes and deployed their attention. Our results are
consistent with theoretical models linking perceptual processing and motor plans in a
perception-action cycle[31], in which perceptual processes depend on movement states[32–
35] and the role of vision is to provide evidence to satisfy behavioral goals[1]. These findings
have important implications for future work investigating cognitive processes where motor
goals are often hampered by less naturalistic paradigms, such as scene perception,
spatial memory, and even social inference.

Of course, our experimental approach also has drawbacks. The design of our passive
condition was limited by the known tendency for image-generated motion to induce
participant motion sickness[36]. As a result, we opted to implement a passive condition that
slowly revealed the panoramic environments to participants, giving passive viewers the

opportunity to explore the same fields of view as active viewers, but did not provide an
exact match for the sequence of moment-to-moment fields of view that an active viewer
would have taken in a scene. We do not think that these limitations impacted our results.
As both semantic and salient scene features were equally distributed around our
panoramic scenes, participants in both conditions were given an equal amount of time to
explore each environment, and our control analyses demonstrate that active viewers
rarely, if ever, dwelled on any portion of the panoramic scene for longer than it would
have been displayed to a passive viewer. Thus, the disproportionate advantage for
meaning over salience in predicting gaze behavior during active viewing conditions can
be attributed to which scene features a participant chose to attend to in any field of view,
rather than which fields of view active vs. passive viewers sampled during a trial. In our
active condition, we were limited by the challenge of self-embodiment[36]: participants could
move their eyes, head, and body, but their movements were not paired with the typical
visual experience of seeing one's body. It is possible that our results would strengthen if
the perception of self-embodiment were afforded to active viewers, as in real-world
viewing conditions. Finally, given the free viewing nature of our experiment, we cannot
rule out the possibility that our effects are mediated by differences in attentional
engagement between our two conditions, particularly given that VR was a novel
experience for most participants.
305
In sum, our results demonstrate for first time that active viewing conditions impact
attentional deployment in 360°, real-world scenes. Signatures of top-down attentional
guidance increase in active viewing conditions: active viewers disproportionately allocate
their attention to semantically relevant scene features using quicker, more exploratory
eye-movements than passive viewers. In addition to providing key benchmarks for active,
naturalistic gaze behavior, these results show that active viewing influences every aspect
of gaze behavior, from the way we move our eyes to what we choose to attend to.

Methods

Participants. Eighteen adults participated in the main experiment (thirteen females; mean age 22 +/- 3.73 STD years). Three additional participants completed a pilot study designed to test eye-tracker accuracy and precision (Supplemental Figure 1). Participants were recruited based on 1) having normal or contact-corrected vision and no colorblindness, 2) having no neurological or psychiatric conditions, and 3) having no history of epilepsy. Written consent was obtained from all participants in accordance with a protocol approved by the Dartmouth College and Massachusetts Institute of Technology Institutional Review Boards.

Stimulus and headmounted display. Stimuli consisted of 360° "photospheres" of real-world scenes, sourced from an online photo sharing website (www.flickr.com). Photospheres depicted a diverse set of indoor and outdoor settings with content including people and objects. Each photosphere was applied to a virtual environment built in Unity version 2017.3.1f1 (www.unity3d.com) and integrated with a headmounted display (Oculus Rift, Development Kit 2, www.oculus.com, low persistence OLED screen, 960 x 1080 resolution per eye; ~100 degree field of view; 75 Hz refresh rate).

Eye-tracker specifications and accuracy. A monocular, in-headset eye-tracker (Pupil Labs: 120 Hz sampling frequency, 5.7 ms camera latency, 3.0 ms processing latency; 0.6 visual degrees accuracy, 0.08 visual degrees precision) continuously monitored the position of participants' right eye during scene viewing. Eye movements were recorded using custom scripts written in C# for Unity. Refer to Supplemental Figure 1 for observed accuracy and precision of Pupil Labs eye-tracker at varying distances from screen center.

Experimental Procedures. On each trial of the experiment (40 trials), participants were presented with a photosphere via the headmounted display (HMD). Participants were instructed to "fully and naturally explore each scene". Participants were given a break after every 10 scenes, after which the eye-tracker was recalibrated.

There were two viewing conditions in this experiment: active and passive (Figure 1). In both conditions, the stimulus was presented via the HMD and each trial lasted for 20s. During the active condition, participants stood while wearing the HMD and actively explored the photosphere via self-directed eye movements and head turns. In contrast, during the passive condition, participants' heads were fixed in a chin rest and the scene panned across the screen, rotating 360° at a constant velocity (22°/ second). In order to prevent the sensation of motion sickness, rotational velocity gradually ramped up and down during the first and last two seconds of each passive trial.

There were 40 total stimuli included in the experiment. Each participant viewed 20 stimuli in each of the two conditions with condition assignment randomized for each trial and participant. Conditions were blocked, but condition order was counterbalanced across

356 participants. The initial rotation angle of each scene was held constant across
357 participants.
358
Practice Trials and Calibration Routine. There were three phases to the experiment:
practice, calibration, and experimental trials. During the practice phase, participants
performed two active condition trials. This ensured that participants had acclimated to the
virtual environments prior to starting the experiment. Following the practice phase,
participants performed a 14-point calibration routine in order to validate eye-tracking
accuracy. Participants repeated the calibration routine after every 10 experimental trials.
365
After each trial in the Experimental Phase, participants returned to a virtually rendered
home screen where they were instructed to take a break. Upon advancing from the home
screen, participants were presented with a pre-trial fixation screen with a target at screen
center. Participants were instructed to fixate on the target so that gaze drift could be
assessed. If significant drift (> 5 degrees visual angle) was detected, a recalibration
routine was performed.
372
373 *Eye-tracking data analysis.* Raw *x (*and *y)* gaze points were converted from normalized
374 screen coordinates to DVA using the following equation[37]:
375

$$B_a = \left(\frac{180°}{\pi}\right) \cdot \left(\frac{2 \cdot FOV_a}{FOV_{max}}\right) \cdot \mathrm{atan2}(p_a, d)$$

376
377
378 where, B_a denotes the azimuth (or elevation) angle of gaze position in visual degrees
379 relative to screen center, FOV_a denotes the field of view of the x (or y) dimension of the
380 HMD as a proportion of the largest dimension of the HMD (i.e., 100 DVA), p_a denotes the
381 gaze position in normalized screen coordinates, and *d* denotes the distance in Unity units
382 that places the participant at the origin of the spherical eye-tracking coordinate system.
383
384 Next, gaze coordinates were rectified with head position (pitch, yaw, roll), and
385 transformed into latitude and longitude positions on a sphere (spherical degrees):
386

$$Lat = x - (B_y \cos(z) + B_x \sin(z))$$
$$Long = y + (\cos(Lat) \cdot (B_x \cos(z) - B_y \sin(z)))$$

387
388
389 Here, *x* denotes pitch in spherical degrees (with up being negative and down being
390 positive), *y* denotes yaw in spherical degrees, and *z* denotes roll in radians. B_x and B_y
391 denote gaze point distance from screen center in visual degrees.
392
393 Within each trial, a gaze point was labelled as invalid if: 1) it fell outside the field of view
394 (i.e., greater than 50° from screen center in either the *x* and/or *y* direction), 2) pupil
395 detection confidence was low (i.e., below 50 percent), or 3) no data was collected (e.g.,
396 during a blink). Trials with more than 75 percent of points labelled as invalid were
397 excluded from the analysis.

Defining fixations. Next, to determine fixations, the orthodromic distance and velocity was calculated between consecutive gaze points. Specifically, the mean absolute deviation (MAD)[38] in gaze position was calculated within a seven-sample sliding window (~80ms) and potential fixations were defined as windows with a MAD less than 50°/s[27]. Potential fixations were concatenated if two group centroids were displaced by less than 1° and the two potential fixations occurred within 150ms of each other. Fixations with durations shorter than 100ms were excluded[27,39]. To standardize fixation density maps across conditions, fixations in the active condition were excluded if they fell beyond the region displayed during the passive condition (27.9 percent of the spherical scene; Figure 2). Given the infrequency with which participants looked at the upper and lower poles of a scene, only 12.2 percent +/- 1.29 STE of fixations were discarded from the active condition. Additionally, because the rotational velocity was changing at the beginning and end of each passive condition trial, fixations made during the first and last two seconds were excluded from both active and passive conditions.

Fixation density map generation. We next characterized the spatial distribution of fixations on each trial. To generate two-dimensional fixation density maps, we first plotted the fixations for all subjects in a given scene and condition in equirectangular space. The resulting fixation maps were smoothed with a variable-width gaussian filter ("modified gaussian"[40]) to account for distortions of the equirectangular image at shorter latitudes (i.e., approaching the poles). Specifically, the width of the gaussian filter is scaled by the latitude of the gaze point using the following equation:

$$a = \frac{B_w}{\cos(Lat)}$$

where the width of the filter, *a*, at a given latitude (*Lat*) has been scaled from the base filter width (*Bw*) applied at the equator.

Gaze map generation. Finally, we generated duration-weighted fixation density maps. In order to prevent extreme fixation durations made by individual subjects from exerting an outsized impact on the group gaze maps, fixations with durations above the 95th percentile were reduced to the 95th percentile value[8,11]. Additionally, each individual subject's fixations were normalized on a scale from 0.1 to 1.

Quantifying central tendency. A routine observation in fixed display studies is the tendency for fixations to be disproportionately allocated at the center of a scene[18]. "Central tendency" has been employed as a metric of visual exploration, where fixations that are less centrally tending are considered more exploratory[21]. Given the tendency for viewers to fixate near the equator in VR[16], "equator bias" was calculated per condition by averaging the distance of each fixation from the equator in the *y* dimension only.

Quantifying entropy. The entropy of the resulting fixation density map was calculated using the following equation[22]:

$$E = -\sum p \cdot \log_2 p$$

where p contains the fixation density map's histogram counts.

Because entropy estimates can be impacted by small sample sizes[41], and because an uneven number of fixations were made across conditions for any single scene, we applied a bootstrapping technique to estimate entropy. Across 100 iterations, we randomly sampled 24 fixations from each participant within each scene in a given condition. The target of 24 fixations was chosen in proportion to previous studies analyzing the entropy of nine fixations per 6s trial[21,42].

Salience map and meaning map generation. To assess the impact of active viewing on the spatial distribution of gaze, we generated two continuous content maps for each scene: 1) a "salience map", a map of low-level visual salience and 2) a "meaning map", a map of high-level semantic features (i.e., "meaning"). Recent approaches using continuous meaning maps to quantify semantic-level salience in a scene have enabled the direct comparison of bottom-up vs. top-down contributions to attentional guidance[8].

Salience maps were generated using the Graph-Based Visual Saliency (GBVS) Toolbox[12]. Each photosphere was uniformly sampled and decomposed into a set of 500 square tiles, each with a diameter of 7.5°. The GBVS model with default feature channels (i.e., color, intensity, orientation) was applied to each tile, which was then projected back to its position in the equirectangular image. Salience maps were smoothed using the variable-width gaussian filter applied to gaze maps.

To generate meaning maps, we applied the procedures described by Henderson and Hayes[8,11] to 360° scenes. Each photosphere was uniformly sampled at both coarse (100 points) or fine (500 points) spatial scales and decomposed into sets of partially overlapping circular tiles with diameters of 20.6 spherical degrees or 7.5 spherical degrees, respectively. Scene tiles were produced by generating a rectilinear projection (1100x1100 pixels) around each point sampled on the sphere. Each coarse tile was down-sampled to match the resolution of fine tiles, resulting in a diameter of 150 pixels for all scene tiles. The full scene tile stimulus set contained 20,000 unique fine-scale tiles and 4,000 unique coarse-scale tiles, for a total of 24,000 scene tiles.

A total of 1,879 participants on Amazon Mechanical Turk rated scene tiles on a 6-point Likert scale (very low, low, somewhat low, somewhat high, high, very high). Participants were instructed to rate the content of each scene tile based on how "informative or recognizable" it was. Participants were first given examples of two low-meaning and two high-meaning tiles, followed by a set of four practice trials to ensure understanding of the task. The practice trials contained two examples expected to score on the low-meaning

484 side of the scale (1-3) and two examples expected to score on the high-meaning side of
485 the scale (4-6). Seventy-nine participants were excluded based on the results of these
486 diagnostic practice trials.
487
488 Each participant rated 40 tiles (20 of each spatial scale). Participants rated exactly one
489 tile from each of the 40 scenes, and participants were prevented from completing the
490 online experiment more than once. In total, the experiment took approximately 3 minutes
491 and participants were compensated for completing the study.
492
493 Each tile was rated by three participants, and responses were averaged to produce a
494 "meaning" rating for each tile. The average rating for each tile was then plotted at its
495 center coordinate and smoothed using the variable-width gaussian filter. This process
496 was completed at both spatial scales, and the average of these two maps was used as
497 the scene's final "meaning map".
498
Spherical sampling of equirectangular maps. To account for the distortion imposed by
equirectangular map projections, which disproportionately represent scene regions at the
poles, we sampled (N = 100,000) points uniformly on a sphere, projected those indices
onto each equirectangular map (i.e., gaze, salience, meaning, and equator), and used
the sampled values at these indices for analyses of spatial attention (Figure 2)[43]. As a
result, each individual index, or location, in an equirectangular map was treated as a
separate observation (n = 6,164,000) in statistical analyses.
506
Statistical analyses. To compute the relative contributions of visual salience and
semantics in predicting gaze behavior, we built a linear mixed effects model using the
lme4 package in R[44]. We included viewing condition (i.e., active vs. passive) and feature
maps of scene content (i.e., salience, meaning, and equator map) as fixed effects and
individual scenes as random effects. Specifically, for each scene, the model predicted the
degree to which each feature map predicted the gaze map value at each location (each
index from the N=100,000 points uniformly sampled around the spherical image).
Because gaze maps were generated at the group level[8,11], individual subjects were not
included as random effects in the model. Two-way interactions (i.e., salience by
condition, meaning by condition) and the three-way interaction between salience,
meaning, and condition were analyzed.
518

519 **Acknowledgements**
520

521 This study was supported by a grant from the Nancy Lurie Marks Family Foundation to
522 C.E.R and the donation of a Titan V GPU by the NVIDIA Corporation to C.E.R. Thanks to
523 Michael Cohen for insightful comments on the manuscript. Thanks also to George
524 Wolford, Anna Mynick, Nancy Kanwisher, Brad Duchaine, and Adam Steel for helpful
525 discussion about the project.

References

1. Hayhoe, M. M. Vision and Action. *Annu. Rev. Vis. Sci.* **3**, 389–413 (2017).
2. Hayhoe, M. M. & Matthis, J. S. Control of gaze in natural environments: effects of rewards and costs, uncertainty and memory in target selection. *Interface Focus* **8**, 20180009 (2018).
3. Goldberg, M. E. & Wurtz, R. H. Activity of superior colliculus in behaving monkey. I. Visual receptive fields of single neurons. *J. Neurophysiol.* **35**, 542–559 (1972).
4. Troncoso, X. G. *et al.* V1 neurons respond differently to object motion versus motion from eye movements. *Nat. Commun.* **6**, 8114 (2015).
5. Held, R. & Hein, A. Movement-produced stimulation in the development of visually guided behavior. *J. Comp. Physiol. Psychol.* **56**, 872–876 (1963).
6. Trewartha, K. M., Case, S. & Flanagan, J. R. Integrating actions into object location memory: A benefit for active versus passive reaching movements. *Behav. Brain Res.* **279**, 234–239 (2015).
7. Henderson, J. M., Hayes, T. R. & Rehrig, G. Meaning Guides Attention during Real-World Scene Description. 1–9 (2018). doi:10.1038/s41598-018-31894-5
8. Henderson, J. M. & Hayes, T. R. Meaning-based guidance of attention in scenes as revealed by meaning maps. *Nat. Hum. Behav.* **1**, (2017).
9. Itti, L. & Koch, C. A saliency-based search mechanism for overt and covert shifts of visual attention. *Vision Res.* **40**, 1489–1506 (2000).
10. Greene, M. R. & Oliva, A. Recognition of natural scenes from global properties: Seeing the forest without representing the trees. *Cogn. Psychol.* **58**, 137–176 (2009).
11. Henderson, J. M. & Hayes, T. R. Meaning guides attention in real-world scene images: Evidence from eye movements and meaning maps. *J. Vis.* **18**, 10 (2018).
12. Harel, J., Koch, C. & Perona, P. Graph-based visual saliency. in *Advances in Neural Information Processing Systems* 545–552 (2007). doi:10.7551/mitpress/7503.003.0073
13. Parkhurst, D., Law, K. & Niebur, E. Modeling the role of salience in the allocation of overt visual attention. *Vision Res.* **42**, 107–23 (2002).
14. Henderson, J. M. Regarding Scenes. *Curr. Dir. Psychol. Sci.* **16**, 219–222 (2007).
15. Wolfe, J. M. & Horowitz, T. S. Five factors that guide attention in visual search. *Nat. Hum. Behav.* **1**, 58 (2017).
16. Sitzmann, V. *et al.* Saliency in VR: How Do People Explore Virtual Environments? *IEEE Trans. Vis. Comput. Graph.* **24**, 1633–1642 (2018).
17. Tatler, B. W. The central fixation bias in scene viewing: Selecting an optimal viewing position independently of motor biases and image feature distributions. *J. Vis.* **7**, (2007).
18. Bindemann, M. Scene and screen center bias early eye movements in scene viewing. *Vision Res.* **50**, 2577–2587 (2010).
19. Tseng, P. H., Carmi, R., Cameron, I. G. M., Munoz, D. P. & Itti, L. Quantifying center bias of observers in free viewing of dynamic natural scenes. *J. Vis.* **9**, 4–4 (2009).

20. Schumann, F. *et al.* Salient features in gaze-aligned recordings of human visual
input during free exploration of natural environments. *J. Vis.* **8**, (2008).
21. Gameiro, R. R., Kaspar, K., König, S. U., Nordholt, S. & König, P. Exploration and
Exploitation in Natural Viewing Behavior. *Sci. Rep.* **7**, 1–23 (2017).
22. Açik, A., Sarwary, A., Schultze-Kraft, R., Onat, S. & König, P. Developmental
changes in natural viewing behavior: Bottomup and top-down differences between
children, young adults and older adults. *Front. Psychol.* **1**, (2010).
23. Tatler, B. W., Baddeley, R. J. & Vincent, B. T. The long and the short of it: Spatial
statistics at fixation vary with saccade amplitude and task. *Vision Res.* **46**, 1857–
1862 (2006).
24. Land, M. F. & Hayhoe, M. In what ways do eye movements contribute to everyday
activities? in *Vision Research* **41**, 3559–3565 (2001).
25. Von Wartburg, R. *et al.* Size matters: Saccades during scene perception.
Perception **36**, 355–365 (2007).
26. Foulsham, T., Walker, E. & Kingstone, A. The where, what and when of gaze
allocation in the lab and the natural environment. *Vision Res.* **51**, 1920–1931
(2011).
27. Peterson, M. F., Lin, J., Zaun, I. & Kanwisher, N. Individual differences in face-
looking behavior generalize from the lab to the world. *J. Vis.* **16**, 1–18 (2016).
28. Ballard, D. H. & Hayhoe, M. M. Modelling the role of task in the control of gaze.
Vis. cogn. **17**, 1185–1204 (2009).
29. Yarbus, A. L. *Eye Movements and Vision. Eye Movements and Vision* (Springer
US, 1967). doi:10.1007/978-1-4899-5379-7
30. Kollmorgen, S., Nortmann, N., Schröder, S. & König, P. Influence of Low-Level
Stimulus Features, Task Dependent Factors, and Spatial Biases on Overt Visual
Attention. *PLoS Comput. Biol.* **6**, e1000791 (2010).
31. Wolpert, D. M. & Landy, M. S. Motor control is decision-making. *Current Opinion
in Neurobiology* **22**, 996–1003 (2012).
32. Jung, S. N., Borst, A. & Haag, J. Flight activity alters velocity tuning of fly motion-
sensitive neurons. *J. Neurosci.* **31**, 9231–9237 (2011).
33. Maimon, G., Straw, A. D. & Dickinson, M. H. Active flight increases the gain of
visual motion processing in Drosophila. *Nat. Neurosci.* **13**, 393–399 (2010).
34. Chiappe, M. E., Seelig, J. D., Reiser, M. B. & Jayaraman, V. Walking modulates
speed sensitivity in drosophila motion vision. *Curr. Biol.* **20**, 1470–1475 (2010).
35. Matthis, J. S., Yates, J. L. & Hayhoe, M. M. Gaze and the Control of Foot
Placement When Walking in Natural Terrain. *Curr. Biol.* **28**, 1224-1233.e5 (2018).
36. Pan, X. & Hamilton, A. F. d. C. Why and how to use virtual reality to study human
social interaction: The challenges of exploring a new research landscape. *Br. J.
Psychol.* **109**, 395–417 (2018).
37. Ehinger, B. V., Groß, K., Ibs, I. & König, P. A new comprehensive eye-tracking
test battery concurrently evaluating the Pupil Labs glasses and the EyeLink 1000.
PeerJ **2019**, e7086 (2019).
38. Voloh, B., Watson, M., Koenig, S. & Womelsdorf, T. MAD saccade: statistically
robust saccade threshold estimation. *psyarxiv* 2–7 (2019).

doi:10.31234/OSF.IO/RZD6V

39.   Wass, S. V, Smith, T. J. & Johnson, M. H. Parsing eye-tracking data of variable quality to provide accurate fixation duration estimates in infants and adults. *Behav. Res. Methods* **45**, 229–250 (2013).

40.   John, B., Raiturkar, P., Le Meur, O. & Jain, E. A Benchmark of Four Methods for Generating 360° Saliency Maps from Eye Tracking Data. *Int. J. Semant. Comput.* **13**, 329–341 (2019).

41.   Wilming, N., Betz, T., Kietzmann, T. C. & König, P. Measures and Limits of Models of Fixation Selection. *PLoS One* **6**, e24038 (2011).

42.   Kaspar, K. *et al.* Emotions' Impact on Viewing Behavior under Natural Conditions. *PLoS One* **8**, (2013).

43.   Gutiérrez, J., David, E., Rai, Y. & Le Callet, P. Toolbox and dataset for the development of saliency and scanpath models for omnidirectional/360 ∙ still images. *Signal Process. Image Commun.* **69**, 35–42 (2018).

44.   Bates, D., Mächler, M., Bolker, B. M. & Walker, S. C. Fitting linear mixed-effects models using lme4. *J. Stat. Softw.* **67**, (2015).

45.   Cognolato, M., Atzori, M. & Müller, H. Head-mounted eye gaze tracking devices: An overview of modern devices and recent advances. *J. Rehabil. Assist. Technol. Eng.* **5**, 205566831877399 (2018).

Supplemental Information

Supplemental Figure 1. Gaze measured in 360 is accurate and precise.
Three head-fixed participants made a series of saccades from a central fixation cross to 16 targets arranged in a cross and spanning the entire headmounted display field of view. Targets were located above, below, and to the right and left of screen center, and were located at distances of 10, 20, 30, and 40 DVA in each direction. Each observer completed this task six times, over separate sessions. The mean accuracy across observers and locations was 2.00 DVA +/- 0.38 STE, and the mean precision across observers and locations was 0.26 DVA +/- 0.05 STE. Eye-tracking accuracy decreased with eccentricity (F(1, 6.126) = 58.175, p < 0.001); however, gaze measured at screen center was accurate within <1 DVA, comparable to the reported accuracy of many mobile eye-tracking systems[45].

647 **Supplemental Table 1: Control analysis results summary.** Meaning:salience:condition interaction
648 remains significant when restricting analysis to the fields of view containing regions ranked in the top 50th
649 percentile for meaning.
650

	NumDF	DenDF	*F* value	*p* value
condition	1	5935512	6.78E+03	< 0.001
meaning	1	5935478	6.89E+04	< 0.001
salience	1	5935534	1.98E+04	< 0.001
condition:meaning	1	5935512	2.21E+04	< 0.001
condition:salience	1	5935512	3.39E+00	0.0656
meaning:salience	1	5935548	6.07E+04	< 0.001
condition:equator	2	5935532	4.37E+05	< 0.001
condition:meaning:salience	1	5935512	4.34E+02	< 0.001