Active Vision in Immersive, 360° Real-World Environments

Amanda J. Haskins[1], Jeff Mentch[1,2], Thomas L. Botch[1], Caroline E. Robertson[1]

[1] *Department of Psychological and Brain Sciences, Dartmouth College, Hanover, NH*

03755, USA

[2] *Department of Brain and Cognitive Sciences, Massachusetts Institute of Technology,*

Cambridge, MA 02139, USA

Correspondence:

Address: 3 Maynard Street, Moore Hall, Hanover NH 03755

Phone: +1 (603) 646 9129

ajh.gr@dartmouth.edu

Abstract

Vision is an active process. Humans actively sample their sensory environment via

saccades, head turns, and body movements. Yet, little is known about active visual

processing in real-world environments. Here, we exploited recent advances in immersive

virtual reality (VR) and in-headset eye-tracking to show that active viewing conditions

impact how humans process complex, real-world scenes. Specifically, we used

quantitative, model-based analyses to compare which visual features participants

prioritize over others while encoding a novel environment in two experimental conditions:

active and passive. In the active condition, participants used head-mounted VR displays

to explore 360º scenes from a first-person perspective via self-directed motion (saccades

and head turns). In the passive condition, 360º scenes were passively displayed to

participants within the VR headset while they were head-restricted. Our results show that

signatures of top-down attentional guidance increase in active viewing conditions: active

viewers disproportionately allocate their attention to semantically relevant scene features,

as compared with passive viewers. We also observed increased signatures of exploratory

behavior in eye movements, such as quicker, more entropic fixations during active as

compared with passive viewing conditions. These results have broad implications for

studies of visual cognition, suggesting that active viewing influences every aspect of gaze

behavior – from the way we move our eyes to what we choose to attend to – as we

construct a sense of place in a real-world environment.

Significance Statement

Eye-tracking in immersive virtual reality offers an unprecedented opportunity to

study human gaze behavior under naturalistic viewing conditions without sacrificing

experimental control. Here, we advanced this new technique to show how humans deploy

attention as they encode a diverse set of 360º, real-world scenes, actively explored from

a first-person perspective using head turns and saccades. Our results build on classic

studies in psychology, showing that active, as compared with passive, viewing conditions

fundamentally alter perceptual processing. Specifically, active viewing conditions

increase information-seeking behavior in humans, producing faster, more entropic

fixations, which are disproportionately deployed to scene areas that are rich in semantic

meaning. In addition, our results offer key benchmark measurements of gaze behavior in

360°, naturalistic environments.

Introduction

45
Constructing a sense of place in a complex environment is an active process.

Humans actively sample their sensory environment to understand their surroundings and

gain information relevant to their behavioral goals (Hayhoe, 2017; Hayhoe and Matthis,

2018). Yet, much of what we know about how people encode real-world environments

comes from computer-based paradigms that severely limit participants' active

affordances. In this context, the participant's behavioral repertoire is limited to eye

movements, and the displayed environment is typically limited to a single field of view. In

contrast, everyday visual environments are actively explored. We gain rich information

about a place by shifting our eyes, turning our heads, and moving our bodies. This is

because real-world scenes are immersive, extending 360º around us and beyond any

single field of view. How does scene understanding unfold in immersive, active viewing

conditions?

It has long been understood that active viewing conditions impact perceptual

processing. Neurons in early stages of the visual system are sensitive to the distinction

between self- and world-generated motion under conditions that are carefully matched

for retinal stimulation and attentional engagement (Goldberg and Wurtz, 1972; Troncoso

et al., 2015). Further, active vision is thought to be necessary for typical visual

development: even basic functions, such as depth perception and contrast sensitivity,

suffer when animals are denied self-motion, but are passively exposed to equivalent

visual environments (Held and Hein, 1963). Studies in humans also suggest that

perceptual systems differentially represent stimuli that are encountered via active vs.

passive viewing (Hayhoe, 2017). For example, an object's spatial location is better

recalled when it has been actively reached for rather than passively moved toward

(Trewartha et al., 2015). Yet, to date, no studies have explored how active viewing

conditions impact the processing of complex visual stimuli, such as real-world scenes.

Here, we used a novel experimental design to study real-world scene processing

during active and passive viewing conditions. We exploited recent developments in virtual

reality (VR) to immerse participants in real-world, 360º scenes. Meanwhile, we monitored

participants' gaze using in-headset eye-tracking as they explored these environments,

revealing which regions they prioritized over others. In one condition, participants

explored scenes from an active, first-person perspective. In the other condition, scenes

were passively displayed to participants while they were head-restricted in a chin rest. In

both conditions, diverse, real-world scenes were displayed with the same wide-angle field

of view (100 DVA), and participants were exposed to comparable portions of the display

over the course of the trial. Thus, this paradigm enabled us to perform quantitative, in-

depth comparisons of gaze behavior and attentional deployment as subjects encoded

novel, real-world scenes during active vs. passive exploration.

Our central hypothesis was that active viewing conditions would increase viewers'

exploratory, information-seeking behavior in a real-world scene. We tested this by

measuring the degree to which participants' overt attention was dominantly predicted by

the spatial distribution of scene features that are semantically informative (e.g., objects,

faces, doors) (Henderson and Hayes, 2017; Henderson et al., 2018), vs. scene regions

that are rich in salient visual features (e.g., luminance, contrast, color, and orientation)

(Itti and Koch, 2000; Greene and Oliva, 2009). Previous studies have shown that these

information sources compete for participants' top-down vs. bottom-up attention, although

attention is predominantly predicted by the distribution of semantic information

(Henderson and Hayes, 2017, 2018).

In brief, we observed that participants' attention was dominantly guided by

semantic meaning as compared low-level visual features in both active and passive

conditions, replicating previous findings (Henderson and Hayes, 2017, 2018). Crucially,

this effect tripled during active viewing, reflecting an increase in signatures of top-down

attentional guidance when participants were free to actively view their environment.

Further, in service of this information-seeking behavior, active viewers made shorter,

more exploratory fixations than passive viewers. These results show that active viewing

influences every aspect of gaze behavior, from the way we move our eyes to what we

choose to attend to.

Methods

Participants. Eighteen adults participated in the main experiment (thirteen females; mean age 22 years +/- 3.73 STD). Three additional participants completed a pilot study designed to test eye-tracker accuracy and precision (Supplemental Figure 1). Participants were recruited based on 1) having normal or contact-corrected vision and no colorblindness, 2) having no neurological or psychiatric conditions, and 3) having no history of epilepsy. Written consent was obtained from all participants in accordance with a protocol approved by the Dartmouth College and Massachusetts Institute of Technology Institutional Review Boards.

Stimulus and headmounted display. Stimuli consisted of 360° "photospheres" of real-world scenes, sourced from an online photo sharing website (www.flickr.com). Photospheres depicted a diverse set of indoor and outdoor settings with content including people and objects. Each photosphere was applied to a virtual environment built in Unity version 2017.3.1f1 (www.unity3d.com) and integrated with a headmounted display (Oculus Rift, Development Kit 2, www.oculus.com, low persistence OLED screen, 960 x 1080 resolution per eye; ~100 degree field of view; 75 Hz refresh rate).

Eye-tracker specifications and accuracy. A monocular, in-headset eye-tracker (Pupil Labs: 120 Hz sampling frequency, 5.7 ms camera latency, 3.0 ms processing latency; 0.6 visual degrees accuracy, 0.08 visual degrees precision) continuously monitored the position of participants' right eye during scene viewing. Eye movements were recorded using custom scripts written in C# for Unity. Refer to Supplemental Figure 1 for observed accuracy and precision of Pupil Labs eye-tracker at varying eccentricities.

Experimental Design. On each trial of the experiment (40 trials), participants were

presented with a photosphere via the headmounted display (HMD). Participants were

instructed to "fully and naturally explore each scene". Participants were given a break

after every 10 scenes, after which the eye-tracker was recalibrated.

There were two viewing conditions in this experiment: active and passive (Figure

1). In both conditions, the stimulus was presented via the HMD and each trial lasted for

20s. During the active condition, participants stood while wearing the HMD and actively

explored the photosphere via self-directed eye movements and head turns. In contrast,

during the passive condition, participants' heads were fixed in a chin rest and the scene

panned across the screen, rotating 360° at a constant velocity (22°/ second). In order to

prevent the sensation of motion sickness, rotational velocity gradually ramped up and

down during the first and last two seconds of each passive trial.

There were 40 total stimuli included in the experiment. Each participant viewed 20

stimuli in each of the two conditions with condition assignment randomized for each trial

and participant. Conditions were blocked, but condition order was counterbalanced

across participants. The initial rotation angle of each scene was held constant across

participants.

Practice Trials and Calibration Routine. There were three phases to the

experiment: practice, calibration, and experimental trials. During the practice phase,

participants performed two active condition trials. This ensured that participants had

acclimated to the virtual environments prior to starting the experiment. Following the

practice phase, participants performed a 14-point calibration routine in order to validate

eye-tracking accuracy. Participants repeated the calibration routine after every 10

experimental trials.

After each trial in the Experimental Phase, participants returned to a virtually

rendered home screen where they were instructed to take a break. Upon advancing from

the home screen, participants were presented with a pre-trial fixation screen with a target

at screen center. Participants were instructed to fixate on the target so that gaze drift

could be assessed. If significant drift (> 5 degrees visual angle) was detected, a

recalibration routine was performed.

Eye-tracking data analysis. Raw *x (*and *y)* gaze points were converted from

normalized screen coordinates to DVA using the following equation(Ehinger et al., 2019):

$$B_a = \left(\frac{180°}{\pi}\right) \cdot \left(\frac{2 \cdot FOV_a}{FOV_{max}}\right) \cdot \text{atan2}(p_a, d)$$

where, B_a denotes the azimuth (or elevation) angle of gaze position in visual degrees

relative to screen center, FOV_a denotes the field of view of the x (or y) dimension of the

HMD as a proportion of the largest dimension of the HMD (i.e., 100 DVA), p_a denotes the

gaze position in normalized screen coordinates, and *d* denotes the distance in Unity units

that places the participant at the origin of the spherical eye-tracking coordinate system.

Next, gaze coordinates were rectified with head position (pitch, yaw, roll), and

transformed into latitude and longitude positions on a sphere (spherical degrees):

$$Lat = x - (B_y \cos(z) + B_x \sin(z))$$
$$Long = y + (\cos(Lat) \cdot (B_x \cos(z) - B_y \sin(z)))$$

Here, *x* denotes pitch in spherical degrees (with up being negative and down being

positive), *y* denotes yaw in spherical degrees, and *z* denotes roll in radians. B_x and B_y

denote gaze point distance from screen center in visual degrees.

Within each trial, a gaze point was labelled as invalid if: 1) it fell outside the field of

view (i.e., greater than 50° from screen center in either the *x* and/or *y* direction), 2) pupil

detection confidence was low (i.e., below 50 percent), or 3) no data was collected (e.g.,

during a blink). Trials with more than 75 percent of points labelled as invalid were

excluded from the analysis.

Defining fixations. Next, to determine fixations, the orthodromic distance and

velocity was calculated between consecutive gaze points. Specifically, the mean absolute

deviation (MAD) (Voloh et al., 2019) in gaze position was calculated within a seven-

sample sliding window (~80ms) and potential fixations were defined as windows with a

MAD less than 50°/s (Peterson et al., 2016). Potential fixations were concatenated if two

group centroids were displaced by less than 1° and the two potential fixations occurred

within 150ms of each other. Fixations with durations shorter than 100ms were excluded

(Wass et al., 2013; Peterson et al., 2016). To standardize fixation density maps across

conditions, fixations in the active condition were excluded if they fell beyond the region

displayed during the passive condition (27.9 percent of the spherical scene; Figure 2D).

Given the infrequency with which participants looked at the upper and lower poles of a

scene, only 12.2 percent +/- 1.29 STE of fixations were discarded from the active

condition. Additionally, because the rotational velocity was changing at the beginning and

end of each passive condition trial, fixations made during the first and last two seconds

were excluded from both active and passive conditions.

Fixation density map generation. We next characterized the spatial distribution of

fixations on each trial. To generate two-dimensional fixation density maps, we first plotted

the fixations for all subjects in a given scene and condition in equirectangular space. The

resulting fixation maps were smoothed with a variable-width gaussian filter ("modified

gaussian" (John et al., 2019)) to account for distortions of the equirectangular image at

shorter latitudes (i.e., approaching the poles). Specifically, the width of the gaussian filter

is scaled by the latitude of the gaze point using the following equation:

$$a = \frac{B_w}{\cos(Lat)}$$

where the width of the filter, *a*, at a given latitude (*Lat*) has been scaled from the base

filter width (B_w) applied at the equator.

Gaze map generation. Finally, we generated duration-weighted fixation density

maps. In order to prevent extreme fixation durations made by individual subjects from

exerting an outsized impact on the group gaze maps, fixations with durations above the

95[th] percentile were reduced to the 95[th] percentile value (Henderson and Hayes, 2017,

2018). Additionally, each individual subject's fixations were normalized on a scale from

0.1 to 1.

Quantifying central tendency. A routine observation in fixed display studies is the

tendency for fixations to be disproportionately allocated at the center of a scene

(Bindemann, 2010). "Central tendency" has been employed as a metric of visual

exploration, where fixations that are less centrally tending are considered more

exploratory (Gameiro et al., 2017). Given the tendency for viewers to fixate near the

equator in VR (Sitzmann et al., 2018), "equator bias" was calculated per condition by

averaging the distance of each fixation from the equator in the *y* dimension only.

Quantifying entropy. The entropy of the resulting fixation density map was

calculated using the following equation (Açik et al., 2010):

$$E = -\sum p \cdot \log_2 p$$

where p contains the fixation density map's histogram counts. Because entropy estimates

can be impacted by small sample sizes (Wilming et al., 2011), and because an uneven

number of fixations were made across conditions for any single scene, we applied a

bootstrapping technique to estimate entropy. Across 100 iterations, we randomly sampled

24 fixations from each participant within each scene in a given condition. The target of 24

fixations was chosen in proportion to previous studies analyzing the entropy of nine

fixations per 6s trial (Kaspar et al., 2013; Gameiro et al., 2017).

Salience map and meaning map generation. Our central hypothesis was that

active viewing conditions would increase exploratory, information-seeking behavior in a

real-world scene. To test this hypothesis, we constructed two models of the visual content

in each environment. First, we computed a traditional "salience map", which reflects the

distribution of low-level visual features in a scene (e.g., contrast, color, orientation, etc.)

(Harel et al., 2007). Prominent low-level visual features in a scene are known to predict a

significant portion of gaze behavior (Itti and Koch, 2000; Parkhurst et al., 2002). However,

as attention is drawn on the basis of visual salience, rather than semantically meaningful

scene regions, the degree to which such maps predict gaze behavior is not related to

information-seeking behavior, thus providing a good baseline model for our hypothesis.

Second, we computed a "meaning map" for each scene, which reflects the distribution of

high-level semantic features in an environment (e.g., faces, objects, doors, etc.)

(Henderson and Hayes, 2017, 2018). "Meaning maps", a recently proposed "conceptual

analogue" of salience maps (Henderson and Hayes, 2017, 2018), reflect the spatial

distribution of features that are relevant to understanding the semantic content and

affordances available to the viewer in a scene. Recent studies have shown that attentional

deployment in novel scene images is dominantly predicted by the spatial distribution of

scene features that are semantically informative (meaning maps) as compared with low-

level features (salience maps) (Henderson and Hayes, 2017, 2018).

Salience maps were generated using the Graph-Based Visual Saliency (GBVS)

Toolbox (Harel et al., 2007). Each photosphere was uniformly sampled and decomposed

into a set of 500 square tiles, each with a diameter of 7.5° (Figure 2A). The GBVS model

with default feature channels (i.e., color, intensity, orientation) was applied to each tile,

which was then projected back to its position in the equirectangular image (Figure 2B).

Salience maps were smoothed using the variable-width gaussian filter applied to gaze

maps.

To generate meaning maps, we applied the procedures described by Henderson

and Hayes (Henderson and Hayes, 2017, 2018) to 360° scenes. Each photosphere was

uniformly sampled at both coarse (100 points) or fine (500 points) spatial scales and

decomposed into sets of partially overlapping circular tiles with diameters of 20.6

spherical degrees or 7.5 spherical degrees, respectively. Scene tiles were produced by

generating a rectilinear projection (1100x1100 pixels) around each point sampled on the

sphere. Each coarse tile was down-sampled to match the resolution of fine tiles, resulting

in a diameter of 150 pixels for all scene tiles. The full scene tile stimulus set contained

20,000 unique fine-scale tiles and 4,000 unique coarse-scale tiles, for a total of 24,000

scene tiles.

A total of 1,879 participants on Amazon Mechanical Turk rated scene tiles on a 6-

point Likert scale (very low, low, somewhat low, somewhat high, high, very high).

Participants were instructed to rate the content of each scene tile based on how

"informative or recognizable" it was. Participants were first given examples of two low-

meaning and two high-meaning tiles, followed by a set of four practice trials to ensure

understanding of the task. The practice trials contained two examples expected to score

on the low-meaning side of the scale (1-3) and two examples expected to score on the

high-meaning side of the scale (4-6). Seventy-nine participants were excluded based on

the results of these diagnostic practice trials.

Each participant rated 40 tiles (20 of each spatial scale). Participants rated exactly

one tile from each of the 40 scenes, and participants were prevented from completing the

online experiment more than once. In total, the experiment took approximately 3 minutes

and participants were compensated for completing the study.

Each tile was rated by three participants, and responses were averaged to produce

a "meaning" rating for each tile (Figure 2C). The average rating for each tile was then

plotted at its center coordinate and smoothed using the variable-width gaussian filter. This

process was completed at both spatial scales, and the average of these two maps was

used as the scene's final "meaning map".

Spherical sampling of equirectangular maps. To account for the distortion imposed

by equirectangular map projections, which disproportionately represent scene regions at

the poles, we sampled (N = 100,000) points uniformly on a sphere, projected those

indices onto each equirectangular map (i.e., gaze, salience, meaning, and equator), and

used the sampled values at these indices for analyses of spatial attention (Figure 2E)

(Gutiérrez et al., 2018). As a result, each individual index, or location, in an

equirectangular map was treated as a separate observation (n = 6,164,000) in statistical

analyses.

Statistical analyses. To compute the relative contributions of visual salience and

semantics in predicting gaze behavior, we built a linear mixed effects model using the

lme4 package in R (Bates et al., 2015). We included viewing condition (i.e., active vs.

passive) and feature maps of scene content (i.e., salience, meaning, and equator map)

as fixed effects and individual scenes as random effects. Specifically, for each scene, the

model predicted the degree to which each feature map predicted the gaze map value at

each location (each index from the N=100,000 points uniformly sampled around the

spherical image). Because gaze maps were generated at the group level (Henderson and

Hayes, 2017, 2018), individual subjects were not included as random effects in the model.

Two-way interactions (i.e., salience by condition, meaning by condition) and the three-

way interaction between salience, meaning, and condition were analyzed.

Results

To test whether active viewing conditions modulate attentional guidance in real-world scenes, we directly compared eye movements while participants viewed immersive, 360° environments in the two experimental conditions. We observed high-quality eye-tracking in the HMD, comparable with that reported in fixed display studies at screen center (accuracy: 0.79 DVA, precision, 0.11 DVA; see Supplemental Figure 1).

We specifically hypothesized that active viewing conditions would increase exploratory, information-seeking behavior, and therefore increase the degree to which meaning-maps predict gaze behavior. One of the few existing observations from eye-tracking in VR is the tendency for viewers to fixate near the equator of 360° scenes (Sitzmann et al., 2018) (a 3D equivalent of "center bias"). Therefore, to test our hypothesis, we first generated a map of the equator to serve as a baseline prediction for 360º viewing behavior. Then, for each condition, we compared the additional predictive contribution of each map of environmental content (salience map, meaning map) using a linear mixed-effects model. Specifically, we included three spatial maps (i.e., salience maps, meaning maps, and our baseline map of the equator) and viewing condition as fixed effects and individual scenes as random effects in the model. All results are summarized in Table 1.

Overall, we observed that overt attention in real-world scenes primarily reflects information-seeking behavior in both active and passive conditions, confirming previous results (Henderson and Hayes, 2017, 2018). Both salience and meaning maps significantly predicted participants' overt attention (salience estimated marginal effect: 0.15 +/- 0.03 STE, CI: [0.09,0.21]; $p < 0.001$; meaning estimated marginal effect: 0.31 +/-

0.03 STE, CI: [0.25, 0.36]; *p* < 0.001). However, in both active and passive conditions,

meaning was significantly more predictive of which scene regions participants explored

than salience (meaning:salience interaction: *p* < 0.001; post-hoc corrected t-tests for

meaning vs. salience: *p* < 0.001 for both conditions).

Critically, however, this advantage for meaningful scene regions nearly tripled in

the active as compared with the passive condition (salience*meaning*condition: *p* <

0.001; Figure 3). Post-hoc analyses revealed that the estimated marginal effect of

meaning (i.e., its predictive contribution, holding other factors constant) was significantly

greater for active as compared with passive viewers (passive: 0.25 +/- 0.03 STE; active:

0.31 +/- 0.03 STE; *p* < 0.001). Conversely, the estimated marginal effect of salience was

greater in the passive condition than in the active condition (passive estimate: 0.20 +/-

0.03 STE; active estimate: 0.15 +/- 0.03 STE; *p* < 0.001). Taken together, these results

show that active viewing conditions specifically increase attentional allocation to

semantically relevant regions of a visual environment.

Control analyses confirmed that these results could be attributed to active

affordances rather than passive viewers' limitations. First, we found that the

disproportionate advantage for meaning-guided attention in the active condition remained

significant even after restricting our analysis to the fields of view containing regions

ranked in the top 50[th] percentile for meaning, thereby eliminating less meaningful scene

regions that passive viewers were required to scan as a result of the panning image

presentation (Supplemental Table 1). Second, we found that our results held even when

accounting for neighboring fixations in the active condition whose combined duration

exceeded the time any given scene region would have been displayed to a participant in

the passive condition (5s). In fact, we found that participants in the active condition rarely

fixated within a region for longer than it would have been displayed during the passive

condition (< 3% of fixations), even when accounting for return fixations. Thus, as

predicted, in the active condition, when participants were free to move their head and

body, participants' attention was disproportionately directed towards semantically

relevant regions of a visual environment.

We further characterized gaze behavior during active viewing using two measures

of the spatial distribution of attention that are independent of individual scene content: 1)

deviation from center bias and 2) entropy. Studies of visual attention using traditional fixed

displays commonly observe a bias to fixate near the center of an image (Tatler, 2007;

Bindemann, 2010). Although the precise source of this bias is disputed (Parkhurst et al.,

2002; Schumann et al., 2008; Tseng et al., 2009), deviation from "center bias" has been

used to describe the degree of visual exploration (Gameiro et al., 2017). On average, we

found that fixations made in the active condition had less center bias, or were further from

the equator (Sitzmann et al., 2018), (17.13 degrees +/- 0.54 STE) than fixations made in

the passive condition (12.53 degrees +/- 0.23 STE) (t(39) = 9.98, p < 0.001; Figure 4). Of

course, this result could reflect a systematic, non-central bias (e.g., active viewers could

have routinely looked toward the poles), rather than more exploratory gaze behavior *per*

se. To address that possibility, we used a second measure, entropy, a measure of

homogeneity (or lack thereof) in the probability distribution of fixations (Açik et al., 2010),

to test whether any systematic biases occurred in each viewing condition. We found that

gaze behavior in the active condition was more entropic (3.49 +/- 0.07 STE) than gaze in

the passive condition (2.88 +/- 0.02 STE) (t(39) = 8.63, p < 0.001). Taken together, these

results further demonstrate that active viewers prioritize rapid exploration of new scene

regions that are rich in semantic content, relative to passive viewers.

Finally, we sought to characterize the eye movements participants made in service

of this increase in information-seeking behavior (Figure 4). Participants made shorter

(0.27s +/- 0.004 STE) and more frequent (29.45 +/- 0.34 STE) fixations in the active as

compared with the passive condition (size: 0.39s +/- 0.008 STE, $t(39) = -14.52$, $p < 0.001$;

frequency: 26.60 +/- 0.31 STE, $t(39) = 7.53$, $p < 0.001$. Further, active viewing conditions

impacted the magnitude of gaze shifts (i.e., the combined movement of eyes and head

between two fixations) participants made while exploring their environment. Gaze shifts

were significantly larger in the active condition (29.17 DVA +/- 0.48 STE) as compared

with the passive condition (19.08 DVA +/- 0.23 STE: $t(39) = 23.11$, $p < 0.001$). Indeed, it

was not uncommon for active viewers to make gaze shifts as large as 150 DVA,

exceeding previous saccade length estimates from fixed display studies (5-10 DVA) by

an order of magnitude (Land and Hayhoe, 2001; Tatler et al., 2006). Notably, our

headmounted display subtended a wider field of view (100 DVA) than typically afforded

by fixed display studies. Importantly, this wide display was matched for both active and

passive conditions; thus, the differences we observed cannot be attributed to the size or

content of our stimuli, which is known to impact the size of gaze shifts (Von Wartburg et

al., 2007). Instead, our results demonstrate that active viewing conditions fundamentally

impact the size of gaze shifts a viewer will routinely choose to make when exploring a

real-world visual environment: people make faster fixations and larger gaze shifts, once

more suggesting more exploratory gaze behavior.

Discussion

Our results provide novel insights into the process by which we actively construct representations of immersive, real-world visual environments. We found that, when participants are unconstrainted and free to choose their field of view, their behavior is most guided by meaningful, semantic properties of the environment, as compared with passive viewers. Moreover, in service of this information-seeking behavior, active viewers employ shorter, more entropic fixations. All in all, we demonstrate that active viewing conditions impact nearly all features of gaze behavior, from gaze mechanics (how we move our eyes) to gaze dynamics (what we choose to attend to). These findings lay the foundation for future studies of gaze behavior in immersive, real-world environments using VR.

The recent development of eye-tracking in immersive VR is a critical advance for investigating real-world scene processing in the context of natural behavioral affordances. VR frees the subject from the limitations typically imposed by head-restricted display studies, allowing for eye, head, and body movements (Hayhoe, 2017). Moreover, it does so without sacrificing experimental control, allowing for the presentation of a diverse set of stimuli within precise trial structures. Such stimulus diversity and controlled presentation is an essential ingredient for quantitative, model-based insights into active human gaze behavior. This opportunity for experimental control and diverse stimulus presentation stands in contrast to mobile eye-tracking paradigms, where participants might only traverse a single, extended environment (e.g., a university campus) in which the low-level visual features (e.g., the lighting/contrast) as well as high-level visual features (e.g., people walking down the street) inevitably vary between participants.

Previous approaches comparing active versus passive viewing have relied on a

combination of fixed-display and mobile paradigms (Foulsham et al., 2011; Peterson et

al., 2016), which inherently differ in terms of task demands (e.g., watching a video vs.

navigating) and displayed field of view. All in all, eye-tracking in immersive VR is an

exciting opportunity to gain insight into active visual cognition.

Our findings have multiple implications for active, real-world vision. Recent studies

have proposed a dominant role for semantically meaningful scene regions in guiding

attention even during passive viewing of fixed-display images, suggesting that gaze

behavior primarily reflects high-level information-seeking priority as scene understanding

unfolds (Henderson and Hayes, 2017, 2018; Henderson et al., 2018). Our results extend

these findings in three key ways. First, we show that semantically relevant features guide

attention in immersive, naturalistic environments. This is an important demonstration if

semantically guided attention is indeed a feature of real-world vision. Second, we show

that active viewing conditions increase the advantage for semantics over low-level visual

salience in guiding gaze behavior. Again, this finding has important implications for real-

world vision; our results suggest that when participants are free to seek out information

and choose their field of view, their behavior is most guided by meaningful, semantic

properties of the scene. Finally, our findings provide key benchmark measurements of

gaze behavior in diverse, real-world scenes during active viewing conditions,

demonstrating that active viewers make quick, entropic fixations and shift their gaze

nearly twice per second.

We attribute the observed increase in exploratory, information-seeking behavior in

active viewing conditions to differences in the *affordances* available to active viewers, not

differences in their *action goals*. Our experiment manipulated self- vs. image-generated

motion, but not participants' task, a factor long understood to impact gaze behavior

(Yarbus, 1967; Ballard and Hayhoe, 2009; Kollmorgen et al., 2010). Participants in the

active condition had no objective to physically interact with meaningful scene regions,

such as objects; nor was this a possibility. Yet, access to a naturalistic behavioral

repertoire – a broader capacity for self-generated action – nonetheless impacted how

participants moved their eyes and deployed their attention. Our results are consistent with

theoretical models linking perceptual processing and motor plans in a perception-action

cycle (Wolpert and Landy, 2012), in which perceptual processes depend on movement

states (Chiappe et al., 2010; Maimon et al., 2010; Jung et al., 2011; Matthis et al., 2018)

and the role of vision is to provide evidence to satisfy behavioral goals (Hayhoe, 2017).

These findings have important implications for future work investigating cognitive

processes where motor goals are often hampered by less naturalistic paradigms, such as

scene perception, spatial memory, and even social inference.

Of course, our experimental approach also has drawbacks. The design of our

passive condition was limited by the known tendency for image-generated motion to

induce participant motion sickness (Pan and Hamilton, 2018). As a result, we opted to

implement a passive condition that slowly revealed the panoramic environments to

participants, giving passive viewers the opportunity to explore the same fields of view as

active viewers, but did not provide an exact match for the sequence of moment-to-

moment fields of view that an active viewer would have taken in a scene. We do not think

that these limitations significantly impacted our results. Both semantic and salient scene

features were equally distributed around our panoramic scenes, participants in both

conditions were given an equal amount of time to explore each environment, and our

control analyses demonstrate that active viewers rarely, if ever, dwelled on any portion of

the panoramic scene for longer than it would have been displayed to a passive viewer.

Thus, the disproportionate advantage for meaning over salience in predicting gaze

behavior during active viewing conditions can be attributed to which scene features a

participant chose to attend to in any field of view, rather than which fields of view active

vs. passive viewers sampled during a trial. In our active condition, we were limited by the

challenge of self-embodiment (Pan and Hamilton, 2018): participants could move their

eyes, head, and body, but their movements were not paired with the typical visual

experience of seeing one's body. It is possible that our results would strengthen if the

perception of self-embodiment were afforded to active viewers, as in real-world viewing

conditions. Finally, given the free viewing nature of our experiment, we cannot rule out

the possibility that our effects are mediated by differences in attentional engagement

between our two conditions, particularly given that VR was a novel experience for most

participants.

In sum, our results provide a window into active vision during first-person

exploration of immersive, real-world scenes. These findings bring into focus the

importance of naturalistic behavioral affordances for studies of visual cognition, and also

raise important question for future research. For example, how do differences in

attentional deployment during active vision impact subsequent memory of immersive

environments, or the body-based representation of such environments (Robertson et al.,

2016; Huffman and Ekstrom, 2019)? How might attentional markers of clinical conditions,

such as autism (Robertson et al., 2013; Wang et al., 2015), be altered by natural

behavioral affordances? All in all, we show that active viewing influences every aspect of

gaze behavior, from the way we move our eyes to what we choose to attend to.

Acknowledgements

This study was supported by a grant from the Nancy Lurie Marks Family Foundation to C.E.R and the donation of a Titan V GPU by the NVIDIA Corporation to C.E.R. Thanks to Michael Cohen for insightful comments on the manuscript. Thanks also to George Wolford, Anna Mynick, Nancy Kanwisher, Brad Duchaine, and Adam Steel for helpful discussion about the project.

References

References

Açik A, Sarwary A, Schultze-Kraft R, Onat S, König P (2010) Developmental changes in

natural viewing behavior: Bottomup and top-down differences between children,

young adults and older adults. Front Psychol 1.

Ballard DH, Hayhoe MM (2009) Modelling the role of task in the control of gaze. Vis cogn

17:1185–1204.

Bates D, Mächler M, Bolker BM, Walker SC (2015) Fitting linear mixed-effects models

using lme4. J Stat Softw 67.

Bindemann M (2010) Scene and screen center bias early eye movements in scene

viewing. Vision Res 50:2577–2587.

Chiappe ME, Seelig JD, Reiser MB, Jayaraman V (2010) Walking modulates speed

sensitivity in drosophila motion vision. Curr Biol 20:1470–1475.

Cognolato M, Atzori M, Müller H (2018) Head-mounted eye gaze tracking devices: An

overview of modern devices and recent advances. J Rehabil Assist Technol Eng

5:205566831877399.

Ehinger B V., Groß K, Ibs I, König P (2019) A new comprehensive eye-tracking test

battery concurrently evaluating the Pupil Labs glasses and the EyeLink 1000. PeerJ

2019:e7086.

Foulsham T, Walker E, Kingstone A (2011) The where, what and when of gaze allocation

in the lab and the natural environment. Vision Res 51:1920–1931.

Gameiro RR, Kaspar K, König SU, Nordholt S, König P (2017) Exploration and

Exploitation in Natural Viewing Behavior. Sci Rep 7:1–23.

Goldberg ME, Wurtz RH (1972) Activity of superior colliculus in behaving monkey. I.

Visual receptive fields of single neurons. J Neurophysiol 35:542–559.

Greene MR, Oliva A (2009) Recognition of natural scenes from global properties: Seeing

the forest without representing the trees. Cogn Psychol 58:137–176.

Gutiérrez J, David E, Rai Y, Le Callet P (2018) Toolbox and dataset for the development

of saliency and scanpath models for omnidirectional/360 • still images. Signal

Process Image Commun 69:35–42.

Harel J, Koch C, Perona P (2007) Graph-based visual saliency. In: Advances in Neural

Information Processing Systems, pp 545–552.

Hayhoe MM (2017) Vision and Action. Annu Rev Vis Sci 3:389–413.

Hayhoe MM, Matthis JS (2018) Control of gaze in natural environments: effects of

rewards and costs, uncertainty and memory in target selection. Interface Focus

8:20180009.

Held R, Hein A (1963) Movement-produced stimulation in the development of visually

guided behavior. J Comp Physiol Psychol 56:872–876.

Henderson JM (2007) Regarding Scenes. Curr Dir Psychol Sci 16:219–222.

Henderson JM, Hayes TR (2017) Meaning-based guidance of attention in scenes as

revealed by meaning maps. Nat Hum Behav 1.

Henderson JM, Hayes TR (2018) Meaning guides attention in real-world scene images:

Evidence from eye movements and meaning maps. J Vis 18:10.

Henderson JM, Hayes TR, Rehrig G (2018) Meaning Guides Attention during Real-World

Scene Description. :1–9.

Huffman DJ, Ekstrom AD (2019) A Modality-Independent Network Underlies the Retrieval

of Large-Scale Spatial Environments in the Human Brain. Neuron 0.

Itti L, Koch C (2000) A saliency-based search mechanism for overt and covert shifts of

visual attention. Vision Res 40:1489–1506.

John B, Raiturkar P, Le Meur O, Jain E (2019) A Benchmark of Four Methods for

Generating 360° Saliency Maps from Eye Tracking Data. Int J Semant Comput

13:329–341.

Jung SN, Borst A, Haag J (2011) Flight activity alters velocity tuning of fly motion-sensitive

neurons. J Neurosci 31:9231–9237.

Kaspar K, Hloucal TM, Kriz J, Canzler S, Gameiro RR, Krapp V, König P (2013) Emotions'

Impact on Viewing Behavior under Natural Conditions. PLoS One 8.

Kollmorgen S, Nortmann N, Schröder S, König P (2010) Influence of Low-Level Stimulus

Features, Task Dependent Factors, and Spatial Biases on Overt Visual Attention

Friston KJ, ed. PLoS Comput Biol 6:e1000791.

Land MF, Hayhoe M (2001) In what ways do eye movements contribute to everyday

activities? In: Vision Research, pp 3559–3565.

Maimon G, Straw AD, Dickinson MH (2010) Active flight increases the gain of visual

motion processing in Drosophila. Nat Neurosci 13:393–399.

Matthis JS, Yates JL, Hayhoe MM (2018) Gaze and the Control of Foot Placement When

Walking in Natural Terrain. Curr Biol 28:1224-1233.e5.

Pan X, Hamilton AF d. C (2018) Why and how to use virtual reality to study human social

interaction: The challenges of exploring a new research landscape. Br J Psychol

109:395–417.

Parkhurst D, Law K, Niebur E (2002) Modeling the role of salience in the allocation of

overt visual attention. Vision Res 42:107–123.

Peterson MF, Lin J, Zaun I, Kanwisher N (2016) Individual differences in face-looking

behavior generalize from the lab to the world. J Vis 16:1–18.

Robertson CE, Hermann KL, Mynick A, Kravitz DJ, Kanwisher N (2016) Neural

Representations Integrate the Current Field of View with the Remembered 360°

Panorama in Scene-Selective Cortex. Curr Biol 26:2463–2468.

Robertson CE, Kravitz DJ, Freyberg J, Baron-Cohen S, Baker CI (2013) Tunnel Vision:

Sharper Gradient of Spatial Attention in Autism. J Neurosci 33:6776–6781.

Schumann F, Einhäuser-Treyer W, Vockeroth J, Bartl K, Schneider E, König P (2008)

Salient features in gaze-aligned recordings of human visual input during free

exploration of natural environments. J Vis 8.

Sitzmann V, Serrano A, Pavel A, Agrawala M, Gutierrez D, Masia B, Wetzstein G (2018)

Saliency in VR: How Do People Explore Virtual Environments? IEEE Trans Vis

Comput Graph 24:1633–1642.

Tatler BW (2007) The central fixation bias in scene viewing: Selecting an optimal viewing

position independently of motor biases and image feature distributions. J Vis 7.

Tatler BW, Baddeley RJ, Vincent BT (2006) The long and the short of it: Spatial statistics

at fixation vary with saccade amplitude and task. Vision Res 46:1857–1862.

Trewartha KM, Case S, Flanagan JR (2015) Integrating actions into object location

memory: A benefit for active versus passive reaching movements. Behav Brain Res

279:234–239.

Troncoso XG, McCamy MB, Jazi AN, Cui J, Otero-Millan J, Macknik SL, Costela FM,

Martinez-Conde S (2015) V1 neurons respond differently to object motion versus

motion from eye movements. Nat Commun 6:8114.

Tseng PH, Carmi R, Cameron IGM, Munoz DP, Itti L (2009) Quantifying center bias of

observers in free viewing of dynamic natural scenes. J Vis 9:4–4.

Voloh B, Watson M, Koenig S, Womelsdorf T (2019) MAD saccade: statistically robust

saccade threshold estimation. psyarxiv:2–7.

Von Wartburg R, Wurtz P, Pflugshaupt T, Nyffeler T, Lüthi M, Müri RM (2007) Size

matters: Saccades during scene perception. Perception 36:355–365.

Wang S, Jiang M, Duchesne XM, Laugeson EA, Kennedy DP, Adolphs R, Zhao Q (2015)

Atypical Visual Saliency in Autism Spectrum Disorder Quantified through Model-

Based Eye Tracking. Neuron 88:604–616.

Wass S V, Smith TJ, Johnson MH (2013) Parsing eye-tracking data of variable quality to

provide accurate fixation duration estimates in infants and adults. Behav Res

Methods 45:229–250.

Wilming N, Betz T, Kietzmann TC, König P (2011) Measures and Limits of Models of

Fixation Selection Wennekers T, ed. PLoS One 6:e24038.

Wolfe JM, Horowitz TS (2017) Five factors that guide attention in visual search. Nat Hum

Behav 1:58.

Wolpert DM, Landy MS (2012) Motor control is decision-making. Curr Opin Neurobiol

22:996–1003.

Yarbus AL (1967) Eye Movements and Vision. Springer US.

Figure 1. Passive viewing condition vs. active viewing condition. On each trial, participants viewed immersive, 360° real-world scenes via a headmounted VR display while gaze position was monitored using an in-headset eye-tracker. **A)** In the passive condition, participants were head-restricted using a chin rest, and scenes panned across the display. **B)** In the active condition, participants explored scenes from a first-person perspective through movement of their eyes, head, and body.

Figure 2. Comparing salience and meaning maps to gaze behavior. A) Each photosphere was first decomposed into smaller undistorted image tiles. Next, we created two models of the content in each real-world environment. **B)** "Salience maps" were generated by modeling low-level visual features for each tile using the GBVS Toolbox(Harel et al., 2007). Each tile was then projected onto a two-dimensional salience map. **C)** "Meaning maps" were generated via online participants who rated the semantic content, or "meaning" of each image tile. Each tile's rating was then projected onto a two-dimensional meaning map. **D)** Group gaze maps were trimmed (vertically) to match the passive condition field of view. **E)** Points are sampled evenly on a sphere and used to account for photosphere distortion in two-dimensional maps. **F)** A linear mixed effects model was used to compare the degree to which each model predicted attentional guidance in our two conditions.

Figure 3. Active viewing increases top-down attentional allocation. Estimated marginal effects of salience and meaning maps on predicting overt attention in each condition (active vs. passive). We found that viewing condition (active vs. passive) significantly modulated gaze behavior (salience*meaning*condition: $p < 0.001$). Specifically, active viewers disproportionately directed their attention to meaningful, over salient, scene regions. Individual points represent random item effects (i.e., individual scenes). Error bars represent prediction intervals (+/- 1 STE). *** denotes $p < 0.001$.

Figure 4. Active viewing impacts eye movements. A) Relative to fixations made in the passive viewing condition, fixations in the active viewing condition were shorter B) and more frequent. C) Gaze shifts in the active viewing condition were also larger, and D) the spatial distribution of gaze in the active viewing condition was less centrally tending. E) Sample duration-weighted fixations and gaze shifts made by a single participant (top) and group fixation map for participants (bottom) per condition. *** denotes $p < 0.001$.

612 **Table 1: Linear mixed effects model results summary.**
613

	numDF	denDF	*F* value	*p* value
condition	1	6163960	8818.25	< 0.001
meaning	1	6163907	71586.82	< 0.001
salience	1	6163982	19920.19	< 0.001
condition:meaning	1	6163960	21579.7	< 0.001
condition:salience	1	6163960	212.22	< 0.001
meaning:salience	1	6163997	64200.96	< 0.001
condition:equator	2	6163980	485605.49	< 0.001
condition:meaning:salience	1	6163960	71.36	< 0.001

Supplemental Figure 1. Gaze measured in 360 is accurate and precise.

Three head-fixed participants made a series of saccades from a central fixation cross to 16 targets arranged

in a cross and spanning the entire headmounted display's field of view. Targets were located above, below,

and to the right and left of screen center, and were located at distances of 10, 20, 30, and 40 DVA in each

direction. Each observer completed this task six times, over separate sessions. The mean accuracy across

observers and locations was 2.00 DVA +/- 0.38 STE, and the mean precision across observers and

locations was 0.26 DVA +/- 0.05 STE. Eye-tracking accuracy decreased with eccentricity ($F(1, 6.126) =$

$58.175, p < 0.001$); however, gaze measured at screen center was accurate within <1 DVA, comparable to

the reported accuracy of many mobile eye-tracking systems(Cognolato et al., 2018).

Supplemental Figure 2. Experimental Stimuli.

Supplemental Table 1: Control analysis results summary. Meaning:salience:condition interaction

remains significant when restricting analysis to the fields of view containing regions ranked in the top 50[th]

percentile for meaning.

	NumDF	DenDF	*F* value	*p* value
condition	1	5935512	6.78E+03	< 0.001
meaning	1	5935478	6.89E+04	< 0.001
salience	1	5935534	1.98E+04	< 0.001
condition:meaning	1	5935512	2.21E+04	< 0.001
condition:salience	1	5935512	3.39E+00	0.0656
meaning:salience	1	5935548	6.07E+04	< 0.001
condition:equator	2	5935532	4.37E+05	< 0.001
condition:meaning:salience	1	5935512	4.34E+02	< 0.001

635 **Supplemental Table 2: Control analysis results summary.** Meaning:salience:condition interaction

636 remains significant when accounting for groups of fixations in the active condition whose combined

637 duration exceeded 5 seconds.

	NumDF	DenDF	*F* value	*p* value
condition	1	6163960	1.46E+04	< 0.001
meaning	1	6163922	8.20E+04	< 0.001
salience	1	6163986	1.24E+04	< 0.001
condition:meaning	1	6163960	2.71E+04	< 0.001
condition:salience	1	6163960	3.76E+02	< 0.001
meaning:salience	1	6163998	4.75E+04	< 0.001
condition:equator	2	6163980	4.71E+05	< 0.001
condition:meaning:salience	1	6163960	1.49E+03	< 0.001