Oscillatory and aperiodic neural activity jointly predict language learning

Zachariah R. Cross[1*], Andrew W. Corcoran[1,2,3], Matthias Schlesewsky[1], Mark. J. Kohler[1,4], Ina Bornkessel-Schlesewsky[1]

[1]Cognitive Neuroscience Laboratory - Australian Research Centre for Interactive and Virtual Environments, University of South Australia, Adelaide, Australia.
[2]Cognition and Philosophy Laboratory, Monash University, Melbourne, Australia.
[3]Monash Centre for Consciousness & Contemplative Studies, Monash University, Melbourne, Australia.
[4]Faculty of Health and Medical Sciences, Adelaide University, Adelaide, Australia.

Corresponding author: Zachariah R. Cross, Room H1-06C, University of South Australia Magill Campus, St Bernards Road, Magill, SA 5072, Australia. E-mail: Zachariah.Cross@unisa.edu.au

Manuscript details

Number of pages:	41
Number of figures:	8
Abstract word count:	201
Introduction word count:	678
Discussion word count:	2,687
Data and code available at:	https://osf.io/7yr46/

Acknowledgements: Preparation of this work was supported by Australian Commonwealth Government funding awarded to ZRC and AWC under the Research Training Program. IB-S is supported by an Australian Research Council Future Fellowship (FT160100437). AWC is supported by the Three Springs Foundation. We thank Isabella Sharrad, Lena Zou-Williams, Erica Wilkinson, Nicole Vass and Angela Osborn for help with data collection. Thank you also to the participants.

Conflict of interest statement: The authors declare no competing financial interests.

Abstract

Memory formation involves the synchronous firing of neurons in task-relevant networks, with recent models postulating that a decrease in low frequency oscillatory activity underlies successful memory encoding and retrieval. However, to date, this relationship has been investigated primarily with face and image stimuli; considerably less is known about the oscillatory correlates of complex rule learning, as in language. Further, recent work has shown that non-oscillatory ($1/f$) activity is functionally relevant to cognition, yet its interaction with oscillatory activity during complex rule learning remains unknown. Using spectral decomposition and power-law exponent estimation of human EEG data (17 females, 18 males), we show for the first time that $1/f$ and oscillatory activity jointly influence the learning of word order rules of a miniature artificial language system. Flexible word order rules were associated with a steeper $1/f$ slope, while fixed word order rules were associated with a shallower slope. We also show that increased theta and alpha power predicts fixed relative to flexible word order rule learning and behavioural performance. Together, these results suggest that $1/f$ activity plays an important role in higher-order cognition, including language processing, and that grammar learning is modulated by different word order permutations, which manifest in distinct oscillatory profiles.

Keywords: language learning • neural oscillations • aperiodic activity • sentence processing • EEG • artificial grammar

Introduction

Memory supports many essential cognitive functions, from learning the distinction between

semantic categories (e.g., animal vs. human) to complex (motor) sequences, such as learning how to

drive a car or speak a new language. However, while a broad literature has related neural oscillatory

dynamics (i.e., [de]synchronisation of neural populations) to the encoding and retrieval of images and

words (e.g., Parish, Hanslmayr, & Bowman, 2018), considerably less is known about oscillatory activity

during the encoding and retrieval of complex sequences, such as in language (cf. de Diego-Balaguer,

Fuentemilla, & Rodriguez-Fornells, 2011; Kepinska, Pereda, Caspers, & Schiller, 2017). Further, the

few studies examining sequence and artificial language learning report mixed findings relative to

(episodic) word and image paradigms: while alpha/beta desynchronisation in the human EEG predicts

encoding of words and images (e.g., Griffiths, et al., 2019), alpha/beta and theta synchronisation is

associated with sequence (Crivelli-Decker et al., 2018) and language learning (e.g., Kepinska et al.,

2017). This apparent inconsistency might be accounted for by stimulus heterogeneity; however, another

possible source of divergence may lie in the mixture of oscillatory power with aperiodic activity

(Ouyang et al., 2020; Wen & Liu, 2016), which has not been addressed in studies on the neural basis of

complex rule learning to date.

Electrophysiological brain activity exhibits a $1/f$-like power distribution, which is often

removed from the signal to isolate transient task-related oscillations (Donoghue et al., 2020; He, 2014;

Lendner et al., 2020). However, this aperiodic component has recently been implicated in a variety of

higher-order cognitive computations (Fellner et al., 2019), partially explaining individual differences

in theta activity during memory encoding and recall performance (Sheehan et al., 2018), and processing

speed over and above that of alpha activity (Ouyang et al., 2020). Work on prediction during language

has also shown that the aperiodic slope – but not oscillatory activity – influences the N400 event-related

potential and performance accuracy (Dave et al., 2018).

These findings suggest that aperiodic brain activity plays a critical functional role in the

neurobiology of cognition (He et al., 2010); however, it is currently unknown whether oscillatory and

aperiodic activity interact during memory encoding of information beyond single words and images,

such as rule-based sequence learning, and whether any such interaction influences behavioural

outcomes. Clarifying the (separable) roles of oscillatory and aperiodic components of the EEG power

spectrum may also bridge diverging results reported in studies using image and word stimuli and

artificial grammar paradigms, lending support to the idea that neural oscillations differentially

contribute to memory formation.

To better characterise the neural mechanisms underlying complex rule learning, we examined

fluctuations in delta, theta, alpha and beta power during an artificial language learning task. We also

modelled the interaction between oscillatory and aperiodic activity to characterise how patterns of

(de)synchronisation and aperiodic fluctuation influence the generalisation of different word order rules

characteristic of many natural languages. Healthy young adults learned the artificial miniature language

Mini Pinyin (Cross, Zou-Williams, Wilkinson, Schlesewsky, & Bornkessel-Schlesewsky, 2020a)

without explicit instruction and then completed a sentence judgement task. Critically, participants –

who were native monolingual English speakers – learned fixed and flexible word order rules: fixed

word order sentences contained temporal- or sequence-based rules, while flexible word order sentences

involved non-adjacent dependencies, likely relying on more associative- than sequence-based memory

processing mechanisms (Cross et al., 2018). From this perspective, we were able to probe different

learning and memory mechanisms that are involved in sentence comprehension (Bornkessel-

Schlesewsky, Schlesewsky et al., 2015). For example, native English speakers typically rely on word-

order-based cues for sentence comprehension, whereas speakers of Mandarin Chinese or the Australian

language Jiwarli rely more strongly on cues other than word order, such as case marking and/or

semantic information, including animacy (Austin, 2001; Bates et al., 2001; Bornkessel-Schlesewsky et

al., 2011).

We recorded EEG during the learning task, implementing generalised additive and linear

mixed-effects regression analyses to model dynamic changes in oscillatory and aperiodic activity during

the learning of the fixed and flexible word order rules. We also modelled learning-related oscillatory

and aperiodic activity to predict subsequent behavioural performance on the sentence judgement task,

quantified as the sensitivity index d'.

 Method

Participants

Data from 36 right-handed healthy, monolingual, native English-speakers were used from a

study examining the effect of sleep on language learning (Cross et al., 2021). This sample size was

based on previous EEG research examining the neural correlates of higher-order language learning (de

Diego-Balaguer et al., 2011; Kepinska et al., 2017; Mueller et al., 2005). One participant was excluded

from analysis for not having electroencephalography recorded during the sentence learning task due to

experimenter error. The final sample size was 35 (M_{age} = 25.3, SD = 7.13; 17 female). Ethics approval

was granted by the University of South Australia's Human Research Ethics committee (I.D.:

0000032556).

Stimuli and experimental design

Stimuli were based on the modified miniature language Mini Pinyin (for a detailed description

of the language, see Cross et al., 2020a; see also Cross et al., 2021), which contains grammatical rules

present in a number of natural languages (see Figure 1A and 1B for example sentence constructions

and vocabulary items). Briefly, each sentence in Mini Pinyin contains two noun phrases and a verb, and

each noun is associated with a different classifier: human nouns are preceded by *ge*, while animals, and

small and large objects are preceded by *zhi*, *xi* and *da*, respectively.

Mini Pinyin includes two main sentence types based on whether the sentence contains the

coverbs *ba* and *bei*. Here we focus on the coverb *ba*: when *ba* is present, the sentence contains a fixed

word order, in that the first noun phrase is invariably the Actor (the active, controlling participant in the

action described by the sentence) and the sentence must be verb final. In this context, accurate sentence

processing is dependent on the linear position of the words. When *ba* is not present, the sentence

contains a flexible word order, in that the first noun phrase can either be the Actor or the Undergoer

(the affected participant); however, the sentence must be verb-medial (i.e., verb must be positioned

between the noun phrases). As such, accurate sentence interpretation is based more heavily on the

animacy status of the noun phrases rather than word order. These manipulations are illustrated below,

with a flexible word order shown in 1a and 1b and fixed (i.e., with the coverb *ba*) shown in 2:

(1)

162   (a) ge yisheng dale da piqiu.

163   (human) doctor hit (object) ball.

164   "the doctor hits the ball."

165   (b) da xianjiao chile zhi laoshu.

166   (object) banana eat (animal) rat.

167   "the rat eats the banana."

168   (2)

169   ge xiaofang ba da shubao liangle.

170   (human) firefighter ba (object) bag measure.

171   "the firefighter measures the bag."

The experiment contained three phases: a vocabulary test, a learning phase, and a

grammaticality judgement task. Approximately seven days before the sentence learning phase,

participants received a paired picture-word vocabulary booklet containing the 25 nouns. Participants

were required to learn the 25 nouns to ensure that they had a basic vocabulary. Prior to the learning and

judgement tasks, participants completed the vocabulary test on a desktop computer by typing in

translations of the nouns from Mini Pinyin to English. Only participants who attained a score > 90%

were eligible to undertake the learning and judgement task phases of the experiment. All 35 participants

achieved 90% accuracy on the vocabulary task and thus completed the main experimental session.

Overall, 576 unique sentences (288 grammatical, 288 ungrammatical) were created and divided into

two equivalent sets.

We focus here on a subset of sentence conditions to investigate the mechanisms underlying the

learning of different word order permutations (for EEG analyses during the sentence judgement task,

see Cross et al., 2021). While no explicit instructions were given to participants in regard to the structure

of the miniature language, a picture was shown prior to each sentence illustrating an event occurring

between two entities, which was then described in the subsequently presented sentence. The learning

task contained four blocks with 128 grammatical picture-sentence pairs overall (96 of which were

included in the subset analysed here) that were presented via rapid visual serial presentation. The subset

contained a further 156 novel sentences (50% grammatical, 50% ungrammatical) that were presented

during the judgement task, which occurred immediately after the learning phase. The remaining

sentences were considered fillers. The ungrammatical sentences induced a violation at either the

position of the Actor or verb in fixed word order sentences (e.g., Actor-ba-Verb-Undergoer [AbaVU]

instead of AbaUV) or the position of the verb in flexible word order sentences (e.g., AUV instead of

AVU; see Figure 1A for an illustration and full list of ungrammatical constructions).

During the learning phase, each picture was presented for 5000ms, while each corresponding

sentence was presented on a word-by-word basis, with each word presented for 700ms with an inter-

stimulus interval (ISI) of 200ms. Across the four blocks, each grammatical construction was presented

32 times, with stimuli pseudo-randomised such that no sentences of the same construction followed

each other. During the judgement task, novel grammatical and ungrammatical sentences were presented

word-by-word with a presentation time of 600ms and an ISI of 200ms. Participants responded via a

button press to indicate whether the sentence conformed to the rules of Mini Pinyin. The assignment of

grammatical/ungrammatical response buttons was counterbalanced across participants. Response time

windows were presented for a maximum of 4000ms. Participants received feedback on whether their

response was correct or incorrect (see Figure 1C and 1D for a schematic of the learning and judgement

tasks, respectively). Both the learning and judgement tasks were created in OpenSesame (Mathot et al.,

2012) and performed on a desktop computer.

(A) Grammatical and Ungrammatical Sentence Constructions

Grammatical:

AVU:	ge shuishou zhuole zhi maomi
UVA:	zhi maomi zhuole ge shuishou
AbaUV:	ge shuishou ba zhi maomi zhuole

Ungrammatical:

UbaAV:	zhi maomi ba ge shuishou zhuole
AbaVU:	ge shuishou ba zhuole zhi maomi
AUV:	ge shuishou zhi maomi zhuole
UAV:	zhi maomi ge shuishou zhuole

English Translation: the sailor captures the cat

(B) Sample of Linguistic Elements from Mini Pinyin and English Translations

Classifier	:	ge (human), zhi (animal), da (large object), xi (small object)
Noun	:	shuishou (sailor), maomi (cat), junma (pirate), pingguo (apple)
Coverb	:	ba (actor-undergoer-verb)
Verb	:	zhoule (capture), xile (wash), zhaole (photograph), chile (eat)

Figure 1. (A) Summary of the grammatical (left) and ungrammatical (right) sentence constructions. (B) A portion of linguistic elements used in the sentence examples provided in (A). (C) Schematic of the sequence of events occurring in the sentence learning phase. (D) Schematic of the sequence of events occurring in the sentence judgement task.

EEG recording and pre-processing

Participants' EEG was recorded using a 32-channel BrainCap with sintered Ag/AgCl electrodes (Brain Products, GmbH, Gilching, Germany) mounted according to the extended International 10-20 system. The online reference was located at FCz. The ground electrode was located at AFz. The electrooculogram (EOG) was recorded via electrodes located at the outer canthus of each eye and above and below participants' left eye. The EEG was amplified using a BrainAmp DC amplifier (Brain Products GmbH, Gilching, Germany) with an initial band-pass filter of DC – 250 Hz and a sampling rate of 1000 Hz. Electrode impedances were kept below 10kΩ. EEG was also recorded during two minutes of eyes-open and two minutes of eyes-closed resting-state periods immediately before the learning task and after the judgement task.

EEG analysis was performed in MATLAB 2017b (The MathWorks, Natick, USA) using custom scripts in conjunction with the Fieldtrip toolbox (Oostenveld et al., 2011). EEG data were re-referenced offline to the average of both mastoids and band-pass filtered from 1 – 40 Hz using a two-pass Butterworth IIR filter (implemented in ft_preprocessing). Data were then epoched from -200ms to 13s relative to the onset of each picture-sentence pair for both fixed and flexible sentences, and corrected for ocular artefacts using Infomax Independent Component Analysis (Bell & Sejnowski, 1995; implemented in runica.m). Components demonstrating clear EOG artefacts were removed (median components rejected = 3, range = 2 – 6) and electrodes showing strong artefacts were visually inspected and subsequently interpolated with surrounding electrodes based on spherical spline interpolation (total channels interpolated $n = 2$; Perrin et al., 1989).

EEG data analysis

The aim of the analysis was to characterise the oscillatory and aperiodic dynamics underlying the initial encoding of complex grammatical rules. To this end, we computed differences between fixed and flexible word order sentences in the following five spectral features of the EEG recorded during the learning phase: mean power density within individualised delta, theta, alpha, and beta bands, and the (inverse) slope of the $1/f$ spectral distribution (i.e., power-law exponent). We then used these

metrics to investigate whether trial-level variation in oscillatory power and $1/f$ slope during the learning

task predicted behavioural performance on the judgement task. We also tested whether interactions

between oscillatory and aperiodic activity afford unique information predicting behavioural

performance.

Spectral decomposition and power-law exponent χ estimation

The power-law scaling exponent χ, which summarises the rate of decay of the power spectrum

in double-logarithmic co-ordinates, was estimated using the Irregular-Resampling Auto-Spectral

Analysis toolbox (IRASA v1.0; Wen & Liu, 2016). Briefly, this technique seeks to separate oscillatory

from aperiodic (random fractal) components by iteratively resampling the power spectrum across a

range of non-integer factors h and their reciprocals $1/h$ (here, $h = 1.1$ to 1.95 in steps of 0.05). This

procedure shifts any narrowband components away from their original location along the frequency

spectrum while leaving the distribution of the fractal component intact. The median of the resampled

spectral estimates is then calculated in order to strip the spectrum of narrowband peaks. For a more

detailed treatment of the IRASA method, see Wen and Liu (2016).

Trial data from each EEG channel were divided into two non-overlapping 4500ms segments

corresponding to the picture and sentence presentation phases, respectively. Picture segments were

timelocked to 500ms post-stimulus onset; sentence segments were timelocked to 100 ms prior to the

first word onset. Both segments were further subdivided into seven 1800ms epochs (25% overlap) and

separately passed to amri_sig_fractal.m for spectral parameter estimation. Once the fractal component

had been recovered from each power spectrum, it was parameterised using amri_sig_plawfit.m. This

function rescales the frequency spectrum to achieve equally-spaced intervals in log-space before fitting

a linear regression to a subregion of the double-log transformed fractal spectrum (here, ~1.9 – 15.8 Hz,

corresponding to an evaluated frequency range of 1 – 35 Hz; see Gerster et al. 2022, for further details).

The absolute value of the regression slope coefficient was taken as the χ exponent.

To ensure the robustness of our analysis, we compared our estimates of the χ exponent against

those derived using the more recently-developed 'FOOOF' method (Donoghue et al., 2020). Briefly,

this technique attempts to separate narrowband oscillatory peak components from broadband aperiodic

activity by iteratively fitting Gaussian functions to the spectrum, and deleting these components until

no further deviations from background activity can be detected (given a predefined noise threshold).

The χ exponent is then estimated by fitting a regression to the residual spectrum in double-log space,

similar to the IRASA procedure (see Donoghue et al., 2020, for details).

273   Since FOOOF requires PSD estimates (rather than timeseries data) as its input, power spectra

were derived from each epoch using the pwelch.m implementation of Welch's (1967) modified

periodogram method. Epochs were Hann-tapered and zero-padded to 2048 points to facilitate

comparability with IRASA-generated spectral estimates. FOOOF was implemented via the MATLAB

wrapper (v1.0.0) using the following parameter settings: peak width limits = 1 – 12 Hz, maximum

number of peaks = infinite, minimum peak height = 0, peak threshold = 2 S.D., aperiodic mode = fixed,

evaluated frequency range = 1 – 35 Hz.

Spectral band power estimation

281   In order to quantify narrowband changes in spectral power independent of underlying changes

in aperiodic activity, mean power densities were estimated following the subtraction of the mean

regression fit of the aperiodic component from the PSD (spectra averaged across epochs within each

segment). This residual, 'oscillatory' spectrum was half-wave rectified (negative values set to zero) and

divided into the four frequency bands of interest. Notably, the limits of each frequency band were

adapted for each participant on the basis of their resting-state EEG. Specifically, the boundaries of each

frequency band were calculated according to the harmonic frequency architecture proposed by

Klimesch (2012; 2013; and which is in line with previous work, e.g., Corcoran et al., 2018, Doppelmayr

et al., 1998, Sauppe et al., 2021), in which the centre frequency of each successive band constitutes a

harmonic series scaled in relation to the individual alpha frequency (IAF). To avoid the potential overlap

of neighbouring frequency bands, we determined lower and upper frequency bounds using the

following formulae:

293
$$f_1 = f_c - f_c/4,$$

294
$$f_2 = f_c + f_c/2,$$

where f_c is the centre frequency (based on the IAF-scaled harmonic series), f_1 the lower bound, and f_2

the higher bound of a given frequency band.

IAF estimates used to determine f_c were obtained from a set of parieto-occipital electrodes

(P3/P4/O1/O2/P7/P8/Pz/Iz) using the *restingIAF* package (v1.0.3; Corcoran et al., 2019; see also Cross

et al. 2020b). This method applies a Savitzky-Golay filter (frame width = 11 bins, polynomial order =

5) to smooth and differentiate the power spectrum prior to estimating the peak frequency within a

specified frequency range (here, 7—14 Hz). Peak estimates were averaged across channels, with a

minimum of 3 channel estimates required to return an IAF for a given recording. Estimates derived

from pre- and post-session eyes-closed resting states were then averaged for each participant using

meanIAF.m. For further details on this algorithm, see Corcoran and colleagues (2018).

Having determined IAF-anchored bounds for the delta, theta, alpha, and beta bands, power

within each band was quantified using the mean power density metric proposed by Westfall (1990):

$$ P_k = \frac{1}{1 + k_{f_2} - k_{f_1}} \sum_{i=k_{f_1}}^{k_{f_2}} p(f_i), $$

where $p(f_i)$ is the power estimate of the i^{th} frequency bin, and f_1 and f_2 index the lower and upper bounds

of the individualised frequency band k, respectively. An advantage of this approach is that power

estimates are scaled by spectral range, thus controlling for differing frequency bandwidths both within

and between individuals.

Statistical analysis

We used *R* v.4.0.0 (R Core Team, 2020) and the packages *lme4* v.1.1.27.1 (Bates et al., 2015),

lmerTest v.3.1.2 (Kuznetsova et al., 2017), *ggeffects* v.4.1.4 (Lüdecke, 2018), *car* v.3.0.7 (Fox et al.,

2011), *tidyverse* v.1.3.0 (Wickham et al., 2019), *mgcv* v.1.8.36 (Wood, 2006), *mgcViz* v.0.1.9 (Fasiolo

et al., 2019), *rgl* v.0.1.54 (Nenadic & Greenacre, 2007), *ggpubr* v.0.4.0 (Kassambara (2020), *cowplot*

v.1.0.0 (Wilke, 2019), and *eegUtils* v.0.7.0 (Craddock, 2022). For linear models, contrasts for

categorical variables were sum-to-zero contrast coded, with coefficients reflecting deviation from the

grand mean (Schad et al., 2020).

Generalised additive mixed models

Generalized additive models (GAMs) are a nonparametric extension of the standard linear

regression model that substitute a linear predictor variable *x* with a smooth function *f(x)* (Hastie &

Tibshirani, 1987, 1990; Wood, 2017). Generalized additive mixed models (GAMMs; Lin & Zhang,

1999) constitute a further extension that incorporates random effects components within the GAM

framework (Pedersen et al., 2019). Together, these innovations offer an elegant solution to the problem

of autocorrelation amongst residuals induced by (1) attempting to fit linear models to non-linear

relationships, and (2) non-independence (or nesting) of observations (e.g., repeated measures within

participants or items; Baayen et al., 2008).

Here, GAMMs were constructed to investigate how the exponent χ, and the mean power density

P for each k^{th} frequency band (delta, theta, alpha, and beta), fluctuate during artificial grammar learning.

Trial-level χ and P_k estimates from the sentence processing phase of each trial were modelled as a

function of learning time (trial number), sensor space (2D Cartesian co-ordinates), and sentence type

(fixed, flexible). Estimates from the preceding image presentation phase were treated as a baseline

measure of spectral activity. Random factor smooth interactions were included to account for individual

differences in the functional relationship between spectral features and time-on-task (see Baayen et al.,

2017, Corcoran, Macefield, & Hohwy, 2021, for similar approaches). Each GAMM took the following

general form:

$$Y_i = \beta_0 + \beta_1 type_i + \beta_2 baseline_i + f(trial_i, topo.x_i, topo.y_i, by = type_i) +$$

$$f_{subject_i}(time) + \epsilon,$$

where Y_i is the i^{th} observation of spectral feature *Y*, β_0 is the model intercept, $\beta_1 type$ is a factor encoding

the main effect of Sentence Type, $\beta_2 baseline$ is a covariate encoding the corresponding observation for

Y during the baseline period, *f(. ,* by = *type)* is the tensor product interaction between the learning time

(*trial*) and sensor space (*topo.x, topo.y*) covariates for each level of Sentence Type, $f_{subject}$ is the by-

participant factor smooth for time-on-task, and *ε* is a *t* distributed error term (since response variables

were heavy-tailed). Note that marginal smooths for sensor space co-ordinates were treated as isotropic

(i.e., assumed to share a common scale).

GAMMs were estimated using the bam() function of the *R* package mgcv (Wood, 2011).

Models were fit using the Fast REML method. P_k estimates for both the baseline and sentence

processing period were $\log_{10}$ transformed prior to model inclusion. Models were fit with tensor product

interaction smooths in order to enable ANOVA-decomposition of main effect and interaction

components (Wood, Scheipl, & Faraway, 2013). All tensor product smooths were fit using low rank

thin plate regression splines as their basis function (Wood, 2003, 2017). Factor smooths were fit with a

first-derivative penalty in order to shrink participant-level smooths towards the population-level. An

additional shrinkage penalty was imposed on the smoothing penalty null space to enable automated

model reduction (see Marra & Wood, 2011). Type was entered as an ordered factor with Fixed assigned

as the reference level, hence model terms involving a Sentence Type interaction assess the difference

between Fixed and Flexible condition splines (see van Rij et al., 2016).

Linear mixed-effects models

The relationship between aperiodic and oscillatory power during grammar learning with

behavioural performance on the judgement task was assessed using linear mixed-effects models.

Behavioural performance was operationalised using the discrimination index (d'). d' is defined as the

difference between the z transformed probabilities of hit rate (HR) and false alarm rate (FA; i.e.,

d'=z[HR] – z[FA]). These models took the following general form:

$$d'_i = \beta_0 + \beta_1 P_{k_i} * \beta_2 bexp_i * \beta_3 type_i * \beta_4 lat_i * \beta_5 sag_i + participant_{0i} + \epsilon,$$

where P_k is mean baseline-corrected (i.e., sentence presentation – pre-sentence interval) power density

in the frequency band of interest (i.e., delta, theta, alpha, beta), *bexp* is the baseline-corrected (i.e.,

sentence presentation – pre-sentence interval) exponent of the aperiodic $1/f$ slope, *type* refers to

Sentence Type (fixed, flexible), *sag* is Sagittality (anterior, central, posterior) and *lat* refers to Laterality

(left, midline, right). Participant ID (*participant*) was modelled as a random intercept. ε refers to a

Gaussian-distributed error term.

Type II Wald χ^2-tests from the *car* package (Fox et al., 2011) were used to provide *p*-values.

An 83% confidence interval (CI) threshold was adopted for visualisations, which corresponds to the

5% significance level with non-overlapping estimates (Austin & Hux, 2002; MacGregor-Fors &

Payton, 2013). General linear models were performed to assess the relationship between baseline

corrected oscillatory power and aperiodic $1/f$ slope between fixed and flexible word orders. Baseline-

corrected oscillatory power values were $\log_{10}$ transformed prior to model inclusion. All data, as well as

analysis scripts (MATLAB and R) are available on the OSF platform: https://osf.io/7yr46/; Cross,

Corcoran, Schlesewsky, Kohler, &. Bornkessel-Schlesewsky, 2022). For a schematic visualisation of

EEG signal processing and statistical analysis steps, see Figure 2.

Figure 2. Schematic of the EEG recording, pre-processing, signal, and statistical analysis

procedures. a. Neurophysiological signals were recorded at rest and during the sentence learning task

using a 32-channel EEG system. **b.** The EEG signal was filtered, re-referenced and subjected to an

independent component analysis. **c.** The individual alpha frequency (IAF) was estimated per participant

from resting-state EEG recordings based on an occipital-parietal electrode cluster (see topoplot). Peak

frequencies within the alpha band (7-14 Hz; light blue shading) were identified using restingIAF, an

automated procedure that smoothes and differentiates the power spectrum before estimating the average

IAF (dotted line) across selected channels. IAF estimates were subsequently used to calculate

participant-specific delta, theta, alpha and beta centre frequencies (f_c) and bandwidths (f_1, f_2) for the

time-frequency decomposition of the sentence learning task. **d.** (i) Grand-average time-frequency

representation of fixed word order sentences during the learning session. Dashed black boxes

correspond to the presentation of elements in the stimulus train above. (ii) Histograms illustrating the

distribution of the aperiodic exponent and alpha power estimated using FOOOF (pink) and IRASA

(blue). **e.** (i) Single-subject power spectral density (PSD) plots at the beginning (left) and end (right) of

the sentence learning task. Straight turquoise and tan lines represent the IRASA-based aperiodic

regression fit for fixed and flexible word order sentences, respectively. (ii) PSD plots illustrating power

in the IAF-derived delta (δ), theta (θ), alpha (α) and beta (β) bands after subtraction of the aperiodic

regression fit depicted in (i). (iii) Raw data at electrode Cz illustrating the analysis performed to estimate

time-varying modulations in the aperiodic exponent between fixed and flexible word orders. (iv)

scatterplots illustrating the analyses predicting behaviour (i.e., judgement accuracy [d']) from the

sentence judgement task from aperiodic and oscillatory activity derived from the sentence learning task.

<div align="center">

Results

</div>

Task performance

The results on the judgement task are visualised in Figure 3. Participants performed moderately

well on the judgement task, with a mean d' score of 1.02 (range: -1.20 – 3.78) and mean reaction time

of 878.08 ms (range: 254.75 – 2076.83). There is clearly a high degree of inter-individual variability

across both fixed and flexible sentences; however, flexible sentences had greater variability in d' scores,

while fixed grammatical sentences had faster responses overall. For a detailed report and interpretation

of these behavioural data, see Cross et al. (2020a).

Figure 3. Raincloud plots illustrating the behavioural responses during the sentence judgement task.
(A) Mean d' scores (x-axis) for Fixed and Flexible sentence types. (B) Mean reaction time (ms; x-axis)
for Grammatical (left) and Ungrammatical (right) Fixed and Flexible sentence types. Individual data
points represent the mean for each participant, while the lines join within-participant differences
between fixed and flexible word order sentences.

Neurophysiological results

420   Individual alpha frequency estimates varied between participants ($M_{IAF} = 9.78$, *SD* = 0.96),

421 resulting in a range of participant-specific frequency bands (summarised in Table 1). A full list of

422 participant-specific IAFs and frequency bandwidth are available on the OSF repository.

Table 1. Mean lower (f_1) and upper (f_2) frequency bounds for the delta, theta, alpha and beta bands. Participant-specific range provides the lowest and highest frequency band limits based on single-participant estimates, as is also provided for IAF estimates.

Band	Mean f_1 (SD)	Mean f_2 (SD)	Participant-Specific Range
Delta	1.83 (0.18)	3.67 (0.36)	1.42 – 4.33
Theta	3.67 (0.36)	7.34 (0.72)	2.83 – 8.66
Alpha	7.34 (0.72)	14.7 (1.45)	5.67 – 17.33
Beta	14.7 (1.45)	29.4 (2.90)	11.36 – 34.67
IAF	--	--	7.57 – 11.55

Note. SD = standard deviation; IAF = individual alpha frequency. Participant-specific range provides the absolute lowest and upper band limits.

Aperiodic and oscillatory changes across time and space during language learning

Neurophysiological signals are non-stationary, showing dynamic changes over time as a function of endogenous and exogenous factors (e.g., Donoghue, Schaworonkow & Voytek, 2021), such as attentional fluctuations and the complexity of incoming sensory information (Waschke et al., 2021). However, neurophysiological signals are typically analysed using linear models, which often do not capture non-linear modulations in neural activity, particularly over time. Here, we examine how aperiodic and oscillatory dynamics evolve over time during language learning, focusing specifically on the way in which spectral activity varies across sentence types (fixed vs flexible word orders). Estimated changes in aperiodic and oscillatory spectral activity across learning task conditions are illustrated in Figure 5 (for topographical maps, see Figure 6).

Comparisons between IRASA and FOOOF showed that FOOOF provided higher exponent estimates than IRASA, irrespective of sentence type (fixed, flexible; Figure 4) and were also more variable ($M_{FOOOF} = 1.08$, $SD = 0.48$; $M_{IRASA} = 1.00$, $SD = 0.42$). However, exponent estimates between IRASA and FOOOF were highly positively correlated across both fixed ($\rho = 0.75$, $p < .001$, 83% CI = [.63, .84] and flexible ($\rho = 0.76$, $p < .001$, 83% CI = [.63, .85]; Figure 4B) word order sentences. These observations were complemented by a linear mixed-effects regression which revealed that while

446 FOOOF had overall higher exponent estimates than IRASA (β = 0.02, *se* = 0.004, *p* < .001), exponent

447 estimates between FOOOF and IRASA did not vary by sentence type (β = 0.0005, *se* = 0.004, *p* = .89;

448 Figure 4C). These observations are consistent with simulations reported by Donoghue et al., 2020;

449 however, given that there was no significant interaction between method (FOOOF, IRASA) and

450 sentence type (fixed, flexible), we present the IRASA-based analysis.

451
Figure 4. Comparison between FOOOF and IRASA exponent estimates. (A) Histogram illustrating the
distribution of exponent estimates derived from FOOOF (red) and IRASA (grey). (B) Scatterplot
showing the relationship between FOOOF (y-axis) and IRASA (x-axis) between fixed (turquoise) and
flexible (tan) sentences. (C) Relationship between the aperiodic exponent (y-axis; higher values indicate
a steeper exponent), method (x-axis; FOOOF, IRASA), and sentence type (left facet = fixed, right facet
= flexible). Bars represent the 83% confidence interval around group-level expected marginal mean
estimates. Dots represent individual data points per participant for aggregated data.
459
The χ-exponent GAMM revealed the $1/f$ slope was steeper on average for Flexible compared

to Fixed word order sentences (β = 0.02, *SE* = 0.008, *F*(1) = 5.84, *p* = .015). Visualisation of smooth

terms (Figure 5A) revealed that exponent values tended to decrease (indicating a flattening of the $1/f$

slope) over the course of the learning period; however, Flexible trials evoked higher values (steeper $1/f$

slopes) at the beginning and during the second half of the session, relative to Fixed trials (Trial $\times$

Sentence Type estimated degrees of freedom [*edf*] = 3.87, *F* = 29.67, *p* < .001). This model further

revealed significant topographic differences between conditions, with Flexible word orders evoking

higher exponent values over fronto-central regions compared to Fixed word order sentences by the end

of the session (Trial $\times$ Sagittality $\times$ Sentence Type *edf* = 1.78, *F* = 1.13, *p* < .001; see Figure 6; for full

summary tables of all models, see Appendix).

Mean delta power was higher on average during Flexible compared to Fixed word order trials,

although this difference was not significant (β = 0.03, *SE* = 0.016, *F* = 3.68, *p* = .055). However,

visualisation of smooth terms (Figure 5B) revealed a complex pattern whereby delta power increased

over early trials, followed by a marked decrease that was more pronounced in response to Fixed than

Flexible sentence stimuli ($edf = 2.74$, $F = 9.66$, $p < .001$). This interaction was significantly modulated

by sagittality, with between-condition differences (Fixed versus Flexible) in mean power density

increasing over fronto-central electrodes as a function of time ($edf = 2.68$, $F = 1.54$, $p < .001$). Theta

power was non-significantly lower on average during Flexible compared to Fixed rule learning ($\beta = -$

0.01, $SE = 0.014$, $F = 0.60$, $p = .437$). Again, smooth terms revealed a nonlinear pattern of spectral

fluctuation, whereby theta power evinced a sigmoidal shape over the course of rule-learning (Figure

5C). This pattern was similar across both conditions, with Fixed sentence stimuli tending to evoke

increased theta power ($edf = 0.824$, $F = 1.25$, $p = .014$). This pattern of activity varied as a function of

topography, with the difference between conditions being more accentuated across lateralised and

posterior sites, as illustrated in Figure 6 ($edf = 7.63$, $F = 0.22$, $p = .003$).

Alpha power tended to increase over the early and later trials of the learning task, although this

pattern was interrupted by a marked decline during the middle of the session ($edf = 3.20$, $F = 12.50$, p

$< .001$). Flexible word orders evoked less alpha power than Fixed word orders at the beginning of the

session, but was similar thereafter ($edf = 3.20$, $F = 13.46$, $p < .001$; Figure 5D). This difference was

most pronounced over left-lateralised and frontal sites ($edf = 2.27$, $F = 0.35$, $p = .012$). Finally, the beta

power model revealed significant differences in the nonlinear profile of power dynamics across the

learning session. In fact, Fixed and Flexible trials evoked markedly different patterns of activity: beta

power showed an approximately triphasic response to Fixed sentence stimuli that was mirrored by the

response to Flexible stimuli ($edf = 2.94$, $F = 30.08$, $p < .001$; Figure 5E). The strongest beta response

was observed over frontal and temporal regions ($edf = 16.59$, $F = 33.04$, $p < .001$), particularly toward

the beginning of the learning phase for Flexible word order sentences ($edf = 6.82$, $F = 1.24$, $p < .001$).

Taken together, these data illustrate dynamic changes in both aperiodic and oscillatory activity

as a function of different word order rules during learning. Both the aperiodic slope and delta power

tended to decrease over time, while theta power tended to increase. By contrast, alpha and especially

beta power evinced more complex dynamics as participants learnt different word order rules.

Figure 5. Modelled effects for changes in the aperiodic exponent (A), delta (B), theta (C), alpha (D) and beta (E) activity across the learning task for fixed (solid line) and flexible (dashed line) word order rules. Time from beginning to the end of the learning task is represented on the x-axis.

Figure 6. Difference in topographical distribution of aperiodic and oscillatory activity between fixed and flexible word order sentences at the beginning and end of the sentence learning task.

Task-related aperiodic and oscillatory activity are dynamically related during language learning

Neurophysiological signals are dominated by transient oscillatory and broadband aperiodic activity; however, in the study of the oscillatory correlates of higher-order language processing, aperiodic activity is rarely considered, with little known regarding its influence on task-related oscillatory activity (cf. Cross et al., 2021). Here, we examined the associations between task-related oscillations in individualised (i.e., anchored on participants' IAF) frequency bands and aperiodic activity during the learning of different word order rules. There was non-significant positive association

between delta power and the aperiodic slope ($\beta = 0.58$, $p = .05$, $R^2 = 0.02$). There was no relationship between theta power and the aperiodic slope ($\beta = 0.09$, $p = .77$, $R^2 = -0.04$); however, there was a significant negative association between alpha power and the aperiodic slope ($\beta = -2.88$, $p < .001$, $R^2 = 0.33$), which did not vary by sentence type. Finally, there was no significant relationship between task-evoked beta power and the aperiodic slope ($\beta = 0.31$, $p = .49$, $R^2 = -0.04$; for a visualisation of these associations, see Figure 7). These results indicate that aperiodic and narrowband spectral estimates may afford complementary information about learning and task performance. Based on this, we now examine whether such aperiodic and (putative) oscillatory activity interact to predict performance on the sentence judgement task.

Figure 7. Association between task-related aperiodic slope and oscillatory power in the delta (A), theta (B), alpha (C) and beta (D) bands during the sentence learning task averaged across all channels. The aperiodic slope is represented on the x-axis (higher values indicate a steeper slope relative to the pre-sentence interval), while oscillatory power is represented on the y-axis (higher values indicate higher power relative to the pre-sentence interval). The density of observations for frequency band power and the aperiodic slope are indicated on the margins of each plot, while the fixed and flexible word order sentences are coded in turquoise and tan, respectively.

Interactions between oscillatory and aperiodic activity modulate behavioural performance

Given the association between task-related oscillatory and aperiodic activity during the learning

of complex linguistic rules, we now examine whether the $1/f$ slope and oscillatory activity interact

during learning to influence behavioural performance on the sentence judgement task. For all analyses,

we used linear mixed-effects regression models (for full summary tables for all models, see Appendix).

For the delta model, there was a significant Power $\times$ $1/f$ Slope $\times$ Sentence Type interaction ($\chi^2(1) =$

12.47, $p < .001$). As shown in Figure 8A, when the $1/f$ slope was steepest and delta power was low, d'

was higher for flexible relative to fixed word orders. By contrast, when the $1/f$ slope was steep and

delta power was high, performance for fixed word orders increased. For the theta model, there was a

significant Power $\times$ Sentence Type ($\chi^2(1) = 4.57$, $p = .03$) and $1/f$ Slope $\times$ Sentence Type interaction

($\chi^2(1) = 17.43$, $p < .001$). Here, when the $1/f$ slope was steep, d' scores increased for flexible sentences

(Figure 8B; left). By contrast, when theta power increased, performance for both fixed sentences was

higher (Figure 8B; right).

For the alpha model, there was a significant three-way Power $\times$ $1/f$ Slope $\times$ Sentence Type

interaction ($\chi^2(1) = 15.94$, $p < .001$). As depicted in Figure 8C, when the $1/f$ slope was shallow, and as

alpha power increased, d' scores were higher for both fixed and flexible word orders. By contrast, when

the $1/f$ slope was steep, and as alpha power decreased, d' scores were lower for flexible word order

sentences. Similarly, the beta model yielded a significant Power $\times$ $1/f$ Slope $\times$ Sentence Type

interaction ($\chi^2(1) = 30.96$, $p < .001$). When the $1/f$ slope was shallow, and as beta power decreased, d'

scores were higher for both fixed and flexible word orders (Figure 8D). By contrast, when the $1/f$ slope

was steep, increased beta power predicted higher d' scores for fixed but lower d' scores for flexible

word order sentences, respectively.

Together, these results suggest that when there is a steeper $1/f$ slope, increased delta and beta

power were associated with better behavioural performance, and thus better learning outcomes for fixed

relative to flexible word order sentences. Further, when the $1/f$ slope was shallow and alpha power

decreased, there was a general benefit in performance for both fixed and flexible word order sentences,

relative to when the $1/f$ slope was steep.

Figure 8. Visualisation of the relation between behavioural performance, aperiodic slope, and oscillatory delta (A), theta (B), alpha (C), and beta (D) activity. Modelled effects of task-related oscillatory activity (x-axis; higher values indicate greater power) on d' scores (y-axis; higher values indicate better performance) for fixed and flexible word order sentences (fixed = solid line; flexible = dashed line). Task-related aperiodic $1/f$ slope estimates are faceted from shallow (left), to moderate (middle), to steep (right). Note that the trichotomisation of the aperiodic slope into shallow, moderate and steep facets is for visualisation purposes only, with the aperiodic slope being entered into all models as a continuous predictor. Note that (B) illustrates the two-way modelled interaction effects of task-related aperiodic slope (left; x-axis, higher values indicate a steeper slope) and theta power (right; x-axis, higher values indicate greater power) for fixed and flexible word order sentences (fixed = solid line; flexible = dashed line). The red dashed line indicates chance-level performance, while the shaded regions indicate the 83% confidence interval. For A, B, C and E, the x-axis reflects scaled single-trial oscillatory power estimates, with negative values reflecting a decrease in power and positive values reflecting an increase in power.

Discussion

Here, we estimated the $1/f$ slope during artificial grammar learning to characterise the influence of dynamic alterations in aperiodic and oscillatory activity on higher-order cognition. This is the first study to examine aperiodic activity and its interaction with oscillatory power in the context of language learning, with three critical findings emerging: (1) both (putative) oscillatory and aperiodic activity dynamically change over time during complex language-related rule learning; (2) the $1/f$ slope becomes steeper during the learning of complex rules, but this effect differed depending on the type of rules being learned, and; (3) learning-related aperiodic activity interacted with oscillatory power to modulate

behavioural performance for both fixed and flexible word orders. These findings speak strongly to the

view that aperiodic $1/f$ dynamics should be explicitly modelled or isolated as a source of variance when

analysing power spectra to ensure that any oscillatory changes are not confounded with modulations in

broadband aperiodic activity (Donoghue et al., 2021).

Indeed, a considerable proportion of work examining the oscillatory correlates of higher-order

language processing have not explicitly accounted for modulations in broadband aperiodic activity (e.g.,

Bonhage et al., 2017; Corcoran et al., 2022; Kepinska et al., 2017; Lewis et al., 2016; Mai, Minett, &

Wang, 2016; Prat et al., 2016; Rossi & Prystauka, 2020; c.f., Cao et al., 2022), making it difficult to

determine whether oscillatory activity parsimoniously explains behavioural outcomes. By separating

oscillatory and aperiodic components, we have demonstrated that the aperiodic exponent flattens across

time, while, for example, theta and alpha power increase across time throughout the language learning

phase. Recent computational work has highlighted the criticality of such a separation of neural signals

(e.g., Donoghue et al., 2020), given that both aperiodic and oscillatory signals vary by clinical status

(Robertson et al., 2019), state of consciousness (e.g., sleep versus wake; Lendner et al., 2020), and are

modulated by task demands (Waschke et al., 2021). From this perspective, language studies reporting

differences in oscillatory activity (e.g., increases in theta power) between experimental conditions (e.g.,

grammatical vs ungrammatical sentences) without accounting for broadband activity may be

confounded by changes in aperiodic dynamics (Donoghue et al., 2021).

Aperiodic and oscillatory activity are modulated by time-on-task

The potential confounding of aperiodic and oscillatory components is further compounded by

the fact that neural activity is non-stationary (Donoghue et al., 2021; Kosciessa et al., 2020; Stokes &

Spaak, 2016). Here, we modelled single trial fluctuations of both aperiodic and oscillatory EEG

components across the learning task, revealing fine-grained temporal dynamics underlying complex

rule learning. For the aperiodic component, we observed a general flattening of the slope across time

for both fixed and flexible sentences; however, the slope was steeper overall for flexible sentences. The

general flattening of the aperiodic slope across time is in line with previous work reporting attentional

modulations of spectral exponents (Kosciessa et al., 2021; Waschke et al., 2021). As exposure to

grammar rules increased with time-on-task, participants may have become more adept at allocating

attention to cues relevant for successful sentence interpretation. Increased attentional modulation in

accordance with learnt rules may have been accompanied by increased excitation/inhibition ratio, which

reflects an increase in high-frequency power in cortical regions involved in processing task-relevant

information (Cohen & Maunsell, 2011; Harris & Thiele, 2011), thus explaining the flattening of the

aperiodic slope (Kosciessa et al., 2021; Waschke et al., 2021).

The observed increases in theta and alpha power over time are also consistent with previous

work on complex rule and language learning (e.g., Crivelli-Decker et al., 2018; de Diego-Balaguer,

Fuentemilla, & Rodriguez-Fornells, 2011; Kepinska et al., 2017). In the few studies examining the

neural oscillations involved in grammar learning (e.g., de Diego-Balaguer et al., 2011; Kepinska et al.,

2017), it has been demonstrated that theta and alpha synchronisation predict learning success. Here,

theta and alpha power showed a non-linear increase in power across the learning task. Theta oscillations,

particularly over frontal regions when recorded with scalp-EEG, are associated with plasticity-related

learning and memory processes, reflecting the encoding and generalisation of new information

(Eschmann et al., 2020; Khader et al., 2010). From this perspective, the observed increase in theta power

for both fixed and flexible word orders may have reflected successful memory encoding and

accumulating knowledge of the underlying grammatical rules.

Beta activity also displayed complex non-linear changes for fixed and flexible word orders

across the learning task. Overall, beta power was higher for flexible than fixed word orders, particularly

in the second half of the learning session (Figure 5E). In the native language processing literature

(Bastiaansen et al., 2010; Davidson & Indefrey, 2007; Kielar et al., 2014, 2015), beta oscillations are

argued to reflect prediction-related activity, with beta power increasing in highly predictable linguistic

contexts, and decreasing when grammatical violations occur (for review, see Lewis et al., 2015, 2016).

However, in studies on second language learning (e.g., Lewis et al. 2016), beta power increases in

response to sentences with long-distance dependencies, possibly indicating more effortful processing

(Meyer et al., 2013). From this position, the observed general increase in beta power for both fixed and

flexible word orders across the task may reflect the accumulation of grammatical knowledge, allowing

participants to better predict underlying rules of the language. Further, the marked increase in beta

power for flexible word order processing may indicate more effortful processing, given that flexible

word orders contain non-adjacent elements that require integration for successful comprehension (Cross

et al., 2018).

Interactions between aperiodic and oscillatory activity predict learning

642   Interactions between oscillatory and aperiodic activity during the learning task also predicted

subsequent behavioural performance. Increased alpha power predicted an increase in performance for

fixed word orders when the aperiodic $1/f$ was shallow, while a decrease in alpha power predicted higher

performance for flexible word orders when the aperiodic slope was steep. By contrast, when the

aperiodic slope was shallow, a decrease in beta power (i.e., beta desynchronisation) was associated with

improved behavioural performance for both fixed and flexible word orders. Further, when the aperiodic

slope was steep, the relationship between beta desynchronisation and flexible word order processing

was stronger, but the inverse was observed for fixed word order sentences.

650   The effect of differing levels of $1/f$ slope on, for instance, beta power and behavioural

performance likely reflect more nuanced inter-individual differences in information processing

capacities (Dziego et al., 2022; Immink, Cross et al., 2021; Thuwal, Banerjee, & Roy, 2021), which

may explain behavioural gains that are otherwise related to the manifestation of oscillatory activity

(e.g., Kepinska et al., 2017). For example, here we observed that a decrease in beta power predicted

better behavioural performance for flexible rules, while the inverse was seen for fixed word order rules.

From this perspective, a steeper slope may be more conducive for learning more complex information

based on distinct neural dynamics, reflecting a decrease in the excitation/inhibition balance, and thus a

decrease in high-frequency activity (Cohen & Maunsell, 2011; Harris & Thiele, 2011; Waschke et al.,

2021). A reduction in high-frequency activity has been associated with error-driven learning (Luft,

Takase, & Bhattacharya, 2014; Luft, 2014; Tan, Jenkinson, & Brown, 2014) and predictive processing-

based activity (Bastos et al., 2012; Arnal & Giraud, 2012), particularly in the context of language

comprehension (Cross et al., 2018; Lewis & Bastiaansen, 2015; Lewis et al., 2016). As such, a steeper

$1/f$ slope, which was observed for flexible relative to fixed word order rules across the learning task

(Figure 5A), may be foundational for task-related oscillatory activity during higher-order language

learning.

The oscillatory-based findings are also broadly consistent with previous work (e.g., Kepinska

et al., 2017), but reveal fine-grained patterns of spectral activity between word order variations, which

may be explained by cue-integration-based models of language processing (Bates et al., 2001;

Bornkessel & Schlesewsky, 2006; Bornkessel-Schlesewsky et al., 2015; Kaufeld et al., 2020; Martin,

2016). Under this framework, cues that are differentially weighted according to the probabilities of the

language are integrated to comprehend incoming linguistic input (e.g., sentences). Here, fixed word

orders contained linear order-based cues, which are analogous to English, while flexible word orders

required animacy-based cues for interpretation. From this perspective, and in line with previous work

on sequence processing (Crivelli-Decker et al., 2018; Kikuchi, et al., 2018; Wang et al., 2019), increased

beta power likely reflected the propagation of top-down predictions during the learning of fixed word

orders (Cross et al., 2018). In fixed sentences, the first noun is invariably the Actor, and as such,

predictions are constrained to anticipating that the second noun will be the Undergoer, while also

containing a verb-final construction. Therefore, due to the strong sequence dependence in fixed word

orders, precision-weighted predictions would likely increase linearly across the sentence, manifesting

in increased beta power (Arnal, 2012; Cross et al., 2018; Lewis & Bastiaansen, 2015).

The inverse relationship with flexible word order processing – which was predicted by a

reduction in beta power– can also be explained under this framework. Given that flexible word orders

contain either Actor-first or Undergoer-first constructions, predictions cannot be based on the linear

position of the words, and instead must be driven by the integration of (non-adjacent) animacy-based

cues to arrive at an accurate sentential percept. Given that our sample consisted of native monolingual

English speakers (a language that relies heavily on word order cues; Bates et al., 2001; Bornkessel-

Schlesewsky, et al. 2011; MacWhinney et al., 1984), a reduction in beta power during flexible word

order processing likely reflected prediction errors and internal model updating. That is, beta

desynchronization during the learning of flexible word orders may have reflected internal model

updating based on mismatches with predicted and actual sensory input, while an increase in beta power

during fixed word order processing likely reflected the accumulation of top-down predictions based on

our sample of native English speakers' preference for word-order-based cues. Importantly, this

interpretation is consistent with temporal sequence learning paradigms, where beta power increases for

fixed relative to "random" sequences (Crivelli-Decker et al., 2018), which also aligns with the observed

beta power increase from the second half the learning task for fixed relative to flexible word orders

(Figure 5E).

Alpha activity showed a similar interaction: when the $1/f$ slope was steep, reduced alpha power

(i.e., alpha desynchronisation) predicted flexible word order processing. Alpha power reductions during

language comprehension may reflect goal-directed processing and enhanced allocation of attentional

resources, which is required for the successful learning of flexible word orders (Kepinska et al., 2017),

given that they deviate from the canonical English word order (Bates et al., 2001). This interpretation

is in line with evidence demonstrating that alpha oscillations reflect rhythmic cortical gating by

alternating the activation of task-relevant cortical regions while inhibiting the processing of task-

irrelevant information (Chapeton et al., 2019; de Vries et al., 2020; Gallotto et al., 2020; Klimesch,

2012; Jensen & Mazaheri, 2010). From this perspective, a decrease in alpha power likely facilitated the

extraction of flexible word order rules by suppressing task-irrelevant input and optimising cortical

communication in a selectively precise manner, promoting the encoding and consolidation of non-

canonical grammatical rules. This interpretation is also supported by the observation that alpha power

was lower for flexible relative to fixed word order rules, particularly at the beginning of the learning

task (Figure 5D).

We also found that an increase in theta power predicted performance for flexible but not fixed

word orders; however, theta did not interact with the aperiodic exponent to predict behavioural

performance. Theta oscillations have been proposed to combine linguistic input into successively more

complex representations, establishing relations between (non-adjacent) elements in a sentence

(Covington & Duff, 2016; Cross et al., 2018). The positive association between theta power and

performance for flexible word orders may reflect the learning and integration of non-adjacent rules,

which involves the decoding and combination of words that are non-adjacent in a sentence. Indeed,

such theta effects have been reported during native sentence processing (Lam et al., 2016). These effects

are also consistent with the general memory literature: retrieval of language (e.g., single words), and

shape/face stimuli elicit higher theta synchronisation (Bastiaansen et al., 2002; Klimesch et al., 2008;

Klimesch et al., 2010; Mormann et al., 2005; Osipova et al., 2006), with these effects manifesting over

medial temporal and prefrontal cortices (Guderian & Düzel, 2005), indexing the activation of relevant

memory traces and executive control processes, respectively.

Functional relevance of aperiodic activity in language and higher-order cognition

Our analysis revealed a link between aperiodic activity during language learning and

performance on a grammaticality judgement task. This finding is consistent with previous studies

demonstrating the influence of aperiodic activity on a range of cognitive computations, including

processing speed (Ouyang et al., 2020), memory (Sheehan et al., 2018) and prediction in language

(Dave et al., 2018). From a neurophysiological perspective, $1/f$-like neural activity has been proposed

to encode information relating to intrinsic brain function (Muthukumaraswamy & Liley, 2018),

including the balance between excitation/inhibition (Gao et al., 2017), likely reflecting glutamate and

GABA synaptic inputs into inter- and intra-cortical networks (Dave et al., 2018; Gao et al., 2017). Based

on this perspective, Dave et al. (2018) argued that aperiodic activity influences prediction in language

by modulating the strength of predictions of upcoming linguistic information via population spiking

synchrony (Engel et al., 2001). This interpretation applies to our finding that aperiodic and beta activity

showed a negative association with performance for fixed and flexible word orders: an increase in beta

power predicted more sensitive behavioural responses for fixed sentences, while reduced beta predicted

performance for flexible word orders. These findings can be explained by integrating two perspectives:

the "spectral fingerprints" hypothesis (Hanslmayr & Staudigl, 2014; Keitel & Gross, 2016; Siegel et

al., 2012; Watrous et al., 2015; Womelsdorf et al., 2014) and generalised predictive coding (Friston,

2010, 2018, 2019).

The "spectral fingerprints" hypothesis argues that power changes in different frequency bands

reflect distinct stages of memory and information processing (Fellner et al., 2019; Keitel & Gross,

2016), rather than reflecting a "spectral tilt" between lower and higher frequencies. For example,

decreases in alpha/beta and increases in gamma power during memory retrieval occur on different

temporal scales and in different brain areas, providing evidence against proposals that a change in the

tilt of the power spectrum solely drives memory computations (Fellner et al., 2019). Further, increases

in high frequency gamma activity have been proposed to reflect the propagation of bottom-up sensory

signals (Lewis et al., 2015; Richter, Thompson, Bosman, & Fries, 2017), while a decrease in alpha/beta

power is thought to index prediction errors (Bressler & Richter, 2015; Friston, 2019; Samaha, Bauer,

Cimaroli, & Postle, 2015). From this perspective, a steeper $1/f$ slope may reflect the maintenance of

top-down predictions that allow comprehenders to generate expectations for incoming stimuli, thus

minimizing prediction error at lower levels of the cortical hierarchy. This interpretation also holds for

interactions observed with aperiodic and oscillatory activity in the alpha and beta bands, and as such,

provides evidence that $1/f$-like activity may partially reflect cortical excitability across the frequency

spectrum that serves to minimize prediction error during language learning and sentence processing.

Conclusions and Future Directions

Taken together, we have demonstrated that oscillatory and aperiodic activity jointly predict the

learning of higher-order language. There are, of course, several open questions that arise from these

results. For example, how do interactions between oscillatory and aperiodic activity relate to individual

differences in atypical populations, such as those with schizophrenia and age-related pathologies,

including Alzheimer's disease? Previous research has shown that cognitive deficits characteristic of

schizophrenia may be better explained by changes in the $1/f$ slope than irregularities in the canonical

frequency bands (Peterson et al., 2018), and that $1/f$ activity mediates age-related deficits in working

memory (Voytek et al., 2015); however, the interaction between aperiodic and oscillatory activity

during more complex cognitive computations, such as sequence learning and language processing,

remains less well known. While we attempt to address the relationship between aperiodic and

oscillatory activity during higher-order language learning, future work would benefit from examining

how and if these interactions emerge in (age-related) pathologies, and whether patterns of aperiodic and

oscillatory activity during language learning and sentence processing are generated by specific

neuroanatomical networks. Such work will provide a better understanding of the neurobiology of

cognition in both health and disease.

References

Allen, M., Poggiali, D., Whitaker, K., Marshall, T. R., & Kievit, R. A. (2019). Raincloud plots: A multi-platform tool for robust data visualization. *Wellcome Open Research*, *4*.

Arnal, L. H. (2012). Predicting "When" Using the Motor System's Beta-Band Oscillations. *Front Hum Neurosci*, *6*, 225. *https://doi.org/10.3389/fnhum.2012.00225*

Arnal, L. H., & Giraud, A. L. (2012). Cortical oscillations and sensory predictions. *Trends in cognitive sciences, 16*(7), 390-398.

Austin, P. (2001). Word order in a free word order language: the case of Jiwarli. *Forty years on: Ken Hale and Australian languages, 2057323.*

Austin, P. C., & Hux, J. E. (2002). A brief note on overlapping confidence intervals. *Journal of Vascular Surgery*, *36*(1), 194–195.

Baayen, H., Vasishth, S., Kliegl, R., & Bates, D. (2017). The cave of shadows: Addressing the human factor with generalized additive mixed models. *Journal of Memory and Language*, *94*, 206–234.

Baayen, R. H., Davidson, D. J., & Bates, D. M. (2008). Mixed-effects modeling with crossed random effects for subjects and items. *Journal of Memory and Language*, *59*(4), 390–412.

Bastiaansen, M. C., Van Berkum, J. J., & Hagoort, P. (2002). Syntactic processing modulates the θ rhythm of the human EEG. *Neuroimage*, *17*(3), 1479–1492.

Bastiaansen, M., Magyari, L., & Hagoort, P. (2010). Syntactic unification operations are reflected in oscillatory dynamics during on-line sentence comprehension. *Journal of Cognitive Neuroscience, 22*(7), 1333-1347.

Bastos, A. M., Usrey, W. M., Adams, R. A., Mangun, G. R., Fries, P., & Friston, K. J. (2012). Canonical microcircuits for predictive coding. *Neuron, 76*(4), 695-711.

Bates, D., Maechler, M., Bolker, B., Walker, S., Christensen, R. H. B., Singmann, H., Dai, B., Grothendieck, G., Green, P., & Bolker, M. B. (2015). Package 'lme4.' *Convergence*, *12*(1), 2.

Bates, E., Devescovi, A., & Wulfeck, B. (2001). Psycholinguistics: A Cross-Language Perspective. *Annual Review of Psychology*, *52*(1), 27.

Bell, A. J., & Sejnowski, T. J. (1995). An information-maximization approach to blind separation and blind deconvolution. *Neural Computation*, *7*(6), 1129–1159.

Bonhage, C. E., Meyer, L., Gruber, T., Friederici, A. D., & Mueller, J. L. (2017). Oscillatory EEG dynamics underlying automatic chunking during sentence processing. *Neuroimage, 152*, 647-657. doi: *https://doi.org/10.1016/j.neuroimage.2017.03.018*

Bornkessel-Schlesewsky, I., Kretzschmar, F., Tune, S., Wang, L., Genc, S., Philipp, M., Roehm, D., & Schlesewsky, M. (2011). Think globally: Cross-linguistic variation in electrophysiological activity during sentence comprehension. *Brain Lang*, *117*(3), 133–152. *https://doi.org/10.1016/j.bandl.2010.09.010*

Bornkessel-Schlesewsky, I., Schlesewsky, M., Small, S. L., & Rauschecker, J. P. (2015).

Neurobiological roots of language in primate audition: Common computational properties.

Trends Cogn Sci, 19(3), 142–150. *https://doi.org/10.1016/j.tics.2014.12.008*

Bornkessel, I., & Schlesewsky, M. (2006). The extended argument dependency model: A

neurocognitive approach to sentence comprehension across languages. *Psychol Rev, 113*(4),

787–821. https://doi.org/10.1037/0033-295X.113.4.787

Bressler, S. L., & Richter, C. G. (2015). Interareal oscillatory synchronization in top-down neocortical

processing. *Current Opinion in Neurobiology, 31*, 62-66. doi:

https://doi.org/10.1016/j.conb.2014.08.010

Cao, Y., Oostenveld, R., Alday, P. M., & Piai, V. (2022). Are alpha and beta oscillations spatially

dissociated over the cortex in context-driven spoken-word production?. *Psychophysiology*,

e13999. doi: *https://doi.org/10.1111/psyp.13999*

Chapeton, J. I., Haque, R., Wittig, J. H., Inati, S. K., & Zaghloul, K. A. (2019). Large-Scale

Communication in the Human Brain Is Rhythmically Modulated through Alpha Coherence.

Curr Biol, 29(17), 2801-2811 e5. *https://doi.org/10.1016/j.cub.2019.07.014*

Claus O. Wilke, C.O. (2019). cowplot: Streamlined Plot Theme and Plot Annotations for 'ggplot2'. R

package version 1.0.0. https://CRAN.R-project.org/package=cowplot

Cohen, M. R., & Maunsell, J. H. (2011). Using neuronal populations to study the mechanisms

underlying spatial and feature attention. *Neuron, 70*(6), 1192-1204.

Corcoran, A. W., Alday, P. M., Schlesewsky, M., & Bornkessel-Schlesewsky, I. (2018). Toward a

reliable, automated method of individual alpha frequency (IAF) quantification.

Psychophysiology, 55(7), e13064. *https://doi.org/10.1111/psyp.1306*

Corcoran, A. W., Macefield, V. G., & Hohwy, J. (2021). Be still my heart: Cardiac regulation as a

mode of uncertainty reduction. *Psychonomic Bulletin & Review, 28*, 1211–1223. doi:

https://doi.org/10.3758/s13423-021-01888-y

Corcoran, A. W., Perera, R., Koroma, M., Kouider, S., Hohwy, H., Andrillon, T. (2022). Expectations

boost the reconstruction of auditory features from electrophysiological responses to noisy

speech, *Cerebral Cortex*. doi: *https://doi.org/10.1093/cercor/bhac094*

Corcoran, A.W., Alday, P.M., Schlesewsky, M., & Bornkessel-Schlesewsky, I. (2019). restingIAF

(v1.0.3). Retrieved from https://github.com/corcorana/restingIAF

Crivelli-Decker, J., Hsieh, L. T., Clarke, A., & Ranganath, C. (2018). Theta oscillations promote

temporal sequence learning. *Neurobiol Learn Mem*.

https://doi.org/10.1016/j.nlm.2018.05.001

Cross, Z. R, Helfrich, R. F., Kohler, M. J., Corcoran, A. W., Coussens, S., Zou-Williams, L.,

Schlesewsky, M., Gaskell, M. G., Knight, R. T., & Bornkessel-Schlesewsky, I. (2021).

Spindle-slow oscillation coupling during sleep predicts sequence-based language learning.

BioRxiv. doi: *https://doi.org/10.1101/2020.02.13.948539*

Cross, Z. R., Corcoran, A. W., Kohler, M. J., Schlesewsky, M., & Bornkessel-Schlesewsky, I. (2022,
March 27). Oscillatory and aperiodic neural activity jointly predict language learning.
Retrieved from osf.io/7yr46.

Cross, Z. R., Kohler, M. J., Schlesewsky, M., Gaskell, M. G., & Bornkessel-Schlesewsky, I. (2018).
Sleep-dependent memory consolidation and incremental sentence comprehension:
computational dependencies during language learning as revealed by neuronal oscillations.
Frontiers in Human Neuroscience, *12*. *https://doi.org/10.3389/fnhum.2018.00018*

Cross, Z. R., Santamaria, A., Corcoran, A. W., Chatburn, A., Alday, P. M., Coussens, S., & Kohler,
M. J. (2020b). Individual alpha frequency modulates sleep-related emotional memory
consolidation. *Neuropsychologica*, *148*. doi: *https://doi.org/10.1101/202176*

Cross, Z. R., Zou-Williams, L., Wilkinson, E., Schlesewsky, M., & Bornkessel-Schlesewsky, I.
(2020a). Mini Pinyin: A modified miniature language for studying language learning and
incremental sentence processing. *Behavior Research Methods*. doi:
https://doi.org/10.3758/s13428-020-01473-6

Dave, S., Brothers, T. A., & Swaab, T. Y. (2018). 1/f neural noise and electrophysiological indices of
contextual prediction in aging. *Brain Res*, *1691*, 34–43.
https://doi.org/10.1016/j.brainres.2018.04.007

Davidson, D. J., & Indefrey, P. (2007). An inverse relation between event-related and time–frequency
violation responses in sentence processing. *Brain Research*, 1158, 81-92.

de Diego-Balaguer, R., Fuentemilla, L., & Rodriguez-Fornells, A. (2011). Brain Dynamics Sustaining
Rapid Rule Extraction from Speech. *J Cogn Neurosci*, *23*(10), 3105–3120.

de Vries, I. E. J., Slagter, H. A., & Olivers, C. N. L. (2020). Oscillatory Control over Representational
States in Working Memory. *Trends Cogn Sci*, *24*(2), 150–162.
https://doi.org/10.1016/j.tics.2019.11.00

Donoghue, T., Dominguez, J., & Voytek, B. (2020). Electrophysiological frequency band ratio
measures conflate periodic and aperiodic neural activity. *Eneuro, 7*(6). doi:
https://doi.org/10.1523/ENEURO.0192-20.2020

Donoghue, T., Haller, M., Peterson, E. J., Varma, P., Sebastian, P., Gao, R., ... & Voytek, B. (2020).
Parameterizing neural power spectra into periodic and aperiodic components. *Nature*
Neuroscience, 23(12), 1655-1665. doi: *https://doi.org/10.1038/s41593-020-00744-x*

Donoghue, T., Schaworonkow, N., & Voytek, B. (2021). Methodological considerations for studying
neural oscillations. *European Journal of Neuroscience*. doi: *https://doi.org/10.1111/ejn.15361*

Doppelmayr, M., Klimesch, W., Pachinger, T., & Ripper, B. (1998). Individual differences in brain
dynamics: important implications for the calculation of event-related band power. *Biological*
Cybernetics, 79(1), 49-57.

Dziego, C., Bornkessel-Schlesewsky, I., Jano, S., Chatburn, A., Schlesewsky, M., Immink, M. A., ...
& Cross, Z. R. (2022). Neural and cognitive correlates of performance in dynamic multi-
modal settings. *bioRxiv*. doi: https://doi.org/10.1101/2022.03.23.485424

Engel, A. K., Fries, P., & Singer, W. (2001). Dynamic predictions: Oscillations and synchrony in top-
down processing. *Nature Reviews Neuroscience*, *2*, 12.

Eschmann, K. C., Bader, R., & Mecklinger, A. (2020). Improving episodic memory: Frontal-midline
theta neurofeedback training increases source memory performance. *NeuroImage*, 222,
117219.

Fasiolo, M., Nedellec, R., Goude, Y., & Wood, S. N. (2019). Scalable visualization methods for
modern generalized additive models. *Journal of Computational and Graphical Statistics*, 1–9.

Fellner, M. C., Gollwitzer, S., Rampp, S., Kreiselmeyr, G., Bush, D., Diehl, B., Axmacher, N.,
Hamer, H., & Hanslmayr, S. (2019). Spectral fingerprints or spectral tilt? Evidence for
distinct oscillatory signatures of memory formation. *PLoS Biol*, *17*(7), e3000403.
https://doi.org/10.1371/journal.pbio.3000403

Fox, J., Weisberg, S., Adler, D., Bates, D., Baud-Bovy, G., Ellison, S., & Heilberger, R. (2011).
Package "car": Companion to applied regression.

Friston, K. (2010). The free-energy principle: A unified brain theory? *Nat Rev Neurosci*, *11*(2), 127–
138. *https://doi.org/10.1038/nrn2787*

Friston, K. (2018). Does predictive coding have a future? *Nature Neuroscience*, *21*(8), 1019–1021.

Friston, K. J. (2019). Waves of prediction. *PLoS Biol*, *17*(10), e3000426.
https://doi.org/10.1371/journal.pbio.3000426

Gallotto, S., Duecker, F., ten Oever, S., Schuhmann, T., de Graaf, T. A., & Sack, A. T. (2020).
Relating alpha power modulations to competing visuospatial attention theories. *NeuroImage*,
207, 116429.

Gao, R., Peterson, E. J., & Voytek, B. (2017). Inferring synaptic excitation/inhibition balance from
field potentials. *Neuroimage, 158*, 70-78. doi: 10.1016/j.neuroimage.2017.06.078

Gerster, M., Waterstraat, G., Litvak, V., Lehnertz, K., Schnitzler, A., Florin, E., ... & Nikulin, V.
(2022). Separating neural oscillations from aperiodic 1/f activity: challenges and
recommendations. *Neuroinformatics*, 1-22.

Griffiths, B. J., Mayhew, S. D., Mullinger, K. J., Jorge, J., Charest, I., Wimber, M., & Hanslmayr, S.
(2019). Alpha/beta power decreases track the fidelity of stimulus-specific information. *Elife*,
8. *https://doi.org/10.7554/eLife.49562*

Guderian, S., & Düzel, E. (2005). Induced theta oscillations mediate large-scale synchrony with
mediotemporal areas during recollection in humans. *Hippocampus*, *15*(7), 901–912.

Hanslmayr, S., & Staudigl, T. (2014). How brain oscillations form memories—A processing based
perspective on oscillatory subsequent memory effects. *Neuroimage*, *85 Pt 2*, 648–655.
https://doi.org/10.1016/j.neuroimage.2013.05.121

Harris, K. D., & Thiele, A. (2011). Cortical state and attention. *Nature Reviews Neuroscience, 12*(9),
509-523.

Hastie, T., & Tibshirani, R. (1987). Generalized additive models: Some applications. *Journal of the*
American Statistical Association, 82(398), 371–386.

Hastie, T., & Tibshirani, R. (1990). Exploring the nature of covariate effects in the proportional
hazards model. *Biometrics*, 1005–1016.

He, B. J. (2014). Scale-free brain activity: Past, present, and future. *Trends Cogn Sci*, *18*(9), 480–487.
https://doi.org/10.1016/j.tics.2014.04.003

He, B. J., Zempel, J. M., Snyder, A. Z., & Raichle, M. E. (2010). The temporal structures and
functional significance of scale-free brain activity. *Neuron*, *66*(3), 353–369.
https://doi.org/10.1016/j.neuron.2010.04.020

Herweg, N. A., Solomon, E. A., & Kahana, M. J. (2020). Theta Oscillations in Human Memory.
Trends Cogn Sci, *24*(3), 208–227. *https://doi.org/10.1016/j.tics.2019.12.006*

Immink, M. A., Cross, Z. R., Chatburn, A., Baumeister, J., Schlesewsky, M., & Bornkessel-
Schlesewsky, I. (2021). Resting-state aperiodic neural dynamics predict individual differences
in visuomotor performance and learning. *Human Movement Science, 78*, 102829. doi:
https://doi.org/10.1016/j.humov.2021.102829

Kassambara, A. (2020). ggpubr: 'ggplot2' Based Publication Ready Plots. R package version 0.4.0.
https://CRAN.R-project.org/package=ggpubr

Kaufeld, G., Bosker, H. R., Alday, P. M., Meyer, A. S., & Martin, A. E. (2020). Linguistic structure
and meaning organize neural oscillations into a content-specific hierarchy. *BioRxiv*,
2020.02.05.935676. *https://doi.org/10.1101/2020.02.05.935676*

Keitel, A., & Gross, J. (2016). Individual Human Brain Areas Can Be Identified from Their
Characteristic Spectral Activation Fingerprints. *PLoS Biol*, *14*(6), e1002498.
https://doi.org/10.1371/journal.pbio.1002498

Kepinska, O., Pereda, E., Caspers, J., & Schiller, N. O. (2017). Neural oscillatory mechanisms during
novel grammar learning underlying language analytical abilities. *Brain Lang*, *175*, 99–110.
https://doi.org/10.1016/j.bandl.2017.10.003

Khader, P. H., Jost, K., Ranganath, C., & Rösler, F. (2010). Theta and alpha oscillations during
working-memory maintenance predict successful long-term memory encoding. *Neuroscience*
letters, 468(3), 339-343.

Kielar, A., Meltzer, J. A., Moreno, S., Alain, C., & Bialystok, E. (2014). Oscillatory responses to
semantic and syntactic violations. *Journal of Cognitive Neuroscience, 26*(12), 2840-2862.

Kikuchi, Y., Sedley, W., Griffiths, T. D., & Petkov, C. I. (2018). Evolutionarily conserved neural
signatures involved in sequencing predictions and their relevance for language. *Current*
Opinion in Behavioral Sciences, *21*, 145–153. *https://doi.org/10.1016/j.cobeha.2018.05.002*

Klimesch, W. (2013). An algorithm for the EEG frequency architecture of consciousness and brain body coupling. *Frontiers in human neuroscience, 7,* 766. doi: https://doi.org/10.3389/fnhum.2013.00766

Klimesch, W., Freunberger, R., & Sauseng, P. (2010). Oscillatory mechanisms of process binding in memory. *Neuroscience & Biobehavioral Reviews*, *34*(7), 1002–1014.

Klimesch, W., Freunberger, R., Sauseng, P., & Gruber, W. (2008). A short review of slow phase synchronization and memory: Evidence for control processes in different memory systems? *Brain Res*, *1235*, 31–44. *https://doi.org/10.1016/j.brainres.2008.06.049*

Klimesch, W.. (2012). Alpha-band oscillations, attention, and controlled access to stored information. *Trends in Cognitive Sciences*, *16*(12), 606–617. *http://dx.doi.org/10.1016/j.tics.2012.10.007*

Kosciessa, J. Q., Grandy, T. H., Garrett, D. D., & Werkle-Bergner, M. (2020). Single-trial characterization of neural rhythms: Potential and challenges. NeuroImage, 206, 116331. doi: https://doi.org/10.1016/j.neuroimage.2019.116331

Kuznetsova, A., Brockhoff, P. B., & Christensen, R. H. B. (2017). lmerTest package: Tests in linear mixed effects models. *Journal of Statistical Software*, *82*(13).

Lam, N. H., Schoffelen, J. M., Udden, J., Hulten, A., & Hagoort, P. (2016). Neural activity during sentence processing as reflected in theta, alpha, beta, and gamma oscillations. *Neuroimage*. *https://doi.org/10.1016/j.neuroimage.2016.03.007*

Lendner, J. D., Helfrich, R. F., Mander, B. A., Romundstad, L., Lin, J. J., Walker, M. P., Larsson, P. G., & Knight, R. T. (2020). An electrophysiological marker of arousal level in humans. *eLife*. doi: 10.7554/eLife.55092

Lewis, A. G., & Bastiaansen, M. (2015). A predictive coding framework for rapid neural dynamics during sentence-level language comprehension. *Cortex*, *68*, 155–168. *https://doi.org/10.1016/j.cortex.2015.02.014*

Lewis, A. G., Lemhöfer, K., Schoffelen, J. M., & Schriefers, H. (2016). Gender agreement violations modulate beta oscillatory dynamics during sentence comprehension: A comparison of second language learners and native speakers. *Neuropsychologia, 89*, 254-272. doi: *https://doi.org/10.1016/j.neuropsychologia.2016.06.031*

Lewis, A. G., Schoffelen, J. M., Schriefers, H., & Bastiaansen, M. (2016). A predictive coding perspective on beta oscillations during sentence-level language comprehension. *Frontiers in human neuroscience, 10*, 85.

Lewis, A. G., Wang, L., & Bastiaansen, M. (2015). Fast oscillatory dynamics during language comprehension: Unification versus maintenance and prediction? *Brain and language, 148*, 51-63.

Lin, X., & Zhang, D. (1999). Inference in generalized additive mixed modelsby using smoothing splines. *Journal of the Royal Statistical Society: Series b (Statistical Methodology)*, *61*(2), 381–400.

Lüdecke, D. (2018). "ggeffects: Tidy Data Frames of Marginal Effects from Regression
Models."_Journal of Open Source Software_, *3*(26), 772. doi: 10.21105/joss.00772
(URL:https://doi.org/10.21105/joss.00772).

Luft, C. D. B. (2014). Learning from feedback: the neural mechanisms of feedback processing
facilitating better performance. *Behavioural brain research*, 261, 356-368.

Luft, C. D. B., Takase, E., & Bhattacharya, J. (2014). Processing graded feedback:
electrophysiological correlates of learning from small and large errors. *Journal of cognitive*
neuroscience, 26(5), 1180-1193.

MacGregor-Fors, I., & Payton, M. E. (2013). Contrasting diversity values: Statistical inferences based
on overlapping confidence intervals. *PLoS One*, *8*(2).

MacWhinney, B., Bates, E., & Kliegl, R. (1984). Cue validity and sentence interpretation in English,
German, and Italian. *Journal of Verbal Learning and Verbal Behavior*, *23*(2), 127–150.
http://dx.doi.org/10.1016/S0022-5371(84)90093-8

Mai, G., Minett, J. W., & Wang, W. S. Y. (2016). Delta, theta, beta, and gamma brain oscillations
index levels of auditory sentence processing. *Neuroimage, 133*, 516-528. doi:
https://doi.org/10.1016/j.neuroimage.2016.02.064

Marra, G., & Wood, S. N. (2011). Practical Variable Selection for Generalized Additive Models.
Computational Statistics & Data Analysis, 55, 2372–2387.

Martin, A. E. (2016). Language Processing as Cue Integration: Grounding the Psychology of
Language in Perception and Neurophysiology. *Frontiers in Psychology*, 7, 120.
https://doi.org/10.3389/fpsyg.2016.00120

Mathot, S., Schreij, D., & Theeuwes, J. (2012). OpenSesame: An open-source, graphical experiment
builder for the social sciences. *Behav Res Methods*, *44*(2), 314–324.
https://doi.org/10.3758/s13428-011-0168-7

Meyer, L., Obleser, J., & Friederici, A. D. (2013). Left parietal alpha enhancement during working
memory-intensive sentence processing. *Cortex, 49*(3), 711-721.

Mormann, F., Fell, J., Axmacher, N., Weber, B., Lehnertz, K., Elger, C. E., & Fernández, G. (2005).
Phase/amplitude reset and theta–gamma interaction in the human medial temporal lobe during
a continuous word recognition memory task. *Hippocampus*, *15*(7), 890–900.

Mueller, J. L., Hahne, A., Fujii, Y., & Friederici, A. D. (2005). Native and nonnative speakers'
processing of a miniature version of Japanese as revealed by ERPs. *Journal of Cognitive*
Neuroscience, 17(8), 1229-1244.

Muthukumaraswamy, S. D., & Liley, D. T. (2018). 1/f electrophysiological spectra in resting and
drug-induced states can be explained by the dynamics of multiple oscillatory relaxation
processes. *Neuroimage*, *179*, 582–595.

Nenadic, O., & Greenacre, M. (2007). Correspondence analysis in R, with two-and three-dimensional
graphics: The ca package. *Journal of Statistical Software*, *20*(3).

Oostenveld, R., Fries, P., Maris, E., & Schoffelen, J.-M. (2011). FieldTrip: Open source software for
advanced analysis of MEG, EEG, and invasive electrophysiological data. *Computational*
Intelligence and Neuroscience, *2011*.

Osipova, D., Takashima, A., Oostenveld, R., Fernandez, G., Maris, E., & Jensen, O. (2006). Theta
and gamma oscillations predict encoding and retrieval of declarative memory. *J Neurosci*,
26(28), 7523–7531. *https://doi.org/10.1523/JNEUROSCI.1948-06.2006*

Ouyang, G., Hildebrandt, A., Schmitz, F., & Herrmann, C. S. (2020). Decomposing alpha and 1/f
brain activities reveals their differential associations with cognitive processing speed.
Neuroimage, *205*, 116304. *https://doi.org/10.1016/j.neuroimage.2019.116304*

Parish, G., Hanslmayr, S., & Bowman, H. (2018). The Sync/deSync Model: How a Synchronized
Hippocampus and a Desynchronized Neocortex Code Memories. *J Neurosci*, *38*(14), 3428–
3440. *https://doi.org/10.1523/JNEUROSCI.2561-17.201*

Pedersen, E. J., Miller, D. L., Simpson, G. L., & Ross, N. (2019). Hierarchical generalized additive
models in ecology: An introduction with mgcv. *PeerJ*, *7*, e6876.

Perrin, F., Pernier, J., Bertrand, O., & Echallier, J. F. (1989). Spherical splines for scalp potential and
current density mapping. *Electroencephalography and Clinical Neurophysiology, 72*(2), 184-
187.

Peterson, E. J., Rosen, B. Q., Campbell, A. M., Belger, A., & Voytek, B. (2017). 1/f neural noise is a
better predictor of schizophrenia than neural oscillations. *BioRxiv*, 113449.

Prat, C. S., Yamasaki, B. L., Kluender, R. A., & Stocco, A. (2016). Resting-state qEEG predicts rate
of second language learning in adults. *Brain & Language, 157*, 44-50. doi:
https://doi.org/10.1016/j.bandl.2016.04.007

Richter, C. G., Thompson, W. H., Bosman, C. A., & Fries, P. (2017). Top-down beta enhances
bottom-up gamma. *The Journal of Neuroscience*, *37*(28), 6698-6711. doi:
10.1523/JNEUROSCI.3771-16.2017

Robertson, M. M., Furlong, S., Voytek, B., Donoghue, T., Boettiger, C. A., & Sheridan, M. A. (2019).
EEG power spectral slope differs by ADHD status and stimulant medication exposure in early
childhood. *Journal of Neurophysiology, 122*(6), 2427-2437. doi:
https://doi.org/10.1152/jn.00388.2019

Rossi, E., & Prystauka, Y. (2020). Oscillatory brain dynamics of pronoun processing in native
Spanish speakers and in late second language learners of Spanish. *Bilingualism: Language*
and Cognition, 23(5), 964-977. doi: . *https://doi.org/10.1017/S1366728919000798*

Samaha, J., Bauer, P., Cimaroli, S., & Postle, B. R. (2015). Top-down control of the phase of alpha-
band oscillations as a mechanism for temporal prediction. *PNAS*, *112*(27), 8439-8444. doi:
https://doi.org/10.1073/pnas.1503686112

Sarkar, D. (2008). *Lattice: Multivariate data visualization with R*. Springer Science & Business
Media.

Sauppe, S., Choudhary, K. K., Giroud, N., Blasi, D. E., Norcliffe, E., Bhattamishra, S., ... & Bickel, B. (2021). Neural signatures of syntactic variation in speech planning. *PLoS Biology, 19*(1), e3001038. doi: https://doi.org/10.1371/journal.pbio.3001038

Schad, D. J., Vasishth, S., Hohenstein, S., & Kliegl, R. (2020). How to capitalize on a priori contrasts in linear (mixed) models: A tutorial. *Journal of Memory and Language*, *110*, 104038.

Schreiner, T., Goldi, M., & Rasch, B. (2015). Cueing vocabulary during sleep increases theta activity during later recognition testing. *Psychophysiology*, *52*(11), 1538–1543. *https://doi.org/10.1111/psyp.12505*

Sheehan, T. C., Sreekumar, V., Inati, S. K., & Zaghloul, K. A. (2018). Signal Complexity of Human Intracranial EEG Tracks Successful Associative-Memory Formation across Individuals. *J Neurosci*, *38*(7), 1744–1755. *https://doi.org/10.1523/JNEUROSCI.2389-17.2017*

Siegel, M., Donner, T. H., & Engel, A. K. (2012). Spectral fingerprints of large-scale neuronal interactions. *Nat Rev Neurosci*, *13*(2), 121–134. *https://doi.org/10.1038/nrn313*

Stokes, M., & Spaak, E. (2016). The importance of single-trial analyses in cognitive neuroscience. Trends in Cognitive Sciences, 20(7), 483-486. doi: *https://doi.org/10.1016/j.tics.2016.05.008*

Tan, H., Jenkinson, N., & Brown, P. (2014). Dynamic neural correlates of motor error monitoring and adaptation during trial-to-trial learning. *Journal of Neuroscience, 34*(16), 5678-5688.

Thuwal, K., Banerjee, A., & Roy, D. (2021). Aperiodic and periodic components of ongoing oscillatory brain dynamics link distinct functional aspects of cognition across adult lifespan. *Eneuro, 8*(5). doi: 10.1523/ENEURO.0224-21.2021

van Rij, J., Wieling, M., Baayen, R. H., van Rijn, H., & van Rij, M. J. (2016). *Package 'itsadug.'*

Voytek, B., Kramer, M. A., Case, J., Lepage, K. Q., Tempesta, Z. R., Knight, R. T., & Gazzaley, A. (2015). Age-Related Changes in 1/f Neural Electrophysiological Noise. *J Neurosci*, *35*(38), 13257–13265. *https://doi.org/10.1523/JNEUROSCI.2332-14.2015*

Wang, P., Maye, A., Daume, J., Xue, G., & Engel, A. K. (2019). Dynamic Predictions: Oscillatory Mechanisms Underlying Multisensory Sequence Processing. *BioRxiv*, 778969.

Waschke, L., Donoghue, T., Fiedler, L., Smith, S., Garrett, D. D., Voytek, B., & Obleser, J. (2021). Modality-specific tracking of attention and sensory statistics in the human electrophysiological spectral exponent. Elife, 10, e70068. doi: 10.7554/eLife.70068

Watrous, A. J., Fell, J., Ekstrom, A. D., & Axmacher, N. (2015). More than spikes: Common oscillatory mechanisms for content specific neural representations during perception and memory. *Curr Opin Neurobiol*, *31*, 33–39. *https://doi.org/10.1016/j.conb.2014.07.024*

Welch, P. (1967) The Use of Fast Fourier Transform for the Estimation of Power Spectra: A Method Based on Time Averaging Over Short, Modified Periodograms. IEEE Transactions on Audio and Electroacoustics, 15, 70-73. doi: *http://dx.doi.org/10.1109/TAU.1967.1161901*

Wen, H., & Liu, Z. (2016). Separating fractal and oscillatory components in the power spectrum of neurophysiological signal. *Brain Topography*, *29*(1), 13–26.

Wickham, H., Averick, M., Bryan, J., Chang, W., McGowan, L., François, R., Grolemund, G., Hayes,
A., Henry, L., & Hester, J. (2019). Welcome to the Tidyverse. *Journal of Open Source*
Software, *4*(43), 1686.

Womelsdorf, T., Valiante, T. A., Sahin, N. T., Miller, K. J., & Tiesinga, P. (2014). Dynamic circuit
motifs underlying rhythmic gain control, gating and integration. *Nat Neurosci*, *17*(8), 1031–
1039. *https://doi.org/10.1038/nn.376*

Wood, S. (2006). *R-Manual: The MGCV package*. Version 1.3–22. Technical Report.

Wood, S. N. (2003). Thin plate regression splines. *Journal of the Royal Statistical Society, Series B*
65, 95–114.

Wood, S. N. (2013). A simple test for random effects in regression models. *Biometrika 100*(4), 1005-
1010.

Wood, S. N. (2017). *Generalized additive models: An introduction with R*. 2nd ed. Boca Raton, FL:
CRC PressWood, S. N., Scheipl, F., & Faraway, J. J. (2013). Straightforward intermediate
rank tensor product smoothing in mixed models. *Stat. Comput. 23*, 341-360.