Data and Text Mining

dom2vec: Assessable domain embeddings and their use for protein prediction tasks

Damianos P. Melidis [1,*]**, Brandon Malone** [2]**, Wolfgang Nejdl** [1,3]

[1]L3S Research Center, Leibniz University of Hannover, Hanover, 30167, Germany,
[2]NEC Laboratories Europe, Heidelberg, 69115, Germany and
[3]Knowledge-based Systems Laboratory, Leibniz University of Hannover, Hanover, 30167, Germany.

*To whom correspondence should be addressed.

Abstract

Motivation: Word embedding approaches have revolutionized Natural Lange Processing (NLP) research. These approaches aim to map words to a low-dimensional vector space in which words with similar linguistic features are close in the vector space. These NLP approaches also preserve local linguistic features, such as analogy. Embedding-based approaches have also been developed for proteins. To date, such approaches treat amino acids as words, and proteins are treated as sentences of amino acids. These approaches have been evaluated either qualitatively, via visual inspection of the embedding space, or extrinsicaly, via performance on a downstream task. However, it is difficult to directly assess the intrinsic quality of the learned embeddings.
Results: In this paper, we introduce dom2vec, an approach for learning protein domain embeddings. We also present four *intrinsic* evaluation strategies which directly assess the quality of protein domain embeddings. We leverage the hierarchy relationship of InterPro domains, known secondary structure classes, Enzyme Commision class information, and Gene Ontology annotations in these assessments. Importantly, these evaluations allow us to assess the quality of learned embeddings independently of a particular downstream task, similar to the local linguistic features used in traditional NLP. We also show that dom2vec embeddings are competitive with, or even outperform, state-of-the-art approaches on downstream tasks.
Availability: The protein domain embeddings vectors and the entire code to reproduce the results will become available.
Contact: melidis@l3s.uni-hannover.de

1 Introduction

A primary way of how proteins evolve is through rearrangement of their functional/structural units, known as *protein domains* (Moore *et al.*, 2008; Forslund and Sonnhammer, 2012). The domains are independent folding and functional modules and so they exhibit conserved sequence segments. Prediction algorithms exploited this information and used as input features the domain composition of a protein for various tasks. For example (Chou and Cai, 2002) classified the cellular location and (Forslund and Sonnhammer, 2008; Doğan *et al.*, 2016) predicted the associated Gene Ontology (GO) terms. There exist two ways to represent domains; either by the linear order in a protein, *domain architecture*, (Scaiewicz and Levitt, 2015), or by a graph where nodes are domains and edges connect domains that co-exist in a protein (Moore *et al.*, 2008; Forslund and Sonnhammer, 2012).

Moreover, (Yu *et al.*, 2019) investigated if the domains architecture has a grammar as a natural spoken language. They compared the bi-gram entropy of domain architecture for PFAM domains (Sonnhammer *et al.*, 1998) to the respective entropy of the English language, showing that although it was lower than the English language, it was significantly different from a language produced after shuffling the domains. Prior to this result, methods had exploited domain architecture representation to various applications, such as fast homology search (Terrapon *et al.*, 2013) and retrieval of similar proteins (Marchler-Bauer *et al.*, 2016).

Word embeddings are unsupervised learning methods which have as input large corpora and they output a dense vector representation of words contained in the sentences of these documents based on the distributional semantic hypothesis, that is the meaning of a word can be understood by its context. Thus a word vector represents local linguistic features, such as lexical or semantical information, of the respective word. Several methods to train word embeddings have been established, for example (Collobert and Weston, 2008; Mikolov *et al.*, 2013b; Pennington *et al.*, 2014). These

1

representations have been shown to hold several properties such as analogy, grouping of semantically similar words (Mikolov *et al.*, 2013a; Drozd *et al.*, 2016). Importantly, these properties are learned without the need of a labeled data set. Word embeddings are currently the mainstream input for neural networks in the Natural Language Processing (NLP) field as first they reduce the feature space (compared to 1-hot representation) and second they provide word features that encapsulate relation between words based on linguistic features. The use of word embeddings improved the performance on most of the tasks (sentiment analysis, Named Entity Recognition (NER), etc).

Various methods to create embeddings for proteins are proposed (Asgari and Mofrad, 2015; Yang *et al.*, 2018; Bepler and Berger, 2019; Asgari *et al.*, 2019; Heinzinger *et al.*, 2019; Alley *et al.*, 2019). ProtVec fragmented the protein sequence in 3-mers for all possible starting shifts, then learned embeddings for each 3-mer and represented the respective protein as the average of its constituting 3-mer vectors (Asgari and Mofrad, 2015). SeqVec utilized and extended the Embeddings from Language Models (ELMo) (Peters *et al.*, 2018) to learn a dense representation per amino acid residue, resulting in matrix representations of proteins, created by concatenating their learned residue vectors (Heinzinger *et al.*, 2019).

Both approaches evaluated the learned representations qualitatively and quantitatively. Qualitatively by having plotted the reduced 2-D embedding space and reported the appearance of cluster of protein with similar properties (biophysical/chemical, structural, enzymatic, taxonomic). For quantitative evaluation, they measured the improvement of performance in down-stream tasks *(protein family classification, cellular location prediction, etc)*.

Focusing on their qualitative evaluation, it lacks the ability to assess different learned embeddings in a sophisticated manner. Indeed for word embeddings there is an increase in methods to evaluate words representations intrinsically such as (Schnabel *et al.*, 2015). All these techniques are thoroughly summarized by the survey (Lastra-Díaz *et al.*, 2019). This is a fruitful direction, because having such evaluation metrics we can validate the knowledge acquired by all trained embedding spaces. And further we can select the best performing space to input to the machine learning algorithm. However creating embeddings for single residues or k-mers residues does not enable intrinsic evaluation methods, as biological information for each such fine-grained feature cannot be obtained for all disposed proteins (that embeddings are learned from).

Given that Interpro database (release 70.0) contains domains for 80.9% of the UniProtKnowledgeBase (UniProtKB) sequences (The UniProt Consortium, 2017) and includes associated biological knowledge for the majority of domains (Mitchell and *et al.*, 2019), we trained domain embeddings and evaluated them both in intrinsic and extrinsic way.

This work has four major contributions:

- We constructed the linear representation for domains of all UniProtKB sequences with an identified Interpro domain. Then using word2vec method, we learned the vector representation for each Interpro domain based on this linear representation of proteins.
- We established intrinsic evaluation methods based on four distinct biological information for a domain. First we evaluated the learned (embedding) space by domain hierarchy (tree structure capturing family-subfamily relations provided by Interpro). We investigated the performance of a nearest neighbor classifier to predict the secondary structure class provided by SCOPe (Fox *et al.*, 2013) and the primary EC class in the learned embedding space. Finally, we examined the performance of this classifier to predict the GO molecular function class for three example model organisms and one human pathogen.
- To evaluate our embeddings extrinsically, we inputted the learned domains embeddings to simple neural networks and compared their performance with state-of-the-art methods in four datasets and five

tasks in total; surpassing both state-of-the-art methods for EC primary class prediction.
- We make available the trained domains embeddings to be used for protein supervised learning tasks by the research community.

2 Related work

2.1 Protein embedding methods

Works on protein embeddings can be divided in two methods based on their word assignment, the former learn embeddings for constant amino acid subsequences and the latter for variable length subsequences.

2.1.1 Constant length subsequence vectors

Early work in protein embeddings (Asgari and Mofrad, 2015) (ProtVec) belongs to this category. In this work, the authors split the protein sequence in 3-mers with the 3 possible starting shifts. They then used the skip-gram model from (Mikolov *et al.*, 2013b) to learn the embeddings for each distinct 3-mer. The embedding for a protein was taken as the mean of all its 3-mers. (Yang *et al.*, 2018) adapted ProtVec by using doc2vec (Le and Mikolov, 2014) to find the whole protein embedding. Similarly (Woloszynek *et al.*, 2019) computed embeddings for all k-mers using a range of k; they also used doc2vec to find the whole protein embedding. (Bepler and Berger, 2019) learned an embedding of each amino acid position incorporating global structural similarity between a pair of proteins and contact map information for each protein. They represented the alignment of two proteins as a soft symmetric alignment of the embeddings of the protein residues. Recently, SeqVec (Heinzinger *et al.*, 2019) applied and extended ELMo model (Peters *et al.*, 2018) to learn a contextualized embedding per amino acid position. Recently, UniRep was introduced (Alley *et al.*, 2019) to learn embeddings for amino acids by a language model that uses RNNs.

2.1.2 Variable-length subsequence vectors

ProtVecX (Asgari *et al.*, 2019) embeds proteins by first extracting (variable-length) motifs from proteins using a data compression algorithm, byte-pair encoding (Gage, 1994). ProtVec is then used to learn embeddings for the motifs.

2.2 Extrinsic evaluation methods

Extrinsic evaluation methods, like performance on a supervised learning task, are most commonly used to evaluate the quality of embeddings. To date, different papers have evaluated performance on different downstream tasks and using different datasets.

Sequence-level prediction (Asgari and Mofrad, 2015) predicted protein family and disorder, while (Yang *et al.*, 2018) evaluated embeddings by predicting the *Channelrhodopsin (ChR)* localization, the thermostability of *Cytochrome P450*, the *Rhodopsin* absorption wavelength and the *Epoxide hydrolase* enantioselectivity. (Bepler and Berger, 2019) predicted transmembrane regions of proteins, and (Heinzinger *et al.*, 2019) used subcellular localization and water solubility as validation. (Asgari *et al.*, 2019) consider venom toxin, subcellular localization, and enzyme primary class predictions tasks for downstream validation. (Alley *et al.*, 2019) predicted stability of proteins and the phenotype of diverse variants of the green fluorescent protein.

Per-residue prediction (Heinzinger *et al.*, 2019) predicted secondary structure and intrinsic disorder and (Alley *et al.*, 2019) predicted functional effect of single amino acid mutations.

2.3 Qualitative evaluation methods

Many of the described approaches use some form of qualitative evaluation. Commonly, the learned embeddings are projected to two dimensions using techniques like tSNE (Maaten and Hinton, 2008) or UMAP (McInnes *et al.*, 2018) to visually inspect the embeddings. While such approaches are helpful to gain trust in the embeddings, they do not provide a rigorous approach to compare the quality of multiple embedding spaces, such as those found when using different hyperparameters for the embedding models.

(Asgari and Mofrad, 2015) used a qualitative intrinsic evaluation approach for ProtVec. They visualized the 2-dimensional reduced protein space along with their biophysical and biochemical properties to report the appearance of clusters with similar biochemical properties.

For intrinsic evaluation they (Heinzinger *et al.*, 2019) visualized the 2-dimensional reduced protein space along with secondary structure class, the EC and the taxonomic kingdoms per protein.

3 Materials and methods

Our approach is summarized in Figure 1, in the following we explain the methodology for each part of the approach.

3.1 dom2vec

We now describe dom2vec, our novel approach for learning protein embeddings based on their domains.

3.1.1 Building domain architecture

Hereafter we will refer to the sequence of domains in a protein as its *domain architecture*. We consider two distinct strategies to represent a protein based on its domain architecture: *non-overlapping* and *non-redundant*. In both cases, the sequences are based on protein domain entries from Interpro. For efficiency, an interval tree is built for each protein to detect overlapping domains, and each protein is split into regions with overlapping domains.

Non-overlapping sequences. For each region with overlapping domains, all domains except the longest are removed.

Non-redundant sequences. For each region with overlapping domains, all domains with the same Interpro identifier, except the longest domain with each identifier, are removed.

In both cases, the domains in each protein are sorted by start position to construct its domain architecture. Following the approach of (Doğan *et al.*, 2016) we also added the "GAP" domain to annotate more than 30 amino acid subsequence that does not match any Interpro domain entry.

3.1.2 Training domain embeddings

Next, we learned task-independent embeddings for each domain using two variants of word2vec (Mikolov *et al.*, 2013b): continuous bag of words (CBOW) and skip-gram (SKIP). See (Mikolov *et al.*, 2013b) for technical details on the difference between these approaches. In our context, each domain is taken as a word, and each protein sequence is considered as a sentence. Thus, after learning, each domain is associated with a task-independent embedding.

In Section 3.3, we consider several *intrinsic* evaluation strategies to determine the quality of these embeddings for various hyperparamers of word2vec.

3.2 Qualitative evaluation

As a preliminary evaluation strategy, we used qualitative evaluation approaches adopted in existing work. To follow the qualitative approach of ProtVec and SeqVec we also visualized the embedding space for selected domain superfamilies, to answer the following research question,

Fig. 1. Summary of our approach divided in four parts, building two forms of domains architecture, training domain embeddings, performing intrinsic and extrinsic evaluation of embeddings. Numbers in parentheses indicate the sections discussing the respective part.

RQ: Did vectors of each domain superfamily form a cluster in the V_{emb}?

Evaluation To find out, we added the vector of each domain in a randomly chosen domain superfamily to an empty space. Then we performed principle component analysis (PCA) (Pearson, 1901) to reduce the space in two dimensions and observed the formed clusters.

3.3 Novel intrinsic evaluation methods

Previous work has evaluated the quality of embeddings only indirectly by measuring performance on downstream, supervised tasks, as described in Section 3.4. However, in the natural language processing field, the quality of a learned word embedding space is often evaluated *intrinsically* by considering relationships among words, such as analogies. Such an evaluation is important because it ensures the learned embeddings are meaningful without choosing a specific downstream task.

Such intrinsic evaluations cannot be performed for the ProtVec and SeqVec protein embeddings, because in contrast with these approaches dom2vec directly learns embeddings for protein domains. That is, protein domains are typically represented using structures like profile hidden Markov models (Eddy, 1998) rather than unique amino acid sequences. Thus, prior approaches, such as ProtVec, SeqVec, *cannot* learn unique embeddings per domain not allowing us to perform the same evaluation tasks for the existing protein embeddings.

We propose four intrinsic evaluation approaches for domain embeddings: domain hierarchy based on the family/subfamily relation, secondary structure class, Enzymatic Commission (EC) primary class, and Gene Ontology (GO) molecular function annotation.

We refer to the embedding space learned by word2vec for a particular set of hyperparameters as V_{emb}. We refer to the k nearest neighbors of a domain d as C_{nearest}^{d} found using the Euclidean distance. To inspect the relative performance of V_{emb} on each of the following evaluations, we *randomized* all domain vectors and run each evaluation task. That is, irrespective of the embedding method parameters and only for each different space dimensionality we assigned to each domain vector a newly created random vector and save this random space to be evaluated.

3.3.1 Domain hierarchy

Interpro defines a strict family-subfamily relationship among domains. This relationship is based on sequence similarity of the domain signatures.

We refer to the children of domain p as C^p. We use these relationships to evaluate an embedding space, posing the following research question,

RQ: Did vectors of hierarchically closely domains form clusters in the V_{emb}?

Evaluation We evaluate V_{emb} by retrieving $C_{nearest}^d$ of each domain. For all learned embedding spaces, we measured their recall performance, $Recall_{hier}$ defined as follows:

$$Recall_{hier} = \sum \frac{|C^p \cap C_{nearest}^p|}{|C^p|}. \tag{1}$$

3.3.2 Secondary structure class
We extracted the secondary structure of Interpro domains from the SCOPe database and form the following research question,

RQ: Did vectors of domains, with same secondary structure class, form clusters in the V_{emb}?

Evaluation We evaluated V_{emb} by retrieving $C_{nearest}^d$ of each domain. Then we applied stratified cross-fold validation and measured the performance of a k-nearest neighbor classifier to predict the structure class of each domain. The intrinsic evaluation performance metric is the average accuracy across all folds, $Accuracy_{SCOPe}$.

3.3.3 Enzyme Commission (EC) primary class
The enzymatic activity of each domain is given by its primary EC class (Fleischmann *et al.*, 2004) and pose the following research question,

RQ: Did vectors of domains, with same secondary structure class, form clusters in the V_{emb}?

Evaluation We again evaluate V_{emb} using k nearest neighbors in a stratified cross-validation setting. Average accuracy across all folds is again used to quantify the intrinsic quality of the embedding space.

3.3.4 GO molecular function
For our last intrinsic evaluation, we aimed to assess V_{emb} using the molecular function GO annotation. We extracted all molecular function GO annotations associated with each domain.[1] Since model organisms have the most annotated proteins we created GO molecular function data sets for one example prokaryote (*Escherichia coli* denoted *E.coli*), one example simple eukaryote (*Saccharomyces cerevisiae* denoted *S.cerevisiae*) and one complex eukaryote (*Homo sapiens* denoted *Human*). To assess our embeddings also for not highly annotated organisms, we included a molecular function data set for an example human pathogen (*Plasmodium falciparum*, denoted as *Malaria*). Finally, we pose the following research question,

RQ: Did vectors of domains, with same GO molecular function, form clusters in the V_{emb}?

Evaluation We again evaluate an embedding space using k nearest neighbors in a stratified cross-validation setting. Average accuracy across all folds is again used to quantify performance.

3.4 Extrinsic evaluation

In addition to assess the learned V_{emb} we also examine the performance change in downstream tasks. That is for four data sets and five different supervised tasks, we feeded the domain representations in simple neural networks and compare the performance of our model with state-of-the-art protein embeddings.

3.4.1 Simple neural models for downstream tasks
We consider a set of simple, well-established neural models to combine the domain embeddings for each protein to perform downstream tasks, that is,

for *extrinsic* evaluation tasks. In particular, we use FastText (Joulin *et al.*, 2017), convolutional neural networks (CNNs) (LeCun *et al.*, 1998), and recurrent neural networks (RNNs) with long-short term memory (LSTM) cells (Hochreiter and Schmidhuber, 1997) and bi-directional LSTMs. We leave evaluation with more sophisticated models, such as transformers like BERT (Devlin *et al.*, 2018), for future work.

3.4.2 DeepLoc
(Almagro Armenteros *et al.*, 2017) introduced *DeepLoc* dataset, which includes 14,004 protein instances with features the uniprot id, the amino acid sequence and two distinct labels, a multi-class task for cellular component location and binary task for membrane or soluble. Finally, we removed all instances with duplicate set of domains, resulting in total of 10,107 protein instances. The class distribution for the two tasks is shown in the Table 1 and Table 2.

Evaluation The location data set is a multi-class task, thus we used as performance metric a multi-class generalization of area under the receiver operating characteristic curve (mc-AuROC). For the membrane data set which is a binary task, the performance metric was the area under the receiver operating characteristic curve (AuROC).

3.4.3 TargetP
We downloaded the TargetP data set provided by (Emanuelsson *et al.*, 2000). To compare with ProtVecX we also used the non-plant data set. This data set consists of 2,738 proteins accompanying with their uniprot id, sequence and the cellular location label which can be nuclear, cytosol, pathway or signal and mitochondrial. Finally, we removed all instances with duplicate set of domains, resulting in total of 2,731. This is a multi-class task and its class distribution is summarized in the Table 3.

Evaluation For the TargetP we used the mc-AuROC performace metric.

3.4.4 Toxin
(Gacesa *et al.*, 2016) introduced a data set associating protein sequence to toxic or other physiological content. To compare with ProtVecX we used the hard setting which provides uniprot id, sequence and the label toxin content or non-toxin content, for 15,496 proteins. Finally, we kept only the proteins with unique domain composition, resulting to 3,620 protein instances in total. This is a binary task and the class distribution is shown at Table 4.

Evaluation As Toxin data set is binary task, we used AuROC as performance metric.

3.4.5 NEW
We downloaded the NEW data set from (Li *et al.*, 2017). For each of the 22,618 proteins the data set provides sequence and the EC number (class). The primary enzyme class, first digit of EC number, is our label on this prediction task, resulting in a multi-class task. Finally, we removed all instances with duplicate domain composition, resulting in a total of 20,881 protein instances. The possible classes are 6 and the class distribution is shown at Table 5.

Evaluation NEW data set is a multi-class task, thus we used mc-AuROC as performance metric.

3.4.6 Data partitioning
We divided each data set into 70/30% train and test splits. To perform model selection, we created inner three-fold cross validation sets on each train split. We investigated the generalization of the classifier for increasing number of training examples, by allowing training only on the 1%, 2%, 5%, 10%, 20%, 50% from the whole train set and then predict on the test

---

[1] In order to account for differences in specificity of different GO annotations, we always used the depth-1 ancestor of each annotation (that is, children of the root molecular function term, GO:0003674).

Location	No. of proteins		Membrane/Soluble	No. of proteins		Location	No. of proteins		Toxicity	No. of proteins		EC Primary class	No. of proteins
Nucleus	3,048		Membrane	2,416		Nuclear	1,211		Toxin	1,564		Oxidoreductases	3,244
Cytoplasm	2,184		Soluble	3,521		Cytosolic	438		Non toxin	2,056		Transferases	7,940
Extracellular	1,025					Pathway/Signal	714					Hydrolases	5,603
Mitochondrion	1,119		Table 2. DeepLoc membrane			Mitochondrial	368		Table 4. Toxin			Lyases	1,409
Cell membrane	971											Isomerases	1,100
Endoplasmic reticulum (ER)	622					Table 3. TargetP						Ligases	1,585
Plastid	536												
Golgi apparatus	255											Table 5. NEW	
Lysosome/Vacuole	235												
Peroxisome	112												

Table 1. DeepLoc location

Fig. 2. Non overlapping and non redundant domain architecture of Diphthine synthase protein. Because all domains are overlapping with the largest one, colored in blue, the non-overlapping sequence is just the single longest domain (IPR035966). All other domains have a unique Interpro id, so the set of non-redundant sequences includes all presented domains sorted by starting position; we colored all these other domains in fading hues of gray based on their starting position.

set. To perform significance testing we created 20 training subsamples for each such percentage.

4 Results and discussion

4.1 Building domain architecture

We downloaded the domain hits, protein2ipr.dat, for UniProt proteins from the Interpro version 75. This file contained 128 660 257 proteins with Interpro signature, making up the 80.9% of the total UniprotKB proteome (version 2019_06). For all these proteins we extracted the non-overlapping and non-redundant sequences, which we processed in the next section. The number of unique non-overlapping sequence was $(35\,183 + 1)$ plus the "GAP" domain and non redundant was $(36\,872 + 1)$ plus the "GAP". Comparing to total number of domains in Interpro version 75, which was 36 872, we observed that non-overlapping sequences captured 95.42% and the non-redundant captured 100% of the Interpro domains. Figure 2 demonstrates the created domain architectures after preprocessing for the subdomains for the tetrapyrrole methylase domain *Diphthine synthase* protein (see (Mitchell and *et al.*, 2019) for more details).

4.2 Training domain embeddings

4.2.1 Domain architecture
Before we applied the word2vec package we examined the histograms of number of domains per protein for non-overlapping and non-redundant sequences. We show the histogram of the number of non-overlapping sequences per protein in Figure 3. We observed that these distributions

Fig. 3. Histogram of non-overlapping sequences (domains) per protein. We used log-scale for both axes; $\log_2$ used for the x-axis, the number domains and $\log_{10}$ for the y-axis, the number of proteins.

are skewed and their mode, most frequent number of domains per protein, was one. Then we used both CBOW and SKIP algorithms to learn domain embeddings. We used the following parameters sets. Based on the histograms we picked the window parameter for word to be 2 or 5, $w = \{2, 5\}$. For the number of dimensions, we used common values from the NLP literature, $dim = \{50, 100, 200\}$. We trained the embeddings from 5 to 50 epochs with step size 5 epochs $ep = \{5, 10, 15, \ldots, 50\}$. Finally, all other parameters were set to their default values. For example, the negative sampling parameter was left to default, ng=5.

4.3 Qualitative evaluation

We randomly selected five Interpro domain superfamilies to perform the experiment. The selected domain superfamilies were *PMP-22/EMP/MP20/Claudin superfamily* with parent Interpro id IPR004031, *small GTPase superfamily* with parent Interpro id IPR006689, *Kinase-pyrophosphorylase* with parent Interpro id IPR005177, *Exonuclease, RNase T/DNA polymerase III* with parent Interpro id IPR013520 and *SH2 domain* with parent Interpro id IPR000980. Similarly to domain hierarchy, we loaded the parent-child tree T_{hier}, provided by Interpro, and for each domain superfamily starting from the parent domain we included recursively all domains that have subfamily relation with this parent domain. For example the *Kinase-pyrophosphorylase* domain superfamily has domain parent IPR005177, which in turn has two immediate domain subfamilies IPR026530, IPR026565 and IPR026565 has domain subfamily IPR017409, consequently the set of domains for *Kinase-pyrophosphorylase* domain superfamily is {IPR005177,IPR026530,IPR026565,IPR017409}.

We retrieved the vectors for each domain in a domain superfamily using the $V_{emb}^{\mathrm{downstream}}$, the best performing dom2vec space selected in Section

Fig. 4. Visualization of domain vectors for five domain superfamilies in best performing dom2vec space ($V_{emb}^{\text{downstream}}$).

4.5. Finally, we visualized the two-dimensional PCA-reduced space at Figure 4. From this Figure 4, we observed that domains embeddings of each superfamily form well-separated clusters; the cluster of *Exonuclease, RNase T/DNA polymerase III* superfamily has the highest dispersion of all presented superfamilies.

4.4 Novel intrinsic evaluation

In the following, we evaluated each instance of learned embedding space V_{emb} for both non-overlapping and non-redundant representations of domain architectures. An instance of V_{emb} space is the embeddings space learned for each combination of the product $non\_overlap \times w \times dim \times ep$. Thus, the total number of embeddings spaces is $|non\_overlap| \times |w| \times |dim| \times |ep| = 2 \times 2 \times 3 \times 10 = 120$. Let V_{emb}^{i} denote such embedding space instance. In the following subsection we evaluated each V_{emb}^{i} instance for domain hierarchy, secondary structure, enzymatic process and GO molecular function.

4.4.1 Domain hierarchy
We loaded the parent-child tree T_{hier}, provided by Interpro, consisting of 2 430 parent domains. Then for each V_{emb}^{i} we compared the actual and predicted children of each parent, and we averaged out the recall for all parents. For ease of presentation, we show the complete results in the supplementary; however, in the following we discuss the results. Please see supplementary A 5 for the complete results.

From Tables 1 and 2 (appendix A), we observed that SKIP performed better overall, and the embeddings learned from non-redundant annotations always have better average recall values compared to non-overlapping. The best performing V_{emb}^{i} achieved average $Recall_{hier}$ of 0.538; that embedding space was trained using non-redundant annotations with SKIP, $w = 2$ and $dim = 200$. We plotted the histogram of recall values for this best performing space, Figure 1 (Supplementary A), and we observed that the embeddings space brought close domains with *not known* family-subfamily relation for almost the one third of the parent domains (827 out of 2 430). To diagnose the reason for this moderate performance, we plotted the histogram of the number of children for each parent having recall 0, Figure 2 (Supplementary A). We observed that most of the parents have only one child. Consequently, the embedding space should have been very precise for each of these parent child relation in order to acquire better recall than 0. We compared this moderate performance of V_{emb}

with the performance of the randomized spaces, which was equal to 0. Thus, we concluded that our embedding spaces greatly outperformed each randomized space for domain hierarchy relation. Consequently, we can answer our initial question: the majority of domains of the same hierarchy are placed in close proximity in the embedding space.

4.4.2 Secondary structure class
We extracted the SCOPe class for each Interpro domain from the interpro.xml file. This resulted to 25 196 domains with unknown secondary structure class, 9 411 with single secondary structure class and 2 265 domains with more than one assigned classes (multi-label). For clarity, we removed all multi-label and unknown instances leaving with 9 411 single-labeled instances; the class distribution of the resulting data set is shown in Table 6.

To answer the research question, we measured the performance of *k-NN* classifier in each V_{emb}^{i} to examine the homogeneity of the space with respect to the SCOPe class. We split the 9 411 domains in 5-fold stratified cross validation sets. To test the change in prediction accuracy for an increasing number of neighbors, we used different sets of neighbors, namely, $k = \{2, 5, 20, 40\}$. We summarized the results for the best performing $C_{nearest}^{d}$ which was for $k = 2$ on Tables 7 and 8. We compared these accuracy measurements to the respective ones of the random spaces, and we found that the lowest accuracy values, achieved for CBOW $w=5$ using non overlapping domains, are twice as high as the accuracy values of the random spaces for all possible dimensions. We observed again that the non-redundant domains resulted in higher accuracy compared to non-overlapping domains. The best performing $C_{nearest}^{d}$ was for 2-NN for (non-redundant, SKIP, $w=5$,$dim=50$,$ep=25$) with average accuracy over the folds equal to 84.56. Consequently, we can answer our second research question: domain embeddings of the same secondary structure class form distinct clusters in a learned embedding space.

4.4.3 Enzyme Commission (EC) primary class
To this end we extracted the EC primary class from the interpro.xml file. This resulted in 29 354 domains with unknown EC, 7 248 domains with only one EC and 721 with more than one EC. As before, we removed all multi-label and unknown instances leaving 7 428 domains with known EC. For each V_{emb}^{i} we augmented a domain instance with its vector representation, and then we used k-NN to predict the EC. We again omit the entire result tables and we discuss the main results. Please see supplementary B 5 for the complete results.

We compared these accuracy measurements to the respective ones of the random spaces. We found that the minimum average $Accuracy_{EC}$ value was equal to 60.51 and was achieved using CBOW $w=5$ for non-overlapping sequences. That value is approximately twice as large than the accuracy values of the random spaces for all possible dimensions (maximum average $Accuracy_{EC}$ for random space with $dim=100$ was 32.64). The best results were always produced using 2-NN, and we saw once more that SKIP trained on non-redundant sequences performed the best with maximum average accuracy of 90.85 (SKIP,$w=5$,$dim=50$,$ep=30$). Consequently, we can answer our third research question: domain embeddings of the same EC primary class form distinct clusters in a learned embedding space.

4.4.4 GO molecular function
We parsed the GO annotation file of Interpro to extract first-level GO molecular function for domains for the four organisms. We followed the same methodology to examine the homogeneity of a V_{emb} with respect to GO molecular function annotations. Thus, for each V_{emb}^{i}, we augmented each domain by its vector and its GO label, and we classified each domain using $C_{nearest}^{d}$. As before, we used 5-fold stratified cross-validation

SCOPe class	No. of domains
a	1,868
b	1,806
a/b	2,303
a+b	2,320
multi-domain	304
membrane/cell	309
small	501

Table 6. SCOPe class summary

Emb. Meth, w	dim=50	dim=100	dim=200
CBOW, w=2	50.01(ep=30)	50.69(ep=25)	50.45(ep=20)
CBOW, w=5	49.59(ep=25)	50.03(ep=25)	48.82(ep=15)
SKIP, w=2	**51.83**(ep=30)	51.79(ep=20)	51.78(ep=15)
SKIP, w=5	51.54(ep=35)	51.65(ep=15)	51.34(ep=15)
random	22.75 (k=40)	24.18 (k=40)	23.39 (k=40)

Table 7. k-NN $Accuracy_{SCOPe}$ for non-overlapping sequences (k=2), best shown in bold case

Emb. Meth, w	dim=50	dim=100	dim=200
CBOW, w=2	77.09 (ep=5)	76.35 (ep=5)	75.77 (ep=5)
CBOW, w=5	78.15 (ep=5)	76.94 (ep=5)	76.84 (ep=5)
SKIP, w=2	84.42 (ep=45)	84.42 (ep=40)	84.08 (ep=30)
SKIP, w=5	**84.56** (ep=25)	84.06 (ep=45)	83.72(ep=10)
random	23.39 (k=40)	23.49 (k=40)	22.76 (k=20)

Table 8. k-NN $Accuracy_{SCOPe}$ for non-redundant sequences (k=2), best shown in bold case

for evaluation. In our experiments, we varied the number of neighbors $k = \{2, 5, 20, 40\}$ to test its influence to the change of performance. For space limitations, we summarized the performances showing only the best average accuracy over the number of neighbors. For the ease of presentation we omit the resulted tables for three first organisms and show only for *Human*; however, we discuss the results for all organisms. Please see supplementary C 5 for full results.

For *Malaria*, the best average accuracy was 76.86, scored by the 2-NN for the V_{emb}^{malaria} corresponding to (non-redundant, SKIP, w=5,dim=100,ep=40). The minimum accuracy value was 56.94 and was achieved using CBOW with w=5 using non-overlapping sequences. We compared this minimum accuracy to the maximum accuracy obtained in a random space, which was 47.57. That is, even the worst-performing dom2vec approach outperformed the random baseline by ten percent.

For *E.coli*, the best average accuracy was 81.72, scored using 2-NN for the V_{emb}^{ecoli} corresponding to (non-redundant,SKIP,w=5,dim=50,ep=5). The minimum accuracy value was 67.34, achieved using CBOW with w=5 using non-overlapping sequences. For *E.coli*, the random baseline was still worse, with an accuracy of 64.46.

For *Yeast*, the best average accuracy was 75.10, scored using 5-NN for the V_{emb}^{yeast} corresponding to (non-redundant,SKIP,w=5,dim=50,ep=50). The minimum accuracy value was 59.82, achieved using CBOW with w=5 using non-overlapping sequences. We compared this miminum accuracy to the maximum accuracy obtained in a random space, which was 53.73.

For *Human*, the best average performance are shown in Table 10. The best average accuracy was 75.96, scored by 2-NN for the V_{emb}^{human}(non-redundant, SKIP, w=5,dim=50,ep=40). We compared the minimum accuracy values, obtained by CBOW with w=5, to accuracy values of the random spaces, and we found that the worst-performing dom2vec was 20 percentage values higher than the random baseline.

For all four example organisms, we observed that the SKIP on non-redundant sequences produced V_{emb} where C_{nearest}^{d} achieved the best average accuracy in. For the three out of the four organisms, the best performances were achieved for the lowest number of dimensions (dim=50). In all cases, we found that the worst-performing dom2vec embeddings outperformed the random baselines.

4.5 Selecting trained embeddings

Based on the previous four experiments, we aimed to evaluate the learned V_{emb} spaces and select the best domain embedding space for downstream tasks. In all experiments, the SKIP algorithm for non-redundant sequences created best performing embedding spaces. From the individual results, we saw that the configuration of parameters (non-redundant, SKIP, w=5, dim=50) brought best results in C_{nearest}^{d} performance for SCOPe, EC and GO for *E.coli*,*Yeast*,*Human*, second best for *Malaria* and the sixth best average recall (0.507) for the domain hierarchy relation. Therefore, for the next of the work $V_{emb}^{\text{downstream}}$ denotes the space produced by (non redundant, SKIP, w=5, dim=50).

4.6 Extrinsic evaluation

4.6.1 Extracting domain architecture

For each data set that contained the UniProt identifier for the protein instance, we extracted the domain architecture for non redundant sequences, already created in Section 4.1. For all proteins whose UniProt identifier could not be matched, or for data sets not providing the protein identifier, we use InterProScan (Jones and *et al.*, 2014) to find the domain hits per protein. For proteins without a domain hit after InterProScan, we created a protein-specific, artificial protein-long domain; for example, for the protein G5EBR8, we assigned a protein-long domain named "G5EBR8_unk_dom".

4.6.2 Model selection

To select which simple neural model we should compare to the baselines, we perform hyperparameter selection using an inner, three-fold cross validation on the training set; the test set is not used to select hyperparameters. We used common parameters, dropout of 0.5, batch size of 64, the Adam optimizer (Kingma and Ba, 2015) with learning rate of 0.0003, weight decay of 0 and number of epochs equal to 300. As a final hyperparameter, we allowed updates to the learned domain embeddings, initialized by $V_{emb}^{\text{downstream}}$. The results are shown in Table 11. The CNN model obtained the best results.

Then, we used the same network as the one in right side of Figure 1 of (Heinzinger *et al.*, 2019); namely, the network first averages the 100 (ProtVec) or 1 024 (SeqVec) dimensional embedding vector for a protein; it then applies a fully connected layer to compress a batch of such vectors into 32 dimensions. Next, a ReLU activation function (with 0.25 dropout) was applied to that vector, followed by batch normalization. Finally, another fully connected layer was followed by the prediction layer. The performance results are shown in Figure 5.

4.6.3 Evaluation

For all datasets, we selected 20 random subsamples of the training set of varying sizes (see Figure 5). We then selected hyperparameters and trained models as described. Finally, we used the trained models on each test set. Thus, this evaluation shows how differences in the training set affect performance on the test set.

4.6.4 Statistical significance

For DeepLoc location, membrane and TargetP SeqVec significantly outperformed the other two methods (paired sample t-test, Benjamini-Hochberg multiple-test corrected p-value <0.05). For the DeepLoc location and membrance data sets, dom2vec significantly outperformed ProtVec when the model was trained on the whole data set. For TargetP, dom2vec significantly outperformed ProtVec for all percentage subsamples of the training set.

For the Toxin data set, both baselines significantly outperformed dom2vec. We hypothesized that this is related to the finding of original

GO class	No. of domains
Catalytic activity	1,945
Binding	1,583
Transporter activity	377
Molecular transducer activity	355
Structural molecule activity	262
Transcription regulator activity	203
Molecular function regulator	168
Cargo receptor activity	9
Molecular carrier activity	1
Cargo adaptor activity	1

Table 9. GO molecular function distribution (Human)

Emb. Meth, w	dim=50	dim=100	dim=200
CBOW, w=2	66.94(ep=5)	66.32(ep=5)	66.32(ep=5)
CBOW, w=5	67.77(ep=5)	65.87(ep=5)	65.77(ep=5)
SKIP, w=2	74.77(ep=40)	74.18(ep=5)	73.14(ep=5)
SKIP, w=5	**75.96**(ep=40)	75.53(ep=10)	74.98(ep=5)
random	37.05 (k=40)	37.03 (k=20)	37.05 (k=40)

Table 10. k-NN $Accuracy_{GO}$ for non-redundant sequences, when k is not shown k=2, best shown in bold case

Model \ Data set	location	membrane	TargetP	Toxin	NEW
CNN, size=1,filters=64	**0.7992**	**0.8138**	**0.8873**	**0.7425**	**0.9869**
FastText (uni-gram)	0.7733	0.7688	0.8498	0.7403	0.9837
FastText (uni&bi-gram)	0.7421	0.7168	0.8117	0.7214	0.979
LSTM, dim=64,layer=1	0.7733	0.7923	0.8607	0.7551	0.9858
bi-LSTM, dim=64,layer=1	0.7792	0.7951	0.8691	0.7504	0.9857

Table 11. Average performance of simple neural architectures using as input dom2vec on inner three-fold cross validation. For DeepLoc location and Toxin AuROC is shown and for the rest of the data sets mc-AuROC is shown. Best values shown in bold case.

work that a non-linear classifier with *only* sequence features as input achieved the state-of-the-art performance (Gacesa *et al.*, 2016).

For the NEW data set dom2vec significantly outperformed both baselines. This finding supports the result in the original work, which showed that domain features are *more* important than sequence features to predict enzymatic class of a protein (Li *et al.*, 2017).

We hypothesize two reasons that SeqVec outperforms dom2vec for DeepLoc and TargetP. First, SeqVec updates an amino-acid based embedding layer but dom2vec approach updates a domain embedding layer. Therefore, if the intersection of domains between training and testing is much smaller than the respective intersection of amino acids, then dom2vec will experience the out-of-vocabulary problem (Luong

et al., 2015). Second, we removed duplicate instances based on domain architecture and not on sequence similarity; consequently, the training and testing data sets may still include proteins with very similar amino acid sequences.

5 Conclusions

We presented dom2vec, an approach for learning protein domain embeddings using the domain architecture of proteins. We *intrinsically* evaluated the dom2vec domain embeddings using four sources of biological knowledge of protein domains. In our evaluation, we found

Fig. 5. Test performance of models trained on 20 subsamples of 1%, 2%, 5%, 10%, 20%, 50% of the training set and on the whole training set. The marked points represent the mean performance on the entire test set and the shaded regions show one standard deviation above and below the mean.

that secondary structure, enzymatic commission class, and GO molecular function are similar to the notion of local linguistic features in NLP (such as analogies) for protein domains. Importantly, intrinsic evaluation allows us to assess the quality of learned embeddings independently of a particular downstream task. Finally, we compared the performance of dom2vec embeddings with state-of-the-art approaches for 5 downstream protein prediction tasks. dom2vec was competitive, especially when large training sets are available, and it outperformed the state of the art on one of the tasks.

References

Alley, E. C., Khimulya, G., Biswas, S., AlQuraishi, M., and Church, G. M. (2019). Unified rational protein engineering with sequence-based deep representation learning. *Nature methods*, **16**(12), 1315–1322.

Almagro Armenteros, J. J., Sønderby, C. K., Sønderby, S. K., Nielsen, H., and Winther, O. (2017). DeepLoc: prediction of protein subcellular localization using deep learning. *Bioinformatics*, **33**(21), 3387–3395.

Asgari, E. and Mofrad, M. R. K. (2015). Continuous distributed representation of biological sequences for deep proteomics and genomics. *PLOS ONE*, **10**(11), e0141287.

Asgari, E., McHardy, A. C., and Mofrad, M. R. K. (2019). Probabilistic variable-length segmentation of protein sequences for discriminative motif discovery (DiMotif) and sequence embedding (ProtVecX). *Scientific Reports*, **9**(3577).

Bepler, T. and Berger, B. (2019). Learning protein sequence embeddings using information from structure. In *Proceedings of the 7^{th} International Conference on Learning Representations*.

Chou, K.-C. and Cai, Y.-D. (2002). Using functional domain composition and support vector machines for prediction of protein subcellular location. *Journal of Biological Chemistry*, **277**(48), 45765–45769.

Collobert, R. and Weston, J. (2008). A unified architecture for natural language processing: Deep neural networks with multitask learning. In *Proceedings of the 25^{th} International Conference on Machine Learning*.

Devlin, J., Chang, M.-W., Lee, K., and Toutanova, K. (2018). Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*.

Doğan, T., MacDougall, A., Saidi, R., Poggioli, D., Bateman, A., O'Donovan, C., and Martin, M. J. (2016). UniProt-DAAC: domain architecture alignment and classification, a new method for automatic functional annotation in UniProtKB. *Bioinformatics*, **32**(15), 2264–2271.

Drozd, A., Gladkova, A., and Matsuoka, S. (2016). Word embeddings, analogies, and machine learning: Beyond king-man+woman=queen. In *Proceedings of the 26^{th} International Conference on Computational Linguistics: Technical Papers*.

Eddy, S. R. (1998). Profile hidden markov models. *Bioinformatics (Oxford, England)*, **14**(9), 755–763.

Emanuelsson, O., Nielsen, H., Brunak, S., and Von Heijne, G. (2000). Predicting subcellular localization of proteins based on their n-terminal amino acid sequence. *Journal of Molecular Biology*, **300**(4), 1005–1016.

Fleischmann, A., Darsow, M., Degtyarenko, K., Fleischmann, W., Boyce, S., Axelsen, K. B., Bairoch, A., Schomburg, D., Tipton, K. F., and Apweiler, R. (2004). Intenz, the integrated relational enzyme database. *Nucleic acids research*, **32**(suppl_1), D434–D437.

Forslund, K. and Sonnhammer, E. L. (2008). Predicting protein function from domain content. *Bioinformatics*, **24**(15), 1681–1687.

Forslund, K. and Sonnhammer, E. L. (2012). Evolution of protein domain architectures. In *Evolutionary Genomics*, pages 187–216. Springer.

Fox, N. K., Brenner, S. E., and Chandonia, J.-M. (2013). SCOPe: Structural classification of proteins–extended, integrating SCOP and ASTRAL data and classification of new structures. *Nucleic Acids Research*, **42**(D1), D304–D309.

Gacesa, R., Barlow, D. J., and Long, P. F. (2016). Machine learning can differentiate venom toxins from other proteins having non-toxic physiological functions. *PeerJ Computer Science*, **2**, e90.

Gage, P. (1994). A new algorithm for data compression. *The C Users Journal*, **12**(2), 23–38.

Heinzinger, M., Elnaggar, A., Wang, Y., Dallago, C., Nechaev, D., Matthes, F., and Rost, B. (2019). Modeling aspects of the language of life through transfer-learning protein sequences. *BMC Bioinformatics*, **20**(723).

Hochreiter, S. and Schmidhuber, J. (1997). Long short-term memory. *Neural Computation*, **9**(8), 1735–1780.

Jones, P. and *et al.* (2014). InterProScan 5: genome-scale protein function classification. *Bioinformatics*, **30**(9), 1236–1240.

Joulin, A., Grave, E., Bojanowski, P., and Mikolov, T. (2017). Bag of tricks for efficient text classification. In *Proceedings of the 15^{th} Conference of the European Chapter of the Association for Computational Linguistics*.

Kingma, D. P. and Ba, J. L. (2015). Adam: A method for stochastic optimization. In *Proceedings of the 3^{rd} International Conference on Learning Representations*.

Lastra-Díaz, J. J., Goikoetxea, J., Taieb, M. A. H., García-Serrano, A., Aouicha, M. B., and Agirre, E. (2019). A reproducible survey on word embeddings and ontology-based methods for word similarity: linear combinations outperform the state of the art. *Engineering Applications of Artificial Intelligence*, **85**, 645–665.

Le, Q. and Mikolov, T. (2014). Distributed representations of sentences and documents. In *Proceedings of the 31^{st} International Conference on Machine Learning,*.

LeCun, Y., Bottou, L., Bengio, Y., Haffner, P., *et al.* (1998). Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, **86**(11), 2278–2324.

Li, Y., Wang, S., Umarov, R., Xie, B., Fan, M., Li, L., and Gao, X. (2017). DEEPre: sequence-based enzyme EC number prediction by deep learning. *Bioinformatics*, **34**(5), 760–769.

Luong, T., Sutskever, I., Le, Q., Vinyals, O., and Zaremba, W. (2015). Addressing the rare word problem in neural machine translation. In *Proceedings of the 53^{rd} Annual Meeting of the Association for Computational Linguistics*.

Maaten, L. v. d. and Hinton, G. (2008). Visualizing data using t-sne. *Journal of machine learning research*, **9**(Nov), 2579–2605.

Marchler-Bauer, A., Bo, Y., Han, L., He, J., Lanczycki, C. J., Lu, S., Chitsaz, F., Derbyshire, M. K., Geer, R. C., Gonzales, N. R., *et al.* (2016). CDD/SPARCLE: functional classification of proteins via subfamily domain architectures. *Nucleic Acids Research*, **45**(D1), D200–D203.

McInnes, L., Healy, J., and Melville, J. (2018). Umap: Uniform manifold approximation and projection for dimension reduction. *arXiv preprint arXiv:1802.03426*.

Mikolov, T., Sutskever, I., Chen, K., Corrado, G. S., and Dean, J. (2013a). Distributed representations of words and phrases and their compositionality. In *Advances in Neural Information Processing Systems* 26.

Mikolov, T., Chen, K., Corrado, G. S., and Dean, J. (2013b). Efficient estimation of word representations in vector space. In *Proceedings of the 1^{st} International Conference on Learning Representations*.

Mitchell, A. L. and *et al.* (2019). InterPro in 2019: improving coverage, classification and access to protein sequence annotations. *Nucleic Acids Research*, **47**(D1), D351–D360.

Moore, A. D., Björklund, Å. K., Ekman, D., Bornberg-Bauer, E., and Elofsson, A. (2008). Arrangements in the modular evolution of proteins. *Trends in Biochemical Sciences*, **33**(9), 444–451.

Pearson, K. (1901). Liii. on lines and planes of closest fit to systems of points in space. *The London, Edinburgh, and Dublin Philosophical Magazine and Journal of Science*, **2**(11), 559–572.

Pennington, J., Socher, R., and Manning, C. (2014). GloVe: Global vectors for word representation. In *Proceedings of the* 2014 *Conference on Empirical Methods in Natural Language Processing*.

Peters, M. E., Neumann, M., Iyyer, M., Gardner, M., Clark, C., Lee, K., and Zettlemoyer, L. (2018). Deep contextualized word representations. In *Proceedings of the 16^{th} Annual Conference of the North American Chapter of the Association for Computational Linguistics : Human Language Technologies*.

Scaiewicz, A. and Levitt, M. (2015). The language of the protein universe. *Current Opinion in Genetics & Development*, **35**, 50–56.

Schnabel, T., Labutov, I., Mimno, D., and Joachims, T. (2015). Evaluation methods for unsupervised word embeddings. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*.

Sonnhammer, E. L., Eddy, S. R., Birney, E., Bateman, A., and Durbin, R. (1998). Pfam: multiple sequence alignments and HMM-profiles of protein domains. *Nucleic Acids Research*, **26**(1), 320–322.

Terrapon, N., Weiner, J., Grath, S., Moore, A. D., and Bornberg-Bauer, E. (2013). Rapid similarity search of proteins using alignments of domain arrangements. *Bioinformatics*, **30**(2), 274–281.

The UniProt Consortium (2017). UniProt: the universal protein knowledgebase. *Nucleic Acids Research*, **45**(D1), D158–D169.

Woloszynek, S., Zhao, Z., Chen, J., and Rosen, G. L. (2019). 16s rRNA sequence embeddings: Meaningful numeric feature representations of nucleotide sequences that are convenient for downstream analyses. *PLoS Computational Biology*, **15**(2), e1006721.

Yang, K. K., Wu, Z., Bedbrook, C. N., and Arnold, F. H. (2018). Learned protein embeddings for machine learning. *Bioinformatics*, **34**(15), 2642–2648.

Yu, L., Tanwar, D. K., Penha, E. D. S., Wolf, Y. I., Koonin, E. V., and Basu, M. K. (2019). Grammar of protein domain architectures. *Proceedings of the National Academy of Sciences*, **116**(9), 3636–3645.

Supplementary Information

Supplementary A: Domain hierarchy

Average recall for all Interpro parents in T_{hier}, see main paper, are shown in Tables 1 and 2. The histogram of average recall for best performing embedding space is shown at Figure 1. Finally, the histogram of number of children for each parent having $Recall_{hier}$=0, is shown at Figure 2.

Fig. 1. $Recall_{hier}$ histogram for SKIP, w=2, dim=200, ep=5 for non redundant annotations.

Fig. 2. Histogram of number of children for parents with $Recall_{hier}$=0.

Emb. Meth, w	dim=50	dim=100	dim=200
CBOW, w=2	0.242 (ep=15)	0.259 (ep=20)	0.263 (ep=15)
CBOW, w=5	0.242 (ep=45)	0.252 (ep=30)	0.25(ep=15)
SKIP, w=2	0.287 (ep=20)	**0.316** (ep=30)	0.32 (ep=20)
SKIP, w=5	0.284 (ep=20)	0.302 (ep=30)	0.311 (ep=30)
random	0	0	0

Table 1. Average $Recall_{hier}$ for non-overlapping sequences, best shown in bold case

Emb. Meth, w	dim=50	dim=100	dim=200
CBOW, w=2	0.406 (ep=10)	0.412 (ep=10)	0.414 (ep=5)
CBOW, w=5	0.405 (ep=30)	0.402 (ep=35)	0.382 (ep=10)
SKIP, w=2	0.512 (ep=5)	0.53 (ep=5)	**0.538** (ep=5)
SKIP, w=5	0.507 (ep=5)	0.525 (ep=5)	0.524 (ep=5)
random	0	0	0

Table 2. Average $Recall_{hier}$ for non-redundant sequences, best shown in bold case

Supplementary B: Enzyme Commission (EC) primary class

Classes distribution of EC primary class is shown at Table 3. Average k-NN $Accuracy_{EC}$ for non overlapping and non redundant sequences shown in Tables 4 and 5 respectively.

EC primary class	No. of domains
Oxidoreductases	1102
Transferases	2490
Hydrolases	2190
Lyases	524
Isomerases	318
Ligases	448
Translocases	176

Table 3. EC class summary

Emb. Meth, w	dim=50	dim=100	dim=200
CBOW, w=2	61.23(ep=10)	61.33(ep=10)	60.66(ep=15)
CBOW, w=5	61.22(ep=20)	60.51(ep=10)	60.61(ep=15)
SKIP, w=2	63.56(ep=10)	**63.92**(ep=20)	62.58(ep=20)
SKIP, w=5	62.47(ep=10)	63.44(ep=10)	62.94(ep=15)
random	31.51 (k=40)	32.64 (k=40)	31.68 (k=20)

Table 4. Average k-NN $Accuracy_{EC}$ non-overlapping sequences (k=2), best shown in bold case

Emb. Meth, w	dim=50	dim=100	dim=200
CBOW, w=2	76.88(ep=5)	75.85(ep=5)	75.39(ep=5)
CBOW, w=5	80.89(ep=5)	79.89(ep=5)	77.16(ep=5)
SKIP, w=2	89.47(ep=35)	89.06(ep=40)	88.86(ep=5)
SKIP, w=5	**90.85**(ep=30)	90.41(ep=15)	90.2(ep=5)
random	33.62 (k=40)	32.06 (k=40)	32.28 (k=40)

Table 5. Average k-NN $Accuracy_{EC}$ non-redundant sequences (k=2), best shown in bold case

Supplementary C: GO molecular function

Malaria

GO class distribution, k-NN $Accuracy_{GO}$ for non-overlapping sequences and non redundant sequences, for *Malaria*, are shown in 6, 7 and 8 respectively.

E.coli

GO class distribution, k-NN $Accuracy_{GO}$ for non-overlapping sequences and non redundant sequences, for *E.coli*, are shown in 9, 10 and 11 respectively.

Yeast

GO class distribution, k-NN $Accuracy_{GO}$ for non-overlapping sequences and non redundant sequences, for *Yeast*, are shown in 12, 13 and 14 respectively.

Human

The k-NN $Accuracy_{GO}$ for non-overlapping sequences, for *Human*, is shown in Table 15.

GO class	No. of domains
Catalytic activity	676
Binding	440
Structural molecule activity	171
Transporter activity	63
Molecular function regulator	22
Transcription regulator activity	13
Cargo receptor activity	1
Molecular carrier activity	1

Table 6. GO molecular function distribution (Malaria)

Emb. Meth, w	dim=50	dim=100	dim=200
CBOW, w=2	58.2 (k=5,ep=35)	58.24(k=5,ep=5)	57.87(ep=5)
CBOW, w=5	57.87(ep=10)	56.94(ep=10)	57.1(ep=5)
SKIP, w=2	59.48(k=5,ep=10)	59.82(ep=15)	58.68(ep=10)
SKIP, w=5	**60.61**(ep=10)	59.01(ep=10)	59.39($ep = 5$)
random	46.21(k=40)	46.62(k=40)	45.99(k=40)

Table 7. Average k-NN $Accuracy_{GO}$ for non-overlapping sequences, whenever k is not shown k=2, best shown in bold case (Malaria)

Emb. Meth, w	dim=50	dim=100	dim=200
CBOW, w=2	67.33(ep=5)	64.88(ep=5)	61.13(ep=5)
CBOW, w=5	66.74(ep=5)	66.75(ep=5)	63.89(ep=5)
SKIP, w=2	75.79(ep=35)	75.64(ep=45)	74.91(ep=5)
SKIP, w=5	76.79(ep=10)	**76.86**(ep=40)	72.75(ep=20)
random	46.58(k=40)	46.22(k=40)	47.57(k=40)

Table 8. Average k-NN $Accuracy_{GO}$ for non-redundant sequences (k=2), best shown in bold case (Malaria)

GO class	No. of domains
Catalytic activity	1565
Binding	476
Transporter activity	211
Structural molecule activity	117
Transcription regulator activity	39
Molecular function regulator	15
Molecular carrier activity	3
Translation regulator activity	1
Molecular transducer activity	1

Table 9. GO molecular function distribution (E.coli)

Emb. Meth, w	$dim = 50$	$dim = 100$	$dim = 200$
CBOW, w=2	67.66(k=5,ep=30)	67.46(k=20,ep=5)	67.34(k=20,ep=5)
CBOW, w=5	67.78(k=5,ep=5)	67.46(k=20,ep=5)	67.34(k=20,ep=5)
SKIP, w=2	68.15(k=5,ep=5)	67.54(k=5,ep=5)	67.75(k=20,ep=5)
SKIP, w=5	**69.1**(k=5,ep=5)	67.82(k=5,ep=5)	68.15(k=5,ep=5)
random	64.46(k=40)	64.46(k=40)	64.46(k=40)

Table 10. Average k-NN $Accuracy_{GO}$ for non-overlapping sequences, best shown in bold case (E.coli)

Emb. Meth, w	dim=50	dim=100	dim=200
CBOW, w=2	71.41(k=5,ep=5)	68.45(k=5,ep=5)	67.87(ep=5)
CBOW, w=5	74.95(ep=5)	71.69(ep=5)	68.91(ep=5)
SKIP, w=2	81.27(ep=5)	80.32(ep=5)	80.36(ep=5)
SKIP, w=5	**81.72**(ep=5)	81.64(ep=5)	80.77(ep=5)
random	64.38(k=40)	64.46(k=40)	64.38(k=40)

Table 11. Average k-NN $Accuracy_{GO}$ for non-redundant domains (k=2), best shown in bold case (E.coli)

GO class	No. of domains
Catalytic activity	1177
Binding	585
Structural molecule activity	208
Transporter activity	112
Transcription regulator activity	46
Molecular function regulator	40
Translation regulator activity	2
Molecular transducer activity	2
Molecular carrier activity	1
Cargo adaptor activity	1

Table 12. GO molecular function distribution (S.cerevisiae)

Emb. Meth, w	dim=50	dim=100	dim=200
CBOW, w=2	60.05(k=20,ep=5)	59.87(k=20,ep=5)	59.87(k=20,ep=5)
CBOW, w=5	59.82(k=20,ep=15)	60.24(k=20,ep=5)	60.70(k=20,ep=5)
SKIP, w=2	60.74(k=5,ep=10)	60.79(k=5,ep=10)	61.53(k=5,ep=5)
SKIP, w=5	**61.38**(k=5,ep=10)	60.75(k=20,ep=5)	60.61(k=20,ep=10)
random	53.36(k=40)	53.64 (k=40)	53.64 (k=40)

Table 13. Average k-NN $Accuracy_{GO}$ for non-overlapping sequences, best shown in bold (S.cerevisiae)

Emb. Meth, w	dim=50	dim=100	dim=200
CBOW, w=2	64.37(k=5,ep=5)	64.87(k=5,ep=5)	62.4(k=5,ep=5)
CBOW, w=5	67.17(k=5,ep=50)	65.11(k=5,ep=5)	63.31(k=5,ep=5)
SKIP, w=2	73.36(k=5,ep=20)	73.86(k=5,ep=5)	72.29(k=5,ep=5)
SKIP, w=5	**75.1**(k=5,ep=50)	74.1(k=5,ep=10)	73.02(k=5,ep=5)
random	53.59(k=40)	53.73(k=40)	53.18(k=40)

Table 14. Average k-NN $Accuracy_{GO}$ for non-redundant sequences, best shown in bold (S.cerevisiae)

Emb. Meth, w	dim=50	dim=100	dim=200
CBOW, w=2	57.7(ep=10)	58.82(ep=10)	58.04(k=5,ep=10)
CBOW, w=5	58.1(ep=30)	58.9(ep=35)	58.2(ep=10)
SKIP, w=2	60.51(k=5,ep=15)	60.67(ep=10)	59.3(ep=10)
SKIP, w=5	**60.59**(k=5,ep= 35)	60.18(k=5,ep=10)	59.84(k=5,ep=10)
random	36.72 (k=40)	36.44 (k=40)	37.36 (k=40)

Table 15. k-NN $Accuracy_{GO}$ for non-overlapping sequences, when k is not shown k=2, best shown in bold case (Human)