Structure-based modeling of SARS-CoV-2 peptide/HLA-A02 antigens

Santrupti Nerli[1] and Nikolaos G. Sgourakis[2]
Email: nsgourak@ucsc.edu

[1]Department of Biomolecular Engineering, University of California Santa Cruz, Santa Cruz, CA 95064, USA.
[2]Department of Chemistry and Biochemistry, University of California Santa Cruz, Santa Cruz, CA 95064, USA.

ABSTRACT

As a first step toward the development of diagnostic and therapeutic tools to fight the Coronavirus disease (COVID-19), it is important to characterize CD8+ T cell epitopes in the SARS-CoV-2 peptidome that can trigger adaptive immune responses. Here, we use RosettaMHC, a comparative modeling approach which leverages existing high-resolution X-ray structures from peptide/MHC complexes available in the Protein Data Bank, to derive physically realistic 3D models for high-affinity SARS-CoV-2 epitopes. We outline an application of our method to model 439 9mer and 279 10mer predicted epitopes displayed by the common allele HLA-A*02:01, and we make our models publicly available through an online database (https://rosettamhc.chemistry.ucsc.edu). As more detailed studies on antigen-specific T cell recognition become available, RosettaMHC models of antigens from different strains and HLA alleles can be used as a basis to understand the link between peptide/HLA complex structure and surface chemistry with immunogenicity, in the context of SARS-CoV-2 infection.

An ongoing pandemic caused by the novel SARS coronavirus (SARS-CoV-2) has become the focus of extensive efforts to develop vaccines and antiviral therapies (1). Immune modulatory interferons, which promote a widespread antiviral reaction in infected cells, and inhibition of pro-inflammatory cytokine function through anti-IL-6/IL-6R antibodies, have been proposed as possible COVID-19 therapies (2, 3). However, stimulating a targeted T cell response against specific viral antigens is hampered by a lack of detailed knowledge of the immunodominant epitopes displayed by common Human Leukocyte Antigen (HLA) alleles across individuals (public epitopes). The molecules of the class I major histocompatibility complex (MHC-I, or HLA in humans) display on the cell surface a diverse pool of 8 to 15 amino acid peptides derived from the endogenous processing of proteins expressed inside the cell (4). This MHC-I restriction of peptide antigens provides jawed vertebrates with an essential mechanism for adaptive immunity: surveillance of the displayed peptide/MHC-I (pMHC-I) molecules by CD8+ cytotoxic T-lymphocytes allows detection of aberrant protein expression patterns, which signify viral infection and can trigger an adaptive immune response (5). A recent study has shown important changes in T cell compartments during the acute phase of SARS-CoV-2 infection (6), suggesting that the ability to quantify antigen-specific T cells would provide new avenues for understanding the

expansion and contraction of the TCR repertoire in different disease cohorts and clinical settings.
Given the reduction in breadth and functionality of the naïve T cell repertoire during aging (7),
identifying a minimal set of viral antigens that can elicit a protective response will enable the
design of diagnostic tools to monitor critical gaps in the T cell repertoire of high-risk cohorts,
which can be addressed using peptide or epitope string DNA vaccines (8).
Human MHC-I molecules are extremely polymorphic, with thousands of known alleles in the
classical HLA-A, -B and -C loci. Specific amino acid polymorphisms along the peptide-binding
groove (termed A-F pockets) define a repertoire of 10^4-10^6 peptide antigens that can be recognized
by each HLA allotype (9, 10). Several machine-learning methods have been developed to predict
the likelihood that a target peptide will bind to a given allele (reviewed in (11)). Generally these
methods make use of available data sets in the Immune Epitope Database (12) to train artificial
neural networks that predict peptide processing, binding and display, and their performance varies
depending on peptide length and HLA allele representation in the database. Structure-based
approaches have also been proposed to model the bound peptide conformation *de novo* (reviewed
in (13)). These approaches utilize various algorithms to optimize the backbone and side chain
degrees of freedom of the peptide/MHC structure according to an all-atom scoring function,
derived from physical principles (14–16), that can be further enhanced using modified scoring
terms (17) or mean field theory (18). While these methods do not rely on large training data sets,
their performance is affected by bottlenecks in sampling of different backbone conformations, and
any possible structural adaptations of the HLA peptide-binding groove.
Predicting the bound peptide conformation whose N- and C- termini are anchored within a fixed-
length groove is a tractable modeling problem that can be addressed using standard comparative
modeling approaches (19). In previous work focusing on the HLA-B*15:01 and HLA-A*01:01
alleles in the context of neuroblastoma neoantigens, we have found that a combined backbone and
side chain optimization approach can yield accurate pMHC-I models for a pool of target peptides,
provided that a reliable template of the same allele and peptide length can be identified in the
database (20). In this approach (RosettaMHC), a local optimization of the backbone degrees of
freedom is sufficient to capture minor (within 0.5 Å heavy atom RMSD) changes of the target
peptide backbone relative to the conformation of the peptide in the template, used as a starting
point. For HLA-A*02:01, the most common HLA allele among disease-relevant population
cohorts (21), there is a large number of high-resolution X-ray structures available in the PDB (22),
suggesting that a similar principle can be applied to produce models of candidate epitopes directly
from the proteome of a pathogen of interest. Here, we apply RosettaMHC to all HLA-A*02:01
epitopes predicted directly from the ~30 kbp SARS-CoV-2 genome, and make our models publicly
available through an online database. The computed binding energies of our models can be used
as an additional validation layer to select high-affinity epitopes from large peptide sets. As detailed
epitope mapping data from high-throughput tetramer staining (23–25) and T cell functional
screens (26) become available, the models presented here can provide a toehold for understanding
links between pMHC-I antigen structure and immunogenicity, with actionable value for the
development of peptide vaccines to combat the disease.

Materials and Methods

Identification of SARS-CoV-2 peptide epitopes

The SARS-CoV-2 protein sequences (https://www.ncbi.nlm.nih.gov/nuccore/NC_045512.2) were obtained from NCBI and used to generate all possible peptides of lengths 9 and 10 (9,621 9mer and 9,611 10mer peptides). We used NetMHCpan-4.0 (27) to derive binding scores to HLA-A*02:01, and retained only peptides classified as strong or weak binders (selected using the default percentile rank cut-off values). The binding classification was performed using eluted ligand likelihood predictions. While in this study we use NetMHCpan-4.0 predictions as inputs to select candidate epitopes for structure modeling, our workflow is fully compatible with any alternative epitope prediction method.

Selection of PDB templates

To model SARS-CoV-2 / HLA-A*02:01 antigens, we identified 3D structures from the PDB that can be used as templates for comparative modeling. First, we selected all HLA-A02 X-ray structures that are below 3.5 Å resolution and retained only those that have 100% identity to the HLA-A*02:01 heavy chain sequence (residues 1-180). We found 241 template structures bound to epitopes of lengths from 8 to 15 residues (of which 170 are 9mers and 61 are 10mers). For each SARS-CoV-2 target peptide, we selected a set of candidate templates of the same length by matching the target peptide anchor positions (P2 and P9/P10) to each peptide in the template structures. Then, we used the BLOSUM62 (28) substitution matrix to score all remaining positions in the pairwise alignment of the target/template sequences, and the PDB template with the top alignment score was selected for modeling. For target peptides where we found no templates which match both peptide anchors, we scored all positions in the pairwise alignment and selected the top scoring template for modeling.

RosettaMHC modeling framework and database

RosettaMHC (manuscript in preparation) is a comparative modeling protocol developed using PyRosetta (29) to model pMHC-I complexes. The program accepts as input a list of peptide sequences, an HLA allele definition and a template PDB file (selected as described in the previous step). To minimize "noise" in the simulation from parts of the MHC-I fold that do not contribute to peptide binding, only the α_1 and α_2 domains are considered in all steps. For each peptide, a full alignment between the target and template peptide/MHC sequences is performed using clustal omega (30). The alignment is used as input to Rosetta's threading protocol (*partial_thread.<ext>*). From the threaded model, all residues in the MHC-I groove that are within a heavy-atom distance of 3.5 Å from the peptide are subjected to 10 independent all-atom refinement simulations using the FastRelax method (31) and a custom movemap file. Binding energies are extracted from the refined structures using interface analyzer protocol (*InterfaceAnalyzer.<ext>*). The top three models are selected based on the binding energies, and used to compute an average energy for each peptide in the input list. RosettaMHC models of SARS-CoV-2/HLA-A*02:01 epitopes are

120   made available through an online database (see data availability). The website that hosts our
121   database was constructed using the Django web framework.
122
123
124   **Results and Discussion**
125
Template identification for structure modeling using RosettaMHC
Our full workflow for template identification and structure modeling is outlined in Figure 1a, with
a flowchart shown in Figure 1b. To identify all possible regular peptide binders to HLA-A*02:01
that are expressed by SARS-CoV-2, we used a recently annotated version of all open reading
frames (ORFs) in the viral genome from NCBI (32), made available through the UCSC genome
browser (33). We used 9- and 10- residue sliding windows to scan all protein sequences, since
these are the optimum peptide lengths for binding to the HLA-A*02:01 groove (34). While spliced
peptide epitopes (35) are not considered in the current study, this functionality can be added to our
method at a later stage. Using NetMHCpan-4.0 (27), we identified all 439 9mer and 279 10mer
epitopes that are predicted to yield positive (classified as both weak and strong) binders. To further
validate this set and derive plausible 3D models of the peptide/HLA-A*02:01 complexes, we used
a structure-guided approach, RosettaMHC, which aims to derive a physically realistic fitness score
for each peptide in the HLA-A*02:01 binding groove using an annotated database of high-
resolution structures and Rosetta's all-atom energy function (36). RosettaMHC leverages a
database of 241 HLA-A*02:01 X-ray structures encompassing a range of bound peptides, to find
the closest match to each target epitope predicted from the SARS-CoV-2 proteome. To identify
the best template for structure modeling, we use sequence matching criteria which first consider
the peptide anchors (positions P2 and P9/P10 for 9mer/10mer epitopes), followed by a sequence
similarity metric calculated from the full alignment between the template and target peptide
sequences. The template assignment statistics for the four different classes of SARS-CoV-2
epitopes in our set are shown in Figure 2a. We find that we can cover the entire set of 718 predicted
binders using a subset of 114 HLA-A*02:01 templates in our annotated database of PDB-derived
structures (Figure 2b). Each target peptide sequence is then threaded onto the backbone of its best
identified template, followed by all-atom refinement of the side chain and backbone degrees of
freedom using Rosetta's Ref2015 energy function (36), and binding energy calculation.
151
RosettaMHC models recapitulate features of high-resolution X-ray structures
The sequence logos derived from 9mer and 10mer peptides with good structural complementarity
to the HLA-A*02:01 groove according to Rosetta's binding energy (see below) adhere to the
canonical motif, with a preference for hydrophobic, methyl-bearing side chains at the peptide
anchor residues P2 and P9 (Figure 3a). The anchor residue preferences are recapitulated in
representative 9mer and 10mer models of the two top binders in our set as ranked by Rosetta's
energy (Figure 3c and 3d), corresponding to epitopes TMADLVYAL and FLFVAAIFYL derived
from the RNA polymerase and nsp3 proteins, respectively, which are both encoded by *orf1ab* in

the viral genome (NCBI Reference YP_009724389.1). In accordance with features seen in high-
resolution structures of HLA-A*02:01-restricted epitopes, the peptides adopt an extended, bulged
backbone conformation. The free N-terminus of both peptides is stabilized by a network of polar
contacts with Tyr 7, Tyr 159, Tyr 171 and Glu 63 in the A- and B- pockets of the HLA-A*02:01
groove. The Met (9mer) or Leu (10mer) side chain of P2 is buried in a B-pocket hydrophobic cleft
formed by Met 45 and Val 67. Equivalently, the C-terminus is coordinated through polar contacts
with Asp 77 and Lys 145 from opposite sides of the groove, with the Leu P9/P10 anchor nestled
in the F-pocket defined by the side chains of Leu 81, Tyr 116, Tyr 123 and Trp 147. Residues P3-
P8 form a series of backbone and side chain contacts with pockets C, D and E, while most
backbone amide and carbonyl groups form hydrogen bonds with the side chains of residues lining
the MHC-I groove. These high-resolution structural features are consistent across low-energy
models of unrelated target peptides in our input set, suggesting that, when provided with a large
set of input templates, a combined threading and side chain optimization protocol can derive
physically realistic models.
174
Selection of high-affinity peptide epitopes using a structure-based score
To evaluate the accuracy of our models and fitness of each peptide within the HLA-A*02:01
binding groove, we computed Rosetta all-atom binding energies across all complexes modeled for
different peptide sets. High binding energies can be used as an additional metric to filter low-
affinity peptides in the NetMHCpan-4.0 predictions, with the caveat that high energies can be also
due to incomplete optimization of the Rosetta energy function as a result of significant deviations
between the target and template backbone conformations, not captured by our protocol. We
performed 10 independent calculations for each peptide, and the 3 lower-energy models were
selected as the final ensemble and used to compute an average binding energy. The results for all
9mer peptides are summarized in Figures 3e, f, while additional results for 10mers are provided
through our web-interface and outlined in Supplemental Table 1. As a positive reference, we used
the binding energies of the idealized and relaxed PDB templates, which are at a local minimum of
the Rosetta scoring function. As a reference set for sub-optimal binders, we modeled decoy
structures of poly alanine (polyA) peptide sequences (predicted by NetMHCpan-4.0 to be a top
9th percentile binder for HLA-A*02:01), threaded onto the same PDB templates.
190
We observe a significant, negative (-26 kcal/mol) energy gap between the average binding energies
for PDB templates and poly alanine models. The binding energies for all modeled 9mers from the
SARS-CoV-2 genome fall between the average energies of the optimal PDB templates and sub-
optimal polyA binders, and show a bimodal distribution with significant overlap with the refined
PDB template energies (Figure 1e). Comparison of the distributions between epitopes that are
classified as strong versus weak binders by NetMHCpan-4.0 shows a moderate bias towards lower
binding energies for the strong binders and a larger spread in energies for weak binders, likely due
to suboptimal residues at the P2 and P9 anchor positions (Figure 3f). As an intendent positive set,
we also modeled 28 9mer peptides that are homologous to peptides in the SARS viral genome and

have been previously reported to bind HLA-A*02:01 in the IEDB and ViPR (12, 37, 38) databases
(Supplemental Table 2). Inspection of Rosetta binding energies derived from models in this set
shows a similar distribution to the epitopes classified by NetMHCpan-4.0 as strong binders, with
the energies of 19/28 peptides falling well within the distribution of the refined PDB templates
(red dots in Figure 3e).

Based on these observations, we further classified all epitopes in the original set provided by
NetMHCpan-4.0 as strong or weak binders according to the Rosetta binding energy. Peptides with
binding energies that fall well within the PDB template distribution (green curve and red dots in
Figure 3e) are classified as strong binders. We obtained 154 9mer and 72 10mer strong binders
which show optimal complementarity within the HLA-A*02:01 peptide-binding groove according
to our modeling simulations. These results suggest that the high-resolution features seen in our
models (Figure 3c, d) yield optimal binding energies for a significant fraction of the epitopes
predicted by NetMHCpan-4.0 (45/33% of strong binders and 30/25% of weak binders for
9mers/10mers, respectively), which are comparable to locally refined PDB structures. The average
binding energies for all peptides are provided in our web-interface and in Supplemental Table 1.

*Surface features of peptide/HLA-A*02:01 models for T cell recognition*
Visualization of our models through an interactive online interface provides direct information on
SARS-CoV-2 peptide residues that are bulging out of the MHC-I groove, and are therefore
accessible to interactions with complementarity-determining regions (CDRs) of T cell receptors
(TCRs). Given that $\alpha\beta$ TCRs generally employ a diagonal binding mode to engage pMHC-I
antigens where the CDR3α and CDR3β TCR loops form direct contacts with key peptide residues
(39, 40), knowledge of the surface features for different epitopes adds an extra layer of information
to interpret sequence variability between different viral strains. For other important antigens with
known structures in the PDB, such features can be derived from an annotated database connecting
pMHC-I/TCR co-crystal structures with biophysical binding data (41), and were recently
employed in an artificial neural network approach to predict the immunogenicity of different HLA-
A*02:01 bound peptides in the context of tumor neoantigen display (42). A separate study has
shown that the electrostatic compatibility between self vs foreign HLA surfaces can be used to
determine antibody alloimmune responses (43). Given that antibodies and TCRs use a common
fold and similar principles to engage pMHC-I molecules (40), it is likely that surface electrostatic
features play an important role in recognition of peptide/HLA surfaces by their cognate TCRs in
the context of SARS-CoV-2 infection.
Electrostatic surface potentials calculated using a numerical solution to the Poisson-Boltzmann
Equation (44) for our modeled peptide/HLA-A*02:01 complexes allow us to compare important
features for TCR recognition between different high-affinity epitopes (Figure 4). We observe a
moderate electropositive character of the HLA-A*02:01 α_1 helix, and a moderate negative
potential on the α_2 helix, which is consistent between complexes with different bound peptides.
However, due to substantial sequence variability in surface-exposed residues at the P2-P8

positions, we observe a range of electrostatic features ranging from negative (epitope TMADLVYAL), to neutral (NLIDSYFVV) or positively charged (KLWAQCVQL). Further classification and ranking of the top binders in our set on the basis of their molecular surface features would enable the selection of the most diverse panel of peptides for high-throughput pMHC tetramer library generation (23-25). Tetramer screening of T cells from COVID-19 patients, recovered individuals and healthy donors can be used to identify critical gaps in the T cell repertoire of high-risk groups, and to design epitope DNA strings for vaccine development.

Acknowledgements

The authors are grateful to Alison Lindberg and ITS/ADC staff at UCSC for assistance in setting up the web server for the database, and Hiram Clawson (UCSC Genome Browser) for providing the SARS-CoV-2 protein sequence data. We thank Andrew McShan, Hailey Wallace (UCSC) for assistance in the development of the RosettaMHC protocol, and David Haussler (UCSC), Michael Betts (University of Pennsylvania) and David Margulies (NIH) for helpful discussions. This work was supported through Grants from NIAID (5R01AI143997) and NIGMS (5R35GM125034).

Code and Data availability

An online web-interface for visualization and download of all models is available at: https://rosettamhc.chemistry.ucsc.edu. The RosettaMHC source code is available at https://github.com/snerligit/mhc-pep-threader. Rosetta binding energies for all 718 HLA-A*02:01-restricted peptides in our set are provided in Supplemental Table 1.

Disclosures

The authors have no financial conflicts of interest.

References

1. Liu, C., Q. Zhou, Y. Li, L. V. Garner, S. P. Watkins, L. J. Carter, J. Smoot, A. C. Gregg, A. D. Daniels, S. Jervey, and D. Albaiu. 2020. Research and Development on Therapeutic Agents and Vaccines for COVID-19 and Related Human Coronavirus Diseases. *ACS Cent. Sci.* .

2. Kumaki, Y., J. Ennis, R. Rahbar, J. D. Turner, M. K. Wandersee, A. J. Smith, K. W. Bailey, Z. G. Vest, J. R. Madsen, J. K.-K. Li, and D. L. Barnard. 2011. Single-dose intranasal administration with mDEF201 (adenovirus vectored mouse interferon-alpha) confers protection from mortality in a lethal SARS-CoV BALB/c mouse model. *Antiviral Res.* 89: 75–82.

3. Kishimoto, T. 2006. Interleukin-6: discovery of a pleiotropic cytokine. *Arthritis Res. Ther.* 8: S2.

4. Rock, K. L., E. Reits, and J. Neefjes. 2016. Present Yourself! By MHC Class I and MHC Class II Molecules. *Trends Immunol.* 37: 724–737.

5. Kaufman, J. 2018. Unfinished Business: Evolution of the MHC and the Adaptive Immune System of Jawed Vertebrates. *Annu. Rev. Immunol.* 36: 383–409.

6. Thevarajan, I., T. H. O. Nguyen, M. Koutsakos, J. Druce, L. Caly, C. E. van de Sandt, X. Jia, S. Nicholson, M. Catton, B. Cowie, S. Y. C. Tong, S. R. Lewin, and K. Kedzierska. 2020.

Breadth of concomitant immune responses prior to patient recovery: a case report of non-severe
COVID-19. *Nat. Med.* 1−3.
7. Goronzy, J. J., F. Fang, M. M. Cavanagh, Q. Qi, and C. M. Weyand. 2015. Naïve T cell
maintenance and function in human aging. *J. Immunol. Baltim. Md 1950* 194: 4073−4080.
8. Oyarzun, P., and B. Kobe. 2015. Computer-aided design of T-cell epitope-based vaccines:
addressing population coverage. *Int. J. Immunogenet.* 42: 313−321.
9. Birnbaum, M. E., J. L. Mendoza, D. K. Sethi, S. Dong, J. Glanville, J. Dobbins, E. Ozkan, M.
M. Davis, K. W. Wucherpfennig, and K. C. Garcia. 2014. Deconstructing the peptide-MHC
specificity of T cell recognition. *Cell* 157: 1073−1087.
10. Wooldridge, L., J. Ekeruche-Makinde, H. A. van den Berg, A. Skowera, J. J. Miles, M. P.
Tan, G. Dolton, M. Clement, S. Llewellyn-Lacey, D. A. Price, M. Peakman, and A. K. Sewell.
2012. A single autoimmune T cell receptor recognizes more than a million different peptides. *J.*
Biol. Chem. 287: 1168−1177.
11. Peters, B., M. Nielsen, and A. Sette. 2020. T Cell Epitope Predictions. *Annu. Rev. Immunol.* .
12. Vita, R., S. Mahajan, J. A. Overton, S. K. Dhanda, S. Martini, J. R. Cantrell, D. K. Wheeler,
A. Sette, and B. Peters. 2019. The Immune Epitope Database (IEDB): 2018 update. *Nucleic*
Acids Res. 47: D339−D343.
13. Antunes, D. A., J. R. Abella, D. Devaurs, M. M. Rigo, and L. E. Kavraki. 2018. Structure-
based Methods for Binding Mode and Binding Affinity Prediction for Peptide-MHC Complexes.
Curr. Top. Med. Chem. 18: 2239−2255.
14. Yanover, C., and P. Bradley. 2011. Large-scale characterization of peptide-MHC binding
landscapes with structural simulations. *Proc. Natl. Acad. Sci.* 108: 6981−6986.
15. King, C., E. N. Garza, R. Mazor, J. L. Linehan, I. Pastan, M. Pepper, and D. Baker. 2014.
Removing T-cell epitopes with computational protein design. *Proc. Natl. Acad. Sci. U. S. A.* 111:
8577−8582.
16. Liu, T., X. Pan, L. Chao, W. Tan, S. Qu, L. Yang, B. Wang, and H. Mei. 2014. Subangstrom
accuracy in pHLA-I modeling by Rosetta FlexPepDock refinement protocol. *J. Chem. Inf.*
Model. 54: 2233−2242.
17. Kyeong, H.-H., Y. Choi, and H.-S. Kim. 2018. GradDock: rapid simulation and tailored
ranking functions for peptide-MHC Class I docking. *Bioinformatics* 34: 469−476.
18. Rubenstein, A. B., M. A. Pethe, and S. D. Khare. 2017. MFPred: Rapid and accurate
prediction of protein-peptide recognition multispecificity using self-consistent mean field theory.
PLoS Comput. Biol. 13: e1005614.
19. Song, Y., F. DiMaio, R. Y.-R. Wang, D. Kim, C. Miles, T. Brunette, J. Thompson, and D.
Baker. 2013. High-Resolution Comparative Modeling with RosettaCM. *Structure* 21: 1735−
1742.
20. Frontiers | A Recurrent Mutation in Anaplastic Lymphoma Kinase with Distinct Neoepitope
Conformations | Immunology. .
21. Robinson, J., L. A. Guethlein, N. Cereb, S. Y. Yang, P. J. Norman, S. G. E. Marsh, and P.
Parham. 2017. Distinguishing functional polymorphism from random variation in the sequences
of >10,000 HLA-A, -B and -C alleles. *PLoS Genet.* 13.
22. Berman, H. M., J. Westbrook, Z. Feng, G. Gilliland, T. N. Bhat, H. Weissig, I. N.
Shindyalov, and P. E. Bourne. 2000. The Protein Data Bank. *Nucleic Acids Res.* 28: 235−242.
23. Bentzen, A. K., A. M. Marquard, R. Lyngaa, S. K. Saini, S. Ramskov, M. Donia, L. Such, A.
J. S. Furness, N. McGranahan, R. Rosenthal, P. T. Straten, Z. Szallasi, I. M. Svane, C. Swanton,
S. A. Quezada, S. N. Jakobsen, A. C. Eklund, and S. R. Hadrup. 2016. Large-scale detection of

antigen-specific T cells using peptide-MHC-I multimers labeled with DNA barcodes. *Nat. Biotechnol.* 34: 1037−1045.

24. Saini, S. K., T. Tamhane, R. Anjanappa, A. Saikia, S. Ramskov, M. Donia, I. M. Svane, S. N. Jakobsen, M. Garcia-Alai, M. Zacharias, R. Meijers, S. Springer, and S. R. Hadrup. 2019. Empty peptide-receptive MHC class I molecules for efficient detection of antigen-specific T cells. *Sci. Immunol.* 4.

25. Overall, S. A., J. S. Toor, S. Hao, M. Yarmarkovich, S. M. O'Rourke, G. I. Morozov, S. Nguyen, A. S. Japp, N. Gonzalez, D. Moschidi, M. R. Betts, J. M. Maris, P. Smibert, and N. G. Sgourakis. High Throughput pMHC-I Tetramer Library Production Using Chaperone-Mediated Peptide Exchange. *Nat. Commun. Press* .

26. Ishizuka, J., K. Grebe, E. Shenderov, B. Peters, Q. Chen, Y. Peng, L. Wang, T. Dong, V. Pasquetto, C. Oseroff, J. Sidney, H. Hickman, V. Cerundolo, A. Sette, J. R. Bennink, A. McMichael, and J. W. Yewdell. 2009. Quantitating T Cell Cross-Reactivity for Unrelated Peptide Antigens. *J. Immunol.* 183: 4337−4345.

27. Jurtz, V., S. Paul, M. Andreatta, P. Marcatili, B. Peters, and M. Nielsen. 2017. NetMHCpan-4.0: Improved Peptide-MHC Class I Interaction Predictions Integrating Eluted Ligand and Peptide Binding Affinity Data. *J. Immunol. Baltim. Md 1950* 199: 3360−3368.

28. Henikoff, S., and J. G. Henikoff. 1992. Amino acid substitution matrices from protein blocks. *Proc. Natl. Acad. Sci. U. S. A.* 89: 10915−10919.

29. Chaudhury, S., S. Lyskov, and J. J. Gray. 2010. PyRosetta: a script-based interface for implementing molecular modeling algorithms using Rosetta. *Bioinformatics* 26: 689−691.

30. Sievers, F., A. Wilm, D. Dineen, T. J. Gibson, K. Karplus, W. Li, R. Lopez, H. McWilliam, M. Remmert, J. Söding, J. D. Thompson, and D. G. Higgins. 2011. Fast, scalable generation of high-quality protein multiple sequence alignments using Clustal Omega. *Mol. Syst. Biol.* 7: 539.

31. Tyka, M. D., D. A. Keedy, I. André, F. Dimaio, Y. Song, D. C. Richardson, J. S. Richardson, and D. Baker. 2011. Alternate states of proteins revealed by detailed energy landscape mapping. *J. Mol. Biol.* 405: 607−618.

32. Wu, F., S. Zhao, B. Yu, Y.-M. Chen, W. Wang, Z.-G. Song, Y. Hu, Z.-W. Tao, J.-H. Tian, Y.-Y. Pei, M.-L. Yuan, Y.-L. Zhang, F.-H. Dai, Y. Liu, Q.-M. Wang, J.-J. Zheng, L. Xu, E. C. Holmes, and Y.-Z. Zhang. 2020. A new coronavirus associated with human respiratory disease in China. *Nature* 579: 265−269.

33. Kent, W. J., C. W. Sugnet, T. S. Furey, K. M. Roskin, T. H. Pringle, A. M. Zahler, and and D. Haussler. 2002. The Human Genome Browser at UCSC. *Genome Res.* 12: 996−1006.

34. Trolle, T., C. P. McMurtrey, J. Sidney, W. Bardet, S. C. Osborn, T. Kaever, A. Sette, W. H. Hildebrand, M. Nielsen, and B. Peters. 2016. The length distribution of class I restricted T cell epitopes is determined by both peptide supply and MHC allele specific binding preference. *J. Immunol. Baltim. Md 1950* 196: 1480−1487.

35. Mishto, M., and J. Liepe. 2017. Post-Translational Peptide Splicing and T Cell Responses. *Trends Immunol.* 38: 904−915.

36. Alford, R. F., A. Leaver-Fay, J. R. Jeliazkov, M. O'Meara, F. P. DiMaio, H. Park, M. V. Shapovalov, P. D. Renfrew, V. K. Mulligan, K. Kappel, J. W. Labonte, M. S. Pacella, R. Bonneau, P. Bradley, R. L. DunbrackJr., R. Das, D. Baker, B. Kuhlman, T. Kortemme, and J. J. Gray. 2017. The Rosetta All-Atom Energy Function for Macromolecular Modeling and Design. *J. Chem. Theory Comput.* 13: 3031−3048.

37. Grifoni, A., J. Sidney, Y. Zhang, R. H. Scheuermann, B. Peters, and A. Sette. 2020. A
Sequence Homology and Bioinformatic Approach Can Predict Candidate Targets for Immune
Responses to SARS-CoV-2. *Cell Host Microbe* .
38. Pickett, B. E., E. L. Sadat, Y. Zhang, J. M. Noronha, R. B. Squires, V. Hunt, M. Liu, S.
Kumar, S. Zaremba, Z. Gu, L. Zhou, C. N. Larson, J. Dietrich, E. B. Klem, and R. H.
Scheuermann. 2012. ViPR: an open bioinformatics database and analysis resource for virology
research. *Nucleic Acids Res.* 40: D593–D598.
39. Rossjohn, J., S. Gras, J. J. Miles, S. J. Turner, D. I. Godfrey, and J. McCluskey. 2015. T Cell
Antigen Receptor Recognition of Antigen-Presenting Molecules. *Annu. Rev. Immunol.* 33: 169–
200.
40. Rudolph, M. G., R. L. Stanfield, and I. A. Wilson. 2006. How TCRs bind MHCs, peptides,
and coreceptors. *Annu. Rev. Immunol.* 24: 419–466.
41. Borrman, T., J. Cimons, M. Cosiano, M. Purcaro, B. G. Pierce, B. M. Baker, and Z. Weng.
2017. ATLAS: A database linking binding affinities with structures for wild-type and mutant
TCR-pMHC complexes. *Proteins Struct. Funct. Bioinforma.* 85: 908–916.
42. Riley, T. P., G. L. J. Keller, A. R. Smith, L. M. Davancaze, A. G. Arbuiso, J. R. Devlin, and
B. M. Baker. 2019. Structure Based Prediction of Neoantigen Immunogenicity. *Front. Immunol.*
10.
43. Mallon, D. H., C. Kling, M. Robb, E. Ellinghaus, J. A. Bradley, C. J. Taylor, D. Kabelitz,
and V. Kosmoliaptsis. 2018. Predicting Humoral Alloimmunity from Differences in Donor and
Recipient HLA Surface Electrostatic Potential. *J. Immunol.* 201: 3780–3792.
44. Baker, N. A., D. Sept, S. Joseph, M. J. Holst, and J. A. McCammon. 2001. Electrostatics of
nanosystems: application to microtubules and the ribosome. *Proc. Natl. Acad. Sci. U. S. A.* 98:
10037–10041.
45. Jurrus, E., D. Engel, K. Star, K. Monson, J. Brandi, L. E. Felberg, D. H. Brookes, L. Wilson,
J. Chen, K. Liles, M. Chun, P. Li, D. W. Gohara, T. Dolinsky, R. Konecny, D. R. Koes, J. E.
Nielsen, T. Head-Gordon, W. Geng, R. Krasny, G.-W. Wei, M. J. Holst, J. A. McCammon, and
N. A. Baker. 2018. Improvements to the APBS biomolecular solvation software suite. *Protein*
Sci. 27: 112–128.
46. *The PyMOL Molecular Graphics System*,. Schrödinger, LLC.
401
402

FIGURE 1. Structure-guided modeling of T cell epitopes in the SARS-CoV-2 proteome

(a) General workflow of our pipeline for structure-guided epitope ranking. **(b)** Protein sequences

from the annotated SARS-CoV-2 proteome are used to generate peptide epitopes with a sliding

window covering all frames of a fixed length (9,621 9mer and 9,611 10mer possible peptides).

Candidate peptides are first filtered by NetMHCpan-4.0 (27) to identify all predicted strong and

weak binders (439 9mer and 279 10mer epitopes). For rapid template matching and structure

modeling, we use a local database of 241 HLA-A*02:01 X-ray structures with resolution below

3.5 Å from the Protein Data Bank (22). Each candidate peptide is scanned against all peptide

sequences of the same length in the database, and the top-scoring template is used to guide the

RosettaMHC comparative modeling protocol and to compute a binding energy.

FIGURE 2. Coverage of predicted HLA-A02 epitopes by structural templates in the PDB

(a) Peptide anchor matching statistics of all predicted SARS-CoV-2 strong (SB) and weak binders

(WB) of lengths 9 and 10 to a database of 241 high-resolution HLA-A*02:01 X-ray structures **(b)**

Plot showing cumulative distribution (CDF) of strong and weak binder peptides of lengths 9 and

10, as a function of the total number of matching templates from the Protein Data Bank (22).

FIGURE 3. Summary of RosettaMHC modeling results for SARS-CoV-2 peptide epitopes
Sequence logos from the *n* top ranking epitopes in the SARS-CoV-2 genome, predicted by
NetMHCpan-4.0 (27) and further refined using RosettaMHC binding simulations are shown for:
(a) 9mers (*n*=154) and **(b)** 10mers (*n*=72). The top 9mer and 10mer epitopes in our refined set are
shown: **(c)** TMADLVYAL, from RNA polymerase and **(d)** FLFVAAIFYL, from nsp3. Dotted
lines indicate polar contacts between peptide and heavy chain residues, with peptide residues
labelled. The template PDB IDs and original peptides used for modeling the target peptides are
indicated below each model. **(e)** Density plots showing distribution of average Rosetta binding
energies (kcal/mol) for all epitopes of length 9. Distributions reflect 93 PDB templates (green),

164 strong binder epitopes (according to NetMHCpan-4.0 (27)) (blue), and 93 poly alanine

peptides modeled using the same PDB templates and used as a reference set for sub-optimal

binders (polyA; pink). The binding energies of models generated for 28 confirmed SARS T cell

epitopes from the IEDB and ViPR (37, 38) are indicated by circles at the bottom of the plot. Red

circles (19/28) indicate epitopes that lie within the distribution of refined PDB templates and black

circles (9/28) indicate epitopes that fall within the distribution of polyA (sub-optimal binders). **(f)**

Box plots showing distribution of average binding energies for 93 PDB templates, 93 poly alanine

peptides, 28 confirmed epitopes (37, 38) and RosettaMHC models for 164 strong (SB) and 275

weak (WB) binder 9mer epitopes predicted from the SARS-CoV-2 proteome using NetMHCpan-

4.0 (27).

FIGURE 4. Variability in TCR recognition features of HLA-A02 with different high-affinity
peptides. Molecular surfaces of SARS-CoV-2/HLA-A*02:01 RosettaMHC models are shown for
four top-scoring epitopes (ranked by Rosetta binding energy from left to right) captured in the A,
B, C, D, E and F pockets of the MHC-I groove (top panel). The origins of the peptide epitopes in
the ~30 kbp SARS-CoV-2 genome are noted. Electrostatic surfaces computed for the same models
are shown in the bottom panel. Solvent-accessible surface representation with electrostatic
potential in the indicated ranges (down to −60 kcal/(mol·e) in red and up to +61 kcal/(mol·e) in
blue) were calculated using the APBS solver (45) in Pymol (46). All calculations were performed
at 150 mM ionic strength, 298.15 Kelvin, pH 7.2, protein dielectric 2.0, and solvent dielectric
78.54. Electrostatic potentials are given in units of kT/e. A 1.4 Å solvent (probe) radius and 10.0
points/Å^2 density was used to calculate molecular surfaces.