Automated Edge-Aware Refinement of Anatomical Atlases in 3D and Its Application to the Developing Mouse Brain

David M Young[1, 2], Siavash Fazel Darbandi[1], Grace Schwartz[1], Zachary Bonzell[1], Deniz Yuruk[1], Mai Nojima[1], Laurent Gole[2], John Rubenstein[1], Weimiao Yu[2], and Stephan J Sanders[1, *]

[1]Department of Psychiatry, UCSF Weill Institute for Neurosciences, University of California, San Francisco, San Francisco, California 94158, USA

[2]Institute of Molecular and Cellular Biology, Agency for Science, Technology and Research, Singapore 138673, Singapore

[*]Address correspondence to Stephan Sanders at UCSF (stephan.sanders@ucsf.edu)

March 26, 2020

Abstract

Anatomical atlases are valuable resources for investigating organogenesis, anatomy, pathology, and therapeutic targeting. Increasing utilization of 3D microscopy from intact tissues necessitates corresponding 3D atlases and anatomical labels. Generating these atlases requires either labor-intensive manual curation or transformation of existing atlases from physically sectioned tissues, resulting in artifacts. Here, we present an automated, edge-aware method to transform existing atlases including imputing incomplete labels and reducing artifacts whilst maintaining anatomical boundaries. Applying these techniques to the Allen Developing Mouse Brain Atlas (ADMBA), we demonstrate improvements, both qualitatively and quantitatively. To test the refined 3D atlas, we generated whole-brain nuclei-resolution images from 15 mice at postnatal day 0, identifying 35 million nuclei per brain. Our atlas improved the alignment between label and anatomical edges by 37% (p.adj=0.007). To promote large-scale comparative analysis of cytoarchitecture, we provide these methods as the MagellanMapper software package and the refined ADMBA atlas as a resource.

Introduction

Anatomical atlases have played a crucial role in research into organogenesis, anatomy, physiology, and

pathology[1–3] and have been used for a wide range of applications, including investigating developmental

biology[4], defining stereotactic coordinates[5], identifying patterns of neural activity associated with

behavior[6,7], and integrating morphological, transcriptomic, and neural activity data across species[1].

Ongoing initiatives continue to develop these resources, including the Human Cell Atlas[8], the BRAIN

Initiative[9,10], the Human Brain Project[11], and centralized repositories of data, including the Allen Brain

Atlas[12].

Macroscale imaging, such as magnetic resonance imaging (MRI), routinely generates data from intact whole

organs[13–19] in contrast to microscale imaging, such as light microscopy, which often relies on physically

cutting thin sections. Technological advances, including serial two-photon tomography (STPT)[20] and tissue

clearing techniques (e.g. CLARITY[21], 3DISCO[22], and CUBIC[23]), have facilitated microscopy of intact

whole organs using optical, instead of physical, sectioning[24–29]. These 3D microscopy methods have been

applied to map cytoarchitecture and cellular connectivity in complex tissues, including the brain[28,30,31],

heart[32,33], and lung[34,35].

The analysis of imaging data frequently requires atlases of the corresponding organ, species, developmental

age, and resolution[36–39]. For 3D imaging data, 3D atlases are required to accurately reference new data to

existing anatomically-defined labels[40,41]. The Allen Reference Atlas (ARA) of the adult (P56) C57BL/6J

mouse brain[42,43] represents one of the most complete 3D atlases at microscopic resolution to date. The most

recent version of the atlas (CCFv3, 2017) incorporated population averages of 1,675 adult mouse brains,

individually imaged through serial two-photon tomography. A team of neuroanatomists and illustrators

redrew structures natively in 3D, sometimes using the original annotations as seeds to guide the redrawing

process, producing 662 structural annotations[36]. To date, this monumental effort to generate a 3D atlas at

microscopic resolution has not been repeated for most combinations of organ, species, and developmental

stage, though numerous atlases based on 2D physical sections exist[5,35,44,45].

Converting an atlas based on 2D physical sections into 3D structures presents multiple challenges, as demon-

strated by the Allen Developing Mouse Brain Atlas (ADMBA), an atlas of 2D physical sections from eight

mouse brains, each at different developmental time point[46] (Fig. 1a). First, all atlases in the ADMBA are

missing labels across large regions, typically the lateral edge of one hemisphere and the entire opposite

hemisphere. Second, slight warping and asymmetrical placement of samples in the histological images pre-

vents simply mirroring labels from the annotated to the non-annotated hemisphere. Third, as noted in the

original Allen Reference Atlas informatics article[43] and by Niedworok, et al.[38], the assembled 3D volume

is smooth in the sagittal planes, in which the atlas annotations were drawn, but suffers from edge artifacts

visible in the coronal and axial planes (Fig. 1a).

Other datasets face similar challenges of converting 2D physical sections into 3D structures, including the rat brain atlas[47]. This atlas was converted to Waxholm Space using a mixture of automated and manual segmentation with visual inspection of all three orientation planes, yielding an atlas with smooth 3D structures, though some edge artifacts remain. Ero, et al.[48] performed non-rigid alignments between histological slice planes of the Common Coordinate Framework (CCFv2, 2011), applying the same deformations to the label images. While this registration improved alignment, the labels often appear to extend beyond the underlying histological planes. Rather than registering planes, Niedworok, et al.[38] applied a smoothing filter on the annotations themselves to reduce label artifacts.

Here, we present a method to automatically generate 3D atlases from existing 2D-derived partial atlases and apply it to the full ADMBA. To achieve this, we perform three steps (Fig. 1a): 1) Extension and mirroring of 2D data to approximate missing labels, 2) Smoothing with 3D watershed and morphological methods to refine jagged edges between 2D sections, and 3) Edge detection from microscopy images to guide the 3D watershed to draw boundaries based on anatomical divisions, which we call "edge-aware" refinement (example atlas shown in Fig. 1b). To assess the resulting 3D atlas, we generated 3D imaging data from 15 C57BL/6J wild-type mouse brains at postnatal day 0 (P0) using tissue clearing and optical sectioning. The 3D labels in our refined atlas match the brain structures better than the initial atlas, as demonstrated by closer alignment between labels and anatomical edges, and decreased variability within labels at the cellular level. We provide the method as open source software called MagellanMapper to apply the algorithms to equivalent atlases and provide the resulting ADMBA 3D atlases as a resource.

Results

Allen Developmental Mouse Brain Atlas

The ADMBA contains data for eight mouse brains each at a different development stage: embryonic day (E) 11.5, E13.5, E15.5, E18.5, postnatal day (P) 4, P14, P28, and P56. The data are generated from 158 to 456 serial 2D sagittal sections of 20-25 μm stained with Nissl or Feulgen-HP yellow and imaged with a light microscope at a lateral resolution of 0.99 to 1.049 μm. For the three earliest stages of development, E11.5, E13.5, E15.5, the entire embryo was imaged, rather than just the brain. Each of the eight atlases

Figure 1: **3D Atlas Refinement Pipeline Overview.** (a) 2D-derived atlases, such as those in the Allen Developing Mouse Brain Atlas, are smooth and consistent in the sagittal plane in which they were annotated. However, in the 3D reconstructions of these 2D sagittal planes, the coronal and axial planes reveal missing sections and jagged edges. To improve their performance for annotating 3D data, the lateral edges are extended to complete the labeled hemisphere. A 3D rotation is applied to bring the brain parallel to the image borders, then both the completed hemisphere labels and underlying microscopy sections are mirrored across the sagittal midline to complete coverage in the opposite hemisphere. To improve anatomical registration, the labels are each eroded and re-grown through a 3D watershed, guided by the anatomical edge map. To smooth the final product, labels are iteratively filtered with a morphological opening operation, or a closing

operation for small, disconnected labels that would otherwise be lost. (b) The pipeline illustrated in axial (top) and sagittal (bottom) views on the ADMBA E13.5 atlas, which requires the full pipeline shown in "a", including an additional step to strip out non-CNS tissue from the original whole embryo imaging. The nomenclature for pipeline steps shown here is used consistently throughout the manuscript. A spreadsheet mapping colors to label names and IDs in the Allen ontology for each atlas in this manuscript can be found at Table S1.

are annotated with expertly-curated labels of brain structures[46,49] in a hierarchy starting with the largest structures (e.g. neural plate) extending through 13 sublevels to the smallest annotated structures (e.g. parvicellular part of Lat). Viewed sagittally, these labels cover the majority of tissue in each brain with smooth, anatomically-aligned edges (Fig. 2a), however only sections on the left side of each brain are annotated and, for six atlases, labels are not present for the most lateral 14-24% sagittal planes of the brain (4-5% by volume; Suppl. Fig. S2; Fig. 2b). Labels extend slightly beyond the midline for several atlases, helping to fully annotate brains with a midline skew.

Atlas similarity

To focus our analysis on the brain tissue, we excluded non-central nervous system (CNS) tissue for the three embryos for which the brain was not dissected prior to imaging. Across all eight atlases the similarity between the microscopy images and the original label annotations was estimated by taking the threshold of each sagittal section on the left hemisphere of the brain as an approximation of ground truth and comparing the label coverage using the Dice Similarity Coefficient (DSC)[50], calculated by Insight Segmentation and Registration Toolkit (ITK)[51]. Higher DSCs reflect greater similarity between the images and labels, with a maximum possible value of 1. The observed DSCs for the original labels ranged from 0.85 to 0.97 (median 0.91; Fig. 2).

Atlas extension

To generate labels across the entire brain, we extended the existing labels to the lateral edges by following histological boundaries before mirroring the labels on the opposite hemisphere (Fig. 2). The most lateral labeled sagittal section provided the initial seed from which to grow labels laterally. First, we resized this plane to match the extent of corresponding microscopy signal in the next, unlabeled lateral sagittal section (Suppl. Fig. S1a, b). Next, we refined label boundaries by eroding each label and regrowing it along histological boundaries, which we call "edge-aware" refinement. To model these boundaries, we generated

113 gross anatomical maps in 3D using edge-detection methods on the volumetric histology images. Taking the
114 Laplacian of Gaussian[52] of each histological volumetric image, using a relatively large Gaussian sigma of 5,
115 highlighted broad regions of similar intensities. A zero-crossing detector converted this regional map into a
116 binary anatomical edge map (Suppl. Fig. S1b). After eroding each label, we next used this anatomical map
117 to guide the regrowth of labels by a compact watershed algorithm[53] step, which adds a size constraint to

120
121

Figure 2: **Atlas extension.** (a) The original E18.5 atlas labels (bottom left) viewed sagittally demonstrate
smooth borders and close correspondence with the underlying microscopy images (upper left; overlaid on
right). The dashed blue line shows the section viewed in "b". (b) When viewed axially, the most lateral
sections lack labels, and label borders are jagged. Slight rotation of the underlying microscopy images leads
to asymmetry between the two hemispheres. (c) The Dice Similarity Coefficient (DSC), a measure of the
completeness of labeling compared to the thresholded atlases, for the labeled hemispheres increased for all
brains in the ADMBA after lateral edge extension (original median = 0.91, extended median = 0.93; p =
0.02, Wilcoxon signed-rank test (WSRT); "Mus musculus," level -1, ID 15564 in the Allen ontology). (d)
To fill in the lateral edges using existing labels, a representative lateral label plane was iteratively resized

to fit the underlying microscopy images. The plane for each subsequent microscopy plane was thresholded,
the bounding box extracted, and the labels resized to fit this bounding box, followed by conforming labels to
the underlying gross anatomical boundaries (Suppl. Fig. S1). A stretch of compressed planes was expanded
(Suppl. Fig. S7), and the completed hemisphere of labels mirrored to the other hemisphere after rotation for
symmetry to complete the labeling.

136
137

the classic watershed algorithm. Distances of each pixel to its nearest edge map pixel formed anatomically

based watershed catchment areas, while each eroded label served as a large seed from which filling of the

nearest catchment areas began and grew until meeting neighboring labels. Thus, we extended a labeled

sagittal plane to an unlabeled one, refined by the histology.

This process was repeated iteratively across all remaining lateral sections (Suppl. Fig. S1b-c). By using a 3D

anatomical map for the watershed and seeding it with the prior plane's labels, we ensured continuity between

planes. To model the tapering of labels laterally, we preferentially eroded central labels by weighting each

label's filter size based on the label's median distance from the tissue section's outer boundaries. Central

labels thus eroded away faster, while the next most central labels grew preferentially to fill these vacated

spaces. In the E18.5 atlas, for example, this approach allowed the basal ganglia to taper off and give way to

the dorsal and medial pallium (Fig. 2b). Although edges between planes remained somewhat jagged, this

extension step creates a substrate for further refinement.

After completing label coverage for the left hemisphere, both the labels and underlying microscopy images

were reflected across the sagittal midline to cover the remaining hemisphere. Care was taken to ensure that

the sagittal midline was identified correctly by inspecting and rotating the 3D image and midline plane from

multiple angles (Fig. 2c). Recalculating the DSC between the microscopy images and labels for the left

hemisphere showed greater similarity across all eight atlases with a median DSC improvement of 0.02 (p =

0.02, WSRT) and a resulting DSC range of 0.87 to 0.97 (median 0.93, Fig. 2d). Equivalent analysis of DSC

for the whole brain would show substantial improvement due to the absence of labels on the right side in the

original.

158
159   **Label smoothing**

160
161   The ADMBA atlases have been provided as 3D volumetric images, combined computationally from the

162   original 2D sagittal reference plates; 2D sections can be generated from these 3D images in orthogonal

163   dimensions to the original sagittal view. Visual inspection of labels in the axial and coronal planes reveals

high-frequency artifacts along most edge borders, likely from the difficulty of drawing contiguous borders in dimensions orthogonal to the drawing plane (Figs. 1-3). To quantify the degree of label smoothness, we used the unit-less compactness metric[54]. The compactness measure applied in 3D incorporates both surface area and volume, allowing for quantification of smoothness to measure shape irregularity. Of note, compactness is independent of scale or orientation, facilitating comparison across all labels, despite size differences, and its sensitivity to noise allows finer detection of label irregularity[55]. Measuring the compactness of each label and taking the weighted mean based on label volume for each atlas gave a median compactness of 13,281 (mean: 33,975, standard deviation (SD): 44,743). For context, across all eight atlases the 3D whole-brain microscopy images were more compact (median compactness: 1,895, mean: 2,615, SD: 2,305; $p = 0.02$, WSRT, Bonferroni corrected; Suppl. Fig. S3a), consistent with the observed irregularity in the label images compared to anatomical images (Figs. 2b and 3).

To reduce this irregularity, we applied a smoothing filter iteratively to the 3D image of each label. Prior approaches to this problem used a Gaussian filter (kernel SD of 0.5, applied in two passes)[38]. While this visually improved the smoothness of label edges, we observed sharp angles along the edges, presumably from the limitation of rounding blurred pixel values to the integers required for label identities rather than allowing the subtler floating-point gradients from the Gaussian kernel (Suppl. Fig. S4a). In addition, the Gaussian filter expanded the volume of each label, leading to label loss as larger labels enveloped smaller ones (Suppl. Fig. S4b).

Optimal smoothing would maximize the smoothness of each label (i.e. compactness[55]) whilst minimizing changes in shape and location. It would also not lead to label loss. To calculate the improvement in compactness, we defined "compaction" as the difference in compactness between the original and smoothed label over the compactness of the original label with a range from 0 or 1, with 1 being optimal. For changes in shape and location, we defined "displacement" as the fraction of the smoothed label that was outside of the original label with a range from 0 or 1, with 0 being optimal. We defined a "smoothing quality" metric to reflect the balance of compaction and displacement, calculated as the difference between these two measures with a range from -1 or 1, with 1 being optimal. To estimate atlas-wide smoothing quality, we took the weighted sum by volume of smoothing quality for all labels in the atlas. Assessing the quality of smoothing using Gaussian blur with increasing Gaussian sigmas, we observed label loss in all atlases in the ADMBA, even with a small sigma where labels remained visibly jagged. At this sigma value, the median atlas-wide smoothing quality across all eight atlases was 0.54 (mean 0.53), rising to a peak of 0.57 (mean 0.56) at sigma 0.5 and 0.49 (mean 0.53) at a sigma of 1.0, but with

substantial loss of labels (median 14% lost at sigma 0.25, rising to 42% lost at sigma 1; mean 11% and 47%, respectively Suppl. Fig. S4b).

To refine smoothing while minimizing label loss, we changed the filter from a Gaussian to a morphological opening filter[56]. This filter first erodes each label to remove artifacts, followed by dilation to restore its original volume. To avoid label loss caused by excessive erosion of small labels, we halved the size of its structuring element for labels with ≤5,000 pixels. A few labels were split into numerous tiny fragments that would disappear with an opening filter. For these small labels, the opening filter was replaced by a closing filter, reversing the process by dilating before eroding to reconnect these components. With this adaptive opening filter approach, labels became more compact with smoother edges, while retaining their overall shape as seen in both 2D and 3D visualizations (Fig. 3a).

Quantifying the improvement with the adaptive opening filter approach, using only filter sizes that completely eliminated label loss, we obtained a median atlas-wide smoothing quality of 0.61 (mean 0.62) across all eight atlases, and improvement over the Gaussian filter approach (sigma 0.25; p = 0.008; Suppl. Fig. S4c). The optimal filter size varied between atlases, ranging from 2 to 5 (E15.5 and P14 shown in Fig. 3c, d; all ADMBA shown in Suppl. Fig. S5). The median overall compactness improved significantly (13,281 (SD = 44,743) for unsmoothed labels vs. 2,540 (SD = 2,624) for smoothed labels, p = 0.02, WSRT, Bonferroni corrected; mean 33,975 vs. 3,190) to a level that did not differ from that observed for the microscopy images of whole brains (p = 1.00, WSRT, Bonferroni corrected; Suppl. Fig. S3b, c).

Because morphological filters such as erosion classically operate globally, a drawback to these filters is the potential loss of thin structures, such as loss of the thin portion of the alar plate of the evaginated telencephalic vesicle (3a). Smoothing in-place also does not address gross anatomical misalignment. We address these issues in subsequent steps.

Label refinement by detected anatomical edges

The extending, mirroring, and smoothing steps lead to a more complete set of labels for the ADMBA and correct the irregular borders in orthogonal planes to which the original labels were drawn; however, in several locations the labels do not align closely to the anatomical edges seen in the underlying histology images, for example the basal ganglia do not follow the curve of the lateral septal nuclei (Fig. 2c). To better map the anatomical fidelity of annotations in all dimensions, without manual relabeling, we leveraged our method for extending labels laterally based on gross anatomical edges to further refine all labels (Fig. 4).

Figure 3: **Label Smoothing.** (a) Irregular edges at the label edges in the original (mirrored) E18.5 atlas (top) were smoothed by applying an adaptive morphological opening filter iteratively to each label, starting from the largest to the smallest labels (bottom). 3D renderings are depicted for two representative labels before (top) and after (bottom) smoothing. (b) To identify the optimal filter structuring element size, we devised an "atlas-wide smoothing quality" metric to incorporate the balance between smoothing (compaction) and changes in size and shape (displacement). While compaction continued to improve with increasing structuring element size, displacement eventually caught up, giving an optimal atlas-wide smoothing quality with a

structuring element size of 4 for the E18.5 atlas (top). We also assessed the number of labels that were lost
(none in this example) and the surface area to volume ratio, for which lower values reflect smoother shapes
(bottom). Vertical dashed lines indicate the optimal filter structuring element size, based on "atlas-wide
smoothing quality". (c) Selection of the optimal filter structuring element size using the same metrics as in
"b" are shown for the E15.5 and (d) P14 atlases.

Using the same gross anatomical map in 3D (shown for an example plane in Fig. 4a, second from left), we

first quantified the distances from 3D label edges to the expected anatomical position. Assuming that the

nearest gross anatomical edge was the correct one, we measured the distance from each label edge to the

nearest gross anatomical edge. We can visualize this distance as a color gradient, in which higher intensity

of color represents a greater distance to each anatomical edge (Fig. 4a, right columns).

To modify the labels in light of the gross anatomical edge map, we again incorporated the edge-aware

algorithm, this time in 3D. We made the assumption that the core of each label is annotated accurately,

whereas label edges are more prone to inaccuracies from plane-to-plane misalignments or the difficulty of

assessing histological edges. To preserve the core while reannotating the periphery, we first eroded each

label to remove edges. These eroded labels became the seed for the watershed step, which re-grew labels

back toward their original size but now guided by the gross anatomical edge map.

Normally the erosion step would lead to loss of thin structures within labels because erosion operates glob-

ally on the entire label. To preserve these thin structures, we skeletonized each label in 3D, which thins

the label to its core structure[57], and added the skeleton back to the eroded label. We used a much more

lightly eroded version of the label for the skeletonization to avoid retaining label edges in the skeleton. By

combining erosion with skeletonization when generating seeds for the watershed, we retained thin structures

such as the alar plate of the evaginated telencephalic vesicle located anterior to the basal ganglia.

After performing this edge-aware step, we ran the adaptive morphological opening filter smoothing step

(Fig. 4b). Because the edge-aware step partially smooths structures, we could use smaller filter sizes for

smoothing to avoid loss of thin structures. The resulting labels show considerable improvement, for example

the basal ganglia now curve around the lateral septal nuclei (Fig. 4c). Visualization of the color gradient

of distances to anatomical edges also confirms substantial improvement in label alignment compared with

the original labels or smoothing or edge-aware steps alone (Suppl. Fig. S8b). To quantify this improvement

brain-wide, we calculated the sum of edge distances for each pixel at label surfaces across the ADMBA.

We observed a significant reduction from a median of 186 million to 81 million μm (p = 0.04, WSRT,

267
268

Figure 4: **Edge-Aware Reannotation.** (a) Edge detection of the volumetric histology image delineated gross anatomical edges (left), shown here with the E18.5 atlas. To compare these histology-derived anatomical edges with the extended and mirrored but unsmoothed label edges (center left), we used a distance transform method to find the distance from each label edge pixel to the nearest anatomical edge (center right), shown here as a heat map of edge distances (right). (b) Eroded labels served as seeds (left) from which to grow

edge-aware labels through a watershed algorithm (center left), guided by the gross anatomical edges. After smoothing, borders matched the anatomical edges more closely (center right), as shown in the edge distance heat map for the modified labels (right), using the same intensity scale. (c) The final E18.5 atlas after edge-aware reannotation and label smoothing to minimize edge artifacts. (d) To evaluate the level of edge match by label, we mapped differences in the intensity coefficient of variation weighted by relative volume for each label before and after label refinement onto each corresponding label for the E18.5 atlas (left) and across all ADMBA atlases (right). For both, the anatomical map depicts this metric as a color gradient across all of the sublevel labels present in a cross section of the E18.5 atlas. Improvements of this metric with the refined atlas are colored in blue, minimal change is shown in white, while red represents better performance with the original atlas. (e) Applied across the full ADMBA, edge-aware reannotation and smoothing led to a significant improvement in the overall variation of intensities (central nervous system, or "neural plate," level 0, ID 15565 in the Allen ontology; $p = 0.04$, $n = 8$ atlases, WSRT, Bonferroni corrected). (f) Distances from labels to anatomical edges similarly showed a significant improvement across atlases ($p = 0.04$, $n = 8$, WSRT, Bonferroni corrected).

Bonferroni corrected; Fig. 4b-c, f), with a median Dice Similarity Coefficient between original (mirrored) and smoothed (edge-aware) labels of 0.72 (mean 0.77) and 9% median (mean 22%) volume reassignment. Example planes from all atlases in the ADMBA before and after refinement are depicted in Fig. 5, and movies across all planes are shown in Videos S1-16.

Anatomical edges in microscopy images reflect differences in intensity between regions. Therefore, we would expect accurate labels to have smaller variation in intensity in the underlying microscopy images than inaccurate labels, though such a difference would need to be apparent even though the majority of the label is unchanged. We used the coefficient of variation of intensity values within each label to quantify this expectation and demonstrated significantly lower variation with edge-aware labeling (mean from all labels weighted by size decreased from 0.305 to 0.289, $p = 0.04$, for all 8 atlases, WSRT, Bonferroni corrected; Fig. 4d, e). Furthermore, edge-aware labeling decreased the absolute coefficient of variation for 94 of the 100 individual labels represented by all atlases. The few labels that showed increased variation were frequently in regions of relatively subtle intensity changes, such as the hindbrain, where histological edges were less well-defined (Fig. 4d).

Application to tissue-cleared whole brains

A major goal of 3D atlas refinement is for automated label propagation to optically sectioned, volumetric mouse brain microscopy images generated from intact tissue using recently developed tissue clearing techniques. As the accuracy of atlas registration is ultimately dependent on the fidelity of the underlying atlas in all dimensions, we sought to test and quantify improvement from our atlas refinements in cleared

mouse whole-brains.

Among the many available methods to clear whole organs, we chose CUBIC[23,58] given its balance of over-
all transparency, morphological retention with minimal tissue expansion, and ease of handling as a passive
aqueous technique[59–61]. After clearing C57BL/6J WT mouse pup brains (age P0) with simultaneous
incubation in SYTO-16 nuclear dye for 2 weeks, we imaged intact whole-brains by lightsheet microscopy
at 5x to obtain volumetric images at cellular resolution, taking approximately 3h to image and generating
approximately 500GB of data per brain (n = 15; 10 male, 5 female).

To detect nuclei throughout cleared whole-brains automatically, we implemented a 3D blob detection
algorithm using the Laplacian of Gaussian filter, which has been shown to work well in equivalent image
data[62] (Fig. 6). To make the nuclei approximately spherical for blob detection, we interpolated the images
axially to match the lateral resolution. Due to the large quantity of data, processing was performed in
parallel on small chunks. Preprocessing and detection settings were optimized using hyperparameter
tuning against a "truth set" of 1118 nuclei selected from multiple brain regions that had been verified by
manual visualization (Suppl. Fig. S11a, b). The resulting model achieved a recall (sensitivity) of 90% and
precision (positive predictive value) of 92%. Furthermore, the model showed high correlation with total
intensity levels brain-wide ($r > 0.99$, $p \leq 1 \times 10^{-16}$, for both original (mirrored) and smoothed (edge-
aware) atlases) and nuclei vs. intensity densities (original: $r = 0.89$; smoothed: $r = 0.93$; $p \leq 1 \times 10^{-16}$ for
both), suggesting the performance was accurate outside the narrow target of the truth set (Suppl. Fig.
S11c-d).

Using the E18.5 brain as the closest atlas to our P0 C57BL/6J wild-type mouse brains (birth typically at
E19[63]), we then registered the atlas volumetric histology images to each sample brain. We chose to
register brains using the Elastix toolkit[64,65], which has been validated on CUBIC cleared brains and
balances computational efficiency and accuracy[66]. After downsampling the volumetric images to the
same dimensions as the atlas for efficiency, we applied rigid, followed by non-rigid, deformable
registration based on a multi-resolution scheme, optimizing the cross-correlation similarity metric as
implemented by the SimpleElastix[66,67] programmable interface to the Elastix toolkit[64,68]. After registration,
the median DSC between the registered atlas volumetric histology images and the lightsheet microscopy
images of each sample brain was 0.91 (mean: 0.91; 95% confidence interval: 0.90-0.92; Suppl. Fig. S10),
although inspection of registered brains also revealed slight misalignments with the atlas, mostly in caudal
regions including the cerebellum, a structure known to be challenging for registration[66]. Variations in

Figure 5: **Refined Atlases.** (a-h) Representative axial planes from all atlases across the ADMBA. For each
pair of images, a plane of the original (left) atlas is depicted next to the refined (right) atlas after undergoing
the full refinement pipeline. Complete atlases before and after refinement are shown as movies in Videos
S1-16.

348
349

sample preparation, including the completeness of the dissected hindbrain and expansion of the third

ventricle during tissue clearing may also have contributed to these misalignments.

To evaluate whether our updated, smoothed 3D labels improved the analysis of true volumetric data, we

registered both the original and refined labels to 15 tissue-cleared, nuclei-labelled whole wild-type mouse

brains (10 male, 5 female). We would expect improved 3D labels to correspond more closely to the under-

lying anatomy. To test this expectation, we generated gross anatomical edge maps for each cleared brain

and measured distances from label borders to anatomical edges. Edge distances significantly improved for

almost all labels (overall decrease from a median of 153 million μm to 96 million μm, p = 0.007, WSRT,

Bonferroni corrected for all hierarchical brain labels, mean 152 million to 99 million μm; Fig. 7a, c-d;

Suppl. Fig. S13a). We would also expect improved 3D labels to have lower variation in image intensity

within each label, as we observed in assessing the refined labels with the original brain images from which

they were derived (Fig. 4e). We observed a small, but significant decrease in the intensity coefficient of

variation at the whole-brain level (0.309 to 0.301, p = 0.007, WSRT, Bonferroni corrected, mean 0.311 to

0.304) and most sub-labels (Suppl. Fig. S13b). For 22 labels (18% of all labels) the variability worsened,

however this was only significant (p = 0.04) for a single label. The majority of these 22 labels describe

small structures (combined 7% of total volume) and therefore sensitive to slight perturbations in border lo-

cation, and located ventrally in the brain, where signal was prone to being distorted by glue artifacts from

the mount for lightsheet imaging. For context, variability improved for 98 labels (82% of all labels) with 27

labels showing significant improvement.

These two analyses support an overall improved performance of the refined 3D labels with the volumetric

images, however we can also test nuclei density - a key use case for whole-brain imaging methods[31]. After

detecting nuclei throughout each brain (Fig. 6), we assigned each nucleus to an atlas label based on the

3D location of the nucleus. Using the numbers of nuclei per label and the volume per registered label, we

calculated nuclei densities using the original and refined labels (Suppl. Fig. S12). As with the volumetric

image data, we would expect accurate labels to encapsulate regions with more constant nuclei density. We

therefore assessed the coefficient of variation for nuclei density and observed a small, but significant

Figure 6: **Nuclei Detection.** (a) Overview of the nuclei detection and assignment pipeline. After tissue clearing by CUBIC and nuclear staining, we imaged intact whole P0 mouse brains by lightsheet microscopy. The E18.5 mouse brain atlas was registered to volumetric sample images. Nuclei were identified brain-wide with a 3D blob detector algorithm, and the nuclei coordinates were used to map to specific region labels, allowing quantification of nuclei counts and density for each label. (b) Axial view of the hippocampus of a P0 mouse brain at the original magnification of 5x (left) and zoomed to 20x (right), with the same region of interest (ROI) depicted by the yellow box in both. (c) Serial 2D planes along the ROI shown by the yellow box in part "b" show the emergence and disappearance of nuclei while progressing vertically (z-axis) through the ROI. Each of four individual nuclei is assigned a unique colored circle. The most central image of the nuclei is indicated by a solid circle and asterisk, while images above or below have dashed circles. (d) 3D schematic of the four nuclei from part "c" demonstrating their spatial orientation.

improvement with the refined labels overall (median 0.629 to 0.625, p = 0.007, WSRT, Bonferroni corrected, mean 0.629 to 0.625) and across the majority of labels in the hierarchy (Suppl. Fig. S13c). A median of 13.5% (4.7 million) nuclei (mean 13.2% (4.6 million) nuclei) were reassigned from original to refined labels. Examples of these nuclei reassignments in a wild-type mouse forebrain is depicted in Fig. 7b. As an independent assessment of label alignment based on nuclei density alone, we measured nuclei clustering within each label under the expectation that well-aligned labels would group nuclei of similar densities, whereas poorly aligned labels would form isolated pockets of nuclei along borders between regions of

Figure 7: **Application of refined labels to C57BL/6J mouse brains.** (a) Example of the original (mirrored, left) and smoothed (edge-aware, right) E18.5 atlases registered to a representative cleared, optically-sectioned P0 wild-type mouse brain. Edge distances between the registered labels and the brain's own anatomical edge map are reduced for this example brain, shown by the color gradient for each edge (bottom). (b) Label alignment at higher resolution. The top row depicts the registered original (mirrored) atlas at 20x and 100x around a region of interest highlighted by a yellow box. This same brain region is depicted in the bottom row, but overlaid with the refined atlas registered using identical transformations as in the original atlas. (c) Summation of the edge distances across all 15 wild-type brains with color gradient showing the edge distances with the original (top) and smoothed (bottom) labels. (d) Total edge distance at the whole-brain level before and after atlas refinement for each of these brains. (e) Density-based nuclei clustering within each label. Many of the isolated nuclei that could not be clustered in the original labels were clustered in the refined labels, with differences in unclustered nuclei shown from 16 regions selected across the hierarchy of labels from the grossest (neural plate, L0, left) to the finest (e.g. dorsal pallium, L7, right). Error bars represent 95% confidence intervals. (f) The differences between the original and refined labels' unclustered nuclei are depicted on an anatomical map showing this metric as a color gradient across all of the sublevel labels present in a cross section. Improvements with the refined atlas are colored in blue, while red represents better performance with the original atlas. A complete list of differences for each metric in each label is provided in Table S2.

419 contrasting nuclei densities. We employed Density-Based Spatial Clustering of Applications with Noise

420 (DBSCAN)[69], an algorithm useful for both clustering and noise or anomaly detection[70], and indeed found

421 that label refinement reduced isolated, unclustered nuclei by 30% (median 4.4×10^5 to 3.1×10^5 nuclei; p

422 = 0.007, WSRT, Bonferroni corrected; mean 4.4×10^5 to 3.1×10^5; Fig. 7e-f), suggesting greater nuclei

423 assignment to labels with nuclei clusters of similar density.

MagellanMapper as a tool

To facilitate both automated atlas refinement and visual inspection of large 3D microscopy images, we

developed the open-source MagellanMapper software suite. This Python-based[71,72] image processing soft-

ware consists of both a graphical user interface (GUI) for visualization and a command-line interface for

automation (Suppl. Fig. S15). A major goal of the suite's GUI is to enable unfiltered, raw visualization and

annotation of original 2D images in a 3D context. The GUI consists of three main components: 1) A region

of interest (ROI) selector and 3D visualizer with 3D rendering, 2) A serial 2D ROI visualizer and annotator,

tailored for building truth sets of 3D nuclei positions, and 3) A simultaneous orthogonal plane viewer with

atlas label editing tools, including painting designed for use with a pen and edge interpolation to smoothly

fill in changes between two edited, non-adjacent planes. The command-line interface provides automated

pipelines for processing of large (terabyte-scale) volumetric images, including 3D nuclei detection at full

image resolution.

The suite makes extensive use of established computer vision libraries such as scikit-image[73], ITK[74] (via

SimpleITK[75] and SimpleElastix[64,67]), visualization toolkits such as Matplotlib[76] and Mayavi[77], and statis-

tical and machine learning libraries such as Numpy[78], SciPy[79], Pandas[80], and scikit-learn[81]. The cross-

platform capabilities of Python allow the suite to be available in Windows, MacOS, and Linux. We also

leverage additional open-source imaging ecosystems such as the ImageJ/Fiji[82,83] suite for image stitching

through the BigStitcher plugin[84], integrated into our automated pipelines through Bash scripts.

Discussion

3D reference atlases are critical resources for interpreting and comparing anatomically complex tissues, especially as techniques for whole-tissue microscopy[20,31] and *in-situ* single-cell transcriptome methodologies are refined[85,86]. Considerable effort has been invested in generating 2D reference atlases, while manually building atlases in 3D is time-consuming and laborious; building 3D atlases from these 2D resources will save time and improve comparability between analyses. Here, we have presented a method to automate the conversion of complete or even partial atlases from 2D sections to complete 3D volumes and applied these methods to the eight developing mouse brain atlases in the ADMBA (Fig. 5).

Key features of our method include, first, an approach to adaptive morphology for label smoothing while preserving image detail by combining skeletonization, morphological erosion, and watershed segmentation. Second, we utilized this method as an edge-aware label refinement approach, which incorporates anatomical edge detection from an underlying intensity-based image to perform two functions: 1) Label extension into incompletely labeled regions, and 2) Anatomically guided label curation. Third, we integrated these approaches into an automated pipeline as a general way to refine serial 2D labeled datasets into 3D atlases and applied the pipeline to complete and refine the full suite of 8 atlases in the Allen Developing Mouse Brain Atlas series from ages E11.5 to P56 as a resource to the neuroscience and neurodevelopmental communities (Fig. 5). Specifically, these tools extend incomplete labels in each atlas to cover the entire brain and smooth artifacts between 2D sections, whilst respecting anatomical boundaries. We show that the refined labels are more complete (Fig. 2), the interface between labels match anatomical images more closely (Fig. 4), and the image intensity within these labels is more homogeneous (Fig. 4). Using whole-brain lightsheet microscopy of 15 mice at P0, we identified the 3D location of 35 million nuclei per brain (median across 15 samples; Fig. 6). Again, we showed that the refined labels match anatomical boundaries better, including at the nuclei level, providing a key step towards comparative analysis of whole brain cytoarchitecture (Fig. 7). Fifth, we have provided the method as an open source, graphical software suite with an end-to-end automated image processing pipeline for refining atlases and detecting nuclei by anatomical label in raw microscopy images of whole tissues.

Building a 3D reference atlas from a physically sectioned atlas presents three main challenges: 1) Incomplete labels resulting in unidentified tissues, 2) Smoothing jagged edge artifacts between sections in two of the three dimensions, and 3) Maintaining anatomical boundaries through the smoothing process. Prior work has addressed these challenges through two approaches. The first is to apply a Gaussian filter

to smooth the label edges[38]. This approach can be implemented automatically to existing 2D data, however

the resulting smoothed labels often cross anatomical boundaries in the ADMBA images and incur loss of

details, a known challenge with smoothing by filtering[87], including loss of small labels (Suppl. Fig. S4).

The second approach, applied to the Allen Reference Atlas for the adult mouse brain in version 3 of the

Common Coordinate Framework (CCFv3, 2017)[36], uses a combination of novel data generation,

automated alignment, and manual curation by neuroanatomists and illustrators. The resulting 3D reference

atlas is highly accurate; however, an equivalent large-scale effort would be required for each stage of

development in the ADMBA.

Our method represents a mid-point between these two approaches by both smoothing and curating atlases

in an automated fashion based on underlying imaging data. To address loss of detail through smoothing, the

combination of adaptive morphology and an edge-aware watershed allowed us to preserve small structures

during automated smoothing. The approach also fit labels to anatomical boundaries to improve both the

accuracy of the resulting 3D reference atlas and its label coverage through extension to incompletely labeled

regions. While automated approaches may not be as accurate as expert curated labeling, as performed in

the Allen CCFv3, even expert curation may lead to inaccurate or controversial labeling[2]. However, our

automated approach does provide substantial refinement over existing reference atlases and creates a

complete resource that is immediately applicable for registration of 3D imaging data (Fig. 7). Furthermore,

it acts as a foundation for further improvements, substantially reducing the work required to generate a

manually curated atlas in the future.

Despite substantial improvements over the original atlases as we demonstrated, we are aware of some

specific limitations of the approach. We expected less variability in image intensity within a region than

between regions, and therefore improved region labels should reduce image intensity variability. While

this expectation was correct for the majority of labels (82%), a small number of regions showed a modest

increase in variability with our refined labels. Most of these labels were in the hindbrain, where

histological contrast is lower, leading to less well-defined anatomical edges. Adjusting the weight of

edge-detected boundaries based on the degree of underlying intensity contrast could lessen the impact of

these edges on reannotation. A few more labels exhibited this paradox when registered to the wild-type

brains, likely owing to artifacts from tissue preparation and mounting, the slight age mismatch between the

closest available E18.5 atlas and the P0 wild-type brains, registration misalignments, and inaccuracies of

the blob detector.

Another limitation is the use of a single filtering kernel size for smoothing across the entire brain (Fig. 3).

In labels with both thick and thin sections, the thin portions are prone to being lost during the erosion step

of smoothing. While our use of skeletonization to preserve the core of such thin sections and the edge-

aware watershed both addressed this issue, applying smaller filter kernel sizes in thin sections would also

be beneficial. More generally, the combination of erosion, skeletonization, and watershed could serve as an

adaptive form of morphological operations to better preserve any label's overall footprint and topological

consistency.

While the refined labels are superior to the original ones in both the ADMBA images and whole-brain

lightsheet microscopy images, we observed more registration artifacts with the whole-brain lightsheet

microscopy images (Fig. 7a). Undoubtedly, biological variation, the slight age mismatch (E18.5 in

ADMBA vs. P0 for lightsheet), and the different preparations and imaging modality (Nissl sections vs.

nuclei-stained whole-brain) are substantial factors. Generating a group-wise composite of nuclei-stained

whole-brain could help reduce biological variation. Deferring the edge-aware reannotation step until after

registration using boundaries identified in the nuclei-stained whole-brain may also reduce these artifacts.

Recent methodological advances may further improve the refined 3D labels. Chon et al. integrated the

Franklin-Paxinos atlas with the CCFv3 atlas and additional cell-type specific markers, addressing

discrepancies between these standard references[2]. Integrating our anatomical edge maps with *in-situ*

hybridization expression patterns[36,46] may similarly improve label boundaries. A deep learning model

utilized histological textures to generate labels[87]. Training the model required substantial manual

annotation to serve as the initial ground truth; in this context, our automated approach to atlases

generation may be able to replace or augment this manual step. Another recent approach used fractional

differential operators to preserve texture as well as edge information for segmentation of single-cell

resolution data[88]. This could be incorporated into the 3D anatomical edge map generation step to further

delineate labels at higher or even full resolution.

Conclusion

531
Mouse whole-brain imaging has been used to understand models of human traits, including sexual di-

morphism[7] and models of human disorders, including Alzheimer's disease[89–91], serotonin dysregulation[92],

epilepsy[93], and Autism Spectrum Disorder (ASD)[94]. These analyses required automated registration to 3D

reference atlases to identify subtle changes not readily appreciable in individual slices. The refinements to

3D reference atlases that we have described here, and the improvements in performance we have

demonstrated, provide a resource to help identify biological differences in the multiple models of human

disorders and traits, including those that affect brain development.

Data Availability

542   The method is freely available as open source software at https://github.com/sanderslab/magellanmapper.

543   Note to editors and reviewers: The refined ADMBA atlas files are too large to be included as supplements.

544   We will upload the full atlases to the Human Brain Project EBRAINS data platform (https://ebrains.eu/) and

545   include the accession numbers in the publication.

References

1. Marquart, G. D. *et al.* High-precision registration between zebrafish brain atlases using symmetric diffeomorphic normalization. *GigaScience* **6.** doi:10.1093/gigascience/gix056. https://academic.oup.com/gigascience/article/6/8/gix056/4085311 (2019) (Aug. 1, 2017).

2. Chon, U., Vanselow, D. J., Cheng, K. C. & Kim, Y. Enhanced and unified anatomical labeling for a common mouse brain atlas. *Nature Communications* **10,** 5067. ISSN: 2041-1723 (Nov. 7, 2019).

3. Liu, C. *et al.* A resource for the detailed 3D mapping of white matter pathways in the marmoset brain. *Nature Neuroscience,* 1–10. ISSN: 1546-1726 (Jan. 13, 2020).

4. Kunst, M. *et al.* A Cellular-Resolution Atlas of the Larval Zebrafish Brain. *Neuron.* ISSN: 0896-6273. doi:10.1016/j.neuron.2019.04.034. http://www.sciencedirect.com/science/article/pii/S0896627319303915 (2019) (May 27, 2019).

5. Franklin, K. B. J. & Paxinos, G. *Paxinos and Franklin's The mouse brain in stereotaxic coordinates* OCLC: 817268868. ISBN: 978-0-12-391057-8 (2013).

6. Renier, N. *et al.* Mapping of Brain Activity by Automated Volume Analysis of Immediate Early Genes. *Cell* **165,** 1789–1802. ISSN: 0092-8674 (June 16, 2016).

7. Kim, Y. *et al.* Brain-wide Maps Reveal Stereotyped Cell-Type-Based Cortical Architecture and Sub-cortical Sexual Dimorphism. *Cell* **171,** 456–469.e22. ISSN: 0092-8674 (Oct. 5, 2017).

8. Regev, A. *et al.* The Human Cell Atlas. *eLife* **6.** ISSN: 2050-084X. doi:10.7554/eLife.27041. https://www.ncbi.nlm.nih.gov/pmc/articles/PMC5762154/ (2019).

9. Ecker, J. R. *et al.* The BRAIN Initiative Cell Census Consortium: Lessons Learned toward Generating a Comprehensive Brain Cell Atlas. *Neuron* **96,** 542–557. ISSN: 0896-6273 (Nov. 1, 2017).

10. Koroshetz, W. *et al.* The State of the NIH BRAIN Initiative. *Journal of Neuroscience* **38,** 6427–6438. ISSN: 0270-6474, 1529-2401 (July 18, 2018).

11. Amunts, K. *et al.* The Human Brain Project: Creating a European Research Infrastructure to Decode the Human Brain. *Neuron* **92,** 574–581. ISSN: 1097-4199 (Nov. 2, 2016).

12. Jones, A. R., Overly, C. C. & Sunkin, S. M. The Allen Brain Atlas: 5 years and beyond. *Nature Reviews Neuroscience* **10,** 821–828. ISSN: 1471-0048 (Nov. 2009).

13. Huang, Z. J. & Luo, L. It takes the world to understand the brain. *Science* **350,** 42–44. ISSN: 0036-8075, 1095-9203 (Oct. 2, 2015).

14. Thompson, P. M. *et al.* The ENIGMA Consortium: large-scale collaborative analyses of neuroimaging and genetic data. *Brain Imaging and Behavior* **8,** 153–182. ISSN: 1931-7557 (2014).

15. Jahanshad, N. *et al.* Multi-site genetic analysis of diffusion images and voxelwise heritability analysis: A pilot project of the ENIGMA–DTI working group. *NeuroImage* **81,** 455–469. ISSN: 1053-8119 (Nov. 1, 2013).

16. Sudlow, C. *et al.* UK Biobank: An Open Access Resource for Identifying the Causes of a Wide Range of Complex Diseases of Middle and Old Age. *PLOS Medicine* **12,** e1001779. ISSN: 1549-1676 (Mar. 31, 2015).

17. Miller, K. L. *et al.* Multimodal population brain imaging in the UK Biobank prospective epidemiological study. *Nature Neuroscience* **19,** 1523–1536. ISSN: 1546-1726 (Nov. 2016).

18. Alfaro-Almagro, F. *et al.* Image processing and Quality Control for the first 10,000 brain imaging datasets from UK Biobank. *NeuroImage* **166,** 400–424. ISSN: 1053-8119 (Feb. 1, 2018).

19. Walhovd, K. B. *et al.* Healthy minds 0–100 years: Optimising the use of European brain imaging cohorts ("Lifebrain"). *European Psychiatry. Workshop on Schizophrenia and other mental disorders - S. Frangou (Editor in Chief), A. Del Guerra, S. Galderisi (Guest Editors)* **50,** 47–56. ISSN: 0924-9338 (Apr. 1, 2018).

20. Ragan, T. *et al.* Serial two-photon tomography for automated ex vivo mouse brain imaging. *Nature Methods* **9,** 255–258. ISSN: 1548-7091 (Mar. 2012).

21. Chung, K. *et al.* Structural and molecular interrogation of intact biological systems. *Nature* **497,** 332–337. ISSN: 0028-0836 (May 16, 2013).

22. Ertürk, A. *et al.* Three-dimensional imaging of solvent-cleared organs using 3DISCO. *Nature Protocols* **7,** 1983–1995. ISSN: 1750-2799 (Nov. 2012).

23. Susaki, E. A. *et al.* Whole-Brain Imaging with Single-Cell Resolution Using Chemical Cocktails and Computational Analysis. *Cell* **157,** 726–739. ISSN: 0092-8674, 1097-4172 (Apr. 24, 2014).

24. Chhetri, R. K. *et al.* Whole-animal functional and developmental imaging with isotropic spatial resolution. *Nature Methods* **advance online publication.** ISSN: 1548-7091. doi:10.1038/nmeth.3632. http://www.nature.com/nmeth/journal/vaop/ncurrent/full/nmeth.3632.html (2015) (Oct. 26, 2015).

25. Meijering, E., Carpenter, A. E., Peng, H., Hamprecht, F. A. & Olivo-Marin, J.-C. Imagining the future of bioimage analysis. *Nature Biotechnology* **34,** 1250–1255. ISSN: 1087-0156 (Dec. 2016).

26. Mano, T. *et al.* Whole-Brain Analysis of Cells and Circuits by Tissue Clearing and Light-Sheet Microscopy. *Journal of Neuroscience* **38,** 9330–9337. ISSN: 0270-6474, 1529-2401 (Oct. 31, 2018).

27. Hillman, E. M., Voleti, V., Li, W. & Yu, H. Light-Sheet Microscopy in Neuroscience. *Annual Review of Neuroscience* **42,** 295–313 (2019).

28. Cai, R. *et al.* Panoptic imaging of transparent mice reveals whole-body neuronal projections and skull–meninges connections. *Nature Neuroscience* **22,** 317. ISSN: 1546-1726 (Feb. 2019).

29. Ueda, H. R. *et al.* Tissue clearing and its applications in neuroscience. *Nature Reviews. Neuroscience.* ISSN: 1471-0048. doi:10.1038/s41583-019-0250-1 (Jan. 2, 2020).

30. Kim, Y. *et al.* Mapping social behavior-induced brain activation at cellular resolution in the mouse. *Cell Reports* **10,** 292–305. ISSN: 2211-1247 (Jan. 13, 2015).

31. Murakami, T. C. *et al.* A three-dimensional single-cell-resolution whole-brain atlas using CUBIC-X expansion microscopy and tissue clearing. *Nature Neuroscience,* 1. ISSN: 1546-1726 (Mar. 5, 2018).

32. Gilbert, K. *et al.* Independent Left Ventricular Morphometric Atlases Show Consistent Relationships with Cardiovascular Risk Factors: A UK Biobank Study. *Scientific Reports* **9,** 1130. ISSN: 2045-2322 (Feb. 4, 2019).

33. Bai, W. *et al.* A bi-ventricular cardiac atlas built from 1000+ high resolution MR images of healthy subjects and an analysis of shape and motion. *Medical Image Analysis* **26,** 133–145. ISSN: 1361-8415 (Dec. 1, 2015).

34. Li, B., Christensen, G. E., Hoffman, E. A., McLennan, G. & Reinhardt, J. M. Establishing a Normative Atlas of the Human Lung: Computing the average transformation and atlas construction. *Academic radiology* **19,** 1368–1381. ISSN: 1076-6332 (Nov. 2012).

35. Ardini-Poleske, M. E. *et al.* LungMAP: The Molecular Atlas of Lung Development Program. *American Journal of Physiology-Lung Cellular and Molecular Physiology* **313,** L733–L740. ISSN: 1040-0605 (Aug. 10, 2017).

36. Allen Institute for Brain Science. *Overview of the design and implementation of the Allen Mouse Common Coordinate Framework* Oct. 2017. http://help.brain-map.org/download/attachments/2818171/Mouse_Common_Coordinate_Framework.pdf?version=4&modificationDate=1508448259091&api=v2.

37. Susaki, E. A. & Ueda, H. R. Whole-body and Whole-Organ Clearing and Imaging Techniques with Single-Cell Resolution: Toward Organism-Level Systems Biology in Mammals. *Cell Chemical Biology* **23,** 137–157. ISSN: 2451-9456 (Jan. 21, 2016).

38. Niedworok, C. J. *et al.* aMAP is a validated pipeline for registration and segmentation of high-resolution mouse brain data. *Nature Communications* **7,** 11879. ISSN: 2041-1723 (July 7, 2016).

39. Watson, A. M. & Watkins, S. C. Massive volumetric imaging of cleared tissue: The necessary tools to be successful. *The International Journal of Biochemistry & Cell Biology* **112,** 76–78. ISSN: 1357-2725 (July 1, 2019).

40. Puelles, L. & Rubenstein, J. L. R. Forebrain gene expression domains and the evolving prosomeric model. *Trends in Neurosciences* **26,** 469–476. ISSN: 0166-2236 (Sept. 2003).

41. Watson, C., Paxinos, G. & Puelles, L. *The Mouse Nervous System* doi:10.1016/C2009-0-00185-8 (Jan. 1, 2012).

42. Lein, E. S. *et al.* Genome-wide atlas of gene expression in the adult mouse brain. *Nature* **445,** 168–176. ISSN: 1476-4687 (Jan. 2007).

43. Ng, L. *et al.* Neuroinformatics for Genome-Wide 3-D Gene Expression Mapping in the Mouse Brain. *IEEE/ACM Transactions on Computational Biology and Bioinformatics* **4,** 382–393. ISSN: 1545-5963 (July 2007).

44. Savolainen, S. M., Foley, J. F. & Elmore, S. A. Histology Atlas of the Developing Mouse Heart with Emphasis on E11.5 to E18.5. *Toxicologic pathology* **37,** 395–414. ISSN: 0192-6233 (2009).

45. De Boer, B. A., van den Berg, G., de Boer, P. A. J., Moorman, A. F. M. & Ruijter, J. M. Growth of the developing mouse heart: An interactive qualitative and quantitative 3D atlas. *Developmental Biology* **368,** 203–213. ISSN: 0012-1606 (Aug. 15, 2012).

46. Thompson, C. L. *et al.* A High-Resolution Spatiotemporal Atlas of Gene Expression of the Developing Mouse Brain. *Neuron* **83,** 309–323. ISSN: 0896-6273 (July 16, 2014).

47. Papp, E. A., Leergaard, T. B., Calabrese, E., Johnson, G. A. & Bjaalie, J. G. Waxholm Space atlas of the Sprague Dawley rat brain. *NeuroImage* **97,** 374–386. ISSN: 1053-8119 (Aug. 15, 2014).

48. Erö, C., Gewaltig, M.-O., Keller, D. & Markram, H. A Cell Atlas for the Mouse Brain. *Frontiers in Neuroinformatics* **12.** ISSN: 1662-5196. doi:10.3389/fninf.2018.00084. https://www.frontiersin.org/articles/10.3389/fninf.2018.00084/full?utm_

source= FWEB & utm_ medium= NBLOG & utm_ campaign= ECO _ FNINF _ blue- brain-cell-atlas#h10 (2019) (2018).

49. Allen Institute for Brain Science. *Technical White Paper: Reference Atlases for the Allen Developing Mouse Brain Atlas, v.2* http://help.brain-map.org/download/attachments/4325389/ReferenceAtlas_DevMouse.pdf?version=1&modificationDate=1370999986479&api=v2 (2019).

50. Dice, L. R. Measures of the Amount of Ecologic Association Between Species. *Ecology* **26,** 297–302. ISSN: 1939-9170 (1945).

51. Tustison, N. & Gee, J. Introducing Dice, Jaccard, and Other Label Overlap Measures To ITK. *The Insight Journal.* Revision: 2, 707. ISSN: 2327-770X (Dec. 1, 2009).

52. Marr, D. & Hildreth, E. Theory of edge detection. *Proceedings of the Royal Society of London. Series B, Biological Sciences* **207,** 187–217. ISSN: 0950-1193 (Feb. 29, 1980).

53. Neubert, P. & Protzel, P. *Compact Watershed and Preemptive SLIC: On Improving Trade-offs of Superpixel Segmentation Algorithms* in *2014 22nd International Conference on Pattern Recognition* 2014 22nd International Conference on Pattern Recognition (Aug. 2014), 996–1001. doi:10.1109/ICPR.2014.181.

54. Ballard, D. H. & Brown, C. M. *Computer Vision* 1st. ISBN: 978-0-13-165316-0 (Prentice Hall Professional Technical Reference, 1982).

55. Bribiesca, E. An easy measure of compactness for 2D and 3D shapes. *Pattern Recognition* **41,** 543–554. ISSN: 0031-3203 (Feb. 1, 2008).

56. Serra, J. *Image Analysis and Mathematical Morphology* ISBN: 978-0-12-637240-3 (Academic Press, Inc., Orlando, FL, USA, 1983).

57. Lee, T. C., Kashyap, R. L. & Chu, C. N. Building Skeleton Models via 3-D Medial Surface Axis Thinning Algorithms. *CVGIP: Graphical Models and Image Processing* **56,** 462–478. ISSN: 1049-9652 (Nov. 1, 1994).

58. Susaki, E. A. *et al.* Advanced CUBIC protocols for whole-brain and whole-body clearing and imaging. *Nature Protocols* **10,** 1709–1727. ISSN: 1754-2189 (Nov. 2015).

59. Kolesová, H., Čapek, M., Radochová, B., Janáček, J. & Sedmera, D. Comparison of different tissue clearing methods and 3D imaging techniques for visualization of GFP-expressing mouse embryos and embryonic hearts. *Histochemistry and Cell Biology* **146,** 141–152. ISSN: 1432-119X (Aug. 2016).

60. Xu, J., Ma, Y., Yu, T. & Zhu, D. Quantitative assessment of optical clearing methods in various intact mouse organs. *Journal of Biophotonics* **12,** e201800134. ISSN: 1864-0648 (Feb. 2019).

61. Bossolani, G. D. P. *et al.* Comparative analysis reveals Ce3D as optimal clearing method for in toto imaging of the mouse intestine. *Neurogastroenterology & Motility* **31,** e13560. ISSN: 1350-1925 (May 1, 2019).

62. Schmid, B., Schindelin, J., Cardona, A., Longair, M. & Heisenberg, M. A high-level 3D visualization API for Java and ImageJ. *BMC Bioinformatics* **11,** 274. ISSN: 1471-2105 (May 21, 2010).

63. Murray, S. A. *et al.* Mouse Gestation Length Is Genetically Determined. *PLOS ONE* **5,** e12418. ISSN: 1932-6203 (Aug. 25, 2010).

64. Klein, S., Staring, M., Murphy, K., Viergever, M. A. & Pluim, J. P. W. elastix: A Toolbox for Intensity-Based Medical Image Registration. *IEEE Transactions on Medical Imaging* **29,** 196–205. ISSN: 0278-0062 (Jan. 2010).

65. Shamonin, D. P. *et al.* Fast Parallel Image Registration on CPU and GPU for Diagnostic Classification of Alzheimer's Disease. *Frontiers in Neuroinformatics* **7.** ISSN: 1662-5196. doi:10.3389/fninf.2013.00050. https://www.frontiersin.org/articles/10.3389/fninf.2013.00050/full (2019) (2014).

66. Nazib, A., Galloway, J., Fookes, C. & Perrin, D. *Performance of Registration Tools on High-Resolution 3D Brain Images* in *2018 40th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC)* 2018 40th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC) (July 2018), 566–569. doi:10.1109/EMBC.2018.8512403.

67. Marstal, K., Berendsen, F., Staring, M. & Klein, S. *SimpleElastix: A User-Friendly, Multi-lingual Library for Medical Image Registration* in *2016 IEEE Conference on Computer Vision and Pattern Recognition Workshops (CVPRW)* 2016 IEEE Conference on Computer Vision and Pattern Recognition Workshops (CVPRW) (June 2016), 574–582. doi:10.1109/CVPRW.2016.78.

68. Hammelrath, L. *et al.* Morphological maturation of the mouse brain: An in vivo MRI and histology investigation. *NeuroImage* **125,** 144–152. ISSN: 1053-8119 (Jan. 15, 2016).

69. Ester, M., Kriegel, H.-P., Sander, J. & Xu, X. *A Density-based Algorithm for Discovering Clusters a Density-based Algorithm for Discovering Clusters in Large Spatial Databases with Noise* in *Proceedings of the Second International Conference on Knowledge Discovery and Data Mining* event-place:

Portland, Oregon (AAAI Press, 1996), 226–231. http://dl.acm.org/citation.cfm?id=3001460.3001507 (2019).

70. Ali, T., Asghar, S. & Sajid, N. A. *Critical analysis of DBSCAN variations* in *2010 International Conference on Information and Emerging Technologies* 2010 International Conference on Information and Emerging Technologies. ISSN: null (June 2010), 1–6. doi:10.1109/ICIET.2010.5625720.

71. Oliphant, T. E. Python for Scientific Computing. *Computing in Science Engineering* **9,** 10–20. ISSN: 1558-366X (May 2007).

72. Millman, K. J. & Aivazis, M. Python for Scientists and Engineers. *Computing in Science Engineering* **13,** 9–12. ISSN: 1558-366X (Mar. 2011).

73. Van der Walt, S. *et al.* scikit-image: image processing in Python. *PeerJ* **2.** ISSN: 2167-8359. doi:10.7717/peerj.453. http://www.ncbi.nlm.nih.gov/pmc/articles/PMC4081273/ (2017) (June 19, 2014).

74. Yoo, T. S. *et al.* Engineering and algorithm design for an image processing Api: a technical report on ITK–the Insight Toolkit. *Studies in Health Technology and Informatics* **85,** 586–592. ISSN: 0926-9630 (2002).

75. Lowekamp, B. C., Chen, D. T., Ibanez, L. & Blezek, D. The Design of SimpleITK. *Frontiers in Neuroinformatics* **7.** ISSN: 1662-5196. doi:10.3389/fninf.2013.00045. https://www.frontiersin.org/articles/10.3389/fninf.2013.00045/full (2019) (2013).

76. Hunter, J. D. Matplotlib: A 2D Graphics Environment. *Computing in Science Engineering* **9,** 90–95. ISSN: 1521-9615 (May 2007).

77. Ramachandran, P. & Varoquaux, G. Mayavi: 3D Visualization of Scientific Data. *Computing in Science Engineering* **13,** 40–51. ISSN: 1521-9615 (Mar. 2011).

78. Van der Walt, S., Colbert, S. C. & Varoquaux, G. The NumPy Array: A Structure for Efficient Numerical Computation. *Computing in Science Engineering* **13,** 22–30. ISSN: 1558-366X (Mar. 2011).

79. Virtanen, P. *et al.* SciPy 1.0–Fundamental Algorithms for Scientific Computing in Python. https://arxiv.org/abs/1907.10121v1 (2019) (July 23, 2019).

80. McKinney, W. *Data Structures for Statistical Computing in Python* in. Proceedings of the 9th Python in Science Conference (2010), 51–56. http://conference.scipy.org/proceedings/scipy2010/mckinney.html (2019).

81. Pedregosa, F. *et al.* Scikit-learn: Machine Learning in Python. *arXiv:1201.0490 [cs].* arXiv: 1201.0490. http://arxiv.org/abs/1201.0490 (2019) (June 5, 2018).

82. Schindelin, J. *et al.* Fiji: an open-source platform for biological-image analysis. *Nature Methods* **9,** 676–682. ISSN: 1548-7105 (July 2012).

83. Rueden, C. T. *et al.* ImageJ2: ImageJ for the next generation of scientific image data. *BMC Bioinformatics* **18,** 529. ISSN: 1471-2105 (Nov. 29, 2017).

84. Hörl, D. *et al.* BigStitcher: reconstructing high-resolution image datasets of cleared and expanded samples. *Nature Methods* **16,** 870–874. ISSN: 1548-7105 (Sept. 2019).

85. Nowakowski, T. J. *et al.* Spatiotemporal gene expression trajectories reveal developmental hierarchies of the human cortex. *Science (New York, N.Y.)* **358,** 1318–1323. ISSN: 1095-9203 (2017).

86. Polioudakis, D. *et al.* A Single-Cell Transcriptomic Atlas of Human Neocortical Development during Mid-gestation. *Neuron* **103,** 785–801.e8. ISSN: 0896-6273 (Sept. 4, 2019).

87. Chen, Y. *et al.* An active texture-based digital atlas enables automated mapping of structures and markers across brains. *Nature Methods* **16,** 341. ISSN: 1548-7105 (Apr. 2019).

88. Xu, X. *et al.* Automated Brain Region Segmentation for Single Cell Resolution Histological Images Based on Markov Random Field. *Neuroinformatics.* ISSN: 1559-0089. doi:10.1007/s12021-019-09432-z. https://doi.org/10.1007/s12021-019-09432-z (2019) (Aug. 2, 2019).

89. Liebmann, T. *et al.* Three-Dimensional Study of Alzheimer's Disease Hallmarks Using the iDISCO Clearing Method. *Cell Reports* **16,** 1138–1152. ISSN: 2211-1247 (July 26, 2016).

90. Delafontaine-Martel, P. *et al.* Whole brain vascular imaging in a mouse model of Alzheimer's disease with two-photon microscopy. *Journal of Biomedical Optics* **23,** 076501. ISSN: 1083-3668, 1560-2281 (July 2018).

91. Whitesell, J. D. *et al.* Whole brain imaging reveals distinct spatial patterns of amyloid beta deposition in three mouse models of Alzheimer's disease. *Journal of Comparative Neurology* **0.** ISSN: 0021-9967. doi:10.1002/cne.24555. https://onlinelibrary.wiley.com/doi/full/10.1002/cne.24555 (2019) (Oct. 12, 2018).

92. Ellegood, J. *et al.* Analysis of neuroanatomical differences in mice with genetically modified serotonin transporters assessed by structural magnetic resonance imaging. *Molecular Autism* **9,** 24. ISSN: 2040-2392 (Apr. 10, 2018).

93. Intson, K. *et al.* Progressive neuroanatomical changes caused by Grin1 loss-of-function mutation. *Neurobiology of Disease,* 104527. ISSN: 0969-9961 (July 9, 2019).

94. Suetterlin, P. *et al.* Altered Neocortical Gene Expression, Brain Overgrowth and Functional Over-Connectivity in Chd8 Haploinsufficient Mice. *Cerebral Cortex* **28,** 2192–2206. ISSN: 1047-3211 (June 1, 2018).