De novo design of high-affinity antibody variable regions (scFv) against the SARS-CoV-2 spike protein

Veda Sheersh Boorla[#], Ratul Chowdhury[#], and Costas D. Maranas[*]

Department of Chemical Engineering, The Pennsylvania State University, University Park. PA 16802

[*]*Corresponding author* | Email: costas@psu.edu

[#] *Equal contribution*

Abstract

The emergence of SARS-CoV-2 is responsible for the pandemic of respiratory disease known as COVID-19, which emerged in the city of Wuhan, Hubei province, China in late 2019. Both vaccines and targeted therapeutics for treatment of this disease are currently lacking. Viral entry requires binding of the viral spike receptor binding domain (RBD) with the human angiotensin converting enzyme (ACE2). In an earlier paper[1], we report on the specific residue interactions underpinning this event. Here we report on the *de novo* computational design of high affinity antibody variable regions through the recombination of VDJ genes targeting the most solvent-exposed ACE2-binding residues of the SARS-CoV-2 spike protein using the software tool OptMAVEn-2.0[2]. Subsequently, we carry out computational affinity maturation of the designed prototype variable regions through point mutations for improved binding with the target epitope. Immunogenicity was restricted by preferring designs that match sequences from a 9-mer library of "human string content" (HSC)[3]. We generated 60 different variable region designs and report in detail on the top five that trade-off the greatest affinity for the spike epitope (quantified using the Rosetta binding energies) with low immunogenicity scores. By grafting these designed variable regions with frameworks, high-affinity monoclonal antibodies can be constructed. Having a potent antibody that can recognize the viral spike protein with high affinity would be enabling for both the design of sensitive SARS-CoV-2 detection devices and for their deployment as neutralizing antibodies.

Main

Over the last few weeks, several studies on using human or humanized antibodies targeted at the SARS-CoV-2 spike protein have been reported[4,5,6,7]. In addition, multiple efforts by laboratories and companies (Cellex, GeneTex etc.) for the development of antibody-based tests for SARS-CoV-2 detection are ongoing[8]. At the same time, significant progress towards the isolation and design of vaccines (mRNA-1273 vaccine © 2020 Moderna, Inc) and neutralizing antibodies[9] has been made. A computational study

identified the structural basis for multi-epitope vaccines[10,11] whereas in another study, the glycosylation

patterns of the spike SARS-CoV-2 protein were computationally deduced[12]. In one study[13], fully human

single domain anti-SARS-CoV-2 antibodies with sub-nanomolar affinities were identified from a phage-

displayed single-domain antibody library by grafting naïve CDRs into framework regions of an identified

human germline IGHV allele using SARS-CoV-2 RBD and S1 protein as antigens. In another study[14], a

human antibody 47D11 was identified to have cross neutralizing effect on SARS-CoV-2 by screening

through a library of SARS-Cov-1 antibodies. In two other studies, potent neutralizing antibodies were

isolated from the sera of convalescent COVID-19 patients[15,16]. To the best of our knowledge, none of

these neutralizing antibody sequences are publicly available. In another very encouraging study[17], human

antibody CR3022 (which is neutralizing against SARS-CoV-1[18]) has been shown to bind to SARS-CoV-2

RBD in a cryptic epitope but without a neutralizing effect for SARS-CoV-2 *in vitro*. Moreover, we did

not find any studies that performed guided design of high affinity antibodies against specific epitopes of

SARS-CoV-2 proteins such as targeting the spike protein and subsequently prevent its binding with

human ACE2.

Motivated by these shortcomings, here we explore the *de novo* design of antibody variable regions

targeting most solvent-exposed residues of the spike protein that are involved in ACE2 binding, and

trade-off binding energy against human sequence content in the variable region. The goal was to

exhaustively explore the sequence space of all possible variable region designs and report a range of

diverse solutions that can serve as neutralizing antibodies (nAb). We find that many different

combinations of VDJ genes followed by mutation can yield potentially high affinity nAbs (scored using

the Rosetta binding energy function) against the epitope of the spike protein involved with ACE2 binding.

Pareto optimal designs with respect to binding affinity vs. human content were drawn and five choicest

designs have been discussed in the results section.

We first performed solvent accessibility analysis using the STRIDE[19] program on the 21 ACE2-binding

residues of the SARS-CoV-2 spike protein (S-protein) RBD to define our binding epitope. The top seven

residues with the highest solvent accessibility scores (i.e., SAS) are (Arg346, Phe347, Ala348, Tyr351,

Ala352, Asn354, and Arg355) comprising our binding epitope (see Figure 1).

Figure 1. The ACE2-spike complex is shown along with the most solvent accessible residues at the binding interface highlighted in purple. These seven residues form the epitope for the variable region of the nAb. The numbering scheme for the S-protein residues matches the one used in PDB with accession id 6LZG (rcsb.org/structure/6LZG or 6VW1[7], and 6M0J[6]).

We next used the previously developed OptMAVEn-2.0[2] software to computationally identify the

combination of VDJ genes forming the variable region that best binds the desired epitope. OptMAVEn[20]

has been used before successfully to design five high affinity CDRs against a FLAG tetrapeptide[21], three

thermally and conformationally stable antibody variable regions (sharing less than 75% sequence

similarity to any naturally occurring antibody sequence) against a dodecapeptide mimic of

carbohydrates[22] and two thermostable, high affinity variable heavy chain domains (V_HH) against α-

synuclein peptide responsible for Parkinson's disease[23]. All these designs were experimentally

constructed and nanomolar affinities for their respective target antigens was demonstrated.

Through a combination of rotations and translations, OptMAVEn-2.0 identified 3,234 unique antigen

poses that presented the epitope to the antibody differently. The combinatorial space of different VDJ

genes that upon recombination form the variable region of the prototype antibody was informed by the

MAPs database of antibody parts[24]. MAPs (see Supp. Info. S1 for link to full database) contains 929

modular antibody (i.e., variable-V*, complementarity determining -CDR3, and joining-J*) parts from

1,168 human, humanized, chimeric, and mouse antibody structures (last updated in 2013). MAPs follows

the antibody parts residue numbering convention as listed in the International iMmunoGeneTics

(IMGT)[25] database. IMGT catalogs antibody parts as variable (V), diversity (D) and joining (J) structure

libraries. MAPs stores complete CDR3 parts, C-terminus-shortened V parts (i.e. V* parts) and N-

terminus-shortened J parts (J* parts). Note that CDR3 includes the entire D gene and also up to the C-

terminus of the V gene and up to the N-terminus of the J gene. In the remainder of the manuscript, the list

of parts used to design the variable region are referred to as CDR3, V* and J* parts.

For each one of the 3,234 spike poses, OptMAVEn-2.0 identified a variable region combination
composed of end-to-end joined V*, CDR3, and J* region parts that minimized the Rosetta binding energy
between the variable region and spike epitope formed by the seven residues. As part of OptMAVEn-2.0,
the combinatorial optimization problem was posed and solved as a mixed-integer linear programming
(MILP) problem using the cplex solver[26]. The solution of this problem identifies, for each one of the spike
poses, the complete design of the variable region using parts denoted as HV*, HCDR3, HJ* for the heavy
chain H and L/KV*, L/KCDR3 and L/KJ* for the light chain-L/K. Only 173 antigen-presenting poses out
of 3,234 explored, yielded non-clashing antigen-antibody complexes. These 173 poses were ranked on the
basis of their Rosetta binding energies with the spike epitope and classified into 27 clusters (using *k-*
means[27]) in a 19-dimensional space defined by quantitative descriptors of sequence similarity, three-
dimensional spatial pose, and the angle at which they bind to the target epitope (see details in original
paper[2]). The top five prototype designs with the highest Rosetta binding energies were present in four
clusters and spanned a highly diverse set of choices of MAPs parts (see Table 1) with minimal
conservation of the same part among the five prototype designs. The number entries in Table 1
correspond to the id of the gene in the MAPs database (which are identical to the ids used in IMGT). Note
that design P5 uses a lambda (L) light chain instead of a kappa (K). Figure 1a plots the pairwise sequence
similarity scores of the five antibody variable domains that were used in the top five designs. As
expected, the top five prototype designs P1, P2, P3, P4, and P5 are the most dissimilar in their respective
CDR3 domains in both light L, heavy H and HV* domain (but not LV*). They are the most similar in the
choice of parts for the J* domains (see Figure 2a) reflecting the lack of diversity among possible choices
for the J* domains in the MAPs database.

Table 1. V*, CDR3, J* gene ids for the top five prototype variable region designs and corresponding Rosetta
binding energies[28,29].Antigen poses are described with the angle that the vertical axis through the epitope (shown in
pink) centroid and the Cβ carbon of the residue with greatest z-axis coordinate forms.

Prototype design	Modular Antibody Parts number chosen in each design						Antigen pose (rotation of epitope about vertical axis)	Rosetta binding energy (kcal/mol)
	HV*	HCDR3	HJ*	L/KV*	L/KCDR3	L/KJ*		
P1	82	315	5	61(K)	4(K)	3(K)	0°	-41.19
P2	52	94	1	61(K)	17(K)	3(K)	0°	-37.86

P3	105	12	5	6(K)	23(K)	4(K)	300°	-34.93
P4	79	204	1	2(K)	1(K)	4(K)	240°	-35.67
P5	108	212	1	37 (L)	5 (L)	5 (L)	360°	-44.31

Inspection of the interaction of design P1 with the spike epitope reveals strong electrostatic contacts
between the S-protein residues Tyr351, Asn354, and Arg355 (see Figure 1c) all of which have been
deemed important for ACE2 binding[1]. The strongest contacts with the three epitope residues are
established by five antibody residues spanning both the heavy and light chains (shown in yellow in Figure
2b). Spike Tyr351 interacts with Ser64 in the HV* domain, Asn354 interacts with Glu38 and Tyr114 in
HV* and KV* domains respectively, while spike Arg355 interacts with Asn37 and Asp110 of HV* and
HCDR3 domains, respectively, in the stable spike-antibody complex (see Figure 2c).

Figure 2. (a) Pairwise sequence similarity percentages between the members of the six parts that were used to
construct the top five prototype variable regions with the lowest Rosetta binding energies with the viral spike
epitope. **(b)** The amino acid sequence of prototype design P1 with the different domain parts highlighted in different
colors. Spike epitope binding residues are highlighted in yellow. **(c)** Structural view of the strongest epitope-
prototype variable region interactions for P1. They imply strong electrostatic capture of three epitope residues by
five variable region residues spanning both heavy (H) and light (K) chains.

We next applied Rosetta-based *in silico* affinity maturation (see Methods) for each one of the top five

prototype designs shown in Table 1 to further enhance the non-covalent binding between the antibody

variable domains and the SARS-CoV-2 spike RBD. This computationally mimics the process of somatic

hypermutation leading to eventual affinity maturation of antibodies in B cells. This procedure identified a

total of 124 unique variable designs by introducing mutations in the five prototypes (see Figure 3a). We

retained the top 60 designs which achieved both an improvement in the Rosetta binding energy over their

respective prototype sequences and also further stabilization (i.e., lower overall Rosetta energy) of the

spike-antibody complex (see upper right quadrant of Figure 3a). On average, upon affinity maturation, the

Rosetta binding energy was improved by ~7.35 kcal/mol and the Rosetta overall energy was improved by

~140 kcal/mol. Supplementary S2 lists the starting prototype design (i.e., P1, P2, P3, P4 or P5) and below

it these 60 affinity matured designs (labeled as P5.D1, P5.D2, etc). On average, there were 4.5 mutations

(Supp. info. S3) between computational affinity matured and prototype variable region designs.

Unsurprisingly, P1 (with 14 affinity matured positions) gave rise to the most retained affinity matured

sequences (i.e. 30 sequences) whereas P4 (with eight affinity matured positions) the fewest (i.e., two

sequences).

Figure 3. (a) The 60 out of 124 Rosetta-affinity matured designs that improve upon both energy criteria fall in the
top right quadrant. **(b)** Plot of the Rosetta binding energy vs. H-score for the 60 retained affinity-matured sequences.
The dotted line connects the designs on the Pareto optimum curve between these two design objectives. The two
best-binding affinity matured designs (emerging from P5) – P5.D1 and P5.D2 are drawn in red whereas the two
most human designs (emerging from P3) – P3.D2 and P3.D3 in green. Design P3.D1 with a balance between both
criteria is shown in blue.
156

We then assessed the departure of the 60 designed variable regions from fully-human antibody sequences

using H-Score[3]. H-score is defined as the sum of the minimum edit distance between all possible 9-mer

fragments in the designed variable region from a library of all 9-mer sequences observed in human

antibodies[20]. The smaller the value of H-score is, the closer the designed variable region to be fully human

and thus less likely to trigger an immunogenic response. Figure 3b illustrates the trade-off between the

Rosetta binding energy vs. H-score for the top 60 affinity matured variable region designs. Note that we

calculated the H-score for the human CR3022[17] (anti-SARS-CoV-1 antibody) to be 667 which in the same

range as our most human designs. We selected five designs that were on the Pareto optimum curve shown

in Figure 3b. The Pareto optimum curve is defined as the collection of designs for which no other design

exists that can simultaneously improve upon both criteria (i.e., Rosetta binding energy and H-score) at the

same time. Designs P5.D1 and P5.D2 shown in red (in Fig. 3b) have the lowest Rosetta binding energies

whereas P3.D2 and P3.D3 shown in green correspond to the ones with the lowest H-scores. Design P3.D1

balances Rosetta binding energy with low H-score. The lowest Rosetta energy designs (P5.D1, P5.D2),

irrespective of H-score, would be relevant in ELISA-based *in vitro* detection assays whereas the lowest

H-score designs (P3.D2, P3.D3) may offer the highest potential as neutralizing antibodies.

Figure 4 shows the sequence alignment of these five selected affinity matured sequences (i.e., P5.D1,

P5.D2, P3.D1, P3.D2, and P3.D3). Shown in cyan are the positions with different residues and in yellow

the positions with different but similar residues. A total of 137 out of 218 residues are conserved among

all designs. Table 2 lists the most important (strongest) contacts with the spike protein as informed by an

in silico alanine scanning (Supp. info. S4) on the spike-binding residues of the variable region designs. In

essence, the alanine scanning analysis identifies the loss in binding energy that is incurred upon mutating

each residue (one at a time) to alanine.

```
1_P5.D1:  EVQLQESGPGLVKPSETLSLTCAVYGGSFSGYWWSWIRQPPGKGLEWIGQINHSGATMYN       60
2_P5.D2:  EVQLQESGPGLVKPSETLSLTCAVYGGSFSGYWWSWIRQPPGKGLEWIGMINHSGATMYN       60
3_P3.D1:  QVQLQQWGAGLLKPSETLSLTCAVYGGSFSGYFWCWIRQPLGKGLEWIGEINASGWTNNN       60
4_P3.D2:  QVQLQQWGAGLLKPSETLSLTCAVYGGSFSGYFWCWIRQPLGKGLEWIGEINHSGWTNNN       60
5_P3.D3:  QVQLQQWGAGLLKPSETLSLTCAVYGGSFSGYFWCWIRQPLGKGLEWIGEINHSGNTNNN       60

1_P5.D1:  PSLKSRITMSVDTSKNQFYLKLSSVTAADTAVYYCATLTGDLDAFDVWGQGTLVTVSSYE       120
2_P5.D2:  PSLKSRITMSVDTSKNQFYLKLSSVTAADTAVYYCATLTGDLDAFDVWGQGTLVTVSSYE       120
3_P3.D1:  PSLKSRATISVDTSKNQFSLKLSSVTAADTAVYYCAR-----HYFDYWGKGTTVTVSSIQ       115
4_P3.D2:  PSLKSRATISVDTSKNQFSLKLSSVTAADTAVYYCAR-----HYFDYWGKGTTVTVSSIQ       115
5_P3.D3:  PSLKSRATISVDTSKNQFSLKLSSVTAADTAVYYCAR-----HYFDYWGKGTTVTVSSIQ       115

1_P5.D1:  LTQ-PLSVSVALGQAARITCGGNNLGYKSVHWYQQKPGQAPVLVIYRDNNRPSGIPERFS       179
2_P5.D2:  LTQ-PLSVSVALGQAARITCGGNNLGYKSVHWYQQKPGQAPVLVIYRDNNRPSGIPERFS       179
3_P3.D1:  MTQSPSSLSASVGDRVTITCRASQGIRNDLGWYQQKPGKAPKRLIYAASSLQSGVPSRFS       175
4_P3.D2:  MTQSPSSLSASVGDRVTITCRASQGIRNDLGWYQQKPGKAPKRLIYAASSLQSGVPSRFS       175
5_P3.D3:  MTQSPSSLSASVGDRVTITCRASQGIRNDLGWYQQKPGKAPKRLIYAASSLQSGVPSRFS       175

1_P5.D1:  GSNSGNTATLTISRAQAGDEADYYCQSYDGSNVVFGSGTKVTVL  223
2_P5.D2:  GSNSGNTATLTISRAQAGDEADYYCQSYDGSNVVFGSGTKVTVL  223
3_P3.D1:  GSGSGTEFTLTISSLQPEDFATYYCQQFS-SNLTFGGGTKVEIK  218
4_P3.D2:  GSGSGTEFTLTISSLQPEDFATYYCQQFS-SNLTFGGGTKVEIK  218
5_P3.D3:  GSGSGTEFTLTISSLQPEDFATYYCQQFS-SNLTFGGGTKVEIK  218
```

Figure 4. Sequence alignment of top five pareto optimal affinity matured sequences. Variable positions are highlighted in cyan and variable though similar in residue type are highlighted in yellow.

Table 2. List of important contacts between the spike protein epitope residues and residues of each of the selected affinity matured designs. For each contact, the loss in binding energy upon mutation of antibody residue from the interface to alanine is tabulated. The corresponding interacting spike residue is also shown.

Matured antibody Design id	Interface residue from antibody	Interacting spike residue	Change in binding energy upon mutation to alanine (kcal/mol)	Corresponding variable region
P5.D1	G109	R346	2.42	LCDR3
	M66	W353	1.14	HV*
	I56	C488	0.90	HV*
	W38	A352	0.89	HV*
	G63	F490	0.30	HV*
P5.D2	G109	R346	2.48	LCDR3
	M66	A348	1.01	HV*
	N57	W353	0.05	HV*
	T77	C488	0.12	HV*
	S59	R457	0.02	HV*
P3.D1	W64	A352	2.30	HV*
	N57	R355	0.65	HV*
	F107	T345	0.59	KCDR3
	S108	G446	0.44	KCDR3
	S29	E340	0.14	HV*
P3.D2	W64	A352, S349	2.52	HV*
	G36	E340	0.84	HV*
	F107	T345	0.77	KCDR3
	N57	N354	0.76	HV*
	F38	F347, A348	0.43	HV*
P3.D3	G36	C336, E340	1.65	HV*
	N57	N354	1.28	HV*
	F107	T345	0.69	KCDR3

N64	N354	0.38	HV*
S29	E340	0.14	HV*

Finally, to gain further insight into the biophysics of interactions, an all-atom Molecular Dynamics (MD)

simulation of the best binding design P5.D1 in complex with the RBD of the SARS-CoV-2 spike protein

was performed. Preliminary results for a 60ns trajectory counted an average of 4.7 hydrogen bonds (st.

dev: 1.8) present at the antibody-antigen interface (Supp. Info. S5 for further details). This is quite

encouraging, as in an earlier study[30], MD simulation of the ACE2 receptor in complex with the spike

protein RBD reported an average of only 2.7 hydrogen bonds at the interface. This implies that this design

has the potential to competitively bind the RBD of the SARS-CoV-2 spike protein thus sequestering it

from ACE2. In addition, we calculated the Rosetta binding energy between the human CR3022[17] (anti-

SARS-CoV-1 antibody) and the SARS-CoV-2 spike protein RBD using complex structure (PDB-

id:6W41) to be -48.83 kcal/mol and both our best binding designs P5.D1 and P5.D2 have better binding

energies (~12 kcal/mol more negative) than CR3022. It is important to stress that our designs rely on the

accuracy of the Rosetta energy function to recapitulate experimental affinities and that running

experimental binding assays are needed to confirm or refute these findings.

Summary

In summary, the goal of this computational analysis was to assess the range of possible antibody designs

that can affect binding with the viral spike protein by occupying the residues involved in ACE2 binding.

We reported on *de novo* prototype variable regions targeting the seven-residue epitope in the spike and

their (computationally) affinity matured sequences with the lowest Rosetta binding energies. Designs

were rank ordered not only in terms of their Rosetta binding energy but also their humanness score metric

H-score. We reported complete amino acid sequences for all 60 affinity matured designs as well as the

five prototype sequences and V*, CDR3, and J* parts used. Importantly, we would like to note that high

affinities of designed antibodies, as modeled using the Rosetta binding energy function, need not

necessarily translate to therapeutic effectiveness. The exact mechanisms underlying the therapeutic action

of monoclonal antibodies are quite complex and often only partially understood. Nevertheless, we hope

that this analysis and data will contribute an important piece to help inform the discovery of effective

neutralizing mAb against SARS-CoV-2. We remain poised to help with any follow up computational

tasks.

Methods

Antibody design in OptMAVEn-2.0

The initial antibody variable domain sequences were predicted using *de novo* antibody design software

tool, OptMAVEn-2.0[2]. Using an interatomic clash-cutoff of 1.25 Å, 173 antigen poses were sampled, and

each of which yielded a successful (not necessarily unique) antibody design targeted at the seven most

solvent accessible ACE2-binding residues of SARS-CoV-2 spike RBD.

Prior to identifying antibody sequences complimentary to the epitopes, OptMAVEn-2.0 first minimizes

the z-coordinate of the epitopes, with their collective centroid set at origin, to allow the *de novo* designed

antibody regions (see Supp. Info. S1 for link to entire MAPs fragment library) to bind from the bottom.

Next, an ensemble of starting antigen poses is generated by a combination of discrete rotations (about the

z-axis) and translations (in x, y, and z) – each of which are subsequently passed into the antibody design

step. We started out with 3234 such antigen poses for the SARS-CoV-2 spike protein with the epitopes

occupying the most negative z-axis coordinates.

Affinity maturation design in Rosetta

The affinity maturation protocol consisted of an initial refinement of the complex by RosettaDock[31]

followed by three iterations of backbone perturbation using RosettaBackrub[32], interface design using

RosettaDesign[33] and rotamer repacking of the complex using a Monte Carlo based simulated annealing

algorithm[34,35]. During the Rosetta affinity maturation, only amino acids in the variable region within 5 Å

from any epitope residue are allowed to mutate. At the end of these affinity maturation iterations, the

entire spike-antibody complex energy was minimized and the Rosetta binding energy was calculated

using the *InterfaceAnalyzer*[29] application. The entire protocol was implemented in RosettaScripts[36] using

the REF2015 energy function[28] (see Supp. info. S6 for further details). This computational protocol was

executed for 8,000 affinity matured sequence-design cycles. The top five variable region designs which

show strong interaction energy scores with the viral spike and low immunogenicity (high H-scores) were

further investigated to glean insight on the biophysics of interactions at the residue level.

Acknowledgements

We acknowledge funding sources: US National Science Foundation (NSF) grant CBET1703274 and

Center for Bioenergy Innovation of US Department of Energy (DE-SC0018420).

References

1.   Chowdhury, R. & Maranas, C. D. Biophysical characterization of the SARS-CoV2 spike protein
binding with the ACE2 receptor explains increased COVID-19 pathogenesis. *bioRxiv*
2020.03.30.015891 (2020) doi:10.1101/2020.03.30.015891.

2.   Chowdhury, R., Allan, M. F. & Maranas, C. D. OptMAVEn-2.0: De novo Design of Variable
Antibody Regions Against Targeted Antigen Epitopes. *Antibodies* **7**, 23 (2018).

3.   Lazar, G. A., Desjarlais, J. R., Jacinto, J., Karki, S. & Hammond, P. W. A molecular immunology
approach to antibody humanization and functional optimization. *Mol. Immunol.* **44**, 1986–1998
(2007).

4.   Yan, R. *et al.* Structural basis for the recognition of the SARS-CoV-2 by full-length human ACE2.
Science **367**, 1444–1448 (2020).

5.   Shang, J. *et al.* Structure of mouse coronavirus spike protein complexed with receptor reveals
mechanism for viral entry. *PLoS Pathog.* **16**, e1008392 (2020).

6.   Lan, J. *et al.* Crystal structure of the 2019-nCoV spike receptor-binding domain bound with the
ACE2 receptor. *bioRxiv* 1–20 (2020) doi:10.1101/2020.02.19.956235.

7.   Shang, J. *et al.* Structural basis of receptor recognition by SARS-CoV-2. *Nature* 1–8 (2020)
doi:10.1038/s41586-020-2179-y.

8.   Petherick, A. Developing antibody tests for SARS-CoV-2. *Lancet* **395**, 1101–1102 (2020).

9.   Jiang, S., Hillyer, C. & Du, L. Neutralizing Antibodies against SARS-CoV-2 and Other Human
Coronaviruses. *Trends Immunol.* (2020) doi:10.1016/j.it.2020.03.007.

10.   Saha, R. & Prasad, B. V. In silico approach for designing of a multi-epitope based vaccine against
novel Coronavirus (SARS-COV-2). *bioRxiv* 2020.03.31.017459 (2020)
doi:10.1101/2020.03.31.017459.

11.   Srivastava, S. *et al.* Structural basis to design multi-epitope vaccines against Novel Coronavirus 19
(COVID19) infection, the ongoing pandemic emergency: an in silico approach. *bioRxiv*
2020.04.01.019299 (2020) doi:10.1101/2020.04.01.019299.

12.   Shajahan, A., Supekar, N. T., Gleinich, A. S. & Azadi, P. Deducing the N- and O- glycosylation
profile of the spike protein of novel coronavirus SARS-CoV-2. *bioRxiv* 2020.04.01.020966 (2020)
doi:10.1101/2020.04.01.020966.

13.   Wu, Y. *et al.* Fully human single-domain antibodies against SARS-CoV-2. *bioRxiv*
2020.03.30.015990 (2020) doi:10.1101/2020.03.30.015990.

14.   Wang, C. *et al.* A human monoclonal 1 antibody blocking SARS-CoV-2 infection. *bioRxiv*

294   2020.03.11.987958 (2020) doi:10.1101/2020.03.11.987958.

295   15.   Poh, C. M. *et al.* Potent neutralizing antibodies in the sera of convalescent COVID-19 patients are

296   directed against conserved linear epitopes on the SARS-CoV-2 spike protein. *bioRxiv*

297   2020.03.30.015461 (2020) doi:10.1101/2020.03.30.015461.

298   16.   Ju, B. *et al.* Potent human neutralizing antibodies elicited by SARS-CoV-2 infection. *bioRxiv*

299   2020.03.21.990770 (2020) doi:10.1101/2020.03.21.990770.

300   17.   Yuan, M. *et al.* A highly conserved cryptic epitope in the receptor-binding domains of SARS-

301   CoV-2 and SARS-CoV. *Science (80-.).* eabb7269 (2020) doi:10.1126/science.abb7269.

302   18.   ter Meulen, J. *et al.* Human Monoclonal Antibody Combination against SARS Coronavirus:

303   Synergy and Coverage of Escape Mutants. *PLoS Med.* **3**, e237 (2006).

304   19.   Heinig, M. & Frishman, D. STRIDE: a web server for secondary structure assignment from known

305   atomic coordinates of proteins. *Nucleic Acids Res.* **32**, W500-2 (2004).

306   20.   Li, T., Pantazes, R. J. & Maranas, C. D. OptMAVEn – A New Framework for the de novo Design

307   of Antibody Variable Region Models Targeting Specific Antigen Epitopes. *PLoS One* **9**, e105954

308   (2014).

309   21.   Entzminger, K. C. *et al.* De novo design of antibody complementarity determining regions binding

310   a FLAG tetra-peptide. *Sci. Rep.* **7**, (2017).

311   22.   Poosarla, V. G. *et al.* Computational de novo design of antibodies binding to a peptide with high

312   affinity. *Biotechnol. Bioeng.* **114**, 1331–1342 (2017).

313   23.   Tiller, K. E. *et al.* Facile affinity maturation of antibody variable domains using natural diversity

314   mutagenesis. *Front. Immunol.* **8**, 986 (2017).

315   24.   Pantazes, R. J. & Maranas, C. D. MAPs: A database of modular antibody parts for predicting

316   tertiary structures and designing affinity matured antibodies. *BMC Bioinformatics* **14**, 168 (2013).

317   25.   Lefranc, M.-P. IMGT, the international ImMunoGeneTics database. *Nucleic Acids Res.* **31**, 307–

318   310 (2003).

319   26.   IBM (2017) IBM ILOG CPLEX 12.7 User's Manual (IBM ILOG CPLEX Division, Incline

320   Village, NV).1.

321   27.   Lloyd, S. P. Least Squares Quantization in PCM. *IEEE Trans. Inf. Theory* **28**, 129–137 (1982).

322   28.   Alford, R. F. *et al.* The Rosetta All-Atom Energy Function for Macromolecular Modeling and

323   Design. *J. Chem. Theory Comput.* **13**, 3031–3048 (2017).

324   29.   Benjamin Stranges, P. & Kuhlman, B. A comparison of successful and failed protein interface

325   designs highlights the challenges of designing buried hydrogen bonds. *Protein Sci.* **22**, 74–82

326   (2013).

327   30.   Lupala, C. *et al.* Computational simulations reveal the binding dynamics between human ACE2

328   and the receptor binding domain of SARS-CoV-2 spike protein. *bioRxiv* 2020.03.24.005561

329   (2020) doi:10.1101/2020.03.24.005561.

330 31. Gray, J. J. *et al.* Protein-protein docking with simultaneous optimization of rigid-body

331   displacement and side-chain conformations. *J. Mol. Biol.* **331**, 281–299 (2003).

332 32. Smith, C. A. & Kortemme, T. Backrub-Like Backbone Simulation Recapitulates Natural Protein

333   Conformational Variability and Improves Mutant Side-Chain Prediction. *J. Mol. Biol.* **380**, 742–

334   756 (2008).

335 33. Kuhlman, B. *et al.* Design of a Novel Globular Protein Fold with Atomic-Level Accuracy. *Science*

336   *(80-.).* **302**, 1364–1368 (2003).

337 34. Leaver-Fay, A., Kuhlman, B. & Snoeyink, J. An adaptive dynamic programming algorithm for the

338   side chain placement problem. *Pac. Symp. Biocomput.* 16–27 (2005).

339 35. Leaver-Fay, A., Snoeyink, J. & Kuhlman, B. On-the-fly rotamer pair energy evaluation in protein

340   design. in *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial*

341   *Intelligence and Lecture Notes in Bioinformatics)* vol. 4983 LNBI 343–354 (Springer, Berlin,

342   Heidelberg, 2008).

343 36. Fleishman, S. J. *et al.* RosettaScripts: A Scripting Language Interface to the Rosetta

344   Macromolecular Modeling Suite. *PLoS One* **6**, e20161 (2011).

345