A new tool for 3D segmentation of computed tomography data：

Drishti Paint and its applications

Yuzhi Hu[1,2], Ajay Limaye[3], Jing Lu[4]*

[1]Department of Applied Mathematics, Research School of Physics, Australian

National University, Canberra, ACT, Australia 2601

[2]Research School of Earth Sciences, Australian National University, Canberra, ACT,

Australia 2601

[3]National Computational Infrastructure, Building 143, Corner of Ward Road and

Garran Road, Ward Rd, Canberra, ACT, Australia 2601

[4]Institute of Vertebrate Paleontology and Paleoanthropology, Chinese Academy of

Sciences, Beijing, China 100044

*Corresponding author: lujing@ivpp.ac.cn

Abstract

Computational tomography is more and more widely used in many fields for its non-

destructive and high-resolution in detecting internal structures of the samples. 3D

segmentation of computed tomography data, which sheds light into internal features

of target objects, is increasingly gaining in importance. However, how to efficiently

and precisely reconstruct computed tomography data and better represent the data

remains a hassle. Here, using a set of scan data of a fossil fish as a case study, we

present a new release of open-source volume exploration, rendering, and 3D

segmentation software, *Drishti* v2.6.6, and its protocol for performing 3D

segmentation and other advanced applications. We provide new toolsets and

workflow to segment computed tomography data thus benefit the scientific

community with more accurate and precise digital reconstruction, 3D modelling and

3D printing results. Our procedure is widely applicable not only in palaeontology, but

also in biological, medical, and industrial researches, and can be used as a framework

to segment computed tomography and other forms of volumetric data from any

research field.

Keywords   3D Segmentation, *Drishti Paint*, computed tomography data,

volumetric data

32   1 Introduction

Nowadays, computed tomography (CT) is widely used in many fields, such as

medicine, science, industry and education [1-5]. To have a better understanding of the

data generated from CT, 3D scientific visualization becomes more and more

important for researchers to obtain better insights [6-9]. For the last four decades, 3D

scientific visualization field have been developed with new ways to visualize and

analyse data more accurately [10-19]. Two techniques have emerged to provide

different visualizations: surface rendering, the method of interpreting data-sets by

generating a set of polygons that represent the wanted feature; and volume rendering

[10], a more direct way for the reconstruction of 3D structures, which represents 3D

objects as a collection of cube-like building blocks called voxels, or volume elements.

However, the importance of scientific visualization software along with their

functionality was underestimated by the community due to lack of public exposure

and communications between multidiscipline.

3D segmentation, segmenting the internal structures in sequences of images, is

a key tool for investigating and understanding the internal structures of target objects

[6, 20-22]. The 3D segmenting methods rely on thresholding, edge detection,

clustering, or region growing to group pixels based on brightness, colour, or texture

[21]. Compared with researches carried out in the image processing field, more

requirements have to be met towards building and developing applications which

require the use of more efficient and effective techniques to save time and resources.

Drishti, as an open-source volume exploration, rendering and 3D

segmentation software [23], is well-known for its superb visualization outcomes [6,

24-26]. Here we present the latest released *Drishti* v2.6.6, and the last developed

module *Drishti Paint* v2.6.6, as a new toolset for 3D segmentation (2D and 3D

painters) of volumetric data (i.e. a 3D volume produced by a group of 2D images of a

slice or section of the scanned object acquired by X-ray imaging and Magnetic

resonance imaging, etc.) by using the CT scan data of a fossil fish as case study. We

also suggest protocols for how to perform 3D segmentation using *Drishti Paint* v2.6.6

efficiently and precisely. New features in *Drishti*, such as mesh generation and

simplification, allow 3D printing, model simulation, etc.) are also covered in this

study.

2 Materials and Methods

2.1 Materials

The material used in this study, a Devonian unnamed placoderm fish (ANU

V244) from Burrinjuck, near Canberra, south-eastern Australia, is held at Australian

National University [3], Canberra, Australia. The whole specimen and the separated

right anterior upper toothplate were scanned in 2015 [27, 28] at CT Lab, ANU [7]

using a HeliScan MicroCT system with 1.2mm aluminium/ 0.35mm stainless steel for

the whole specimen and 2mm aluminium filters for the upper toothplate to yield sharp

images [18, 29] at a resolution of 21μm and 2μm respectively. CT data was

reconstructed using an in-house software called *Mango*

(https://physics.anu.edu.au/appmaths/capabilities/mango.php).

2.2 Methods

The CT datasets were explored and rendered using *Drishti* v2.6.6. The

individual data sets were read at low resolution, and contrast was incremented with

the help of histograms and slides were filtered. The information thus generated is

written as *.pvl.nc for saved files (i.e. processed volume format) or *. xml (i.e.

Extensible Markup Language format) for saved projects. The scan data was

demonstrated by a protocol for segmenting the 3D volumetric data using *Drishti Paint*

v2.6.6. The right check complex was segmented out of the whole dataset. The internal

structure under the region-of-interest of its right anterior upper toothplate has been

segmented as another case study.

3 Results and discussions

3D segmentation is often hampered by the time-intensive nature of extracting

information from samples, the complexity of preparing fossils digitally, and the need

for hardware. Here we highlight the workflow and key features of the *Paint* module

for *Drishti* and the general applications of *Drishti* using CT data of an Early Devonian

placoderm fish [27, 28] as an example. A suggested workflow of segmenting

volumetric data in *Drishti* v2.6.6 is presented here (figure 1), which can generate good

results in terms of segmentation, rendering and surface mesh generation outputs. Our

protocols can be used as a baseline or starting point to practice accordingly in order to

obtain an ideal result for a specified dataset. To help with a better understanding into

other aspects of *Drishti*, we also provide additional information about *Drishti*, such as

installation instructions, a summary of all *Drishti*-supported import formats,

additional learning resources and background of the program (see supplemental

information).

Three modules, *Drishti import*, *Drishti render* and *Drishti paint*, have their

capacities and features, and can be used in combination with each other to ensure an

accurate and precise segmentation along with volume rendering to help with visualize

a region-of-interest and solve scientific problems. *Drishti Paint* uses a combination of

discontinuity detection based and similarity detection-based image segmentation

approaches. There are two modes in *Drishti Paint* v2.6.6, Graph Cut and Curve,

which are designed specifically to consider 2D slices in volumetric data or 3D volume

directly.

Two transformations in mathematical morphology (i.e. erosion and dilation)

were implemented in *Drishti Paint* and we used a combination of these two

transformations with 3D Freeform Painter to help with a faster segmentation process.

The right cheek complex has been segmented from the original CT dataset of the

whole specimen (figure 2). The internal canal networks of a selected region-of-

interest on the right anterior upper toothplate have been segmented from the original

dataset of the toothplate (figure 3). Processed data then exported as separate volumes

by extracting the tagged volume after tagging the regions of interests using the

tagging function. Both segmentations were carried out in 16-bits full resolution in

alignment with their source data and used type 2 gradient thresholding with values

thresholding to select the range of the histogram for segmenting.

We suggest that these two transforms are more useful when using clean and

high contract dataset as a risk of changing the morphology of the input datasets by

doing multiple transformations at once. Multiple-thresholding (i.e. use both values

and gradient thresholding) in *Drishti Paint* v2.6.6 is very effective for volume

segmentation and usually is the first step towards segmenting a volume (figures 2d

and 3b), however, it is also very sensible to noise and intensity in homogeneities. In

this case, to segment the internal canal networks of the selected region is tightly

related to the selected thresholds, and any small changes in the thresholds values can

lead to different segmented results, which is one of the key factors need to set up

specifically and choose carefully per dataset (figures 2 and 3, supplementary figures 3

and 4).

The segmented right cheek unit has also been extracted as surface meshes

(figure 4). The surface mesh data of the right cheek unit went through different stages

of simplification process (figure 4b-d) to produce good quality surface models with

relatively small file size allowing quicker physical analysing (e.g. finite element

analysis) and 3D printing. Mesh simplification results show that the number of

vertices affects the presentation of the information and the detection of details (figure

3). When more triangles have been decimated, fewer details from data are detected

(i.e. loss of information) resulting in a reduction in file size which allows easier

sharing of the digital 3D model [20] or uploading the model to open data repository

for educating the public [21] without giving out details that are still under

investigation. By looking at the amount of details lost/preserved pointed by the arrows

(figure 4), we recommend a mesh smoothing factor of 2 and 50% decimation based

on our segmented cheek 3D model (figure 4d) as it halves the data size but still

preserves most of the information. 3D models can then be used to generate 3D

printouts [30] or 3D portable documents [31] to test a previous hypothesis or help

with functional morphology investigations.

4 Conclusions

Here we provide a new tool and workflow to segment volumetric data thus

benefit the scientific community with more accurate and precise digital reconstruction,

3D modelling and 3D printing in *Drishti*. This procedure can be used as a framework

to segment computed tomography and other forms of volumetric data and widely

applicable in biological, medical and earth science researches. Our work will surely

fuel further multiple cross-discipline collaborations between scientific visualization

and many other fields.

Data accessibility

3D surface mesh data of the segmented right cheek complex with different levels of

simplification, and a movie shows the segmented internal canal networks of the

toothplate are available from the fig share repository:

https://figshare.com/s/244e5f407d331a39b402.

Drishti v2.6.6 is available from: https://github.com/nci/Drishti

Authors' Contributions

J.L. and Y.H. designed the study. Y.H., J.L., A.L. performed the research and drafted

the manuscript. Y.H. and J.L. prepared the figures. A.L. developed *Drishti* v2.6.6. All

authors revised the manuscript. Y.H. and A.L. contributed equally.

Competing Interests

The authors declare no competing interests.

Funding

This research was funded by the Strategic Priority Research Program of the Chinese

Academy of Sciences (Grant No. XDB26000000) and the National Natural Science

Foundation of China (41872023). Y.H. was supported by a Postgraduate Research

Scholarship at the Research School of Physics, Australian National University. The

development of *Drishti* is supported by National Computational Infrastructure,

Australian National University. CT scans and 3D printing are supported by ANU CT

Lab.

Acknowledgements

We acknowledge Tim Senden and Gavin Young for their continuous support and help

with proofreading. We thank the CT Lab at the Australian National University for CT

Scanning.

References

1.   Kingston AM, Myers GR, Latham SJ, Recur B, Li H, Sheppard AP. 2018

Space-filling X-ray source trajectories for efficient scanning in large-angle cone-beam

computed tomography. *IEEE Transactions on Computational Imaging* **4**, 447-458.

(doi: 10.1109/TCI.2018.2841202)

2.   Zhu M, Ahlberg PE, Pan Z, Zhu Y, Qiao T, Zhao W, et al. 2016 A Silurian

maxillate placoderm illuminates jaw evolution. *Science* **354**, 334-336. (doi:

10.1126/science.aah3764)

3.   Geier B, Sogin EM, Michellod D, Janda M, Kompauer M, Spengler B, et al.

2020 Spatial metabolomics of in situ host-microbe interactions at the micrometre

scale. *Nat. microbiol.* **5**: 498-510. (doi: 10.1038/s41564-019-0664-6)

4.   O'Rourke JC, Smyth L, Webb AL, Valter K. 2020 How Can We Show You, If

You Can't See It? Trialing the Use of an Interactive Three Dimensional Micro CT

Model in Medical Education. *Anat. Sci. Educ.* **13**: 206-217.(doi: 10.1002/ase.1890)

5.   Taylor GJ, Hall SA, Gren JA, Baird E. 2020 Exploring the visual world of

fossilized and modern fungus gnat eyes (Diptera: Keroplatidae) with X-ray

microtomography. *J. R. Soc. Interface* **17**:20190750. (doi: 10.1098/rsif.2019.0750).

6.   Lautenschlager S. 2016 Reconstructing the past: Methods and techniques for

the digital restoration of fossils. *R. Soc. open sci.* **3**:160342. (doi:

10.1098/rsos.160342).

7.   Davies TG, Rahman IA, Lautenschlager S, Cunningham JA, Asher RJ, Barrett

PM, et al. 2017 Open data and digital morphology. Proc. R. Soc. B. 284: 20170194.

(doi: 10.1098/rspb.2017.0194).

8.   Hoffmann R, Lemanis RE, Falkenberg J, Schneider S, Wesendonk H, Zachow

S, et al. 2018 Integrating 2D and 3D shell morphology to disentangle the

palaeobiology of ammonoids: a virtual approach. *Palaeontology* **61**:89-104.

(doi:10.1111/pala.12328)

9.   Semple TL, Peakall R, Tatarnic NJ. 2019 A comprehensive and user friendly

framework for 3D data visualisation in invertebrates and other organisms. *J.*

Morphol. **280**:223-231. (doi: 10.1002/jmor.20938)

10.   Drebin RA, Carpenter L, Hanrahan P. 1988 Volume rendering. *ACM Siggraph*

Computer Graphics **22**:65-74.

11.   Upson C, Faulhaber T, Kamins D, Laidlaw D, Schlegel D, Vroom J, et al.

1989 The application visualization system: A computational environment for

scientific visualization. *IEEE Computer Graphics and Applications* **9**:30-42. (doi:

10.1109/38.31462)

12.   Westover L. 1990 Footprint evaluation for volume rendering. *Proceedings of*

the 17th annual conference on Computer graphics and interactive techniques. Dallas,

TX, USA: Association for Computing Machinery; 1990. p.367–376. (doi:

10.1145/97879.97919)

13.   Hall PM, Watt AH. 1991 Rapid volume rendering using a boundary-fill

guided ray cast algorithm. In: *Patrikalakis N.M. (eds) Scientific Visualization of*

Physical Phenomena. Springer, Tokyo. p. 235-249. (doi: 10.1007/978-4-431-68159-

5_13)

14.   Cabral B, Cam N, Foran J.1994 Accelerated volume rendering and

tomographic reconstruction using texture mapping hardware. In: *Proceedings of the*

1994 symposium on Volume visualization. p. 91-98. (doi: 10.1145/197938.197972)

15.   Lacroute P, Levoy M. 1994 Fast volume rendering using a shear-warp

factorization of the viewing transformation. In: *Proceedings of the 21st annual*

conference on Computer graphics and interactive techniques. p.451-458. (doi:

10.1145/192161.192283)

16.   Manssour IH, Furuie SS, Olabarriaga SD, Freitas CM. 2002 Visualizing inner

structures in multimodal volume data. In: *Proceedings XV Brazilian Symposium on*

Computer Graphics and Image Processing IEEE. (doi:

10.1109/SIBGRA.2002.1167123)

17.   Johnson C. 2004 Top scientific visualization research problems. *IEEE*

Computer Graphics and Applications **24**:13-17. (doi:10.1109/MCG.2004.20)

18.   Latham SJ, Varslot T, Sheppard A.2008 Automated registration for

augmenting micro-CT 3D images. *Anziam Journal* **50**:534-548.(doi:

10.21914/anziamj.v50i0.1389)

19.   Brodlie KW, Carpenter LA, Earnshaw RA, Gallop JR, Hubbold RJ, Mumford

AM, et al. 2012 Scientific visualization: techniques and applications. Springer

Science & Business Media.

20.   Lakare S, Kaufman A. 2000 3D segmentation techniques for medical volumes.

Center for Visual Computing, Department of Computer Science, State University of

New York. 2000:59-68.

21.   Kaur D, Kaur Y. 2014 Various image segmentation techniques: a review.

International Journal of Computer Science and Mobile Computing **3**:809-814.

22.   Carvalho LE, Sobieranski AC, von Wangenheim A. 2018 3D Segmentation

Algorithms for Computerized Tomographic Imaging: a Systematic Literature Review.

Journal of digital imaging **31**:799-850. (doi: 10.1007/s10278-018-0101-z)

23.   Limaye A. 2012 Drishti: a volume exploration and presentation tool. In:

Developments in X-ray Tomography VIII 2012 Oct 17 (Vol. 8506, p. 85060X).

International Society for Optics and Photonics. (doi: 10.1117/12.935640.short?SSO=1)

24.   Cunningham JA, Rahman IA, Lautenschlager S, Rayfield EJ, Donoghue PCJ.

2014 A virtual world of paleontology. *Trends in Ecology & Evolution* **29**:347-357.

(doi: 10.1016/j.tree.2014.04.004)

25.   Johnson EH, Carter AM. 2019 Defossilization: A Review of 3D Printing in

Experimental Paleontology. *Frontiers in Ecology and Evolution* **7**: 430. (doi:

10.3389/fevo.2019.00430)

26.   Sutton M, Rahman I, Garwood R. 2017 VIRTUAL PALEONTOLOGY—AN

OVERVIEW. *The Paleontological Society Papers* **22**:1-20. (doi:10.1017/scs.2017.5)

27.   Hu Y-Z, Lu J, Young GC. 2017 New findings in a 400 million-year-old

Devonian placoderm shed light on jaw structure and function in basal gnathostomes.

Scientific Reports **7**:1-12. (doi:10.1038/s41598-017-07674-y)

28.   Hu Y-Z, Young GC, Burrow C, Zhu Y-A, Lu J. 2019 High resolution XCT

scanning reveals complex morphology of gnathal elements in an Early Devonian

arthrodire. *Palaeoworld* **28**:525-534. (doi:10.1016/j.palwor.2018.12.003)

29.   Myers GR, Kingston AM, Varslot TK, Turner ML, Sheppard AP. 2011

Dynamic tomography with a priori information. *Appl. Opt.* **50**:3685-3690. (doi:

10.1364/AO.50.003685)

30.   Hu Y-Z, Young GC, Lu J. 2019 The Upper Devonian tetrapodomorph

Gogonasus andrewsae from Western Australia: Reconstruction of the shoulder girdle

and opercular series using X-ray Micro-Computed Tomography. *Palaeoworld*

28:535-542. (doi:10.1016/j.palwor.2019.07.008)

31.   Tesařová M, Heude E, Comai G, Zikmund T, Kaucká M, Adameyko I, et al.

2019 An interactive and intuitive visualisation method for X-ray computed

tomography data of biological samples in 3D Portable Document Format. *Scientific*

Reports **9**:1-8. (doi:10.1038/s41598-019-51180-2)

32.   Cignoni P, Callieri M, Corsini M, Dellepiane M, Ganovelli F, Ranzuglia G.

2008 Meshlab: an open-source mesh processing tool. In: *Eurographics Italian chapter*

conference 2008. p. 129-136.

Figure legends

Figure 1. The general workflow for operating *Drishti* v2.6.6. Data formats in this

figure are only abbreviations, for detailed information please refer to Supplementary

Table 1.

Figure 2. Extract a 3D virtual volumetric model in *Drishti*. A. Raw data of the right

cheek complex of a Devonian placoderm fish (ANU V244) in *Drishti Import* v2.6.6.

B. V244 in *Drishti Render* v2.6.6 in 16 bits full resolution (lateral view). C. Selected

region-of-interest for segmentation. D. Selected region-of-interest in *Drishti Paint*

v2.6.6 for segment the right cheek complex. E. Segmented right cheek complex in

Drishti Render v2.6.6 (external view).

Figure 3. Segmenting internal structures of a toothplate (an Early Devonian

placoderm fish, ANU V244) in *Drishti Paint*. A. Right upper anterior toothplate in

Drishti Render v2.6.6 (external view). B. Raw data of the right upper anterior

toothplate in *Drishti Paint* v2.6.6. The white-boxed area shows the selected region-of-

interest on the right upper anterior toothplate for segmentation. C. Segmented outer

surface of the region-of-interest on the right upper anterior toothplate and its internal

canal networks underneath in *Drishti Render* v2.6.6. D. Segmented internal canal

networks with a close-focus in *Drishti Render* v2.6.6.

Figure 4. 3D surface meshes of the extracted right cheek unit (Devonian placoderm

fish, ANU V244) with attached perichondral-ossified cartilages, showing the

differences of vertex count and file sizes after different mesh simplification

applications. The Vertex count was calculated in MeshLab v1.3.4 [32].

Volumetric data

supporting 13 different
volumetric data formats

Drishti Import
converts the source data
into the format (. pvl.nc);
sub-volume; data cropping;
data smoothing; data dilution;
8 or16 bits data output

.pvl.nc in 8 bits or 16 bits   .pvl.nc in 8 bits or 16 bits

Drishti Paint
2D & 3D segmentation;
data cropping; sub-volume;
mesh generation
& smoothing

Drishti Render
visualization,
mesh generation
& simplification,
volume reslicing
& smoothing,
illuminations

.ply

.pvl.nc
.xml
.ply

standard/stereo images and movies; 3D printing;
physical & digital reconstructions; visualization projects

(a)

(b)

20mm

Select the Histogram
& Region of Interest

(c)

5mm

(d)

Segmentation

(e)

5mm

(a)

(b)

| F | 0 | 🔍 | 🔍 | 495 | ⛶ |

| F | 0 | 🔍 | 🔍 | 213 | ⛶ |

| F | 0 | 🔍 | 🔍 | 148 | ⛶ |

box(0 0 0 : 486 425 849 : 487 426 850) mb(167.237 @ 1)
LOD(1) Vol(487 426 850)

Extract two volumes- surface of the teeth
& internal cannal networks

Extract one volume-
internal cannal networks

(c)

(d)

(a)

20um

(b)

vertices_799612
faces_159928400
size: 40.4 MB

40um

Original mesh

(c)

20um

(d)

vertices_159899
faces_31985600
size: 8.08 MB

40um

mesh smoothing 2
decimate 80% of triangles
aggressive 1
color smoothing 50

(e)

20um

(f)

vertices_399791
faces_79964200
size: 20.2 MB

40um

mesh smoothing 2
decimate 50% of triangles
aggressive 1
color smoothing 50

(g)

20um

(h)

vertices_399791
faces_79964201
size: 20.2 MB

40um

mesh smoothing 5
decimate 50% of triangles
aggressive 1
color smoothing 50