A separable neural code in monkey IT enables perfect CAPTCHA decoding

Harish Katti & S. P. Arun

Centre for Neuroscience, Indian Institute of Science, Bangalore, 560012, India

*Correspondence to:

Harish Katti (harish2006@gmail.com) & SP Arun (sparun@iisc.ac.in)

ABSTRACT

Reading distorted letters is easy for us but so challenging for machine vision that it is used on websites as CAPTCHAs (Completely Automated Public Turing test to tell Computers and Humans Apart). How does our brain solve this problem? One solution to have neurons invariant to letter distortions but selective for letter combinations. Another is for neurons to separately encode letter distortions and combinations. Here, we provide evidence for the latter using neural recordings in the monkey inferior temporal cortex. Neurons encoded letter distortions as a product of letter and distortion tuning, and letter combinations as a sum of letters. These rules were sufficient for perfect CAPTCHA decoding, and present in neural networks trained for letter recognition. Thus, a separable neural code enables efficient reading.

INTRODUCTION

Reading relies upon our ability to recognize letters and words despite variations in appearance. These include variations due to size, position or viewpoint, but also arising from writing style, font and distortions of the writing surface. Yet we do solve this task so much better than computers that it is exploited on websites as CAPTCHAs (Completely Automated Public Turing test to tell Computers and Humans Apart) (von Ahn et al., 2003). How does the brain solve this problem? A widely held view is that neurons in higher visual areas are invariant to letter distortions and selective for specific combinations of letters (Dehaene et al., 2005). In this scenario, neural responses to letter combinations cannot be understood using single letters because of the presence of emergent features (Figure 1). This view is supported by observations that neurons in the monkey inferior temporal (IT) cortex, an area critical for recognition (Tanaka, 1996; DiCarlo et al., 2012), contain neurons invariant to size, position and viewpoint (Ito et al., 1995; Zoccolan et al., 2007; Ratan Murty and Arun, 2015), but selective for feature combinations (Kobatake and Tanaka, 1994; Baker et al., 2002; Brincat and Connor, 2004; Yamane et al., 2008). This selectivity for feature combinations increases with discrimination learning (Baker et al., 2002; Dehaene et al., 2005).

An alternate possibility is that neurons may encode letters and their distortions as well as longer strings of letters in a separable fashion (Figure 1). By separable encoding we mean that responses to letter distortions or combinations can be understood in terms of their constituent letter or distortion selectivity. Evidence for this account comes from recent studies showing that IT neurons separably encode object identity and invariant attributes (Ratan Murty and Arun, 2018) and respond to objects as a sum of their parts (Zoccolan et al., 2005; Sripati and Olson, 2010; Pramod and

Arun, 2018). This separability increases with reading expertise in humans (Agrawal et

al., 2019).

However, these possibilities have not been investigated in IT neurons by

recording their responses to distorted letter strings, which are unlike natural objects in

that their constituent units (letters) are spatially separated and can undergo a wide

variety of natural as well as stylistic distortions. Thus, it is not clear if the pre-existing

neural machinery in naïve monkey IT itself suffices to solve CAPTCHAs.

To this end, we recorded neural responses in IT cortex of monkeys trained to

fixate distorted letter strings but with no explicit training to discriminate or recognize

these stimuli. We found that IT neurons encode distorted letter strings according to

two systematic rules: letter distortions were encoded as a product of letter and

distortion tuning, and letter combinations were encoded as a sum of single letters. To

confirm that these rules are indeed sufficient to solve CAPTCHAs, we instantiated

these rules in artificial neurons and asked whether these neural responses can be

used to decode CAPTCHAs. Finally, we show that these rules naturally emerge in

later layers of deep neural networks trained for letter and word recognition.

RESULTS

We recorded from 139 IT neurons across two monkeys while they performed a fixation task. We tested each neuron with a fixed set of stimuli which comprised CAPTCHA-like strings that were 2-6 letters long, each of which was presented at four distortions (Figure S1). The stimuli also included single letters presented at each retinal location and at each distortion. This design enabled us to answer two fundamental questions regarding the separability of neural responses (Figure 1). First, can neural responses to letters and strings across distortions be predicted using their shape selectivity and distortion selectivity (Figure 1A)? Second, can neural responses to strings be explained using their responses to single letters (Figure 1B)?

=

A **Responses to distorted strings**　　　**B** **Responses to letter combinations**

	Distortion D_1	Distortion D_2
String S_1	y7Ka	Y7Ka
String S_2	Tyad	Tyad

	y	7
y	yy	y7
7	7y	77

Separable response　$R_{12} = f(S_1, D_2)$　　　Separable response　$R(y7Ka) = f(R_y, R_7, R_K, R_a)$

Inseparable response　$R_{12} \neq f(S_1, D_2)$　　　Inseparable response　$R(y7Ka) \neq f(R_y, R_7, R_K, R_a)$

Figure 1. Separability of distortions and letter combinations.
(A) We define the neural response to distorted strings as separable if the response to a particular string at a particular distortion can be understood as a function of the string tuning and distortion tuning, and inseparable otherwise.
(B) We define the neural response to letter combinations as separable if the response to a particular letter combination (e.g. y7Ka) can be understood as a function of the individual letter responses (e.g. y, 7, K and a separately), and inseparable otherwise. Inseparable responses could occur for instance if neurons were selective to specific combinations of letters.

Do IT neurons show separability of letter shape, position and distortion?

We first characterized neural responses to single letters across retinal positions and distortions. The responses of an example IT neuron to each letter at every retinal position are shown in Figure 2A (the full set of responses to all stimuli can be seen in Figure S2). It can be seen that this neuron preserves its letter shape preference across retinal locations (Figure 2A, *top row*), and its location preference across letters (Figure 2A, *left column*) – suggesting that its response to letter and position is separable. Likewise, the response matrix for this neuron for each letter at every distortion is shown in Figure 2B – here too it can be seen that the neuron prefers some distortions over others and some letters over others. To quantitatively establish whether neural responses to shape x position x distortion combinations are separable, we compared two models in which the predicted response is either a sum or product of shape, position and distortion tuning. To avoid overfitting, we trained each model on odd-numbered trials, and evaluated its correlation on the even-numbered trials. We compared these model predictions with an estimate of neural reliability (split-half correlation; see Methods). The multiplicative model yielded excellent predictions of the neural response ($r = 0.36$, p < 0.0005; Figure 2C) that were close to the split-half correlation for this neuron ($r_{sh} = 0.38$, p < 0.0005). Thus, this neuron shows a response that is separable into shape, retinal position and distortion components.

Although this particular neuron shows separable responses, overall CAPTCHA decoding by the entire population might be driven by small numbers of neurons with highly consistent but inseparable responses. This would produce systematically worse model fits for neurons with high response consistency. We observed no such trend upon plotting model correlation against response reliability (Figure 2D). Rather, model correlations were close to the response reliability, indicating that they explained nearly

105   all the explainable variance in the responses. We observed equivalent fits for the

106   additive and multiplicative models for every level of response reliability (Figure 2E).

107
Figure 2. IT neurons show separable encoding of distorted letters.
(A) Colormap showing the firing rate of an example IT neuron to undistorted single
characters at each retinal location. Darker colors indicate higher firing rate.
Above: Responses across retinal positions for each character. *Left:* Responses
to characters at each retinal location.
(B) Colormap showing responses to each character at each of four distortions at a
specific retinal location (location 4, 0.83° contralateral to fixation).
(C) Observed responses (on even-numbered trials) to distorted letters across retinal
locations plotted against predictions from the multiplicative model for the same
neuron obtained from odd-numbered trials. Responses are normalized to the
maximum firing rate.
(D) Model correlation for the multiplicative (*red*) and additive (*green*) models plotted
against response reliability across all 139 visual neurons.
(E) Progression of model correlation with response reliability for each quartile of
response variability for the multiplicative (*red*) and additive (*green*) models. Error
bars represent standard error of the mean in each bin. The p-value indicates the
outcome of a paired t-test comparing the additive and multiplicative model

correlations for neurons belonging to that quartile. All quartiles showed no
significant difference between the two models.
(F) Colormap of responses to 6-grams at every distortion for the example neuron.
(G) Observed responses to 6-grams across distortions (from even-numbered trials)
plotted against the multiplicative model predictions for the example neuron
(trained on odd-numbered trials). Responses are normalized to the maximum
firing rate.
(H) Model correlation for the multiplicative (*red*) and additive (*green*) models plotted
against response reliability across all 139 visual neurons.
(I) Progression of model correlation with response reliability for each quartile of
response variability for the multiplicative (*red*) and additive (*green*) models. Error
bars represent standard error of the mean in each bin. Asterisks indicate
statistical significance (** is $p < 0.005$) of a paired t-test comparing model
correlations of the additive and multiplicative models for neurons belonging to that
quartile. All other quartiles showed no significant difference.
140

Do IT neurons show separability of string and distortions?

Next we asked whether neural responses to longer strings across distortions

are separable i.e. can be understood in terms of string and distortion selectivity. The

responses of the same example neuron to 6-grams at multiple distortions is shown in

Figure 2F. For each n-gram length (ranging from 2 to 6), we calculated the tuning for

n-gram string as the average response to a given string (averaged across distortions)

and the tuning for distortion as the response to a given distortion (averaged across

strings) – and asked whether the response to n-gram strings across distortions can be

understood in terms of the product or sum of tuning for n-gram string and tuning for

distortion. The multiplicative model yielded excellent fits to the observed responses (r

= 0.41, $p < 0.0005$; Figure 2G) that were comparable to the response reliability (r_{sh} =

0.37, $p < 0.0005$).

This pattern was true across the population: model fits were close to the

response reliability for every level of reliability (Figure 2H). Furthermore, multiplicative

models yielded slightly better fits than additive models across these consistent

neurons (Figure 2H). This effect was most pronounced for the most reliable quartile of

neurons (average correlations across 34 neurons with reliability > 0.13: r = 0.136 ± 0.1

for multiplicative model, r = 0.129 ± 0.1 for additive model; p = 0.00077, paired t-test,

Figure 2I).

We conclude that IT neurons show separable encoding of distorted letter strings

in that the response to distorted strings is a product of shape and distortion tuning.

Do IT neurons show separability of responses to letter combinations?

Next we set out to characterize neural responses to letter combinations. The

responses of an example IT neuron to n-grams varying in length from 2 to 6 letters is

shown in Figure 3A. It can be seen that this neuron responded strongly to strings that

contained the trigram "gsT" – but it also responds strongly to the letter "g" (Figure S2)

suggesting that responses to longer strings can be explained using single letter

responses. To quantitatively assess this possibility, we asked whether the response

of each neuron to n-grams of each given length can be explained as a position-

weighted sum of multiplicatively reconstructed responses to single letters (see

Methods). The position-weighting accounts for the contribution of a given letter

depending on its position within the full string. This model yielded excellent fits for the

example neuron (r = 0.41, p < 0.0005; Figure 3B) that were equivalent to the response

reliability (r_{sh} = 0.38, p < 0.0005). This pattern of results were true for the entire

population: model fits approached or exceeded response reliability across neurons for

every level of reliability (Figure 3C).

Figure 3: Neural responses to ngrams are compositional

(A) Response of the example neuron (same as Figure 1) to all undistorted ngrams in the experiment.

(B) Observed responses to all n-grams (on even-numbered trials) plotted against the predictions of the single letter model (trained on odd-numbered trials) for the example neuron.

(C) Model correlation for each neuron plotted against the response reliability across neurons. Average model correlations for each 20th percentile of neurons with positive response reliability are shown in red, with error bars depicting s.e.m across each such group.

(D) Average estimated summation weights for each retinal location for different ngram lengths across all 139 neurons.

The above analysis shows that neural responses to letter strings is well approximated by a sum of single letter responses, but neurons might still show systematic model errors indicative of selectivity for letter combinations. To explore this

possibility, we asked whether bigrams that have high model error show systematically

larger errors for longer strings that contain these bigrams. This revealed no such

systematic difference (Figure S3).

Next we examined the estimated summation weights at each retinal location.

For each neuron, we normalized its response to the maximum firing rate across all

stimuli, and estimated summation weights for each retinal location and each n-gram

length (across all n-grams). The average summation weights are shown in Figure 3D.

For all n-gram lengths, we observed larger weights of letters close to fixation compared

to more peripheral locations. This is consistent with the well-known bias of IT neuron

receptive fields towards fixation (Op De Beeck and Vogels, 2000). Moreover, the

relationship between n-gram responses and the sum of single letter responses

followed a characteristic 1/n progression (Figure S4). This is consistent with the

divisive normalization observed previously in IT neurons (Zoccolan et al., 2005).

We conclude that IT neurons show separable encoding of letter strings whereby

the responses to strings can be predicted using a sum of single letter responses.

Is separability sufficient for CAPTCHA decoding?

The above analyses show that IT neurons encode distorted letter strings as a

product of shape and distortion tuning, and encode letter combinations as a sum of

single letters. However they do not establish that CAPTCHAs can be solved using

these responses, or that they can be solved if responses are separable.

To address these issues, we first asked whether CAPTCHAs can be solved

using the responses of IT neurons to the distorted letter strings. To this end, we trained

a 9-way linear classifier to decode character identity at every retinal location (see

Methods). Since each retinal location could have one of 8 possible letters or be a blank

space, chance performance for this decoding scheme is 1/9 or 11%. We used 5-fold cross-validation to avoid overfitting. As expected, decoding accuracy using the recorded population of neurons was well above chance (average accuracy across 6 locations = 29%).

The above result shows that we can decode letter identities successfully using a small population of neurons, but it is not clear how this decoding accuracy would scale with a larger population of neurons. It is also not clear whether the decoding accuracy is being driven by neurons with separable or inseparable responses. To resolve this issue, we asked whether CAPTCHAs can be decoded by a population of synthetic neurons with separable encoding.

We created 1,000 synthetic neurons that had either broad or sharp tuning for shape, position and distortion (see Methods; Figure 4A). We calculated neural responses to shape-position-distortion combinations either using an additive or multiplicative function. Their responses to longer strings was taken simply as a sum of their responses to single letters, and finally we included divisive normalization whereby the net response to longer strings is divided by the string length. To provide a tough challenge of the CAPTCHA solving ability of this neural population, we created a large set of ngrams (n = 17,920) of varying string lengths, which could even contain spaces between letters (see Methods). We then asked whether these separable neural responses could be used to decode character identity at each location as before. In this manner, we created several groups of neurons: broad tuning with multiplicative/additive integration with/without normalization, sharp tuning with multiplicative/additive integration with/without normalization and mixed tuning with multiplicative/additive integration with/without normalization.

The resulting character decoding accuracy for each of these artificial neuron

populations is summarized in Figure 4B. We observed several interesting patterns.

First, decoding accuracy was always better when shape and distortion tuning were

multiplicatively combined. This is because multiplying two signals enables efficient

decoding compared to adding them, as reported previously (Ratan Murty and Arun,

2018). Second, decoding was better when neural responses were divisively

normalized than when they were not. This is because normalization avoids excessively

large responses to increasing content in the visual field. Since ngrams of different

lengths can have the same character at a given location (e.g.; "7yKa " and "Ty7Kad"

both have "y" in the second position), longer ngrams will automatically have higher

firing rates in the absence of divisive normalisation and will result in two different read-

outs for the same character label. Third, decoding is worse when neurons with sharp

tuning are subjected to divisive normalization, which happens because sharply tuned

neurons respond to only a few retinal locations and divisive normalization results in

excessive scaling by the total string length. Finally, and most importantly, we obtained

near-perfect CAPTCHA decoding accuracy with a mixed population of neurons with

sharp and broad tuning.

We conclude that response separability is sufficient to solve CAPTCHAs.

A

1. Selectivity

2. Integration of invariant attributes

Response to shape, position and distortion

Additive: $r_{shape} + r_{position} + r_{distortion}$

Multiplicative: $r_{shape} \times r_{position} \times r_{distortion}$

3. Compositionality

$r(ABCDE) = r_A + r_B + r_C + r_D + r_E$

4. Divisive normalization

$$rd(ABCDE) = \frac{r(ABCDE)}{5}$$

B

Figure 4: Response separability is sufficient for solving CAPTCHAs.

(A) To explore what properties present in a population of separable neurons can solve CAPTCHAs, we first created 1,000 artificial neurons with either sharp or broad tuning for letter, position and distortion. Next, we calculated responses to distorted letters using either additive or multiplicative combination of shape, position and distortion tuning. To calculate responses to letter combinations, we simply added the responses to all the constituent letters. Finally, responses were (or were not) subjected to divisive normalization. We tested the CAPTCHA solving ability of these artificial neurons on a large set of 17,920 ngrams.

(B) To evaluate this neural population for CAPTCHA decoding, we trained a linear classifier to decode which of 9 possible characters (8 letters + 1 blank) were present at each retinal location in each ngram. The resulting average character decoding accuracy is shown for each neural population created with a specific set of choices. Error bars represent standard deviation over 100 iterations of sampling with replacement from a population of 1000 synthetic neurons.

Do neural networks trained for letter recognition show separability?

The above sections demonstrate that IT neurons show separable encoding of letter distortions and combinations. We then asked whether this is indeed an essential property of a visual system that aims to decode words and letters and is not merely restricted to biological neurons. Would separability be equally important even when the visual system was explicitly trained to identity entire words or ngrams as opposed to individual characters?

To address this issue, we analysed the responses of four deep convolutional networks. The first network served as a baseline since it was trained on a standard object classification task and not for letter recognition (denoted as *imagenet*) (Simonyan and Zisserman, 2014). The remaining three of these were trained on a large-scale annotated dataset of about 8 million images generated from strings of variable lengths and different choices of fonts, projective transformations and backgrounds (Jaderberg et al., 2014). The networks were trained with three different goals: (1) identifying the character at each of the 23 possible positions in the input word (denoted as *charnet*); (2) enumerating all ngrams contained within the input word (denoted as *ngramnet*) and (3) whole word identification from a dictionary of 90,000 words (denoted as *dictnet*). In all networks, we selected the penultimate fully connected layer (fc7, with 4096 units) for further analysis, because this layer has the same dimensionality and is subsequently used by the decision layer.

We next analysed the activations of each network to the stimuli used in the neural recordings. As before we fit additive and multiplicative models to predict the response of each unit in the fc7 layer to single letters across retinal positions and distortions. In all four networks, unit activations were better fit by the multiplicative model (Figure 5A). Interestingly, the *imagenet* network yielded lower model fits compared to the networks

trained on word recognition, whereas the *dictnet* model fits were the highest among

all networks. We obtained similar results on analysing n-gram responses across

distortions (Figure 5A). Next we asked whether unit activations to longer ngram strings

in our dataset, can be explained using single letters. Here too we observed a clear

progression, whereby the *imagenet* units yielded the least separability, and *dictnet*

units were most separable (Figure 5B). However in all cases, model correlations are

well below 1, suggesting that neural responses are not fully separable despite training.

Such emergent compositionality has been observed in high-performing deep networks

trained for natural scene categorisation (Zhou et al., 2014).

Since the network trained on complete word recognition (*dictnet*) shows the

greatest separability, we wondered whether its performance on letter recognition

would also be the best across all networks. To investigate this issue, we compared the

performance of each network on 9-way decoding of character decoding at each retinal

location as before on the responses to our original ngram set (50 unique ngrams x 4

distortions). As predicted the performance of *dictnet* was better than the other

networks (decoding accuracy: 74%, 92%, 93% and 95% for *imagenet, charnet,*

ngramnet and *dictnet*; Figure 5C).

Thus, deep networks trained for word recognition tasks develop separable neural

representations for distortions and letter combinations. We speculate further that

imposing separability as a constraint during learning can lead to better character

decoding performance.

330
Figure 5: Compositionality in CNNs trained for text decoding
(A) *Left:* Model correlations for additive and multiplicative models for shape x position
x distortion for each neural network. *Right:* Model correlations for additive and
multiplicative models for shape x distortion for each neural network. Error bars
represent s.e.m across neurons. Asterisks represent statistical significance
calculated using a paired t-test on the additive and multiplicative model
correlations across all 4096 units (**** is p < 0.00005).
(B) Average model correlations for the linear model that predicts n-gram responses
as a weighted sum of single letter responses. Error bars represent s.e.m. across
neurons.
(C) Character decoding accuracy across the stimulus set used in the neural recording
experiment for each neural network. Error bars represent s.e.m over character
decoding accuracy over 6 retinal locations.
344

Can IT neurons decode both easy and hard CAPTCHAs?

The above results were based on testing IT neurons with distorted letter strings

with spatially separate letters and relatively simple distortions. However we also

included a small set of more challenging CAPTCHAs which contain overlapping letters

or cluttered backgrounds (Figure 6A). We predicted that letter decoding should also

be possible in these hard CAPTCHAs, albeit at a weaker level.

To assess this possibility, we took linear classifiers to perform 9-way character

decoding at each retinal location as before, and asked whether they could decode

letter identity from the hard CAPTCHA strings. Decoding accuracy was weaker for the

hard CAPTCHAs but still remained significantly above chance (Figure 6A). Thus,

CAPTCHAs that are hard for computer algorithms are also challenging for IT neurons.

Since hard CAPTCHAs are harder to decode, we wondered whether their

responses are less separable with respect to distortions and string responses. To

investigate this issue, we took the 8 six-letter strings that were common to both the

easy and hard CAPTCHAs (with 4 distortions each), and asked whether these

responses were separable in terms of distortions and ngram responses. We first fit a

shape x distortion multiplicative model to the responses to the 8 grams across 4

distortions. To compare the model performance, we divided the model correlation of

each cell by its split-half correlation for each set of stimuli. Both easy and hard

CAPTCHAs were equally separable (Figure 6B). Next we asked whether the average

response of each ngram (on even-numbered trials) can be predicted using a weighted

sum of the single letter responses (with weights learned from responses on odd-

numbered trials), and normalized the model correlation as before. The resulting

normalized model correlations   are shown in Figure 6C. As predicted, model

correlations for hard CAPTCHAs were significantly smaller than for easy CAPTCHAs.

We conclude that hard CAPTCHAs are less separable than easy CAPTCHAs,

which explains why they are harder to decode by the IT neural population.

Figure 6. Decoding and separability for easy and hard CAPTCHAs by IT neurons.

A) Average decoding accuracy (of 9 characters across all retinal locations) for classifiers trained on the easy CAPTCHAs (left) and tested on the hard CAPTCHA strings (right). Error bars represent s.e.m across decoding accuracy across all ngrams. Asterisks above each bar represent the statistical significance of the decoding accuracy compared to chance decoding which is 1/9 = 11% (*** is $p < 0.0005$, based on calculating the binomial probability of exceeding this number of correct labels out of a total of 8 strings x 6 retinal locations x 4 distortions = 192 responses given a binomial distribution with N = 192, p = 1/9 = 11.1%). Asterisks straddling the two bars represent the statistical significance of the difference in decoding accuracy (** is $p < 0.005$, rank-sum test for medians).

B) Normalized model correlation for the shape x distortion multiplicative model, for the easy and hard CAPTCHA strings. Error bars represent s.e.m across neurons. For each neuron, we calculated the correlation between observed responses on even-numbered trials and the model predictions based on odd-numbered trials, and divided by the split-half correlation to obtain a normalized measure. Asterisks above each bar indicate whether the median normalized correlation is different from zero (*** is $p < 0.0005$, based on a sign-rank test across 139 neurons). Although the hard CAPTCHA strings show greater separability, this difference was not statistically significant ($p = 0.2$, signed-rank test across 139 neurons).

C) Normalized model correlations for the ngram responses predicted by single letter responses. Normalized correlations for hard CAPTCHA strings were not significantly different from zero ($p = 0.09$, signed-rank test), and this separability was significantly smaller than for the easy CAPTCHA strings (* is $p < 0.05$, signed-rank test across 139 neurons). All other conventions are as in B.

GENERAL DISCUSSION

Here we characterized the neural representation of distorted letters in IT neurons. We found two systematic encoding rules: neural responses to distorted letters was a product of distortion and shape tuning, whereas responses to letter combinations was a sum of single letter responses. These two rules were sufficient for perfect CAPTCHA solving and emerged in neural networks trained for letter but not object recognition. Below we discuss these findings in relation to the literature.

Our main finding is that there is a systematic separable code for distorted letter strings in monkey IT neurons, consisting of two rules. The first rule was that neural responses to distorted letters is approximated well by a product of distortion and shape tuning. This is consistent with recent observations that object identity and invariant attributes combine multiplicatively in IT neurons (Ratan Murty and Arun, 2018). By contrast, we have found the neural response to multiple objects to be a weighted sum of the constituent letters. This is consistent with several previous studies showing linear summation in IT neurons for objects (Zoccolan et al., 2005) as well as their parts (Sripati and Olson, 2010; Pramod and Arun, 2018). We speculate that IT neurons switch between multiplicative and additive integration of features depending on feature similarity.

Our findings are however discordant with a recent preprint showing that ngram responses are not predictable from letters in IT (Rajalingham et al., 2019). We speculate that the lower separability in that study could be due to more posterior recording sites (compared to ours which were from anterior ventral IT), different response noise distributions (multi-unit activity in that study vs single units in ours), and shorter presentation times (100 ms in their study with no inter-stimulus interval vs 200 ms on/off duration in ours), apart from of course stimulus and animal

differences. We speculate that there is a gradual progression in separability as well

as invariance along the ventral pathway that enables efficient object recognition

(DiCarlo et al., 2012).

Our results have important implications for how exactly letter and word

representations change with reading. First, we note that perfect CAPTCHA decoding

using a perfectly separable neural population (Figure 4), but encoding in IT neurons

was not perfectly separable (e.g. Figure 3C). Based on this we propose that reading

could increase the overall separability of word representations. This was indeed

observed recently in the anterior LOC (Agrawal et al., 2019), the homolog of IT cortex

in humans. Whether this separability comes with exposure to single letters or to letter

strings would be interesting to study. Second, we note that familiarity has widespread

effects on IT neurons (Woloszyn and Sheinberg, 2012; Meyer et al., 2014; Srihasam

et al., 2014) and on human visual cortex (Agrawal et al., 2019; Gomez et al., 2019).

We speculate that reading could lead to enhanced discrimination as letters become

familiar, as has been observed recently (Agrawal et al., 2019).

Our results have important implications for machine vision. They indicate the

specific representational rules that need to be embodied in order to solve

CAPTCHAs. Indeed, there are deep network design and training principles that

implement one or few of the following attributes namely compositionality, sparseness

and divisive normalization. An attempt has been made to bring in compositionality

(Stone et al., 2017) into deep networks albeit maintaining a veridical mapping

between sensory input and internal representation. Randomly deleting connections

during training iterations, also called drop-out, as well as non-linearities such as

rectified linear units (ReLUs) can bring in sparseness (Hinton et al., 2012; Warde-

Farley et al., 2013). Finally, averaging CNN filter responses in a spatial neighborhood

(mean-pool) is similar to divisive normalization for broadly tuned neurons and

retaining only the highest response in a local neighborhood (max-pool) can

approximate aggregation of highly sparse neurons (Nagi et al., 2011). We propose

that explicitly encoding separability could lead to vastly improved performance of

deep neural networks on distorted letter recognition.

METHODS

All experiments were performed in accordance with a protocol approved by the

Institutional Animal Ethics Committee of the Indian Institute of Science and by the

Committee for the Purpose of Control and Supervision of Experiments on Animals,

Government of India. Most experimental procedures were common to previously

reported studies in our lab and are only briefly summarized below.

Neurophysiology. We recorded from the left IT cortex of two macaque monkeys

(*macaca radiata*, *Ka* & *Sa*, both male, aged 7 years) using standard neurophysiological

procedures. Recording sites were located in the anterior ventral portion of IT.

Extracellular wideband signals were recorded at 40 KHz using 24-channel laminar

electrodes (Uprobes with 100 µm inter-contact spacing, Plexon Inc). We manually

sorted these signals offline into distinct clusters using spike-sorting software

(OfflineSorter, Plexon Inc). We selected 139 visually responsive units for further

analysis.

Stimuli. We created a set of 432 unique stimuli. We selected eight letters which

included lower- and upper-case letters and numbers ('a', 'd', 'g', 's', 'T', 'y', '7', 'K').

Each single letter was rendered at six retinal locations 0.8° apart, three adjacent

positions being ipsilateral and three contralateral. Presenting each of the unique letter

shapes at six unique spatial locations resulting in a total of 48 possible single letter

placements. These positions were chosen to match the letter locations in the longer

ngram strings described in the next section. Letters were rendered in the Times New

Roman font and subtended 0.8° visually on an average.

These letters were also used to create 10 bigrams, 10 trigrams all the way to

10 6-grams (Figure S1), resulting in a total of 50 unique ngrams. Thus, there were a

total of 98 undistorted single letters and ngrams.

Next we applied three different distortions drawn from commercial captcha

algorithms to each of these 98 letter or ngram placements. In the first, we applied a

local fish-eye lens distortion that expands and translates pixels in x and y directions

(https://in.mathworks.com/matlabcentral/fileexchange/22573-pinch-and-spherize-

filter). We applied a second distortion over and above the first distortion which involved

randomly rotations (uniformly chosen from -15 to 15 degrees) of every character in the

string. The third distortion was added over and above the second distortion and

affected the global shape of the string. It involved bending the entire ngram about one

of two different spline curves. All distortions were implemented using custom scripts

written in MATLAB. Since each stimulus was presented in its undistorted form and

three distortions, this resulted in a total of 98 x 4 = 392 stimuli.

In addition to these distortions, we also included hard CAPTCHA variants used

by Google, Yahoo and other web services (Figure 6). We selected a subset of eight

6-gram strings ('7Kadgs', 'KadgsT', 'Ty7Kad', 'Tyadgs', 'gsTy7K', 'sTy7Ka', 'y7Kadg',

'yadgsT') which were distorted in four additional ways: (1) rotating the letters in place

so that they touched each other; (2) retaining only the letter outlines; (3) adding a fish-

eye transformation, rotating letters in place and adding a background line grid and (4)

adding a fish-eye transformation, rotating letters in place (uniformly at random

between 15 to -15 degrees) and adding a wavy stroke cutting through the letters.

These distortions can be seen in Figure 6. These distortions are known to be

challenging for computer vision algorithms and are used for human-vs-robot

authentication tests (von Ahn et al., 2003) in commercial web services from Yahoo®

(touching solid letter and letter outline hard CAPTCHAS) and Google® (hard

CAPTCHAS with strike-through and background grid).

Behavioural task. Each animal was trained to fixate a series of 8 images presented at

fixation in return for a juice reward. Each image was shown for 200 ms with an inter-

stimulus interval of 200 ms. Thus, each trial lasted 3.2 s. Trials contained either single

letters or ngrams, randomly ordered with the constraint that the same stimulus should

not repeat in a given trial. The 432 stimuli were organised into 54 blocks of 8 stimuli

each and we generated four unique sets of these 54 trials using pseudo-random

assignment of letter or ngram stimuli. During recordings, a set of 54 trials were

completed (corresponding to one repetition of the entire stimulus set) before starting

another set of 54 trials. Ngrams with even number of letters (2-, 4- & 6-grams) were

centered on fixation whereas those with odd number of letters (3- & 5-grams) were

positioned such that the contralateral side had one extra letter.

Calculation of response reliability. We obtained a measure of response reliability for

each neuron, which represents an upper bound on model performance. To do so, we

calculated the average firing rate of the neuron across all stimuli under consideration

across the odd-numbered and even-numbered trials separately. We then calculated

the split-half correlation between these two estimates, and applied a Spearman-Brown

correction given by $r_c = 2r_{sh}/(1+r_{sh})$ where r_{sh} is the split-half correlation. This corrected

split-half correlation represents the correlation expected between two full sets of neural

responses. Since the models reported are trained on the full data, this corrected split-

half correlation is an upper bound on model performance.

Model fits for letter x position x distortion encoding (Figure 2C-E). We tested each

neuron with 8 letters presented at 6 retinal locations and 4 distortions. We used the

firing rate of each neuron (calculated in a 50-200 ms window after stimulus onset) to

these 192 stimuli to fit two models. To do so, we first calculated the average shape

tuning for the neuron by averaging its response (on odd-numbered trials) to every

shape across retinal positions and distortions. We proceeded likewise to calculate the

average retinal position tuning and average distortion tuning. For the additive model,

the response to shape i, position j and distortion k is given by $R(s_i, p_j, d_k) = S_i + P_j +$

D_k, where S_i is the average shape tuning for shape i, P_j is the average position tuning

for position j and D_k is the average distortion tuning for distortion k. Likewise, for the

multiplicative model, the response is given by $R(s_i, p_j, d_k) = S_i * P_j * D_k$. Both model

predictions were scaled and shifted to be in the same range as the observed response.

To evaluate the model fit, we calculated the correlation between the model predictions

(trained on odd-numbered trials) and the firing rate of the neuron on even-numbered

trials. For Figure 2E, we excluded 37 neurons with high response variability that

caused them to have a negative split-half correlation.

Model fits for ngram x distortion encoding (Figure 2G-I). We tested each neuron with

10 ngrams at each of four distortions for each length from 2 to 6 letters. We used the

firing rate of each neuron calculated as before to the 40 ngrams of each specific length

to fit two models. As before we calculated the average ngram tuning and average

distortion tuning. For the additive model, the response to shape i, distortion k is given

by $R(s_i, d_k) = S_i + D_k$, where S_i is the average shape tuning for shape i and D_k is the

average distortion tuning for distortion k. Likewise, for the multiplicative model, the

response is given by $R(s_i, d_k) = S_i * D_k$. Both model predictions were scaled and

shifted to be in the same range as the observed response. As before, we trained the

model on the odd-numbered trials and calculated its correlation with the firing rate on

even-numbered trials. For Figure 2I, we excluded 31 neurons with high response

variability that caused them to have a negative split-half correlation.

Model fits for letter combinations (Figure 3). Each neuron was tested with 10 strings

at 4 distortions for each ngram length (n = 2, 3, 4, 5, 6). We used the firing rate of each

neuron calculated as before to the 40 ngrams of a given ngram length to fit a model

based on single letters. For each ngram (e.g. "yadgsT"), we compiled the

corresponding predicted single letter responses from the multiplicative model (shape

x distortion x location) (e.g. to "y" at location 1, "a" at location 2, etc). Using the raw

firing rates to single letters yielded qualitatively similar results. We compiled the ngram

responses (for each length) and the corresponding single letter responses into the

matrices **y** and **x** respectively where **y** is a 40 x 1 vector containing the responses to

the 40 ngrams of that length in odd reps, **x** is a 40 x n matrix containing the

corresponding single letter responses at each of n retinal locations together with a

constant term. We then modelled the full set of 200 unique ngram responses as a

single equation **Y = Xb**, where **Y** is a concatenation of all **y** ngram response vectors at

each length (n = 2, 3, 4, 5, 6) and the letter response matrix **X** was a 200 x 25 matrix

in in which corresponding single letter responses at each length were entered into a

separate set of columns. In other words, the matrix **X** had a total of 25 columns made

up of 3 columns for bigram letter responses (two weights & one constant), 4 columns

for trigrams (three weights and one constant), and so on. The regression weight vector

b is a vector of 25 unknowns representing the weights of each location within the

ngram for each particular ngram length. To avoid overfitting since these models have

relatively few parameters compared to observations, model predictions were

calculated using cross-validation: we trained the model on 80% of the data (i.e. 160

stimuli) and calculated its prediction on the held-out 40 stimuli. These predictions were

compared with the observed responses for the plots in Figure 3B & 3C. For Figure 3D,

since the goal was to analyse the summation weights, we fit the model only once on

the full set of 40 n-gram responses and used these weights for averaging. In addition,

neural responses were normalized by the maximum firing rate across all 40 stimuli, so

that the resulting weights could be averaged across neurons without being unduly

influenced by high firing neurons. For Figure 3C, we excluded 48 neurons with high

response variability that caused them to have a negative split-half correlation.

Decoding character identity for every location in a ngram. For each neural population,

we trained linear classifiers to decode the individual letters at each retinal location.

To simultaneously decode all ngrams, we included a blank as a character so that

there were 9 possible labels (8 letters + 1 blank) at each retinal location. For every

retinal location, a ngram response was assigned the label corresponding to the

character contained at that location. i.e.; the ngram 'adgsT' would have the letter

labels {'blank', 'a', 'd', 'g', 's', 'T'} in retinal locations 1 through 6. The number of

labeled training instances for each label class were balanced to avoid classifier bias.

In this manner, we trained six 9-way linear classifiers for each of the six retinal

locations. Decoding accuracy is reported throughout as the average performance

across these six retinal locations. Since there are 9 classes in the classifier, chance

performance is 1/9 = 11%. Since blank spaces occurred more frequently at eccentric

retinal locations, we calculated the average number of observations across the 8

character classes at a given retinal location and sampled an equal number randomly

from the set of responses corresponding to blank spaces. We did this to prevent the

classifier from learning trivial decision boundaries such as classifying all test

observations as blanks.

Creation of artificial neurons with separable responses (Figure 4A). We created a

population of 1,000 artificial neurons with separable responses as follows. Each

neuron was initialized with tuning for letter, position and distortion that could be sharp

or broad. For broad tuning, we selected responses to be uniformly sampled from 0 to

1 generator (rand function in MATLAB). For sharp tuning, we chose only one

response to equal 1 and the remaining to be 0 according to a sparse matrix generator

(sprand function in MATLAB, with density 1/ngram-length). A given neuron was

chosen as sharply (or broadly) tuned for all three attributes (shape, position,

distortion) since IT neurons are known to have this property (Zhivago and Arun,

2016). For the mixed population of neurons, each neuron was randomly assigned

(with equal probability) to be sharply or broadly tuned. We then calculated the

response of each neuron to distorted letters and strings by applying either additive or

multiplicative. Finally, the response to ngrams was calculated as the sum of the

responses to single letters at the corresponding retinal locations, and divided by the

number of letters (if divisive normalization was selected). In this manner, we created

several groups of artificial neurons: broad tuning with multiplicative/additive

integration with/without normalization, sharp tuning with multiplicative/additive

integration with/without normalization and mixed tuning tuning with

multiplicative/additive integration with/without normalization.

To truly test the capabilities of CAPTCHA decoding for each synthetic neuron

population, we calculated the response of each group to 17,920 ngram stimuli. We

this multi-letter ngram dataset using the same 8 characters as the set of stimuli for

which we recorded responses of biological neurons. For ngram lengths varying from

2 to 6, we first assigned characters without replacement to the same adjacent retinal

locations that were used in our original set of ngrams (e.g.; central-most two locations

for bigrams) We then performed circular-shifts on these strings to obtain strings with

new spatial mappings for adjacent characters. To avoid training biases, we sampled

from the longer string sets to obtain a dataset with 17,920 unique strings and had

3,584 ngrams of every length.

Separability in deep convolutional neural networks. We analyzed four deep

convolutional neural networks for their responses to our stimulus set. The first

network served as a baseline and is a VGG-16 architecture trained for object

classification on the ImageNet dataset (Russakovsky et al., 2015). The VGG-16

model we used had 5 convolution stages that had 3x3 filters and 64, 128, 256, 512,

512 channels respectively. Each convolution was accompanied by 2x2 max-pooling

and RelU (Rectified linear unit) operations.

We also selected three deep networks trained for text decoding using images as

inputs (Jaderberg et al., 2014, 2016). These networks were trained in these studies

using a large-scale dataset created by generating words of lengths up to 23

characters and rendering them using a variety of distortions, fonts, border/shadow

rendering, noise and background information statistics. The common backbone in

these networks have four convolutional layers and two fully connected layers and

RelU are used after each weight layer except for the last one. The convolutional

layers had 64, 128, 256, and 512 square filters with an edge size of 5, 5, 3, and 3.

Convolution stride was 1 and input feature maps were padded to preserve spatial

dimensionality. 2 × 2 max-pooling followed the first, second and third convolutional

layers.

The first network, which we denote as *charnet*, was trained to correctly identity

the letter or number at each retinal location in words of up to length 23. Words were

left aligned in a large-scale training dataset of approximately 8 million words. The

final decision layer for *charnet* comprised of 851 nodes corresponding to character

identities (26 letters + 10 numbers + 1 blank space) for each of 23 locations. The

second network, which we denote as *ngramnet*, was trained to detect the presence

of every ngrams present in a word out of a possible 10,000 ngrams. For example,

when the input image contains the string 'ad', this network will return the ngrams {'a',

'd', 'ad'}. The third network, which we denote as *dictnet*, was trained to identify whole

words from a dictionary of 90,000 possible words. These three models have a

common backbone architecture consisting of input (32x100x1), convolutional

(32x100x64, 16x50x128, 8x25x256, 4x13x512) and fully connected (1x1x4096)

stages, before being connected to either 23 output stages (each 1x1x37) for *charnet*,

a single ngram output stage (1x1x10,000) for *ngramnet* or a single word output stage

(1x1x90,000) for *dictnet*.

Because information in all four networks passes through a fully connected stage

with 4096 nodes before the final classification stage, we selected this layer for our

analyses. To analyze the separability of distorted letter strings in each network, we

generated its activations for the stimuli in our neural recordings, and performed the

exact same analysis as for real neurons.

680
REFERENCES
Agrawal A, Hari KVS, Arun SP (2019) Reading Increases the Compositionality of
Visual Word Representations. Psychol Sci 30:1707–1723.
Baker CI, Behrmann M, Olson CR (2002) Impact of learning on representation of parts
and wholes in monkey inferotemporal cortex. Nat Neurosci 5:1210–1216.
Brincat SL, Connor CE (2004) Underlying principles of visual shape selectivity in
posterior inferotemporal cortex. Nat Neurosci 7:880–886.
Dehaene S, Cohen L, Sigman M, Vinckier F (2005) The neural code for written words:
a proposal. Trends Cogn Sci 9:335–341.
DiCarlo JJ, Zoccolan D, Rust NC (2012) How does the brain solve visual object
recognition? Neuron 73:415–434.
Gomez J, Barnett M, Grill-Spector K (2019) Extensive childhood experience with
Pokémon suggests eccentricity drives organization of visual cortex. Nat Hum
Behav:415729.
Hinton GE, Srivastava N, Krizhevsky A, Sutskever I, Salakhutdinov RR (2012)
Improving neural networks by preventing co-adaptation of feature detectors. :1–
18.
Ito M, Tamura H, Fujita I, Tanaka K (1995) Size and position invariance of neuronal
responses in monkey inferotemporal cortex. J Neurophysiol 73:218–226.
Jaderberg M, Simonyan K, Vedaldi A, Zisserman A (2014) Synthetic Data and Artificial
Neural Networks for Natural Scene Text Recognition. :1–10.
Jaderberg M, Simonyan K, Vedaldi A, Zisserman A (2016) Reading Text in the Wild
with Convolutional Neural Networks. Int J Comput Vis 116:1–20.
Kobatake E, Tanaka K (1994) Neuronal selectivities to complex object features in the
ventral visual pathway of the macaque cerebral cortex. J Neurophysiol 71:856–
867.
Meyer T, Walker C, Cho RY, Olson CR (2014) Image familiarization sharpens
response dynamics of neurons in inferotemporal cortex. Nat Neurosci 17:1388–
1394.
Nagi J, Ducatelle F, Di Caro GA, Cireşan D, Meier U, Giusti A, Nagi F, Schmidhuber
J, Gambardella LM (2011) Max-pooling convolutional neural networks for vision-
based hand gesture recognition. 2011 IEEE Int Conf Signal Image Process Appl
ICSIPA 2011:342–347.
Op De Beeck H, Vogels R (2000) Spatial sensitivity of macaque inferior temporal
neurons. J Comp Neurol 426:505–518.
Pramod RT, Arun SP (2018) Symmetric Objects Become Special in Perception
Because of Generic Computations in Neurons. Psychol Sci 29:95–109.
Rajalingham R, Kar K, Sanghavi S, Dehaene S, DiCarlo JJ (2019) A potential cortical
precursor of visual word form recognition in untrained monkeys. bioRxiv:739649.
Ratan Murty NA, Arun SP (2015) Dynamics of 3D view invariance in monkey
inferotemporal cortex. J Neurophysiol 113:2180–2194.
Ratan Murty NA, Arun SP (2018) Multiplicative mixing of object identity and image
attributes in single inferior temporal neurons. Proc Natl Acad Sci U S A
115:E3276–E3285.
Russakovsky O, Deng J, Su H, Krause J, Satheesh S, Ma S, Huang Z, Karpathy A,
Khosla A, Bernstein M, Berg AC, Fei-Fei L (2015) ImageNet Large Scale Visual
Recognition Challenge. Int J Comput Vis 115:211–252.
Simonyan K, Zisserman A (2014) Very Deep Convolutional Networks for Large-Scale
Image Recognition. Inf Softw Technol 51:769–784.

Srihasam K, Vincent JL, Livingstone MS (2014) Novel domain formation reveals proto-
architecture in inferotemporal cortex. Nat Neurosci:1–10.
Sripati AP, Olson CR (2010) Responses to compound objects in monkey
inferotemporal cortex: the whole is equal to the sum of the discrete parts. J
Neurosci 30:7948–7960.
Stone A, Wang H, Stark M, Liu Y, Phoenix DS, George D (2017) Teaching
compositionality to CNNs. Proc - 30th IEEE Conf Comput Vis Pattern Recognition,
CVPR 2017 2017-Janua:732–741.
Tanaka K (1996) Inferotemporal cortex and object vision. Annu Rev Neurosci 19:109–
139.
von Ahn L, Blum M, Hopper NJ, Langford J (2003) CAPTCHA: Using Hard AI Problems
for Security. In: EUROCRYPT. Lecture Notes in Computer Science, pp 294–311.
Warde-Farley D, Goodfellow IJ, Courville A, Bengio Y (2013) An empirical analysis of
dropout in piecewise linear networks. :1–10.
Woloszyn L, Sheinberg DL (2012) Effects of Long-Term Visual Experience on
Responses of Distinct Classes of Single Units in Inferior Temporal Cortex. Neuron
74:193–205.
Yamane Y, Carlson ET, Bowman KC, Wang Z, Connor CE (2008) A neural code for
three-dimensional object shape in macaque inferotemporal cortex. Nat Neurosci
11:1352–1360.
Zhivago KA, Arun SP (2016) Selective IT neurons are selective along many
dimensions. J Neurophysiol 115:1512–1520.
Zhou B, Khosla A, Lapedriza A, Oliva A, Torralba A (2014) Object Detectors Emerge
in Deep Scene CNNs. Arxiv:12.
Zoccolan D, Cox DD, DiCarlo JJ (2005) Multiple object response normalization in
monkey inferotemporal cortex. J Neurosci 25:8150–8164.
Zoccolan D, Kouh M, Poggio T, Dicarlo JJ (2007) Trade-Off between Object Selectivity
and Tolerance in Monkey Inferotemporal Cortex. 27:12292–12307.
758

759 **ACKNOWLEDGEMENTS**

760   This work was supported by a DST CSRI post-doctoral fellowship (HK) from
761 the Department of Science and Technology, Government of India and by
762 Intermediate and Senior Fellowships (500027/Z/09/Z and IA/S/17/1/503081) from the
763 Wellcome Trust-DBT India Alliance to SPA.

Supplementary material for

A separable neural code in monkey IT enables perfect CAPTCHA decoding

Harish Katti & S. P. Arun

Centre for Neuroscience, Indian Institute of Science, Bangalore, 560012, India

CONTENTS
       Supplementary Figures

A Single letter stimuli

a   d   g   s   T   y   7   K

Each letter is shown at 6 retinal locaitons and 4 distortions

B Distortions

yadgsT   yadgsT   yadgsT   yadgsT

Original   Fish-eye   Rotated   Global

C ngram stimuli

ad	dg	gs	sT	Ty	y7	7K	Ka	ya	dT
adg	dgs	gst	sTy	Ty7	y7K	7Ka	Kad	yad	Tya
adgs	dgsT	gsTy	sTy7	Ty7K	y7Ka	7Kad	Kadg	yadT	Tyad
adgsT	dgsTy	gsTy7	Ty7K	Ty7Ka	y7Kad	7Kadg	Kadgs	yadgT	Tyadg
adgsTy	dgsTy7	gsTy7K	sTy7Ka	Ty7Kad	y7Kadg	7Kadgs	KadgsT	yadgsT	Tyadgs

Each ngram is shown in 4 distortions

1
2
3 **Figure S1. Stimuli used in neural recordings.**
4 (A) Eight single letters were presented at 6 retinal locations and 4 distortions.
5 (B) Each stimulus was distorted in three ways: fish-eye, rotated and global.
6 (C) Ngram stimuli were created by combining the 8 single letters in various ways, and
7   ensuring that longer ngrams contained several smaller ngrams.
8

Figure S2: Responses of the neuron ka60_ch20_u1 to all stimuli

(A) Responses to single characters that were shown at 6 retinal locations and 4 different distortion versions. Responses have been grouped by the distortion type.

(B) Responses to ngrams that were shown at fixation in one of 4 different distortion versions. Responses have been grouped by the distortion type.

18
19
Figure S3. Error analysis for combination detectors
(A) Consider a neuron selective for the bigram "ty"– by definition it would mean that
its response to "ty" systematically deviates from the prediction from single letters.
(B) If this neuron is consistently detecting the bigram "ty" its response to any longer
string containing "ty" should deviate in the same direction.
(C) To assess this possibility, we sorted bigrams according to the bigram model error
into two groups, one with higher model errors and the other with lower model
errors. We then calculated the average model error for longer strings containing
high-error bigrams and low-error bigrams after fitting the linear model to strings of
each length. There were no systematic differences in model error as would be
expected from combination detectors.
(D) Similar analysis for trigram detectors. We sorted all longer strings (4-grams, 5-
grams and 6-grams) into those containing high-error trigrams and low-error
trigrams. We observed no systematic differences in model error as would be
expected from trigram detectors.
(E) Same as (D) but for 4-gram detectors.
(F) Same as (D) but for 5-gram detectors.
37
38

Figure S4. Divisive normalization in ngram responses.
(A) Normalization weights calculated as the slope of best fit line that predicts observed ngram responses at each length using the sum of observed single character responses at corresponding retinal locations. Only undistorted strings and characters have been used and neuronal firing rates have been normalized for every neuron. Each plot has 1390 points corresponding to 10 unique ngrams at each ngram length, from every neuron.
(B) Estimated slopes of the best fit line are plotted against ngram length.