VCFdbR: A method for expressing biobank-scale Variant Call Format data in a SQLite database using R

Tanner Koomar[1,*], Jacob J Michaelson[1]

1 The University of Iowa

* tanner-koomar@uiowa.edu

Abstract

As exome and whole-genome sequencing cohorts grow in size, the data they produce strains the limits of current tools and data structures. The Variant Call Format (VCF) was originally created as part of the 1,000 Genomes project. Flexible and concise enough to describe the genetic variations of thousands of samples in a single flat file, the VCF has become the standard for communicating the results of large-scale sequencing experiments. Because of its static and text-based structure, VCFs remain cumbersome to parse and filter in an interactive way, even with the aid of indexing. Iterating on previous concepts, we propose here a pipeline for converting VCFs to simple SQLite databases, which allow for rapid searching and filtering of genetic variants while minimizing memory overhead. Code can be found at https://github.com/tkoomar/VCFdbR

Introduction   1

The Variant Call Format is a well-specified and flexible way to describe genetic variants   2
identified by sequencing, along with annotations describing those variants. These   3
annotations are a particularly powerful feature of the VCF, and set it apart from more   4
efficient formats of expressing genetic variants, like PLINK and BGEN. Unfortunately,   5
despite advances in processing VCFs [3] as a flat text file, searching and filtering   6
variants in a VCF based on its annotations is slow and cumbersome.   7

When studying genetics of larger cohorts, it is often necessary to begin with   8
exploratory analyses – which require rapid iteration and changes to filtering schemes.   9
Data from these studies are often so large that they cannot be read directly into RAM,   10
and writing subsets of variants to a hard disk repeatedly is slow and introduces   11
overhead that does not scale well. Therefore, faster methods of identifying variants of   12
interest from sequencing data are needed, such as databases or datastores.   13

For example, the GenomicsDB format, a datastore developed by GATK team and   14
Intel [5], is fast, scaleable and efficient. However, it is currently only widely used for the   15
merging of gVCFs produced by GATK, and much work is still needed to make it a   16
standard that can replace the VCF. The Hail data-analysis library [10] does a good job   17
of implementing GenomicsDB, but attempts to be an end-to-end solution. This requires   18
learning its own interface and is not compatible with the tools many computational   19
geneticists already use – particularly R [9] and Bioconductor [4] packages.   20

The Gemini database [8] is a somewhat more flexible alternative that takes the   21
approach of converting a VCF to an SQLite database that can be manipulated with any   22

suitable interface. SQLite is a single-file database that does not require a server, making it suitable for working on high performance computing clusters that are available and widely used by computational geneticists in academic institutions. However, Gemini compresses genotypes to save space, which slows down queries. Users can opt not to compress genotypes with Gemini, but this creates 1 column per sample (i.e. 'wide' format), which can rapidly exceed the column limit of an SQLite database. Additionally, this is not scaleable to very large cohorts which might result in databases which violate file system limits on the size of single file.

Many researchers would benefit from a method for converting a VCF to an SQLite database that is suitable for large cohorts. This requires genotypes to be stored in the more database-friendly 'long' format as well as an option to save genotypes to external files to avoid hitting single-file size limits. Such a method should also avoid operations that require writing intermediate files to disk and the requirement to learn bespoke interfaces. The R language is widely used by computational geneticists, and has the excellent general-purpose SQL database interface provided by the dbplyr package [11]. Additionally, R is under-served in this realm, as both Gemini and Hail utilize Python-based interfaces. For these reasons, we propose a relatively simple pipeline for converting a VCF to an SQLite database, which we call VCFdbR.

The VCFdb Table Schema

Overview

SQLite is a server-less, single-file relational database composed of one or more 'tables', which may be linked by shared 'keys'. In a VCFdb created by VCFdbR, this 'key' is a integer that uniquely identifies each variant in the VCF. Specific columns within a given SQLite table may also be indexed, so that they may be searched rapidly.

Information describing each variant of a VCF is divided among up to three tables of a VCFdb. Core information and INFO columns are stored in a table called `variant_info`. If annotations produced by the Variant Effect Predictor (VEP) [6] are present, they are in a table called `variant_impact`. Genotypes are stored in a `variant_geno` table if the database is created in 'Table-GT mode', or as individual files in a separate directory if created in 'File-GT mode'. Table-GT databases are simpler, producing a single portable database file. File-GT databases require care to move after creation, but allow for a database to be created for tens or hundreds of thousands of individuals (assuming sufficient disk space).

Core Tables and Files

variant_info   The `variant_info` table contains all of the core information that uniquely describes a variant. The columns that appear here depend on the annotations provided in the input VCF. To save disk space, it is recommended to remove all unneeded INFO columns from the VCF, e.g. with `bcftools annotate --remove`. Each variant appears in this table exactly once.

Table 1. variant_info table schema

variant_id	chr	start	end	ref	alt	qual	filter	an	ac	...
1	chr22	16050075	16050075	A	G	100	PASS	50	8	...
2	chr22	16050115	16050115	G	A	100	PASS	50	12	...
...	...	...	...	...	...	...	...	...	...	...
961	chr22	16136747	16136751	TATTA	T	100	PASS	50	22	...
...	...	...	...	...	...	...	...	...	...	...

variant_impact   The `variant_impact` table is created if the input VCF has been ⟨62⟩
annotated with VEP (i.e. it has an INFO field named CSQ). This information is placed ⟨63⟩
into its own table because each variant may have multiple effects or affect multiple ⟨64⟩
genes/transcripts. Thus, each variant may appear in `variant_impact` multiple times.

Table 2. variant_impact table schema

variant_id	consequence	impact	symbol	...
840	upstream_gene_variant	MODIFIER	LA16c-60H5.7	...
840	intron_variant	MODIFIER	NBEAP3	...
840	non_coding_transcript_variant	MODIFIER	NBEAP3	...
...	...	...	...	...

⟨65⟩

Genotypes ⟨66⟩

Table-GT: variant_geno   When a VCFdbR is run in 'table' mode, the resulting ⟨67⟩
Table-GT database will have a table called `variant_geno`. Each entry of this table ⟨68⟩
describes the genotype (as dosage) of one individual for one variant, along with ⟨69⟩
additional columns for all FORMAT fields from the VCF. With a moderate to large ⟨70⟩
number of samples, this portion of the database takes up the most disk space. To save ⟨71⟩
substantial space, it is recommended to remove all unneeded FORMAT fields from the ⟨72⟩
VCF before database creation, e.g. with `bcftools annotate --remove!`. If the input ⟨73⟩
VCF contains n samples and m variants, then this table will have rows equal to $n \times m$. ⟨74⟩

Table 3. variant_geno table schema

variant_id	sample	gt	gt_raw	gq	dp	...
840	HG00096	0	0|0	35	20	...
840	HG00097	2	1|1	19	14	...
840	HG00098	1	0|1	47	40	...
...	...	...	...	...	...	...

File-GT: geno directory   When a VCFdbR is run in 'table' mode, the resulting ⟨75⟩
FILE-GT database will not have a `variant_geno`, instead one file per variant will be ⟨76⟩
saved to a write-protected directory. The absolute path to these files will be saved to a ⟨77⟩
`geno` column on the `variant_info` table. These files may be read in to R with the ⟨78⟩
`read.rds()` or `read_rds()` commands, and otherwise have an identical layout to the ⟨79⟩
genotypes of a Table-GT database. This separation of the genotypes from the ⟨80⟩
annotations (which remain in the database) makes it possible to move the database to a ⟨81⟩
faster but smaller disk for quicker filtering (e.g. a local SSD) while keeping the ⟨82⟩
genotypes on a larger be slower disk (e.g. a network-connected hard disk). ⟨83⟩

Table 4. variant_info table schema for a File-GT database

variant_id	chr	start	...	geno
1	chr22	16050075	...	/path/prefix-genos/1.rds
2	chr22	16050115	...	/path/prefix-genos/2.rds
...	...	...	...	...
961	chr22	16136747	...	/path/prefix-genos/961.rds
...	...	...	...	...

Additional Table and Files

Miscellaneous Tables   Additional tables will be created based on the full content of the VCF header. For example, a `sample` table will list all samples, while an `INFO` table will contain the descriptions for each INFO column provided in the input VCF.

gene_map   If VEP annotations were provided on the input VCF, an additional `gene_map` table will be produced in the final database. This is a terse mapping of all of the genes and genomic elements which actually appear in the database. This table can be useful for identifying the universe of genes or other annotations which are present in the database.

Table 5. gene_map table schema

symbol	source	canonical	...	feature_type
LA16c-4G1.3	Ensembl	YES	...	Transcript
NBEAP3	Ensembl	YES	...	Transcript
...	...	...	...	...

Genomic Ranges   After database creation, VCFdbR creates a GenomicRanges representation of each variant. The GenomicRanges data structure is the bedrock of many Bioconductor genomics packages. This file can be used to identify variants of interest based on annotations external to the database, or even to generate new columns to be added to the `variant_info` table. This is a minimal representation of the variants, and only includes the position, REF/ALT alleles, and possibly the path to the corresponding variant files (for File-GT databases only).

Database Creation

Input Requirements

Input VCFs should conform to the format standard, be gzipped/tabixed indexed, and must have multi-allelic sites split, e.g. with

```
bcftools norm -m -
```

A VCF which has been annotated with VEP should be passed through

```
sed /^#/\! s/;;/;/g
```

to ensure proper parsing of the annotations when read into R. Finally, VCFdbR requires an up-to-date version of R, preferably greater than version 3.5. Specific package requirements can be found on the GitHub repo.

Pipeline Overview

To accommodate RAM limits, VCFdbR operates by reading in chunks of the input VCF and writing to the database iteratively. To identify chunks of variants, minimal information from the VCF is read into R with the VariantAnnotation [7] package, and GenomicRanges corresponding to 1,000 variants each are written to a file. The number of variants per chunk can be reduced based on memory constraints at the expense of some processing time.

The header of the VCF is then parsed and written to the miscellaneous tables of the database. For each chunk, the VCF's INFO field is then parsed and searched for a CSQ

field. Then, the genotypes are parsed, converting them to 'long' format. Once the data ₁₁₉

INFO, CSQ and FORMAT are fully parsed, they are appended to the corresponding ₁₂₀ database tables (`variant_info`, `variant_impact` and `variant_geno`, respectively). If ₁₂₁ operating in File-GT mode, the parsed FORMAT fields are written to the file system ₁₂₂ instead of the database. ₁₂₃

After all VCF chunks have been processed, the database tables are indexed. ₁₂₄ Indexing always includes the `variant_id`, and new indexes can be added by the user at ₁₂₅ any time. Finally, the GenomicRanges representation of the database is written to disk ₁₂₆ and the `gene_map` table is created (if the input VCF had VEP annotations). ₁₂₇

Benchmarks

Database Creation

For benchmarking, three databases were prepared from phase 3 of the 1,000 Genomes ₁₃₀ Project [1]. First, a File-GT database from the whole genome sequences of all 2,504 ₁₃₁ subjects from the project was created. Then, both File-GT and Table-GT databases ₁₃₂ were created from the exome-captured variants for first 1,000 samples. A summary of ₁₃₃ the time required for each of the major steps of database creation (chunking, building, ₁₃₄ and indexing) can be seen in Table **??**. All databases were created with a chunk size of ₁₃₅ 10,000, and the File-GT databases were written with four threads. This – and all other ₁₃₆ benchmark steps – were carried out on server-grade compute nodes and NFS-networked ₁₃₇ disks on the high performance computing cluster at the University of Iowa. ₁₃₈

Dataset	Samples	Variants	VCF Size	Mode	Componant	Size		Step	Time	
exome	1,000	1,417,043	693 MB	table	database	22.6 GB		chunk		2 min
								build	1 hr	32 min
					geno files			index		20 min
					total	**22.6 GB**		**total**	**1 hr**	**54 min**
exome	1,000	1,417,043	693 MB	file	database	2.8 GB		chunk		2 min
								build	2 hr	3 min
					gene files	34.4 GB		index		12 min
					total	**37.2 GB**		**total**	**2 hr**	**17 min**
genome	2,504	85,211,481	29.7 GB	file	database	64.8 GB		chunk	2 hr	19 min
								build	218 hr	8 min
					geno files	2.55 TB		index	5 hr	56 min
					total	**2.61 TB**		**total**	**225 hr**	**23 min**

Variant Filtering

Because the filtering of variants based on annotations of interest occurs entirely within ₁₄₀ the database, it can be extremely fast. This requires all annotations used for filtering to ₁₄₁ be indexed, but is generally worth the time and small increase in database size since the ₁₄₂ time to query an indexed column is on the log scale. ₁₄₃

To illustrate this, the time to filter variants to those with an alternate allele ₁₄₄ frequency less than 5% and within each gene in both the genome and exome databases ₁₄₅ prepared from 1,000 Genomes Phase 3 is plotted in Figure 1. Although this requires ₁₄₆ filtering the variants on both the `variant_impact` (for gene) and `variant_info` (for ₁₄₇

alternate allele frequency) tables, genes with 10,000 qualifying variants typically take 148
less than 1.5 seconds to identify and read into memory (Figure 1.B). 149

Figure 1. The time to identify variants of interest based on indexed columns is nonlinear with the number matching variants. The filtering here is performed on both numeric (allele frequency) and text (gene name) columns in both exome data (**A**) and whole-genome (**B**) data.

Because this example performs no filtering based on genotypes or other FORMAT 150
fields, there is no effective difference between File-GT and Table-GT databases. If 151
substantial filtering is needed on FORMAT fields, there is a significant increase in the 152
speed of filtering for Table-GT databases (provided the `variant_geno` table is 153
appropriately indexed). 154

Genotype Pulling 155

Though computationally trivial, reading genotypes into memory is by far the most I/O 156
intensive part of working with a VCFdb. This process can be sped up somewhat 157
through the use of multiprocessing across more than one processor core. However, disk 158
and network limitations mean that using more threads may have diminishing returns 159
even before the principles of Amdhal's Law [2] become relevant. 160
To illustrate this, random subsets of variants from each of the three 1,000 Genomes 161
databases described above were generated, ranging in size from 50 to 5,000 variants. 162
The genotypes for these variant sets were then read in to memory using a range of cores 163
for multiprocessing. The time taken for each subset of variant across each database and 164
number of multiprocessing cores is illustrated in Figure 2. On the particular hardware 165
used for these benchmarks, there was little improvement in speed when using more than 166
4 threads to read genotypes simultaneously, and virtually no difference between using 8 167
and 16 threads. This indicates that disk or network speeds likely saturated when using 168
around 4 cores. Performing this sort of benchmarking is recommended when running on 169
new hardware to ensure resources are used as efficiently as possible. 170

Figure 2. Reading genotypes with many simultaneous processes has limited benefit. In benchmarks of (**A**): a Table-GT exome database with 1,000 samples, (**B**): a File-GT exome database with 1,000 samples, and (**C**): a File-GT whole genome database with 2,504 samples, speed gains from using more than 4 simultaneous processes is minimal.

Acknowledgments 171

Ethan Bahl, Leo Brueggeman, Yongchao Huang, Taylor R. Thomas, and everyone else 172
who tested and used VCFdb through multiple iterations. 173

References

1. A global reference for human genetic variation. *Nature*, 526(7571):68–74, sep 2015.

2. G. M. Amdahl. Validity of the single processor approach to achieving large scale computing capabilities. In *Proceedings of the April 18-20, 1967, spring joint computer conference on - AFIPS 67 (Spring)*. ACM Press, 1967.

3. P. Danecek, A. Auton, G. Abecasis, C. A. Albers, E. Banks, M. A. DePristo, R. E. Handsaker, G. Lunter, G. T. Marth, S. T. Sherry, G. McVean, and R. D. and. The variant call format and VCFtools. *Bioinformatics*, 27(15):2156–2158, jun 2011.

4. R. C. Gentleman, V. J. Carey, D. M. Bates, B. Bolstad, M. Dettling, S. Dudoit, B. Ellis, L. Gautier, Y. Ge, J. Gentry, K. Hornik, T. Hothorn, W. Huber, S. Iacus, R. Irizarry, F. Leisch, C. Li, M. Maechler, A. J. Rossini, G. Sawitzki, C. Smith, G. Smyth, L. Tierney, J. Y. Yang, and J. Zhang. *Genome Biology*, 5(10):R80, 2004.

5. A. McKenna, M. Hanna, E. Banks, A. Sivachenko, K. Cibulskis, A. Kernytsky, K. Garimella, D. Altshuler, S. Gabriel, M. Daly, and M. A. DePristo. The genome analysis toolkit: A MapReduce framework for analyzing next-generation DNA sequencing data. *Genome Research*, 20(9):1297–1303, jul 2010.

6. W. McLaren, L. Gil, S. E. Hunt, H. S. Riat, G. R. S. Ritchie, A. Thormann, P. Flicek, and F. Cunningham. The ensembl variant effect predictor. *Genome Biology*, 17(1), jun 2016.

7. V. Obenchain, M. Lawrence, V. Carey, S. Gogarten, P. Shannon, and M. Morgan. Variantannotation: a bioconductor package for exploration and annotation of genetic variants. *Bioinformatics*, 30(14):2076–2078, 2014.

8. U. Paila, B. A. Chapman, R. Kirchner, and A. R. Quinlan. GEMINI: Integrative exploration of genetic variation and genome annotations. *PLoS Computational Biology*, 9(7):e1003153, jul 2013.

9. R Core Team. *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria, 2014.

10. H. Team. Hail. `https://github.com/hail-is/hail/releases/tag/0.2.13`, 2020.

11. H. Wickham and E. Ruiz. *dbplyr: A 'dplyr' Back End for Databases*, 2019. R package version 1.4.2.