A Behavioral Association Between Prediction Errors and Risk-Seeking: Theory and Evidence

Short title: Prediction Errors and Risk-Seeking

Moritz Moeller*1, Jan Grohn*2, Sanjay Manohar**12, Rafal Bogacz**1+.

*: equal contributions

**: equal contributions

1: Nuffield Department of Clinical Neurosciences, University of Oxford

2: Department of Experimental Psychology, University of Oxford

+: corresponding author (rafal.bogacz@ndcn.ox.ac.uk)

Abstract

Reward prediction errors (RPEs) and risk preferences have two things in common: both can shape decision making behavior, and both are commonly associated with dopamine. RPEs drive value learning and are thought to be represented in the phasic release of striatal dopamine. Risk preferences bias choices towards or away from uncertainty; they can be manipulated with drugs that target the dopaminergic system. The common neural substrate suggests that RPEs and risk preferences might be linked on the level of behavior as well, but this has never been tested. Here, we aim to close this gap. First, we apply a recent theory of learning in the basal ganglia to predict how exactly RPEs might influence risk preferences. We then test our behavioral predictions using a novel bandit task in which value and risk vary independently across options. Critically, conditions are included where options vary in risk but are matched for value. We find that subjects become more risk seeking if choices are preceded by positive RPEs, and more risk averse if choices are preceded by negative RPEs. These findings cannot be explained by other known effects, such as nonlinear utility curves or dynamic learning rates. Finally, we show that RPE-induced risk-seeking is indexed by pupil dilation: participants with stronger pupillary correlates of RPE also show more pronounced behavioral effects.

Author's summary

Many of our decisions are based on expectations. Sometimes, however, surprises happen: outcomes are not as expected. Such discrepancies between expectations and actual outcomes are called prediction errors. Our brain recognises and uses such prediction errors to modify our expectations and make them more realistic--a process known as reinforcement learning. In particular, neurons that release the neurotransmitter dopamine show activity patterns that strongly resemble prediction errors. Interestingly, the same neurotransmitter is also known to regulate risk preferences: dopamine levels control our willingness to take risks. We theorised that, since learning signals cause dopamine release, they might change risk preferences as well. In this study, we test this hypothesis. We find that participants are more

likely to make a risky choice just after they experienced an outcome that was better than expected, which is precisely what out theory predicts. This suggests that dopamine signalling can be ambiguous--a learning signal can be mistaken for an impulse to take a risk.

Introduction

Reward-guided learning in humans and animals can often be modelled simply as reducing the difference between the obtained and the expected reward—a reward prediction error. This well-established behavioral phenomenon (Rescorla and Wagner 1972) has been linked to the neurotransmitter dopamine (Schultz, Dayan et al. 1997). Dopamine neurons project to brain areas relevant for reward learning, such as that striatum, the cortex and the amygdala (Wise 2004, Björklund and Dunnett 2007). Dopamine activity is known to change synaptic efficacy in the striatum (Reynolds, Hyland et al. 2001) and has been causally linked to learning (Steinberg, Keiflin et al. 2013). This and other biological evidence have led to a family of mechanistic theories of learning within the basal ganglia network (Collins and Frank 2014, Mikhael and Bogacz 2016, Möller and Bogacz 2019). According to these models, positive and negative outcomes of actions are encoded separately in the direct and indirect pathways of the basal ganglia.

Crucially, the balance between those pathways is also controlled by dopamine (Gerfen and Surmeier 2011): An increased dopamine level promotes the direct pathway, whereas low levels of dopamine promote the indirect pathway. The family of basal ganglia models includes these modulatory mechanisms too; this makes them consistent with well-studied phenomena whereby dopamine modulates how uncertainty and risk affect decision making: dopaminergic medication can bias human decision making towards or away from risk (Voon, Hassan et al. 2006, Gallagher, O'Sullivan et al. 2007, St Onge and Floresco 2009, Weintraub, Koester et al. 2010), and phasic responses in dopaminergic brain areas predict people's moment-to-moment risk-preferences (Chew, Hauser et al. 2019).

In summary, ample evidence suggests that dopamine bursts are related to distinct behavioral phenomena—learning and risk-taking—by way of 1) acting as reward prediction errors, affecting

synaptic weights during reinforcement learning, and 2) inducing risk-seeking behavior directly. There is

no obvious a priori reason for those functions to be bundled together; in fact, one would perhaps expect

them to work independently, and their conflation might lead to interactions, unless some separation

mechanism exists. There have been different suggestions for such separation mechanisms: it has been

proposed that the tonic level of dopamine might modulate behavior directly, while phasic dopamine

bursts provide the prediction errors necessary for reward learning (Niv 2007). Alternatively, cholinergic

interneurons might flag dopamine activity that is to be interpreted as prediction errors by striatal neurons

(Berke 2018). However, it has also been suggested that the prediction errors encoded by dopaminergic

neurons might drive both learning and decision making simultaneously (Bogacz 2020).

Curiously, even though the multi-functionality of dopamine has been noted and separation mechanisms

have been proposed, interference between the different functions has, to our knowledge, never been tested

experimentally. Here, we investigate this: if dopamine indeed provides prediction errors and modulates

risk preferences at the same time, do these two processes interfere with each other, or are they cleanly

separated by some mechanism? In other words, we test whether prediction errors are associated with risk-

seeking.

A common method to provoke prediction-error related dopamine bursts in humans is to present cues and

outcomes in sequential decision-making tasks, hence causing prediction errors both when options are

presented, and at the time of outcome (Seymour, O'Doherty et al. 2004, Pessiglione, Seymour et al. 2006,

Niv, Edlund et al. 2012). To test whether such prediction errors induce risk seeking, we used a learning

task in which prediction errors are followed by choices between options with different levels of risk. If

there was a clear separation of roles, then risk preferences should be independent of prediction errors.

Incomplete separation, in contrast, should result in a correlation between risk preferences and preceding

prediction errors. In particular, we hypothesized that positive prediction errors, occurring when

expectations are exceeded, should induce risk seeking, while negative prediction errors should lead to risk

aversion.

We further hypothesized that participants who experience stronger prediction errors also show stronger

risk preferences. Thus, we tracked participants' pupil dilation, which is known to reflect surprising events

such as prediction errors (Preuschoff, t Hart et al. 2011, Cavanagh, Wiecki et al. 2014, Browning,

Behrens et al. 2015, Lawson, Mathys et al. 2017). We expected that increased perception of prediction

errors should lead to increased pupil responses as well as stronger risk preferences, and hence predicted a

correlation between pupil response to prediction errors and risk seeking associated with prediction errors.

Overall, we found effects that were consistent with our predictions: Risk seeking was higher when

choices followed positive prediction errors than when they followed negative prediction errors. These

preferences emerged gradually over the course of learning and could not be explained by any of several

other known mechanisms. In addition, they were associated with pupil dilation in a way predicted by our

theory.

Results

Task & Theory

97 In this first section, we introduce our task and provide a detailed theoretical analysis of the behavior we

98 expect from our participants. This analysis is based on models of the basal ganglia network and allows us

99 to derive concrete predictions and models for behavior which we use for data analysis below.

Task

Our task consisted of sequences of two-alternative forced choice trials. On each trial, after an inter-trial

interval (ITI) of 1 s, two stimuli (fractal images, Fig 1A) were drawn from a set of four stimuli and shown

to the participant, who had to choose one. Following the choice, after a short delay of 0.8 s a numerical

reward between 1 and 99 was displayed under the chosen stimulus for 1.5 s. Then, the next trial began.

Participants were instructed to try to maximize the total number of reward points throughout the

experiment.

Fig 1: Task design and theory

A) Task structure. Each trial begins with a blank screen. After 1 s, two out of four possible stimuli are

selected and shown to the participant. The participant chooses one of them, which is then highlighted

after a delay of 0.2 s. After another delay of 0.8 s, a point reward is displayed underneath the chosen

stimulus. During each trial two separate prediction errors occur: At stimulus presentation the participant

discovers whether the two displayed stimuli are better (positive prediction error) or worse (negative

prediction error) than the expected average stimulus. At outcome presentation the participant discovers

whether the obtained reward is higher or lower than the expected average reward of the selected

stimulus.

B) Reward distributions. Each stimulus (top) is associated with a different reward distribution (bottom).

The distributions differ in mean (60 points versus 40 points) and standard deviation (20 points versus 5

points). Reward distributions were unknown to participants and the association of stimuli and

distributions was shuffled between blocks. The dashed line in the background indicates the middle of the

reward range, which was at 50 points.

C) Events during the first half of a trial (ITI to response) according to our theory. As the blank screen

appears, the participant's reward expectation (black horizontal line in the first thought-bubble) is based

on all past rewards (distributions in the first thought-bubble). Above-average past rewards are encoded

in the Go pathway (green dots) and below-average past rewards in the NoGo pathway (red dots). They

are weighed equally since the Go and the NoGo pathways are in balance (first diagram in bottom row).

As the stimuli appear, only the relevant past rewards are considered (irrelevant rewards greyed out in the

middle thought-bubble), and the reward expectation changes (black horizontal line in the middle thought-

bubble is higher than the black line in the first thought-bubble). The upward change in reward

expectation constitutes a temporal difference prediction error which is signaled by increased dopamine

transmission in the striatum (blue transient in bottom row; delta stimulus in panel A). This suppresses the

NoGo pathway and enhances the Go pathway (second diagram in bottom row). As a result, below-

average past rewards are ignored, and the focus is on above average past rewards (below average

rewards greyed out in last thought-bubble). The stimulus with the larger spread is now valued higher

(green lines in last thought-bubble) and is therefore chosen.

The reward on each trial depended on the participant's choice: each stimulus was associated with a

specific reward distribution from which rewards were sampled. The four reward distributions associated

with the four stimuli were approximately Gaussian and followed a two-by-two design: the mean of the

Gaussian could be either high or low (60 or 40), and the standard deviation could be either large or small

(20 or 5), resulting in four reward distributions in total (risky-high, risky-low, safe-high and safe-low, Fig

1B). The names derive from the idea that it is "risky" to pick a stimulus associated with a broad reward

distribution, since outcomes might deviate a lot from the expected outcome. Correspondingly, it is "safe"

to pick a stimulus with a narrow distribution, since the outcomes will mostly be as expected.

We organize trials into three conditions: 1) "**different**": trials in which the shown stimuli have different

average rewards (for example risky-high and safe-low, which have average rewards of 60 and 40

respectively), 2) "**both-high**": trials in which both stimuli have a high average reward (risky-high and

safe-high, both have an average reward of 60 points) and 3) "**both-low**": trials in which both stimuli have

a low average reward (risky-low and safe-low, both have an average reward of 40 points).

Theoretical analysis of learning and decision making

In this section, we sketch a mechanistic theory of learning and decision-making in our task. This theory is

used to derive the computational model we use in our modelling analysis (see Results/Modelling). We

also use it to derive behavioral predictions (see Results/Task & Theory/Behavioral Predictions).

Our theory is based on (Mikhael and Bogacz 2016, Möller and Bogacz 2019). Its premise is that choices

are governed by competing action channels in the basal ganglia (BG) network, an assumption common to

many models of the basal ganglia (Gurney, Prescott et al. 2001, Frank 2006). We assume that for each

option i in our task, there is one such action channel, and that the probability of choosing option i

depends on the total activation A_i of that action channel. There are two contributions to this activation:

excitation of magnitude G_i through the direct pathway (also called Go pathway), and inhibition of

magnitude N_i through the indirect pathway (also called No-Go pathway). These contributions are

differentially modulated by dopamine (DA), mediated through the D1 and D2 receptors expressed in the

direct and indirect pathway respectively. Let δ represent the deviation of DA levels from baseline (i.e.,

$\delta = 0$ means baseline DA levels, $\delta > 0$ means DA is above baseline etc.). Then, the activation of an

action channel corresponding to option i can be approximated as

$$A_i = (0.5 + \delta) \times G_i - (0.5 - \delta) \times N_i.$$

166   Eq. 1

167   What determines G_i and N_i for each option? According to (Mikhael and Bogacz 2016, Möller and Bogacz

168   2019), the direct and indirect pathway are subject to DA-dependent plasticity. Hence, G and N change

169   through reward-driven learning—roughly, G tracks the upper end of the reward distribution, while N

170   tracks the lower end. More accurately, we may assume that $G - N$ tracks Q, the mean of the reward

171   distribution, according to the rule

172 $$\Delta Q_i = \alpha_Q (r - Q_i),$$

173   Eq. 2

174   and that $G + N$ tracks S, the spread of the reward, according to the rule

175 $$\Delta S_i = \alpha_S,$$

176   Eq. 3

where $\alpha_Q > \alpha_S$. Using this notation, Eq. 1 reads $A_i = Q_i + \delta \times S_i$—the impact of reward spread on

action activation is *gated* by the level of DA.

In our task, the Q and S of the four action channels should converge to the means and spreads of the four

reward distributions. With DA at baseline (i.e., $\delta = 0$) activation is proportional to Q, and hence to the

mean reward. Choices should thus be biased towards options with high mean rewards. If DA levels are

increased (i.e., $\delta > 0$), the learned spread S contributes positively to action activation, biasing choices

towards risky options. If, on the other hand, DA levels are below baseline (i.e., $\delta < 0$), the learned spread

S reduces action activation, biasing choices towards safe options.

Theoretical analysis of prediction errors

In this section, we focus on how the participant's reward prediction should theoretically change over the

course of a trial. This is based on the theory of temporal difference learning (Sutton and Barto 2018),

which has been applied to describe dopaminergic responses to rewards (Schultz, Dayan et al. 1997). The

basic assumption of these theories is that participants maintain a prediction of upcoming rewards at all

times. This prediction is based on learned estimates Q of average rewards associated with the four stimuli.

At the beginning of a trial (before the stimuli appear), participants do not have any specific information to

base their prediction on. Depending on whether they anticipate the appearance of the stimuli or not, they

might either predict the average reward over all trials (which we take to be the average learned value

across all options), or no reward at all. Neither of these two possibilities can be ruled out on theoretical

grounds only. We will therefore consider them both, and develop two versions of our hypothesis,

ultimately resulting into two slightly different models (see section Results/Models).

After the options appear, participants should adjust their reward prediction based on the learned values of

the displayed options. We take the participants' updated prediction to be the average learned value over

the presented options. The updated prediction should differ across conditions: if the participants learned

accurate estimates of the values, their prediction would be 60 points in the both-high condition and 40

points in the both-low condition.

This change in participants' reward expectation through the appearance of reward-predicting stimuli

constitutes a prediction error called **stimulus prediction error** δ_{stim} , previously described in (Jang,

Nassar et al. 2019), and should cause phasic DA activity (Schultz, Dayan et al. 1997). If participants'

initial reward expectation is the average over all trials (this corresponds to the first version of our

hypothesis), the magnitude of that prediction error is given by

$$\delta_{stim} = mean_{shown}(Q) - mean_{all}(Q).$$

208   Eq. 4

209 If the values of the stimuli are learned with reasonable accuracy, this prediction error should be $60 -$

210 $50 = 10$ in the both-high condition and $40 - 50 = -10$ in the both-low condition.

211   If, on the other hand, participants don't predict any reward at the beginning of the trial (this corresponds

212   to the second variant of our model), the magnitude would be given by

213
$$\delta_{stim} = mean_{shown}(Q).$$

214   Eq. 5

We would then expect a magnitude of 60 in the both-high condition and a magnitude of 40 in the both-

both-low condition.

Next, participants will make a choice. Now, their reward expectation is the value of the option they chose.

Finally, a reward is displayed, forcing participants to update their reward estimate again. This second

prediction error—the difference between the learned value of the option and the actual reward received—

we call the **outcome prediction error** δ_{out}. Its magnitude is given by

221
$$\delta_{out} = r - Q_{selected}.$$

222   Eq. 6

It is the outcome prediction error that drives learning about the stimuli (see Eq. 2 and Eq. 3 above).

In summary, our analysis reveals that two prediction errors (and two corresponding DA responses) should

occur in each trial: first the stimulus prediction error shortly after the presentation of the options, and

second the outcome prediction error after the presentation of the reward.

Behavioral Predictions

Here, we combine the results of the analyses above to derive task-specific behavioral predictions from our

theory (see Fig 1C for a schematic representation). Let us first assume that the stimulus prediction error is

given by Eq. 4. We have seen that in the matched-mean conditions (both-high and low), the presentation

of the options should cause a prediction error (positive and negative, respectively), and hence a transient

change in DA levels (increase and decrease, respectively) in the striatum during the choice period (Fig

1C, mechanistic level). We have also seen that DA levels affect choices through modulation of the BG

pathways: increased DA makes people risk seeking, decreased DA makes them risk averse. If the average

reward is similar for two options (as it is in the both-high and the both-low condition), these risk

preferences should be the decisive factor in decisions (Fig 1C, task level and past rewards level).

Taken together, these premises suggest that we should see a preference for the risky stimulus in the both-

high condition (depicted in Fig 1C), and a preference for the safe stimulus in the both-low condition.

These effects should appear gradually, since they require that both mean and spread of the reward

distributions are learned. Specifically, risk preferences in the both-high and both-low conditions should

appear slower than value preferences in the difference condition. This follows from the underlying

plasticity rules: one can show that the learning rate for spread must always be lower than the learning rate

for value (Möller and Bogacz 2019). In addition to this, a reasonably accurate value estimate is required

for the spread estimate to converge; this also contributes to a higher in learning speed for value compared

to spread.

Relaxing now our assumption that the stimulus prediction error is given by Eq. 4 and allowing stimulus

prediction errors of the type of Eq. 5, we can still be sure that the stimulus prediction error would be

stronger in the both-high condition than in the both-low condition. We should thus see a difference in risk

preference between conditions independent of the exact nature of the stimulus prediction error.

In summary, we have derived two predictions: 1) We should see a difference in risk preference between

conditions, and 2) we should see gradually emerging risk seeking in the both-high and risk aversion in the

both-low condition (prediction 2 depends on a stronger assumption on the nature of the stimulus

prediction error). To arrive at these predictions, we took into account neural mechanisms. However, the

predictions are purely on the level of behavior. In the empirical part of this study, we hence focus on

behavior, conscious that this will only provide indirect evidence for the neural underpinnings of the

proposed mechanism. However, it might reveal a previously unknown effect with a clear, plausible

biological explanation. We provide further predictions based on neural signals in the Discussion.

Behavior

In the previous section, we introduced a novel reinforcement learning task and performed a theoretical analysis to derive behavioral predictions. In this section, we present the results of testing these predictions.

We recruited a cohort of participants (N=27, 3 excluded, see Fig S1) and recorded their behavior in the task described above. Each participant performed four blocks of 120 trials. During each block, all six possible stimuli pairings occurred equally often. Each block used a new set of four stimuli, mapped to the same four distributions.

First, we investigated whether participants' performance improved during the task. Based on the premise of associative learning, we expected choice accuracy (i.e., likelihood of choosing the option with the higher average reward) to increase gradually over trials. To confirm this, we focused on choices in the difference condition, where participants had to choose between stimuli with different average rewards. We found that indeed, the probability of choosing the stimulus with the higher average reward increased gradually over trials across the population. Average performance differed from chance level with high significance (Fig 2A, t-test, $t(27) = 31.9$, $p < 0.001$) and approached its asymptote in the second half of the block. These findings suggest that our participants successfully used associative learning in our task, confirming a basic assumption of our theory.

Fig 2: Choice probabilities

A) Probability of choosing a stimulus with high average reward over a stimulus with low average reward,

as a function of trial number. Choices were binned according to trial number. For each bin, we show the

mean (dot) and SE (bar) over subject means. The stars (*: p < 0.05, **: p < 0.01, ***: p < 0.001)

indicate that the population mean across all trials is significantly different from indifference (0.5).

B) Probability of choosing the risky stimulus over the safe stimulus, i) if mean rewards are both high, ii) if

mean rewards are both low, as a function of trial number. Data represented as in A.

C) Correlation between risk preferences in the both-high mean and the both-low condition. Each point

represents one participant. Preference for the risky stimulus if mean rewards are high is plotted against

preference for the risky stimulus if mean rewards are low. If a point falls below the diagonal, the

participant was more risk seeking for high-mean stimuli than for low-mean stimuli. The stars indicate

that the population mean is significantly below the diagonal.

Next, we tested our first prediction—that participants would be risk-seeking in the both-high condition

and risk-averse in the both-low condition, and that these effects would emerge gradually and more slowly

than increases in task performance. For this, we analyzed choices in the both-high and both-low

condition. For each condition, we investigated the likelihood of choosing the stimulus with the broad

distribution (risky) over the stimulus with the narrow distributing (save). Preferring risky over safe was

considered risk-seeking, preferring safe over risky was considered risk-averse. As predicted, we found

significant risk-seeking in the both-high condition (Fig 2Bi; two-tailed t-test: p = 0.0343, t(26) = 2.23)

and significant risk aversion in the both-low condition (Fig 2Bii; two-tailed t-test: p = 0.0317, t(26) = -

2.27). These preferences emerged gradually as a function of trial number, at a slower rate than the

preferences for the high over low value stimuli (compare Fig 2A against Fig 2Bi and Fig 2Bii; mixed

effects model (see methods): p = 0.001). In summary, the data confirmed our first prediction in all

aspects.

We then tested our second prediction—that there would be a difference in risk-preferences (i.e., in the

likelihood to choose the risky option over the save option) between the both-high and the both-low

condition. Specifically, we predicted higher risk-seeking in both-high than in low. To test this, we

computed the difference in risk-preference between conditions for each participant. We found that most

of the participants were more risk seeking in the both-high condition than in the both-low condition (Fig

2C; two-tailed paired t-test: t(27) = 3.58, p = 0.0016), which confirmed our second prediction.

In summary, in data recorded from the task described above, we found the two behavioral effects we

predicted. The second effect was clearer than the first effect (t = 3.58 versus t = 2.23 and t = -2.27). This

is consistent with our theory: the first effect rests on more assumptions than the second. We will thus

focus on the second effect in the analyses below.

Our findings provide initial evidence for a behavioral link between prediction errors and risk preferences.

In the next section, we use computational modelling to compare our explanation of the measured effects

to alternative explanations.

Modelling

In the previous section, we have shown that effects like those predicted by our theory can be found in experimental data. Our analysis so far rested on the assumption that participants know the ground-truth means and standard-deviations of the reward distributions. However, these statistics have to be learned when participants perform the task. To capture this learning process trial-by-trial learning models can be fit to the data. These models allow us to answer some other important questions that have not yet been addressed:

1. Are there alternative explanations for the observed effects?

2. Does our theory fit the data better than existing theories?

In this section, we use computational modelling to answer these questions. To test our theory against alternative explanations, we use simulations as well as model comparison techniques (Palminteri, Wyart et al. 2017).

Models

Associative learning in tasks like ours is commonly described with the Rescorla-Wagner (RW) model (Rescorla and Wagner 1972). All models we use here are variants of this base model. RW is also the first type of explanation for the effects we observed—it has been shown that even basic associative learning can yield risk preferences through sampling biases (Niv, Edlund et al. 2012).

The second type of explanation involves the utility of reward points: risk aversion as well as risk seeking have been explained as consequences of nonlinear utility functions (Kahneman and Tversky 2013). For our analysis, we considered RW-type learning in combination with the two most common families of utility functions: the concave utility of expected utility theory and s-shaped utility of prospect theory. The corresponding models are called concave UTIL and s-shaped UTIL.

The third type of explanation is based on RW with variable learning rates. It has been observed that

humans use different learning rates for positive and negative outcomes (Gershman 2015), and that this

can lead to risk preferences (Niv, Edlund et al. 2012). We implement this in the model pos-neg RATES. It

has also been observed that when tracking a reward signal, humans adapt to the signal statistics (Daw,

O'doherty et al. 2006), akin to the Kalman filter used in engineering. In Kalman filters, the learning rate

depends on the variance of the signal that is tracked. We thus included a model with different learning

rates for high variance and low variance rewards, referred to as variance RATES.

Finally, the explanation that we propose in this study is that prediction errors induce transient risk

preferences, as detailed above. We represent our hypothesis with two very similar models, called PEIRS

(Prediction Errors Induce Risk Seeking) and PIRS (Predictions Induce Risk Seeking). These models

differ only in how the stimulus prediction error is computed—PEIRS assumes that the initial reward

expectation corresponds to the average reward over all options (Eq. 4), while PIRS assumes that the initial

reward expectation is zero (Eq. 5).

Alternative explanations

First, we wanted to know which of the models could reproduce (and hence explain) the observed effects.

To check this, we first fitted all models to our dataset and extracted maximum-likelihood parameters for

each participant. We then used these parameters to simulate behavior in our task with all candidate

models to generate synthetic datasets. Finally, we analyzed these synthetic datasets in the same way as the

experimental dataset. In our analysis, we focused on the difference of risk preferences between conditions

(Fig 2C), as this was the most pronounced of the predicted effects.

We found that the models that represented our hypothesis reproduced the effect best: the PEIRS model

captures the overall distribution of risk preferences across the population best (Fig 3A, panel PEIRS, see

Fig S2 for likelihood ratios) and produces the most realistic effect size among all models we considered

(Fig 3B, empirical effect size: 0.122, simulated effect size with PEIRS model: 0.087, no significant

difference between experimental data and simulated data, two-tailed paired t-test, t(26)=-1.72, p=0.0976).

The PIRS model, on the other hand, is the only model that captures the part of our population that is risk

seeking in both the both-high and the both-low condition (Fig 3A, panel PIRS, upper right quadrant, see

Fig S2 for likelihood ratios). It also produces the second most realistic effect size (Fig 3B, empirical

effect size: 0.122, simulated effect size with PEIRS model: 0.059, no significant difference between

experimental data and simulated data, two-tailed paired t-test, t(26)=-2.01, p=0.0552).

Fig 3: Modelling results

A) Risk preferences in simulated datasets. The risk preference distributions extracted from simulated data

are plotted as blue contour plots. The corresponding experimental data is superimposed as a grey

scatterplot (identical in all panels). The shading corresponds to estimated probability density functions

and is scaled to match each distribution's density value range for better visibility.

B) Difference in risk preferences between conditions, for simulated and empirical datasets. Simulated

datasets are shown as blue bars, the experimental dataset is shown as a grey bar. We show the mean

(bar) and the SE (errorbar) of subject means (averaged over experiment repetitions for simulated

datasets).

C, D) Model comparison with and without PEIRS (C) / PIRS (D) extension. Lower BIC indicates a better

fit. The y-axis is valid for all plots in the same row.

Most of the alternative models (RW, concave UTIL, s-shaped UTIL, pos-neg RATES) predicted very

narrow distributions for the risk preferences, which is at odds with our empirical results. The variance

RATES model was the only alternative model that produced a somewhat realistic distribution of risk

preferences (albeit not as realistic as the PEIRS model, see Fig 3A, PEIRS and variance RATES and Fig

S3 for likelihood ratios).

With respect to our main effect—the difference of risk preferences between conditions—all alternative

models predicted effect sizes that differed significantly from the empirical findings (Fig 3B, two-tailed

paired t-tests, s-shaped UTIL: $t(26)=-4.71$, $p < 0.001$, RW: $t(26)=-2.78$, $p=0.010$, concave UTIL: $t(26)=-$

2.66, $p=0.013$, pos-neg RATES: $t(26)=-2.4$, $p=0.024$, variance RATES: $t(26)=-3.04$, $p=0.005$).

We concluded that among the tested models, our theory (specifically the PEIRS variant) was the best

explanation for the observed risk preferences (both distribution and difference between conditions). None

of the other models provided a convincing alternative explanation.

Model fit

After showing that the PEIRS model can reproduce the risk preferences that we measured, we wanted to

use model comparison techniques to test more formally whether our dataset provides evidence for or

against the PEIRS / PIRS models. One might be tempted to do this by simply comparing all candidate

models directly and selecting the best fitting one as the winner. However, this is not the right strategy

here. Consider for example a population with strongly concave utility functions and, in addition, moderate

PEIRS. A direct comparison between a utility model and a PEIRS model would favor the utility model

for this population, even though PEIRS was present. More generally, if it is possible that more than one of

the considered effects (nonlinear utility, variable learning rates, PEIRS / PIRS) is present in the same

participant, a direct model comparison between the effects will only determine the largest effect. It cannot

tell us whether effects are there or not.

The correct way to test whether there is PEIRS in our dataset is to compare models with PEIRS (extended

models) against models without PEIRS (base models). This should be done for different base models, as

they constitute different alternative explanations. We therefore performed a fit for all conventional models

(RW, concave UTIL, s-shaped UTIL, pos-neg RATES, variance RATES), and for each fit computed the

Bayesian Information Criterion (BIC) across the entire population. We then added the PEIRS mechanism

to each of these models, performed a fit with the extended models, and again computed the BIC across the

population. Finally, we compared the BICs with and without the PEIRS extension. We repeated the same

analysis with PIRS as well.

We found that adding the PEIRS extension improved parsimony for all but one model (variance RATES,

Fig 3C), and that adding PIRS improved all models (Fig 3D). This suggests that PIRS and PEIRS tend to

improve model fits enough to compensate for increased complexity, and hence capture some non-trivial

feature of the data that the other models cannot capture.

We concluded that in all but one case, our theory helps to explain empirical data better than existing

theories. The variance RATES model was not improved by PEIRS, perhaps because it already reproduced

the distribution of risk-preferences fairly well (Fig 3A, variance RATES). However, variance RATES

predicted an effect size that differed significantly from the empirical one (Fig 3B) and was improved by

the PIRS extension (Fig 3D). This suggests that variable learning rates cannot capture all features within

the realm of our theory.

Finally, we considered the possibility that prediction errors might influence choices even across trials—

that the outcome prediction error of one trial might induce risk preferences in the next. To test this, we

defined another model, called Outcome Errors Induce Risk Seeking (OEIRS) and performed an analysis

similar to Fig 3C and 3D. We found no evidence for across trial effects, likely due to comparatively large

delays (Fig S3, see supplementary discussion). This negative result is interesting in itself, but also

provides additional confidence for our positive results for PEIRS and PIRS—these models did not simply

win because they had the more parameters (PEIRS, PIRS and OEIRS have the same number of

parameters), but because they explained the data better.

Pupillometry

Above, we used choice data to look for the effects we predicted, and computational modelling to rule out

alternative explanations. In this section, we use an additional physiological marker—pupil dilation—to

provide additional evidence for our hypothesis. It is known that pupils dilate in response to surprise

(Preuschoff, t Hart et al. 2011, Cavanagh, Wiecki et al. 2014, Browning, Behrens et al. 2015, Lawson,

Mathys et al. 2017). This means that they allow an indirect readout of the magnitude of prediction errors,

since outcomes that are further from the prediction are more surprising.

We exploit this in three steps: first, we confirm that we can read out the magnitude of prediction errors by

computing the pupil response to the well documented outcome prediction errors. Second, we prove the

occurrence of stimulus prediction errors by extracting the corresponding pupil response. Finally, we show

that the strength of the stimulus prediction error, as measured through pupil dilation, is connected to the

strength of risk seeking extracted from choices.

Pupil dilation reflects outcome prediction errors

Can we measure prediction error magnitude through pupil dilation? To test this, we took the absolute

value of the outcome prediction error $|\delta_{outcome}|$ as a measure of surprise. Trial-by-trial estimates of this

prediction error were extracted from the PEIRS model fits. Regression analyses were used to determine

whether pupil dilation after reward presentation encoded $|\delta_{outcome}|$. In this analysis, we focused on the

first half of the block (trials 1 to 60) where the learning from feedback occurs (Fig 2A). We found a

phasic response which peaked 0.9 s after reward presentation (Fig 4A t-test: t(26) = 4.61, p = 0.0001;

statistical significance was established through leave-one-out unbiased peak detection and confirmed

through a cluster-based permutation test, see Fig S4A). This confirmed pupil dilation as a proxy for

prediction error magnitude.

Fig 4: Pupil responses to prediction error magnitude index behavioral effects

A) Pupil dilation encodes the magnitude of the outcome prediction errors in the first half of the block

(trials 1 -60). The blue line and shading represent mean and SE across participants of the regression

coefficients obtained from a linear model. Pupil dilation was predicted from trial-by-trial estimates of

outcome prediction errors, obtained from the fitted PEIRS model. Responses were aligned at reward

presentation. For display, the trace was smoothed using spline interpolation.

B) Pupil dilation encodes the magnitude of the stimulus prediction errors in the second half of the block

(trials 61 - 120). Similar to A), with pupil dilation predicted from trial-by-trial estimates of stimulus

prediction errors. Responses were aligned at stimulus presentation but truncated before the time of the

outcome.

C) Effect strength in behavior predicts effect strength in pupil dilation. The plot shows the correlation

between $BIC_{RW} - BIC_{PEIRS}$ (x-axis) and the regression coefficient for the stimulus prediction error as a

predictor of pupil dilation, at time of maximum effect strength (y-axis), which was determined using a

leave-one-out procedure.

Pupil dilation confirms occurrence of stimulus prediction errors

Next, we sought to confirm the occurrence of stimulus prediction errors, which are essential for our

theory of prediction-error induced risk seeking. For this, we extracted estimates of $\delta_{Stimulus}$ V for every

trial and used an analysis similar to the previous step to extract the corresponding pupil response. Here,

we aligned the pupil signal at stimulus presentation, and censored all data points collected after reward

presentation to avoid confounding factors such as reward or outcome prediction errors. We also focused

on the second half of the block (trials 61 to 120) where we observe pronounced risk preferences (Fig 2B).

We found a phasic response which peaked 1.6 s after stimulus onset (Stimulus prediction error: Fig 4B; t-

test: $t(26) = 2.89$, $p = 0.0079$. Statistical significance was established through leave-one-out unbiased

peak detection and confirmed through a cluster-based permutation test, see Fig S4B). This confirms the

existence of a stimulus prediction error that occurs after stimulus onset, as hypothesized.

The response to the stimulus prediction error was roughly similar to the response to the outcome

prediction error, except for a longer delay between stimulus prediction error onset and the peak of the

pupil response. There might be many reasons for this difference in delay. Among those, differences in

information processing might play a role: generating a stimulus prediction error involves two stimuli,

hence attention mechanisms, in addition to retrieval of value estimates from memory. Generating the

outcome prediction error, on the other hand, just requires the processing of a number.

Stimulus prediction errors are linked to risk seeking

Our theory suggests that risk seeking is caused by transiently increased dopamine levels that reflect

reward prediction errors, specifically the stimulus prediction error. If this is the case, we should expect to

see stronger risk preferences in individuals that respond stronger to stimulus prediction errors.

We tested this using individual behavior and pupil responses. To quantify the strength of prediction error

induced risk preferences in behavior, we used the difference in BIC computed from the RW fit and the

PEIRS fit (see Results/Modelling). This difference is a measure of evidence for the PEIRS model over the

RW model, and hence reflects the overall strength of the effects of interest. The strength of the pupil

response was quantified through the regression factor's t-statistic at the time of strongest effect

(determined though leave-one-out peak detection to avoid bias). Using a linear model to relate pupil effect

strength and behavioral effect strength, we found that participants responded stronger to stimulus

prediction errors if they showed more pronounced prediction-error induced risk seeking in their behavior

(Fig 4C, adjusted R^2: 0.23, p = 0.008). This confirmed our prediction, thus providing additional evidence

to our explanation.

Discussion

Different behavioral phenomena—learning from prediction errors and biased risk-preferences–are attributed to the same neurotransmitter, dopamine. Based on this, we first developed a model that predicts shifts in behavioral risk preference as a function of reward prediction errors. Second, we tested it using a task where reward prediction errors are immediately followed by decisions that involve risk. We found that reward prediction errors and the probability of subsequent risk-taking are positively correlated: positive reward prediction errors induce risk seeking, negative ones inhibit it. Finally, we showed that the magnitude of the reward prediction error (as indexed by pupil dilation) determines its effect on risk-preferences.

Our results are consistent with our initial hypothesis: the two roles of dopamine (teaching signal and risk modulator) interfere with each other. This study hence provide evidence *against* the conjecture that the roles of dopamine are well separated. That conclusion fits in well with other recent findings: it has been shown that phasic dopamine correlates with motivational variables (Hamid, Pettibone et al. 2016) and movement vigor (da Silva, Tecuapetla et al. 2018) just as well as with reward prediction errors. Together, these findings cast doubt on the separation into tonic and phasic and on separations in general.

Predictions or Prediction errors?

In our theoretic analysis, we considered two possibilities for how the stimulus PE might be calculated: the first possibility was to take the difference between value of the options and the overall average reward. This was codified in the PEIRS model. The other possibility was to take the difference between the value of the options and zero, which corresponded to no reward expectation during the ITI. This was codified in the PIRS model, which is short for Predictions Induce Risk Seeking. We called it as such because in this case, there is no way to distinguish between prediction and prediction error. Our task design in general is not suitable to empirically differentiate between these two possibilities, because predictions and prediction errors are strongly correlated at stimulus presentation. We did not aim to empirically

distinguish the two mechanisms, but rather, to show that either of these mechanisms explains our data

better than alternative explanations (with one exception, see Fig 3C and D). Differentiating between the

two mechanisms is an interesting direction for future work.

Another question that might arise in this context is about the role of the outcome prediction error of the

previous trial. According to our theory, that prediction error should be broadcasted by the dopamine

system just like the stimulus prediction error and might therefore also affect risk preferences. Of course,

there is a difference in timing: the choice follows the outcome prediction error of the previous trial with

3.47 s delay on average (standard deviation 0.51). In contrast, there is only an average delay of 0.97 s

(standard deviation 0.51) between stimulus onset and choice. We might thus expect that the impact of the

outcome prediction error, if at all observable, might be much weaker than that of the stimulus prediction

error. A supplementary analysis similar to those displayed in Fig 3C and 3D confirmed this: there is no

evidence for an association of risk preferences and outcome prediction error of the previous trial in our

dataset (Fig S3).

Relation to behavioral economics

Decision making under uncertainty has been extensively studied in behavioral economics. One main

finding in this field, codified in prospect theory, is that humans tend to be risk-averse if decisions concern

gains, and risk-seeking if decisions concern losses (Kahneman and Tversky 2013). However, those classic

findings rely on explicit knowledge about the probabilities involved in the decisions. Several more recent

studies indicate that those tendencies reverse when risks and probabilities are learned from experience

(i.e., by trial and error): if learning is incremental and based on feedback, humans tend to make risky

decisions about gains and risk-averse decisions about losses (Wulff, Mergenthaler-Canseco et al. 2018).

This phenomenon has been termed the description-experience gap and is considered a "major challenge"

for neuroeconomics (Garcia, Cerrotti et al. 2021). In cognitive neuroscience and psychology, some

studies have reproduced this phenomenon (Madan, Ludvig et al. 2014), while others report risk aversion

in the gain domain (Niv, Edlund et al. 2012).

Our task differs somewhat from the tasks studied in the description-experience gap literature, since we

only use gains (reward points are always positive). However, it is also known that humans often evaluate

outcomes with respect to a reference point (Kahneman and Tversky 2013). In the context of our task, it

seems plausible that rewards are evaluated relative to the average of previous rewards, or relative to the

middle of the experienced reward range, which rapidly converges to 50 points within the first few trials.

Rewards under 50 (and hence the majority of the rewards that result from choosing stimuli 3 and 4) would

then be considered losses. Decisions between the two low-valued stimuli (both-low condition), would fall

in the loss domain. Under this perspective, our results are in line with the description-experience-gap, and

differ to those of (Niv, Edlund et al. 2012). This might be due to the degree of implicitness of the

knowledge that is gained during the task: Niv et al. used classical bimodal reward distributions (e.g., 40

points with probability 50 %, 0 points otherwise) which participants might be able to recognize as such

after a few trials. Here, we used high-entropy reward distributions (normal distributions, see Fig. 1B),

which could not be mapped onto bimodal gambles, and thus made anything but implicit learning

intractable.

Relation to other theories

For our behavioral results, interpretations other than our dopaminergic explanation may be evoked: the

behavior in a similar task (Madan, Ludvig et al. 2014) was interpreted as the result of memory replay:

experiences ("Obtained reward X after choosing option Y") might not only be used for immediate value

updates but might also be stored in a memory buffer. This buffer can then be used for offline learning

from past experiences in times of inactivity, such as during the inter-trial interval. It was proposed by

(Madan, Ludvig et al. 2014) that experiences are more likely to enter the buffer if they are extreme. If

entering the buffer is biased in this way, then so are the values learned from replaying those experiences.

In our task, extreme might mean that the reward was extremely high or low. The corresponding bias

would drive choice towards the stimuli that produce the highest rewards, and away from those that

produce the lowest, and thereby lead to a pattern similar to the one we observed.

Which theory is closer to the truth? One relevant piece of data is the gradual emergence of the risk

preferences (Fig 2B). We detailed above that our theory predicts slowly emerging risk preferences. In

particular, risk preferences should emerge after value preferences. The memory theory, on the other hand,

holds that risk preferences stem from biased values. If that was the case, risk preferences should emerge

at the same rate as value preferences, which is not what we observed.

Beyond this, it is difficult to compare the memory theory directly to prediction-error induced risk-

seeking; it is unclear how to obtain trial-by-trial choice predictions from the memory model, which rules

out a formal model comparison. Indeed, the memory model has so far only been fitted to and assessed

based on summary statistics of a large collection of trials. Further, the memory model has so far not been

equipped with a mechanistic underpinning and was therefore not validated on physiological variables

such as pupil dilation. In contrast, prediction-error induced risk-seeking can be fitted trial-by-trial,

allowing it to make predictions not only about summary statistics but about the evolution of preferences

during the task as well as about the immediate impact of extreme events such as large prediction errors.

The corresponding latent variables can be correlated with physiological variables, proving that they can

explain aspects of pupil dilation in addition to behavior (Fig. 4C and 4D).

Further experimental predictions

In this paper, we present a theory based on neural effects, and test some of its behavioral predictions. The

results could have falsified our theory, but they did not—all our predictions where confirmed. This

suggests that our theory is valid on the level of behavior, but it does not prove that our theory is correct on

the level of neural mechanisms. More direct measurements are needed to establish this.

Correlational studies are possible. They should have sufficient time resolution to differentiate the

prediction errors at different times during the trial, such as EEG, electrophysiology, voltammetry or

similar. With those, one could gain more direct measurements of the PEs, and hence resolve more clearly

how they are associated with subsequent risk seeking. Another possibility are causal studies. For example,

optogenetic tools could be used to elicit or suppress prediction errors just before choices involving risk,

for instance by stimulation VTA dopamine neurons at the time of stimulus onset.

Conclusion

In summary, we demonstrate that a biologically inspired theory of basal ganglia learning predicts an

interaction between prediction errors and risk seeking. This is based on dopamine's dual role in learning

and action selection. We present behavioral data that matches these predictions. We further show that

between-participant variability in behavior can be linked to differences in pupil responses—the stronger

the pupil response to stimulus prediction errors, the stronger the prediction error induced risk seeking.

Methods

Participants

We tested 30 participants (15 female, median age: 26, range: 18-42). Our participants did not suffer from visual, motor or cognitive impairments. Participants were recruited from the Oxford Participant Recruitment system and gave informed written consent. All experimental procedures were approved by the Oxford Central University Research Ethics Committee, approval number R45265/RE004.

Participants were given a written set of instructions, as well as an oral instruction. They were first provided with a description of the task sequence. Then, they were told that the rewards were random, but nevertheless higher on average for some shapes than for others. Finally, they were advised to get as much total reward as possible and that their compensation would be between 8 and 12 GBP, depending on their performance. After the task, all participants received a compensation of 10.50 GBP.

Our results are based on 27 of the 30 participants. Three participants were excluded from the analysis due to their failure to understand the task: we evaluated the participants' understanding of the task by scoring their preferences in different-mean choices during the second half of the blocks. Participants were included in the analysis if they chose the high-valued option in more than 70 % of those trials (Fig S1).

Emerging preferences

To test whether value preferences emerged faster than risk preferences, we used a linear mixed effects model to model choices. As predictors, we included fixed effects of decision type, trial number, and their interaction. Here, decision type was defined as value decision (difference condition) versus risk decision (both-high and both-low conditions). We also included random effects for all predictors and a random intercept, by participant. A likelihood ratio test for the fixed effect of the interaction between trial number and decision type revealed a significant positive effect ($p < 0.001$; based on comparing the empirical likelihood to a distribution of likelihoods obtained from 1000 Monte Carlo simulations of data from the

model without the fixed effect, as implemented in MATLAB's 'compare' function). This confirms value

preferences emerged faster than value preferences (Fig 2A and 2B).

Models

The models we used in this study are all variants of the RW model (Rescorla and Wagner 1972). They

consist of learning rules for latent variables, such as value and spread, and choice rules that convert latent

variables into choice probabilities. Below, we provide these rules for all models, along with some

auxiliary rules as necessary.

For all models, $i \in \{1,2,3,4\}$ is the stimulus index, and Q_i is the value of stimulus i. The index j is used

for the options on screen in each trial (for example, $j = \{1,3\}$ if stimuli 1 and 3 are shown). The initial

values at the beginning of each block are denoted by Q_0. The update rules are only applied to the values

and spreads of the chosen stimuli; the values and spreads of unchosen stimuli do not change. The

probability of choosing stimulus i is denoted by p_i, the received reward is denoted by r.

<u>*RW*</u>

In the RW model, learning is driven by differences $\delta_{outcome}$ between the reward expected and received:

640
$$\delta_{outcome} = r - Q_{chosen}$$

641   Eq. 6

642
$$\Delta Q_{chosen} = \alpha \times \delta_{outcome}$$

643   Eq. 7

644   Here, α denotes the learning rate. Learned values were linked to choice probabilities via a standard

645   softmax rule (Daw 2011):

646
$$p_i = \frac{exp(\beta Q_i)}{\sum_j exp(\beta Q_j)}$$

647   Eq. 8

648   The RW model has free parameters $\alpha \in [0,1]$, $\beta > 0$ and fixed parameters $Q_0 = 50$.

649   *Concave utility*

650   To allow for concave subjective utility of reward points in our experiment, we used an exponential family

651   of functions (Guyaguler and Horne 2001), which we adapted to our reward range through appropriate

652   scaling (σ) and shifting (m):

653 $$z = \frac{r - m}{\sigma}$$

654                                      $$U = m + \sigma \times \frac{1 - exp(-k_{concave}z)}{k_{concave}}$$

655   The nonlinear utility of reward enters through the computation of the prediction error:

656 $$\delta_{coutcome} = U - Q_{chosen}$$

657   Eq. 10

Updates are computed with Eq. 7, choices are modeled using the softmax rule in Eq. 8. The concave

UTIL model has free parameters $\alpha \in [0,1]$, $\beta > 0$, $k_{concave} > 0$. and fixed parameters $Q_0 = 50$, $\sigma = 50$,

$m = 50$.

S-shaped Util

Utilities can also be s-shaped, with different curvatures on both sides of a reference point (Kahneman and

Tversky 2013). We modelled s-shaped utility functions using sign-preserving power functions (Spitzer,

Waschke et al. 2017), which we adapted to our reward range:

665 $$z = \frac{r - m}{\sigma}$$

666                                      $$U = m + s \times sign(z)|z|^{k_{s-shaped}}$$

Prediction errors are calculated as in Eq. 10, updates happen according to Eq. 7, choices are modeled

using the softmax rule in Eq. 8. The s-shaped UTIL model has free parameters $\alpha \in [0,1]$, $\beta > 0$,

$k_{s-shaped} \in [0,1]$ and fixed parameters $Q_0 = 50$, $\sigma = 50$, $m = 50$.

Different learning rates for positive and negative prediction errors

It has been shown that learning from positive outcomes can differ from learning from negative outcomes

(Gershman 2015). We model this by letting the learning rate depend on the sign of the prediction error

(computed according to Eq. 6). The update rules then become:

674
$$\alpha(\delta) = \begin{cases} \alpha_+ \ if \ \delta > 0 \\ \alpha_- \ if \ \delta < 0 \end{cases}$$

675
$$\Delta Q_{chosen} = \alpha(\delta_{outcome}) \times \delta_{outcome}$$

Choices are modeled using the softmax rule Eq. 8. The pos-neg RATES model has free parameters $\alpha_+ \in$

$[0,1]$, $\alpha_- \in [0,1]$, $\beta > 0$, and fixed parameters $Q_0 = 50$.

Different learning rates for noisy and save stimuli

Similarly, it has been shown that the statistics of the reward distribution can have an effect on the learning

rate (Daw, O'doherty et al. 2006, Behrens, Woolrich et al. 2007). In our task, normative theory (Welch

and Bishop 1995) suggests that the learning rate should depend on the variance of the signal that is being

learned. We model this by allowing different learning rates for different levels of noise. The update

equations become:

684
$$\alpha_i = \begin{cases} \alpha_{risky} \ if \ i \in \{1,3\} \\ \alpha_{safe} \ if \ i \in \{2,4\} \end{cases}$$

685
$$\Delta Q_{chosen} = \alpha_{chosen} \times \delta_{outcome}$$

Prediction errors are computed according to Eq. 6, choices are modeled using the softmax rule in Eq. 8.

The pos-neg RATES model has free parameters $\alpha_{risky} \in [0,1]$, $\alpha_{safe} \in [0,1]$, $\beta > 0$, and fixed

parameters $Q_0 = 50$.

PEIRS

Our model of prediction error induced risk seeking is based on recent models of the basal ganglia

(Mikhael and Bogacz 2016, Möller and Bogacz 2019). The relevant equations have been derived in

section Results/Theory. They describe how the average and the spread S of a reward signal can be tracked.

Here, S_i denotes the spread of the spread of the rewards received for choosing stimulus i. The update

equations for value are given as:

695
$$\Delta Q_{chosen} = \alpha_Q \times \delta_{outcome}$$

696   Eq. 11

697 With the outcome prediction error from Eq. 6. The update equation for spread is given as:

698
$$\Delta S_{chosen} = \alpha_S(|\delta_{outcome}| - S_i)$$

699   Eq. 12

700 The choice rule is a variant of the softmax rule in Eq. 8:

701
$$p_i = \frac{exp(\beta(Q_i + \gamma\delta_{stimulus}S_i))}{\sum_j exp(\beta(Q_j + \gamma\delta_{stimulus}S_j))}$$

702   Eq. 13

703 Here, spreads can contribute to decisions. The impact of spread on choice probability is gated by the

704 stimulus prediction error:

705
$$\delta_{stimulus} = \frac{1}{2}(Q_{option1} + Q_{option2}) - \frac{1}{4}\sum_i Q_i$$

The PEIRS model has free parameters $\alpha_Q \in [0,1]$, $\alpha_S \in [0,1]$, $\beta > 0$, γ $S_0 > 0$ and fixed parameters

$Q_0 = 50$. The initial spread estimate S_0 was allowed to vary since participants were not given no prior

information about the spread magnitude. Initial estimates might thus have differed strongly across

individuals.

PIRS

In another variant of the PEIRS model predictions induce risk seeking. It differs from PEIRS only in how

the stimulus prediction error is computed:

714
$$\delta_{stimulus} = \frac{1}{2}\left(Q_{option1} + Q_{option2}\right)$$

The above formula is used instead of Eq. 14. Updates and choices are governed by Eq 11, 12 and 13. The

PIRS model has free parameters $\alpha_Q \in [0,1]$, $\alpha_S \in [0,1]$, $\beta > 0$, γ, $S_0 > 0$ and fixed parameters $Q_0 = 50$.

OEIRS

If risk-preferences are associated with stimulus prediction errors, they might also be associated with

outcome prediction errors from the previous trial. This is the assumption of the OEIRS model, which

differs from the PEIRS model in that the outcome prediction error $\delta_{outcome}$ (computed according to Eq.

6) is substituted for $\delta_{stimulus}$ in Eq. 13. Otherwise, OEIRS is identical to PEIRS and PIRS.

Parameter transformations and Priors

We used exponential and sigmoid transformations to constrain the parameters to their appropriate ranges.

Priors were specified as multivariate normal distributions over the untransformed parameters. All but

diagonal elements of the covariance matrices of those normal distributions were set to zero. Hence, the

prior distributions could be factorized into univariate normal distributions (one for each parameter).

Below, we provide the statistics of those prior distributions. For parameters that occur in more than one

model (such as learning rate α), we used the same priors across models. The notation $X \sim N(\mu, \sigma)$ means

that X has a normal distribution with mean μ and variance σ.

$$logit(\alpha) \sim N(-1,2)$$

$$log(\beta) \sim N(-2,2)$$

$$log(k_{concave}) \sim N(-3,4)$$

$$logit(k_{s-shaped}) \sim N(3,4)$$

$$logit(\alpha_+) \sim N(-1,2)$$

$$logit(\alpha_-) \sim N(-1,2)$$

$$logit(\alpha_{risky}) \sim N(-1,2)$$

$$logit(\alpha_{safe}) \sim N(-1,2)$$

$$logit(\alpha_S) \sim N(-1,2)$$

$$\gamma \sim N(0,20)$$

$$log(S_0) \sim N(2,2)$$

Fitting & Simulation

Fits were performed using the VBA toolbox (Daunizeau, Adam et al. 2014). This toolbox implements a

Variational Bayes scheme. It takes a set of measurements, a generative probabilistic model that describes

how the measurements arise (which usually contains some latent, i.e., unobserved, variables) and prior

distributions over the model parameters as input, and outputs among other things an approximate

posterior distribution over model parameters, an approximate posterior distribution over the latent

variables, and fit statistics such as the BIC. We estimated parameters and latent variables (such as values

and prediction errors) using the mean of the posterior distributions over parameters from the toolbox

outputs.

Simulations were performed with parameters taken from fits: for each model, a fit provided us with 27

parameter sets corresponding to the 27 participants. Using those parameter sets we simulated our task and

generated datasets of the same size as the dataset we obtained in our experiment. We repeated this 1000

times to obtain stable distributions. We extracted 27000 pairs of risk preferences per model from the

simulated datasets (27 simulated participants in each of 1000 simulated experiments). We then used a

kernel smoothing function to estimate the probability density underlying the distribution of risk

preferences (MATLAB's *ksdensity* function). Finally, we computed and visualized isolines of those

estimated probability densities using MATLAB's *contour* function (Fig 3A).

For Fig 3B, for each model we first computed the average difference in risk preference between

conditions for each simulated participant in each simulated experiment, yielding 27000 differences in risk

preference per model. We then averaged those across experiments, obtaining 27 differences in risk

preferences per model. Those distributions were compared to the empirical distribution of mean

difference in risk preference between conditions, which has 27 datapoints as well (one for each

participant).

Pupillometry

We recorded time series of pupil diameters for every trial, using an EyeLink 1000 system. For each

participant, the system was calibrated before the first block, and after subsequent blocks if required.

The raw measurements were screened for blinks, which were identified as missing values in the

recordings. Data points in the direct vicinity of blinks as well as data segments shorter than 50 ms were

removed. After cleaning, missing value segments of less than 400 ms were filled using linear

interpolation (Manohar 2019). Then, the traces were aligned to the relevant temporal markers (stimulus

onset, or reward onset). We used the mean over 500 ms prior to the alignment point to define a trial-wise

baseline. All traces were divided and shifted by that baseline, resulting in traces reflecting the relative

change of pupil diameter after the alignment point. Finally, traces were downsampled to 10 Hz.

Pupil responses to prediction errors were obtained using linear models: for each participant, we regressed

pupil dilation against a trial-by-trail estimate of the prediction error magnitude of interest, which was

obtained from a model fit. This was done for each time bin of the pupil signal and resulted in a pupil

response time course (beta weights and t-statistics as functions of time) for each individual. The

population response was computed as the average of individual responses.

To uncover the pupil response to the stimulus prediction error, we aligned the pupil time courses at

stimulus onset. After stimulus onset, participants would eventually make a choice (with variable delay,

the median reaction time was 0.86 s) and receive a reward (with a 1 s delay) after their choice. Since the

reward or the resulting outcome prediction error might confound our regression analysis, we censored out

all data after reward presentation. This means that the number of observations on which regressions can

be based rapidly declines after the median reward presentation time, which is at 1.86 s after stimulus

onset. Estimates obtained later are increasingly unreliable, since they are based on insufficient data. We

hence conducted our analyses for the interval 0 s to 1.9 s after stimulus onset. This allows us to obtain

reliable estimates of the statistics, while still avoiding confounding effects related to reward presentation.

To test whether the pupil responses to the prediction errors are statistically significant, we performed a

test at a single time-point corresponding to the peak of the effect. To avoid circularity, the time of the

peak was identified using a leave-one-out method: For each participant, we used the individual pupil

response time courses of all other participants to determine the time of the peak. This was achieved by

executing t-tests on the response strength (t-statistic) across participants in each time bin and selecting the

bin with the smallest p-value. We then took the left-out participant's response strength from that time bin,

considering it to be their response strength at the peak of the group response. In a final step, we pooled all

those individual response strengths and used a t-test to check whether they deviated significantly from

zero.

References

798 Behrens, T. E., et al. (2007). "Learning the value of information in an uncertain world." <u>Nature</u>
799 <u>neuroscience</u> **10**(9): 1214-1221.

800
801 Berke, J. D. (2018). "What does dopamine mean?" <u>Nature neuroscience</u> **21**(6): 787-793.

802
803 Björklund, A. and S. B. Dunnett (2007). "Dopamine neuron systems in the brain: an update." <u>Trends in</u>
804 <u>neurosciences</u> **30**(5): 194-202.

805
806 Bogacz, R. (2020). "Dopamine role in learning and action inference." <u>Elife</u> **9**: e53262.

807
808 Browning, M., et al. (2015). "Anxious individuals have difficulty learning the causal statistics of aversive
809 environments." <u>Nature neuroscience</u> **18**(4): 590-596.

810
811 Cavanagh, J. F., et al. (2014). "Eye tracking and pupillometry are indicators of dissociable latent decision
812 processes." <u>Journal of Experimental Psychology: General</u> **143**(4): 1476.

813
814 Chew, B., et al. (2019). "Endogenous fluctuations in the dopaminergic midbrain drive behavioral choice
815 variability." <u>Proceedings of the National Academy of Sciences</u> **116**(37): 18732-18737.

816
817 Collins, A. G. and M. J. Frank (2014). "Opponent actor learning (OpAL): Modeling interactive effects of
818 striatal dopamine on reinforcement learning and choice incentive." <u>Psychological review</u> **121**(3): 337.

819
820 da Silva, J. A., et al. (2018). "Dopamine neuron activity before action initiation gates and invigorates
821 future movements." <u>Nature</u> **554**(7691): 244-248.

822
823 Daunizeau, J., et al. (2014). "VBA: a probabilistic treatment of nonlinear models for neurobiological and
824 behavioural data." <u>PLoS Comput Biol</u> **10**(1): e1003441.

825
826 Daw, N. D. (2011). "Trial-by-trial data analysis using computational models." <u>Decision making, affect, and</u>
827 <u>learning: Attention and performance XXIII</u> **23**(1).

828
829 Daw, N. D., et al. (2006). "Cortical substrates for exploratory decisions in humans." <u>Nature</u> **441**(7095):
830 876-879.

831
832 Frank, M. J. (2006). "Hold your horses: a dynamic computational role for the subthalamic nucleus in
833 decision making." <u>Neural networks</u> **19**(8): 1120-1136.

835 Gallagher, D. A., et al. (2007). "Pathological gambling in Parkinson's disease: risk factors and differences
836 from dopamine dysregulation. An analysis of published case series." Movement disorders: official
837 journal of the Movement Disorder Society **22**(12): 1757-1763.

838
839 Garcia, B., et al. (2021). "The description–experience gap: a challenge for the neuroeconomics of
840 decision-making under uncertainty." Philosophical Transactions of the Royal Society B **376**(1819):
841 20190665.

842
843 Gerfen, C. R. and D. J. Surmeier (2011). "Modulation of striatal projection systems by dopamine." Annual
844 review of neuroscience **34**: 441-466.

845
846 Gershman, S. J. (2015). "Do learning rates adapt to the distribution of rewards?" Psychonomic bulletin &
847 review **22**(5): 1320-1327.

848
849 Gurney, K., et al. (2001). "A computational model of action selection in the basal ganglia. I. A new
850 functional anatomy." Biological cybernetics **84**(6): 401-410.

851
852 Guyaguler, B. and R. N. Horne (2001). Uncertainty assessment of well placement optimization. SPE
853 annual technical conference and exhibition, Society of Petroleum Engineers.

854
855 Hamid, A. A., et al. (2016). "Mesolimbic dopamine signals the value of work." Nature neuroscience **19**(1):
856 117-126.

857
858 Jang, A. I., et al. (2019). "Positive reward prediction errors during decision-making strengthen memory
859 encoding." Nature human behaviour **3**(7): 719-732.

860
861 Kahneman, D. and A. Tversky (2013). Prospect theory: An analysis of decision under risk. Handbook of
862 the fundamentals of financial decision making: Part I, World Scientific**:** 99-127.

863
864 Lawson, R. P., et al. (2017). "Adults with autism overestimate the volatility of the sensory environment."
865 Nature neuroscience **20**(9): 1293.

866
867 Madan, C. R., et al. (2014). "Remembering the best and worst of times: Memories for extreme outcomes
868 bias risky decisions." Psychonomic bulletin & review **21**(3): 629-636.

869
870 Manohar, S. (2019). Matlib: MATLAB tools for plotting, data analysis, eye tracking and experiment
871 design (Public).

872
Mikhael, J. G. and R. Bogacz (2016). "Learning reward uncertainty in the basal ganglia." PLoS
computational biology **12**(9): e1005062.

Möller, M. and R. Bogacz (2019). "Learning the payoffs and costs of actions." PLoS computational
biology **15**(2): e1006285.

Niv, Y. (2007). "Cost, benefit, tonic, phasic: what do response rates tell us about dopamine and
motivation?" Annals of the New York Academy of Sciences **1104**(1): 357-376.

Niv, Y., et al. (2012). "Neural prediction errors reveal a risk-sensitive reinforcement-learning process in
the human brain." Journal of Neuroscience **32**(2): 551-562.

Palminteri, S., et al. (2017). "The importance of falsification in computational cognitive modeling."
Trends in cognitive sciences **21**(6): 425-433.

Pessiglione, M., et al. (2006). "Dopamine-dependent prediction errors underpin reward-seeking
behaviour in humans." Nature **442**(7106): 1042-1045.

Preuschoff, K., et al. (2011). "Pupil dilation signals surprise: Evidence for noradrenaline's role in decision
making." Frontiers in neuroscience **5**: 115.

Rescorla, R. A. and A. R. Wagner (1972). "A theory of Pavlovian conditioning: Variations in the
effectiveness of reinforcement and nonreinforcement." Classical conditioning II: Current research and
theory **2**: 64-99.

Reynolds, J. N., et al. (2001). "A cellular mechanism of reward-related learning." Nature **413**(6851): 67-
70.

Schultz, W., et al. (1997). "A neural substrate of prediction and reward." Science **275**(5306): 1593-1599.

Seymour, B., et al. (2004). "Temporal difference models describe higher-order learning in humans."
Nature **429**(6992): 664-667.

Spitzer, B., et al. (2017). "Selective overweighting of larger magnitudes during noisy numerical
comparison." Nature human behaviour **1**(8): 1-8.

St Onge, J. R. and S. B. Floresco (2009). "Dopaminergic modulation of risk-based decision making."
Neuropsychopharmacology **34**(3): 681-697.

Steinberg, E. E., et al. (2013). "A causal link between prediction errors, dopamine neurons and learning."
Nature neuroscience **16**(7): 966-973.

Sutton, R. S. and A. G. Barto (2018). Reinforcement learning: An introduction, MIT press.

Voon, V., et al. (2006). "Prospective prevalence of pathologic gambling and medication association in
Parkinson disease." Neurology **66**(11): 1750-1752.

Weintraub, D., et al. (2010). "Impulse control disorders in Parkinson disease: a cross-sectional study of
3090 patients." Archives of neurology **67**(5): 589-595.

Welch, G. and G. Bishop (1995). An introduction to the Kalman filter, Citeseer.

Wise, R. A. (2004). "Dopamine, learning and motivation." Nature reviews neuroscience **5**(6): 483-494.

Wulff, D. U., et al. (2018). "A meta-analytic review of two modes of learning and the description-
experience gap." Psychological bulletin **144**(2): 140.