1 **Evaluating the sensitivity of functional connectivity measures to motion artifact**
2 **in resting-state fMRI data**
3

4 Arun S. Mahadevan[1], Ursula A. Tooley[6], Maxwell A. Bertolero[1], Allyson P. Mackey[7], Danielle
5 S. Bassett[1,2,3,4,5,8]
6
[1]Department of Bioengineering, School of Engineering & Applied Science, University of
Pennsylvania, Philadelphia, PA 19104 USA
[2]Department of Electrical & Systems Engineering, School of Engineering & Applied Science,
University of Pennsylvania, Philadelphia, PA 19104 USA
[3]Department of Physics & Astronomy, College of Arts & Sciences, University of Pennsylvania,
Philadelphia, PA 19104 USA
[4]Department of Neurology, Perelman School of Medicine, University of Pennsylvania,
Philadelphia, PA 19104 USA
[5]Department of Psychiatry, Perelman School of Medicine, University of Pennsylvania,
Philadelphia, PA 19104 USA
[6]Neuroscience Graduate Group, Perelman School of Medicine, University of Pennsylvania,
Pennsylvania, PA 19104, USA
[7]Department of Psychology, School of Arts and Sciences, University of Pennsylvania,
Philadelphia, PA, USA
[8]Santa Fe Institute, 1399 Hyde Park Rd, Santa Fe, NM 87501 USA
22

Abstract

Functional connectivity (FC) networks are typically inferred from resting-state fMRI data using the Pearson correlation between BOLD time series from pairs of brain regions. However, alternate methods of estimating functional connectivity have not been systematically tested for their sensitivity or robustness to head motion artifact. Here, we evaluate the sensitivity of six different functional connectivity measures to motion artifact using resting-state data from the Human Connectome Project. We report that correlation-based measures (Pearson and Spearman correlation) have a relatively high residual distance-dependent relationship with motion compared to coherence and information theory-based measures, even after implementing rigorous methods for motion artifact mitigation. This disadvantage of correlation-based measures, however, may be offset by their higher test-retest reliability and system identifiability. We highlight spatial differences in the sub-networks affected by motion with different FC metrics. Further, we report that intra-network edges in the default mode and retrosplenial temporal sub-networks are highly correlated with motion in all FC methods. Our findings indicate that the method of estimating functional connectivity is an important consideration in resting-state fMRI studies and must be chosen carefully based on the parameters of the study.

Keywords

Functional connectivity, correlation, coherence, mutual information, resting-state, motion

Introduction

Ever since the initial observation of correlations in spontaneous functional magnetic resonance imaging (fMRI) blood-oxygen level dependent (BOLD) signals acquired from subjects at rest, the field of resting-state functional connectivity has grown exponentially[1]. Functional connectivity has been used as a tool to explore large-scale features of human brain organization[2–6], how this organization changes over the course of development[7–13], and the association of such organization with individual behavior[14,15]. However, head motion artifact is a pervasive problem in functional connectivity analysis, decreasing certainty of findings and impacting subsequent interpretations. In-scanner head movements result in structured noise that leads to the spurious identification of putative functional connections, a problem further compounded by the fact that some individuals move systematically more than others[16]. Consequently, a number of research groups have developed statistical preprocessing methods to mitigate the impact of motion artifact; the development of such methods is an ongoing and active field of research in its own right[17–20].

While much effort has been directed toward developing effective denoising pipelines to mitigate motion artifact, the subsequent estimation of functional connectivity in fMRI data has remained fairly constant. Functional connectivity (FC) between brain regions is typically estimated through a Pearson correlation between the BOLD time series of two regions of interest (ROIs). However, functional connectivity is formally defined as any statistical relation between time series[21] and there exist many other statistical methods to compute similarity between time series. A few examples include coherence methods[22–24], which compute similarity in frequency space, and methods based on information theory[25–27], which quantify the amount of shared information between signals.

The performance of different FC estimation methods has been evaluated using generative models for a variety of neurophysiological data, including simulated BOLD signals[28,29]. These studies have typically focused on the ability of FC estimation methods to recover the underlying network structure from simulated BOLD data. Major findings include the success of full or partial correlation at recovering the underlying network structure in simulated data[28]. It is perhaps due to these results, and the associated ease of implementation, that correlation-based methods are so

popular in the field. Yet, very few studies have used real fMRI data to compare the differential

sensitivity or robustness of different FC estimation methods to motion artifact. The field awaits an

appraisal of different FC estimation approaches with regard to their ability to overcome the specific

type of noise introduced by motion artifact in fMRI data[16,30].

In the present study, we used resting state fMRI data from the Human Connectome Project (HCP)

to evaluate six different FC estimation methods: Pearson correlation, Spearman correlation,

coherence, wavelet coherence, mutual information in the time domain, and mutual information in

the frequency domain. The sensitivity of each of these methods to subject motion and their success

in identifying network structure was evaluated using four benchmarks: (a) correlations of subject

motion with edge weights after denoising (QC-FC correlations), (b) the distance-dependence of

QC-FC correlations, (c) the degree to which canonical brain systems could be identified through

modularity maximization, and (d) the extent to which the functional connectivity estimates could

be reproduced in successive scans (test-retest reliability). Collectively, these efforts serve to inform

our usage of FC estimation methods, and their relative strengths and weaknesses.

Methods

In order to evaluate the differential sensitivity of different FC estimation methods to motion, we

first applied common denoising pipelines to a large resting state dataset, estimated functional

connectivity matrices using 6 different methods, and finally compared the performance of each of

these estimates using a set of common quality control (QC) measures. Details of data

preprocessing, FC estimation, and QC measures are described below.

Data and preprocessing

In this study, we leveraged data from the S1200 release of the Human Connectome Project

(HCP)[31], a multi-site consortium that collected extensive MRI, behavioral, and demographic data

from a large cohort of over 1000 subjects. As part of the HCP protocol, subjects underwent four

separate resting-state scans, which included both left-right (REST1_LR, REST2_LR) and right-

left (REST1_RL, REST2_RL) phase encoding directions. All functional connectivity data

analyzed in this report came from these scans.

We preprocessed the ICA-FIX resting-state data provided by the Human Connectome Project,

which used 24-parameter regression followed by ICA+FIX denoising to remove nuisance and

motion signals[32,33]. In addition, we removed the mean global signal and bandpass filtered the time

series from 0.009 to 0.08 Hz. Further, we did not analyze subjects for whom greater than 50% of

frames had a framewise displacement above 0.2 millimeters or a derivative root mean square above

75, leaving 802 subjects from REST1_LR, 820 from REST1_RL, 798 from REST2_LR, and 790

from REST2_RL. This threshold was chosen because it is typical for analyses of functional

connectivity, and we wanted our conclusions about motion and functional connectivity to apply to

common analysis pipelines[34–37].

For each scan, we used the mean relative RMS (root-mean squared) displacement during

realignment using MCFLIRT, provided by the Human Connectome Project, as our primary

measure of motion. Summary statistics of the cohorts analyzed and their head motion are shown

in Table 1.

Table 1. Summary statistics of motion in cohort from HCP S1200 release

Scan	REST1_LR	REST1_RL	REST2_LR	REST2_RL
Number of subjects analyzed (n)	802	820	798	790
Mean relative RMS motion (average)	0.078	0.077	0.078	0.079
Mean relative RMS motion (standard deviation)	0.022	0.021	0.021	0.023

From the preprocessed data, we estimated mean BOLD time series using two cortical parcellation

schemes: the 333-node Gordon parcellation[38] and the 100-node Schaefer parcellation[35]. For all

scans, the MSMAII registration was used, and the mean time series of vertices on the cortical

surface (fsL32K) in each parcel was calculated.

Description of functional connectivity measures

In the present study, we evaluated 6 different methods for estimating functional connectivity from

BOLD time series data. Here we provide a brief overview of the methods evaluated.

Pearson's correlation coefficient

The Pearson correlation coefficient is a simple and ubiquitous method to evaluate linear correlation

between two time series as the covariance between the two signals over time divided by the product

of their standard deviations. The zero-order (without lag) Pearson correlation, ρ_{ij}, between the

signals of regions i and j is given by

136
$$\rho_{ij} = \frac{cov_{ij}(t)}{\sqrt{var_i(t).var_j(t)}}.$$

Note that ρ_{ij} varies in the interval [-1, 1] with positive values indicating positive correlation and

negative values indicating negative correlation.

Spearman's rank correlation coefficient

This method evaluates the rank correlation between two time series, providing an estimate of the

extent to which one time series is a monotonic function of the other. The zero-order Spearman

rank correlation, r_{ij}, between the signals of regions i and j is given by the Pearson correlation

between their respective rankings,

146
$$r_{ij} = \rho_{R_i,R_j} = \frac{cov(R_i, R_j)}{\sqrt{var(R_i).var(R_j)}},$$

where R_i and R_j are the rankings of the individual time series from low to high values. Note that

r_{ij} varies in the interval [-1, 1] with $r_{ij} = +1$ indicating a perfect monotonic relationship between

the time series of region i and the time series of region j.

Mutual information (time domain)

The mutual information is a statistical measure of the shared information between two time series.

The information content of a given time series $X(t)$ can be defined through its Shannon

entropy[25,26], which is given by

155
$$I(X) = -\sum_{i=1}^{M} p_i.lnp_i,$$

156 where $X(t)$ is partitioned into M bins, with p_i representing the probability of the i-th bin. Now,

157 the joint entropy between $X(t)$ and a second time series $Y(t)$ is defined as

158
$$I(X,Y) = -\sum_{i,j} p_{ij}^{XY} \ln p_{ij}^{XY},$$

159 where p_{ij}^{XY} is the joint probability of $X = X_i$ and $Y = Y_i$. The mutual information between X and

160 Y is then,

161
$$MI(X,Y) = I(X) + I(Y) - I(X,Y).$$

163 In order to obtain values in the range [0, 1], we computed the normalized mutual information[39] as

164
$$NMI = \frac{MI(X,Y)}{\sqrt{I(X).I(Y)}}.$$

Thus, the normalized mutual information between two independent signals is 0 and has a

maximum of 1 for identical signals. While the Pearson and Spearman correlation coefficients

measure linear and monotonic relationships, respectively, the mutual information is a statistical

measure of both linear and non-linear relationships between time series.

Coherence

Coherence is a measure of the cross-correlation between two signals in the frequency domain. At

a given frequency λ, the coherence between the signal of region i and the signal of region j is

given by

174
$$C_{ij}(\lambda) = \frac{|f_{ij}(\lambda)|^2}{f_{ii}(\lambda).f_{jj}(\lambda)},$$

where $f_{ij}(\lambda)$ is the cross-spectral density between signals i and j, and $f_{ii}(\lambda)$ and $f_{jj}(\lambda)$ are the

auto-spectral densities of signal i and j, respectively. Note that $C_{ij}(\lambda)$ varies in the interval [0, 1].

We evaluated coherence using the MATLAB toolbox for functional connectivity[40], in which

spectral densities are calculated using Welch's averaged, modified periodogram method.

Wavelet coherence

Wavelet coherence is a measure of the correlation between two signals in the time-frequency

space. It is calculated in a similar manner to coherence, but spectral densities are calculated by

convolving time series with wavelet functions such as the Morlet wavelet function, which expand

the signal in time-frequency space. We evaluated wavelet coherence using the Grinsted toolbox[41].

Mutual information (frequency domain)

Mutual information can also be evaluated based on coherence in the frequency domain[27], defined

for a given frequency range $[\lambda 1, \lambda 2]$ as

189
$$\delta_{ij} = \frac{1}{2\pi} \int_{\lambda 1}^{\lambda 2} log\left(1 - C_{ij}(\lambda)\right) d\lambda \, .$$

190   With a simple transformation, a normalized mutual information in the range [0, 1] can be obtained

191   as

192
$$\emptyset_{ij} = \left[1 - exp\left(-2\delta_{ij}\right)\right]^{\frac{1}{2}} \, .$$

We used the implementation provided in the MATLAB toolbox for functional connectivity[40].

Overview of functional connectivity estimation

Using the 6 measures described above, we estimated functional connectivity between each pair of

preprocessed BOLD times series, resulting in $n \times n$ matrices for each subject, where n is the

number of parcels in the parcellation scheme. The estimated networks provide a description of

interactions (edges) among brain regions (nodes) that can then be probed for various features of

interest using network science[42].

The 6 metrics evaluated can be broadly classified into categories based on their mode of operation.

Pearson, Spearman, and mutual information (time) work in the time domain, whereas coherence

and mutual information (frequency) work in the frequency domain, and wavelet coherence works

in time-frequency space. For all the frequency-based methods, we evaluated the average

connectivity in the frequency range [0.009Hz, 0.08Hz], which is the same frequency range at

which all resting-state scans were bandpass filtered. It is to be noted that while Pearson and

Spearman correlations fall in the interval [-1, 1], all the other metrics fall in the interval [0, 1]

(Table 2).

Correlation matrices are typically subjected to Fisher's r-to-z transformation to normalize the

range of values. Figure S1 shows that results do not change significantly when the transform is

applied to the correlation matrices. Therefore, we report results in the main text without performing

Fisher transforms on any of the matrices, in order to facilitate a more direct comparison between
methods.
218
219 *Table 2. Overview of functional connectivity estimation measures, their range and domain of operation*

Domain	Metric	Range
Time	Pearson correlation	[-1,1]
	Spearman correlation	[-1,1]
	Mutual Information (time)	[0,1]
Frequency	Coherence	[0,1]
	Mutual Information (frequency)	[0,1]
Time-frequency	Wavelet Coherence	[0,1]

Overview of outcome measures

We evaluated the sensitivity of each FC metric to subject motion using four benchmarks: residual
QC-FC correlations, distance-dependence of QC-FC correlations, test-retest reliability, and the
modularity quality index.

Residual QC-FC correlations
Quality control-functional connectivity (QC-FC) correlations are a widely used benchmark
measure to evaluate the efficacy of denoising pipelines applied in resting-state fMRI connectivity
analysis[17,18]. Here we used this benchmark to evaluate residual motion artifact for each of the
functional connectivity estimates after application of a common denoising pipeline. First, we
computed functional connectivity based on the 6 metrics described in the previous section, for the
333-node Gordon and 100-node Yeo parcellation schemes. We then computed the partial
correlation between functional connectivity estimates for each edge and the relative mean RMS
motion of each subject, controlling for subject age and sex, thus obtaining a distribution of edge-
specific correlations with subject motion. From this distribution, we computed the percentage of
edges for which the QC-FC correlations were statistically significant ($p < 0.05$, no correction for
multiple comparisons).

Distance-dependence of QC-FC correlations

Motion artifact has been known to have a distance-dependent effect on FC estimates, for instance

inflating the estimated strength of short-distance connections and reducing the estimated strength

of long-distance connections[16,43]. To quantify this effect, we measured the correlation between the

absolute values of QC-FC correlations (see above section) and the Euclidean distance separating

the centroids of the node pair associated with each edge. This correlation served as a benchmark

for the distance-dependence of the residual motion artifact.

Test-retest reliability

To evaluate the reliability of functional connectivity estimates, we computed the intra-class

correlation (ICC) across different resting-state scans performed on the same subject in the HCP

dataset. The intra-class correlation coefficient ρ is defined[44] as

252
$$\rho = \frac{MS_b - MS_w}{MS_b + (n-1)MS_w},$$

where MS_b is the between-subject mean square strength of each edge, MS_w is the within-subject

mean square strength of each edge, and n is the number of scans per subject, which in this case is

4.

System identifiability

To evaluate the possibility that more motion-resilient FC metrics might enable better detection of

signals of interest, we consider the outcome measure of system identifiability[17,45,46]. We use the

term system to refer to a set of brain regions that are strongly functionally connected; and we use

the phrase system identifiability to refer to the ease with which such systems can be detected from

functional connectivity matrices. We employed the modularity quality index, *Q,* as a measure of

system identifiability. The modularity quality index is a quantification of the extent to which a

network can be subdivided into groups or modules characterized by strong intramodular

connectivity and weak intermodular connectivity. Such modularity is indicative of the assortative

community structure commonly found to be present in functional brain networks[47,48].

We estimated the modularity quality index for each subject's network by maximizing the

modularity quality function originally defined by Newman[45] and subsequently extended to

weighted and signed networks by Rubinov and Sporns[49], among others[50,51]. For FC metrics

resulting in weights falling within the interval [0,1], or results estimated from the absolute value

of edge weights, we employed the weighted generalization of the modularity quality index. We

first let the weight of a positive edge between nodes i and j be given by a_{ij}^{+}, and the strength of a

node i, $s_i^{\pm} = \sum_j a^{\pm}ij$, be given by the sum of the positive edge weights of i. We denote the chance

expected within-module edge weights as e_{ij}^{+} for positive weights where $e_{ij}^{\pm} = \dfrac{s_i^{\pm} s_j^{\pm}}{v^{\pm}}$. We let the total

weight, $v^{\pm} = \sum_{ij} a_{ij}^{\pm}$, be the sum of all positive edge weights in the network. Then the weighted

generalization of the modularity quality index is given by

278
$$Q^{+} = \tfrac{1}{v^{+}} \Sigma_{ij}(a_{ij}^{+} - \gamma e_{ij}^{+})\delta_{M_i M_j},$$

where M_i is the community to which node i is assigned, and M_j is the community to which node j

is assigned. The Kronecker delta function, $\delta_{M_i M_j}$, takes on a value of 1 when $M_i = M_j$ and a value

of 0 when $M_i \neq M_j$. The tunable structural resolution parameter, γ, scales the relative importance

of the expected within-module weights (the null model) and in practice, the size of the

communities; smaller or larger values of γ result in correspondingly larger or smaller communities.

We use a Louvain-like locally greedy algorithm[52] as a heuristic to maximize this modularity

quality index subject to a partition M of nodes into communities.

For FC metrics resulting in weights falling in the interval [-1,1], specifically the Pearson and

Spearman correlations, we employed the asymmetrically weighted generalization of Q suitable for

networks containing negative weights[49]. Specifically, we follow Rubinov and Sporns[49] by first

letting the weight of a positive edge between nodes i and j be given by a_{ij}^{+}, the weight of a negative

edge between nodes i and j be given by a_{ij}^{-}, and the strength of a node i, $s_i^{\pm} = \sum_j a^{\pm}ij$, be given by

the sum of the positive or negative edge weights of i. We denote the chance expected within-

module edge weights as e_{ij}^+ for positive weights and e_{ij}^- for negative weights, where $e_{ij}^{\pm} = \frac{s_i^{\pm} s_j^{\pm}}{v^{\pm}}$. We

let the total weight, $v^{\pm} = \sum_{ij} a_{ij}^{\pm}$, be the sum of all positive or negative edge weights in the network.

Then an asymmetric signed generalization of the modularity quality index can be written as

298
$$Q^* = \frac{1}{v^+}\Sigma_{ij}(a_{ij}^+ - \gamma e_{ij}^+)\delta_{M_i M_j} - \frac{1}{v^+ + v^-}\Sigma_{ij}(a_{ij}^- - \gamma e_{ij}^-)\delta_{M_i M_j},$$

where M_i, M_j, $\delta_{M_i M_j}$, and γ are defined as above.

We examined average Q for each FC metric as a measure of system identifiability, as well as the

partial correlation between Q and mean relative RMS for each subject while controlling for average

network weight, age, and sex. Additionally, we addressed two potential confounds that have not

been previously addressed in work examining Q as a measure of system identifiability: the number

of communities k detected during modularity maximization, and the mean and distribution of edge

weights in a given network (see Supplementary Methods for details).

Results

Characteristics of FC matrices computed using different methods

We first characterized the functional connectivity edge weights estimated using different methods.

Figure 1 shows pairwise scatterplots between edge weights computed using all 6 methods. These

plots show the non-linear relationships between edges estimated using correlation-based methods

(Pearson and Spearman) and the other methods. Of particular interest is the mapping from negative

edges in correlation-based methods to others. For instance, the weights of negative edges in

Pearson matrices have an inverse relationship with the weights of edges in wavelet coherence

matrices – the more negative a Pearson edge weight, the higher its wavelet coherence edge weight.

Figure 1. Edge weight correlations for different FC metrics. Pairwise scatter plots between edge weights calculated using different FC methods. Diagonal entries show histograms of edge weights. Results are shown for the REST1_LR scan, with FC estimated using the 100-node Schaefer parcellation, and denoising performed using ICA-FIX.

Figure 2. FC matrices using different estimation methods. Edge weight heatmaps are shown for the 333-node Gordon parcellation, with canonical systems labeled as color bars. Each entry in the heatmap is the average edge weight across 802 subjects in the REST1_LR scans, estimated using **(A)** Pearson correlation, **(B)** Spearman correlation, **(C)** mutual information (time), **(D)** coherence, **(E)** wavelet coherence, and **(F)** mutual information (frequency). **(G)** Canonical systems for the Gordon parcellation displayed on the HCP S1200 group average cortical surface.

318   In Figure 2, FC matrices estimated using different methods are displayed as heatmaps, with

319   canonical systems in the Gordon parcellation highlighted in the x and y color bars. Modular

320   structure can clearly be seen in all matrices, with clean delineation of canonical systems in all

321 matrices. Further, in the correlation-based methods, well known negative correlations are apparent,

322 for instance between the default mode and dorsal attention systems[53].

Figure 3. Correlation-based methods show higher residual QC-FC correlations. Fraction of edges significantly associated with motion for all 4 resting-state scans. **(A)** FC estimated using the 333-node Gordon parcellation. **(B)** FC estimated using the 100-node Schaefer parcellation. In both panels **A** and **B**, metric names are shortened as follows: P=Pearson, S=Spearman, MIT=Mutual Information (time), C=Coherence, WC=Wavelet Coherence, and MIF=Mutual Information (frequency). Notches represent mean and error bars show standard deviation. **(C)** Histograms of QC-FC correlations for all estimation methods. Note the wider distributions for edge weights computed using Pearson and Spearman correlation.

Correlation-based methods show high residual QC-FC correlations

Next, we evaluated the sensitivity of edge weights (computed using different methods) to subject motion. We used the residual QC-FC correlation benchmark, which measures the edgewise relationship between the relative mean RMS motion of each subject and their estimated edge weights, after the application of denoising pipelines.

Panels A and B of Figure 3 show the fraction of edges for which the QC-FC correlations are statistically significant ($p < 0.05$, no correction for multiple comparisons). Correlation-based methods (Pearson and Spearman) perform poorly compared to coherence and information theory-based methods, with a relatively high fraction of edges displaying weights that are significantly associated with motion. If only the absolute values of edge weights are taken or if negative edges are set to zero, the performance of correlation-based measures improves, but is still worse than other measures (Figure S2, Figure S3). With CompCor preprocessing, wavelet coherence emerges as the best performing measure (Figure S4).

Figure 3C shows the distribution of QC-FC correlations for each FC estimation method. The distributions for correlation-based methods are wider than for other methods, confirming that more edges in correlation-based methods are significantly associated with motion.

Motion differentially affects putative cognitive systems

Next, we analyzed the amount of motion artifact in edges connecting regions within specific putative cognitive systems. Figure 4 shows heatmaps of QC-FC correlations for all edges in the Gordon parcellation, arranged by the associated *a priori* defined systems[38]. Heatmaps of QC-FC correlations averaged for each system pair is shown in Figure S5. We also computed pairwise inter- and intra-community QC-FC correlations and rank-ordered them by their median values. The six highest ranked inter-community QC-FC correlations are shown in Figure 5.

Figure 4. Distribution of QC-FC correlations across functional brain networks. QC-FC correlation heatmaps are shown for the REST1_LR scan, the 333-node Gordon parcellation, and with canonical *a priori* defined systems labeled as color bars. Each entry in the heatmap is the absolute value of the Pearson correlation coefficient (across subjects) between an edge's weight and RMS motion, with edge weights estimated using **(A)** Pearson correlation, **(B)** Spearman correlation, **(C)** mutual information (time), **(D)** coherence, **(E)** wavelet coherence, and **(F)** mutual information (frequency). **(G)** Canonical systems for the Gordon parcellation displayed on the HCP S1200 group average cortical surface.

Our analysis reveals a number of interesting details about the differential vulnerability of brain
systems to motion artifact. Edges connecting regions within a given system appear to be affected
more than inter-system edges, with 58.3% of the top-ranking QC-FC correlations belonging to
intra-system edges. Edges within the default mode (D-D) and the retrosplenial temporal systems
(RT-RT) appear to be especially vulnerable to motion artifact regardless of FC estimation method
(Figure 5, Figure S6). Notably, the fronto-parietal and auditory systems do not feature in the top
six inter-system QC-FC correlations for any FC measure. Within the correlation-based FC metrics
(Pearson and Spearman), edges between cingulo-opercular and visual (CO-V), and between
default and visual (D-V) systems have high QC-FC correlations but are not affected as much in
the other FC measures.

Figure 5. System affiliations of edges highly impacted by motion. Boxplots of inter-system QC-FC correlations are shown for the REST1_LR scan and the 333-node Gordon parcellation. All inter-system edges were rank-ordered by their median absolute QC-FC correlation, and the top 6 ranking distributions are shown for each FC metric. CO=cingulo-opercular; CP=cingulo-parietal; D=default; DA=dorsal attention; RT=retrosplenial temporal; SH=sensory, motor, hand; SM=sensory, motor, mouth; S=salience, VA=ventral attention; V=visual.

Figure 6. Distance-dependence of QC-FC correlations. Residual distance-dependence of motion artifact for different FC estimation methods, shown for all 4 resting-state scans. **(A)** FC estimated using the 333-node Gordon parcellation. **(B)** FC estimated using the 100-node Schaefer parcellation. In both panels **A** and **B**, the functional connectivity metric names are abbreviated as follows: P=Pearson, S=Spearman, MIT=Mutual Information (time), C=Coherence, WC=Wavelet Coherence, and MIF=Mutual Information (frequency). Notches represent mean and error bars show standard deviation.

364 **Distance-dependence of motion artifact**

365

366 Next, we evaluated the distance-dependence of motion artifact by measuring edgewise correlations

367 between the Euclidean distance between nodes and the edge's absolute QC-FC correlation value.

368 We find that correlation-based FC metrics (Pearson and Spearman) have higher positive distance-

369 dependence than coherence and information theory-based methods, implying that long-distance

370 edges are more affected by motion than short-distance edges (Figure 6). With CompCor

371 preprocessing, most measures display relatively similar negative distance-dependence (Figure S7).

372

373 **Test-retest reliability of functional connectivity**

374

375 To estimate the reproducibility in functional connectivity estimates with different methods, we

376 measured the intra-class correlation across 4 resting state scans in the HCP dataset. Panels A and

377 B of Figure 7 show that the intra-class correlations for correlation-based measures (Pearson and

378 Spearman) are higher than for coherence and information theory-based methods. This relatively

379 high reliability could be due to accurate estimates of trait-like biology or could be due to a

sensitivity to a highly reliable third-party variable, such as motion. To determine whether the latter

could be the case, we evaluated the reliability of subject motion. We found that the intra-class

correlation for relative RMS motion was also high (0.7169), indicating that motion itself is

reproducible across scans. In order to separate the reproducibility of motion from reproducibility

of FC edges, we re-computed the intra-class correlations for edges that were in the bottom 20% of

absolute QC-FC correlation values in all 4 scans. This analysis showed that correlation-based

measures still had higher intra-class correlations than other measures after mitigating the influence

of reliable motion, indicating that edges estimated using correlation-based methods are more

reproducible over this time scale than edges estimated using other methods (Figure 7C, D).

Figure 7. Test-retest reliability of edge weights for different FC metrics. (A-B) Intra-class correlation for all edge weights across 4 resting-state scans. **(A)** FC estimated using the 333-node Gordon parcellation. **(B)** FC estimated using the 100-node Schaefer parcellation. **(C-D)** Intra-class correlation for edges in the bottom 20% of QC-FC correlations for all 4 resting-state scans. **(C)** 257 edges in the Gordon parcellation. **(D)** 35 edges in the Schaefer parcellation. For all panels, the names of functional connectivity metrics have been abbreviated as follows: P=Pearson, S=Spearman, MIT=Mutual Information (time), C=Coherence, WC=Wavelet Coherence, and MIF=Mutual Information (frequency).

System Identifiability

Finally, we examined the extent to which different metrics of FC resulted in different levels of

system identifiability, or identification of the coherent intramodular structure that is commonly

found in functional brain networks[47,48]. Panels A and B of Figure 8 show that on average, our

measure of system identifiability, the modularity quality index, is highest in systems estimated

using a Pearson's or Spearman's correlation.

Figure 8. System identifiability is differentially associated with motion across FC metrics. **(A, B)** The modularity quality index is highest in networks estimated using a time-based correlation metric (Pearson or Spearman correlation). Modularity maximization was tuned across subjects to estimate between 6 and 8 communities for each metric. **(C, D)** Partial correlation between Q and mean relative RMS, controlling for average network weight, age, and sex. Correlation-based metrics show large negative correlations between subject motion and Q. P=Pearson, S=Spearman, MIT=Mutual Information (time), C=Coherence, WC=Wavelet Coherence, MIF=Mutual Information (frequency). Notches represent mean and error bars show standard deviation.

The high system identifiability in correlation-based metrics could be due to an accurate sensitivity
to the biology of putative cognitive systems or could be due to motion impacting regions of the
brain in a spatially heterogeneous manner that partially drives the data-driven identification of
systems. To address these possibilities, we studied the relation between Q and motion. We find
that the relationship between Q and motion is also strongest in the correlation-based metrics, even
when controlling for average weight, age, and sex (Figure 8C, D). Modularity quality index
estimated on networks containing only edges that were in the bottom 20 % of absolute QC-FC

Figure 9. A correlation-based metric results in higher system identifiability even when using edge weight ranks rather than edge weight values. (A, B) Holding the edge weight distribution constant, higher Q is found when using the ranking of a time-based metric (Pearson) than a time-frequency-based metric (Wavelet Coherence). Notches represent mean and error bars show standard deviation.

correlation values in all 4 scans showed that Q is still highest in networks estimated with Pearson

or Spearman's correlations (Figure S8). We also estimated Q from networks containing only the

absolute values of edge weights, which reduces but does not eliminate differences in system

identifiability between correlation-based metrics and other metrics (Figure S9). Finally, to ensure

that differences in system identifiability were not driven by differences in the functional systems

detected when maximizing the modularity quality index, we also calculated Q using the canonical

system partition associated with each of our 2 parcellations and obtained similar results (Figure

S10).

To further ensure that results were not driven by variability in edge weight distributions across FC

metrics, we examined two boundary cases from prior results as the FC metrics of interest:

Pearson's correlation and wavelet coherence. We reordered the edge weight values in our *weights*

matrix (see Supplementary Methods) to reflect the rank order of weights in the ordering matrix.

We estimated the modularity quality index Q of these reordered matrices, and found that Q was

consistently higher when the ordering matrix was derived from Pearson's correlations (Figure 9).

Taken together, these results suggest that correlation-based FC metrics consistently result in higher

levels of system identifiability, and that they may better reflect the modular architecture of

functional brain networks than other methods.

Discussion

In this report, we systematically investigated the sensitivity to motion of six different FC

estimation measures drawn from the correlation, coherence, and mutual information families,

based on their performance on commonly used benchmarks. The context, implications, and

limitations of our results are discussed below.

Clear distinction between correlation-based FC measures and other measures

Our main finding is that correlation-based measures (Pearson and Spearman) result in a high

fraction of edges significantly correlated with motion and a high distance-dependence of motion

artifact compared to all other methods. These results imply that commonly used correlation-based

measures are relatively susceptible to subject motion.

Head motion artifact predominantly manifests as spurious signal fluctuations in BOLD signal

across multiple voxels in the brain[16,30]. Since traditional correlation-based functional connectivity

measures temporal covariance, it follows that such measures of connectivity are directly impacted

by artifactual covariance introduced by head motion. On the other hand, coherence-based FC

measures quantify statistical dependencies in the frequency domain, including phase locking and

correlation in power spectra. We also evaluated mutual information in the frequency domain[27],

which is an information theoretic measure of relationships in the frequency domain. Frequency-

based FC measures are less likely to be influenced by short-lived temporal fluctuations in the

BOLD signal. Thus, we posit that the statistical properties of correlation-based methods render

them relatively more sensitive to temporal outliers introduced by head motion.

In our study, we averaged frequency-based connectivity estimates (coherence, wavelet coherence,

and mutual information in frequency) within a low frequency band (0.009-0.08Hz). Although

information on the power spectral properties of motion artifact is limited, some prior studies have

shown that motion affects the spectral power and connectivity estimates mainly at high

frequencies[54–56]. It is therefore possible that averaging connectivity estimates within a low

frequency band reduced the impact of high-frequency motion artifact in these measures. Further,

if motion artifact manifested in any one given frequency, the process of averaging in multiple

frequency bands may have diluted the overall impact of motion on the FC estimates.

When time series were denoised using the CompCor pipeline, wavelet coherence FC estimates had

substantially lower fraction of edges significantly correlated with motion compared to other

methods. With CompCor preprocessing, residual QC-FC correlations were quite high on average,

meaning that denoised signals were still quite noisy. In this context, the benefit of wavelet

coherence might derive from the suitability of wavelet transform methods to model long-memory

or 1/f-like processes[23]. Wavelet methods are natural optimal whitening or decorrelating filters for

1/f-like processes, which means that they are less sensitive to the slow drift type of head

motion[23,57–59]. Therefore, wavelet coherence is a good choice for estimating functional

connectivity with resting-state data that is significantly contaminated by motion.

We found that the performance of correlation-based methods on the QC-FC benchmark improved

when taking the absolute values of edge weights, and when negative edges were set to zero (Figure

S2, S3). Analysis of fully connected complex networks with positive and negative weights can be

rigorously performed[49]. However, the interpretation of negative correlations is controversial,

especially in the context of global signal regression[60–62]. As a result, many studies omit negative

edges from analyses of functional and dynamic connectivity[63,64]. Our results indicate that omitting

negative edges or taking their absolute values might also reduce the susceptibility to motion

artifact.

The systems whose edges were most affected by motion differed among FC estimation methods.

For instance, connections between large-scale systems such as the default mode, cingulo-opercular

and visual systems were related to motion in correlation-based methods but not in other FC

methods. In contrast, within-system edges in the default mode system and retrosplenial temporal

cortex were strongly related to motion in all FC estimation methods. This last result deserves

attention, given the large number of scientific hypotheses surrounding the brain's default mode

system[53,65].

The strong relationship between motion and default mode connectivity is unlikely solely due to

geometry because other networks whose edges are less correlated with motion, including the

frontoparietal network, are similarly distributed with anterior and posterior nodes on both medial

and lateral surfaces. It is possible that individuals with specific patterns of default mode

connectivity find it more difficult to remember to stay still as their minds wander[66–68].

Retrosplenial cortex, another network that we found to have a strong relationship with motion, is

often functionally integrated with the default mode network to support memory processes, but also

plays a role in spatial navigation and locomotion[69–71]. Specifically, retrosplenial cortex integrates

vestibular input, which encodes head position, with visual cortex, to calibrate self-motion with

visual motion signals[72,73]. Our findings highlight the need to carefully consider the confounding

effects of motion, as well as the causes of motion, while studying these systems.

Perhaps surprisingly, correlation-based measures also resulted in significantly higher system
identifiability than other measures. These results held even when restricting analysis only to the
20% of edges that were least affected by motion. This observation suggests that findings of higher
system identifiability in time-based correlation methods are not solely driven by motion, and that
these metrics, while highly motion-sensitive, might excel in detecting coherent community
structure. Alternatively, these findings may hint that the well-established finding of a modular
architecture in human functional brain networks may be relatively metric-dependent[74,75].

The success with which correlation-based measures detect modular architecture may be due to the
presence of negative edge weights or anticorrelations in these measures, which contribute to
reducing inter-module connections in calculations of modularity quality. A negative edge
calculated using Pearson correlation, for instance between the default mode and dorsal attention
systems, reduces the overall inter-module connectivity, crystallizing the boundaries between
modules. However, the same edge calculated using coherence is highly positive, increasing inter-
module connectivity and obfuscating boundaries between modules. Further, taking absolute values
of correlation-based edges acts as a similar transformation, converting negative edges to positive
edges, reducing the modularity quality index. The presence of negative edges or anticorrelation
between internal and external attention systems has been argued to reflect a functional toggle
between systems[61,76–79]. It is therefore unclear which method best captures true interactions
between systems. Indeed, both could reflect complementary aspects of network dynamics if dorsal
attention activation lags default mode activation at a consistent delay.

Lastly, correlation-based measures scored higher on test-retest reliability compared to other
methods. While this was partly caused by the well-known reproducibility of motion itself[80,81], we
observed similar results when restricting our analysis to the 20% of edges with the lowest absolute
QC-FC correlations for all 4 scans. This additional finding suggests that correlation-based
methods, while highly sensitive to motion, lead to relatively reproducible functional connectivity
estimates.

Implications for researchers

We have shown that moving away from standard correlation-based FC measures can improve the robustness of FC estimates to head motion. However, correlation-based FC measures excel at detecting community structure and are highly reliable. Our findings indicate that the FC estimation method should be chosen carefully based on the nature of the study. For instance, studies on group comparisons, where motion artifact can introduce systematic bias in connectivity estimates[16], could benefit from using frequency-based FC estimation methods like coherence. The appropriate choice for studies on modular brain architecture, in contrast, would likely remain correlation-based metrics.

Our results also highlight a spatial heterogeneity in the impact of motion. FC edges in the default mode and retrosplenial cortex were especially sensitive to the effects of motion. Studies that explore the fine-scale organization and function of these networks could benefit from exploring different choices of FC estimation.

Finally, correlation-based metrics are computationally less expensive than the rest of the measures reported here and would therefore be preferable for large datasets. Other metrics can be used for smaller datasets where computational time is not prohibitive.

Limitations

It is prudent to mention several limitations of our study. First, the lack of a noise-free ground truth is a challenge while estimating the impact of motion artifact in real fMRI data. It is difficult to separate out true signal from noise in fMRI data, a challenge further complicated by findings that head motion is a stable trait, and likely related to an individual's physiology and neural dynamics[82,83]. Second, due to the lack of ground truth, it is necessary to rely on indirect benchmarks such as QC-FC correlations and QC-FC distance-dependence. Central to the computation of these benchmarks is the estimation of an average measure of head motion for the whole scan from realignment estimates[16]. This average measure can miss important spatiotemporal details of motion. Future studies could use voxel-wise displacement maps to extract more detailed

information about motion and its impact on FC[55]. Third, some recent studies have highlighted the

qualitative differences in motion estimates and physiological noise parameters from datasets with

fast sampling rates compared to older datasets with larger TRs[84,85]. Thus, the estimates of head

motion from realignment parameters, including those used in the current study, may need to be

modified in the future for datasets with smaller TRs. Fourth, we used data from the Human

Connectome Project that was preprocessed using ICA-FIX. This denoising approach has been

shown to be particularly effective with HCP data[32]. In the future, it might be beneficial to

investigate the effect of varying FC estimation methods with more noisy datasets with different

denoising pipelines. Further, because we imposed a fairly stringent motion exclusion threshold, it

is unclear whether our results generalize to samples with higher motion including pediatric,

geriatric, or psychiatric samples. Finally, we did not evaluate FC estimation methods from many

statistical families, including Bayes nets, Granger causality, and generalized synchronization.

Further, we restricted analysis to full correlations, and did not investigate partial correlation

methods. Future studies could investigate additional families of FC estimation methods omitted

from this study.

Citation diversity statement

Recent work in neuroscience and other fields has identified a bias in citation practices such that

papers from women and other minorities are under-cited relative to the number of such papers in

the field[86–91]. Here we sought to proactively consider choosing references that reflect the

diversity of the field in thought, form of contribution, gender, and other factors. We used

automatic classification of gender based on the first names of the first and last authors[89,92], with

possible combinations including male/male, male/female, female/male, and female/female.

Excluding self-citations to the first and last authors of our current paper, the references

contain 53.1% male/male, 9.9% male/female, 23.5% female/male, 13.6% female/female. We

look forward to future work that could help us to better understand how to support equitable

practices in science.

Disclosure of competing interests

The authors declare no competing interests

Acknowledgements

We thank Linden Parkes for helpful discussions. U.A.T was supported by the National Science Foundation Graduate Research Fellowship. A.P.M. was supported by a Jacobs Foundation Early Career Research Fellowship and the National Institute on Drug Abuse (1R34DA050297-01). ASM was primarily supported by the Paul G. Allen Family Foundation and the Army Research Office (Falk W911NF-18-1-0244). DSB would also like to acknowledge the John D. and Catherine T. MacArthur Foundation, the ISI Foundation, the Army Research Laboratory (W911NF-10-2-0022), the Army Research Office (Bassett-W911NF-14-1-0679, Grafton-W911NF-16-1-0474), the National Science Foundation (BCS1631550, PHY-1554488, NCS-FO-1926829), the National Institute of Mental Health (2-R01-DC-009209-11, R01-MH112847, R01-MH107235, R21-M MH-106799, R01-MH-116920), and the National Institute of Child Health and Human Development (1R01HD086888-01). The content is solely the responsibility of the authors and does not necessarily represent the official views of any of the funding agencies.

Author contributions

Arun S. Mahadevan: Methodology, Software, Formal Analysis, Visualization, Writing – Original Draft Preparation

Ursula Tooley: Methodology, Software, Formal Analysis, Visualization, Writing – Original Draft Preparation

Maxwell P. Bertolero: Data curation, Writing – Original Draft Preparation

Allyson P. Mackey: Supervision, Writing – Reviewing and Editing

Danielle S. Bassett: Conceptualization, Supervision, Formal Analysis, Writing – Reviewing and Editing

References

1. Buckner, R. L., Krienen, F. M. & Yeo, B. T. T. Opportunities and limitations of intrinsic
functional connectivity MRI. *Nat. Neurosci.* **16**, 832–837 (2013).

2. Achard, S., Salvador, R., Whitcher, B., Suckling, J. & Bullmore, E. A resilient, low-
frequency, small-world human brain functional network with highly connected association
cortical hubs. *J. Neurosci.* **26**, 63–72 (2006).

3. van den Heuvel, M. P. & Hulshoff Pol, H. E. Exploring the brain network: A review on
resting-state fMRI functional connectivity. *Eur. Neuropsychopharmacol.* **20**, 519–534
(2010).

4. Morgan, S. E., Achard, S., Termenon, M., Bullmore, E. T. & Vértes, P. E. Low-
dimensional morphospace of topological motifs in human fMRI brain networks. *Netw.*
Neurosci. **2**, 285–302 (2017).

5. Vértes, P. E. *et al.* Simple models of human brain functional networks. *Proc. Natl. Acad.*
Sci. U. S. A. **109**, 5868–5873 (2012).

6. Achard, S. & Bullmore, E. Efficiency and cost of economical brain functional networks.
PLoS Comput. Biol. **3**, 0174–0183 (2007).

7. Gu, S. *et al.* Emergence of system roles in normative neurodevelopment. *Proc. Natl. Acad.*
Sci. **112**, 13681–13686 (2015).

8. Tooley, U. A. *et al.* Associations between Neighborhood SES and Functional Brain
Network Development. *Cereb. Cortex* **30**, 1–19 (2020).

9. Thomason, M. E. Development of Brain Networks In Utero: Relevance for Common
Neural Disorders. *Biological Psychiatry* **0**, (2020).

10. Wheelock, M. D. *et al.* Sex differences in functional connectivity during fetal brain
development. *Dev. Cogn. Neurosci.* **36**, 100632 (2019).

11. van den Heuvel, M. I. *et al.* Hubs in the human fetal brain network. *Dev. Cogn. Neurosci.*
30, 108–115 (2018).

12. Morgan, S. E., White, S. R., Bullmore, E. T. & Vértes, P. E. A Network Neuroscience
Approach to Typical and Atypical Brain Development. *Biological Psychiatry: Cognitive*
Neuroscience and Neuroimaging **3**, 754–766 (2018).

13. Vértes, P. E. & Bullmore, E. T. Annual research review: Growth connectomics - The
organization and reorganization of brain networks during normal and abnormal

648   development. *J. Child Psychol. Psychiatry Allied Discip.* **56**, 299–320 (2015).

649 14. Finn, E. S. *et al.* Functional connectome fingerprinting: Identifying individuals using

650   patterns of brain connectivity. *Nat. Neurosci.* **18**, 1664–1671 (2015).

651 15. Gratton, C. *et al.* Functional Brain Networks Are Dominated by Stable Group and

652   Individual Factors, Not Cognitive or Daily Variation. *Neuron* **98**, 439-452.e5 (2018).

653 16. Power, J. D., Schlaggar, B. L. & Petersen, S. E. Recent progress and outstanding issues in

654   motion correction in resting state fMRI. *Neuroimage* **105**, 536–551 (2015).

655 17. Ciric, R. *et al.* Benchmarking of participant-level confound regression strategies for the

656   control of motion artifact in studies of functional connectivity. *Neuroimage* **154**, 174–187

657   (2017).

658 18. Parkes, L., Fulcher, B., Yücel, M. & Fornito, A. An evaluation of the efficacy, reliability,

659   and sensitivity of motion correction strategies for resting-state functional MRI.

660   *Neuroimage* **171**, 415–436 (2018).

661 19. Caballero-Gaudes, C. & Reynolds, R. C. Methods for cleaning the BOLD fMRI signal.

662   *Neuroimage* **154**, 128–149 (2017).

663 20. Burgess, G. C. *et al.* Evaluation of Denoising Strategies to Address Motion-Correlated

664   Artifacts in Resting-State Functional Magnetic Resonance Imaging Data from the Human

665   Connectome Project. *Brain Connect.* **6**, 669–680 (2016).

666 21. Friston, K. J. Functional and Effective Connectivity: A Review. *Brain Connect.* **1**, 13–36

667   (2011).

668 22. Sun, F. T., Miller, L. M. & D'Esposito, M. Measuring interregional functional

669   connectivity using coherence and partial coherence analyses of fMRI data. *Neuroimage*

670   **21**, 647–658 (2004).

671 23. Bullmore, E. *et al.* Wavelets and functional magnetic resonance imaging of the human

672   brain. *Neuroimage* **23**, 234–249 (2004).

673 24. Beauchene, C., Roy, S., Moran, R., Leonessa, A. & Abaid, N. Comparing brain

674   connectivity metrics: a didactic tutorial with a toy model and experimental data. *J. Neural*

675   *Eng.* **15**, 56031 (2018).

676 25. Shannon, C. E. A Mathematical Theory of Communication. *Bell Syst. Tech. J.* **27**, 379–

677   423 (1948).

678 26. Quiroga, R. Q., Kraskov, A., Kreuz, T. & Grassberger, P. On the performance of different

synchronization measures in real data: a case study on EEG signals. **65**, 1–14 (2001).

27.   Salvador, R., Suckling, J., Schwarzbauer, C. & Bullmore, E. Undirected graphs of

frequency-dependent functional connectivity in whole brain networks. *Philos. Trans. R.*

Soc. B Biol. Sci. **360**, 937–946 (2005).

28.   Smith, S. M. *et al.* Network modelling methods for FMRI. *Neuroimage* **54**, 875–91

(2011).

29.   Wang, H. E. *et al.* A systematic framework for functional connectivity measures. *Front.*

Neurosci. **8**, 1–22 (2014).

30.   Ciric, R. *et al.* Mitigating head motion artifact in functional connectivity MRI. *Nat.*

Protoc. **13**, 2801–2826 (2018).

31.   Van Essen, D. C. *et al.* The WU-Minn Human Connectome Project: An overview.

Neuroimage **80**, 62–79 (2013).

32.   Salimi-Khorshidi, G. *et al.* Automatic denoising of functional MRI data: Combining

independent component analysis and hierarchical fusion of classifiers. *Neuroimage* **90**,

449–468 (2014).

33.   Griffanti, L. *et al.* ICA-based artefact removal and accelerated fMRI acquisition for

improved resting state network imaging. *Neuroimage* **95**, 232–247 (2014).

34.   Bertolero, M. A. *et al.* The network architecture of the human brain is modularly encoded

in the genome. (2019).

35.   Schaefer, A. *et al.* Local-Global Parcellation of the Human Cerebral Cortex from Intrinsic

Functional Connectivity MRI. *Cereb. Cortex* **28**, 3095–3114 (2018).

36.   Whitaker, K. J. *et al.* Adolescence is associated with genomically patterned consolidation

of the hubs of the human brain connectome. *Proc. Natl. Acad. Sci. U. S. A.* **113**, 9105–

9110 (2016).

37.   Vértes, P. E. *et al.* Gene transcription profiles associated with inter-modular hubs and

connection distance in human functional magnetic resonance imaging networks. *Philos.*

Trans. R. Soc. B Biol. Sci. **371**, (2016).

38.   Gordon, E. M. *et al.* Generation and Evaluation of a Cortical Area Parcellation from

Resting-State Correlations. *Cereb. Cortex* **26**, 288–303 (2016).

39.   Strehl, A. & Ghosh, J. Cluster Ensembles --- A Knowledge Reuse Framework for

Combining Multiple Partitions. *J. Mach. Learn. Res.* **3**, 583–617 (2002).

40.   Zhou, D., Thompson, W. K. & Siegle, G. MATLAB toolbox for functional connectivity.
711   *Neuroimage* **47**, 1590–1607 (2009).

712   41.   Grinsted, A., Moore, J. C. & Jevrejeva, S. Application of the cross wavelet transform and
713   wavelet coherence to geophysical time series. *Nonlinear Process. Geophys.* **11**, 561–566
714   (2004).

715   42.   Bassett, D. S. & Sporns, O. Network neuroscience. *Nat. Neurosci.* **20**, 353–364 (2017).

716   43.   Satterthwaite, T. D. *et al.* Impact of in-scanner head motion on multiple measures of
717   functional connectivity: Relevance for studies of neurodevelopment in youth. *Neuroimage*
718   **60**, 623–632 (2012).

719   44.   Shrout, P. E. & Fleiss, J. L. Intraclass correlations: Uses in assessing rater reliability.
720   *Psychol. Bull.* **86**, 420–428 (1979).

721   45.   Newman, M. Modularity and community structure in networks. *Proc. Natl. Acad. ...* **103**,
722   8577–82 (2006).

723   46.   Girvan, M. & Newman, M. E. J. Community structure in social and biological networks.
724   *Proc. Natl. Acad. Sci. U. S. A.* **99**, 7821–7826 (2002).

725   47.   Porter, M. A., Onnela, J.-P. & Mucha, P. J. Communities in Networks. *Not. AMS* **56**,
726   1082–1097 (2009).

727   48.   Fortunato, S. Community detection in graphs. *Phys. Rep.* **486**, 75–174 (2010).

728   49.   Rubinov, M. & Sporns, O. Weight-conserving characterization of complex functional
729   brain networks. *Neuroimage* **56**, 2068–2079 (2011).

730   50.   Traag, V. A. & Bruggeman, J. Community detection in networks with positive and
731   negative links. *Phys. Rev. E - Stat. Nonlinear, Soft Matter Phys.* **80**, 1–6 (2009).

732   51.   Gómez, S., Jensen, P. & Arenas, A. Analysis of community structure in networks of
733   correlated data. *Phys. Rev. E - Stat. Nonlinear, Soft Matter Phys.* **80**, 1–5 (2009).

734   52.   Blondel, V. D., Guillaume, J. L., Lambiotte, R. & Lefebvre, E. Fast unfolding of
735   communities in large networks. *J. Stat. Mech. Theory Exp.* **2008**, 0–12 (2008).

736   53.   Buckner, R. L. & DiNicola, L. M. The brain's default network: updated anatomy,
737   physiology and evolving insights. *Nat. Rev. Neurosci.* (2019). doi:10.1038/s41583-019-
738   0212-7

739   54.   Salvador, R. *et al.* A simple view of the brain through a frequency-specific functional
740   connectivity measure. *Neuroimage* **39**, 279–289 (2008).

55.   Satterthwaite, T. D. *et al.* An improved framework for confound regression and filtering for control of motion artifact in the preprocessing of resting-state functional connectivity data. *Neuroimage* **64**, 240–256 (2013).

56.   Kim, J., Van Dijk, K. R. A., Libby, A. & Napadow, V. Frequency-dependent relationship between resting-state functional magnetic resonance imaging signal power and head motion is localized within distributed association networks. *Brain Connect.* **4**, 30–39 (2014).

57.   Zhang, Z., Telesford, Q. K., Giusti, C., Lim, K. O. & Bassett, D. S. Choosing wavelet methods, filters, and lengths for functional brain network construction. *PLoS One* **11**, 1–24 (2016).

58.   Wink, A. M., Bernard, F., Salvador, R., Bullmore, E. & Suckling, J. Age and cholinergic effects on hemodynamics and functional coherence of human hippocampus. *Neurobiol. Aging* **27**, 1395–1404 (2006).

59.   Maxim, V. *et al.* Fractional Gaussian noise, functional MRI and Alzheimer's disease. *Neuroimage* **25**, 141–158 (2005).

60.   Anderson, J. S. *et al.* Network anticorrelations, global regression, and phase-shifted soft tissue correction. *Hum. Brain Mapp.* **32**, 919–934 (2011).

61.   Chai, X. J., Castañán, A. N., Öngür, D. & Whitfield-Gabrieli, S. Anticorrelations in resting state networks without global signal regression. *Neuroimage* **59**, 1420–1428 (2012).

62.   Murphy, K. & Fox, M. D. Towards a consensus regarding global signal regression for resting state functional connectivity MRI. *Neuroimage* **154**, 169–173 (2017).

63.   Grady, C., Sarraf, S., Saverino, C. & Campbell, K. Age differences in the functional interactions among the default, frontoparietal control, and dorsal attention networks. *Neurobiol. Aging* **41**, 159–172 (2016).

64.   Chan, M. Y., Park, D. C., Savalia, N. K., Petersen, S. E. & Wig, G. S. Decreased segregation of brain systems across the healthy adult lifespan. *Proc. Natl. Acad. Sci. U. S. A.* **111**, E4997–E5006 (2014).

65.   Fox, M. D. & Raichle, M. E. Spontaneous fluctuations in brain activity observed with functional magnetic resonance imaging. *Nat. Rev. Neurosci.* **8**, 700–11 (2007).

66.   Christoff, K., Gordon, A. M., Smallwood, J., Smith, R. & Schooler, J. W. Experience

sampling during fMRI reveals default network and executive system contributions to mind

wandering. *Proc. Natl. Acad. Sci. U. S. A.* **106**, 8719–8724 (2009).

67.   Kajimura, S., Kochiyama, T., Nakai, R., Abe, N. & Nomura, M. Causal relationship

between effective connectivity within the default mode network and mind-wandering

regulation and facilitation. *Neuroimage* **133**, 21–30 (2016).

68.   Golchert, J. *et al.* Individual variation in intentionality in the mind-wandering state is

reflected in the integration of the default-mode, fronto-parietal, and limbic networks.

Neuroimage **146**, 226–235 (2017).

69.   Vann, S. D., Aggleton, J. P. & Maguire, E. A. What does the retrosplenial cortex do? *Nat.*

Rev. Neurosci. **10**, 792–802 (2009).

70.   Fischer, L. F., Mojica Soto-Albors, R., Buck, F. & Harnett, M. T. Representation of visual

landmarks in retrosplenial cortex. *Elife* **9**, 1–25 (2020).

71.   Mao, D., Molina, L. A., Bonin, V. & McNaughton, B. L. Vision and Locomotion

Combine to Drive Path Integration Sequences in Mouse Retrosplenial Cortex. *Curr. Biol.*

1–9 (2020). doi:10.1016/j.cub.2020.02.070

72.   Vélez-Fort, M. *et al.* A Circuit for Integration of Head- and Visual-Motion Signals in

Layer 6 of Mouse Primary Visual Cortex. *Neuron* **98**, 179-191.e6 (2018).

73.   Chaplin, T. A. & Margrie, T. W. Cortical circuits for integration of self-motion and visual-

motion signals. *Curr. Opin. Neurobiol.* **60**, 122–128 (2020).

74.   Bertolero, M. A., Thomas Yeo, B. T. & D'Esposito, M. The modular and integrative

functional architecture of the human brain. *Proc. Natl. Acad. Sci. U. S. A.* **112**, E6798–

E6807 (2015).

75.   Sporns, O. & Betzel, R. F. Modular Brain Networks. *Annu. Rev. Psychol.* **67**, 613–640

(2016).

76.   Gao, W. & Lin, W. Frontal parietal control network regulates the anti-correlated default

and dorsal attention networks. *Hum. Brain Mapp.* **33**, 192–202 (2012).

77.   Clare Kelly, A. M., Uddin, L. Q., Biswal, B. B., Castellanos, F. X. & Milham, M. P.

Competition between functional brain networks mediates behavioral variability.

Neuroimage **39**, 527–537 (2008).

78.   Owens, M. M., Duda, B., Sweet, L. H. & MacKillop, J. Distinct functional and structural

neural underpinnings of working memory. *Neuroimage* **174**, 463–471 (2018).

79.   Murphy, A. C., Bertolero, M. A., Papadopoulos, L., Lydon-Staley, D. M. & Bassett, D. S.
804   Multiscale and multimodal network dynamics underpinning working memory. 3–6 (2019).

805   80.   Noble, S., Scheinost, D. & Constable, R. T. A decade of test-retest reliability of functional
806   connectivity: A systematic review and meta-analysis. *Neuroimage* **203**, 116157 (2019).

807   81.   van Dijk, K. R. A., Sabuncu, M. R. & Buckner, R. L. The influence of head motion on
808   intrinsic functional connectivity MRI. *Neuroimage* **59**, 431–438 (2012).

809   82.   Engelhardt, L. E. *et al.* Children's head motion during fMRI tasks is heritable and stable
810   over time. *Dev. Cogn. Neurosci.* **25**, 58–68 (2017).

811   83.   Beyer, F. *et al.* Weight loss reduces head motion: Revisiting a major confound in
812   neuroimaging. *Hum. Brain Mapp.* 1–5 (2020). doi:10.1002/hbm.24959

813   84.   Agrawal, U., Brown, E. N. & Lewis, L. D. Model-based physiological noise removal in
814   fast fMRI. *Neuroimage* 116231 (2019). doi:10.1016/j.neuroimage.2019.116231

815   85.   Power, J. D. *et al.* Distinctions among real and apparent respiratory motions in human
816   fMRI data. *Neuroimage* **201**, 116041 (2019).

817   86.   Caplar, N., Tacchella, S. & Birrer, S. Quantitative evaluation of gender bias in
818   astronomical publications from citation counts. *Nat. Astron.* **1**, (2017).

819   87.   Chakravartty, P., Kuo, R., Grubbs, V. & McIlwain, C. #CommunicationSoWhite. *J.*
820   *Commun.* **68**, 254–266 (2018).

821   88.   Dion, M. L., Sumner, J. L. & Mitchell, S. M. L. Gendered Citation Patterns across
822   Political Science and Social Science Methodology Fields. *Polit. Anal.* **26**, 312–327 (2018).

823   89.   Dworkin, J. D. *et al.* The extent and drivers of gender imbalance in neuroscience reference
824   lists. (2020).

825   90.   Maliniak, D., Powers, R. & Walter, B. F. *The gender citation gap in international*
826   *relations. International Organization* **67**, (2013).

827   91.   Thiem, Y., Sealey, K. F., Ferrer, A. E., Trott, A. M. & Kennison, R. *Just Ideas? The*
828   *Status and Future of Publication Ethics in Philosophy: A White Paper*. (2018).

829   92.   Zhou, D. *et al.* Gender Diversity Statement and Code Notebook v1.0. (2020).
830   doi:10.5281/zenodo.3672110