Cancer phylogenetic tree inference at scale from 1000s of single cell genomes

Sohrab Salehi [*,1], Fatemeh Dorri [*,2], Kevin Chern[1], Farhia Kabeer[3], Nicole Rusk[4], Tyler Funnell[4], Marc J Williams[4], Daniel Lai[3,5], Mirela Andronescu[3,5], Kieran R. Campbell[6,7,8], Andrew McPherson[4], Samuel Aparicio[3,5], Andrew Roth[2,3,5], Sohrab Shah[4], and Alexandre Bouchard-Côté[1, *]

[1] Department of Statistics, University of British Columbia
[2] Department of Computer Science, University of British Columbia
[3] Department of Pathology and Laboratory Medicine, University of British Columbia
[4] Computational Oncology, Department of Epidemiology and Biostatistics, Memorial Sloan Kettering Cancer Center
[5] Department of Molecular Oncology, BC Cancer Research Centre
[6] Lunenfeld-Tanenbaum Research Institute, Mount Sinai Hospital
[7] Department of Molecular Genetics, University of Toronto
[8] Department of Statistical Sciences, University of Toronto
[*] Correspondence: `bouchard@stat.ubc.ca`

Abstract

A new generation of scalable single cell whole genome sequencing (scWGS) methods allows unprecedented high resolution measurement of the evolutionary dynamics of cancer cell populations. Phylogenetic reconstruction is central to identifying subpopulations and distinguishing the mutational processes that gave rise to them. Existing phylogenetic tree building models do not scale to the tens of thousands of high resolution genomes achievable with current scWGS methods. We constructed a phylogenetic model and associated Bayesian inference procedure, sitka, specifically for scWGS data. The method is based on a novel phylogenetic encoding of copy number (CN) data, the sitka transformation, that simplifies the site dependencies induced by rearrangements while still forming a sound foundation to phylogenetic inference. The sitka transformation allows us to design novel scalable Markov chain Monte Carlo (MCMC) algorithms. Moreover, we introduce a novel point mutation calling method that incorporates the CN data and the underlying phylogenetic tree to overcome the low per-cell coverage of scWGS. We demonstrate our method on three single cell datasets, including a novel PDX series, and analyse the topological properties of the inferred trees. Sitka is freely available at https://github.com/UBC-Stat-ML/sitkatree.git.

---

[*] Equal contribution

1 Introduction

A main challenge in investigating cancer evolution is the need to resolve the subpopulation structure of a heterogeneous tumour sample. Advances in next generation scWGS have enabled more accurate, quantitative measurements of tumours as they evolve [1, 2, 3, 4]. Phylogenetic reconstruction is central to identifying clones in longitudinal xenoengraftment [5, 6] as well as patients [7], and has been used to approximate the rate and timing of mutation [8] to determine the origins and clonality of metastasis [9, 10]. Single cell cancer phylogenetics is an evolving field. Multiple approaches, spanning different study designs and data sources are reviewed in [11]. Many phylogenetic inference methods assume point mutations as input or a small number of leaf nodes [12, 13, 14, 15]. However, emerging single cell platforms produce up to thousands of single cell genomes and are suitable for determining copy number aberrations (CNA) [16, 1]. The method of [17] assumes a tree inferred from CNA exists and incorporates it in inference of point mutation based phylogenies. Distance based and agglomerative clustering methods such as neighbour joining are scalable and are used to elucidate hierarchical structures over cells [18, 19]. While these are useful heuristics, they are statistically sub-optimal relative to likelihood based methods [20].

We describe sitka, a phylogenetic model and the associated Bayesian inference procedure designed specifically for inference based on CN information extracted from scWGS data. Our method addresses two key challenges: first, each CN event typically affects a large number of genomic sites, breaking the independence assumptions required by existing phylogenetic methods [21, 15, 13, 22]; second, while detailed modelling of dependent evolutionary processes is in principle possible, they entail computational requirements incompatible with the scale of modern scWGS data [23]. To confront these two difficulties, sitka uses a novel phylogenetic encoding of CN data, providing a statistical-computational trade-off by simplifying the site dependencies induced by rearrangements, while still forming a sound foundation to phylogenetic inference. Based on this encoding, we propose an innovative phylogenetic tree exploration move which makes the cost of Markov chain Monte Carlo (MCMC) iterations bounded by $O(|C| + |L|)$, where $|C|$ is the number of cells and $|L|$ is the number of loci. In contrast, existing off-the-shelf likelihood-based methods incur an iteration cost of $O(|C|\,|L|)$ [24, 13, 15]. Moreover, the novel move considers an exponential number of neighbouring trees whereas off-the-shelf moves consider a polynomial size set of neighbours.

We compare sitka with other tree-inference methods on three real-world datasets, including triple negative breast cancer patient derived xenograft samples, high grade serous ovarian primary and matched relapse samples. Since the true phylogeny is unknown, we design a phylogenetic goodness-of-fit framework to quantitatively assess the performance of our method and to visualize reconstruction confidence as well as violations of our assumptions.

We use the sitka inferred trees to analyse the topological properties of the real-world datasets. Finally, we introduce a model extension that enables the placement of single nucleotide variants (SNV) with high levels of missingness on a tree inferred from the CN data.

2 Results

2.1 Sitka: scalable single cell phylogenetic tree inference

Fig. 1 shows the workflow of the sitka method. Sitka is based on a transformation of single cell copy number matrices retaining only presence or absence of changes in copy number profiles between contiguous genomic bins. This transformation allows us to approximate a complex evolutionary process (integer-valued copy numbers, prone to a high degree of homoplasy and dense dependence structure across sites) using a probabilistic version of a perfect phylogeny (see **Supplementary Fig. 1**). We leverage the special structure created by the change point transformation to build a special purpose MCMC kernel, which has better computational scalability per move compared to classical phylogenetic kernels (Methods section 9.4.3).

We visualise the input data to sitka in a colour-coded matrix exemplified in **Supplementary Fig. 1**-**a**. Each row in the matrix corresponds to an individual cell that has been sequenced in a single-cell platform. Each column in the matrix is a locus that is represented by a bin (a contiguous set of genomic positions). We assume that the integer copy number of each bin has been estimated as a preprocessing step, e.g., using a hidden Markov model [16]. In **Supplementary Fig. 1**-**a** the copy number state is encoded by the colour of each entry in the matrix.

The output of sitka includes two types of directed rooted trees. Type I is the tree used for MCMC sampling in the inference procedure, and type II, which is derived from type I, is used in visualisation (**Fig. 2**-**a-c**). The set of nodes in a type I tree is given by the union of the cells, the CN change points (markers) under study, and a root node v^*. The topology of a type I tree bears the following phylogenetic interpretation: given a cell c in the tree, c is hypothesized to harbour the markers in the shortest path between c and the root node v^*, and only those markers. We enforce the constraint that all cells are leaf nodes, while markers can be either internal or leaf nodes. Markers placed at the leaves are interpreted as outliers, for example measured CN change points that are false positives.

We remove from the type I tree all marker nodes that are leaf nodes, i.e., markers that are not present in any cells. We also collapse into a single node, the list of connected marker nodes that have exactly one descendent (i.e., chains). **Supplementary Fig. 2** shows a small *type I tree*, its transformation to a *type II tree* and the respective marker matrix. We visualise the input matrix and the estimated tree simultaneously by sorting the individual cells (rows of the matrix) such that they line up with the position of the corresponding leaves of the tree.

Sitka uses change points as phylogenetic traits modelled using a relaxation of the perfect phylogeny assumption. Change points arising from non-overlapping CNA events do not break the perfect phylogeny assumption. **Supplementary Fig. 3** shows examples of overlapping CNA events and their effect on markers. The two scenarios that can lead to the violation of the perfect phylogeny assumption are (i) when a CNA gain event is followed by an overlapping loss event or (ii) when a loss event is followed by an overlapping loss event, and the second event removes either end-point of the first event. For both (i) and (ii), a violation occurs only when the second overlapping event hits the same copy as the first event.

Imposing a perfect phylogeny on the *observed* change points is restrictive, as we expect
both violations of the assumptions (e.g., due to homoplasy), and measurement noise. To
address this we use an observation model (Methods section 9.4.1) which assigns positive
probability to arbitrary deviations from the perfect phylogeny assumption, while encourag-
ing configurations where few loci and cells are involved in violations. Subsequently we
impose the perfect phylogeny assumption on a *latent* maker matrix defined as follows.
Given a type I tree t, the latent marker matrix x is a deterministic function $x = x(t)$. We
compute $x : t \to \{0, 1\}^{C \times L}$ by setting $x_{c,l} = 1$ if the single-cell c is a descendent of the
marker node l in tree t, and otherwise $x_{c,l} = 0$. We use $y_{c,l}$ to refer to the observed change
point l in individual cell c (Methods section 9.4.1).

Synthetic experiments show that sitka's performance degrades gracefully in the face of
some of the key types of expected violation of the perfect phylogeny assumption (**Fig. 3**-
a,b, Methods section 9.5).

2.2   Performance of sitka relative to alternative approaches

We compare the performance of sitka to alternative approaches on three scWGS datasets
introduced here (**Fig. 2**-**a-c**). The first dataset, $SA535$, is generated for this project and
contains 679 cells from three passages of a triple negative breast cancer (TNBC) patient
derived xenograft sample. Passages X1, X5, and X8 had 62, 369, and 231 cells post quality
filtering (Methods section 9.1) respectively. We also include 17 mostly diploid control cells.
These cells are combined to generate the input to the analysis pipeline (**Supplementary
Fig. 6**). The second dataset, labelled OVA, consists of cells from three samples taken
from a patient with high grade serous (HGS) ovarian cancer. The first sample, $SA1090$,
was from an ascites pre-treatment, while $SA922$ was from an ascites post-treatment. The
third sample, $SA921$, was taken from the ovary. See **Supplementary Fig. 7** for the tree and
the CNA profile heatmap for this dataset. The final dataset, $SA501$ [25], is another TNBC
xenograft tumour from 6 untreated passages, namely X2, X5, X6, X8, X11, and X15. After
filtering, 515, 236, 328, 189, 836, and 308 cells remain in each passage respectively (for
a total of 2,412 cells, see **Supplementary Fig. 8**). Table 1 shows the attrition after each
step of filtering cells per passage in each dataset.

To evaluate inferred trees from sitka and other tree reconstruction methods, we use a good-
ness of fit performance metric, which compares the compatibility of observed CN change
points with a given phylogeny using Youden's J index (Methods section 9.6, **Fig. 2**-**d**). Sitka
has the highest Youden's index across all three datasets. UPGMA and WPGMA perform simi-
larly on $SA501$ and $SA535$. UPGMA performs slightly better than WPGMA on the OVA dataset.
HDBSCAN has a close but slightly smaller Youden's index than UPGMA over the $SA535$ and
OVA datasets, but performs marginally better on $SA501$. NJ trails WPGMA on $SA501$ and
the OVA datasets, and has the lowest Youden's index on $SA535$. MrBayes performs well
on the smallest dataset, $SA535$, with MrBayes-np2 and MrBayes-np8 performing similar to
WPGMA, and MrBayesWithBinaryInput having achieved the second highest Youden's in-
dex. On the OVA data, MrBayesWithBinaryInput and MrBayes-np2 trail behind NJ, while
MrBayes-np2 has the lowest Youden's index among all methods on all datasets. Similar
to the OVA case, MrBayesWithBinaryInput and MrBayes-np2 trail behind NJ over the
$SA501$ dataset. Following [25], we run MrBayes for 10,000,000 generations. MrBayes-np8
had completed only 278,000 iterations running on $SA501$ after several days. The results
in this comparison suggest that sitka performs better than the baseline methods. Running

sitka on the real-world datasets took on average 22.3, 46.6, and 12.9 hours for the OVA, $SA501$, and $SA535$ datasets respectively, on a Linux workstation with 72 Intel Xeon Platinum 8272CL 2.60GHz CPU processors and 144 GB of memory. We complement these benchmarking results with experiments on synthetic data where sitka is also the highest performing method based on metrics measuring phylogenetic tree distance.

2.3   Single cell resolution phylogenetic inference in PDX

Here we analyse the foregoing three multi-sample datasets. To visualise the tree inference results we arrange the inferred consensus tree t (Methods section 9.4.5) and the cell-by-locus CN matrix side by side where the rows of the matrix correspond to the position of individual cells on the tree and the markers are arranged by their genomic position (**Fig. 1**-**h**). **Fig. 2**-**a-c** shows examples of the multi-channel visualisation where each marker is represented by a tuple of three different data-types or *channels*, namely: (i) the latent markers induced by the consensus tree, $x(t)$; (ii) the matrix of marginal posterior probability that cell c is a descendent of marker l, computed via the average $\bar{m}$ (**Fig. 1**-**g**, Methods section 9.4.5); and (iii) the sitka transformed input data $y_{c,l}$.

We use this view to assess potential discrepancies between the input data and the inferred tree. In most cells and loci (as quantified in **Supplementary Fig. 9.6**), the observed data is in close agreement with the inferred tree. In the following we provide some examples of disagreements. Consider first the ChrX in the $OV2295$ dataset (**Fig. 2**-**a**). ChrX has a long orange band (inferred marker in channel (i)) not matched by a black band (observed marker in channel (iii)) suggesting that a perfect phylogeny violation has occurred. The pattern in this marker is consistent with the presence of an ancestral event followed by a deletion. In **Fig. 2**-**b**, a set of diploid cells are attached to the root of the tree. These are control cells included in the experiment and correspond to a region in the bottom of the matrix with no inferred markers (orange bands) and almost no observed markers (black bands). In this dataset, there are change points where the observed marker has a high density (black band), but the tree is reconstructed with the marker absent (no matching orange band). Examples can be found in Chr1, Chr7 and Chr16. One possible explanation could be that the end-points of each event were detected as slightly shifted across cells. For instance, in **Supplementary Fig. 8** there are two loci with an amplification (CN state equal to three) in Chr1p where cells that harbour a mutation in the first locus appear not to have a mutation in the second locus, suggesting that the same event was called in the first locus in some cells, and in the second locus in others. An alternative hypothesis is that the cells in this dataset have a mutator phenotype that promotes CN mutations in these loci.

Supplementary Fig. 9 shows the distribution of mismatch rates for each dataset, defined as the fraction of times that the observed and inferred markers do not match, i.e., $\frac{1}{C}\sum_{c\in C}\mathbf{1}[y_{c,l} \neq x_{c,l}]$ for $l \in L$ (corresponding to the black and orange bands in **Fig. 2**-**a**). In $OV2295$, 41 markers (11%) have a mismatch rate of over 50%, where marker *chr15_67000001_67500000* has the highest mismatch rate at 70%. In SA501, 30 markers (11%) have a mismatch rate of over 50%, 13 of which (5%) have a mismatch rate of over 75%. SA535 has the lowest maximum mismatch rate at 49% (marker *15_72000001_72500000*).

2.4   Placement of SNVs using the CNA inferred tree

To determine the presence or absence of SNVs in cells using data with high levels of missingness, we develop an extension of sitka, the sitka-snv model. Given single cell level variant read counts, the model incorporates CN data to place SNVs on the sitka-inferred phylogenetic tree. This *backbone* CN tree, provides a principled way to pool statistical strength across groups of single cells sequenced at low coverage, including data from the DLP+ platform [16]. The output of the sitka-snv model is an *extended* tree that has marker nodes that comprise SNVs in addition to the original CNAs.

The SNVs are added to the existing CNA-based tree with the computational complexity of $O(|C| + |L|)$ per SNV. **Fig. 3**-**c** shows the result of SNV placement with the number of variant reads in $SA535$, corresponding to the tree shown in **Fig. 2**-**c**. **Supplementary Figs. 17**, **18**, and **19** show the number of variant reads and the matching SNV call probabilities for the $SA535$, OVA and $SA501$ datasets respectively. Sitka and sitka-snv provide a comprehensive genomic analysis tool for large scale low-coverage scWGS.

3   Discussion

In this work we use data in which the genome of the single cells CNA profiles are partitioned into bins of a fixed size (500Kb), each assigned a constant integer CN state. The relatively large size is due to the low coverage inherent to the scWGS platform, but it implies that the same bin may harbour multiple CNA events. Biological processes that result in complex DNA rearrangements could further increase the probability of having two hits in one bin [26, 27]. Such multiple hits can violate the perfect phylogeny assumptions. This highlights the importance of our goodness-of-fit and visualisation methods as they can detect such violations.

Structural variations such as chromothripsis, that affect multiple segments of the genome at the same time, make it difficult to determine the rate of CNA events and suggest that CNA events may not be suitable molecular clocks to estimate branch lengths. One possible remedy is to first infer the tree topology via markers based on CNA events and then conditioned on this topology, add SNVs to the tree. The number of SNVs on each edge of the tree may be used to inform branch lengths.

Our preprocessing pipeline excludes multiple cells from the analysis (see Table 1). We filter out a fraction of cells to remove contaminated cells, either doublets or mouse cells, cells with too many erroneous sequencing artefacts, and cycling cells. Removing a portion of the sequenced cells will decrease the statistical power to determine the subclonal structure of the population—an important application of this work—, and may bias the sampling against clones that have a higher division rate. We expect this will be an intrinsic limitation to any scWGS phylogenetic methods and this motivates the design of improved classification methods detecting cell cycling from genomic and imaging data.

Evaluating the performance of a phylogenetic reconstruction method on real-world datasets is difficult, mainly due to a lack of ground truth. One promising area of research is the use of CRISPR-Cas9 based lineage tracing [6]. In absence of ground truth data, we developed a goodness-of-fit framework that to our knowledge enables a first of a kind benchmarking of phylogenetic inference methods over real-world scWGS CNA datasets.

Phylogenetic tree reconstruction is a principled way to identify subpopulations in a heterogeneous single-cell population. This in turn enables the use of population genetics models that track the abundance of subpopulations over multiple timepoints [5] and to make inferences about the evolutionary forces acting on each clone. Further study with timeseries modelling will provide insight into therapeutic strategies promoting early intervention, drug combinations and evolution-aware approaches to clinical management.

4 Acknowledgements

This project was generously supported by the BC Cancer Foundation at BC Cancer and Cycle for Survival supporting Memorial Sloan Kettering Cancer Center. SPS holds the Nicholls Biondi Chair in Computational Oncology and is a Susan G. Komen Scholar (#GC233085). SA holds the Nan and Lorraine Robertson Chair in Breast Cancer and is a Canada Research Chair in Molecular Oncology (950-230610). Additional funding provided by the Terry Fox Research Institute Grant 1082, Canadian Cancer Society Research Institute Impact program Grant 705617, CIHR Grant FDN-148429, Breast Cancer Research Foundation award (BCRF-18-180, BCRF-19-180 and BCRF-20-180), MSK Cancer Center Support Grant/Core Grant (P30 CA008748), National Institutes of Health Grant (1RM1 HG011014-01), CCSRI Grant (#705636), the Cancer Research UK Grand Challenge Program, Canada Foundation for Innovation (40044) to SA, SPS and ABC. We extend our gratitude to Sarah P. Otto for her helpful comments on a draft of this manuscript.

5 Funding

6 Author Contributions

SS, FD: computational method development, data analysis, manuscript writing; KC: data analysis, manuscript writing; KRC, AR: method development; FK, data generation; DL, MA, AM, MW, TF: computational biology, data analysis; NR: manuscript editing; SA: data generation and oversight; SPS: method development and oversight; ABC: project conception and oversight, statistical inference method development, manuscript writing, senior responsible author;

7 Competing Interests

S.P.S. and S.A. are founders, shareholders, and consultants of Canexia Health Inc.

8 Code availability

Sitka is available at https://github.com/UBC-Stat-ML/sitkatree.git.

9 Methods

9.1 Pre-processing

The raw data contain cells that are either contaminated (e.g., contains biological material from mice) or have undesired sequencing artefacts. These include cells that were captured for DNA sequencing when undergoing mitosis. Since the sitka model does not account for such phenomena, the filtering is an important step. **Supplementary Fig. 15** shows the steps taken from pulling the raw data to the CNA integer matrix ready for sitka transformation (details in the Supplementary Information). Briefly, we remove control cells, cells with highly-noisy CN calls, and cells that have very few mapped reads. We also remove copy number bins that lie in difficult to sequence regions of the genome (bins with low-mappability). Finally, we drop cells that, based on their CNA profile, are suspected to be cycling cells.

9.2 The sitka transformation

To obtain the $C \times L_{\mathsf{Markers}}$ phylogenetic markers matrix y that comprises the input to the sitka model, we apply a lossy transformation to the $C \times L_{\mathsf{Bins}}$ CNA matrix a that involves computing the change in copy number state between two consecutive bins. **Supplementary Fig. 1** shows a small CNA matrix and its corresponding transformation into the marker matrix. For brevity, in what follows we assume that only one chromosome is used, so that $L_{\mathsf{Bins}} = L$ and $L_{\mathsf{Markers}} = L_{\mathsf{Bins}} - 1$. In practice, we use all available chromosomes, and $L_{\mathsf{Markers}} = L_{\mathsf{Bins}} - N_{\mathsf{Chr}}$ where N_{Chr} denotes the total number of chromosomes used.

Given a filtered cell-by-locus matrix a, we sort bins by their genomic position. Then in each chromosome, we compute markers as the binarised difference between consecutive bins. In other words, $y = (y_{c,l'})$ and $l' \in \{1, \ldots, L-1\}$, and

$$y_{c,l'} := \mathbf{1}\left(\left|a_{c,l'} - a_{c,l'+1}\right| > 0\right), \tag{1}$$

where $\mathbf{1}(x)$ is the indicator function.

9.3 Fixing jitter and selection of phylogenetic markers

The copy numbers available to us in this work are estimated independently for each cell. This is one reason why the start position (bin) of the same CN change event may be slightly different across cells, generating some *jitter*. We address this by enumerating each change point column in order of decreasing density (where the density of column l is given by $\sum_{c \in C} y_{c,l}/|C|$) and merging the column with its $k = 2$ immediate neighbours (see Algorithm 1 for details). An example of the result of the jitter correction heuristic is shown in **Fig. 1** panel **c**. To speed-up computation, only a subset of markers present in at least a minimum number of cells are chosen for phylogenetic inference. That is, we removed columns l in y with relative density $\sum_{c \in C} y_{c,l}/|C|$ less than a threshold, set to 5%. Larger values of this threshold may lead to less resolved clades in the inferred tree.

Algorithm 1 JitterFix

1: **procedure** JITTER-FIX(y, k)
2:     column-queue ← OrderByDensityDecreasing(y)
3:     columns-visited ← {}
4:     **for** column-index c in column-queue **do**
5:         neighbours ← neighbours (c, y, k)
6:         **for** column-index n in neighbours **do** ▷ The function neighbours is defined as the k columns to the left and k to the right of c (when applicable)
7:             **if** $n \notin$ columns-visited **then**
8:                 $y_{1:C,c} \leftarrow y_{1:C,c} \vee y_{1:C,n}$
9:                 $y_{1:C,n} \leftarrow 0$
10:                columns-visited ← columns-visited $\cup\, n$
11:     **return** y

9.4 The sitka model

9.4.1 Model description

The sitka model starts with the perfect phylogeny assumption for the latent variables $x_{c,l}$ but allows deviation from it via allowing noisy observations $y_{c,l}$. In a perfect phylogeny model, each phylogenetic trait arises only once on the rooted tree topology and all cells descending from that position will inherit that trait and no deletions are allowed.

Let C and L denote the disjoint sets of cells and loci respectively.

We posit an observation probability model $p(y|x, \theta)$, where θ are model parameters described shortly, and both x and y are cell by locus matrices, the former being latent (derived from the unobserved tree via $x = x(t)$), while the latter is the matrix obtained from the sitka transformation. To model errors in copy number calls as well as perfect phylogeny violations, we introduce false positive and negative rate parameters $r^{\mathsf{FP}} \in (0,1)$ and $r^{\mathsf{FN}} \in (0,1)$ respectively, and an error matrix

$$e^{r^{\mathsf{FP}}, r^{\mathsf{FN}}} = \begin{bmatrix} 1 - r^{\mathsf{FP}} & r^{\mathsf{FP}} \\ r^{\mathsf{FN}} & 1 - r^{\mathsf{FN}} \end{bmatrix},$$

$$p\left(y_{c,l} | x_{c,l}, r^{\mathsf{FP}}, r^{\mathsf{FN}}\right) = e^{r^{\mathsf{FP}}, r^{\mathsf{FN}}}_{x_{c,l}, y_{c,l}},$$

from which we set:

$$p(y|x, \theta) = \prod_{l \in L} \prod_{c \in C} p\left(y_{c,l} | x_{c,l}, r^{\mathsf{FP}}_{c,l}(\theta), r^{\mathsf{FN}}_{c,l}(\theta)\right).$$

We define two type of models, differing in the choice of functions $r^{\cdot}_{c,l}(\cdot)$ and dimensionality of θ: one based on global error parameters, and one based on locus-specific error parameters.

For the global parameterization, $\theta = \theta_{\mathsf{global}} = (r^{\mathsf{FN}}_{\mathsf{global}}, r^{\mathsf{FN}}_{\mathsf{global}})$, and the false positive and false negative functions are given by $r^{\mathsf{FP}}_{c,l}(\theta_{\mathsf{global}}) = r^{\mathsf{FP}}_{\mathsf{global}}$ and $r^{\mathsf{FN}}_{c,l}(\theta_{\mathsf{global}}) = r^{\mathsf{FN}}_{\mathsf{global}}$.

For the locus-specific error model, we set the error rates to be locus-dependent: $\theta = (r^{\mathsf{FP}}_1, r^{\mathsf{FP}}_2, \ldots, r^{\mathsf{FP}}_{|L|}, r^{\mathsf{FN}}_1, r^{\mathsf{FN}}_2, \ldots, r^{\mathsf{FN}}_{|L|})$, $r^{\mathsf{FP}}_{c,l}(\theta) = r^{\mathsf{FP}}_l$ and $r^{\mathsf{FN}}_{c,l}(\theta) = r^{\mathsf{FN}}_l$. With this extra flexibility, the model can discount the effect of a trait violating the perfect phylogeny assumption, by setting high error rates for the trait's locus.

The two parameterizations are compared in the Supplementary Information. We use the
global parameterization by default unless mentioned otherwise.

In both the global and locus-specific parameterizations, we need to construct a prior dis-
tribution $p(\theta)$ over the error parameters. Using a uniform prior distribution with support on
$[0, 1]$ can lead to pathological cases as shown in **Supplementary Fig. 4**. To avoid that, we
use the following prior distributions on the two types of error:

$$r^{\mathsf{FP}} \sim \mathsf{Uniform}\left(0, \overline{r^{\mathsf{FP}}}\right),$$
$$r^{\mathsf{FN}} \sim \mathsf{Uniform}\left(0, \overline{r^{\mathsf{FN}}}\right).$$

We use $\overline{r^{\mathsf{FP}}} = 1/10$ and $\overline{r^{\mathsf{FN}}} = 1/2$ as default in our experiments.

Next, we describe the prior $p(t)$ on phylogenies using a two-step generative process:

Sampling a mutation tree: let $\mathcal{V}^{\mathsf{m}} = L \cup \{v^*\}$ denote a vertex set composed of one vertex
for each of the $|L|$ loci plus one artificial root node v^*. The artificial root node induces
an implicit notion of direction on the edges, viewing them as pointing away from v^*.
Let $\mathcal{T}^{\mathsf{m}}$ denote the set of trees t^{m} spanning $\mathcal{V}^{\mathsf{m}}$. The interpretation of t^{m} is as follows:
there is a directed path from vertex/locus l to l' in t^{m} if and only if the trait indexed by
l is hypothesized to have emerged in a cell which is ancestral to the cell in which l'
emerged. Pick one element $t^{\mathsf{m}} \in \mathcal{T}^{\mathsf{m}}$.

Sampling cell assignments: assign each cell to a vertex in t^{m}. The interpretation of
assigning cell c to locus l is that among the traits under study, c is hypothesized to
possess only the traits visited by the shortest path from v^* to l in t_m. If a cell c is
assigned to v^*, the interpretation is that c is hypothesized to possess none of the
traits under study.

The number of possible trees obtained from this two-step sampling process is:

$$|\mathcal{T}| = |\mathcal{T}^{\mathsf{m}}||\{f : C \to L \cup \{v^*\}\}|$$
$$= (|L| + 1)^{(|L|+1)-2}(|L| + 1)^{|C|}$$
$$= (|L| + 1)^{|L|+|C|-1},$$

353 where we use Cayley's formula to compute $|\mathcal{T}^{\mathsf{m}}|$. Hence the uniform prior probability mass
354 function over the possible outputs of this two-step sampling process is given by:

$$p(t) = \frac{\mathbf{1}[t \in \mathcal{T}]}{(|L| + 1)^{|L|+|C|-1}},$$

where $\mathcal{T}$ is the set of all perfect phylogenetic trees that result from the two step generative
process described above. This simple prior has a useful property: if a collection of say
two splits are supported by m_1 and m_2 traits, then the prior probability for an additional
trait to support the first versus second split is proportional to $(m_1 + 1, m_2 + 1)$. Therefore,
there is a "rich gets richer" behaviour built-in into the prior, which is viewed as useful in
many Bayesian non-parametric models. Of course, more complicated priors over $\mathcal{T}$ could
be easily incorporated as the complexity of inference typically comes from the likelihood
rather than the prior. Simulation from the prior can be performed using Wilson's algorithm
[28], followed by independent categorical sampling to simulate the cell assignments.

9.4.2 Inference

The posterior distribution,

$$\pi(t, \theta) \propto p(t)p(\theta)p(y|x(t), \theta),$$

is approximated using MCMC. Two MCMC moves are used, described in the next two sections. The posterior distribution is summarized using a Bayes estimator described in Section 9.4.5. The model is implemented in the Blang probabilistic programming language [29].

9.4.3 MCMC tree exploration move

Sitka uses a tree sampling move to efficiently explore, at each MCMC iteration, the posterior distribution in a large neighbourhood of a given tree. Given a tree t and locus l, we define a neighbourhood $N^l(t) \subset \mathcal{T}$ by removing l from t, and considering all possible ways to reattach l and hence defining a neighbourhood of phylogenetic trees (we also implemented a separate move reattaching cell nodes instead of locus nodes, its derivation follows similar lines as the move described in this section). The process of removing l is called an *edge-contraction* (removing an edge after connecting its two end-points) while the process of adding back a locus is called an *edge-insertion*. An edge insertion can be described as follows:

1. Pick a non-cell vertex v, i.e. an element from the set $R = \{v^*\} \cup L\backslash\{l\}$ where v^* is the root node.

2. Pick any subset of v's descendent subtrees and disconnect them from v.

3. Add a new node l under v and move the selected nodes from step 2 above and attach them to l.

Fig. 1-**f** (right) shows an example of an edge-insertion. A locus named *chr15_5950* coloured red, has three children at MCMC iteration 100. This corresponds to node v in the above description. In step 2 of the edge insertion process, two of its children, namely cells *RC07C* and *RC05C4* are chosen and disconnected from v. They are then inserted under locus *chr1_4900*, corresponding to l, which becomes a child of locus *chr15_5950*.

In the following, we derive the probability distributions to be used in steps 1 and 2 above that lead to a Gibbs sampling algorithm (i.e. an MCMC move with no rejection step). The Gibbs sampler first selects a locus l from a fixed distribution (a tuning parameter), which we take for simplicity as being uniform over the $|L|$ loci.

After having sampled l, we partition $N^l(t_{\backslash l})$ into blocks corresponding to the choice of node v made in Step 1, $N^l(t_{\backslash l}) = \cup_v N^l_v(t_{\backslash l})$. The Gibbs conditional probabilities required in step 1 above are of the form:

$$\bar{\rho}_v = \frac{\rho_v}{\sum_{\tilde{v} \in R} \rho_{\tilde{v}}},$$

where:

$$\rho_v = \sum_{t \in N^l_v(t_{\backslash l})} p(t)p(y|x(t), \theta), \tag{2}$$

and $t_{\setminus l}$ denotes the tree obtained after performing an edge contraction, where the contracted edge is between l and the parent node of l. To compute ρ_v efficiently, we start with the following likelihood recursion for all vertex v in $t_{\setminus l}$. First, for all vertices c corresponding to a cell and $b \in \{0, 1\}$, define:

$$p_c^b = p\left(y_{c,l}|b, \theta\right).$$

Next, we perform the following bottom-up recursion for all subtrees of $t_{\setminus l}$: for all $v \in R$, $b \in \{0, 1\}$,

$$p_v^b = \prod_{v'' \in \text{children}(v)} p_{v''}^b,$$

where $\text{children}(v)$ denotes the list of children of vertex v.

We can now return to the problem of computing $\bar{\rho}_v$. First, observe that the sum in Equation (2) can be re-indexed by a bit vector $\boldsymbol{b} = (b_1, b_2, \ldots, b_k)$, $b_{v''} \in \{0, 1\}$ of length equal to $k = |\text{children}(v)|$. Each bit $b_{v''}$ is equal to one if children v'' is to be moved into a child of v' (refer to **Supplementary Fig. 5**), and zero if it is to stay as a child of v. For each possible assignment, we obtain a tree $t \in N_v^l(t_{\setminus l})$, and its probability can be decomposed into factors corresponding to cells that are descendant of v (denoted C_v, solid red thick line under the tree of **Supplementary Fig. 5-B**) and those that are not (denoted $C_{\setminus v}$, dashed green thick line under the tree of **Supplementary Fig. 5-B**).

The product of the likelihood factors corresponding to cells that are not descendants of v ("outside product") does not depend on the choice of the bit vector. This outside product can be obtained as follows:

$$\prod_{c \in C_{\setminus v}} p_c^0 = \frac{p_{v*}^0}{p_v^0}.$$

Note that this assumes $p_v^0 > 0$. As a workaround to cases where there are structural zeros, we recommend injecting small numerical values if $p_v^0 = 0$ (we used 10^{-6} in our implementation).

For the cells under v, we now have to take into account whether they are selected under the newly introduced locus or not. More precisely, for each of the children $v_1, v_2, \ldots, v_k$, we have to take into account the value of the bit vector $b = (b_1, b_2, \ldots, b_k)$. The sum over possible assignments written naively has a number of terms which is exponential in k, but can be rewritten into a product over k factors:

$$\sum_{t \in N_v^l(t_{\setminus l})} \prod_{c \in C_v} p_c^{x_{c,l}(t)} = \sum_{b_1=0}^{1} \cdots \sum_{b_k=0}^{1} \prod_{i=1}^{k} p_{v_i}^{b_i} = \prod_{i=1}^{k}(p_{v_i}^0 + p_{v_i}^1).$$

Putting it all together, we obtain for some constants K_i independent of v:

$$\rho_v = K_1 \sum_{t \in N_v^l(t_{\setminus l})} p(y|x(t), \theta)$$

$$= K_1 \sum_{t \in N_v^l(t_{\setminus l})} \prod_{l' \in L} \prod_{c \in C} p\left(y_{c,l'}|x_{c,l'}(t), r_{c,l'}^{\mathsf{FP}}(\theta), r_{c,l'}^{\mathsf{FN}}(\theta)\right)$$

$$= K_1 \left(\prod_{l' \in L, l' \neq l} \prod_{c \in C} p\left(y_{c,l'} | x_{c,l'}(t), r_{c,l'}^{\mathsf{FP}}(\theta), r_{c,l'}^{\mathsf{FN}}(\theta)\right) \right) \sum_{t \in N_v^l\left(t_{\backslash l}\right)} \prod_{c \in C} p\left(y_{c,l} | x_{c,l}(t), r_{c,l}^{\mathsf{FP}}(\theta), r_{c,l}^{\mathsf{FN}}(\theta)\right)$$

$$= K_1 K_2 \sum_{t \in N_v^l\left(t_{\backslash l}\right)} \prod_{c \in C} p\left(y_{c,l} | x_{c,l}(t), r_{c,l}^{\mathsf{FP}}(\theta), r_{c,l}^{\mathsf{FN}}(\theta)\right)$$

$$= K_1 K_2 \sum_{t \in N_v^l\left(t_{\backslash l}\right)} \prod_{c \in C} p_c^{x_{c,l}(t)}$$

$$= K_1 K_2 \sum_{t \in N_v^l\left(t_{\backslash l}\right)} \left(\prod_{c \in C_v} p_c^{x_{c,l}(t)} \right) \left(\prod_{c \in C_{\backslash v}} p_c^{x_{c,l}(t)} \right)$$

$$= K_1 K_2 \left(\prod_{c \in C_{\backslash v}} p_c^{x_{c,l}(t)} \right) \sum_{t \in N_v^l\left(t_{\backslash l}\right)} \prod_{c \in C_v} p_c^{x_{c,l}(t)}$$

$$= K_1 K_2 \left(\frac{p_{v^*}^0}{p_v^0} \right) \sum_{t \in N_v^l\left(t_{\backslash l}\right)} \prod_{c \in C_v} p_c^{x_{c,l}(t)}$$

$$= K_1 K_2 \left(\frac{p_{v^*}^0}{p_v^0} \right) \prod_{i=1}^{k} (p_{v_i}^0 + p_{v_i}^1)$$

$$= K_1 K_2 K_3 \frac{\prod_{i=1}^{k}(p_{v_i}^0 + p_{v_i}^1)}{p_v^0}.$$

414 Putting these together we can compute the probabilities required in step 1 above:

$$\bar{\rho}_v = \frac{\rho_v}{\sum_{\tilde{v} \in R} \rho_{\tilde{v}}} \tag{3}$$

$$= \frac{\left(\frac{\prod_{v_i \in \mathsf{children}(v)} \left(p_{v_i}^0 + p_{v_i}^1\right)}{p_v^0} \right)}{\sum_{\tilde{v} \in R} \left(\frac{\prod_{v_i' \in \mathsf{children}(\tilde{v})} \left(p_{v_i'}^0 + p_{v_i'}^1\right)}{p_{\tilde{v}}^0} \right)}. \tag{4}$$

415 Once v is sampled, we choose a subset of its children to move to v' by sampling k inde-
416 pendent Bernoulli random variables with the i-th one having bias

$$\frac{p_{v_i}^1}{p_{v_i}^0 + p_{v_i}^1},$$

417 and selecting children with corresponding Bernoulli realisations of 1.

9.4.4 MCMC parameter exploration move

419 To resample the parameters θ we condition on the tree t, and hence on the hidden state
420 matrix x, and update θ in a Metropolis-within-Gibbs framework. There are two different

samplers depending on whether the global or locus-specific parameterization is used. We start with describing the former.

We compute two sufficient statistics from the matrix x (i) the number of false positive instances, n^{FP}, and (ii) the number of false negative instances, n^{FN},

$$n^{\mathsf{FP}} = n^{\mathsf{FP}}(x) = \sum_{c \in C} \sum_{l \in L} \mathbf{1}[x_{c,l} = 0, y_{c,l} = 1]$$
$$n^{\mathsf{FN}} = n^{\mathsf{FN}}(x) = \sum_{c \in C} \sum_{l \in L} \mathbf{1}[x_{c,l} = 1, y_{c,l} = 0].$$

Based on these cached statistics, we obtain:

$$p(y|x, \theta_{\mathsf{global}}) \propto \left(r^{\mathsf{FP}} \right)^{n^{\mathsf{FP}}} \left(r^{\mathsf{FN}} \right)^{n^{\mathsf{FN}}} \left(1 - r^{\mathsf{FP}} \right)^{n^{\mathsf{N}} - n^{\mathsf{FN}}} \left(1 - r^{\mathsf{FN}} \right)^{n^{\mathsf{P}} - n^{\mathsf{FP}}}, \tag{5}$$

where the the number of positive n^{P} and negative n^{N} instances in the data can be pre-computed,

$$n^{\mathsf{P}} = \sum_{c \in C} \sum_{l \in L} \mathbf{1}[y_{c,l} = 1]$$
$$n^{\mathsf{N}} = |C||L| - n^{\mathsf{P}}.$$

Based on the above expression, which can be evaluated in $O(1)$ once the statistics are computed, we then use a slice sampling algorithm to update the parameters [30].

The sampler for the locus-specific parameterization is very similar. The main difference is that we compute the statistics for each locus l:

$$n_l^{\mathsf{FP}} = n_l^{\mathsf{FP}}(x) = \sum_{c \in C} \mathbf{1}[x_{c,l} = 0, y_{c,l} = 1]$$
$$n_l^{\mathsf{FN}} = n_l^{\mathsf{FN}}(x) = \sum_{c \in C} \mathbf{1}[x_{c,l} = 1, y_{c,l} = 0]$$
$$n_l^{\mathsf{P}} = \sum_{c \in C} \mathbf{1}[y_{c,l} = 1]$$
$$n_l^{\mathsf{N}} = |C| - n_l^{\mathsf{P}}$$
$$p(y|x, \theta) = \prod_l \left(r_l^{\mathsf{FP}} \right)^{n_l^{\mathsf{FP}}} \left(r_l^{\mathsf{FN}} \right)^{n_l^{\mathsf{FN}}} \left(1 - r_l^{\mathsf{FP}} \right)^{n_l^{\mathsf{N}} - n_l^{\mathsf{FN}}} \left(1 - r_l^{\mathsf{FN}} \right)^{n_l^{\mathsf{P}} - n_l^{\mathsf{FP}}}.$$

Then a slice sampling move is applied to each locus-specific parameter.

9.4.5 Posterior summarization

Here we approximate the Bayes estimator by minimising the Bayes risk:

$$\operatorname{argmin}_{t \in \mathcal{T}} \sum_{t' \in \mathcal{T}} \int L(t, t') \pi(t, \mathrm{d}\theta), \tag{6}$$

using the L1 metric on the matrices of induced indicators $x(t)$ as the loss function:

$$L(t, t') = \sum_{l \in L} \sum_{c \in C} |x_{c,l}(t) - x_{c,l}(t')|.$$

It is useful to define the marginal indicators $m_{c,l}$ that can be conceptualised as the posterior probability of cell c to have trait l:

$$m_{c,l} = \sum_{t \in \mathcal{T}} \int \mathbf{1}[x_{c,l}(t) = 1]\pi(t, \mathrm{d}\theta).$$

Using the MCMC samples $t^1, t^2, \ldots, t^N$, we obtain a Monte Carlo approximation:

$$\bar{m}_{c,l} = \frac{1}{N} \sum_{i=1}^{N} x_{c,l}(t^i) \to m_{c,l},$$

with probability one.

Fig. 1-**g** shows an example of the matrix m each element of which is one of the approximated $\bar{m}_{c,l}$. We can now write the objective function of Equation (6) via the above marginal indicators:

$$
\begin{aligned}
\sum_{t' \in \mathcal{T}} \int L(t, t')\pi(t, \mathrm{d}\theta) &= \sum_{t' \in \mathcal{T}} \int \sum_{l \in L} \sum_{c \in C} |x_{c,l}(t) - x_{c,l}(t')|\pi(t, \mathrm{d}\theta) \\
&= \sum_{l \in L} \sum_{c \in C} \sum_{t' \in \mathcal{T}} \int |x_{c,l}(t) - x_{c,l}(t')|\pi(t, \mathrm{d}\theta) \\
&= \sum_{l \in L} \sum_{c \in C} \left\{ m_{c,l}(1 - x_{c,l}(t)) + (1 - m_{c,l})x_{c,l}(t) \right\} \\
&= \sum_{l \in L} \sum_{c \in C} \left\{ x_{c,l}(t) - 2m_{c,l}x_{c,l}(t) \right\} + \text{constant.} \quad (7)
\end{aligned}
$$

We use a greedy algorithm to approximately minimize Equation (7). We start with a star tree with leaves C rooted at v^* and add loci from L one by one from a locus queue sorted by priority score. The priority score of each locus l is computed as

$$\text{priority}(l) = \max_{t' \in N^l(t)} \frac{q(t')}{\sum_{t'' \in N^l(t)} q(t'')},$$

where

$$q(x) = \prod_{c \in C} \prod_{l \in L(x)} q_{c,l}(x_{c,l})$$

$$q_{c,l}(x_{c,l}) = 2m_{c,l}x_{c,l} - x_{c,l}.$$

The quantities in the priority queue can be computed as in Section 9.4.3. We take the result of the minimization of the Bayes risk as the consensus tree.

9.4.6 Consensus tree and CNA heatmap visualisation

To visualize the consensus tree, we collapse the chains (sequence of loci having only one child) as well as remove the subtrees containing no cells. We align the leaves of the tree which correspond to cells after collapsing to the rows of a cell-locus matrix.

9.5 Synthetic experiments

9.5.1 Benchmarking

To assess the performance of sitka against alternative approaches, we ran inference on 72 simulated datasets of varying characteristics. We will refer to this set of datasets as $S72$; its simulation procedure is described in Section 9.5.3. For each dataset in $S72$, we scored each method by computing the Robinson-Foulds (RF) [31] distance between the simulated tree and the inferred tree. The scores were normalized within each dataset by dividing each method's score by the worst performing method's score.

We compared sitka against the following baseline methods: `UPGMA`, `WPGMA`, `NJ`, `HDBSCAN`, and balanced and ordinary least-squares minimum-evolution methods (`BME`, `OME` respectively) of [32]. We also report the score of a uniformly random bifurcating tree, `Uniform`, to help interpret the absolute scores. Each method was given raw data from $S72$, as well as input identical to that of sitka, i.e., filtered binary marker data. Sitka's inference settings are summarized in **Supplementary Table 2**.

Baseline methods performed significantly worse with sitka's input and are thus omitted from the following summary. Sitka's normalized RF score (0.62 ± 0.06) dominated all baseline methods, the next best performer was `BME` (0.90 ± 0.08). Sitka ranked first in all 72 but one set of data, where it ranked 6 for one dataset of size 500×800. Summing each method's rank over all datasets, sitka scored a total rank of 77, while `BME` scored 193.5 (lower is better). These results are summarized in **Supplementary Fig. 12**.

9.5.2 Exploratory experiments within sitka

To explore the effectiveness of global versus *local* (locus-specific) parameterization (Section 9.4.1), and the posterior summarization method (Section 9.4.5), we ran inference on 10 datasets. We will refer to this set of datasets as $S10$; its simulation procedure is described in Section 9.5.3. Inference settings are summarized in **Supplementary Table 2**.

RF distances from the *best-possible tree* were computed as a metric. The best-possible tree is defined as the perfect phylogenetic tree constructed from the noiseless synthetic, unviolated cell-locus matrix data. For a baseline to compare the greedy estimator (GE) of Section 9.4.5 with, consider the *trace search estimator* (TSE). The TSE is defined as a tree in the sampler trace that minimizes the sample L1 distance (Section 9.4.5).

The GE outperformed the TSE under both models. This suggests the proposed GE can, informally, harness more information from the posterior and more accurately summarize a posterior to arrive at a consensus tree than, say, a search over the posterior under some criterion. Under the TSE, the global model (0.44 ± 0.09) outperformed the local model (0.71 ± 0.06). This observation suggests that the local parameterization has a strong influence on the trace (in tree space) of our sampler, as the TSE is essentially a search

over the posterior sample. Under the GE, the global model (0.31 ± 0.07) and local model (0.30 ± 0.07) performed evenly well. This observation suggests that the choice of parameterization does not heavily influence the information contained in the marginal posterior over trees. Ultimately this experiment suggests that the GE summarizes the marginal posterior sufficiently well such that the global model, the simpler model of the two, suffices for reconstructing phylogenies and should be the preferred model. A summarizing plot is shown in **Supplementary Fig. 13**.

In our final synthetic experiment, we aimed to study the effects of perfect phylogeny assumption violations on the reconstruction of trees, and attempted to draw connections to real world data. The two violations considered are infinite sites and loss violations, described in Section 9.5.3. Inference was performed on 130 datasets ($S130$). Inference settings are summarized in **Supplementary Table 2**, and the simulation procedure for $S130$ is described in Section 9.5.3.

The experiment results are summarized in **Fig. 3**-**a**. Holding one violation rate fixed at zero and varying the other, we observed linear effects for both types of violations. The results suggest sitka is more robust to infinite sites violations, with estimated effects to be 0.31 ± 0.07, which is much less than loss violations (0.47 ± 0.07). When varied together, the linear effects were estimated to be $0.25 \pm 0.04, 0.38 \pm 0.04$ respectively. In an attempt to draw connections to real datasets, we estimated both violation rates of real data to be less than 0.25 (the estimation procedure is described below; **Fig. 3**-**b**). These observations suggest sitka should perform reasonably well for the real datasets considered in this study, with RF distances in the vicinity of $(0.2, 0.3)$.

The violation rate estimation procedure was performed post-inference, and can be described as follows. Given the inferred tree and its corresponding marker matrix x (as in Section 9.4.1), and the sitka-transformed marker matrix y (as in Section 9.2), define the difference matrix $z := x - y$, i.e., z has entries $z_{i,j} = x_{i,j} - y_{i,j}$. Next, define z_{Loss} with entries $z_{i,j}^{\mathsf{Loss}} := \mathbf{1}(z_{i,j} > 0)$, and similarly z_{IS} with entries $z_{i,j}^{\mathsf{IS}} := \mathbf{1}(z_{i,j} < 0)$. Given an integer-valued threshold $\epsilon_{\mathsf{v}} > 0$, we say a column or trait l in z_v (for $v \in \{\mathsf{Loss}, \mathsf{IS}\}$) has a violation if there exists an *island* of size at least as large as ϵ_{v}. An island in column l is defined to be any sequence of row indices $i, i+1, \ldots, i+s$ such that $z_{i,l}^v = z_{i+1,l}^v = \cdots = z_{i+s,l}^v = 1$ and $z_{i-1,l}^v, z_{i+s+1,l}^v$ are, not necessarily the same, 0 or undefined. Finally, the proportion of columns with a given type of violation, loss or infinite sites, is taken to be the violation rate estimate. The intuition behind this estimation procedure is to identify the proportion of loci where the inferred tree (or its marker matrix) is in contradiction with observations.

9.5.3 Data simulation

Datasets in $S72$ were generated in two steps: (i) simulate a cell tree and its corresponding CNA data, and (ii) inject noise into the CNA data from step one.

In the first step we used the simulator of [33] to generate trees along with CNAs, where leaf nodes represent observed cells and internal nodes represent latent ancestral cells, i.e., unobserved cells. An edge in the tree represents an ancestral relationship between the respective cells.

The simulator of [33] itself consists of two parts, which we briefly describe as follows. First, the simulator samples a tree based on a generalization of the Blum-François Beta-

splitting model [34, 35], which is inspired by the Beta-splitting model of [36]. The Beta-splitting model is particularly well-suited for generating a wide range of topologies, varying from balanced to imbalanced tree structures. Second, given a tree, CNAs are simulated on the edges of the tree where the number and size of CNAs are drawn from Poisson and exponential distributions respectively. The simulator also accounts for clonal whole chromosome amplification events, motivated by punctuated evolution models [37].

The second step of our synthetic data simulation process, independent of [33], injects noise into a cell by locus input CNA matrix y, and outputs a noisy matrix of the same size. Three types of noise were employed, namely, uniform noise, jitter noise, and a doubling noise.

The uniform noise is parameterized by false positive (FPR) and false negative (FNR) rate parameters. For each element of the input matrix y_{ij}, add an integer $N_{ij} \sim$ Binomial(y_{ij}, FNR) or subtract an integer $M_{ij} \sim$ Binomial$(1, \text{FPR})$.

The doubling noise is parameterized by a probability p_{d}: for each row of the CNA matrix y, draw a factor K where $K - 1 \sim$ Binomial$(1, p_{\text{d}})$, which is then multiplied to the row of the CNA matrix as noise. This procedure effectively, on average, doubles the copy number values for p_{d} proportion of cells in the sample.

The jitter noise is parameterized by a probability p_{j}. First, map the CNA matrix to its marker matrix. Then for each marker, the locus corresponding to the marker is randomly duplicated to the previous bin(s), or the next bin(s). The number of bins J to be overwritten — zero, one, or two — is drawn from a Binomial$(2, p_{\text{j}})$ distribution.

Datasets in $S72$ were of sizes $\{500, 1000, 1500, 2000, 2500, 3000\}$ cells by (approximately) $\{400, 600, 800\}$ markers. For each combination of sizes, we generated four datasets based on different random seeds to make a total of $6 \times 3 \times 4 = 72$ datasets. The approximate number of markers is the target number of markers after correcting for jitter and filtering. **Supplementary Fig. 11** shows the CNA profiles of a subset of simulated data.

To describe the simulation parameters used for $S72$, we follow the terminologies and notation used in [33]. For generating trees, the α and β values parameterize the generalized Beta-splitting model. We drew α, β from a uniform distribution on the interval $(-1, 10)$. For generating CNA data, the mean number of CNA to be added to a branch in the tree was chosen to generate data with approximately the number of desired markers post filtering and jitter-fixing. The multiplier of the mean CNA on the root was set to 8, the whole amplification rate (rate of an allele chosen to be amplified) was set to 0.5. The remaining parameters used default settings. See [33] for a more thorough description of parameters.

For injecting noise, we drew the uniform noise parameters FPR and FNR from uniform distributions on the intervals $(0.001, 0.01), (0.01, 0.03)$ respectively. The doubling noise parameter p_{d} was drawn from a Uniform$(0.03, 0.07)$ distribution. The jitter noise parameter p_{j} was drawn from a Uniform$(0.3, 0.7)$ distribution.

Datasets in $S10$ and $S130$ were also generated in two steps: (i) simulate a cell tree and its corresponding binary marker data satisfying perfect phylogeny assumptions, and (ii) inject noise and/or violations into the the binary marker data from step one.

In the first step, a tree is generated via Kingman's coalescent [38].[1] Briefly, we sample a coalescent tree for the set of cells C by uniformly selecting pairs of cells $c_i, c_j \in C$ to coalesce backwards in time. The waiting time, or the branch length, between each event is exponentially distributed. Conditionally on the coalescent tree and given a set of loci L, we simulate a $|C| \times |L|$ marker matrix y. Every entry $y_{i,j}$ is initialized to 0. Then for each column l, we select a subset of cells C' from C to set $y_{i,l}$ to 1, for all $i \in C'$. The subset of cells is sampled by choosing a branch on the tree with probability proportional to the branch length, and selecting all cells descendant from the selected branch. In essence, we are simulating the number of events via a Poisson process, and directly mapping these events to the cell-locus marker matrix. The above concludes the data generation procedure satisfying perfect phylogeny assumptions.

In the second step of $S10$'s simulator, we injected artificial noise by introducing standard false positive and negative values into y. This concludes $S10$'s simulator. The simulator for $S130$ has an additional sampling step for controlling the degree of perfect phylogeny violations. We considered two types of violations: (i) the loss of markers along a tree's branches, and (ii) the violation of the infinite sites (IS) assumption, that is, the occurrence of multiple distinct events in the same locus.

The procedure for simulating loss of marker events can be described as follows. First, randomly select a locus l, then identify the most recent common ancestor a for the set of cells $\{i : y_{i,l} = 1\}$. Given a, sample a cell d descendant of a (including a). Finally, the loss event is simulated by reverting $y_{i,l}$ to 0, for all i descendant of, and including, d.

IS model violations were simulated as follows. Uniformly sample a pair of loci (j, k), and merge $y_{.,j}, y_{.,k}$ into one column, yielding a cell-locus matrix of size one less than the original size. However, to maintain control over $|L|$, datasets in $S130$ were simulated with $|L| + N_{\text{IS}}$ loci such that after simulating IS violations, we recover a matrix of size $|C| \times |L|$, where N_{IS} is the number of IS violations.

The total number of loss and infinite sites violation events (N_{Loss}, N_{IS}) were drawn from binomial distributions with probability $p_{\text{Loss}}, p_{\text{IS}}$ respectively (and size $|L|$). As a final step, false positives and negatives were artificially injected.

For both $S10$ and $S130$, datasets of size $|C| \times |L| = 500 \times 100$ with FNR and FPR both set to 0.002 were generated. For $S130$, the unordered pair $(p_{\text{Loss}}, p_{\text{IS}})$ were set to values in $\{(0,0), (0.1, 0.1), \dots, (0.4, 0.4)\} \cup \{(0, 0.1), (0, 0.2), (0, 0.3), (0, 0.4)\}$. For each configuration of simulation parameters, 10 different seeds were used to generate a total of 10 and 130 datasets for $S10$ and $S130$ respectively.

9.6 Goodness-of-fit

To evaluate the goodness-of-fit of inferred trees on real data, we suggest a test comparing the posterior distribution over entries of the matrix x with the data y.

Consider an inferred tree, τ and the corresponding genotype matrix $g = g(\tau)$. We set $g(\tau) = x(\tau)$ for trees inferred from sitka. For trees inferred from the baseline methods, we define $g(\tau)$ as $x(\tau)$ except that $g : \tau \to \{0,1\}^{C \times U}$ where U the set of internal nodes of τ (Methods section 9.4.1). In general the inferred trees from the baseline methods do not

---

[1]We used the R packages [39, 40] for simulation.

have named internal nodes, nor do they have the same number of internal nodes as the number of loci L. Therefore we do not know which locus in the inferred tree τ corresponds to which locus in the matrix y. We note that this is not the case with trees inferred from sitka where the internal nodes of the tree correspond to the columns of the induced genotype matrix g. As a result, for methods other than sitka, for each column in the input data matrix, we pick a clade in τ that has the highest prediction accuracy for the entries in that column.

For each method, we report Youden's J index [41] which is equal to the sum of the sensitivity and specificity minus 1. We now define a binary classification counts matrix function h, i.e., a function which, for two vectors w and z of length C, forms the confusion matrix:

$$h_{i,j}(w, z) = \sum_{c \in C} \mathbf{1}\left(w_c = i\right) \mathbf{1}\left(z_c = j\right).$$

For example $h_{0,0}(w, z)$ would count the number of times both elements of w and z were equal to zero (or *true negative*). We define accuracy for a given confusion matrix o computed from the h map above as:

$$\text{acc}(o) := \frac{o_{0,0} + o_{1,1}}{\sum_{i,j} o_{i,j}}.$$

We further define sensitivity and specificity as

$$\text{sensitivity}(o) := \frac{o_{1,1}}{o_{1,1} + o_{1,0}},$$
$$\text{specificity}(o) := \frac{o_{0,0}}{o_{0,0} + o_{0,1}},$$
$$\text{youden}(o) := \text{sensitivity}(o) + \text{specificity}(o) - 1.$$

For a given tree τ and its corresponding matrix g we compute the Youden's score as follows:

1. for all locus l in y, $o_l = \text{argmax}_{o'_l, l' \in \text{columns(g)}} \text{acc}(o_{l'})$,

2. $o_\tau = \sum_{l' \in, \text{columns(g)}} o_{l'}$

3. $\text{youden}_\tau := \text{youden}(o_\tau)$.

That is for each locus in y, we take the clade that among all possible clades in τ maximizes the accuracy in predicting which cells are present in the l-th column of y. We then sum over all these scores to compute a confusion matrix for τ and use this agglomerative matrix to compute the Youden's score for the tree. We use the delta method to calculate confidence intervals. **Fig. 2**-**d** shows the Youden's score and its 95% confidence interval for sitka and 6 baseline methods on 3 different real-world datasets. Sitka has a higher score than all competing methods.

9.7 Application: assignment of single nucleotide variants

Here we posit an observation probability model for adding single nucleotide variant (SNV) data to an existing phylogenetic tree.

For locus l in cell c, let $y_{c,l}^{SNV} = (d_{c,l}, \nu_{c,l}, c_{c,l})$ denote the observed SNV data where the
total number of reads, the number of reads with a variant allele, and the corresponding
copy number are indicated by $d_{c,l}$, $\nu_{c,l}$, and $c_{c,l}$ respectively.

We use $x_{c,l}^{SNV}$ to denote an indicator variable taking the value one if and only if an an-
cestor of cell c harboured a single nucleotide alteration event at locus l. This variable is
unobserved and the focus of inference in this section. As in the sitka model, we assume a
perfect phylogeny structure on these indicator variables, and add an error model to relate
$x_{c,l}^{SNV}$ to the observed data while allowing violations of the perfect phylogeny assumption
and measurement noise. In the context of single nucleotide data, this is similar to [12]. The
parameters of the error model are denoted $\theta^{SNV} = (\epsilon_{FP}, \epsilon_{FN})$, where ϵ_{FP} and ϵ_{FN} are
false positive rate and false negative rates, respectively. Define:

$$q_{c,l}^b = p(y_{c,l}^{SNV}|x_{c,l}^{SNV}, \theta^{SNV}) = p(\nu_{c,l}|d_{c,l}, c_{c,l}, x_{c,l}^{SNV} = b, \theta^{SNV}), \tag{8}$$

where $d_{c,l}$ and $c_{c,l}$ are given inputs. The likelihood probability of cell node c is denoted by
$q_{c,l}^b$, where $b \in \{0, 1\}$. For $b = 1$, $q_{c,l}^b$ reflects the likelihood of cell c being mutated at locus l;
and for $b = 0$, $q_{c,l}^b$ reflects the likelihood of cell c not being mutated at locus l. For $d_{c,l} = 0$,
we set $q_{c,l}^b = 0.5$.

The probability $q_{c,l}^b$ is obtained by marginalizing a mixture of binomial distributions depend-
ing on all possible genotype states of locus l at cell c. Given the copy number $c_{c,l}$, the
possible genotype states are $\mathcal{G} = \{A \dots A, AA \dots B, A \dots BB, \dots, B \dots B\}$, where each
element has a length equal to $c_{c,l}$. For example, the genotype AAB refers to a genotype
with one variant allele B and two reference alleles A. For each genotype state g_i, where i
indexes the elements of $\mathcal{G}$, the mean parameter of the corresponding binomial distribution
is denoted by $\xi_{c,l}^i$:

$$\xi_{c,l}^i = \begin{cases} \frac{\mathcal{B}(g_i)}{c_{c,l}}, & 1 \le \mathcal{B}(g_i) < c_{c,l}, \\ 1 - \epsilon_{FP}, & \mathcal{B}(g_i) = c_{c,l}, \\ \epsilon_{FP}, & \text{otherwise}, \end{cases} \tag{9}$$

where $\mathcal{B}(g_i)$ represents the number of variant alleles of genotype g_i. Therefore, for $b = 1$,

$$q_{c,l}^1 = p(\nu_{c,l}|d_{c,l}, c_{c,l}, x_{c,l}^{SNV} = 1, \theta^{SNV}) \tag{10}$$

$$= \sum_{i=1}^{c_{c,l}} p(g_i)[\xi_{c,l}^{\nu_{c,l}}(1 - \xi_{c,l})^{d_{c,l}-\nu_{c,l}}] \tag{11}$$

$$+ \epsilon_{FN}[\epsilon_{FP}^{\nu_{c,l}}(1 - \epsilon_{FP})^{d_{c,l}-\nu_{c,l}}].$$

The value of $p(g_i)$ equals $\frac{1-\epsilon_{FN}}{c_{c,l}}$, and ϵ_{FN} represents the error due to mutation loss or tree
errors.

If the mutation status of cell c at locus l is a wildtype (i.e., mutation is not present), then
the possible genotype states should not have any variant allele. The only possible geno-
type state is $\{A \dots A\}$. The mean parameter of the binomial distribution equals ϵ_{FP} (false
positive rate). Therefore,

$$q_{c,l}^0 = p(\nu_{c,l}|d_{c,l}, c_{c,l}, x_{c,l}^{SNV} = 0, \epsilon_{FP}). \tag{12}$$

With the proposed probability model for SNVs, we can incorporate both SNV data and CNA data to infer the underlying tree phylogeny in the sitka model. Therefore,

$$p(y|x,\theta) = \prod_{c \in C} \prod_{l \in L_{CNA}} p(y_{c,l}^{CNA}|x_{c,l}^{CNA}, \theta^{CNA}) \prod_{l \in L_{SNV}} p(y_{c,l}^{SNV}|x_{c,l}^{SNV}, \theta^{SNV}), \tag{13}$$

where C and L are the disjoint set of cells and loci, respectively. In this section, the loci set L includes both CNA and SNV traits.

Assume now that we seek to add one locus to an existing tree. We proceed similarly to Section 9.4.3. Equation (4) can be rewritten in the following form:

$$\bar{\rho}_v = \frac{\left(\dfrac{\prod_{v_i \in \text{children}(v)} (\gamma_{v_i}^0 + \gamma_{v_i}^1)}{\gamma_v^0} \right)}{\sum_{\bar{v} \in R} \left(\dfrac{\prod_{\bar{v}_i \in \text{children}(\bar{v})} (\gamma_{\bar{v}_i}^0 + \gamma_{\bar{v}_i}^1)}{\gamma_{\bar{v}}^0} \right)}, \tag{14}$$

where γ_v^b, for $b \in \{0,1\}$ is:

$$\gamma_v^b = \begin{cases} p_v^b, & \text{if } l \text{ represents a CNA loci,} \\ q_v^b, & \text{if } l \text{ represents a SNV loci.} \end{cases}$$

For $v \in R = \{v^*\} \bigcup L \backslash \{l\}$, and $b \in \{0,1\}$, the value of q_v^b is

$$q_v^b = \prod_{v'' \in \text{children}(v)} q_{v''}^b. \tag{15}$$

For the cell nodes that are the leaves of the tree $q_v^b = q_{c,l}^b$.

9.7.1 Detection of SNVs for individual cells

Given a fixed CNA tree (denoted by t) and the read counts data (y^{SNV} denoted by y for simplicity), here the goal is to calculate the posterior distribution of $x_{c,l}^{SNV}$, the mutation status of locus l at cell c, which we denote by $x_{c,l}$ for simplicity.

The joint probability distribution of $x_{c,l}$, y and t can be written as:

$$p(x_{c,l}, y, t) = \sum_{v \in R} \sum_{t' \in \mathcal{N}_v^l(t \backslash l)} p(x_{c,l}, t', y) \tag{16}$$

$$= \sum_{v \in R} \sum_{t' \in \mathcal{N}_v^l(t \backslash l)} p(x_{c,l}|t')p(y|t')p(t'), \tag{17}$$

where R is the set of all loci nodes in the tree (including the root) excluding locus l. The joint probability distribution is calculated as

$$p(x_{c,l} = 1, y, t) = \sum_{v \in \mathcal{P}(c,t)} \sum_{t' \in \mathcal{N}_v^l(t \backslash l)} p(y|t')p(t'). \tag{18}$$

The set $\mathcal{P}(c,t)$ denotes all nodes on the shortest path from cell c to the root of the tree (including the root and excluding the cell c node). An example of the path on an imaginary tree is depicted in **Supplementary Fig. 14**. The nodes coloured in green belong to $\mathcal{P}(c,t)$. Therefore, the posterior probability distribution of $x_{c,l} = 1$ yields

$$p(x_{c,l} = 1|y,t) = \frac{p(x_{c,l}=1,y,t)}{p(y,t)} = \frac{\sum_{v\in\mathcal{P}(c,t)}\sum_{t'\in\mathcal{N}_v^l(t\backslash l)}p(y|t')p(t')}{p(y,t)}. \tag{19}$$

Rewriting Equation (19) assuming uniform probability distribution for $p(t')$ yields:

$$\begin{aligned}
p(x_{c,l} = 1|y,t) &\propto \sum_{v\in\mathcal{P}(c,t)}\sum_{t'\in\mathcal{N}_v^l(t\backslash l)} p(y|t'),\\
&= \sum_{v\in\mathcal{P}(c,t)}\sum_{t'\in\mathcal{N}_v^l(t\backslash l)} \prod_{l'\in L}\prod_{c'\in C} p(y_{c',l'}|t'),\\
&= \sum_{v\in\mathcal{P}(c,t)}\sum_{t'\in\mathcal{N}_v^l(t\backslash l)} \prod_{\substack{l'\in L\\ l'\neq l}}\prod_{c'\in C} p(y_{c',l'}|t') \prod_{m'\in C} p(y_{c',l}|t'),\\
&= K_1 \sum_{v\in\mathcal{P}(c,t)}\sum_{t'\in\mathcal{N}_v^l(t\backslash l)} \prod_{c'\in C} p(y_{c',l}|t'),\\
&= K_1 \sum_{v\in\mathcal{P}(c,t)}\sum_{t'\in\mathcal{N}_v^l(t\backslash l)} \prod_{c'\in C_{\backslash v}} p(y_{c',l}|t') \prod_{c'\in L_v} p(y_{c',l}|t'),
\end{aligned}$$

where N denotes the set of all trait nodes, C denotes the set of all cell nodes, C_v denotes the cells that are a descendant of node v, and $C_{\backslash v}$ denotes the cells that are a not descendant of node v. The product of the likelihood contributions for non-descendant nodes can be calculated by taking the product of q_c^0 for all cells, divided by the ones that are descendant of v:

$$\prod_{c'\in C_{\backslash v}} q_{c'}^0 = \frac{q_{v^*}^0}{q_v^0}.$$

Therefore:

$$p(x_{c,l} = 1|y,t) \propto K_1 \sum_{v\in\mathcal{P}(c,t)} \frac{q_{v^*}^0}{q_v^0} \sum_{t'\in\mathcal{N}_v^l(t\backslash l)} \prod_{c'\in C_v} p(y_{c',l}|t'). \tag{20}$$

The likelihood contribution of descendant cells can be re-indexed by a binary vector $\mathbf{b} = (b_1, b_2, \ldots, b_k)$, where $b_i \in \{0,1\}$, and $b_i = 1$ if the child v is to be moved into a child of the node l. The value of k denotes the number of children of v. The i^*th child of v which is on the path from node v to cell c is called v_i^*. This implies $b_{i^*} = 1$ (See **Supplementary Fig. 14**). Therefore:

$$\sum_{t'\in\mathcal{N}_v^l(t\backslash l)} \prod_{c'\in C_v} p(y_{c',l}|t') = q_{v_c^*}^1 \sum_{b_1=0}^{1}\sum_{b_2=0}^{1}\cdots\sum_{b_{i-1}=0}^{1}\sum_{b_{i+1}=0}^{1}\cdots\sum_{b_k=0}^{1} \prod_{\substack{i=1\\ i\neq i^*}}^{k} q_{v_i}^{b_i}. \tag{21}$$

Rewriting Equation (20) using Equation (21) yields:

$$p(x_{c,l} = 1|y, t) \propto K_1 \sum_{v \in \mathcal{P}(c,t)} \frac{q_{v^*}^0}{q_v^0} q_{v_c^*}^1 \sum_{b_1=0}^{1} \sum_{b_2=0}^{1} \cdots \sum_{b_{i-1}=0}^{1} \sum_{b_{i+1}=0}^{1} \cdots \sum_{b_k=0}^{1} \prod_{\substack{i=1 \\ i \neq i^*}}^{k} q_{v_i}^{b_i},$$

$$= K_1 \sum_{v \in \mathcal{P}(c,t)} \frac{q_{v^*}^0}{q_v^0} q_{v_c^*}^1 \prod_{\substack{i=1 \\ i \neq i^*}}^{k} (q_{v_i}^0 + q_{v_i}^1),$$

$$= K_1 \sum_{v \in \mathcal{P}(c,t)} \frac{q_{v^*}^0}{q_v^0} \frac{\prod_{i=1}^{k}(q_{v_i}^0 + q_{v_i}^1)}{(q_{v_{i^*}}^0 + q_{v_{i^*}}^1)} q_{v_{i^*}}^1,$$

$$= K_1 q_{v^*}^0 \sum_{v \in \mathcal{P}(c,t)} \frac{q_{v_{i^*}}^1}{q_v^0(q_{v_{i^*}}^0 + q_{v_{i^*}}^1)} \prod_{i=1}^{k}(q_{v_i}^0 + q_{v_i}^1). \tag{22}$$

9.8 Computational complexity of the SNV calling algorithm

The computational complexity of Equation (22) is $O(|C| \cdot |L|)$ with $|C|$ the number of cells and $|L|$ the number of loci. In order to reduce the complexity of calculating $p(x_{c,l} = 1|y, t)$ for each locus and cell, $\mathcal{P}'(c, t)$ is defined to denote the nodes sitting on the path from root to cell c, excluding the root node and including the cell c node. Then,

$$q_v^* = \prod_{i=1}^{k}(q_{v_i}^0 + q_{v_i}^1). \tag{23}$$

Therefore,

$$K_1 q_{v^*}^0 \sum_{v \in \mathcal{P}(c,t)} \frac{q_{v_{i^*}}^1}{q_v^0(q_{v_{i^*}}^0 + q_{v_{i^*}}^1)} \prod_{i=1}^{k}(q_{v_i}^0 + q_{v_i}^1) = K_1 q_{v^*}^0 \sum_{v \in \mathcal{P}'(c,t)} \frac{q_v^1}{(q_v^0 + q_v^1)} \frac{q^*_{\mathrm{parent}(v)}}{q^0_{\mathrm{parent}(v)}}.$$

Calculating $p(x_{c,l} = 1|y, t)$ with a recursive approach reduces the complexity from $O(|C||L|)$ to $O(|C| + |L|)$, where as in the last section L is the union of SNV and CNA loci.

a Copy numbers

b Observed markers

c Observed markers
Jitter fixed

d Selection of
phylogenetic markers

e MCMC

Iter = 100 Iter = 101 Iter = 1000

f Edge insertion

Iter = 100 Iter = 101

g Averaging

h Consensus tree &
sorted CNA heatmap

i

Figure 1

Figure 2.

Figure 3

List of Figures

Figure 1. Workflow of sitka. (**a**) Sitka takes copy number calls data from a heterogeneous single-cell population. The cells (rows of the copy number matrix) are randomly sorted. (**b**) A lossy binary transformation is applied to obtain markers data. (Methods section 9.2 and **Supplementary Fig. 1**). Note that each single-cell is now represented by the presence or absence of CN changes between consecutive bins. (**c**) The boundary conditions are smoothed to account for cell-specific marker miss-alignment. (Methods section 9.3) to correct for this marker misalignment. Note how the columns in the inset in panel-**c** are less noisy than their counterpart in panel-**b**. (**d**) A subset of markers present in at least 5 percent of the cells are chosen for input to the tree inference algorithm. (**e**) An MCMC algorithm efficiently explores the tree space. (**f**) An example of an edge-insertion. (**g**) The indicator matrix of all post-bun-in MCMC trees are averaged to generate a matrix indicating the posterior probability of a cell being attached to a marker (Methods section 9.4.5). (**h**) The copy number data in (**a**) is sorted according to the inferred consensus tree, shown on the left of the matrix. (**i**) The inset shows the tuple of marker columns in the context of the copy number calls, namely **inf**. (inferred markers, i.e., latent state $x_{c,l}$), **post**. (posterior probability of the latent state $x_{c,l}$), and **obs**. (observed markers), interlaced with the CN columns (similar to **Supplementary Fig. 1**). The results are from the $SA535$ dataset, a triple negative breast cancer patient derived xenograft sample (Methods section 2.2).

Figure 2. Results over real-datasets and benchmarking against baseline methods. (**a**), (**b**), and (**c**) show the consensus tree and marker-space matrix for the OVA, $SA501$, and $SA535$ datasets respectively. (**d**) Comparison to baseline methods.

Figure 3. Synthetic experiments and an application to point mutation placement. (**a**) RF distance of Bayes tree estimate to the best-possible tree. The first plot holds p_{is} constant at zero. The second plot holds p_{loss} constant at 0. The third plot varies $p_{is} = p_{loss}$ jointly. (**b**) Estimation of violation rates in real data and a set of synthetic data. (**c**) Over 20,000 SNV's with high levels of missingness are placed on a backbone tree inferred from the CNA data for $SA535$.

References

[1]   E. Laks et al. "Clonal Decomposition and DNA Replication States Defined by Scaled Single-Cell Genome Sequencing". In: *Cell* 179.5 (2019), 1207–1221.e22.

[2]   M. Pellegrino et al. "High-throughput single-cell DNA sequencing of acute myeloid leukemia tumors with droplet microfluidics". In: *Genome research* 28.9 (2018), pp. 1345–1352.

[3]   T. Baslan et al. "Genome-wide copy number analysis of single cells". In: *Nature protocols* 7.6 (2012), pp. 1024–1041.

[4]   C. Gawad, W. Koh, and S. R. Quake. "Single-cell genome sequencing: current state of the science". In: *Nature Reviews Genetics* 17.3 (2016), p. 175.

[5]   S. Salehi et al. "Clonal fitness inferred from time-series modelling of single-cell cancer genomes". In: *Nature* (2021). DOI: 10.1038/s41586-021-03648-3. URL: https://doi.org/10.1038/s41586-021-03648-3.

[6]   J. J. Quinn et al. "Single-cell lineages reveal the rates, routes, and drivers of metastasis in cancer xenografts". In: *Science* (2021). ISSN: 0036-8075. DOI: 10.1126/science.abc1944. eprint: https://science.sciencemag.org/content/early/2021/01/21/science.abc1944.full.pdf. URL: https://science.sciencemag.org/content/early/2021/01/21/science.abc1944.

[7]   C. Abbosh et al. "Phylogenetic ctDNA analysis depicts early-stage lung cancer evolution". In: *Nature* 545.7655 (2017), pp. 446–451.

[8]   Y. Wang et al. "Clonal evolution in breast cancer revealed by single nucleus genome sequencing". In: *Nature* 512.7513 (2014), pp. 155–160.

[9]   M. L. Leung et al. "Single-cell DNA sequencing reveals a late-dissemination model in metastatic colorectal cancer". In: *Genome research* 27.8 (2017), pp. 1287–1299.

[10]   C. Yu et al. "Discovery of biclonal origin and a novel oncogene SLC12A5 in colon cancer by single-cell sequencing". In: *Cell research* 24.6 (2014), pp. 701–712.

[11]   R. Schwartz and A. A. Schäffer. "The evolution of tumour phylogenetics: principles and practice". In: *Nature Reviews Genetics* 18.4 (Apr. 2017), pp. 213–229. ISSN: 1471-0064.

[12]   K. Jahn, J. Kuipers, and N. Beerenwinkel. "Tree inference for single-cell data". In: *Genome Biology* 17 (2016), p. 86. ISSN: 1474-760X.

[13]   E. M. Ross and F. Markowetz. "OncoNEM: inferring tumor evolution from single-cell sequencing data". In: *Genome Biology* 17 (Apr. 2016), p. 69. ISSN: 1474-760X.

[14]   C. A Miller et al. "SciClone: inferring clonal architecture and tracking the spatial and temporal patterns of tumor evolution". In: *PLoS Comput Biol* 10.8 (2014), e1003665.

[15]   Jochen Singer et al. "Single-cell mutation identification via phylogenetic inference". In: *Nature communications* 9.1 (2018), pp. 1–8.

[16]   H. Zahn et al. "Scalable whole-genome single-cell library preparation without preamplification". In: *Nature Methods* 14.2 (2017), pp. 167–173. ISSN: 1548-7105.

[17]   Gryte Satas et al. "Scarlet: Single-cell tumor phylogeny inference with copy-number constrained mutation losses". In: *Cell Systems* 10.4 (2020), pp. 323–332.

[18]   F. Wang et al. "Single-cell copy number lineage tracing enabling gene discovery". In: *bioRxiv* (2020). DOI: 10.1101/2020.04.12.038281. eprint: https://www.biorxiv.org/content/early/2020/04/13/2020.04.12.038281.full.pdf. URL: https://www.biorxiv.org/content/early/2020/04/13/2020.04.12.038281.

[19] X. Xu et al. "Single-Cell Exome Sequencing Reveals Single-Nucleotide Mutation Characteristics of a Kidney Tumor". In: *Cell* 148.5 (Mar. 2012), pp. 886–895. ISSN: 0092-8674.

[20] T. L. Williams and B. M. E. Moret. "An investigation of phylogenetic likelihood methods". In: *Third IEEE Symposium on Bioinformatics and Bioengineering, 2003. Proceedings.* Mar. 2003, pp. 79–86.

[21] S. Malikic et al. "Integrative inference of subclonal tumour evolution from single-cell and bulk sequencing data". In: *Nature communications* 10.1 (2019), pp. 1–12.

[22] J. Ma et al. "The infinite sites model of genome evolution". In: *Proceedings of the National Academy of Sciences* 105.38 (2008), pp. 14254–14261.

[23] C. D. Greenman et al. "Estimation of rearrangement phylogeny for cancer genomes". In: *Genome Research* 22.2 (Feb. 2012), pp. 346–361. ISSN: 1088-9051, 1549-5469.

[24] H. Zafar et al. "SiFit: A Method for Inferring Tumor Trees from Single-Cell Sequencing Data under Finite-site Models". In: *bioRxiv* (Dec. 2016), p. 091595.

[25] P. Eirew et al. "Dynamics of genomic clones in breast cancer patient xenografts at single-cell resolution". In: *Nature* 518.7539 (2015), pp. 422–426.

[26] K. Yi and Y. Seok Ju. "Patterns and mechanisms of structural variations in human cancer". In: *Experimental & Molecular Medicine* 50.8 (2018), p. 98. DOI: 10.1038/s12276-018-0112-3. URL: https://doi.org/10.1038/s12276-018-0112-3.

[27] S. Mishra and J. R. Whetstine. "Different Facets of Copy Number Changes: Permanent, Transient, and Adaptive". In: *Molecular and Cellular Biology* 36.7 (2016), pp. 1050–1063. ISSN: 0270-7306. DOI: 10.1128/MCB.00652-15. eprint: https://mcb.asm.org/content/36/7/1050.full.pdf. URL: https://mcb.asm.org/content/36/7/1050.

[28] D.B. Wilson. "Generating Random Spanning Trees More Quickly Than the Cover Time". In: *Proceedings of the Twenty-eighth Annual ACM Symposium on Theory of Computing.* STOC '96. New York, NY, USA: ACM, 1996, pp. 296–303. ISBN: 978-0-89791-785-8.

[29] A. Bouchard-Côté et al. "Blang: Bayesian declarative modelling of general data structures and inference via algorithms based on distribution continua". In: *arXiv:1912.10396 [stat]* (2021). arXiv: 1912.10396 [stat.CO].

[30] R.M. Neal. "Slice sampling". In: *The Annals of Statistics* 31.3 (June 2003), pp. 705–767. ISSN: 0090-5364, 2168-8966.

[31] D. F. Robinson and L. R. Foulds. "Comparison of phylogenetic trees". In: *Mathematical biosciences* 53.1-2 (1981), pp. 131–147.

[32] R. Desper and O. Gascuel. "Fast and accurate phylogeny reconstruction algorithms based on the minimum-evolution principle". In: *International Workshop on Algorithms in Bioinformatics*. Springer. 2002, pp. 357–374.

[33] X. F Mallory et al. "Methods for copy number aberration detection from single-cell DNA-sequencing data". In: *Genome biology* 21.1 (2020), pp. 1–22.

[34] R. Sainudiin and A. Véber. "A Beta-splitting model for evolutionary trees". In: *Royal Society open science* 3.5 (2016), p. 160016.

[35] M. G. B. Blum and O. François. "Which random processes describe the tree of life? A large-scale study of phylogenetic tree imbalance". In: *Systematic Biology* 55.4 (2006), pp. 685–691.

[36] D. Aldous. "Probability distributions on cladograms". In: *Random discrete structures*. Springer, 1996, pp. 1–18.

[37] R. Gao et al. "Punctuated copy number evolution and clonal stasis in triple-negative
breast cancer". In: *Nature genetics* 48.10 (2016), p. 1119.
[38] J. F. C. Kingman. "The coalescent". In: *Stochastic processes and their applications*
13.3 (1982), pp. 235–248.
[39] K.P. Schliep. "phangorn: phylogenetic analysis in R". In: *Bioinformatics* 27.4 (2011),
pp. 592–593.
[40] P. R. Staab and D. Metzler. "Coala: an R framework for coalescent simulation". In:
Bioinformatics (2016). DOI: 10.1093/bioinformatics/btw098.
[41] W. J. Youden. "Index for rating diagnostic tests". In: *Cancer* 3.1 (1950), pp. 32–35.

Supplemental Figure 1. Description of the process involved in the construction of *markers*, the input to the sitka model. A *bin* is a contiguous set of genomic positions. Each pair of consecutive bins (e.g., bins 1 and 2 in (**a**)) is associated with a *marker* (e.g., marker 1) that measures for each individual cell, whether there is a difference between the CNA states of the two bins. (**a**) The observed CNA matrix for a subset of bins on a chromosome. The rows are sequenced single cells, and the columns are bins. The CN states are colour-coded. (**b**) The three markers shown are associated with the four bins. Each marker records the presence (black) or absence (white) of a CN state change between a pair of consecutive bins. Note that in the CNA matrix, there is a CN change at row 3 from bin 1 to bin 2 (CN state 3 to 6). This is reflected in the marker matrix, at row 3 of marker 1 with a black square. There are no changes between bins 2 and 3 across any rows in the CNA matrix. This is reflected in marker 2 comprising all white squares. (**c**) For visualisation purposes, the CNA matrix can be interlaced with the marker matrix to more clearly show where the CNA changes occur. Each column of the marker matrix is inserted between the associated pair of columns in the CNA matrix. The resulting matrix is an example of an *augmented* view that combines data from two or more sources (here the CNA matrix and the marker matrix). In an augmented view, we call columns from each source a *channel*.

Supplemental Figure 2. Visualisation of a small type I tree t (**a**), its transformation into a type II tree (**b**), and the corresponding marker matrix $x = (x_{c,l})$ (**c**). Given a tree t, the latent marker matrix x is a deterministic function $x = x(t)$. Note that the clade comprising single-cells 3 and 4 has support in both markers 1 and 3. For clarity, we do not visualise type I trees, but plot their transformation, i.e., type II trees as follows. We remove from the type I tree all marker nodes that have $x_{c,l} = 0$ for all single-cells c. Lists of connected edges that have exactly one descendent (i.e., chains) are also collapsed into a single edge, e.g., the edge corresponding to markers 2 and 3 are collapsed into one edge (since marker 2 has only one descendent, namely single-cell 2).

Perfect phylogeny maintained by two overlapping CN gains.

Perfect phylogeny violated by a CNA loss
followed by a CNA loss

Perfect phylogeny violated by a CNA gain
followed by a CNA loss

Supplemental Figure 3. The effects of overlapping CNA events on the perfect phylogeny assumption. A segment of a chromosome with five consecutive bins and their four corresponding markers are shown. Each panel follows the CN states interlaced with markers for a cell at the ancestral state (top), after a CNA event (middle), and after a second overlapping CNA event (bottom). The numbers in the CNA squares show the integer CN state (e.g., the ancestral state has two copies of the 5-bins long segment). (**a**) Two overlapping CNA gains maintain the perfect phylogeny assumption. By the infinite site argument, it is unlikely for the end-points of the two gain events to exactly match. The same argument holds for a CNA loss followed by a CNA gain event. Note that in these cases, once a change point is acquired, it is not lost. (**b**) If a loss event is followed by another loss event in which either end-points of the first event is removed, the perfect phylogeny assumption will be violated (e.g., marker 3 is lost after the second loss event). Note that a violation does not occur if the loss events hit different copies of a segment. (**c**) Similarly, if a gain event is followed by a loss event, only if the latter erases the end-points of the former is the perfect phylogeny violated. Note how marker 2 and marker 3 are lost after the second CNA event.

Supplemental Figure 4. Pathological tree reconstruction under default observation prior. (**a**) The true tree reconstruction in a simple example with a balanced phylogeny with two clades of size two, and two unique markers, coloured red and blue, that distinguish the left and right clades respectively. (**b**) The binarised input matrix corresponding to the four cells at the two markers. The desired observation error rates should be zero and the latent and observed marker matrices should match exactly, as the perfect phylogeny assumption holds. If the observation error parameters are set to one, that is $r_{\text{global}}^{\text{FP}} = 1$ and $r_{\text{global}}^{\text{FN}} = 1$, then the latent marker matrix with all entries flipped as shown in (**c**) will have an equal likelihood under this setting as the desired latent matrix has when error rates are set to zero. (**d**) The incorrect tree reconstruction where the left and right clades are erroneously assigned to the blue and red markers.

Supplemental Figure 5. (**a**) Reading from left to right: the interpretation of removing a column in the matrix x is to perform contraction of an edge corresponding to a locus shown in bold. Reading from right to left: the interpretation of inserting back a column while assigning new binary values is an edge insertion. The circled node v refers to Step 1. The subtrees in bold refer to those selected in Step 2. The edge in bold, the one introduced in Step 3. (**b**) Decomposition used for the recursion of Section 9.4.3.

SA535, 493 cells

Supplemental Figure 6. Phylogenetic tree and CNA profile heatmap for the SA535 dataset. The rows of the heatmap are sorted according to the placement of cells on the phylogenetic tree. The columns of the heatmap are sorted by their genomic position.

OVA, 997 cells

Supplemental Figure 7. Phylogenetic tree and CNA profile heatmap for the OVA dataset. The nearly diploid cells with the loss of heterozygosity on chromosome X are from SA1090. The cells with an amplification on chromosome 22 are from SA922. The rest belong to SA921.

Supplemental Figure 8. Phylogenetic tree and CNA profile heatmap for the SA501 dataset. Note that the diploid cells at the bottom of the heatmap are control cells that were included in the experiment.

Supplemental Figure 9. the distribution of mismatch rate defined as the fraction of cells that have a mismatch between the inferred and jitter-fixed value of a marker.

Supplemental Figure 10. **(a)** Tree imbalance index where zero indicates that the tree is consistent with one simulated from a Yule model (completely balanced) and positive values indicate deviation from the Yule model (more imbalanced). For ease of plotting, each balance index is normalised by the absolute value of the maximum estimated statistic among all samples. Cumulatively adding more timepoints (**b**), or for the maximal subtree comprising cells of a specific timepoint (**c**).

Supplemental Figure 11. Synthetic datasets simulated from Beta-splitting processes.

Benchmark versus baseline methods

Supplemental Figure 12. Tree reconstruction evaluation using a normalized Robinson–Foulds metric on synthetic datasets from $S72$, simulated from Beta-splitting processes. Here normalization is done by dividing the RF distance of each inference method by the worst performer per dataset.

Supplemental Figure 13. A model and estimator comparison based on tree reconstruction accuracy for datasets from $S10$. For each dataset, inference was performed on both the globally- and locally-parameterized model. Both the greedy and trace search estimates were computed for each inference result.

Supplemental Figure 14. A schematic view of the underlying tree inferred from CNA and SNV loci across multiple cells. Black and white nodes represent cells and loci, respectively. The grey triangle represents a subtree rooted at a node. It includes all of the nodes and edges in the subtree.

Copy number and cell meta-data

```
cn.csv
```

drop low-mapability bins

```
cn_bin_filtered.c
sv
```

drop low-quality,
contaminated,
and cycling cells

```
cn_bin_cell_filte
red.csv
```

drop suspect cycling cells

```
cn_bin_cell_filte
red_no_jump.csv
```

Supplemental Figure 15. Filtering the CNA data for tree inference.

Supplemental Figure 16. An example of replicating cells. Note the scattered localised deletions. This heatmap is from a HER2+ PDX line. These late replicating cells form a *finger* like clade in the tree. The top inset shows chromosome 4 while the bottom inset spans chromosomes 7 and 8.

Supplemental Figure 17. SNV variant reads data and SNV call probabilities for SA535 dataset beside the underlying phylogenetic tree.

Supplemental Figure 18. SNV variant reads data and SNV call probabilities for OVA dataset beside the underlying phylogenetic tree..

Supplemental Figure 19. SNV variant reads data and SNV call probabilities for SA501 dataset beside the underlying phylogenetic tree.

List of Supplementary Figures

Supplemental Table 1. Summary of real-world datasets used. `final` is the final number of cells after all filters except for `!lmr` are applied. `final` additionally filters out `lmr` cells, those that have total mapped reads fewer than 500,000. Abbreviations used are tp: time point; qual. : quality; !sphase: not sphase; !lmr: not low mapped reads.

Dataset	parameter	value
Real datasets	engine	PT
Real datasets	globalParameterization	true
Real datasets	fprBound	0.1
Real datasets	fnrBound	0.5
Real datasets	nChains	1
Real datasets	nScans	1000
Real datasets	nPassesPerScan	1
Real datasets	thinning	1
Real datasets	burnin fraction	0.5
$S72$	engine	PT
$S72$	globalParameterization	true
$S72$	fprBound	0.1
$S72$	fnrBound	0.5
$S72$	nChains	1
$S72$	nScans	20000
$S72$	nPassesPerScan	1
$S72$	thinning	1
$S72$	burnin fraction	0.5
$S10$	globalParameterization	true, false
$S130$	globalParameterization	true
$S10,S130$	engine	PT
$S10,S130$	fprBound	0.1
$S10,S130$	fnrBound	0.5
$S10,S130$	nChains	8
$S10,S130$	nScans	5000
$S10,S130$	nPassesPerScan	10
$S10,S130$	thinning	1
$S10,S130$	burnin fraction	0.5

Supplemental Table 2. Inference settings used for each dataset.