Neural encoding of task-dependent errors during adaptive learning

Chang-Hao Kao[1], Sangil Lee[1], Joshua I. Gold[2], Joseph W. Kable[1]

[1]Department of Psychology, University of Pennsylvania, Philadelphia, PA 19104, USA

[2]Department of Neuroscience, University of Pennsylvania, Philadelphia, PA 19104, USA

Corresponding authors:

Chang-Hao Kao: chakao@sas.upenn.edu

Joseph W. Kable: kable@psych.upenn.edu

Abstract

Effective learning requires using errors in a task-dependent manner, for example adjusting to

errors that result from unpredicted environmental changes but ignoring errors that result from

environmental stochasticity. Where and how the brain represents errors in a task-dependent

manner and uses them to guide behavior are not well understood. We imaged the brains of

human participants performing a predictive-inference task with two conditions that had different

sources of errors. Their performance was sensitive to this difference, including more choice

switches after fundamental changes versus stochastic fluctuations in reward contingencies. Using

multi-voxel pattern classification, we identified task-dependent representations of error

magnitude and past errors in posterior parietal cortex. These representations were distinct from

representations of the resulting behavioral adjustments in dorsomedial frontal, anterior cingulate,

and orbitofrontal cortex. The results provide new insights into how the human brain represents

errors in a task-dependent manner and guides subsequent adaptive behavior.

Introduction

Errors often drive adaptive adjustments in beliefs that inform behaviors that maximize positive outcomes and minimize negative ones (Sutton & Barto, 1998). A major challenge to error-driven learning in uncertain and dynamic environments is that errors can arise from different sources that have different implications for learning. For example, a bad experience at a restaurant that recently hired a new chef might lead you to update your belief about the quality of the restaurant, whereas a similar experience at a well-known restaurant with a chef that has long been your favorite might be written off as a one-time bad night. That is, the same errors should be interpreted differently in different contexts. In general, errors that represent fundamental changes in the environment or that occur during periods of uncertainty should probably lead you to update your beliefs and change your behavior, whereas those that result from environmental stochasticity are likely better ignored (d'Acremont & Bossaerts, 2016; Li, Nassar, Kable, & Gold, 2019; Nassar, Bruckner, & Frank, 2019; O'Reilly et al., 2013).

Neural representations of key features of these kinds of dynamic, error-driven learning processes have been identified in several brain regions. For example, several studies focused on variables derived from normative models that describe the degree to which individuals should dynamically adjust their beliefs in response to error feedback under different task conditions, including the probability that a fundamental change in the environment just occurred (change-point probability, or CPP, which is a form of surprise) and the reducible uncertainty associated with estimates of environmental features (relative uncertainty, or RU). Correlates of these variables have been identified in dorsomedial frontal (DMFC) and dorsolateral prefrontal (DLPFC) cortex and medial and lateral posterior parietal cortex (PPC) (Behrens, Woolrich, Walton, & Rushworth, 2007; McGuire, Nassar, Gold, & Kable, 2014; Nassar, McGuire, Ritz, & Kable, 2019). These and other studies also suggest specific roles for these different brain regions in error-driving learning, including representations of surprise induced by either state changes or outliers (irrelevant to state changes) in the PPC that suggest a role in error monitoring (Nassar, Bruckner, et al., 2019; O'Reilly et al., 2013), and representations of variables more closely related to belief and behavior updating in the prefrontal cortex (PFC) (McGuire et al., 2014; O'Reilly et al., 2013). However, these previous studies, which typically used continuous rather than discrete feedback, were not designed to identify neural signals related to a key aspect of

flexible learning in uncertain and dynamic environments: responding to the same kinds of errors
differently in different conditions.
To identify such task-dependent neural responses to errors, we adapted a paradigm from
our previous single-unit recording study (Li et al., 2019). In this paradigm, we generated two
different dynamic environments by varying the amount of noise and the frequency that change-
points occur (i.e., hazard rate; Behrens et al., 2007; Glaze, Kable, & Gold, 2015; Nassar et al.,
2012; Nassar, Wilson, Heasly, & Gold, 2010). In one environment, noise was absent and the
hazard rate was high, and thus errors unambiguously signaled a change in state. We refer to this
high hazard/low noise condition as the *unstable* environment, because most errors can be
attributed to volatility. In another environment, noise was high and the hazard rate was low, and
thus small errors were ambiguous and could indicate either a change in state or noise. We refer to
this low hazard/high noise condition as the *noisy* environment, because most errors can be
attributed to stochasticity. Thus, effective learning requires treating errors in the two conditions
differently, including adjusting immediately to errors in the unstable environment but using the
size of errors and recent error history as cues to aid interpretation of ambiguous errors in the
noisy environment.
In our previous study, we found many single neurons in the anterior cingulate cortex
(ACC) or posterior cingulate cortex (PCC) that responded to errors or the current condition, but
we found little evidence that single neurons in these regions combined this information in a task-
dependent manner to discriminate the source of errors or drive behavior. In the current study, we
used whole-brain fMRI and multi-voxel pattern classification to identify task-dependent neural
responses to errors and activity predictive of behavioral updating in the human brain. The results
show task-dependent encoding of error magnitude and past errors in PPC and encoding of
behavioral shifts in frontal regions including ACC, DMFC, DLPFC and orbitofrontal cortex
(OFC), which provide new insights into the distinct roles these brain regions play in representing
errors in a task-dependent manner and using errors to guide adaptive behavior.
83
Results
Sixteen human participants performed a predictive-inference task (Figure 1A) while
fMRI was used to measure their blood-oxygenation-level-dependent (BOLD) brain activity. The
task required them to predict the location of a single rewarded target from a circular array of ten

targets. The location of the rewarded target was sampled from a distribution based on the

location of the current best target and the noise level in the current condition. In addition, the

location of the best target could change according to a particular, fixed hazard rate (H). Two

conditions with different noise levels and hazard rates were conducted in separate runs. In the

noisy condition (Figure 1B–C), the rewarded target would appear in one of the five locations

relative to the location of the current best target, and the hazard rate was low ($H = 0.02$). In the

unstable condition (Figure 1D–E), the rewarded target always appeared at the location of the best

target, and the hazard rate was high ($H = 0.35$). On each trial, participants made a prediction by

looking at a particular target, and then were given explicit, visual feedback about their chosen

target and the rewarded target. Effective performance required them to use this feedback in a

flexible and task-dependent manner, including typically ignoring small errors in the noisy

condition but responding to small errors in the unstable condition by updating their beliefs about

the best-target location.

Behavior

Nearly all of the participants' choice patterns were consistent with a flexible, task-

dependent learning process (closed symbols in Figure 2). On average, they learned the location

of the best target after a change in its location more quickly and reliably in the unstable than the

noisy condition (Figure 2A). This flexible learning process had two key signatures. First, target

switches (i.e., predicting a different target than on the previous trial) tended to follow errors of

any magnitude in the unstable condition but only errors of high magnitude (i.e., when the chosen

target was 3, 4, or 5 targets away from the rewarded target) in the noisy condition (sign test for

H_0: equal probability of switching for the two conditions; error magnitude of 1: median = -0.35,

interquartile range (IQR) = [-0.62, -0.25], $p<0.001$; error magnitude of 2: median = -0.30, IQR =

[-0.70, -0.11], $p<0.001$; Figure 2B–C). Second, target switches depended on error history only

for low-magnitude errors (i.e., when the chosen target was 1 or 2 targets away from the rewarded

target) in the noisy condition but not otherwise (sign test for H_0: switching was unaffected when

recent history contained fewer errors; error magnitude of 1: median = -0.29, IQR = [-0.42, -0.10],

$p=0.004$; error magnitude of 2: median = -0.25, IQR = [-0.38, -0.14], $p<0.001$; Figure 2D–F).

We accounted for these behavioral patterns with a reduced Bayesian model that is similar

to ones we have used previously to model belief updating in a dynamic environment (open

symbols in Figure 2; Tables 1 and 2). This model provides a framework to interpret and use

errors differently according to the current task conditions, as defined by hazard rate and noise

level. The decision-maker's trial-by-trial updates are governed by ongoing estimates of the

probability that the best target changed (change-point probability, or CPP) and reducible

uncertainty about the best target's location (relative uncertainty, or RU). Both quantities are

influenced by the two free parameters in the model, subjective estimates of the task hazard rate

and noise level, which were fitted separately in each condition for each participant. As expected,

the fitted hazard rates were higher in the unstable condition than in the noisy condition, although

both tended to be higher than the objective values, as we have observed previously (Nassar et al.,

2010). However, the fitted noise estimates were not reliably different between the noisy and

unstable conditions (Table 2). As we observed in our previous study (Li et al., 2019), the

subjective estimates of noise level were high in the unstable condition despite the objective

absence of noise.

We also tested several alternative models but they did not provide as parsimonious

descriptions of the data (Figure 2 – figure supplement 2, and Tables 1 and 2). Notably, an

alternative model that assumed a condition-specific fixed learning rate also assumed errors were

treated differently in the two conditions but did not include trial-by-trial adjustments of learning

rates used by the reduced Bayesian model. Although this model performed better than the

reduced Bayesian model in the unstable condition, it cannot capture participants' behaviors in the

noisy condition, where dynamically integrating both current and past errors is required for

adapting trial-by-trial behavior. Other hybrid models performed worse than the reduced Bayesian

model in both conditions.

Neural representation of CPP and RU

The two key internal quantities in the reduced Bayesian model are CPP and RU, both of

which contribute to processing errors in a task-dependent manner (Figure 2 – figure supplement

3). CPP increases as the current error magnitude increases and achieves large values more

quickly in the unstable condition because of the higher hazard rate. These dynamics lead to a

greater probability of switching targets after smaller errors in the unstable condition. RU

increases on the next trial after the participant makes an error and does so more strongly in the

noisy condition because of the lower hazard rate. These dynamics lead to a greater probability of

target switches when the last trial was an error, which is most prominent for small errors in the
noisy condition. Thus, CPP and RU each account for one of the two key signatures of task-
dependent learning that we identified in participants' behavior, with CPP driving a task-
dependent influence of error magnitude and RU driving a task-dependent influence of error
history on target switches.

Though not the main focus of this study, we were able to replicate our previous findings
regarding the neural representations of CPP and RU (McGuire et al., 2014). Similar to our
previous study, we found activity that was positively correlated with the levels of CPP and RU
across DLPFC and PPC (Figure 2 – figure supplement 3 and 4). The regions of DLPFC and PPC
that were responsive to both CPP and RU were a subset of those identified as showing this
conjunction in our previous study. Because CPP and RU both contribute to responding to errors
in a task-dependent manner, the brain regions that responded to both variables are good
candidates for encoding errors in a task-dependent manner. In the following analyses, we aimed
to directly identify task-dependent neural representations of error magnitude and error history, as
well as activity that predicts subsequent shifts in behavior.

Task-dependent neural representation of errors

We used multi-voxel pattern analysis (MVPA) to identify error-related neural signals that
were similar and different for the two task conditions. Given the two key signatures of flexible
learning that we identified in behavior, we were especially interested in identifying neural
representations of error magnitude and past errors that were stronger in the noisy than the
unstable condition.

We found robust, task-dependent representations of the magnitude of the error on the
current trial in PPC. Consistent with the task-dependent behavioral effects, this representation of
error magnitude was stronger in the noisy than the unstable condition (Figure 3 and Table 3).
Specifically, we could classify correct versus error feedback on the current trial across almost the
entire cortex, in both the unstable and noisy conditions. However, for error trials, we could
classify error magnitude (in three bins: 1, 2, 3+ targets away from the rewarded target) only for
the noisy condition and most strongly in the lateral and medial parietal cortex and in the occipital
pole. In a parallel set of analyses, we found that univariate activity in PPC also varied in a task-

dependent way, responding more strongly to error magnitude in the noisy than the unstable

condition (Figure 3 – figure supplement 1).

We also found robust, task-dependent representations of past errors in PPC. These

representations also were stronger in the noisy than the unstable condition, particularly on trials

for which past errors had the strongest influence on behavior. Specifically, we could classify

correct versus error on the previous trial in PPC for both task conditions (Figure 4). This

classification of past errors depended on the outcome of the current trial. We separated trials

according to whether the current feedback was correct or an error, or whether the error

magnitude provided ambiguous (error magnitudes of 1 or 2) or unambiguous (error magnitudes

of 0 or 3+) feedback in the noisy condition (Figure 4). We found reliable classifications of past

errors in the lateral and medial parietal cortex in both conditions for correct trials and trials with

error magnitudes of 0 or 3+. Moreover, these representations depended on the current condition,

and, consistent with behavioral effects of error history, were stronger for error trials and trials

with error magnitudes of 1 or 2 in the noisy than in the unstable condition (Table 3). These task-

dependent signals for past errors were not clearly present in univariate activity (Figure 4 – figure

supplement 1). An additional conjunction analysis across MVPA results showed that PPC

uniquely encoded task-dependent error signals for both error magnitude of the current trials and

past errors when the current trial's error magnitude was 1 or 2 (Table 3).

Neural prediction of subsequent changes in behavior

Although PPC responds to errors in a task-dependent manner that could be used for

determining behavioral updates, we did not find that activity in this region was predictive of the

participants' future behavior. Instead, we found such predictive activity more anteriorly in the

frontal lobe. Specifically, we investigated whether multi-voxel neural patterns could predict

participants' target switches on the subsequent trial. We focused on the trials with small error

magnitudes (1 or 2) in the noisy condition, because these were the only trial types that

participants consistently exhibited an intermediate probability of switching (20–80%, Figure 2).

We found that activity patterns in large cluster encompassing motor cortex, OFC, ACC, DMFC,

and DLPFC could predict subsequent stay/switch decisions (Figure 5, Table 4). We also

evaluated this result with different approaches to cluster formation that were more or less

spatially specific (Figure 5 – figure supplement 1). We did not find any regions where univariate

activity reliably predicted participants' subsequent behavior (Figure 5 – figure supplement 2).

Discussion

We identified task-dependent neural representations of errors in humans performing

dynamic learning tasks. Participants were required to learn in two different dynamic

environments. In the unstable condition (high hazard rate and low noise), errors unambiguously

indicated a change in the state of the environment, and participants reliably updated their

behavior in response to errors. In contrast, in the noisy condition (low hazard rate and high noise),

small errors were ambiguous, and participants used both the current error magnitude and recent

error history to distinguish between those errors that likely signal change-points and those likely

arising from environmental noise. Using MVPA, we showed complementary roles of PPC and

prefrontal regions (including motor cortex, OFC, ACC, DMFC and DLPFC) in the outcome-

monitoring and action-selection processes underlying these flexible, task-dependent behavioral

responses to errors. Neural patterns in PPC encoded the magnitude of errors and past errors,

more strongly in the noisy than the unstable condition. These task-dependent neural responses to

errors in PPC were not reliably linked to subsequent changes in behavior. In contrast, neural

patterns in prefrontal regions could predict subsequent changes in behavior (whether participants

switch their choice on the next trial or not) in response to ambiguous errors in the noisy

condition.

Task-dependent behavior adaptation

Consistent with previous studies of ours and others (d'Acremont & Bossaerts, 2016;

McGuire et al., 2014; Nassar, Bruckner, et al., 2019; Nassar et al., 2012; Nassar et al., 2010;

O'Reilly et al., 2013; Purcell & Kiani, 2016), human participants adapted their response to errors

differently in different environments. In the unstable condition, participants almost always

switched their choice after errors and quickly learned the new state after change-points. In

contrast, in the noisy condition, participants ignored many errors and only slowly learned the

new state after change-points. In this condition, participants had to distinguish true change-points

from environmental noise, and they used error magnitude and recent error history as a cue for

whether the state had recently changed or not. These flexible and task-dependent responses to

errors could be accounted for by a reduced Bayesian model (McGuire et al., 2014; Nassar et al.,
2012; Nassar et al., 2010). This model assumes that participants use approximately optimal
inference processes but can have subjective estimates of environmental parameters (hazard rate,
noise) that depart from their true values.
245
Neural representation of change-point probability and relative uncertainty
In the reduced Bayesian model, beliefs and behavior are updated dynamically according
to two key internal quantities, CPP and RU. Replicating our previous work (McGuire et al.,
2014), we identified neural activity correlated with both CPP and RU in PPC and DLPFC. This
replication shows the robustness of these neural representations of CPP and RU across
experimental designs that differ dramatically in their visual stimuli and motor demands, yet share
the need to learn in dynamic environments with similar statistics. We extended those findings to
show that some brain regions that encode both CPP, which in the model accounts for task-
dependent behavioral responses to error magnitude, and RU, which in the model accounts for
task-dependent behavioral responses to recent error history, also encode errors in a task-
dependent manner or predict subsequent behavioral updates.
257
Task-dependent neural representation of errors
Advancing beyond previous work, we identified task-dependent encoding of errors in
neural activity in the PPC. Mirroring the task dependence of behavior, the multivariate neural
pattern in PPC encoded current error magnitude more strongly in the noisy condition than in the
unstable condition and encoded past errors more strongly on trials that provided ambiguous
feedback in the noisy condition. These same regions of PPC have been shown previously to
represent errors, error magnitudes, surprise and salience (Fischer & Ullsperger, 2013; Gläscher,
Daw, Dayan, & O'Doherty, 2010; McGuire et al., 2014; Nassar, Bruckner, et al., 2019; Nassar,
McGuire, et al., 2019; O'Reilly et al., 2013; Payzan-LeNestour, Dunne, Bossaerts, & O'Doherty,
2013). In addition, these regions have been shown to integrate recent outcome or stimulus history
in human fMRI studies (FitzGerald, Moran, Friston, & Dolan, 2015; Furl & Averbeck, 2011) and
in animal single neuron recording studies (Akrami, Kopec, Diamond, & Brody, 2018; Brody &
Hanks, 2016; Hanks et al., 2015; Hayden, Nair, McCoy, & Platt, 2008; Hwang, Dahlen,
Mukundan, & Komiyama, 2017). Our results extend on these past findings by demonstrating that

the neural encoding of error magnitude and error history in PPC is modulated across different

conditions in precisely the manner that could drive adaptive behavior.

These whole-brain fMRI results complement our previous results recording from single

neurons in ACC and PCC in the same task (Li et al., 2019). In that study, we identified single

neurons in both ACC and PCC that encoded information relevant to interpreting errors, such as

the magnitude of the error or the current condition. However, we did not find any neurons that

combined this information in a manner that could drive adaptive behavioral adjustments. Our

whole-brain fMRI results suggest that PPC would be a good place to look for task-dependent

error representations in single neurons, including a region of medial parietal cortex slightly

dorsal to the PCC area we recorded from previously.

Neural representations of task-dependent behavioral updating

Also advancing beyond previous work, we identified neural activity predictive of

behavioral updates across the frontal cortex, including DLPFC. In the noisy condition, small

errors provided ambiguous feedback that could reflect either a change in state or environmental

noise. Accordingly, after small errors in the noisy condition, participants exhibited variability

across trials in whether they switched from their current choice on the subsequent trial or not. In

these ambiguous situations, the multivariate neural pattern in large cluster in frontal cortex,

including motor cortex, OFC, ACC, DMFC and DLPFC, predicted whether people switched or

stayed on the subsequent trial. These results extend previous findings that the multivariate

pattern in frontal cortex, particularly ACC and medial PFC, can decode subsequent switching

versus staying in a reversal learning task (Hampton & O'Doherty, 2007). These results suggest a

dissociation between PPC regions that monitor error information in a task-dependent manner and

frontal regions that may use this information to update beliefs and select subsequent actions.

This ability to decode subsequent choices might arise from different kinds of

representations in different areas of frontal cortex. Whereas motor and premotor regions may

reflect the change in action plans, other frontal regions might reflect changes in abstract

representations of belief states. Medial PFC is involved in performance monitoring,

distinguishing errors from different sources such as actions and feedback (Ullsperger,

Danielmeier, & Jocham, 2014), registering a hierarchy of prediction errors from those due to

environmental noise to those due to a change in the environmental state (Alexander & Brown,

2015), and interacting with lateral PFC to guide subsequent behavioral adjustments in response

to errors (Alexander & Brown, 2015). Consistent with this role, activity in DMFC also reflects

the extent of belief updating in dynamic environments (Behrens et al., 2007; Hampton, Bossaerts,

& O'Doherty, 2006; McGuire et al., 2014; O'Reilly et al., 2013). OFC and DMFC encode the

identity of the current latent state in a mental model of the task environment and neural

representations in these regions changes as the state changes (Chan, Niv, & Norman, 2016; Hunt

et al., 2018; Karlsson, Tervo, & Karpova, 2012; Nassar, McGuire, et al., 2019; Schuck, Cai,

Wilson, & Niv, 2016; Wilson, Takahashi, Schoenbaum, & Niv, 2014). Activity in inferior frontal

junction reflects the updating of task representations (Brass & Cramon, 2004; Derrfuss, Brass,

Neumann, & von Cramon, 2005). Neural activity in frontopolar cortex (Daw, O'Doherty, Dayan,

Seymour, & Dolan, 2006) and DMFC (Blanchard & Gershman, 2018; Kolling, Behrens, Mars, &

Rushworth, 2012; Kolling et al., 2016; Muller, Mars, Behrens, & O'Reilly, 2019) increases

during exploratory choices, which occur more frequently during periods of uncertainty about the

most beneficial option. In a recent study, we identified distinct representations of latent states,

uncertainty, and behavioral policy in distinct areas of frontal cortex during learning in a dynamic

environment (Nassar et al., 2019). Our results extend these past findings and demonstrate the

role of these frontal regions in adjusting behavior in response to ambiguous errors.

Caveats

A few caveats should be considered when interpreting our results. First, we had relatively

small number of participants in this study (n=16). Although we control the false positive rates

through permutation tests that have been validated empirically (Eklund, Nichols, & Knutsson,

2016), it is possible that we lacked the statistical power to detect some effects, and so null results

should be interpreted with caution. Second, in this study, we created two qualitatively different

task conditions by manipulating both the noise levels and hazard rates. Thus, we cannot attribute

any behavioral or neural differences across conditions specifically to changes in either noise

levels or hazard rates alone, but rather to how the combinations of these two variables affect the

interpretation and use of small errors. Future studies can manipulate hazard rate and noise

independently to examine their independent contributions to adaptive learning.

Conclusion

People adapt their behavior in response to errors in a task-dependent manner,

distinguishing between errors that indicate change-points in the environment versus noise. Here

we used MVPA to identify two distinct kinds of neural signals contributing to these adaptive

behavioral adjustments. In PPC, neural patterns encoded error information in a task-dependent

manner, depending on error magnitude and past errors only under conditions where these were

informative of the source of error. In contrast, activity in frontal cortex could predict subsequent

choices that could be based on this information. These findings suggest a broad distinction

between outcome monitoring in parietal regions and action selection in frontal regions when

learning in dynamic and uncertain environments.

Materials and Methods

Participants

All procedures were approved by University of Pennsylvania Internal Review Board. We

analyzed data from sixteen participants (9 females, 7 males, mean age = 23.5, SD = 4.3, range =

18–33 years) recruited for the current study. One additional participant was excluded from

analyses because of large head movements during MRI scanning (>10% of timepoint-to-

timepoint displacements were >0.5 mm). All participants provided informed consent before the

experiment. Participants received a participation fee of $15, as well as extra incentives based on

their performance (mean = $15.09, SD = $2.26, range = $8.5–17.5).

Task

Participants performed a predictive-inference task during MRI scanning. On each trial,

participants saw a noisy observation sampled from an unobserved state. The participants' goal

was to predict the location of the noisy observation. To perform this task well, however, they

should infer the location of the current state.

In this task (Li et al., 2019), there were 10 targets aligned in a circle on the screen (Figure

1A). At the start of each trial, participants had to fixate a central cross for 0.5 seconds to

initialize the trial. After the cross disappeared, participants could choose one of 10 targets (red)

by looking at it within 1.5 seconds and keeping fixation on the chosen target for 0.3 seconds.

Then, an outcome would be shown for 1 second. During the outcome phase, a green dot

indicated the chosen target. A purple or cyan target indicated the rewarded target, with color

denoting 10 or 20 points of reward value, respectively. At the end of experiment, every 75 points

were converted to $0.25 as participants' extra incentives.

Participants performed this task in two dynamic conditions separated into two different

runs: a high-noise/low-hazard ("noisy") condition and an low-noise/high-hazard ("unstable")

condition. In the noisy condition, the rewarded target could be one of five targets, given the

underlying state (Figure 1B). The rewarded target probabilities for the relative locations ([-2, -1,

0, 1, 2]) of the current state were [0.05, 0.15, 0.6, 0.15, 0.05]. Thus, the location of the current

state was most likely rewarded, but nearby targets could also be rewarded. Occasionally, the

state would change its location with a hazard rate of 0.02 (Figure 1C). When a change-point

happens, the new state would be selected among the ten targets based on a uniform distribution.

In the unstable condition, there was no noise (Figure 1D). That is, the location of the state would

be always rewarded. However, the state was unstable, as the hazard rate in this condition was

0.35 (Figure 1E). There were 300 trials in each run.

Behavior analysis

We investigated how participants used error feedback flexibly across different conditions.

Before the behavioral analysis, we removed two different kinds of trials. First, we removed trials

in which participants did not make a choice within the time limit (Unstable: median number of

trials = 10.5, range = 1–83; Noisy: median = 10, range = 2–88). Second, we also removed trials

in which the location of the chosen target was not on the shortest distance between the previously

chosen and previously rewarded targets (Unstable: median = 3, range = 0–24; Noisy: median =

17, range = 5–37). All of the belief updating models we tested predict that participants' choice

should be along the shortest distance between the previously chosen target and the previously

rewarded target. That is, participants should update in a clockwise direction, if the shortest

distance to rewarded target was clockwise of the chosen target. Otherwise, they should update in

a counterclockwise direction. We removed trials where participants' update was in the opposite

direction of the rewarded target (which would correspond to a learning rate < 0) and trials where

participants' update was beyond the location of the rewarded target (which would correspond to

a learning rate > 1), as this behavior cannot be captured by any of the belief updating models we

tested. Further, this behavior might suggest that participants had lost track of the most recently

chosen or rewarded targets.

First, we investigated how fast participants learned the location of the current state. For

each condition and participant, we binned trials from trial 0 to trial 20 after change-points. Then,

we calculated the probability of choosing the location of the current state for each bin.

Second, we examined how different magnitudes of errors lead to shifts in behavior. For

each condition and participant, we binned trials based on the current error magnitude (from 0 to

5). Then, for each bin, we calculated the probability that participants switch their choice to

another target on the subsequent trial. We hypothesized participants would have a lower

probability of switching after small error magnitudes (1 or 2) in the noisy condition than in the

unstable condition since such errors could be due to environment noise in the noisy condition but

would signal a state change in the unstable condition.

Third, we further investigated how error history influenced participants' behavioral shifts.

Similarly, we binned trials based on the current error magnitude and the error history of the last

three trials. Here, we used four bins of error magnitudes (0, 1, 2, 3+). Based on the outcome of

correct or error on the last three trials, there were 8 types of error history. For each error

magnitude, we calculated the probability of switching for each type of error history. We

hypothesized that participants in the noisy condition would tend to switch their choice after small

errors more if they had made more errors recently. To test this hypothesis, we ordered the 8 types

of error history based on the number of recent errors and calculated the slope of probability of

switching against the order of error history. A negative slope means that participants tend to

switch as they receive more recent errors.

Behavior modeling

We fit several different computational models to participants' choices to evaluate which

ones could best account for their behavior in the task.

Reduced Bayesian (RB) model

Previous studies have shown that a reduced Bayesian model, which approximates the full

Bayesian ideal observer, could account well for participants' behavior in dynamic environments

similar to the current task (McGuire et al., 2014; Nassar et al., 2012; Nassar et al., 2010). In this

model, belief is updated by a delta rule:

$$\delta_t = x_t - B_t \tag{1}$$

428
$$B_{t+1} = B_t + \alpha_t \delta_t \tag{2}$$

430   where B_t is the current belief and x_t is the current observation. The new belief (B_{t+1}) is formed

431   by updating the old belief according to the prediction error $(x_t - B_t)$ and a learning rate (α_t).

432   The learning rate controls how much a participant revises their belief based on the prediction

433   error. In this model, the learning rate is adjusted on a trial-by-trial basis according to:

435
$$\alpha_t = \Omega_t + (1 - \Omega_t)\tau_t \tag{3}$$

437   where Ω_t is the change-point probability and τ_t is the relative uncertainty. That is, α_t is high as

438   either Ω_t or τ_t is high. The change-point probability is the relative likelihood that the new

439   observation represents a change-point as opposed to a sample from the currently inferred state

440   (Nassar et al., 2010):

442
$$\Omega_t = \frac{U(x_t|1, 10)H}{U(x_t|1, 10)H + f_p(x_t|\gamma_t, B_t)(1-H)} \tag{4}$$

444   where H is the hazard rate, $U(x_t|1, 10)$ is the probability of outcome derived from a uniform

445   distribution, and $f_p(x_t|\gamma_t, B_t)$ is the probability of outcome derived from the current predictive

446   distribution. That is, $U(x_t|1, 10)$ reflects the probability of outcome when a change-point has

447   occurred while $f_p(x_t|\gamma_t, B_t)$ reflects the probability of outcome when the state has not changed.

448   The predictive distribution is an integration of the state distribution and the noise distribution:

450
$$f_p(X|\gamma_t, B_t) = C \times P(X|B_t)^{\gamma_t} \times P(X|B_t) \tag{5}$$

where X is a random variable determining the locations of target, $P(X|B_t)$ is the noise

distribution in the current condition, $P(X|B_t)^{\gamma_t}$ is the state distribution, γ_t is the expected run

length after the change-point, and C is a normalizing constant to make the sum of probabilities in

the predictive distribution equal one. Thus, the uncertainty of this predictive distribution comes

from two sources: the uncertainty of the state distribution (σ_s^2) and the uncertainty of the noise

distribution (σ_N^2). The uncertainty of the state distribution would decrease as the expected run

length increases.

The expected run length reflects the expected number of trials that a state remains stable,

and thus is updated on each trial based on the change-point probability (Nassar et al., 2010):

$$\gamma_{t+1} = (\gamma_t + 1)(1 - \Omega_t) + \Omega_t \tag{6}$$

where the expected run length is a weighted average conditional on the change-point probability.

If no change-point occurs (i.e., change-point probability is low), the expected run length would

increase, leading the uncertainty of the state distribution to decrease. That is, as more

observations from the current state are received, participants are more certain about the location

of the current state. However, if the change-point probability is high, which signals a likely

change in the state, the expected run length would be reset to 1. Thus, the uncertainty of the state

distribution becomes large. Participants are more uncertain about the current state after a change-

point.

The other factor influencing the learning rate is the relative uncertainty, which is the

uncertainty regarding the current state relative to the irreducible uncertainty or noise (McGuire et

al., 2014; Nassar et al., 2012):

$$\tau_{t+1} = \frac{\Omega_t \sigma_N^2 + (1-\Omega_t)\sigma_S^2 + \Omega_t(1-\Omega_t)[\delta_t(1-\tau_t)]^2}{\Omega_t \sigma_N^2 + (1-\Omega_t)\sigma_S^2 + \Omega_t(1-\Omega_t)[\delta_t(1-\tau_t)]^2 + \sigma_N^2} \tag{7}$$

The three terms in the numerator contribute to the uncertainty about the current state. The

first term reflects the uncertainty conditional on the change-point distribution; the second term

reflects the uncertainty conditional on the non-change-point distribution; and the third term

reflects the uncertainty due to the difference between the two distributions. The denominator

shows the total variance which is the summation of the uncertainty about the current state and the

noise. As more precise observations are received in a given state, this relative uncertainty would

decrease.

To fit the reduced Bayesian model to behavior, we assumed that participants can depart

from the ideal observer by having subjective estimates of the key environmental variables,

hazard rate and noise, that may differ from the true value of these variables. During model fitting,

the subjective noise distribution was estimated with the von Mises distribution, which is a

circular Gaussian distribution:

$$P(x_t|B_t, K) = \frac{e^{K\cos(x_t - B_t)}}{\sum_{i=1}^{10} e^{K\cos(x_i - B_t)}}$$ (8)

where B_t is the location of the current belief, x_i is the location of target, and K controls the

uncertainty of this distribution. When K is 0, this is a uniform distribution. As K increases, the

uncertainty decreases. The denominator is used as a normalization term to make sure the sum of

all the probabilities equals one. Thus, there are two free parameters in this model: hazard rate (*H,*

in Eq. 4) and noise level (*K,* in Eq. 8). The range of hazard rate is between 0 and 1 and the noise

level is greater than or equal to zero.

Fixed learning rate (fixedLR) model

We also consider an alternative model in which participants used a fixed learning rate in

each of the two dynamic conditions. That is, the learning rate is the same over all trials in a

condition. This model has one free parameter, the fixed learning rate (α_{fixed}), for each condition

(Eq. 2). The fixed learning rate is between 0 and 1.

Hybrid of RB model and fixedLR model

Furthermore, we consider a hybrid model, in which the learning rate on each trial is a

mixture of the learning rates from the RB model and the fixedLR model:

$$\alpha_t = w\alpha_{RB} + (1 - w)\alpha_{fixed}$$ (9)

where α_{RB} is the learning rate from the RB model and is varied trial by trial according to Ω_t and

τ_t, α_{fixed} is the learning rate from the fixedLR model and w reflects the weight to integrate these

two learning rates. In this model, there are four free parameters: hazard rate, noise level, fixed

learning rate and weight. The weight is between 0 and 1.

Hybrid of RB model and P$_{stay}$

Finally, we consider a hybrid model, which combines the RB model with a fixed

tendency to stay on the current target regardless of the current observation. Such a fixed

tendency to stay was observed in monkeys in our previous study (Li et al., 2019). Here the belief

is updated by:

523
$$B_{t+1} = B_t + [(1 - P_{stay}) \times \alpha_t(X_t - B_t) + P_{stay} \times 0] \tag{10}$$

where P_{stay} is the probability that participants stay on the current target. This model has three

free parameters: hazard rate, noise level and the probability of stay. The probability of stay is

between 0 and 1.

Model fitting and comparison

Each model was fitted to data from each participant and within each condition separately.

Optimal parameters were estimated by minimizing the mean of the squared error (MSE) between

a participant's prediction and the model prediction.

534
$$MSE = \frac{\sum_{t=1}^{n}(B_t - \widehat{B_t})^2}{n} \tag{11}$$

536   where t is the trial, n is the total number of included trials, B_t is a participant's prediction on trial

537   t, and $\widehat{B_t}$ is the model prediction on trial t.

538   Because each model used a different number of parameters and each participant had a

539   different number of included trials, we used Bayesian Information Criterion (BIC) to compare

540   the performance of different models:

542
$$BIC = n\ln(MSE) + k\ln(n) \tag{12}$$

where n is the number of included trials and k is the number of free parameters in a model. A

model with lower BIC performs better.

MRI Data Acquisition and Preprocessing

We acquired MRI data on a 3T Siemens Prisma with a 64-channel head coil. Before the

task, we acquired a T1-weighted MPRAGE structural image (0.9375 X 0.9375 X 1 mm voxels,

192 X 256 matrix, 160 axial slices, TI = 1,100 ms, TR = 1,810 ms, TE = 3.45 ms, flip angle = 9°).

During each run of the task, we acquired functional data using a multiband gradient echo-planar

imaging (EPI) sequence (1.9592 X 1.9592 X 2 mm voxels, 98 X 98 matrix, 72 axial slices tilted

30° from the AC-PC plane, TR = 1,500 ms, TE = 30 ms, flip angle = 45°, multiband factor = 4).

The scanning time (mean = 24.14 minutes, SD = 1.47, range = 21.85-30.00) for each run was

dependent on the participants' pace. After the task, fieldmap images (TR = 1,270 ms, TE = 5 ms

and 7.46 ms, flip angle = 60°) were acquired.

Data were preprocessed using FMRIB's Software Library (FSL) (Jenkinson, Beckmann,

Behrens, Woolrich, & Smith, 2012; Smith et al., 2004). Functional data were motion corrected

using MCFLIRT (Jenkinson, Bannister, Brady, & Smith, 2002), high-pass filtered with a

Gaussian-weighted least square straight line fitting of $\sigma = 50\ s$, undistorted and warped to MNI

space. To map the data to MNI space, boundary-based registration was applied to align the

functional data to the structural image (Greve & Fischl, 2009) and fieldmap-based geometric

undistortion was also applied. In addition, the structural image was normalized to the MNI space

(FLIRT). Then, these two transformations were applied to the functional data.

fMRI analysis: univariate activity correlated with CPP and RU

Using similar procedures to our previous study (McGuire et al., 2014), we examined the

effects of CPP and RU on univariate activity. Both the current study and the previous study

investigate the computational process and neural mechanisms during learning in dynamic

environments. The underlying task structures (which involved noisy observations and sudden

change-points) are similar between the two studies, but the two studies used very different visual

stimuli and motor demands. We specifically focused on the noisy condition in the current study

because it was more similar to the underlying structure, in terms of noisy observations and

hazard rate of change-points, to our previous study.

We investigated the factors of CPP, RU, reward values and residual updates. The trial-by-

trial CPP and RU were either estimated from the RB model with subjective estimates of hazard

rate and noise (as this was the best-fitting model in the current study, analyses presented in

Figure 2 – Supplement 3) or from the RB model with true estimates of hazard rate and noise (as

this corresponds to how correlates of CPP and RU were identified in our previous study, analyses

presented in Figure 2 – Supplement 4). The residual update reflects the difference between the

participants' update and the predicted update, and is estimated from a behavioral regression

model in a similar manner as our previous study:

$$Update_t = \beta_0 + \beta_1 \delta_t + \beta_2 \delta_t \Omega_t + \beta_3 \delta_t (1 - \Omega_t)\tau_t + \beta_4 \delta_t Reward + \varepsilon \qquad (13)$$

where $Update_t$ is the difference between B_{t+1} and B_t, δ_t is the error magnitude, both Ω_t and τ_t

were derived from the RB model, and the reward value indicated whether a correct response

earned a large or a small value on that trial.

Then, a general linear model using these four factors was implemented on the neural data.

Here we further smoothed the preprocessed fMRI data with a 6 mm FWHM Gaussian kernel. We

included several trial-by-trial regressors of interest in the GLM: onsets of outcome, CPP, RU,

reward value, and residual update. Six motion parameters were also included as confounds. To

control false-positive rates (Eklund et al., 2016), statistical testing was implemented through one-

sample cluster-mass permutation tests with 5,000 iterations. The cluster-forming threshold was

uncorrected voxel $p<0.01$. Statistical testing was then based on the corrected cluster p value. For

the conjunction analyses, we used the same procedure as the previous study (McGuire et al.,

2014). We kept regions that passed the corrected threshold and showed the same sign of effects.

For these conjunction tests, we only kept regions that have at least 10 contiguous voxels.

Because the number of participants was fewer in this study (n=16) than in the previous

study (n=32), we might have lower power to detect effects in the whole-brain analyses. Thus, we

also implemented ROI analyses. We selected seven ROIs that showed the conjunction effects of

CPP, RU and reward value in the previous study (McGuire et al., 2014) and tested the effects of

CPP and RU in these ROIs.

We found previously that for a similar task, the presence or absence of reward on a given

trial influenced both belief-updating behavior and some aspects of its neural representation

(McGuire et al., 2014). To further examine those effects, here we included two different earnable

values (10 versus 20 points). However, we did not find any significant effects of earnable values

on either belief updating (β_4 in Eq. 13 was not significantly different than zero) or neural activity

(for the contrast of high versus low earnable value). We therefore do not further consider the

effects of this manipulation in the current report. We speculate that this lack of an effect

contrasts from our earlier finding because here we used high versus low earnable values, whereas

in that study we used the presence versus absence of earnable value.

fMRI analysis: multi-voxel pattern analysis (MVPA)

We implemented MVPA to understand the neural representation of error signals and

subsequent choices. Our analyses focus on the multi-voxel pattern when participants received an

outcome. Before implementing MVPA, we estimated trial-by-trial beta values using the

unsmoothed preprocessed fMRI data. We used the general linear model (GLM) to estimate the

beta weights for each trial (Mumford, Turner, Ashby, & Poldrack, 2012). In each GLM, the first

regressor is the trial of interest and the second combines the rest of trials in the same condition.

These two regressors were then convolved with a gamma hemodynamic response function. In

addition, six motion parameters were included as control regressors. We repeated this process

(one GLM per trial) to estimate trial-by-trial beta values for all the trials in the two conditions.

We then used these beta values as observations for MVPA. A whole-brain searchlight was

implemented (Kriegeskorte, Goebel, & Bandettini, 2006). In each searchlight, a sphere with the

diameter of 5 voxels (10 mm) was formed, and the pattern of activity across the voxels within the

sphere were used to run MVPA.

A support vector machine (SVM) with a linear kernel was used to decode different error

signals and choices in our whole-brain searchlight analysis. We implemented SVM through the

LIBSVM toolbox (Chang & Lin, 2011). To avoid overfitting, we used 3-fold cross-validation,

with one fold used as testing data and the other two as training data. Training data were used to

train the classifier and then this classifier was used on testing data to examine the classification

accuracy. In linear SVM, a free parameter c regularizes the trade-off between decreasing training

error and increasing generalization. Thus, during the training of classifier, the training data were

further split into 3-folds to select the optimal value of the parameter c through cross-validation.

We pick the optimal value for c from [0.001, 0.01, 0.1, 1, 10, 100, 1000] and this optimal

parameter should maximize the cross-validation accuracy. Then, we used the optimal parameter

c to train the model again based on the entire training data and calculated the classification

accuracy on the testing data. We repeated this procedure with each of the three folds held out as

testing data and calculated the average of the classification accuracy. To minimized the influence

of different number of trials for each category on the classification accuracy, we used balanced

accuracy. For balanced accuracy, we first calculated the classification accuracy within each

category, and then averaged the accuracies across all categories. The baseline balanced accuracy

was also validated via permutations with 5,000 iterations. For each permutation, each trial was

randomly assigned one category with a probability proportional to the number of trials in that

category among all the trials. We then used the average of balanced accuracy across these

iterations as the baseline accuracy. The baseline accuracy for two categories was 50% and for

three categories was 33%.

We first examined how the multi-voxel neural pattern on the current trial could

discriminate correct versus error on the current trial or error magnitudes on error trials. For the

analysis of error magnitudes, we split trials into three bins of error magnitude: 1, 2, and 3+.

We next examined how the multi-voxel neural pattern on the current trial could

discriminate whether the previous trial was an error or not. We also investigated how the

classification of past errors differs conditional on the type of the current trial. We classified trial

t-1 as correct or error separately for four different types of current trials: correct trials, error trials,

trials with error magnitudes of 0 or 3+ and trials with error magnitudes of 1 or 2. We

differentiated between trials with error magnitudes of 0 or 3+ and trials with error magnitudes of

1 or 2 because error magnitudes of 0 or 3+ provide unambiguous evidence regarding a change of

state in the noisy condition while error magnitudes of 1 or 2 provide ambiguous evidence about a

change of the state in the noisy condition.

Lastly, we examined how the multi-voxel neural pattern on the current trial could classify

the choice on the next trial. In this analysis, we focused only on the trials with error magnitudes

of 1 or 2 in the noisy condition, because only under these conditions were participants similarly

likely to switch versus stay. For these trials, we examined whether the multi-voxel pattern on the

current trial predicted whether the participant stayed or switched on the next trial.

After obtaining the classification accuracy for each participant, we subtracted the baseline

accuracy from the classification accuracy. Before conducting a group-level test, we smoothed

these individual accuracy maps with a 6 mm FWHM Gaussian kernel. To control false-positive

rates (Eklund et al., 2016), statistical testing was implemented through one-sample cluster-mass

permutation tests with 5,000 iterations. We used uncorrected voxel $p<0.01$ to form a cluster and

estimated the corrected cluster p value for each cluster. For comparison, we report our results

using other cluster-forming procedures in supplemental analyses. For the conjunction analyses,

we used the same procedure described above.

Acknowledgments

This work was supported by grants from National Institute of Mental Health (R01-MH098899 to

J.I.G. and J.W.K.) and National Science Foundation (1533623 to J.I.G. and J.W.K.). We thank

Yin Li for valuable comments; M. Kathleen Caulfield for fMRI scanning.

References

Akrami, A., Kopec, C. D., Diamond, M. E., & Brody, C. D. (2018). Posterior parietal cortex represents sensory history and mediates its effects on behaviour. *Nature, 554*, 368. doi:10.1038/nature25510

Alexander, W. H., & Brown, J. W. (2015). Hierarchical error representation: a computational model of anterior cingulate and dorsolateral prefrontal cortex. *Neural Computation, 27*(11), 2354-2410.

Behrens, T. E. J., Woolrich, M. W., Walton, M. E., & Rushworth, M. F. S. (2007). Learning the value of information in an uncertain world. *Nat Neurosci, 10*(9), 1214-1221. doi:10.1038/nn1954

Blanchard, T. C., & Gershman, S. J. (2018). Pure correlates of exploration and exploitation in the human brain. *Cognitive, Affective, & Behavioral Neuroscience, 18*(1), 117-126. doi:10.3758/s13415-017-0556-2

Brass, M., & Cramon, D. Y. v. (2004). Decomposing components of task preparation with functional magnetic resonance imaging. *Journal of cognitive neuroscience, 16*(4), 609-620.

Brody, C. D., & Hanks, T. D. (2016). Neural underpinnings of the evidence accumulator. *Current Opinion in Neurobiology, 37*, 149-157. doi:10.1016/j.conb.2016.01.003

Chan, S. C. Y., Niv, Y., & Norman, K. A. (2016). A Probability Distribution over Latent Causes, in the Orbitofrontal Cortex. *The Journal of Neuroscience, 36*(30), 7817-7828. doi:10.1523/jneurosci.0659-16.2016

Chang, C.-C., & Lin, C.-J. (2011). LIBSVM: a library for support vector machines. *ACM transactions on intelligent systems and technology, 2*(3), 27. doi:10.1145/1961189.1961199

d'Acremont, M., & Bossaerts, P. (2016). Neural Mechanisms Behind Identification of Leptokurtic Noise and Adaptive Behavioral Response. *Cerebral Cortex, 26*(4), 1818-1830. doi:10.1093/cercor/bhw013

Daw, N. D., O'Doherty, J. P., Dayan, P., Seymour, B., & Dolan, R. J. (2006). Cortical substrates for exploratory decisions in humans. *Nature, 441*(7095), 876-879. doi:10.1038/nature04766

Derrfuss, J., Brass, M., Neumann, J., & von Cramon, D. Y. (2005). Involvement of the inferior frontal junction in cognitive control: Meta-analyses of switching and Stroop studies. *Human Brain Mapping, 25*(1), 22-34. doi:10.1002/hbm.20127

Eklund, A., Nichols, T. E., & Knutsson, H. (2016). Cluster failure: Why fMRI inferences for spatial extent have inflated false-positive rates. *Proceedings of the National Academy of Sciences, 113*(28), 7900-7905. doi:10.1073/pnas.1602413113

Fischer, Adrian G., & Ullsperger, M. (2013). Real and Fictive Outcomes Are Processed Differently but Converge on a Common Adaptive Mechanism. *Neuron, 79*(6), 1243-1255. doi:10.1016/j.neuron.2013.07.006

FitzGerald, T. H. B., Moran, R. J., Friston, K. J., & Dolan, R. J. (2015). Precision and neuronal dynamics in the human posterior parietal cortex during evidence accumulation. *NeuroImage, 107*, 219-228. doi:10.1016/j.neuroimage.2014.12.015

Furl, N., & Averbeck, B. B. (2011). Parietal Cortex and Insula Relate to Evidence Seeking Relevant to Reward-Related Decisions. *The Journal of Neuroscience, 31*(48), 17572-17582. doi:10.1523/jneurosci.4236-11.2011

Gläscher, J., Daw, N., Dayan, P., & O'Doherty, J. P. (2010). States versus Rewards: Dissociable
Neural Prediction Error Signals Underlying Model-Based and Model-Free Reinforcement
Learning. *Neuron, 66*(4), 585-595. doi:10.1016/j.neuron.2010.04.016
Glaze, C. M., Kable, J. W., & Gold, J. I. (2015). Normative evidence accumulation in
unpredictable environments. *eLife, 4*, e08825. doi:10.7554/eLife.08825
Greve, D. N., & Fischl, B. (2009). Accurate and robust brain image alignment using boundary-
based registration. *NeuroImage, 48*(1), 63-72. doi:10.1016/j.neuroimage.2009.06.060
Hampton, A. N., Bossaerts, P., & O'Doherty, J. P. (2006). The Role of the Ventromedial
Prefrontal Cortex in Abstract State-Based Inference during Decision Making in Humans.
The Journal of Neuroscience, 26(32), 8360-8367. doi:10.1523/jneurosci.1010-06.2006
Hampton, A. N., & O'Doherty, J. P. (2007). Decoding the neural substrates of reward-related
decision making with functional MRI. *Proceedings of the National Academy of Sciences,*
104(4), 1377-1382. doi:10.1073/pnas.0606297104
Hanks, T. D., Kopec, C. D., Brunton, B. W., Duan, C. A., Erlich, J. C., & Brody, C. D. (2015).
Distinct relationships of parietal and prefrontal cortices to evidence accumulation.
Nature, 520, 220. doi:10.1038/nature14066
Hayden, B. Y., Nair, A. C., McCoy, A. N., & Platt, M. L. (2008). Posterior Cingulate Cortex
Mediates Outcome-Contingent Allocation of Behavior. *Neuron, 60*(1), 19-25.
doi:10.1016/j.neuron.2008.09.012
Hunt, L. T., Malalasekera, W. M. N., de Berker, A. O., Miranda, B., Farmer, S. F., Behrens, T.
E. J., & Kennerley, S. W. (2018). Triple dissociation of attention and decision
computations across prefrontal cortex. *Nature Neuroscience, 21*(10), 1471-1481.
doi:10.1038/s41593-018-0239-5
Hwang, E. J., Dahlen, J. E., Mukundan, M., & Komiyama, T. (2017). History-based action
selection bias in posterior parietal cortex. *Nature Communications, 8*(1), 1242.
doi:10.1038/s41467-017-01356-z
Jenkinson, M., Bannister, P., Brady, M., & Smith, S. (2002). Improved Optimization for the
Robust and Accurate Linear Registration and Motion Correction of Brain Images.
NeuroImage, 17(2), 825-841. doi:10.1006/nimg.2002.1132
Jenkinson, M., Beckmann, C. F., Behrens, T. E., Woolrich, M. W., & Smith, S. M. (2012). FSL.
NeuroImage, 62(2), 782-790. doi:10.1016/j.neuroimage.2011.09.015
Karlsson, M. P., Tervo, D. G. R., & Karpova, A. Y. (2012). Network Resets in Medial Prefrontal
Cortex Mark the Onset of Behavioral Uncertainty. *Science, 338*(6103), 135-139.
doi:10.1126/science.1226518
Kolling, N., Behrens, T. E. J., Mars, R. B., & Rushworth, M. F. S. (2012). Neural Mechanisms of
Foraging. *Science, 336*(6077), 95-98. doi:10.1126/science.1216930
Kolling, N., Wittmann, M. K., Behrens, T. E. J., Boorman, E. D., Mars, R. B., & Rushworth, M.
F. S. (2016). Value, search, persistence and model updating in anterior cingulate cortex.
Nature Neuroscience, 19, 1280. doi:10.1038/nn.4382
Kriegeskorte, N., Goebel, R., & Bandettini, P. (2006). Information-based functional brain
mapping. *Proceedings of the National Academy of Sciences of the United States of*
America, 103(10), 3863-3868. doi:10.1073/pnas.0600244103
Li, Y. S., Nassar, M. R., Kable, J. W., & Gold, J. I. (2019). Individual neurons in the cingulate
cortex encode action monitoring, not selection, during adaptive decision-making. *The*
Journal of Neuroscience, 0159-0119. doi:10.1523/jneurosci.0159-19.2019

McGuire, J. T., Nassar, M. R., Gold, J. I., & Kable, J. W. (2014). Functionally Dissociable
Influences on Learning Rate in a Dynamic Environment. *Neuron, 84*(4), 870-881.
doi:10.1016/j.neuron.2014.10.013
Muller, T. H., Mars, R. B., Behrens, T. E., & O'Reilly, J. X. (2019). Control of entropy in neural
models of environmental state. *eLife, 8*, e39404. doi:10.7554/eLife.39404
Mumford, J. A., Turner, B. O., Ashby, F. G., & Poldrack, R. A. (2012). Deconvolving BOLD
activation in event-related designs for multivoxel pattern classification analyses.
NeuroImage, 59(3), 2636-2643. doi:10.1016/j.neuroimage.2011.08.076
Nassar, M. R., Bruckner, R., & Frank, M. J. (2019). Statistical context dictates the relationship
between feedback-related EEG signals and learning. *eLife, 8*, e46975.
doi:10.7554/eLife.46975
Nassar, M. R., McGuire, J. T., Ritz, H., & Kable, J. W. (2019). Dissociable Forms of
Uncertainty-Driven Representational Change Across the Human Brain. *The Journal of*
Neuroscience, 39(9), 1688-1698. doi:10.1523/jneurosci.1713-18.2018
Nassar, M. R., Rumsey, K. M., Wilson, R. C., Parikh, K., Heasly, B., & Gold, J. I. (2012).
Rational regulation of learning dynamics by pupil-linked arousal systems. *Nature*
Neuroscience, 15(7), 1040-1046. doi:10.1038/nn.3130
Nassar, M. R., Wilson, R. C., Heasly, B., & Gold, J. I. (2010). An approximately Bayesian delta-
rule model explains the dynamics of belief updating in a changing environment. *The*
Journal of Neuroscience, 30(37), 12366-12378. doi:10.1523/JNEUROSCI.0822-10.2010
O'Reilly, J. X., Schüffelgen, U., Cuell, S. F., Behrens, T. E. J., Mars, R. B., & Rushworth, M. F.
S. (2013). Dissociable effects of surprise and model update in parietal and anterior
cingulate cortex. *Proceedings of the National Academy of Sciences, 110*(38), E3660-
E3669. doi:10.1073/pnas.1305373110
Payzan-LeNestour, E., Dunne, S., Bossaerts, P., & O'Doherty, John P. (2013). The Neural
Representation of Unexpected Uncertainty during Value-Based Decision Making.
Neuron, 79(1), 191-201. doi:10.1016/j.neuron.2013.04.037
Purcell, B. A., & Kiani, R. (2016). Hierarchical decision processes that operate over distinct
timescales underlie choice and changes in strategy. *Proceedings of the National Academy*
of Sciences, 113(31), E4531-E4540. doi:10.1073/pnas.1524685113
Schuck, N. W., Cai, M. B., Wilson, R. C., & Niv, Y. (2016). Human Orbitofrontal Cortex
Represents a Cognitive Map of State Space. *Neuron, 91*(6), 1402-1412.
doi:10.1016/j.neuron.2016.08.019
Smith, S. M., Jenkinson, M., Woolrich, M. W., Beckmann, C. F., Behrens, T. E., Johansen-Berg,
H., . . . Flitney, D. E. (2004). Advances in functional and structural MR image analysis
and implementation as FSL. *NeuroImage, 23 (S1)*, S208-S219.
doi:10.1016/j.neuroimage.2004.07.051
Sutton, R. S., & Barto, A. G. (1998). *Reinforcement Learning*. Cambridge, MA: MIT Press.
Ullsperger, M., Danielmeier, C., & Jocham, G. (2014). Neurophysiology of Performance
Monitoring and Adaptive Behavior. *Physiological Reviews, 94*(1), 35-79.
doi:10.1152/physrev.00041.2012
Wilson, R. C., Takahashi, Y. K., Schoenbaum, G., & Niv, Y. (2014). Orbitofrontal Cortex as a
Cognitive Map of Task Space. *Neuron, 81*(2), 267-279.
doi:10.1016/j.neuron.2013.11.005
814
815

816
817
Figure 1
Overview of task and experimental design. (**A**) Sequence of the task. At the start of the trial, participants
look at a cross in the center of the screen and maintain fixation for 0.5 sec to initialize the trial. After the
cross disappears, participants choose one of 10 targets (red) by looking at it within 1.5 sec and then
holding fixation on the chosen target for 0.3 sec. During the outcome phase (1 sec), a green dot inside the
target indicates the participants' choice. The rewarded target is shown in purple or cyan to indicate the
number of earnable points as 10 or 20, respectively. (**B**) Probability distribution of the rewarded target
location in the noisy condition. Target location is relative to the location of the state (generative mean).
The rewarded target probabilities for the relative locations of [-2, -1, 0, 1, 2] are [0.05, 0.15, 0.6, 0.15,
0.05]. (**C**) Example of trials in the noisy condition. The states change occasionally with a hazard rate of
0.02. (**D**) Probability distribution of the rewarded target location in the unstable condition. Because there
is no noise in this condition, the rewarded target is always at the location of the state. (**E**) Example of
trials in the unstable condition. The states change frequently with a hazard rate of 0.35.
831

832
833
Figure 2
Behavioral results. (**A**) Probability of choosing the best target after change-points. Symbols and error bars
are mean±SEM across subjects (solid symbols) or simulations (open symbols). (**B**) Relationship between
error magnitude and switch probability. Symbols and error bars are as in **A**. (**C**) The distribution of switch
probabilities for small errors (magnitude of 1 or 2) in both conditions. Each data point represents one
participant. Distributions for all error magnitudes are shown in Figure 2 – Figure Supplement 1. (**D**)
Probability of switch as a function of current error magnitude and error history in the unstable condition.
Different colors represent different error histories for the past 3 trials. A correct trial is marked as O, and
an error trial is marked as X. For example, XOO implies that trial t-1 was an error trial, and trial t-2 and
trial t-3 were correct trials. Symbols and error bars are mean±SEM across subjects. (**E**) Probability of
switch as a function of current error magnitude and error history in the noisy condition. Symbols and error
bars are as in **D**. (**F**) The distribution of the slopes of switch probability against error history for small
errors (magnitude of 1 or 2) in both conditions. Each data point represents one participant. Distributions
for all error magnitudes are shown in Figure 2 – Figure Supplement 1.
848

849
850
Figure 3
Representations of error and error magnitude. For error versus correct analyses, multi-voxel neural
patterns were used to classify whether the response on the current trial was correct or an error. For error
magnitude analyses, multi-voxel neural patterns were used to classify different error magnitudes (1, 2, 3+)
conditional on the current trial being an error. Accuracies were calculated and compared with the baseline
accuracy within each subject and then tested at the group level. The representation of current error
magnitude is stronger in parietal cortex in the noisy condition than the unstable condition. The cluster-
forming threshold was an uncorrected voxel $p<0.01$ (t=2.6), with cluster extent corrected for multiple
comparisons using non-parametric permutation tests.

"Error vs Correct" on the previous trial

860
861
Figure 4
Representations of errors on the previous trial conditional on different types of current trials (columns).
Multi-voxel neural patterns were used to classify correct responses versus errors on the previous trial.
This analysis was repeated for different types of current trials: all feedback, correct feedback, error
feedback, error magnitude of 0 or 3+, and error magnitude of 1 or 2. The representation of past errors is
stronger in parietal cortex in the noisy condition than the unstable condition when the current trial is an
error or the current error magnitude is 1 or 2. The cluster-forming threshold was an uncorrected voxel
$p<0.01$ (t=2.6), with cluster extent corrected for multiple comparisons using non-parametric permutation
tests.

871
872
Figure 5
Representations of subsequent behavioral choices (switch versus stay) after ambiguous small errors in the
noisy condition. (**A**) Overlap of results for switch versus stay on the next trial and error magnitude on the
current trial. Multi-voxel neural patterns were used to classify whether participants switch their choice to
another target or stay on the same target on the next trial. We focused on the most ambiguous errors (error
magnitude of 1 or 2 in the noisy condition). Above-chance classification performance was found in a
large cluster encompassing the frontal lobe. The cluster-forming threshold was an uncorrected voxel
$p<0.01$ ($t=2.6$), with cluster extent corrected for multiple comparisons using non-parametric permutation
tests. (**B**) Overlap of results for switch versus stay on the next trial and past error conditional on error
magnitude of 1 or 2 on the current trial.
883

884
885
886 **Figure 2 - Figure supplement 1**
887 Distributions of behavior as a function of error magnitude. (**A**) Distributions of switch probability as a
888 function of error magnitude. Each data point represents one participant. (**B**) Distributions of slopes of
889 switch probability against error history as a function of error magnitude. Each data point represents one
890 participant.
891

892
893
Figure 2 - Figure supplement 2
Behavioral data and predictions from different models. (**A**) Probability of choosing the best target after
change-points. (RB: reduced Bayesian; fixedLR: fixed learning rate; P_{stay}: fixed tendency to stay) (**B**) The
relationship between error magnitude and switch probability. (**C**) Probability of switch as a function of
current error magnitude and error history in the unstable condition. (**D**) Probability of switch as a function
of current error magnitude and error history in the noisy condition. Symbols and colors are as in Figure 2.
900

Figure 2 - Figure supplement 3

Reduced Bayesian model applied to behavioral and imaging data. (**A**) Model prediction for CPP. We calculated CPP from the fitted reduced Bayesian model, which incorporates subjective estimates of hazard rate and noise for each condition. The value of CPP increases as the current error magnitude increases in both conditions, but with a stronger dependence on the outcome of the previous trial in the noisy condition. (**B**) Model prediction for RU. We calculated RU from the fitted reduced Bayesian model, which incorporates subjective estimates of hazard rate and noise for each condition. The value of RU is minimally affected by the current error magnitude. Instead, a past error tends to increase RU. (**C**) Model prediction for probability of switching choices. Increasing CPP causes the probability of switching to increase more steeply as the current error magnitude increases in the unstable condition versus in the noisy condition. For small errors (error magnitude of 1 and 2) in the noisy condition, the probability of switching is further influence by RU, which is affected by past errors. (**D**) Neural representation of CPP and RU. CPP selective effect represents the conjunction of CPP>0 and CPP>RU. RU selective effect represents the conjunction of RU>0 and RU>CPP. The results were thresholded based on uncorrected voxel $p<0.01$ (t=2.6). (**E**) ROI analysis for CPP and RU. These ROIs were selected based on the common

918 regions of CPP, RU, and reward effects in McGuire et al. (2014). Significance was tested by a sign test.
919 *$p<0.05$, **$p<0.01$, ***$p<0.001$.
920

921
922
Figure 2 - Figure supplement 4
Neural representations of CPP and RU from the approximately ideal observer, which is the reduced
Bayesian model with true hazard rate and noise, for direct comparison to analyses in McGuire et al.
(2014), which used covariates constructed from the ideal rather than the fitted model. (**A**) Neural
representation of CPP and RU in the current study and in McGuire et al. (2014). CPP selective effect
represents the conjunction of CPP>0 and CPP>RU. RU selective effect represents the conjunction of
RU>0 and RU>CPP. The results were thresholded based on uncorrected voxel $p<0.01$ (t=2.6). (**B**) ROI
analysis for CPP and RU. These ROIs were selected based on the common regions of CPP, RU and
reward effects in McGuire et al. (2014). Significance was tested by a sign test. *$p<0.05$, **$p<0.01$,
***$p<0.001$.
933

935
936
Figure 3 - Figure supplement 1
Univariate representations of error and error magnitude. A GLM was implemented on the preprocessed
fMRI data (smoothed with 6 mm FWHM Gaussian kernel). The trial-by-trial regressors of interest that
were included in the GLM were: onset of correct trials, earnable value on correct trials, onset of error
trials, error magnitude on error trials, switch or stay on error trials and earnable value on error trials. We
focused on the effects of error (which is the difference between the onset of error trials and the onset of
correct trials) and error magnitude. Group *t*-values are shown. For statistical testing, we implemented one-
sample cluster-mass permutation tests with 5,000 iterations. The cluster-forming threshold was
uncorrected voxel *p*<0.01 (*t*=2.6).
946

"Error vs Correct" on the previous trial

947
948
Figure 4 - Figure supplement 1
Univariate representations of error on the previous trial conditional on different types of current trials
(columns). Several GLMs were implemented on the preprocessed fMRI data (smoothed with 6 mm
FWHM Gaussian kernel). First, we examined errors on the previous trial across all trials. The trial-by-trial
regressors of interest that were included in the GLM were: onset of trials, error on trial t, error on trial t-1,
error on trial t-2, and error on trial t-3. We focused on the effect of error on trial t-1. Second, we separated
the analysis of past errors conditional on the current trial being correct or an error. The trial-by-trial
regressors of interest that were included in the GLM were: onset of current correct trials, errors on trial t-1,
t-2, or t-3 conditional on the current trial being correct, onset of current error trials, errors on trial t-1, t-2,
or t-3 conditional on the current trial being an error. We focused on the effects of error on trial t-1
conditional on the current trial being correct or an error. Third, we separated errors conditional on error
magnitudes of 0 or 3+ or error magnitudes of 1 or 2. The trial-by-trial regressors of interest that were
included in the GLM were: onset of current trials with error magnitudes of 0 or 3+, errors on trial t-1, t-2
or t-3 conditional on the current trial error magnitude of 0 or 3+, onset of current trials with error
magnitudes of 1 or 2, errors on trial t-1, t-2 or t-3 conditional on the current trial error magnitude of 1 or 2.
We focused on the effects of errors on trial t-1 conditional on the current trials error magnitude of 0 or 3+
or error magnitude of 1 or 2. Group *t*-values are shown. For statistical testing, we implemented one-
sample cluster-mass permutation tests with 5,000 iterations. The cluster-forming threshold was
uncorrected voxel *p*<0.01 (*t*=2.6).
968

969
970
Figure 5 - Figure supplement 1
Representations of subsequent behavioral choices (switch versus stay) thresholded via threshold-free
cluster enhancement (TFCE) or with a cluster-forming threshold of $p<0.001$. (**A**) Overlap of results for
switch versus stay on the next trial and error magnitude on the current trial. We implemented two types of
cluster-forming approaches: TFCE and uncorrected voxel $p<0.001$. First, significance testing was
implemented through permutation tests with threshold-free cluster enhancement (FSL's randomize),
which does not require a pre-defined cluster-forming threshold. The result of switch versus stay showed
little spatial specificity. For the purpose of display, the results were thresholded based on uncorrected
voxel $p<0.03$ ($t=2$). Second, we used a cluster-forming threshold of uncorrected voxel $p<0.001$ ($t=3.73$)
and tested the significance of the formed cluster via one-sample cluster-mass permutation tests with 5,000
iterations. The results showed high spatial specificity and several previously identified regions were still
significant: middle cingulate cortex [14, -8, 30], right insula [38, 4, 2], medial OFC [-4, 50, -10], left
premotor cortex [-62, 2, 24] and left superior temporal gyrus [-50, -32, 12]. (**B**) Overlap of results for
switch versus stay on the next trial and past error conditional on error magnitude of 1 or 2 on the current
trial. The two types of cluster-forming approaches are shown.
986

Figure 5 - Figure supplement 2
Univariate GLM for switch versus stay on small error trials (magnitudes of 1 or 2) in the noisy condition.
A GLM was implemented with several trial-by-trial regressors of interest: onset of trials with error
magnitude of 0, onset of trials with error magnitude of 3+, onset of trials with error magnitudes of 1 or 2
followed by switching, onset of trials with error magnitudes of 1 or 2 followed by staying. We tested the
effects of the difference between switch and stay for small errors. For statistical testing, we implemented
one-sample cluster-mass permutation tests with 5,000 iterations. The cluster-forming threshold was
uncorrected voxel $p<0.01$ (t=2.6). There were no significant clusters. For the demonstration, the results
were shown with uncorrected voxel $p<0.01$.
997

998   Table 1

999   BIC of behavior models

Model	Condition	BIC improvement by RB model
Reduced Bayesian model (RB)	Unstable	
	Noisy	
Fixed learning rate model (fixedLR)	Unstable	5.06 [3.63, 5.71]**
	Noisy	-21.05 [-76.63, 0.20]†
RB + fixedLR	Unstable	-9.83 [-11.20, -8.07]***
	Noisy	-4.64 [-10.51, 0.89]
RB + P$_{stay}$	Unstable	-5.20 [-5.65, -3.68]**
	Noisy	-5.55 [-5.65, -2.67]*

1000   Values are shown as median [IQR]. A negative value means that the RB model performed better
1001   than the alternative model. Significance was tested by a sign test. $^\dagger p<0.08$, $**p<0.01$,
1002 $***p<0.001$.
1003

1004 Table 2

1005 Parameters of behavior models

Model	Parameter	Unstable	Noisy	Unstable > Noisy
RB	H	0.82 [0.64, 0.90]	0.33 [0.11, 0.50]	0.37 [0.24, 0.62]***
	K	0.59 [0.03, 2.22]	1.86 [1.22, 2.32]	-0.23 [-1.97, 0.71]
fixedLR	α_{fixed}	0.96 [0.86, 0.97]	0.63 [0.37, 0.73]	0.33 [0.19, 0.49]***
RB + fixedLR	H	0.07 [0.00, 0.86]	0.03 [0.00, 0.19]	0.03 [-0.03, 0.77]
	K	11.19 [2.78, 18.01]	3.22 [2.28, 9.90]	5.13 [-4.91, 16.10]
	α_{fixed}	0.96 [0.75, 1.00]	0.88 [0.23, 1.00]	0.02 [-0.12, 0.52]
	w	0.38 [0.16, 0.81]	0.71 [0.52, 0.87]	-0.28 [-0.57, 0.22]
RB + P$_{stay}$	H	0.73 [0.64, 0.88]	0.31 [0.06, 0.53]	0.27 [0.15, 0.66]**
	K	8.42 [0.73, 30.42]	2.19 [1.62, 9.09]	2.71 [-2.60, 23.94]
	P_{stay}	0.01 [0.00, 0.05]	0.01 [0.00, 0.13]	0.00 [-0.11, 0.03]

1006 Parameter values are shown as median [IQR]. Difference of parameter values between the two

1007 conditions was tested by a sign test. **p<0.01, ***p<0.001.

1008

1009   Table 3

1010   Summary of fMRI results: error magnitude and past error

Cluster index	#Voxels	Region	Peak t	Peak x	Peak y	Peak z
Error magnitude: noisy versus unstable						
1	21032	R Precuneus	5.22	16	-56	12
		R Angular gyrus	5.17	44	-70	32
		L Precuneus	5.08	-18	-58	20
		Occipital pole	5.07	2	-98	-2
		L Superior parietal lobule	4.91	-10	-66	48
		R Occipital cortex	4.69	26	-76	18
		L Occipital cortex	4.54	-38	-86	26
		R Superior parietal lobule	4.44	44	-44	54
		Posterior cingulate cortex	4.43	2	-46	20
Past error on current error magnitude of 1 or 2: noisy versus unstable						
1	1881	Posterior cingulate cortex	4.79	12	-24	52
		R Superior parietal lobule	4.04	32	-38	54
		R Precuneus	3.58	6	-54	70
		L Superior parietal lobule	3.54	-16	-54	62
Conjunction: Error magnitude & Past error on current error magnitude of 1 or 2						
1	304	R Superior parietal lobule	3.41	38	-40	52
2	103	R Precuneus	3.02	2	-58	70
3	81	L Superior parietal lobule	3.23	-18	-56	72

1011

1012   Table 4

1013   Summary of fMRI results: behavior change

Cluster index	#Voxels	Region	Peak t	Peak x	Peak y	Peak z
Switch versus stay on error magnitude of 1 or 2 in the noisy condition						
1	12042	Middle cingulate cortex	4.35	14	-8	30
		R Insula	4.33	38	4	2
		Medial orbitofrontal cortex	4.24	-4	50	-10
		R Frontal pole	4.11	40	46	0
		R Inferior frontal gyrus	4.11	48	26	10
		L Frontal pole	4.01	-24	52	-2
		Dorsomedial frontal cortex	3.96	0	26	34
		Posterior cingulate cortex	3.93	2	-28	50
		R Primary motor cortex	3.91	48	-6	50
		Anterior cingulate cortex	3.51	0	48	20
2	3134	L Premotor cortex	4.43	-62	2	24
		L Superior temporal gyrus	4.28	-50	-32	12
		L Inferior frontal junction	3.72	-38	4	28
		L Postcentral gyrus	3.61	-50	-26	44

1014