1   Distinct neural encoding of context-dependent error signals and context-dependent changes in

2   behavior during adaptive learning

Chang-Hao Kao[1], Sangil Lee[1], Joshua I. Gold[2], Joseph W. Kable[1]

[1]Department of Psychology, University of Pennsylvania, Philadelphia, PA 19104, USA

[2]Department of Neuroscience, University of Pennsylvania, Philadelphia, PA 19104, USA

Corresponding authors:

Chang-Hao Kao: chakao@sas.upenn.edu

Joseph W. Kable: kable@psych.upenn.edu

Abstract

Learning effectively from errors requires using them in a context-dependent manner, for example

adjusting to errors that result from unpredicted environmental changes but ignoring errors that

result from environmental stochasticity. Where and how the brain represents errors in a context-

dependent manner and uses them to guide behavior are not well understood. We imaged the

brains of human participants performing a predictive-inference task with two conditions that had

different sources of errors. Their performance was sensitive to this difference, including more

choice switches after fundamental changes versus stochastic fluctuations in reward contingencies.

Using multi-voxel pattern classification, we identified context-dependent representations of error

magnitude and past errors in posterior parietal cortex. These representations were distinct from

representations of the resulting context-dependent behavioral adjustments in dorsomedial frontal,

anterior cingulate, and orbitofrontal cortex. The results provide new insights into human brain

that represent and use errors in a context-dependent manner to support adaptive behavior.

Introduction

Errors often drive adaptive adjustments in beliefs that inform behaviors that maximize

positive outcomes and minimize negative ones (Sutton & Barto, 1998). A major challenge to

error-driven learning in uncertain and dynamic environments is that errors can arise from

different sources that have different implications for learning. For example, a bad experience at a

restaurant that recently hired a new chef might lead you to update your belief about the quality of

the restaurant, whereas a similar experience at a well-known restaurant with a chef that has long

been your favorite might be written off as a one-time bad night. That is, the same errors should

be interpreted differently in different contexts. In general, errors that represent fundamental

changes in the environment or that occur during periods of uncertainty should probably lead you

to update your beliefs and change your behavior, whereas those that result from environmental

stochasticity are likely better ignored (d'Acremont & Bossaerts, 2016; Li, Nassar, Kable, & Gold,

2019; Nassar, Bruckner, & Frank, 2019; O'Reilly et al., 2013).

Neural representations of key features of these kinds of dynamic, error-driven learning

processes have been identified in several brain regions. For example, several studies focused on

variables derived from normative models that describe the degree to which individuals should

dynamically adjust their beliefs in response to error feedback under different task conditions,

including the probability that a fundamental change in the environment just occurred (change-

point probability, or CPP, which is a form of surprise) and the reducible uncertainty associated

with estimates of environmental features (relative uncertainty, or RU). Correlates of these

variables have been identified in dorsomedial frontal (DMFC) and dorsolateral prefrontal

(DLPFC) cortex and medial and lateral posterior parietal cortex (PPC) (Behrens, Woolrich,

Walton, & Rushworth, 2007; McGuire, Nassar, Gold, & Kable, 2014; Nassar, McGuire, Ritz, &

Kable, 2019). These and other studies also suggest specific roles for these different brain regions

in error-driving learning, including representations of surprise induced by either state changes or

outliers (irrelevant to state changes) in the PPC that suggest a role in error monitoring (Nassar,

Bruckner, et al., 2019; O'Reilly et al., 2013), and representations of variables more closely

related to belief and behavior updating in the prefrontal cortex (PFC) (McGuire et al., 2014;

O'Reilly et al., 2013). However, these previous studies, which typically used continuous rather

than discrete feedback, were not designed to identify neural signals related to a key aspect of

flexible learning in uncertain and dynamic environments: responding to the same exact errors
differently in different contexts.

To identify such context-dependent neural responses to errors, we adapted a paradigm
from our previous single-unit recording study (Li et al., 2019). In this paradigm, we generated
two different dynamic environments by varying the amount of noise and the frequency that
change-points occur (i.e., hazard rate; Behrens et al., 2007; Glaze, Kable, & Gold, 2015; Nassar
et al., 2012; Nassar, Wilson, Heasly, & Gold, 2010). In the unstable environment, noise was
absent and the hazard rate was high, and thus errors unambiguously signaled a change in state. In
the high-noise environment, noise was high and the hazard rate was low, and thus small errors
were ambiguous and could indicate either a change in state or noise. Thus, effective learning
requires treating errors in the two conditions differently, including adjusting immediately to
errors in the unstable environment but using the size of errors and recent error history as cues
aid interpretation of ambiguous errors in the high-noise condition.

In our previous study, we found many single neurons in the anterior cingulate cortex
(ACC) or posterior cingulate cortex (PCC) that responded to errors or the current context, but we
found little evidence that single neurons in these regions combined this information in a context-
dependent manner to discriminate the source of errors or drive behavior. In the current study, we
used whole-brain fMRI and multi-voxel pattern classification to identify context-dependent
neural responses to errors and activity predictive of context-dependent behavioral updating in the
human brain. The results show context-dependent encoding of error magnitude and past errors in
PPC and encoding of behavioral shifts in a large array of frontal regions including ACC, DMFC,
DLPFC and orbitofrontal cortex (OFC), which provide new insights into the distinct roles these
brain regions play in representing and using, respectively, errors in a context-dependent manner
to guide adaptive behavior.

Results

Sixteen human participants performed a predictive-inference task (Figure 1A) while
fMRI was used to measure their blood-oxygenation-level-dependent (BOLD) brain activity. The
task required them to predict the location of a single rewarded target from a circular array of ten
targets. The location of the rewarded target was sampled from a distribution based on the
location of the current best target and the noise level in the current condition. In addition, the

location of the best target could change according to a particular, fixed hazard rate (H). Two

conditions with different noise levels and hazard rates were conducted in separate runs. In the

high-noise condition (Figure 1B–C), the rewarded target would appear in one of the five

locations relative to the location of the current best target, and the hazard rate was low ($H = 0.02$).

In the unstable condition (Figure 1D–E), the rewarded target always appeared at the location of

the best target, and the hazard rate was high ($H = 0.35$). On each trial, participants made a

prediction by looking at a particular target, and then were given explicit, visual feedback about

their chosen target and the rewarded target. Effective performance required them to use this

feedback in a flexible and context-dependent manner, including typically ignoring small errors in

the high-noise condition but responding to small errors in the unstable condition by updating

their beliefs about the best-target location.

Behavior

Nearly all of the participants' choice patterns were consistent with a flexible, context-

dependent learning process (closed symbols in Figure 2). On average, they learned the location

of the best target after a change in its location more quickly and reliably in the unstable versus

high-noise condition (Figure 2A). This flexible learning process had two key signatures. First,

target switches (i.e., predicting a different target than on the previous trial) tended to follow

errors of any magnitude in the unstable condition but only errors of high magnitude (i.e., when

the chosen target was 3, 4, or 5 targets away from the rewarded target) in the high-noise

condition (sign test for H_0: equal probability of switching for the two conditions; error magnitude

of 1: median = -0.35, interquartile range (IQR) = [-0.62, -0.25], $p<0.001$; error magnitude of 2:

median = -0.30, IQR = [-0.70, -0.11], $p<0.001$; Figure 2B–C). Second, target switches depended

on error history only for low-magnitude errors (i.e., when the chosen target was 1 or 2 targets

away from the rewarded target) in the high-noise condition but not otherwise (sign test for H_0:

switching was unaffected when recent history contained fewer errors; error magnitude of 1:

median = -0.29, IQR = [-0.42, -0.10], $p=0.004$; error magnitude of 2: median = -0.25, IQR = [-

0.38, -0.14], $p<0.001$; Figure 2D–F).

We accounted for these behavioral patterns with a reduced Bayesian model that is similar

to ones we have used previously to model belief updating in a dynamic environment (open

symbols in Figure 2; Tables 1 and 2). According to this model, the decision-maker's trial-by-trial

choices are governed by ongoing estimates of the probability that the best target changed

(change-point probability, or CPP) and reducible uncertainty about the best target's location

(relative uncertainty, or RU). Both quantities are influenced by the two free parameters in the

model, subjective hazard rate and noise level, which were fitted separately in each condition for

each participant. As expected, the fitted hazard rates were higher in the unstable condition than

in the high-noise condition, although both tended to be higher than the objective values, as we

have observed previously (Nassar et al., 2010). The fitted noise estimates were not reliably

different between the high-noise versus unstable condition (Table 2).

In the reduced Bayesian model, both CPP and RU contribute to processing errors in a

context-dependent manner. CPP increases as the current error magnitude increases and achieves

high values more quickly in the unstable condition because of the higher hazard rate (Figure 3A).

These dynamics lead to a greater probability of switching targets after smaller errors in the

unstable condition. RU increases on the next trial after the participant makes an error and does so

more in the high-noise condition because of the lower hazard rate (Figure 3B). These dynamics

lead to a greater probability of target switches when the last trial was an error, which is most

prominent for small errors in the high noise condition. Thus, CPP and RU each account for one

of the two key signatures of context-dependent learning that we identified in participants'

behavior, with CPP driving a context-dependent influence of error magnitude and RU driving a

context-dependent influence of error history on target switches (Figure 3C).

We also tested several alternative models but they did not provide as parsimonious

descriptions of the data (Figure 2 – figure supplement 1, and Tables 1 and 2). Notably, an

alternative model that assumed a condition-specific fixed learning rate also assumed errors were

treated differently for the two conditions but did not include trial-by-trial adjustments of learning

rates used by the reduced Bayesian model. Thus, although this model performed better than the

reduced Bayesian model in the unstable condition, it cannot capture participants' behaviors in the

high-noise condition, where dynamically integrating both current and past errors is required for

adapting trial-by-trial behavior. Other hybrid models performed worse than the reduced Bayesian

model under both conditions.

Neural representation of CPP and RU

To compare our current data directly to our previously identified neural representations of
CPP and RU (McGuire et al., 2014), the two key quantities in the reduced Bayesian model, we
conducted univariate analyses of our imaging data using those behaviorally derived variables as
regressors. This comparison also allowed us to better isolate representations of these variables
from those related to visual and motor processing demands that differed considerably for the two
tasks (the other task included a more complex visual scene and used hand, not eye, movements).
Similar to our previous findings, we found activity that was positively correlated with the levels
of CPP and RU across DLPFC and PPC (Figure 3D). We identified these joint neural
representations of CPP and RU in the high-noise condition, because both CPP and RU varied
across trials in this condition, in contrast to the unstable condition in which RU did not vary. The
regions of DLPFC and PPC that were responsive to both CPP and RU were a subset of those
identified as showing this conjunction in our previous study (Figure 3E, Figure 3 – figure
supplement 1).
Because CPP and RU both contribute to responding to errors in a context-dependent
manner, we considered the brain regions that responded to both variables as good candidates for
encoding errors in a context-dependent manner that is linked to subsequent behavioral shifts. In
the following analyses, we aimed to directly identify context-dependent neural representations of
error magnitude and error history, as well as activity that predicts subsequent shifts in behavior,
in these and other brain regions.
169
Context-dependent neural representation of errors
We used multi-voxel pattern analysis (MVPA) to identify error-related neural signals that
were similar and different for the two task conditions. Given the two key signatures of flexible
learning that we identified in behavior, we were especially interested in identifying neural
representations of error magnitude and past errors that were stronger in the high-noise than the
unstable condition.
We found robust, context-dependent representations of the magnitude of the error on the
current trial in PPC. Consistent with the context-dependent behavioral effects, this representation
of error magnitude was stronger in the high-noise than the unstable condition (Figure 4 and
Table 3). Specifically, we could classify correct versus error feedback on the current trial across
almost the entire cortex, in both the unstable and noisy conditions. However, for error trials, we

could classify error magnitude (in three bins: 1, 2, 3+ targets away from the rewarded target)

only for the high-noise condition and most strongly in the lateral and medial parietal cortex and

in the occipital pole. In a parallel set of analyses, we found that univariate activity in PPC also

varied in a context-dependent way, responding more strongly to error magnitude in the high-

noise than the unstable condition (Figure 4 – figure supplement 1).

We also found robust, context-dependent representations of past errors in PPC. These

representations also were stronger in the high-noise than the unstable condition, particularly on

trials for which past errors had the strongest influence on behavior. Specifically, we could

classify correct versus error on the previous trial in PPC for both task conditions (Figure 5). This

classification of past errors depended on the outcome of the current trial. We separated trials

according to whether the current feedback was correct or an error, or whether the error

magnitude provided ambiguous (error magnitudes of 1 or 2) or unambiguous (error magnitudes

of 0 or 3+) feedback in the high-noise condition (Figure 5). We found reliable classifications of

past errors in the lateral and medial parietal cortex in both conditions for correct trials and

unambiguous feedback. Moreover, these representations depended on the current context, and,

consistent with behavioral effects of error history, were stronger for error trials and ambiguous

feedback in the high-noise than in the unstable condition (Table 3). These context-dependent

signals for past errors were not clearly present in univariate activity (Figure 5 – figure

supplement 1). An additional conjunction analysis across MVPA results showed that PPC

uniquely encoded context-dependent error signals for both error magnitude of the current trials

and past errors when the current trial provided ambiguous feedback (Table 3).

Neural prediction of subsequent changes in behavior

Although PPC responds to errors in a context-dependent manner that could be used for

determining behavioral updates, we did not find that activity in this region was predictive of the

participants' future behavior. Instead, we found such predictive activity more anteriorly

throughout the frontal lobe. Specifically, we investigated whether multi-voxel neural patterns

could predict participants' target switches on the subsequent trial. We focused on the trials with

small error magnitudes (1 or 2) in the high-noise condition, because these were the only trial

types that participants consistently exhibited an intermediate probability of switching (20–80%,

Figure 2). We found that activity patterns in widespread regions in OFC, ACC, DMFC, and

DLPFC could predict subsequent stay/switch decisions (Figure 6, Table 4). We did not find any

regions where univariate activity reliably predicted participants' subsequent behavior (Figure 6 –

figure supplement 1).

Discussion

We identified context-dependent neural representations of errors in humans performing a

dynamic learning task. The task required participants to learn in two different dynamic

environments. In the unstable condition (high hazard rate and low noise), errors unambiguously

indicated a change in the state of the environment, and participants reliably updated their

behavior in response to errors. In contrast, in the high-noise condition (low hazard rate and high

noise), small errors were ambiguous, and participants used both the current error magnitude and

recent error history to distinguish between those errors that likely signal change-points and those

likely arising from environmental noise. Using MVPA, we showed complementary roles of PPC

and prefrontal regions (including OFC, ACC, DMFC and DLPFC) in the outcome-monitoring

and action-selection processes underlying these flexible, context-dependent behavioral responses

to errors. Neural patterns in PPC encoded the magnitude of errors and past errors, more strongly

in the high-noise than the unstable condition. These context-dependent neural responses to errors

in PPC were not reliably linked to subsequent changes in behavior. In contrast, neural patterns in

prefrontal regions could predict subsequent changes in behavior (whether participants switch

their choice on the next trial or not) in response to ambiguous errors in the high-noise condition.

Context-dependent behavior adaptation

Consistent with previous studies of ours and others (d'Acremont & Bossaerts, 2016;

McGuire et al., 2014; Nassar, Bruckner, et al., 2019; Nassar et al., 2012; Nassar et al., 2010;

O'Reilly et al., 2013; Purcell & Kiani, 2016), human participants adapted their response to errors

differently in different contexts. In the unstable condition, participants almost always switched

their choice after errors and quickly learned the new state after change-points. In contrast, in the

high-noise condition, participants ignored many errors and only slowly learned the new state

after change-points. In this condition, participants had to distinguish true change-points from

environmental noise, and they used error magnitude and recent error history as a cue for whether

the state had recently changed or not. These flexible and context-dependent responses to errors

could be accounted for by a reduced Bayesian model (McGuire et al., 2014; Nassar et al., 2012;

Nassar et al., 2010). In this model, beliefs and behavior are dynamically updated according to

two key quantities, CPP and RU.

Neural representation of change-point probability and relative uncertainty

248   Replicating our previous work (McGuire et al., 2014), we identified neural activity

correlated with both CPP and RU in PPC and DLPFC. This replication shows the robustness of

these neural representations of CPP and RU across experimental designs that differ dramatically

in their visual stimuli and motor demands, yet share the need to learn in dynamic environments

with similar statistics. In addition, given that CPP and RU account for the context-dependent

behavioral responses to error magnitude and recent error history, respectively, the regions

responding to both CPP and RU are strong candidates for neural representations of errors and

subsequent behavioral updates that are context dependent.

Context-dependent neural representation of errors

258   Advancing beyond previous work, we identified context-dependent encoding of errors in

neural activity in the PPC. Mirroring the context dependence of behavior, the multivariate neural

pattern in PPC encoded current error magnitude more strongly in the high-noise condition than in

the unstable condition and encoded past errors more strongly on trials that provided ambiguous

feedback in the high-noise condition. That is, the multivariate pattern in PPC could distinguish

between the same exact error stimuli depending on the context. These same regions of PPC have

been shown previously to represent errors, error magnitudes, surprise and salience (Fischer &

Ullsperger, 2013; Gläscher, Daw, Dayan, & O'Doherty, 2010; McGuire et al., 2014; Nassar,

Bruckner, et al., 2019; Nassar, McGuire, et al., 2019; O'Reilly et al., 2013; Payzan-LeNestour,

Dunne, Bossaerts, & O'Doherty, 2013). In addition, these regions have been shown to integrate

recent outcome or stimulus history in human fMRI studies (FitzGerald, Moran, Friston, & Dolan,

2015; Furl & Averbeck, 2011) and in animal single neuron recording studies (Akrami, Kopec,

Diamond, & Brody, 2018; Brody & Hanks, 2016; Hanks et al., 2015; Hayden, Nair, McCoy, &

Platt, 2008; Hwang, Dahlen, Mukundan, & Komiyama, 2017). Our results extend on these past

findings by demonstrating that the neural encoding of errors in PPC is modulated across different

contexts in precisely the manner that could drive adaptive behavior.

These whole-brain fMRI results complement our previous results recording from single
neurons in ACC and PCC in the same task (Li et al., 2019). In that study, we identified single
neurons in both ACC and PCC that encoded information relevant to interpreting errors, such as
the magnitude of the error or the current context. However, we did not find any neurons that
combined this information in a manner that could drive adaptive behavioral adjustments. Our
whole-brain fMRI results suggest that PPC would be a good place to look for context-dependent
error representations in single neurons, including a region of medial parietal cortex slightly
dorsal to the PCC area we recorded from previously.
282
Neural representations of context-dependent behavioral updating
Also advancing beyond previous work, we identified neural activity predictive of
context-dependent behavioral updates in DLPFC and across the frontal cortex. In the high-noise
condition, small errors provided ambiguous feedback that could reflect either a change in state or
environmental noise. Accordingly, after small errors in the high-noise condition, participants
exhibited variability across trials in whether they switched from their current choice on the
subsequent trial or not. In these ambiguous situations, the multivariate neural pattern across
frontal regions, including OFC, ACC, DMFC and DLPFC, predicted whether people switched or
stayed on the subsequent trial. That is, the multivariate pattern in frontal regions could
distinguish whether people would update their behavior or not in response to the same exact
error stimuli. These results suggest a dissociation between PPC regions that monitor error
information in a context-dependent manner and frontal regions that may use this information to
update beliefs and select subsequent actions.
This ability to decode subsequent choices might arise from different kinds of
representations in different areas of frontal cortex. Activity in DMFC reflects the extent of belief
updating in dynamic environments (Behrens et al., 2007; Hampton, Bossaerts, & O'Doherty,
2006; McGuire et al., 2014; O'Reilly et al., 2013), and the multivariate pattern in this region can
decode subsequent switching versus staying in a reversal learning task (Hampton & O'Doherty,
2007). OFC and DMFC encode the identity of the current latent state in a mental model of the
task environment and neural representations in these regions changes as the state changes (Chan,
Niv, & Norman, 2016; Hunt et al., 2018; Karlsson, Tervo, & Karpova, 2012; Nassar, McGuire,
et al., 2019; Schuck, Cai, Wilson, & Niv, 2016; Wilson, Takahashi, Schoenbaum, & Niv, 2014).

Neural activity in frontopolar cortex (Daw, O'Doherty, Dayan, Seymour, & Dolan, 2006) and

DMFC (Blanchard & Gershman, 2018; Kolling, Behrens, Mars, & Rushworth, 2012; Kolling et

al., 2016; Muller, Mars, Behrens, & O'Reilly, 2019) increases during exploratory choices, which

occur more frequently during periods of uncertainty about the most beneficial option. In a recent

study, we identified distinct representations of latent states, uncertainty, and behavioral policy in

distinct areas of frontal cortex during learning in a dynamic environment (Nassar et al., 2019).

Our results extend these past findings and demonstrate the role of these frontal regions in

adjusting behavior in response to ambiguous errors.

Conclusion

People adapt their behavior in response to errors in a context-dependent manner,

distinguishing between errors that indicate change-points in the environment versus noise. Here

we used MVPA to identify two distinct kinds of neural signals contributing to these adaptive

behavioral adjustments. In PPC, neural patterns encoded error information in a context-

dependent manner, depending on error magnitude and past errors only under conditions where

these were informative of the source of error. In contrast, activity in frontal cortex could predict

subsequent choices that could be based on this information. These findings suggest a broad

distinction between outcome monitoring in parietal regions and action selection in frontal regions

when learning in dynamic and uncertain environments.

Materials and Methods

Participants

All procedures were approved by University of Pennsylvania Internal Review Board. We

analyzed data from sixteen participants (9 female, mean age = 23.5, SD = 4.3, range = 18–33

years) recruited for the current study. One additional participant was excluded from analyses

because of large head movements during MRI scanning (>10% of timepoint-to-timepoint

displacements were >0.5 mm). All participants provided informed consent before the experiment.

Participants received a participation fee of $15, as well as extra incentives based on their

performance (mean = $15.09, SD = $2.26, range = $8.5–17.5).

Task

Participants performed a predictive-inference task during MRI scanning. On each trial,

participants saw a noisy observation sampled from an unobserved state. The participants' goal

was to predict the location of the noisy observation. To perform this task well, however, they

should infer the location of the current state.

In this task (Li et al., 2019), there were 10 targets aligned in a circle on the screen (Figure

1A). At the start of each trial, participants had to fixate a central cross for 0.5 seconds to

initialize the trial. After the cross disappeared, participants could choose one of 10 targets (red)

by looking at it within 1.5 seconds and keeping fixation on the chosen target for 0.3 seconds.

Then, an outcome would be shown for 1 second. During the outcome phase, a green dot

indicated the chosen target. A purple or cyan target indicated the rewarded target, with color

denoting 10 or 20 points of reward value, respectively. At the end of experiment, every 75 points

were converted to $0.25 as participants' extra incentives.

Participants performed this task in two dynamic conditions separated into two different

runs: a high-noise condition and an unstable condition. In the high-noise condition, the rewarded

target could be one of five targets, given the underlying state (Figure 1B). The rewarded target

probabilities for the relative locations ([-2, -1, 0, 1, 2]) of the current state were [0.05, 0.15, 0.6,

0.15, 0.05]. Thus, the location of the current state was most likely rewarded, but nearby targets

could also be rewarded. Occasionally, the state would change its location with a hazard rate of

0.02 (Figure 1C). When a change-point happens, the new state would be selected among the ten

targets based on a uniform distribution. In the unstable condition, there was no noise (Figure 1D).

That is, the location of the state would be always rewarded. However, the state was unstable, as

the hazard rate in this condition was 0.35 (Figure 1E). There were 300 trials in each run.

Behavior analysis

We investigated how participants' used error feedback flexibly across different contexts.

Before the behavioral analysis, we removed two different kinds of trials. First, we removed trials

in which participants did not make a choice within the time limit (Unstable: median number of

trials = 10.5, range = 1–83; High-noise: median = 10, range = 2–88). Second, we also removed

trials in which the location of the chosen target was not on the shortest distance between the

previously chosen and previously rewarded targets (Unstable: median = 3, range = 0–24; High-

noise: median = 17, range = 5–37). These trials implied that participants might have lost track of

the most recently rewarded target and cannot be captured by any of the belief updating models
we tested.

First, we investigated how fast participants learned the location of the current state. For
each condition and participant, we binned trials from trial 0 to trial 20 after change-points. Then,
we calculated the probability of choosing the location of the current state for each bin.

Second, we examined how different magnitudes of errors lead to shifts in behavior. For
each condition and participant, we binned trials based on the current error magnitude (from 0 to
5). Then, for each bin, we calculated the probability that participants switch their choice to
another target on the subsequent trial. We hypothesized participants would have a lower
probability of switching after small error magnitudes (1 or 2) in the high-noise condition than in
the unstable condition since such errors could be due to environment noise in the high-noise
condition but would signal a state change in the unstable condition.

Third, we further investigated how error history influenced participants' behavioral shifts.
Similarly, we binned trials based on the current error magnitude and the error history of the last
three trials. Here, we used four bins of error magnitudes (0, 1, 2, 3+). Based on the outcome of
correct or error on the last three trials, there were 8 types of error history. For each error
magnitude, we calculated the probability of switching for each type of error history. We
hypothesized that participants in the high-noise condition would tend to switch their choice after
small errors more if they had made more errors recently. To test this hypothesis, we ordered the
8 types of error history based on the number of recent errors and calculated the slope of
probability of switching against the order of error history. A negative slope means that
participants tend to switch as they receive more recent errors.
389
390   *Behavior modeling*
391   We fit several different computational models to participants' choices to evaluate which
392   ones could best account for their behavior in the task.
393
394   *Reduced Bayesian (RB) model*
395   Previous studies have shown that a reduced Bayesian model, which approximates the full
396   Bayesian ideal observer, could account well for participants' behavior in dynamic environments

397 similar to the current task (McGuire et al., 2014; Nassar et al., 2012; Nassar et al., 2010). In this
398 model, belief is updated by a delta rule:

400
$$\delta_t = x_t - B_t \tag{1}$$
401
$$B_{t+1} = B_t + \alpha_t \delta_t \tag{2}$$

403 where B_t is the current belief and x_t is the current observation. The new belief (B_{t+1}) is formed
404 by updating the old belief according to the prediction error $(x_t - B_t)$ and a learning rate (α_t).
405 The learning rate controls how much a participant revises their belief based on the prediction
406 error. In this model, the learning rate is adjusted on a trial-by-trial basis according to:

408
$$\alpha_t = \Omega_t + (1 - \Omega_t)\tau_t \tag{3}$$

410 where Ω_t is the change-point probability and τ_t is the relative uncertainty. That is, α_t is high as
411 either Ω_t or τ_t is high. The change-point probability is the relative likelihood that the new
412 observation represents a change-point as opposed to a sample from the currently inferred state
413 (Nassar et al., 2010):

415
$$\Omega_t = \frac{U(x_t|1,10)H}{U(x_t|1,10)H + f_p(x_t|\gamma_t, B_t)(1-H)} \tag{4}$$

417 where H is the hazard rate, $U(x_t|1,10)$ is the probability of outcome derived from a uniform
418 distribution, and $f_p(x_t|\gamma_t, B_t)$ is the probability of outcome derived from the current predictive
419 distribution. That is, $U(x_t|1,10)$ reflects the probability of outcome when a change-point has
420 occurred while $f_p(x_t|\gamma_t, B_t)$ reflects the probability of outcome when the state has not changed.
421 The predictive distribution is an integration of the state distribution and the noise distribution:

423
$$f_p(X|\gamma_t, B_t) = C \times P(X|B_t)^{\gamma_t} \times P(X|B_t) \tag{5}$$

where X is a random variable determining the locations of target, $P(X|B_t)$ is the noise
distribution in the current condition, $P(X|B_t)^{\gamma_t}$ is the state distribution, γ_t is the expected run

length after the change-point, and C is a normalizing constant to make the sum of probabilities in

the predictive distribution equal one. Thus, the uncertainty of this predictive distribution comes

from two sources: the uncertainty of the state distribution (σ_S^2) and the uncertainty of the noise

distribution (σ_N^2). The uncertainty of the state distribution would decrease as the expected run

length increases.

432   The expected run length reflects the expected number of trials that a state remains stable,

433 and thus is updated on each trial based on the change-point probability (Nassar et al., 2010):

435
$$\gamma_{t+1} = (\gamma_t + 1)(1 - \Omega_t) + \Omega_t \tag{6}$$

where the expected run length is a weighted average conditional on the change-point probability.

If no change-point occurs (i.e., change-point probability is low), the expected run length would

increase, leading the uncertainty of the state distribution to decrease. That is, as more

observations from the current state are received, participants are more certain about the location

of the current state. However, if the change-point probability is high, which signals a likely

change in the state, the expected run length would be reset to 1. Thus, the uncertainty of the state

distribution becomes large. Participants are more uncertain about the current state after a change-

point.

445   The other factor influencing the learning rate is the relative uncertainty, which is the

446 uncertainty regarding the current state relative to the irreducible uncertainty or noise (McGuire et

447 al., 2014; Nassar et al., 2012):

449
$$\tau_{t+1} = \frac{\Omega_t \sigma_N^2 + (1-\Omega_t)\sigma_S^2 + \Omega_t(1-\Omega_t)[\delta_t(1-\tau_t)]^2}{\Omega_t \sigma_N^2 + (1-\Omega_t)\sigma_S^2 + \Omega_t(1-\Omega_t)[\delta_t(1-\tau_t)]^2 + \sigma_N^2} \tag{7}$$

The three terms in the numerator contribute to the uncertainty about the current state. The first

term reflects the uncertainty conditional on the change-point distribution; the second term

reflects the uncertainty conditional on the non-change-point distribution; and the third term

reflects the uncertainty due to the difference between the two distributions. The denominator

shows the total variance which is the summation of the uncertainty about the current state and the

noise. As more precise observations are received in a given state, this relative uncertainty would

decrease.

During model fitting, the noise distribution was approximated by the von Mises

distribution, which is a circular Gaussian distribution:

461
$$P(x_t|B_t, K) = \frac{e^{K\cos(x_t - B_t)}}{\sum_{i=1}^{10} e^{K\cos(x_i - B_t)}} \qquad (8)$$

where B_t is the location of the current belief, x_i is the location of target, and K controls the

uncertainty of this distribution. When K is 0, this is a uniform distribution. As K increases, the

uncertainty decreases. The denominator is used as a normalization term to make sure the sum of

all the probabilities equals one. Thus, there are two free parameters in this model: hazard rate (H)

and noise level (K). The range of hazard rate is between 0 and 1 and the noise level is greater

than or equal to zero.

Fixed learning rate (fixedLR) model

We also consider an alternative model in which participants used a fixed learning rate in

each of the two dynamic conditions. That is, the learning rate is the same over all trials in a

condition. This model has one free parameter, the fixed learning rate (α_{fixed}), for each condition

(Eq. 2). The fixed learning rate is between 0 and 1.

Hybrid of RB model and fixedLR model

Furthermore, we consider a hybrid model, in which the learning rate on each trial is a

mixture of the learning rates from the RB model and the fixedLR model:

480
$$\alpha_t = w\alpha_{RB} + (1 - w)\alpha_{fixed} \qquad (9)$$

where α_{RB} is the learning rate from the RB model and is varied trial by trial according to Ω_t and

τ_t, α_{fixed} is the learning rate from the fixedLR model and w reflects the weight to integrate these

two learning rates. In this model, there are four free parameters: hazard rate, noise level, fixed

learning rate and weight. The weight is between 0 and 1.

Hybrid of RB model and P$_{stay}$

Finally, we consider a hybrid model, which combines the RB model with a fixed

tendency to stay on the current target regardless of the current observation. Such a fixed

tendency to stay was observed in monkeys in our previous study (Li et al., 2019). Here the belief

is updated by:

$$B_{t+1} = B_t + [(1 - P_{stay}) \times \alpha_t(X_t - B_t) + P_{stay} \times 0] \qquad (10)$$

where P_{stay} is the probability that participants stay on the current target. This model has three

free parameters: hazard rate, noise level and the probability of stay. The probability of stay is

between 0 and 1.

Model fitting and comparison

Each model was fitted within each participant and within each condition separately.

Optimal parameters were estimated by minimizing the mean of the squared error (MSE) between

a participant's prediction and the model prediction.

$$MSE = \frac{\sum_{t=1}^{n}(B_t - \widehat{B_t})^2}{n} \qquad (11)$$

where t is the trial, n is the total number of included trials, B_t is a participant's prediction on trial

$t,$ and $\widehat{B_t}$ is the model prediction on trial t.

Since each model used a different number of parameters and each participant had a

different number of included trials, we used Bayesian Information Criterion (BIC) to compare

the performance of different models:

$$BIC = n \ln(MSE) + k \ln(n) \qquad (12)$$

where n is the number of included trials and k is the number of free parameters in a model. A

model with lower BIC performs better.

MRI Data Acquisition and Preprocessing

We acquired MRI data on a 3T Siemens Prisma with a 64-channel head coil. Before the

task, we acquired a T1-weighted MPRAGE structural image (0.9375 X 0.9375 X 1 mm voxels,

192 X 256 matrix, 160 axial slices, TI = 1,100 ms, TR = 1,810 ms, TE = 3.45 ms, flip angle = $9^{°}$).

During each run of the task, we acquired functional data using a multiband gradient echo-planar

imaging (EPI) sequence (1.9592 X 1.9592 X 2 mm voxels, 98 X 98 matrix, 72 axial slices tilted

$30^{°}$ from the AC-PC plane, TR = 1,500 ms, TE = 30 ms, flip angle = $45^{°}$, multiband factor = 4).

The scanning time (mean = 24.14 minutes, SD = 1.47, range = 21.85-30.00) for each run was

dependent on the participants' pace. After the task, fieldmap images (TR = 1,270 ms, TE = 5 ms

and 7.46 ms, flip angle = $60^{°}$) were acquired.

Data were preprocessed using FMRIB's Software Library (FSL) (Jenkinson, Beckmann,

Behrens, Woolrich, & Smith, 2012; Smith et al., 2004). Functional data were motion corrected

using MCFLIRT (Jenkinson, Bannister, Brady, & Smith, 2002), high-pass filtered with a

Gaussian-weighted least square straight line fitting of $\sigma = 50\ s$, undistorted and warped to MNI

space. To map the data to MNI space, boundary-based registration was applied to align the

functional data to the structural image (Greve & Fischl, 2009) and fieldmap-based geometric

undistortion was also applied. In addition, the structural image was normalized to the MNI space

(FLIRT). Then, these two transformations were applied to the functional data.

fMRI analysis: univariate activity correlated with CPP and RU

Using similar procedures to our previous study (McGuire et al., 2014), we examined the

effects of CPP and RU on univariate activity. Both the current study and the previous study

investigate the computational process and neural mechanisms during learning in dynamic

environments. The underlying task structures (which involved noisy observations and sudden

change-points) are similar between the two studies, but the two studies used very different visual

stimuli and motor demands. We specifically focused on the high-noise condition in the current

study since it was more similar to the underlying structure, in terms of noisy observations and

hazard rate of change-points, to our previous study.

We investigated the factors of CPP, RU, reward values and residual updates. The trial-by-

trial CPP and RU were estimated from the RB model with subjective estimates of hazard rate and

noise. The residual update reflects the difference between the participants' update and the

predicted update, and is estimated from a behavioral regression model in a similar manner as our

previous study:

$$Update_t = \beta_0 + \beta_1 \delta_t + \beta_2 \delta_t \Omega_t + \beta_3 \delta_t (1 - \Omega_t)\tau_t + \beta_4 \delta_t Reward + \varepsilon \qquad (13)$$

where $Update_t$ is the difference between B_{t+1} and B_t, δ_t is the error magnitude, both Ω_t and τ_t

were derived from the RB model with subjective estimates of hazard rate and noise, and the

reward value indicated whether a correct response earned a large or a small value on that trial.

Then, a general linear model using these four factors was implemented on the neural data.

Here we further smoothed the preprocessed fMRI data with a 6 mm FWHM Gaussian kernel. We

included several trial-by-trial regressors of interest in the GLM: onsets of outcome, CPP, RU,

reward value, and residual update. Six motion parameters were also included as confounds. For

statistical testing, we implemented one-sample cluster-mass permutation tests with 5,000

iterations. The cluster-forming threshold was uncorrected voxel $p<0.005$. Statistical testing was

then based on the corrected cluster p value. For the conjunction analyses, we used the same

procedure as the previous study (McGuire et al., 2014). We kept regions that passed the

corrected threshold and showed the same sign of effects. For these conjunction tests, we only

kept regions that have at least 10 contiguous voxels.

Since the number of participants was fewer in this study (n=16) than in the previous

study (n=32), we might have lower power to detect effects in the whole-brain analyses. Thus, we

also implemented ROI analyses. We selected seven ROIs that showed the conjunction effects of

CPP, RU and reward value in the previous study (McGuire et al., 2014) and tested the effects of

CPP and RU in these ROIs.

fMRI analysis: multi-voxel pattern analysis (MVPA)

We implemented MVPA to understand the neural representation of error signals and

subsequent choices. Our analyses focus on the multi-voxel pattern when participants received an

outcome. Before implementing MVPA, we estimated trial-by-trial beta values using the

unsmoothed preprocessed fMRI data. We used the general linear model (GLM) to estimate the

beta weights for each trial (Mumford, Turner, Ashby, & Poldrack, 2012). In each GLM, the first

regressor is the trial of interest and the second combines the rest of trials in the same condition.

These two regressors were then convolved with a gamma hemodynamic response function. In

addition, six motion parameters were included as control regressors. We repeated this process

(one GLM per trial) to estimate trial-by-trial beta values for all the trials in the two conditions.

We then used these beta values as observations for MVPA. A whole-brain searchlight was

implemented (Kriegeskorte, Goebel, & Bandettini, 2006). In each searchlight, a sphere with the

diameter of 5 voxels (10 mm) was formed, and the pattern of activity across the voxels within the

sphere were used to run MVPA.

A support vector machine (SVM) with a linear kernel was used to decode different error

signals and choices in our whole-brain searchlight analysis. We implemented SVM through the

LIBSVM toolbox (Chang & Lin, 2011). To avoid overfitting, we used 3-fold cross-validation,

with one fold used as testing data and the other two as training data. Training data were used to

train the classifier and then this classifier was used on testing data to examine the classification

accuracy. In linear SVM, a free parameter c regularizes the trade-off between decreasing training

error and increasing generalization. Thus, during the training of classifier, the training data were

further split into 3-folds to select the optimal value of the parameter c through cross-validation.

We pick the optimal value for c from [0.001, 0.01, 0.1, 1, 10, 100, 1000] and this optimal

parameter should maximize the cross-validation accuracy. Then, we used the optimal parameter

c to train the model again based on the entire training data and calculated the classification

accuracy on the testing data. We repeated this procedure with each of the three folds held out as

testing data and calculated the average of the classification accuracy. To minimized the influence

of different number of trials for each category on the classification accuracy, we used balanced

accuracy.

We first examined how the multi-voxel neural pattern on the current trial could

discriminate correct versus error on the current trial or error magnitudes on the current error trial.

For the analysis of correct versus error, the baseline accuracy is 50%. For the analysis of error

magnitudes, we split trials into three bins of error magnitude: 1, 2, and 3+. Thus, the baseline

accuracy is 33%.

We next examined how the multi-voxel neural pattern on the current trial could

discriminate whether the previous trial was an error or not. We also investigated how the

classification of past errors differs conditional on the type of the current trial. We classified trial

t-1 as correct or error separately for four different types of current trials: correct trials, error trials,

unambiguous feedback trials and ambiguous feedback trials. Unambiguous feedback trials were

trials with error magnitudes of 0 or 3+, while ambiguous feedback trials were trials with error

magnitudes of 1 or 2, in which participants would be uncertain about the change of the state in

the high-noise condition.

Lastly, we examined how the multi-voxel neural pattern on the current trial could classify

the choice on the next trial. In this analysis, we focused only on the trials with error magnitudes

of 1 or 2 in the high-noise condition, since only under these conditions were participants

similarly likely to switch versus stay. For these trials, we examined whether the multi-voxel

pattern on the current trial predicted whether the participant stayed or switched on the next trial.

The baseline accuracy was 50%.

After obtaining the classification accuracy for each participant, we subtracted the baseline

accuracy from the classification accuracy. Before conducting a group-level test, we smoothed

these individual accuracy maps with a 6 mm FWHM Gaussian kernel. For statistical testing, one-

sample cluster-mass permutation was applied with 5,000 iterations. We used uncorrected voxel

$p<0.005$ to form a cluster and estimated the corrected cluster p value for each cluster. For the

conjunction analyses, we used the same procedure described above.

Acknowledgments

This work was supported by grants from National Institute of Mental Health (R01-MH098899 to

J.I.G. and J.W.K.) and National Science Foundation (1533623 to J.I.G. and J.W.K.). We thank

Yin Li for valuable comments; M. Kathleen Caulfield for fMRI scanning.

Competing interests

The authors declare no competing interests.

References

Akrami, A., Kopec, C. D., Diamond, M. E., & Brody, C. D. (2018). Posterior parietal cortex
represents sensory history and mediates its effects on behaviour. *Nature, 554*, 368.
doi:10.1038/nature25510
Behrens, T. E. J., Woolrich, M. W., Walton, M. E., & Rushworth, M. F. S. (2007). Learning the
value of information in an uncertain world. *Nat Neurosci, 10*(9), 1214-1221.
doi:10.1038/nn1954
Blanchard, T. C., & Gershman, S. J. (2018). Pure correlates of exploration and exploitation in the
human brain. *Cognitive, Affective, & Behavioral Neuroscience, 18*(1), 117-126.
doi:10.3758/s13415-017-0556-2
Brody, C. D., & Hanks, T. D. (2016). Neural underpinnings of the evidence accumulator.
Current Opinion in Neurobiology, 37, 149-157. doi:10.1016/j.conb.2016.01.003
Chan, S. C. Y., Niv, Y., & Norman, K. A. (2016). A Probability Distribution over Latent Causes,
in the Orbitofrontal Cortex. *The Journal of Neuroscience, 36*(30), 7817-7828.
doi:10.1523/jneurosci.0659-16.2016
Chang, C.-C., & Lin, C.-J. (2011). LIBSVM: a library for support vector machines. *ACM
transactions on intelligent systems and technology, 2*(3), 27.
doi:10.1145/1961189.1961199
d'Acremont, M., & Bossaerts, P. (2016). Neural Mechanisms Behind Identification of
Leptokurtic Noise and Adaptive Behavioral Response. *Cerebral Cortex, 26*(4), 1818-
1830. doi:10.1093/cercor/bhw013
Daw, N. D., O'Doherty, J. P., Dayan, P., Seymour, B., & Dolan, R. J. (2006). Cortical substrates
for exploratory decisions in humans. *Nature, 441*(7095), 876-879.
doi:10.1038/nature04766
Fischer, Adrian G., & Ullsperger, M. (2013). Real and Fictive Outcomes Are Processed
Differently but Converge on a Common Adaptive Mechanism. *Neuron, 79*(6), 1243-
1255. doi:10.1016/j.neuron.2013.07.006
FitzGerald, T. H. B., Moran, R. J., Friston, K. J., & Dolan, R. J. (2015). Precision and neuronal
dynamics in the human posterior parietal cortex during evidence accumulation.
NeuroImage, 107, 219-228. doi:10.1016/j.neuroimage.2014.12.015
Furl, N., & Averbeck, B. B. (2011). Parietal Cortex and Insula Relate to Evidence Seeking
Relevant to Reward-Related Decisions. *The Journal of Neuroscience, 31*(48), 17572-
17582. doi:10.1523/jneurosci.4236-11.2011
Gläscher, J., Daw, N., Dayan, P., & O'Doherty, J. P. (2010). States versus Rewards: Dissociable
Neural Prediction Error Signals Underlying Model-Based and Model-Free Reinforcement
Learning. *Neuron, 66*(4), 585-595. doi:10.1016/j.neuron.2010.04.016
Glaze, C. M., Kable, J. W., & Gold, J. I. (2015). Normative evidence accumulation in
unpredictable environments. *eLife, 4*, e08825. doi:10.7554/eLife.08825
Greve, D. N., & Fischl, B. (2009). Accurate and robust brain image alignment using boundary-
based registration. *NeuroImage, 48*(1), 63-72. doi:10.1016/j.neuroimage.2009.06.060
Hampton, A. N., Bossaerts, P., & O'Doherty, J. P. (2006). The Role of the Ventromedial
Prefrontal Cortex in Abstract State-Based Inference during Decision Making in Humans.
The Journal of Neuroscience, 26(32), 8360-8367. doi:10.1523/jneurosci.1010-06.2006
Hampton, A. N., & O'Doherty, J. P. (2007). Decoding the neural substrates of reward-related
decision making with functional MRI. *Proceedings of the National Academy of Sciences,
104*(4), 1377-1382. doi:10.1073/pnas.0606297104

Hanks, T. D., Kopec, C. D., Brunton, B. W., Duan, C. A., Erlich, J. C., & Brody, C. D. (2015).
Distinct relationships of parietal and prefrontal cortices to evidence accumulation.
Nature, 520, 220. doi:10.1038/nature14066

Hayden, B. Y., Nair, A. C., McCoy, A. N., & Platt, M. L. (2008). Posterior Cingulate Cortex
Mediates Outcome-Contingent Allocation of Behavior. *Neuron, 60*(1), 19-25.
doi:10.1016/j.neuron.2008.09.012

Hunt, L. T., Malalasekera, W. M. N., de Berker, A. O., Miranda, B., Farmer, S. F., Behrens, T.
E. J., & Kennerley, S. W. (2018). Triple dissociation of attention and decision
computations across prefrontal cortex. *Nature Neuroscience, 21*(10), 1471-1481.
doi:10.1038/s41593-018-0239-5

Hwang, E. J., Dahlen, J. E., Mukundan, M., & Komiyama, T. (2017). History-based action
selection bias in posterior parietal cortex. *Nature Communications, 8*(1), 1242.
doi:10.1038/s41467-017-01356-z

Jenkinson, M., Bannister, P., Brady, M., & Smith, S. (2002). Improved Optimization for the
Robust and Accurate Linear Registration and Motion Correction of Brain Images.
NeuroImage, 17(2), 825-841. doi:10.1006/nimg.2002.1132

Jenkinson, M., Beckmann, C. F., Behrens, T. E., Woolrich, M. W., & Smith, S. M. (2012). FSL.
NeuroImage, 62(2), 782-790. doi:10.1016/j.neuroimage.2011.09.015

Karlsson, M. P., Tervo, D. G. R., & Karpova, A. Y. (2012). Network Resets in Medial Prefrontal
Cortex Mark the Onset of Behavioral Uncertainty. *Science, 338*(6103), 135-139.
doi:10.1126/science.1226518

Kolling, N., Behrens, T. E. J., Mars, R. B., & Rushworth, M. F. S. (2012). Neural Mechanisms of
Foraging. *Science, 336*(6077), 95-98. doi:10.1126/science.1216930

Kolling, N., Wittmann, M. K., Behrens, T. E. J., Boorman, E. D., Mars, R. B., & Rushworth, M.
F. S. (2016). Value, search, persistence and model updating in anterior cingulate cortex.
Nature Neuroscience, 19, 1280. doi:10.1038/nn.4382

Kriegeskorte, N., Goebel, R., & Bandettini, P. (2006). Information-based functional brain
mapping. *Proceedings of the National Academy of Sciences of the United States of
America, 103*(10), 3863-3868. doi:10.1073/pnas.0600244103

Li, Y. S., Nassar, M. R., Kable, J. W., & Gold, J. I. (2019). Individual neurons in the cingulate
cortex encode action monitoring, not selection, during adaptive decision-making. *The
Journal of Neuroscience*, 0159-0119. doi:10.1523/jneurosci.0159-19.2019

McGuire, J. T., Nassar, M. R., Gold, J. I., & Kable, J. W. (2014). Functionally Dissociable
Influences on Learning Rate in a Dynamic Environment. *Neuron, 84*(4), 870-881.
doi:10.1016/j.neuron.2014.10.013

Muller, T. H., Mars, R. B., Behrens, T. E., & O'Reilly, J. X. (2019). Control of entropy in neural
models of environmental state. *eLife, 8*, e39404. doi:10.7554/eLife.39404

Mumford, J. A., Turner, B. O., Ashby, F. G., & Poldrack, R. A. (2012). Deconvolving BOLD
activation in event-related designs for multivoxel pattern classification analyses.
NeuroImage, 59(3), 2636-2643. doi:10.1016/j.neuroimage.2011.08.076

Nassar, M. R., Bruckner, R., & Frank, M. J. (2019). Statistical context dictates the relationship
between feedback-related EEG signals and learning. *eLife, 8*, e46975.
doi:10.7554/eLife.46975

Nassar, M. R., McGuire, J. T., Ritz, H., & Kable, J. W. (2019). Dissociable Forms of
Uncertainty-Driven Representational Change Across the Human Brain. *The Journal of
Neuroscience, 39*(9), 1688-1698. doi:10.1523/jneurosci.1713-18.2018

Nassar, M. R., Rumsey, K. M., Wilson, R. C., Parikh, K., Heasly, B., & Gold, J. I. (2012).
Rational regulation of learning dynamics by pupil-linked arousal systems. *Nature*
Neuroscience, 15(7), 1040-1046. doi:10.1038/nn.3130
Nassar, M. R., Wilson, R. C., Heasly, B., & Gold, J. I. (2010). An approximately Bayesian delta-
rule model explains the dynamics of belief updating in a changing environment. *The*
Journal of Neuroscience, 30(37), 12366-12378. doi:10.1523/JNEUROSCI.0822-10.2010
O'Reilly, J. X., Schüffelgen, U., Cuell, S. F., Behrens, T. E. J., Mars, R. B., & Rushworth, M. F.
S. (2013). Dissociable effects of surprise and model update in parietal and anterior
cingulate cortex. *Proceedings of the National Academy of Sciences, 110*(38), E3660-
E3669. doi:10.1073/pnas.1305373110
Payzan-LeNestour, E., Dunne, S., Bossaerts, P., & O'Doherty, John P. (2013). The Neural
Representation of Unexpected Uncertainty during Value-Based Decision Making.
Neuron, 79(1), 191-201. doi:10.1016/j.neuron.2013.04.037
Purcell, B. A., & Kiani, R. (2016). Hierarchical decision processes that operate over distinct
timescales underlie choice and changes in strategy. *Proceedings of the National Academy*
of Sciences, 113(31), E4531-E4540. doi:10.1073/pnas.1524685113
Schuck, N. W., Cai, M. B., Wilson, R. C., & Niv, Y. (2016). Human Orbitofrontal Cortex
Represents a Cognitive Map of State Space. *Neuron, 91*(6), 1402-1412.
doi:10.1016/j.neuron.2016.08.019
Smith, S. M., Jenkinson, M., Woolrich, M. W., Beckmann, C. F., Behrens, T. E., Johansen-Berg,
H., . . . Flitney, D. E. (2004). Advances in functional and structural MR image analysis
and implementation as FSL. *NeuroImage, 23 (S1)*, S208-S219.
doi:10.1016/j.neuroimage.2004.07.051
Sutton, R. S., & Barto, A. G. (1998). *Reinforcement Learning*. Cambridge, MA: MIT Press.
Wilson, R. C., Takahashi, Y. K., Schoenbaum, G., & Niv, Y. (2014). Orbitofrontal Cortex as a
Cognitive Map of Task Space. *Neuron, 81*(2), 267-279.
doi:10.1016/j.neuron.2013.11.005
754
755

Figure 1

Overview of task and experimental design. (**A**) Sequence of the task. At the start of the trial, participants
look at a cross in the center of the screen and maintain fixation for 0.5 sec to initialize the trial. After the
cross disappears, participants choose one of 10 targets (red) by looking at it within 1.5 sec and then
holding fixation on the chosen target for 0.3 sec. During the outcome phase (1 sec), a green dot inside the
target indicates the participants' choice. The rewarded target is shown in purple or cyan to indicate the
number of earnable points as 10 or 20, respectively. (**B**) Probability distribution of the rewarded target
location in the high-noise condition. Target location is relative to the location of the state (generative
mean). The rewarded target probabilities for the relative locations of [-2, -1, 0, 1, 2] are [0.05, 0.15, 0.6,
0.15, 0.05]. (**C**) Example of trials in the high-noise condition. The states change occasionally with a
hazard rate of 0.02. (**D**) Probability distribution of the rewarded target location in the unstable condition.
Because there is no noise in this condition, the rewarded target is always at the location of the state. (**E**)
Example of trials in the unstable condition. The states change frequently with a hazard rate of 0.35.

Figure 2

Behavioral results. (**A**) Probability of choosing the best target after change-points. Symbols and error bars are mean±SEM across subjects (solid symbols) or simulations (open symbols). (**B**) Relationship between error magnitude and switch probability. Symbols and error bars are as in **A**. (**C**) The distribution of switch probabilities for small errors (magnitude of 1 or 2) in both conditions. Each data point represents one participant. (**D**) Probability of switch as a function of current error magnitude and error history in the unstable condition. Different colors represent different error histories for the past 3 trials. A correct trial is marked as O, and an error trial is marked as X. For example, XOO implies that trial t-1 was an error trial, and trial t-2 and trial t-3 were correct trials. Symbols and error bars are mean±SEM across subjects. (**E**) Probability of switch as a function of current error magnitude and error history in the high-noise condition. Symbols and error bars are as in **D**. (**F**) The distribution of the slopes of switch probability against error history for small errors (magnitude of 1 or 2) in both conditions. Each data point represents one participant.

Figure 3

Reduced Bayesian model applied to behavioral and imaging data. (**A**) Model prediction for CPP. We calculated CPP from the reduced Bayesian model using subjective estimates of hazard rate and noise for each condition. The value of CPP increases as the current error magnitude increases in both conditions, but with a stronger dependence on the outcome of the previous trial in the high-noise condition. (**B**) Model prediction for RU. We calculated RU from the reduced Bayesian model using subjective estimates of hazard rate and noise for each condition. The value of RU is minimally affected by the current error magnitude. Instead, a past error tends to increase RU in the high-noise, but not the unstable, condition. (**C**) Model prediction for probability of switching choices. Increasing CPP causes the probability of switching to increase more steeply as the current error magnitude increases in the unstable condition versus in the high-noise condition. For small errors (error magnitude of 1 and 2) in the high-noise condition, the probability of switching is further influence by RU, which is affected by past errors. (**D**) Neural representation of CPP and RU. (**E**) ROI analysis for CPP and RU. These ROIs were selected based on the common regions of CPP, RU, and reward effects in McGuire et al. (2014). Significance was tested by a sign test. *$p<0.05$, **$p<0.01$, ***$p<0.001$.

Figure 4
Representations of error and error magnitude. For error versus correct analyses, multi-voxel neural
patterns were used to classify whether the response on the current trial was correct or an error. For error
magnitude analyses, multi-voxel neural patterns were used to classify different error magnitudes (1, 2, 3+)
conditional on the current trial being an error. Accuracies were calculated and compared with the baseline
accuracy within each subject and then tested at the group level. The representation of current error
magnitude is stronger in parietal cortex in the high-noise condition than the unstable condition.
813

"Error vs Correct" on the previous trial

Figure 5
Representations of errors on the previous trial conditional on different types of current trials (columns).
Multi-voxel neural patterns were used to classify correct responses versus errors on the previous trial.
This analysis was repeated for different types of current trials: all feedback, correct feedback, error
feedback, unambiguous feedback (error magnitudes are 0/3+), and ambiguous feedback (error magnitudes
are 1/2). The representation of past errors is stronger in parietal cortex in the high-noise condition than the
unstable condition when the current trial is an error or provides ambiguous feedback.
822

A

Error magnitude on the current trial
Switch vs stay on the next trial

B

Past error conditional on ambiguous feedback on the current trial
Switch vs stay on the next trial

Figure 6

Representations of subsequent behavioral choices (switch versus stay) after ambiguous small errors in the high-noise condition. (**A**) Overlap of results for switch versus stay on the next trial and error magnitude on the current trial. Multi-voxel neural patterns were used to classify whether participants switch their choice to another target or stay on the same target on the next trial. We focused on the most ambiguous errors (error magnitude of 1 or 2 in the high-noise condition). Above-chance classification performance was found throughout much of the frontal lobe. (**B**) Overlap of results for switch versus stay on the next trial and past error conditional on ambiguous feedback on the current trial.

834
Figure 2 - Figure supplement 1
Behavioral data and predictions from different models. (**A**) Probability of choosing the best target after
change-points. (RB: reduced Bayesian; fixedLR: fixed learning rate; P_{stay}: fixed tendency to stay) (**B**) The
relationship between error magnitude and switch probability. (**C**) Probability of switch as a function of
current error magnitude and error history in the unstable condition. (**D**) Probability of switch as a function
of current error magnitude and error history in the high-noise condition. Symbols and colors are as in
Figure 2.
842

Figure 3 - Figure supplement 1
Reduced Bayesian model with true hazard rate and noise applied to behavioral and imaging data. (**A**)
Model prediction for CPP. We calculated CPP from the reduced Bayesian model using the true hazard
rate and noise for each condition. (**B**) Model prediction for RU. We calculated RU from the reduced
Bayesian model using the true hazard rate and noise for each condition. (**C**) Model prediction for
probability of switch. Probability of switch is influenced by both CPP and RU. (**D**) Neural representation
of CPP and RU in the current study and in McGuire et al. (2014). CPP selective effect represents the
conjunction of CPP>0 and CPP>RU. RU selective effect represents the conjunction of RU>0 and
RU>CPP. (**E**) ROI analysis for CPP and RU. These ROIs were selected based on the common regions of
CPP, RU and reward effects in McGuire et al. (2014). Significance was tested by a sign test. *$p<0.05$,
**$p<0.01$, ***$p<0.001$.
856

Figure 4 - Figure supplement 1
Univariate representations of error and error magnitude. A GLM was implemented on the preprocessed
fMRI data (smoothed with 6 mm FWHM Gaussian kernel). The trial-by-trial regressors of interest that
were included in the GLM were: onset of correct trials, earnable value on correct trials, onset of error
trials, error magnitude on error trials, switch or stay on error trials and earnable value on error trials. We
focused on the effects of error (which is the difference between the onset of error trials and the onset of
correct trials) and error magnitude. Group *t*-values are shown. For statistical testing, we implemented one-
sample cluster-mass permutation tests with 5,000 iterations. The cluster-forming threshold was
uncorrected voxel *p*<0.005.

"Error vs Correct" on the previous trial

868
Figure 5 - Figure supplement 1
Univariate representations of error on the previous trial conditional on different types of current trials
(columns). Several GLMs were implemented on the preprocessed fMRI data (smoothed with 6 mm
FWHM Gaussian kernel). First, we examined errors on the previous trial across all trials. The trial-by-trial
regressors of interest that were included in the GLM were: onset of trials, error on trial t, error on trial t-1,
error on trial t-2, and error on trial t-3. We focused on the effect of error on trial t-1. Second, we separated
the analysis of past errors conditional on the current trial being correct or an error. The trial-by-trial
regressors of interest that were included in the GLM were: onset of current correct trials, errors on trial t-1,
t-2, or t-3 conditional on the current trial being correct, onset of current error trials, errors on trial t-1, t-2,
or t-3 conditional on the current trial being an error. We focused on the effects of error on trial t-1
conditional on the current trial being correct or an error. Third, we separated errors conditional on
unambiguous (error magnitudes are 0/3+) or ambiguous feedback (error magnitudes are 1/2). The trial-
by-trial regressors of interest that were included in the GLM were: onset of current trials with
unambiguous feedback, errors on trial t-1, t-2 or t-3 conditional on the current trial providing
unambiguous feedback, onset of current trials with ambiguous feedback, errors on trial t-1, t-2 or t-3
conditional on the current trial providing ambiguous feedback. We focused on the effects of errors on trial
t-1 conditional on the current trials providing unambiguous or ambiguous feedback. Group *t*-values are
shown. For statistical testing, we implemented one-sample cluster-mass permutation tests with 5,000
iterations. The cluster-forming threshold was uncorrected voxel *p*<0.005.
888

889
Figure 6 - Figure supplement 1
Univariate GLM for switch versus stay on ambiguous feedback in the high-noise condition. A GLM was
implemented with several trial-by-trial regressors of interest: onset of trials with error magnitude of 0,
onset of trials with error magnitude of 3+, onset of ambiguous feedback (error magnitudes are 1/2)
followed by switching, onset of ambiguous feedback followed by staying. We tested the effects of the
difference between switch and stay after ambiguous feedback. Group *t*-values are shown. The results were
thresholded based on uncorrected voxel *p*<0.01.

903 Table 1

904 BIC of behavior models

Model	Condition	BIC improvement by RB model
Reduced Bayesian model (RB)	Unstable	
	High-noise	
Fixed learning rate model (fixedLR)	Unstable	5.26 [3.97, 5.71]**
	High-noise	-22.22 [-77.36, 0.03]†
RB + fixedLR	Unstable	-9.85 [-10.97, -7.65]***
	High-noise	-4.60 [-9.93, 0.98]
RB + P$_{stay}$	Unstable	-5.20 [-5.66, -3.76]**
	High-noise	-5.57 [-5.68, -2.60]**

905 The values were shown as median [IQR]. A negative value means that RB model performed
906 better than the compared model. Significance was tested by a sign test. $^{\dagger}p<0.08$, **$p<0.01$,
907 ***$p<0.001$.
908

909 Table 2

910 Parameters of behavior models

Model	Parameter	Unstable	High-noise	Unstable > High-noise
RB	H	0.88 [0.68, 0.92]	0.33 [0.11, 0.50]	0.46 [0.25, 0.72]***
	K	0.59 [0.03, 2.22]	1.86 [1.22, 2.32]	-0.35 [-1.98, 0.71]
fixedLR	α_{fixed}	0.96 [0.86, 0.97]	0.63 [0.37, 0.73]	0.33 [0.19, 0.49]***
RB + fixedLR	H	0.27 [0.00, 0.84]	0.02 [0.00, 0.13]	0.14 [0.00, 0.64]†
	K	7.76 [2.18, 9.99]	3.83 [2.36, 9.02]	0.26 [-0.68, 5.77]
	α_{fixed}	0.97 [0.75, 1.00]	0.93 [0.23, 1.00]	0.02 [-0.10, 0.56]
	w	0.41 [0.15, 0.79]	0.65 [0.40, 0.87]	-0.23 [-0.57, 0.24]
RB + P$_{stay}$	H	0.86 [0.73, 0.94]	0.35 [0.11, 0.60]	0.47 [0.18, 0.72]**
	K	4.54 [0.12, 9.99]	2.09 [1.51, 4.71]	0.02 [-1.33, 6.41]
	P_{stay}	0.00 [0.00, 0.05]	0.01 [0.00, 0.13]	0.00 [-0.11, 0.02]

911 Parameter values were shown as median [IQR]. Difference of parameter values between the two

912 conditions was tested by a sign test. †$p<0.08$, **$p<0.01$, ***$p<0.001$.

914   Table 3

915   Summary of fMRI results: error magnitude and past error

Cluster index	#Voxels	Region	Peak t	Peak x	Peak y	Peak z
Error magnitude: high-noise versus unstable						
1	21032	R Precuneus	5.22	16	-56	12
		R Angular gyrus	5.17	44	-70	32
		L Precuneus	5.08	-18	-58	20
		Occipital pole	5.07	2	-98	-2
		L Superior parietal lobule	4.91	-10	-66	48
		R Occipital cortex	4.69	26	-76	18
		L Occipital cortex	4.54	-38	-86	26
		R Superior parietal lobule	4.44	44	-44	54
		Posterior cingulate cortex	4.43	2	-46	20
Past error on ambiguous feedback: high-noise versus unstable						
1	1881	Posterior cingulate cortex	4.79	12	-24	52
		R Superior parietal lobule	4.04	32	-38	54
		R Precuneus	3.58	6	-54	70
		L Superior parietal lobule	3.54	-16	-54	62
Conjunction: Error magnitude & Past error on ambiguous feedback						
1	304	R Superior parietal lobule	3.41	38	-40	52
2	103	R Precuneus	3.02	2	-58	70
3	81	L Superior parietal lobule	3.23	-18	-56	72

917   Table 4

918   Summary of fMRI results: behavior change

Cluster index	#Voxels	Region	Peak t	Peak x	Peak y	Peak z
Switch versus stay on ambiguous feedback in the high-noise condition						
1	12042	Middle cingulate cortex	4.35	14	-8	30
		R Insula	4.33	38	4	2
		Medial orbitofrontal cortex	4.24	-4	50	-10
		R Frontal pole	4.11	40	46	0
		R Inferior frontal gyrus	4.11	48	26	10
		L Frontal pole	4.01	-24	52	-2
		Dorsomedial frontal cortex	3.96	0	26	34
		Posterior cingulate cortex	3.93	2	-28	50
		R Precentral gyrus	3.91	48	-6	50
		Anterior cingulate cortex	3.51	0	48	20
2	3134	L Precentral gyrus	4.43	-62	2	24
		L Superior temporal gyrus	4.28	-50	-32	12
		L Postcentral gyrus	3.61	-50	-26	44