A normative account of confirmation bias during reinforcement learning

Germain Lefebvre[1], Christopher Summerfield[2†], Rafal Bogacz[1†*]

[1] MRC Brain Network Dynamics Unit, Nuffield Department of Clinical Neurosciences, University of Oxford, Oxford, UK.

[2] Department of Experimental Psychology, University of Oxford, Oxford, UK.

[†] Equal contribution

[*] Corresponding Author: rafal.bogacz@ndcn.ox.ac.uk

Running title: Confirmation bias in reinforcement learning

Abstract

Reinforcement learning involves updating estimates of the value of states and actions on the basis of experience. Previous work has shown that in humans, reinforcement learning exhibits a confirmatory bias: when updating the value of a chosen option, estimates are revised more radically following positive than negative reward prediction errors, but the converse is observed when updating the unchosen option value estimate. Here, we simulate performance on a multi-arm bandit task to examine the consequences of a confirmatory bias for reward harvesting. We report a paradoxical finding: that confirmatory biases allow the agent to maximise reward relative to an unbiased updating rule. This principle holds over a wide range of experimental settings and is most influential when decisions are corrupted by noise. We show that this occurs because on average, confirmatory biases lead to overestimating the value of more valuable bandits, and underestimating the value of less valuable bandits, rendering decisions overall more robust in the face of noise. Our results show how apparently suboptimal learning policies can in fact be reward-maximising if decisions are made with finite computational precision.

Introduction

Confirmation bias refers to seeking or interpreting evidence in ways that are influenced by
existing beliefs, and it is a ubiquitous feature of human perceptual, cognitive and social
processes, and a longstanding topic of study in psychology (Nickerson, 1998). Confirmatory
biases can be pernicious in applied settings, for example when clinicians overlook the correct
diagnosis after forming a strong initial impression of a patient (Groopman, 2007). In laboratory,
confirmation bias has been studied with a variety of paradigms (Nickerson, 1998; Talluri, Urai,
Tsetsos, Usher, & Donner, 2018). One paradigm in which the confirmation bias can be
observed and measured involves reinforcement learning tasks, where participants have to
learn from positive or negative feedback which options are worth taking (Chambon et al., 2019;
Palminteri, Lefebvre, Kilford, & Blakemore, 2017), and this paper focusses on confirmation bias
during reinforcement learning.

In the laboratory, reinforcement learning is often studied via a "multi-armed bandit" task in
which participants choose between two or more states that pay out a reward with unknown
probability (Daw, O'Doherty, Dayan, Seymour, & Dolan, 2006). Reinforcement learning on this
task can be modelled with a simple principle known as a delta rule (Rescorla & Wagner, 1972),
in which the estimated value V_t^i of the chosen bandit i on trial t is updated according to:

$$V_{t+1}^i = V_t^i + \alpha \cdot \delta_t^i \quad \text{where} \quad \delta_t^i = R_t^i - V_t^i \qquad (1)$$

In the above equation, R_t^i is the payout for option i on trial t, δ_t^i is the reward prediction error,
and α is a learning rate in unity range. If α is sufficiently small, V_t^i tend to converge over time
to the vicinity of expected value of bandit i (in stationary environments).

This task and modelling framework have also been used to study the biases that humans
exhibit during learning. One line of research has suggested that humans may learn differently
from positive and negative outcomes. For example, variants of the model above which include
distinct learning rates for positive and negative updates to V_t^i have been observed to fit human
data from a 2-armed bandit task better, even after penalising for additional complexity
(Gershman, 2015; Niv, Edlund, Dayan, & O'Doherty, 2012). When payout is observed only for
the option that was chosen, updates seem to be larger when the participant is positively rather
than negatively surprised, which might be interpreted as a form of optimistic learning
(Lefebvre, Lebreton, Meyniel, Bourgeois-Gironde, & Palminteri, 2017). However, a different
pattern of data was observed in follow-up studies in which counterfactual feedback was also
offered – i.e., the participants were able to view the payout associated with both chosen and
unchosen options. Following a feedback on the unchosen option, larger updates were
observed for negative prediction errors (Chambon et al., 2019; Palminteri et al., 2017; Schuller
et al., 2020). This is consistent with a confirmatory bias rather than a strictly optimistic bias,
whereby belief revision helps to strengthen rather than weaken existing preconceptions about
which option may be better.

One obvious question is why confirmatory biases persist as a feature of our cognitive landscape
– if they promote suboptimal choices, why have they not been selected away by evolution?
One variant of the confirmation bias, a tendency to overtly sample information from the
environment that is consistent with existing beliefs, has been argued to promote optimal data
selection: where the agent chooses its own information acquisition policy, exhaustively ruling

out explanations (however obscure) for an observation would be highly inefficient (Oaksford
& Chater, 2003). However, this account is unsuited to explaining the differential updates to
chosen and unchosen options in a bandit task with counterfactual feedback, because in this
case feedback for both options is freely displayed to the participant, and there is no overt data
selection problem.

It has been demonstrated previously that biased estimates of value can paradoxically be
beneficial in two-armed tasks in the sense that under standard assumptions, they maximise
the average total reward for the agent (Caze & van der Meer, 2013). This happens because
with such biased value estimates, the difference $V_t^1 - V_t^2$ may be magnified, so with a noisy
choice rule (typically used in reinforcement learning models) the option with the higher reward
probability is more likely to be selected. Caze and van der Meer (2013) considered a standard
reinforcement learning task in which feedback is provided only for the chosen option. In that
task the reward probabilities of the two options in the task determine whether it is beneficial
to have higher learning rate after positive or negative prediction error (Caze & van der Meer,
2013). In other words, when only outcome of chosen option is observed, optimistic bias is
beneficial for some reward probabilities, while pessimistic bias for other.

In this paper we show that if the participants are able to view the payouts associated with both
chosen and unchosen options, reward is typically maximized if the learning rates follow the
pattern of the confirmation bias, i.e. are higher when the chosen option is rewarded and
unchosen option is unrewarded. We find that this benefit holds over a wide range of settings,
including both stationary and nonstationary bandits, with different reward probabilities, across
different epoch lengths, and under different levels of choice variability. We also demonstrate
that such confirmation bias tends to magnify the difference $V_t^1 - V_t^2$ and hence makes the
choice more robust to the decision noise. These findings may explain why the humans tend to
revise beliefs to a smaller extent when outcomes do not match with their expectations.

Below we formalize the confirmation bias in a reinforcement learning model, compare its
performance in simulations with models without confirmation bias, and formally characterise
the biases introduced in value estimates. We also point that the confirmation bias not only
typically increases the average reward, but may increase the reward rate to even higher extent.

Reinforcement learning models

Confirmation model

We analyse properties of a *confirmation* model (Palminteri et al., 2017), which describes
learning in a two-armed bandit task where feedback is provided for both options on each trial.
The model updates the corresponding value estimates V_t^i according to a delta rule with two
learning rates: α^C for confirmatory updates (i.e. following positive prediction errors for the
chosen option, and negative for the unchosen option) and α^D for disconfirmatory updates (i.e.
following negative prediction errors for the chosen option, and positive for the unchosen
option) (Palminteri et al., 2017). Thus on each trial t, if the agent chooses the option 1, the
model updates the values V_t^1 and V_t^2 of the chosen and unchosen options respectively, such
that:

$$110 \qquad V_{t+1}^1 = V_t^1 + \begin{cases} \alpha^C \cdot \delta_t^1, & if \ \delta_t^1 > 0 \\ \alpha^D \cdot \delta_t^1, & if \ \delta_t^1 < 0 \end{cases} \qquad (2)$$

111 and

$$112 \qquad V_{t+1}^2 = V_t^2 + \begin{cases} \alpha^D \cdot \delta_t^2, & if \ \delta_t^2 > 0 \\ \alpha^C \cdot \delta_t^2, & if \ \delta_t^2 < 0 \end{cases} \qquad (3)$$

113 with δ_t^i being the prediction error for bandit i on trial t defined in Equation 1. We define an
114 agent with a confirmatory bias as one for whom $\alpha^C > \alpha^D$, whereas an agent with a
115 disconfirmatory bias has $\alpha^C < \alpha^D$, and an agent with no bias (or a neutral setting) has $\alpha^C =$
116 α^D. Note that for $\alpha^C = \alpha^D = \alpha$, the model amounts to a standard delta-rule model with a
117 unique learning rate α defined in Equation 1, and we refer to it as *unbiased*.

Decaying learning rate model

We compared the performance of the *confirmation* model in a stable environment to an
optimal value estimator which for each option computes the average of rewards seen so far.
Such values can be learned by a model using the update given in Equation 1 with the learning
rate α decreasing over trials according to $\alpha = \frac{1}{t}$, where t is the trial number (note that with
the counterfactual feedback, t is also equal to the number of times the reward for this option
has been observed).

Decision Policies

126 In this paper we consider three policies for making a choice on the basis of learned values:
127 *hardmax*, *softmax* and *ε-greedy* policies. The hardmax is a noiseless policy selecting
128 deterministically the arm associated to the highest value. The softmax is a probabilistic action
129 selection process associating to each arm a the probability P_t^a of being selected based on their
130 respective values such that:

$$131 \qquad P_t^a = \frac{exp\,(V_t^a/\beta)}{exp\,(V_t^1/\beta) + exp\,(V_t^2/\beta)} \qquad (4)$$

132 In the above equation β is the temperature of the *softmax* function, and the higher the
133 temperature, the more random the decision is. To mathematically analyse properties of the
134 confirmation model, we also consider a simpler stochastic choice rule ε-greedy, which on
135 majority of trials selects option with highest estimated value, while with certain fixed
136 probability selects an action randomly.

Effects of confirmation bias on average reward

Methods of simulation

Our goal was to test how outcomes vary with a confirmatory, disconfirmatory or neutral bias
across a wide range of different settings that have been the subject of previous empirical
investigation in humans and other animals. We considered the tasks involving choice between
two options. Each bandit i may yield reward $R = 1$ with probability p^i, and no reward ($R = 0$)

with probability $1 - p^i$. Importantly we assumed that the agent observes on each trial the
payouts for both options: the chosen one and the not chosen option (**Fig. 1a**). We consider an
agent who chooses among bandits for 2^n trials, where n varied from 2 to 10 in simulations
(**Fig. 1b**), and the presented rewards were averaged over these values of n (unless otherwise
stated).

We considered four different ways in which the reward probabilities p^i are set, illustrated
schematically in **Fig. 1c**. First we considered *stable* environments in which reward probabilities
were constant. We also considered *1 reversal* and *3 reversals* conditions where the payout
probabilities were reversed to $1 - p^i$ once in the middle of the task (second display in **Fig. 1c**),
or three times at equal intervals (third display in **Fig. 1c**). In *stable*, *1 reversal* and *3 reversals*
conditions, the initial probabilities p^i at the start of the task were sampled at intervals of 0.1
in the range [0.05, 0.95] such that $p^1 \neq p^2$, and we tested all possible combinations of these
probabilities (that is 45 probability pairs). Unless otherwise noted, results are averaged across
these initial probabilities.

Additionally, we considered *random walk* condition where the probabilities were initialized to
a random number from uniform distribution on interval from 0 to 1, and then drifted over trials
as follows:

$$p_{t+1}^i = p_t^i \,+\, \kappa \cdot (0.5 \,-\, p_t^i) + \mathcal{N}(0, \sigma^2)$$

with κ being a parameter decaying the reward probability towards 0.5 (here set to $\kappa = 0.001$)
and σ being the standard deviation of the normal distribution from which the fluctuations in
probabilities were sampled (here set to $\sigma = 0.02$). Sample probabilities generated from this
process are shown in the fourth display in **Fig. 1c**.

We conduct all simulations numerically, sampling the initial payout probabilities and
experiment length(s) exhaustively, varying α^C and α^D exhaustively, and noting the average
reward obtained by the agent in each setting. The model is simulated with all possible
combinations of learning rates α^C and α^D defined in the range $[0.05, 0.95]$ with increments
of 0.1, that is 19^2 learning rate combinations. For each combinations of parameters, the
simulations were performed 1000 times for all but the random walk condition where
simulations are performed 100000 times to account for the increased variability. Results are
averaged for plotting and analysis. In all cases, inferential statistics were conducted using
nonparametric tests with an alpha of $p < 0.001$ and Bonferroni correction for multiple
comparisons.

Results of simulations

Fig. 2 plots total reward obtained in the stationary bandit problem as a function of α^C (y-axis)
and α^D (x-axis), for the sequence length of 1024 and averaged across payout probabilities, for
both the hardmax (left) and softmax (right) rules. The key result is that rewards are on average
greater when $\alpha^C > \alpha^D$ (warmer colours above the diagonal) relative to when they are equal
or when $\alpha^C < \alpha^D$. We tested this finding statistically by repeating our simulations multiple
times with resampled stimulus sequences (and choices in the softmax condition) and
comparing the accrued reward to a baseline in which $\alpha^C = \alpha^D = 0.05$, i.e. the most promising
unbiased setting for α. The area enclosed by black line in **Fig. 2a-b** indicate combinations of

learning rates that yield rewards higher than the unbiased setting. **Fig. 2b** confirms that in
particular for the more plausible case where decisions are noisy (i.e. softmax temperature $\beta >$
0), there is a reliable advantage for a confirmatory update policy in the bandit task.

We compared the performance of the confirmation model to the decaying learning rate model
described above, which maximizes reward under the assumption that payout probabilities are
stationary and decisions are noiseless (i.e. under a hardmax choice rule). We confirmed this by
plotting the average reward under various temperature values for three models: one in which
a single learning rate was set to a fixed low value $\alpha = 0.05$ (*small learning rate* model) one in
which it was optimally annealed (*decaying learning rate* model), and one in which there was a
confirmatory bias (*confirmation* model; **Fig. 2c**). As can be seen, only under $\beta = 0$ the
confirmation bias does not increase rewards; as soon as decision noise increases, the relative
merit of the confirmation model grows sharply. Importantly, whereas the performance
advantage for the decaying learning rate model in the absence of noise (under $\beta = 0$) was very
small (on the order of 0.2%), the converse advantage for the confirmatory bias given noisy
decisions was numerically larger (1.6%, 4.6% and 5.5% under $\beta = 0.1, 0.2, 0.3$ respectively).

Next, we verified that these results held over different trial lengths and for differing volatility
conditions. The results (averaged over different numbers of trials) are shown in **Fig. 3**. One can
see equivalent results presented for a paradigm involving stable contingencies (**Fig. 3a and 3e**),
a reversal of probability between the two bandits midway through the sequence (**Fig. 3b and
3f**), for three such reversals (**Fig. 3c and 3g**), and for a random walk in which probabilities drift
upwards or downwards on each trial (**Fig. 3d and 3h**). When decisions are noisy, in all four
cases, confirmatory agents reap more rewards than disconfirmatory agents, and also than
agents for whom there is a single α selected to maximise reward (**Fig. 3e-h**). When the
decisions are based on the hardmax choice rule, there was no biased combination of learning
rates giving significantly higher rewards than unbiased model (**Fig. 3a-d**). Nevertheless, there
still existed combinations of parameters with $\alpha^C > \alpha^D$ yielding reward similar to that from the
unbiased model.

Subsequently, we tested how the sequence length affected the relative advantage conferred
by a confirmatory bias. In **Fig. 4a**, we show that the advantage for the confirmatory over the
unbiased model holds true for all but the very shortest sequences and continues to grow up to
sequences of 1024 trials. Finally, the confirmatory model is most advantageous at intermediate
levels of decisions noise (as quantified here by the softmax temperature). As we have seen,
the relative numerical and statistical advantage is lower if we assume no decision noise, but as
decision noise grows to the extent that performance tends towards random, all differences
between different update policies disappear (**Fig. 4b**).

Fig. 5a-c show that confirmation bias increases average reward irrespectively of the range of
reward probabilities for the two options. The consistent effect of confirmation bias contrasts
with the effects of biases in learning rates found in a previous study mentioned in the
Introduction (Caze & van der Meer, 2013), and we will come back to comparison of these
studies in the Discussion. **Fig. 5d-f** show that confirmation bias also increases the average
outcome in the aversive tasks in which the outcome on each trial R_t^i is either -1 or 0.

Confirmation bias magnifies difference between estimated values

The above simulations show that a confirmatory update strategy – one which privileges the
chosen over the unchosen option – is reward-maximising across a wide range of experimental
conditions, in particular when decisions are noisy. Why would this be the case? It is well
known, for example, that adopting a single small value for α will allow value estimates to
converge to their ground truth counterparts. Why would an agent want to learn biased value
estimates? To answer this question, we demonstrate below that the confirmation bias often
magnifies the differences between estimated values and hence make choices more robust to
decision noise. We first show it on an intuitive example and then more formally.

Example of the effects of confirmation bias

We selected three parametrisations of the update rules and examined their consequences in
more detail. The selected pairs of values for α^C and α^D are illustrated in **Fig. 6a** (symbols Δ, ×
and o). The first corresponded to an unbiased update rule: $\alpha^C = \alpha^D = 0.25$; the second to a
moderately biased rule ($\alpha^C = 0.35, \alpha^D = 0.15$); and the third to a severely biased rule ($\alpha^C =
0.45, \alpha^D = 0.05$). Let us refer to the bandit with a higher reward probability as richer and to
the other bandit as poorer. We chose a setting in which reward probability for the richer bandit
is $p^+ = 0.65$, while for the poorer bandit it is $p^- = 0.35$.

For each update rule, we plotted the evolution of the value estimate for the richer bandit V^+
over trials (**Fig. 6b**) as well as aggregate choice accuracy (**Fig. 6c**). Beginning with the choice
accuracy data, one can see that intermediate levels of bias are reward-maximising, in the sense
that they increase the probability that the agent chooses the bandit with the higher payout
probability, relative to an unbiased or a severely biased update rule (**Fig. 6c**). This is of course
simply a restatement of the finding that biased policies maximise reward (see shading in **Fig.
6a**). However, perhaps more informative are the value estimates for V^+ under each update
rule (**Fig. 6b**). As expected, the unbiased learning rule allows the agent to accurately learn the
appropriate value estimate, such that after a few tens of trials, $V^+ \approx p^+ = 0.65$ (grey line). By
contrast, the confirmatory model *overestimates* the value of the richer option (converging
close to $V^+ \sim 0.8$ despite $p^+ = 0.65$, and (not shown) the model *underestimates* the value of
the poorer option $p^- = 0.35$). Thus, the confirmation model outperforms the unbiased model
despite misestimating the value of both the better and the worse option. How is this possible?

To understand this phenomenon, it is useful to consider the policy by which simulated choices
are made. In the two-armed bandit case, the softmax choice rule of Equation 4 can be re-
arranged to the following logistic function:

258
$$P_t^1 = \frac{1}{1+\exp((V_t^2 - V_t^1)/\beta)} \tag{5}$$

Here, the choice probability depends both on the inverse slope of the choice function β and
the difference in value estimates for bandits 1 and 2. The effect of the confirmation bias is to
inflate the quantity $V_t^1 - V_t^2$ away from zero in either the positive or the negative direction,
thereby ensuring choice probabilities that are closer to 0 or 1 even in the presence of decision
noise (i.e. larger β). This comes at a potential cost of overestimating the value of the poorer
option rather than the richer, which would obviously hurt performance. The relative merits of
an unbiased vs. biased update rule are thus shaped by the relative influence of these factors.
When the rule is unbiased, the model does not benefit from the robustness conferred by
inflated value estimates. When the model is severely biased, the probability of confirming the

incorrect belief is excessive – leading to a high probability that the poorer option will be
overvalued rather than the richer (see the bimodal distribution of value estimates in **Fig. 6b**,
inset). Our simulations show that when this happens, the average reward is low, resulting in
bimodal distribution of rewards across simulations (inset in **Fig. 6a**). However, there exists a
"goldilocks zone" for confirmatory bias in which the benefit of the former factor outweighs the
cost of the latter. This is why a confirmation bias can help maximise reward.

Analysis of biases in estimated values

This section shows formally that under certain assumptions the confirmation bias increases
the distance between the estimated values. We followed the approach from a previous study
analysing biases in values due to unequal learning rates (Caze & van der Meer, 2013) and
analysed the values learned in a stable environment. Due to stochastic nature of rewards in
the task, V_t^i constantly fluctuate, but with time they approach a vicinity of values known as a
stochastic fixed points V_∞^i, in which they will not change on average, i.e. $\mathrm{E}(\Delta V_\infty^i) = 0$.

We were not able to obtain tractable analytic expressions for stochastic fixed points of values
when the softmax choice rule was assumed, hence we considered a simpler ε-greedy choice
rule. We denote the probability of selecting an option with a lower estimated value by ε. For
simplicity, let us assume that a learned value for the richer option V_t^+ is higher than the value
for the poorer option V_t^-. This assumption tends to be correct when p^+ is sufficiently higher
p^-, but it may not be satisfied when p^+ and p^- are similar, because of fluctuations in values
occurring during learning and a possibility that the model is stuck in preferring poorer option
due to the confirmation bias. Under this assumption the richer option is selected with
probability $1 - \varepsilon$, while the poorer option with probability ε.

The average change in the value of the richer option is then given by:

$$
\begin{aligned}
\mathrm{E}(\Delta V_t^+) = &(1 - \varepsilon)[p^+\alpha^C(1 - V_t^+) + (1 - p^+)\alpha^D(-V_t^+)] \\
&+ \quad \varepsilon \quad [p^+\alpha^D(1 - V_t^+) + (1 - p^+)\alpha^C(-V_t^+)]
\end{aligned}
$$

In the above equation the first line corresponds to changes occurring when the richer option
is chosen, and the second line when the poorer option is chosen. Within each line, the first
term in a square bracket corresponds to a change when the richer option yields rewards, while
the second term when the richer option is not rewarded. To find the value in a stochastic fixed
point, we set the left hand side of the above equation to 0 (because the stochastic fixed point
is defined as the value in which the average value change is 0), and solve for V_∞^+ to obtain:

$$
V_\infty^+ = \frac{bp^+(1 - \varepsilon) + p^+\varepsilon}{b(p^+(1 - \varepsilon) + (1 - p^+)\varepsilon) + (1 - p^+)(1 - \varepsilon) + p^+\varepsilon}
$$

300   where $b = \frac{\alpha^C}{\alpha^D}$ quantifies the amount of confirmation bias. The above equation shows that the
301   value V_∞^+ in a stochastic fixed point does not depend on the individual learning rates, but only
302   on their ratio, similarly as in a previous study (Caze & van der Meer, 2013). Analogous analysis
303   shows that the stochastic fixed point for the poorer option is equal to:

$$
V_\infty^- = \frac{bp^-\varepsilon + p^-(1 - \varepsilon)}{b(p^-\varepsilon + (1 - p^-)(1 - \varepsilon)) + (1 - p^-)\varepsilon + p^-(1 - \varepsilon)}
$$

305 We now demonstrate that the confirmation bias increases V_∞^+ and decreases V_∞^-. To evaluate
306 the effect to increasing α^C relatively to α^D on V_∞^+, we compute

$$\frac{dV_\infty^+}{db} = \frac{p^+(1-p^+)(1-2\varepsilon)}{[b(p^+(1-\varepsilon)+(1-p^+)\varepsilon)+(1-p^+)(1-\varepsilon)+p^+\varepsilon]^2}$$

308 The above expression is non-negative because the denominator is non-negative (as it is a
309 square) and the numerator is a product of non-negative terms. This derivative will be positive
310 if $0 < p^+ < 1$, and $0 < \varepsilon < \frac{1}{2}$, i.e. when the rewards are non-deterministic, and the choice
311 policy is stochastic but not completely random. The derivative for V_∞^- is equal to an analogous
312 expression but with a negative sign:

$$\frac{dV_\infty^-}{db} = -\frac{p^-(1-p^-)(1-2\varepsilon)}{\left[b\big(p^-\varepsilon+(1-p^-)(1-\varepsilon)\big)+(1-p^-)\varepsilon+p^-(1-\varepsilon)\right]^2}$$

In summary, for stochastic rewards and stochastic choice policy, the confirmation bias
increases V_∞^+ and decreases V_∞^-, and hence it magnifies the difference between the values.

Fig. 7 compares theoretically predicted difference between the learned values (dashed lines)
with the results of simulations. The simulations match experimental predictions well except for
when p^+ and p^- are equal or close to each other (in **Fig. 7a** and **7c**), because then the
assumption that $V^+ > V^-$ stated at the start of the section is no longer always valid. For the
unbiased model (green curves), the difference in estimated values follow the difference in
reward probabilities. Importantly, when p^+ and p^- differ, the confirmation bias increases the
difference between the learned values (except for the case where both outcomes are
deterministic, i.e. $p^+ = 1$ and $p^- = 0$ in **Fig. 7a**).

Effects of confirmation bias on reward rate

The analysis shown in **Fig. 6** illustrates why the benefit confirmation drops off as the bias tends
to the extreme – it is because under extreme bias, the agent falls into a feedback loop whereby
it confirms its false belief that the lower-valued bandit is in fact the best. Over multiple
simulations, this radically increases the variance in performance and thus dampens overall
average reward (**Fig. 6c**). However, it is noteworthy that this calculation is made under the
assumption that all trials are made with equivalent response times. In the wild, incorrect
choices may be less pernicious if they are made rapidly, if biological agents ultimately seek to
optimise their reward per unit time (or reward rate).

In our final analysis, we relaxed this assumption and asked how the confirmatory bias affected
overall reward *rates*, under the assumption that decisions are drawn to a close after a bounded
accumulation process that is described by the drift-diffusion model. This allows us to model
not only the choice probabilities but also reaction times.

Methods of simulations

We simulated a *reinforcement learning drift diffusion model* (RLDDM) in which the drift rate
was proportional to the difference in value estimates between the two bandits (Pedersen,
Frank, & Biele, 2017), which in turn depends on the update policy (confirmatory,

disconfirmatory, or neutral). At each trial, the relative evidence x in favour of one of the two
options is integrated over time, discretized in finite time step i, until it reaches a threshold a,
implying the selection of the favoured option such that:

344
$$x_{i+1} = x_i + v_t * dt \, + \, c * \sqrt{dt} * \mathcal{N}(0,1)$$

345 with x_0, the initial evidence defined as: $x_0 = \frac{a}{2}$, dt set to 0.001 and c to 0.1. The drift rate v_t,
346 is linearly defined from the difference in values such that:

347
$$v_t = v_{mod} * (V_t^+ - V_t^-)$$

348 V_t^+ and V_t^- being the values at trial t, of the correct and incorrect options respectively. We
349 used in our simulation a drift rate scaling parameter and a threshold values that make the drift-
350 diffusion model to produce the same choice probabilities as the *softmax* policy with a
351 temperature $\beta = 0.1$. In particular, the probability of making a correct choice by a diffusion
352 model (Bogacz, Brown, Moehlis, Holmes, & Cohen, 2006) is given by:

353
$$P_t^+ = \frac{1}{1 + \exp(-av_t/c^2)}$$

354 The above probability is equal to that in Equation 5 if $av_{mod}/c^2 = 1/\beta$. Thus, we set $v_{mod} =$
355 $a = \sqrt{0.1}$. The values are updated exactly the same way as in the *confirmation* model
356 (Equations 2 and 3). We employed the setting with 128 trials, used stable contingencies with
357 reward probabilities equal to $p^- = 0.35$ and $p^+ = 0.65$.

Results of simulations

When we plotted the overall accuracy of the model, the results closely resemble those from
previous analyses, as is to be expected (**Fig. 8a**). When we examined simulated reaction times,
we observed that confirmatory learning leads to faster decisions (**Fig. 8b**). This follows naturally
from the heightened difference in values estimates for each bandit, as shown in **Fig. 6**.
Critically, however, responses were faster for both correct and incorrect trials. This meant that
confirmatory biases have the potential to draw decisions to a more rapid close, so that
unrewarded errors give way rapidly to new trials which have a chance of yielding reward. This
was indeed the case: when we plotted reward rate as a function of confirmatory bias, there
was a relative advantage over a neutral bias even for those more extreme confirmatory
strategies that were detrimental in terms of accuracy alone (**Fig. 8c**). Thus, even a severe
confirmatory bias can be beneficial to reward rates in the setting explored here. However, we
note that this may be limited to the case explored here, where the ratio of reward to penalty
is greater than one.

Discussion

Humans have been observed to exhibit confirmatory biases when choosing between stimuli or
actions that payout with uncertain probability (Chambon et al., 2019; Palminteri et al., 2017;
Schuller et al., 2020). These biases drive participants to update positive outcomes (or those
that are better than expected) for chosen options more sharply than negative outcomes, but
to reverse this update pattern for the unchosen option. Here, we show through simulations

that in an extended range of settings traditionally used in human experiments, this asymmetric
update is advantageous in the presence of noise in the decision process. Indeed, agents who
exhibited a confirmatory bias, rather than a neutral or disconfirmatory bias, were in most
circumstances tested those agents that reaped the largest quantities of reward. This
counterintuitive result directly stems from the update process itself that biases the value of
the chosen and unchosen options (corresponding overall to the best and worst options
respectively), increasing mechanistically their relative distance from each other and ultimately
the probability of selecting the best option in the upcoming trials.

Exploring the evolution of action values under confirmatory updates offers an insight into why
this occurs. Confirmatory updating has the effect of rendering subjective action values more
extreme than their objective counterparts – in other words, options that are estimated to be
good are overvalued, and options estimated to be bad are undervalued (**Fig. 6**). This can have
both positive and negative effects. The negative effect is that a confirmatory bias can drive a
feedback loop whereby poor or mediocre items that are chosen by chance can be falsely
updated in a positive direction, leading to them being chosen more often. The positive effect,
however, is that where decisions are themselves intrinsically variable (for example, because
they are corrupted by Gaussian noise arising during decision-making or motor planning,
modelled here with the softmax temperature parameter) overestimation of value makes
decisions more robust to decision noise, because random fluctuations in the value estimate at
the time of the decision are less likely to reverse a decision away from the better of the two
options. The relative strength of these two effects depends on the level of decision noise:
within reasonable noise ranges the latter effect outweighs the former and performance
benefits overall.

Relationship to other studies

The results described here thus join a family of recent-reported phenomena whereby decisions
that distort or discard information lead to reward-maximising choices under the assumption
that decisions are made with finite computational precision – i.e. that decisions are intrinsically
noisy (Summerfield & Tsetsos, 2015). For example, when averaging features from a multi-
element array to make a category judgment, under the assumption that features are equally
diagnostic (and that the decision policy is not itself noisy), then normatively, they should be
weighted equally in the choice. However, in the presence of "late" noise, encoding models that
overestimate the decision value of elements near the category boundary are reward-
maximising, for the same reason as the confirmatory bias here: they inflate the value of
ambiguous items away from indifference, and render them robust to noise (Li, Herce Castanon,
Solomon, Vandormael, & Summerfield, 2017). A similar phenomenon occurs when comparing
gambles defined by different monetary values: utility functions that inflate small values away
from indifference (rendering the subjective difference between $2 and $4 greater than the
subjective difference between $102 and $104) have a protective effect against decision noise,
providing a normative justification for convex utility functions (Juechems, Spitzer, Balaguer, &
Summerfield, 2020). Related results have been described in problems that involve sequential
sampling in time, where they may account for violations of axiomatic rationality, such as
systematically intransitive choices (Tsetsos et al., 2016). Moreover, a bias in how evidence is
accumulated within a trial has been shown to increase the accuracy of individual decisions,
making the decision variable more extreme and thus less likely to be corrupted by noise (Zhang
& Bogacz, 2010).

A recent preprint also reports simulations of the confirmation bias model (Tarantola, Folke,
Boldt, Perez, & De Martino, 2021). The simulations in that study paralleled an experimental
paradigm reported in that paper, and a confirmation model was simulated for parameters
(including softmax temperature) corresponding to those estimated for participant of the study.
The simulated agents employing confirmation bias obtained higher average reward than
unbiased learners, as well as learners described by other models. Our paper suggests the same
conclusion employing a complementary approach in which the models have been simulated in
variety of conditions and analysed mathematically.

As mentioned earlier, the consistent benefit of confirmation bias for different reward
probabilities (**Fig. 5a** and **5b**) contrasts with the differential effects of biases in learning rates
found in a previous study (Caze & van der Meer, 2013). That study considered a standard
reinforcement learning task in which feedback is provided only for the chosen option. The
study showed that if reward probabilities for both options $p^i < 0.5$, then it is beneficial to have
a larger learning rate when δ_t^i is positive than when it is negative. With such unbalanced
learning rates, both V^1 and V^2 will be overestimated and critically the difference $V^1 - V^2$ will
be magnified, so with a noisy choice rule the option with the higher reward probability will be
more likely to be selected. By contrast, if both $p^i > 0.5$, then overestimating V^1 and V^2 would
actually reduce the difference $V^1 - V^2$ due to a ceiling effect, because according to Eq 1
reward estimates cannot exceed the maximum reward available, i.e. $V^i \leq 1$. In this case, it is
beneficial to have a larger learning rate when δ_t^i is negative than when it positive. In summary,
if one assumes that learning rates can differ between rewarded and unrewarded trials, the
type of reward-increasing bias depends on magnitude of reward probabilities in a task (Caze &
van der Meer, 2013). By contrast, here we show that if one assumes that learning rates can
differ between confirmatory and disconfirmatory trials, then confirmation bias tend to
increase reward and magnify difference in estimated values both for low reward probabilities
(**Fig. 5a** and **7b**) and high reward probabilities (**Fig. 5b** and **7c**).

Validity of model's assumptions

Reinforcement learning models fit to human data often assume that choices are stochastic, i.e.
that participants fail to choose the most valuable bandit. In standard tasks involving only
feedback about the value of the chosen option (factual feedback), some randomness in choices
promotes exploration which in turns allows information to be acquired that may be relevant
for future decisions. However, our task involves both factual and counterfactual feedback, and
so exploration is not required to learn the value of the two bandits. Nevertheless, in some
simulations we modelled choices with a softmax rule, which assumes that decisions are
corrupted by Gaussian noise, or an ε-greedy policy, which introduces lapses to the choice
process with a fixed probability. Implicitly, thus, we are committing to the idea that value-
guided decisions may be irreducibly noisy even where exploration is not required (Renart &
Machens, 2014). Indeed, others have shown that participants continue to make noisy decisions
even where counterfactual feedback is available, even if they have attributed that noise to
variability in learning rather than choice (Findling, Skvortsova, Dromnelle, Palminteri, & Wyart,
2019).

Due to our assumptions, the present study has a number of limitations. Firstly, we explored
the properties of a confirmatory model that has been previously shown to provide a good fit
to human data performing a bandit task with factual and counterfactual feedback. However,

we acknowledge that this is not the only possible model that could increase reward by enhancing the difference between represented values of options. In principle, any other models producing choice hysteresis might be able to explain these results (Katahira, 2018; Miller, Shenhav, & Ludvig, 2019; Worthy, Pang, & Byrne, 2013). An analysis of these different models and of their respective resilience to decision noise in different settings is beyond the scope of the current study but would be an interesting target for future research. Secondly, the results described here hold assuming a fixed and equal level of stochasticity (e.g. *softmax* temperature) in agents' behaviours, irrespective of their bias (i.e. the specific combination of learning rates). Relaxing this assumption, an unbiased agent could perform equally well as a biased agent subject to more decision noise. Thus, the benefit of confirmatory learning is relentlessly linked to the level of noise and one level of confirmation bias cannot be thought as being beneficial overall. Thirdly, the present study does not investigate the impact on the performance of other kinds of internal noise such like an update noise (Findling et al., 2019). The latter, instead of perturbing the policy itself, perturbs at each trial the update process of the options' value (i.e. predictions errors are blurred with a Gaussian noise), and cannot presumably produce a similar increase in performance, having overall no effect on the average difference between these option values.

Limits to the benefits of biased beliefs

It is important to point out that confirmation bias is beneficial in many but not all circumstances. Although in almost all presented simulations there exists a combination of biased learning rates giving performance that is higher or as good as the best unbiased learner, the optimal learning rates and hence the amount of bias differ depending on task parameters. At the start of the task, a learner usually is unable to know the details of the task a priori, so needs to adopt a certain default combination of learning rates. One could expect that such default learning rates would be determined by past experience or even be to a certain extent influenced by evolution. However such default set of biased learning rates will lead to detrimental effects on performance in certain tasks. For example, a recent study estimated average learning rates of human participants to be $\alpha^C \approx 0.15$ and $\alpha^D \approx 0.05$ (Tarantola et al., 2021) giving a confirmation bias of $b \approx 3$. Although such strong confirmation bias increases reward in many simulated scenarios when decisions are noisy (e.g. **Fig. 3e-h**), it would have a negative effect on performance when decisions are accurately made on the basis of values and in changing environments (e.g. **Fig. 3a-d**). If the default confirmation bias is influenced by evolution, its value is likely to be relatively high, because many of the key decisions of our ancestors had to be quick and thus were noisy due to the speed accuracy trade-off. By contrast, in the modern world, we often can take time to consider important choices, hence the biases that brought evolutionary advantage to our ancestor may not always be beneficial to modern humans.

Acknowledgements

This work has been supported by MRC grants MC_UU_12024/5, MC_UU_00003/1, BBSRC grant BB/S006338/1, and ERC Consolidator grant 725937.

References

Bogacz, R., Brown, E., Moehlis, J., Holmes, P., & Cohen, J. D. (2006). The physics of optimal decision making: a formal analysis of models of performance in two-alternative forced-choice tasks. *Psychol Rev, 113*(4), 700-765. Retrieved from http://www.ncbi.nlm.nih.gov/entrez/query.fcgi?cmd=Retrieve&db=PubMed&dopt=Citation&list_uids=17014301

Caze, R. D., & van der Meer, M. A. (2013). Adaptive properties of differential learning rates for positive and negative outcomes. *Biol Cybern, 107*(6), 711-719. doi:10.1007/s00422-013-0571-5

Chambon, V., Thero, H., Vidal, M., Vandendriessche, H., Haggard, P., & Palminteri, S. (2019). Choosing and learning: outcome valence differentially affects learning from free versus forced choices. *BiorXiv preprint*. Retrieved from https://doi.org/10.1101/637157

Daw, N. D., O'Doherty, J. P., Dayan, P., Seymour, B., & Dolan, R. J. (2006). Cortical substrates for exploratory decisions in humans. *Nature, 441*(7095), 876-879. Retrieved from http://www.ncbi.nlm.nih.gov/entrez/query.fcgi?cmd=Retrieve&db=PubMed&dopt=Citation&list_uids=16778890

Findling, C., Skvortsova, V., Dromnelle, R., Palminteri, S., & Wyart, V. (2019). Computational noise in reward-guided learning drives behavioral variability in volatile environments. *Nat Neurosci, 22*(12), 2066-2077. doi:10.1038/s41593-019-0518-9

Gershman, S. J. (2015). Do learning rates adapt to the distribution of rewards? *Psychon Bull Rev, 22*(5), 1320-1327. doi:10.3758/s13423-014-0790-3

Groopman, J. (2007). *How Doctors Think*: Mariner Books.

Juechems, K., Spitzer, B., Balaguer, J., & Summerfield, C. (2020). Optimal utility and probability functions for agents with finite computational precision. *PsyArXiv*. Retrieved from https://psyarxiv.com/6yhwg/

Katahira, K. (2018). The statistical structures of reinforcement learning with asymmetric value updates. *J. Math. Psychol.* doi:10.1016/j.jmp.2018.09.002

Lefebvre, G., Lebreton, M., Meyniel, F., Bourgeois-Gironde, S., & Palminteri, S. (2017). Behavioural and neural characterization of optimistic reinforcement learning. *Nat Hum Behav, 1*.

Li, V., Herce Castanon, S., Solomon, J. A., Vandormael, H., & Summerfield, C. (2017). Robust averaging protects decisions from noise in neural computations. *PLoS Comput Biol, 13*(8), e1005723. doi:10.1371/journal.pcbi.1005723

Miller, K. J., Shenhav, A., & Ludvig, E. A. (2019). Habits without values. *Psychol Rev, 126*(2), 292-311. doi:10.1037/rev0000120

Nickerson, R. S. (1998). Confirmation bias: a ubiquitous phenomenon in many guises. *Review*
of General Psychology, 2, 175-220.

Niv, Y., Edlund, J. A., Dayan, P., & O'Doherty, J. P. (2012). Neural prediction errors reveal a risk-
sensitive reinforcement-learning process in the human brain. *J Neurosci, 32*(2), 551-
562. doi:10.1523/JNEUROSCI.5498-10.2012

Oaksford, M., & Chater, N. (2003). Optimal data selection: revision, review, and reevaluation.
Psychon Bull Rev, 10(2), 289-318. doi:10.3758/bf03196492

Palminteri, S., Lefebvre, G., Kilford, E. J., & Blakemore, S. J. (2017). Confirmation bias in human
reinforcement learning: Evidence from counterfactual feedback processing. *PLoS*
Comput Biol, 13(8), e1005684. doi:10.1371/journal.pcbi.1005684

Pedersen, M. L., Frank, M. J., & Biele, G. (2017). The drift diffusion model as the choice rule in
reinforcement learning. *Psychon Bull Rev, 24*(4), 1234-1251. doi:10.3758/s13423-016-
1199-y

Renart, A., & Machens, C. K. (2014). Variability in neural activity and behavior. *Curr Opin*
Neurobiol, 25, 211-220. doi:10.1016/j.conb.2014.02.013

Rescorla, R. A., & Wagner, A. R. (1972). A theory of Pavlovian conditioning: Variations in the
effectiveness of reinforcement and nonreinforcement. In B. A.H. & W. F. Prokasy (Eds.),
Classical Conditioning II: Current Research and Theory (pp. 64-99). New York: Appleton
Century Crofts.

Schuller, T., Fischer, A. G., Gruendler, T. O. J., Baldermann, J. C., Huys, D., Ullsperger, M., &
Kuhn, J. (2020). Decreased transfer of value to action in Tourette syndrome. *Cortex,*
126, 39-48. doi:10.1016/j.cortex.2019.12.027

Summerfield, C., & Tsetsos, K. (2015). Do humans make good decisions? *Trends Cogn Sci, 19*(1),
27-34. doi:10.1016/j.tics.2014.11.005

Talluri, B. C., Urai, A. E., Tsetsos, K., Usher, M., & Donner, T. H. (2018). Confirmation bias
through selective overweighting of choice-consistent evidence. *Current Biology,*
28(19), 3128-3135. e3128.

Tarantola, T. O., Folke, T., Boldt, A., Perez, O. D., & De Martino, B. (2021). Confirmation bias
optimizes reward learning. *bioRxiv*.

Tsetsos, K., Moran, R., Moreland, J., Chater, N., Usher, M., & Summerfield, C. (2016). Economic
irrationality is optimal during noisy decision making. *Proc Natl Acad Sci U S A, 113*(11),
3102-3107. doi:10.1073/pnas.1519157113

Worthy, D. A., Pang, B., & Byrne, K. A. (2013). Decomposing the roles of perseveration and
expected value representation in models of the Iowa gambling task. *Front Psychol, 4*,
640. doi:10.3389/fpsyg.2013.00640

Zhang, J., & Bogacz, R. (2010). Bounded Ornstein–Uhlenbeck models for two-choice time
controlled tasks. *Journal of Mathematical Psychology, 54*(3), 322-333.
doi:10.1016/j.jmp.2010.03.001

a Contingencies

1 factual — 1 counterfactual

$p(1) = 0.05 : 0.1 : 0.95 \mid p(0) = 1 - p(1)$

b Learning Periods

2^n trials n=2:10

c Volatility Types

P_{reward}

Stable 100 1 Reversal 100 3 Reversals 100 Random Walk 100

Trials

Figure 1. Simulation Setup. a. Reward contingencies. The illustration represents the chosen (orange) and unchosen (blue) bandits each with a feedback signal (central number). Below, we state the range of possible outcomes and probabilities. **b**. Learning Periods. The illustration represents the different length of the learning period and the different outcomes combinations potentially received by the agents. **c**. Volatility Types. The line plots represent the evolution of the two arms probability across trials in the different volatility conditions.

Figure 2. Dependence of reward on learning rate and decision noise in a stable environment.
a and **b**. Average reward for all learning rate combinations. The heatmaps represent the per trial average reward for combinations of α^C (y-axis) and α^D (x-axis), averaged across all reward contingencies and agents in the stable condition with 1024 trials. Areas enclosed by black lines represent learning rate combinations for which the reward is significantly higher than the performance of the best equal learning rates combination represented by a black circle, one-tailed independent samples rank-sum tests, p<0.001 corrected for multiple comparison. **a**. Deterministic Decisions. Simulated reward is obtained using a noiseless *hardmax* policy. **b**. Noisy Decisions. Simulated reward is obtained using a noisy *softmax* policy with $\beta = 0.1$. **c**. Comparison with optimal models. The bar plot represents the per trial average reward of the *confirmation* model, the *small learning rate* model and the *decaying learning rate* model for four different levels of noise in the decision process. In simulations of the *confirmation model*, the best learning rates combination was used for each noise level (i.e. $\alpha^C = [0.1, 0.15, 0.3, 0.35]$ and $\alpha^D = 0.05$). Bars represent the means and error bars the standard deviations across agents, all reward levels are significantly different from each other, two-tailed independent samples rank-sum tests, p<0.001.

Figure 3. Dependence of reward on learning rate and decision noise in different environments.
a, **b**, **c** ,**d**, **e**, **f**, **g** & **h**. The heatmaps represent the per trial average reward for combinations of
α^C (y-axis) and α^D (x-axis) given a *hardmax* policy (**a, b, c, d**) or a *softmax* policy ($\beta = 0.3$) (**e,**
f, g, h). The performance is averaged across all reward contingencies, period lengths and 1000
agents in the stable condition (**a, e**), 1 reversal condition (**b, f**), 3 reversals condition (**c, g**) or
100000 agents in the random walk condition (**d, h**). Areas enclosed by black lines represent
learning rate combinations for which the reward is significantly higher than the reward of the
best equal learning rates combination represented by a black circle, one-tailed independent
samples rank-sum tests, $p < 0.001$ corrected for multiple comparisons.

a Period Length

b Decision Noise

Figure 4. Effects of period length and decision noise on the relative performance of confirmation model. a. Effect of period length on reward. The line plot represents the difference in average reward between the confirmation model (with the best confirmatory learning rate combination per period) and the unbiased model (with the best per period single learning rate) in function of the log of the period length, and for the four different volatility conditions. The logarithmic transformation of the trial number is for illustrative purpose only. *, $p < 0.001$, two-tailed independent rank-sum tests. **b**. Effect of decision noise on performance. The line plot represents the difference in per trial average performances of the confirmation model (with the best confirmatory learning rates combination) and the unbiased model (with the single best learning rate) in function of the log of *softmax* temperature, and for the four different volatility conditions. The logarithmic transformation of the *softmax* temperature is for illustrative purpose only. *, $p < 0.001$, two-tailed independent rank-sum tests.

Figure 5. Dependence of reward on learning rate, outcome valence and reward contingencies.
a, **b**, **c** ,**d**, **e**, **& f**. The heatmaps represent the per trial average reward for combinations of α^C
(y-axis) and α^D (x-axis) given a *softmax* policy ($\beta = 0.3$) in a stable environment. The
performance is averaged across 1000 agents, all period lengths and low reward contingencies,
i.e. $p^1 < 0.5$ and $p^2 < 0.5$ (**a, d**), high reward contingencies, i.e. $p^1 > 0.5$ and $p^2 > 0.5$ (**b, e**),
mixed reward contingencies, i.e. $p^1 > 0.5$ and $p^2 < 0.5$ (**c, f**). Outcome valence was either
positive, i.e. [0 1] (**a, b, c**) or negative , i.e. [-1 0] (**d, e, f**). Areas enclosed by black lines represent
learning rate combinations for which the reward is significantly higher than the reward of the
best equal learning rates combination represented by a black circle, one-tailed independent
samples rank-sum tests, $p < 0.001$ corrected for multiple comparisons.

Figure 6. **Mechanism by which confirmation bias tends to increase reward. a**. Average reward
and reward distributions for different levels of confirmation bias. The heatmap represents the
per trial average reward of the confirmation model for all learning rates combinations
(confirmatory learning rates are represented on the y-axis whereas disconfirmatory learning
rates are represented on the x-axis) associated with a *softmax* policy with $\beta = 0.1$. The
rewards concern the stable condition with 128 trials and asymmetric contingencies ($p^- = 0.35$
and $p^+ = 0.65$) and are averaged across agents. The three signs inside the heatmap (Δ, x and
+) represent the three learning rates combinations used in the simulations illustrated in panels
b and **c**. The histograms show the distribution across agents of the average per trial reward for
the three different combinations. **b**. Estimated values. The line plots represent the evolution
of the best option value V^+ across trials. The large plot represents the agents-averaged value
of the best option across trials for three different learning rates combinations, "unbiased"
($\alpha^C = \alpha^D = 0.25$), "biased (low)" ($\alpha^C = 0.35$ and $\alpha^D = 0.15$) and "biased (high)" ($\alpha^C = 0.45$
and $\alpha^D = 0.05$). The lines represent the mean and the shaded areas, the SEM. The small plots
represent the value of the best option across trials plotted separately for the three
combinations. The thick lines represent the average across agents and the lighter lines the
individual values of 5% of the agents. **c**. Choice Accuracy. The line plots represent the evolution
of the probability to select the best option across trials. The large plot represents the agents-
averaged probability to select the best option across trials for three different learning rates
combinations, "unbiased" ($\alpha^C = \alpha^D = 0.25$), "biased (low)" ($\alpha^C = 0.35$ and $\alpha^D = 0.15$) and
"biased (high)" ($\alpha^C = 0.45$ and $\alpha^D = 0.05$). The lines represent the mean and the shaded
areas, the SEM. The small plots represent the probability to select the best option across trials
plotted separately for the three combinations. The thick lines represent the average across
agents and the lighter lines the individual probability for 5% of the agents.
672

Figure 7. Differences between learned values of the richer and poorer options. Dashed lines
show theoretically predicted difference. Solid lines were obtained in simulations, and show the
difference between the learned values after 1000 trials in a stable environment. These
differences are averaged over 1000 simulations and error bars show standard error. Different
colours correspond to different combinations on learning rates (shown in key). X-axes show
the difference in reward probabilities of the richer and poorer options in panel a, and the
reward probability for the richer option in the other panels. Different panels correspond to
different constraints on reward probabilities, stated above each panel.
682

Figure 8. **Effect of confirmation bias on reward rate. a**. The heatmap represents the per trial average reward simulated with the confirmation RLDDM for all learning rates combinations (confirmatory learning rates are represented on the y-axis whereas disconfirmation learning rates are represented on the x-axis). The rewards concern the stable condition with 128 trials and asymmetric contingencies ($p^- = 0.35$ and $p^+ = 0.65$) and are averaged across agents. **b**. The heatmap represents the per trial average reaction time estimated with the confirmation RLDDM for all learning rates combinations. **c**. The heatmap represents the per trial average reward rate simulated with the confirmation RLDDM for all learning rates combinations.