IRRIGATION LEVELS AND SOIL COVERS IN CARROT CROP

Joslanny Higino Vieira [1][¶][*][#a]; Catariny Cabral Aleman [1][¶][#a]; Elis Marina de Freitas[1][¶][#a];

Laylton de Albuquerque Santos [2][¶][#b] ; Gustavo Henrique da Silva [1][&][#a]; Pedro Henrique

Franco Fernandes[1][&][#a]

[1] Department of Agricultural Engineering, Federal University of Viçosa, Viçosa, Minas

Gerais, Brazil

[2] Master´s of agriculture and environment, University Federal of Alagoas, Arapiraca,

Alagoas, Brazil

[#a] Current Address: Department of Agricultural Engineering, Federal University of

Viçosa, Viçosa, Minas Gerais, Brazil

[#b] Current Address: Master of agriculture and environment, Federal University of

Alagoas, Arapiraca, Alagoas, Brazil

[*] Corresponding author

Email: joslannyhigino@gmail.com

[¶] These authors contributed equally to this work.

[&] These authors also contributed equally to this work.

Abstract

To increase the sustainability of irrigated cultivation, the use of soil coverings can favor the reduction of water consumption. Thus, the aim of this research was to characterize the carrot collection (cultivar Brasília) grown under different irrigation water depths and different soil cover conditions. The experiment was conducted at the Federal University of Viçosa, MG. The experimental design was a randomized block in a factorial scheme. Five percentages of the water capacity of the soil (20, 40. 60, 80 and 100%) were applied using tensiometry, and three cultivation environments without cover (control), white colored polyethylene, and biodegradable semi kraft paper. Soil and leaf temperature, number of plants, root length, Normalized Difference Vegetation Index (NDVI) and fresh root mass were evaluated. Then, the analysis of variance was performed using the F test. For comparison of means, the Tukey test ($P \leq 0.05$) was used. For the regression analysis, the equation with the largest significant fit was chosen. According to the results, the use of semi kraft paper is an option in the cultivation of carrots. The use of semi-kraft paper is an option for growing carrots better than white polyethylene. Levels up to 60% of the actual water capacity in the soil showed positive results in the carrot production.

Introduction

A carrot (*Daucus carota* L.) is one of the most important vegetables on the world stage, due to its large area of planted and for enabling the socioeconomic development of farmers [1] since the return on invested capital is relatively quick. In addition, this root vegetable has high nutritional value, as it contains vitamins, fibers, minerals and other phytochemicals, which can be beneficial for cancer prevention [2][3][4].

Brazil is the fifth largest world producer of carrots (5) and the crop is considered

one of the four most important vegetable crops in the country. In 2017, the world

production of carrot was 42,831,598 tons (6) in Brazil alone, the 2018 harvest reached

about 14,077 kg ha, with emphasis on the state of Minas Gerais (7).

The irrigation of carrots, like most vegetables, increases and improves the quality

of the product, moreover, it is an important factor in determining the production (5).With

an adequate application of the amount of water, the water needs of the harvest are

supplied, reducing the proliferation of pests, diseases and leaching of nutrientes (8).

Hence, irrigation planning and management must be adopted to obtain maximum

efficiency and preserve the carrot's high economic value in the market (9).

In order to favor the reduction of evapotranspiration and, thus, reduce the irrigation

necessary for agricultural crops, some soil coverings can be used. The technique of

covering the soil with organic or inorganic materials forms a physical barrier to limit

evaporation of water from the soil, it also maintains a good soil structure and protect crops

from contamination in contact with the soil (10).

According to (11) soil cover with polyethylene film is still the most used in

vegetables by producers and this is due to the relatively low price of polymer materials

and durability. Despite this, there are several types of paper with potential for use as soil

cover, among which stand out the alternative papers, such as semi-kraft, recycled, paper

for printing newspapers and paper produced from cane straw sugar (12). In this context,

studies related to this technique can make it possible to increase production in a

sustainable way. The objective of this research was to evaluate the biophysical parameters

of carrots grown under different levels of irrigation and different conditions in the soil

cover.

Materials and methods

Experimental site

The experiment was conducted in the Experimental Area of Irrigation and Drainage, belonging to the Department of Agricultural Engineering of the Federal University of Viçosa (DEA / UFV), in Viçosa-MG. Located at 20° 45 'S latitude, 42° 52' W longitude and 648 m altitude. The experiment was conducted between the months of August and November 2019.

The climate of the region, according to Köppen, is of the "Cwa" type, tropical altitude, with rainy summer and dry winter. The experiment was developed between the months of August and November 2019. The soil in the experimental area is classified as Red-Yellow Argisol, with a granulometric distribution of 46% clay, 39% sand and 15% silt. The density of the soil in the layers of 0-0.20, 0.20-0.40m is 1.3 g / cm3. Field capacity is 36.8%, and the wilt point is 19.5% according to the soil water retention curve made in the area.

Plant material and experimental design

The experimental design was in randomized blocks with four replications, in a 5 x 3 factorial scheme, totaling 60 experimental plots. Five percentages of the water capacity of the soil (20, 40. 60, 80 and 100%) and three cultivation environments without cover (control), white colored polyethylene, and biodegradable semi kraft paper.

In the experimental area, 5 seedbed were made with dimensions of 12.0 m x 1.0 m x 0.3 m in length, width and height, respectively. Fertilization, based on soil analysis, was carried out following a fifth approach to the use of correctives and fertilizers from the State of Minas Gerais described by (13)

96   The cultivar used was Brasília, which has high field resistance to leaf burning. At

97   the seedbed, the spacing between rows was 0.30 m and sowing was carried out with 3

98   seeds per hole at 0.10 m deep in the soil, with a spacing of 0.10 m between plants.

99   Thinning was carried out after the culture was established at 0.10 m in height.

Irrigation management and Water consumption

The irrigation levels (20; 40; 60; 80 and 100%) based on the actual water capacity

in the soil, were equivalent to 4.54; 9.04; 13.56; 18.08 and 22.6 mm, respectively. The

drip system used was the irrigation system. The uniformity of water distribution by the

emitters under field conditions was evaluated. Irrigation management was carried out by

tensiometers that was installed at a depth of 0-0.10 and 0.10-0.30 m. The tensimeter

reading was converted to soil moisture through the soil water retention curve, obtained

by the Richards chamber method. The Van Genuchten model (14) was adopted. The

irrigation age calculated for each treatment according to Equação 1.

$$I = \frac{(\theta cc - \theta a) \times Z}{Ie} \ (1)$$

Where, I - irrigation level, mm ; θcc -soil volumetric density with field capacity, $m^3 \ m^{-3}$;

θa - current volumetric soil moisture before irrigation, $m^3 \ m^{-3}$; Z - irrigated soil layer,

mm; Ie - Field irrigation system efficiency, 0.99.

The actual water consumption during the carrot cycle was calculated based on

equation 2 of the soil water balance of (15).

$$WU = (P + I) - (R_0 - Dep + Dr) \ (2)$$

Where, WC is water consumption (mm), P is precipitation (mm), I is the amount of

irrigation water applied (mm), R0 is capillary increase (mm), Dep is the depletion of soil

moisture (mm); Dp is superficial runoff (mm).

In this method, the depletion of soil moisture (Dep) between the sampling intervals

was calculated keeping in mind the amount of irrigation (I) and precipitation (P), if there

is between the intervals and then the integration during the period of cultivation. The R0

was considered null because the water table was more than 15 meters below the surface,

Dp was also assumed to be insignificant because an experimental area is flat.

Soil temperature

125   After thinning the carrots, data on maximum and minimum temperature and thermal

126   amplitude were collected daily. Every 30 minutes, digital sensors, model DS18B20 with

127   an accuracy of $\pm$ 273.5K in the range of 272.9K to + 358K, previously installed in the

128   center of 15 experimental plots, collected the temperature data and stored in dataloggers.

Agronomic variables

The evaluations were carried out in five plants on the central line of each

experimental unit. The number of sheets (units) was counted manually. The leaf

temperature (K) was estimated by a digital infrared thermometer with laser sight, model

ST600, from the INCOTERM® manufacturer ($\pm$ 275.0 K precision and 273.1 K

resolution). During the readings the device was positioned 0,15m away from the leaves.

At harvest, the root length was measured using a millimeter ruler. To measure the

root diameter, a caliper (mm) was used. The fresh mass was determined with the aid of

an analytical balance with a resolution of 0.01 g.

Data analysis

139   The data obtained were subjected to analysis of variance through the F test, using

140   the R software, with the Experimental Designer package. The Tukey test ($P \leq 0.05$) was

141   applied to compare the means. For the regression analysis, the most significant adjustment

142   equation was chosen.

Results and discussion

The water consumption during the carrot cycle in five irrigation depths and three types of cover can be seen in Fig 1. For all irrigation depths, the carrot showed higher water consumption when grown in soil without cover (control).

Fig 1. Carrot water consumption (mm) in situations of percentage of the actual water capacity in the soil (CRA) and soil cover.

The situation of 20% of the CRA (L1) had a higher consumption (33 mm) in an environment with no cover (control).In soil with white polyethylene and semi-paper coverage kraft, there was a saving of 0.45 and 0.68 in water consumption when compared to the control situation. This condition have occurred because the cover provided a decrease in the rate of evaporation in the soil and greater water retention in the soil (16).

As the treatments of polyethylene and semi-kraft paper required less water volume during the whole harvest cycle, when compared to the soil without cover (control), this resulted in a reduction in the water resource applied to the crop. (17) and (12) claim that the use of toppings can save water when growing vegetables.

The coverage with polyethylene had the water consumption of the crop superior to the situation of covering with semi kraft paper. This may be related to the fact that the white plastic covering provides greater conversion of energy from solar radiation, increasing the heat flow in the soil (18), therefore, it increases the temperature of the soil and the transpiration of the plant, which will need more water for the photosynthetic processes (19). (20) claim that paper coverage is efficient in saving water and is it comparable to polyethylene film, hence, it can be a suitable alternative to replace it.

The values of the maximum and minimum temperatures, in the depths of 0.05m, were lower in the conditions of covering of the ground with recyclable semi Kraft paper in comparison to the other treatments (Table 2).

Table 2. Soil temperature at 0.05m depth, grown with carrots at different percentages of the actual water capacity in the soil and ground cover

Cover	Temperature (°K)	Irrigation levels in percentage of CRA				
		20	40	60	80	100
Control test	Average	296,17	296,01	296,28	296,24	295,86
	Maximum	298,54	298,60	298,20	298,93	298,58
	Minimum	293,60	293,68	293,73	293,86	291,63
	Range	4,94	4,93	4,47	5,07	6,95
White polyethylene	Average	295,46	273,00	295,53	295,44	296,08
	Maximum	299,81	299,42	298,15	298,19	298,65
	Minimum	294,05	292,50	294,13	294,13	294,46
	Range	5,75	6,92	4,02	4,06	4,19
Semi kraft paper	Average	296,04	294,87	295,22	295,31	294,77
	Maximum	298,58	297,00	296,91	297,94	296,97
	Minimum	293,60	292,04	292,36	294,11	293,59
	Range	4,97	4,95	4,55	3,83	3,38

Table 2 shows that the highest temperature averages were observed for the control treatment, in all applied irrigation depths. However, for maximum and minimum temperatures, it was observed that there was variation according to the blade used in each treatment. The highest temperatures were obtained in the irrigation depths for 20 and 40% of the CRA combined with soil cover with white polyethylene. Meanwhile, the lowest temperatures were observed in the cultivation with irrigation depths of 40 and 60% of the CRA combined with semi-kraft paper. According to (21) this occurs because the coverage with white polyethylene increases considerably the heat flow in the soil, therefore, it increases the temperature of the soil, meanwhile, the paper is not developed in the same way.

According to (19), this is because the coverage with white polyethylene considerably increases the heat flow in the soil, therefore, it increases the temperature of the soil, while the paper is not developed in the same way. Similar results were found in the lettuce culture by (22). (23) who found that the soil temperature was lower when they

used brown Kraft paper, compared to the soil covered with black polyethylene film and

without coverage. (24) found that the polyethylene film increased the average soil

temperature between 2 and 3º C compared to the soil without cover. (25) working with

the pepper culture, found that the soil cover with polyethylene film increased the soil

temperature around 2 ºC in relation to the conventional weeding system.

(26)in Japan, (27) in the United States, (28) in Vietnam, and (29) in Mexico,

observed that the coverage with black colored polyethylene film provided the highest soil

temperatures. Indeed, when covering the soil, there are interferences in variables such as

soil temperature, humidity, wind, radiation, energy and, consequently, the evaporation

process (30). It is observed that the soil cover does not allow wind and radiation, which

are mainly responsible for the evaporation of water, to reach the soil directly, thus having

an interception of these parameters by the cover used (31).

The use of soil cover allows to reduce the temperature fluctuation and the

evaporative rate of the soils. This can accelerate the development of the crop during the

initial growth stage and promoting the control of weeds (18), (32) and (33)

The soil without cover had an average temperature of 296 ° K, with minimums

around 293 ° C, this is because the soil had a greater conversion of energy from solar

radiation into latent heat, as there is no barrier for water evaporation from the soil. Thus,

the temperature of the soil does not decrease as much as the other environments found in

this study and remain high during the cycle, with little variation in thermal amplitude.

(32) found the greatest variations in thermal amplitude of treatments with plastic soil

cover in relation to organic materials.

The agronomic variables of root length, fresh weight the vegetation index by

Normalized difference (NDVI) and diameter were influenced ($P < 0.05$) by the soil cover

factor (Table 3).

Table 3. Agronomic variables of the carrot (*Daucus carota* L.) submitted to different

soil coverings.

Cover	Root length (cm)	Fresh weight (t ha $^{-1}$)	NDVI	Diameter (cm)
Control test	21,95 a	21,501 b	0,68 a	4,79 c
White polyethylene	19,43 b	26,265 ab	0,51 b	5,81b
Semi kraft paper	20,83 a	28,353 a	0,62 a	6,25a
Significance level	**	**	**	**
CV (%)	8,74	26,06	15,95	7,3

The means followed by the same letters in the column do not differ by the Tukey

test. Significance level: * (P≤0.05), ** (P≤0.01), ns (not significant)

It was observed that the length of the roots is longer in a situation of soil without

cover. However, there is no significant difference between it and the cover with semi kraft

paper. The white polyethylene cover provided the lowest root length values, this may be

related to the fact that the soil cover reduces the harmful effect of spontaneous plants(34)

(35) thereby, probably the carrot grown without cover (control) needs to compete for

water and nutrients.

The fresh weight obtained a lower average when subjected to cultivation without

soil cover, reaching only 21,501 tons per hectare, and a better average for the cultivation

with paper, nevertheless, there was no difference between the three treatments. There are

many reports informing the increase in plant growth and the consequent gains in plant

yield through the use of plastic coverings (26). (36) studying with water deficit and soil

coverings on onion, found that polyethylene improves the recovery of water from the

onion harvest.

The diameter is one of the characteristics of the carrot most appreciated by the

consumer. In this study, the factores both coverages (Table 3) and irrigation levels (Fig

1) influenced the results of this variable in isolation (p<0,01). The coverage using semi

kraft paper obtained the best averages, reaching an average of 6 cm, corroborating with

(37).

The irrigation depths factor shows a quadratic behavior, with a tendency to increase the root when submitted to larger depths (Fig 1). The highlight in this variable is the 100% of the CRA (22.6 mm), as the water in the field capacity provided a balanced environment in the soil-plant-water-atmosphere relationship.

Fig 2. Carrot (*Daucus carota* L.) diameter in percentages of soil water capacity

The Normalized Difference Vegetation Index (NDVI) indicates the nutritional status of the plant in relation to nitrogen (38) . The effects found in this work indicate superior results for the treatment with soil without cover and semi kraft paper (table 3), because the higher the value of NDVI, the greater the growth force of the culture (39). This result indicates that there was a difference in reflectance values between the plastic cover and the other treatments. In addition, the vegetation index by Normalized difference (NDVI) was influenced by the irrigation depths (Fig 2), with a decrease in the index as the percentage of water in the soil increases, with a critical point in 76% of the CRA, allowing a maximum point of 0.67.

Fig 3. Vegetation Index of Normalized Differences (NDVI) in carrots (Daucus carota L.) submitted to percentages of soil water capacity

The number of leaves and the leaf temperature (Figs 3 and 4) were influenced ($P < 0.05$) by the irrigation depths. In the commercial market, there is a niche for the sale of carrot leaves and, considering the response of this experiment, it is observed that the maximum point can be reached in the cultivation of carrots irrigation at 83% of the CRA, the result of which will be approximately 7 leaves per plant. These results are different from the one found by (40), where the number of leaves per plant did not differ significantly in irrigation treatments.

Fig 4. Number of leaves in carrots (Daucus carota L.) submitted to percentages of soil water capacity

The leaf temperature had little variation, being around 291.5 to 293 °K, being lower when submitted to the smaller irrigation depth (Fig 4). This result may have occurred because, when water is limited for the crop, the photosynthesis and transpiration processes become less active, so the maximum rate of carbon assimilation can be inhibited by decreasing stomatal conductance and the leaf temperature becomes lower (41).

Fig 5. Leaf temperature in carrots (Daucus carota L.) submitted to percentages of soil water capacity

The temperature of the leaf determines the concentration or pressure of water vapor within the leaf and therefore determines the driving force of transpiration (42). The difference in leaf temperature in plants with and without stress is based on their water status, stomatal behavior and the loss of latent heat through perspiration. Nevertheless, this whole process varies for each species, depending on the intensity and duration of water stress (43).

Conclusions

The irrigation depth of 60% of the real water capacity of the soil can be used in the production of carrots in order to promote water saving and good crop development.

It is recommended to use soil cover with semi-kraf paper in the cultivation of carrots, as it provides thermal comfort even in situations of water stress and helps in the sustainability of the environment.

Referências

1. Freitas FCL, Almeida MEL, Negreiros MZ, Honorato ARF, Mesquita HC, Silva

SVOF. Periods of Weed Interference in Carrot in Function of Spacing Between

Rows. Planta Daninha. 2009;27(3):473–80.

2.   Li C et al. Serum ␣ -Carotene Concentrations and Risk of Death Among US

Adults. Arch Intern Med. 2011;171(6):507–15.

3.   Chen H, Shao F, Zhang F, Miao Q. Association between dietary carrot intake and

breast cancer. 2018;0(August).

4.   Titcomb TJ, Kaeppler MS, Beatriz S, Cates S, Shannon JM, Simon PW, et al.

Concentrations in Male Mongolian Gerbils Regardless of the Ratio of α - to β -

Carotene When β -Carotene Equivalents Are Equalized. 2019;1–8.

5.   Junior JA de L, Pereira, Geraldo Magela Geisenhoff, Luciano Oliveira da Silva

WG, De Melo ROR, Boas RCV. Economic viability of a drip irrigation system

on carrot crop ** Viabilidade econômica do uso do sistema de irrigação por

gotejamento na cultura da cenoura. Rev Ciências Agrárias. 2013;57:15–21.

6.   Faostat. Área colhida, rendimento e produção nos principais países produtores de

cenoura. Disponível em: <http://faostat.fao.org/>. Acesso em: 9 Janeiro. 2020.

2011.

7.   Boteon M. Hortifruti Brasil. Vol. 53, Centro de Estudos Avançados em

Economia. 2018. 1689–1699 p.

8.   Aleman CC, Marques PAA. Manejo e viabilidade econômica da irrigação no

cultivo dE Calendula officinalis L. Irriga. 2016;Edição Esp:29–37.

9.   Carvalho DF, Neto DH de O, Felix LF, Guerra JGM, Salvador CA. Yield , water

use efficiency , and yield response factor in carrot crop under different irrigation

depths. Ciência Rural. 2016;46:1145–50.

10.   Kasirajan S, Ngouajio M. Polyethylene and biodegradable mulches for

agricultural applications : a review. 2012;(April).

11.   Teófilo TMS, Medeiros JF, Fernandes D, Grageiro L., Tomaz HVQ. E ficiência

no u so da á gua e i nterferência de p lantas d aninhas water use Efficiency and

Weed Interference in Melon Crop under Conventional and No-Tillage Systems.

Planta Daninha. 2012;30(M):547–56.

12.   Freitas AR de J. Potencial do papel no cultivo da alface visando controle de

plantas daninhas, temperatura e perda de água. Viçosa; 2017. (dissertação).

Report No.: 635.52.

13.   Ribeiro AC, Guimarães paulo TG, Alvarez V VH. Recomendações para o uso de

corretivos e fertilizantes em Minas Gerais - 5ª Aproximação [Internet].

Recomendações para o uso de corretivos e fertilizantes em Minas Gerais - 5°

Aproximação. 1999. 359 p. Available from:

http://www.labominas.com.br/userfilesfiles/5-aproximacao.pdf

14.   Genuchten V M. A closed-form equation for predicting the hydraulic

conductivity of unsaturated soils. Soil Sci Soc Am J. 1980;44(5):892–8.

15.   Hanks RJ, Ashcrof GL. Unit 1 Water Quantities. In: water quantities. 1980. p. 1–

2.

16.   Yaghi T, Arslan A, Naoum F. Cucumber (Cucumis sativus, L.) water use

efficiency (WUE) under plastic mulch and drip irrigation. Agric Water Manag

[Internet]. 2013;128:149–57. Available from:

http://dx.doi.org/10.1016/j.agwat.2013.06.002

17.   Chakraborty D, Garg RN, Tomar RK, Singh R, Sharma SK, Singh RK, et al.

Synthetic and organic mulching and nitrogen effect on winter wheat (Triticum

aestivum L .) in a semi-arid environment. Agric Water Manag [Internet].

2010;97(5):738–48. Available from:

http://dx.doi.org/10.1016/j.agwat.2010.01.006

18.   Allen RG, Pereira LS, Raes D, Smith M, Ab W. Crop evapotranspiration -

332   Guidelines for computing crop water requirements - FAO Irrigation and drainage

333   paper 56 By. 1998. 1–15 p.

334   19.   Fan Y, Ding R, Kang S, Hao X, Du T, Tong L. Plastic mulch decreases available

335   energy and evapotranspiration and improves yield and water use efficiency in an

336   irrigated maize cropland. Agric Water Manag [Internet]. 2016; Available from:

337   http://dx.doi.org/10.1016/j.agwat.2016.08.019

338   20.   Silva GH da. Biodegradable mulch of recycled paper reduces water consumption

339   and crop coefficient of pak choi. Sci Hortic (Amsterdam) [Internet].

340   2020;267(October 2019):109315. Available from:

341   https://doi.org/10.1016/j.scienta.2020.109315

342   21.   Fan Y, Ding R, Kang S, Hao X, Du T, Tong L. Plastic mulch decreases available

343   energy and evapotranspiration and improves yield and water use efficiency in an

344   irrigated maize cropland. Agric Water Manag [Internet]. 2017;179:122–31.

345   Available from: http://dx.doi.org/10.1016/j.agwat.2016.08.019

346   22.   Evans KI, Brodic BB, Sis C. Annales agriculturae fenniae. J Agric resarch Cent.

347   1964;3:79–89.

348   23.   Zhang Y, Han JH, Kim GN. Biodegradable mulch film made of starch-coated

349   paper and its effectiveness on temperature and moisture content of soil. Commun

350   Soil Sci Plant Anal. 2008;39(7–8):1026–40.

351   24.   Andrade Júnior VC de, Yuri JE, Nunes UR, Pimenta FL, Matos C de SM de,

352   Florio FC de A, et al. Emprego de tipos de cobertura de canteiro no cultivo da

353   alface. Hortic Bras. 2005;23(4):899–903.

354   25.   Coelho MEH, Freitas FCL, Cunha JLXL, Silva KS, Grangeiro LC, Oliveira JB.

355   Coberturas do solo sobre a amplitude térmica e a produtividade de pimentão.

Planta Daninha. 2013;31(2):369–78.

26.   Hanada T. The effect of mulching and row covers on vegetable production. 1977.

1–23 p.

27.   Ngouajio M, Ernest J. Changes in the Physical , Optical , and Thermal Properties

of Polyethylene Mulches during Double Cropping. 2005;40(1):94–7.

28.   Ramakrishna A, Minh H, Wani SP, Dinh T. Effect of mulch on soil temperature ,

moisture , weed infestation and yield of groundnut in northern Vietnam. F Crop

Res. 2006;95:115–25.

29.   Ibarra-jiménez L, Lira-saldivar RH, Valdez-aguilar LA, Río JL, Lira-saldivar

RH, Valdez-aguilar LA, et al. Colored plastic mulches affect soil temperature and

tuber production of potato. 2011;4710.

30.   Yuri JE, de Resende GM, Costa ND, Mota JH. Cultivo de morangueiro sob

diferentes tipos de mulching. Hortic Bras. 2012;30(3):424–7.

31.   Yang N, Sun ZX, Feng LS, Zheng MZ, Chi DC, Meng WZ, et al. Plastic film

mulching for water-efficient agricultural applications and degradable films

materials development research. Mater Manuf Process [Internet].

2015;30(2):143–54. Available from:

http://dx.doi.org/10.1080/10426914.2014.930958

32.   Braga MB, Marouelli WA, Geraldo MR, Moura MS, Costa ND, Calgaro M, et al.

Coberturas do solo e uso de manta agrotêxtil (TNT) no cultivo do meloeiro.

Hortic Bras. 2017;147–53.

33.   Hou X, Wang F, Han J, Kang S, Feng S. Agricultural and Forest Meteorology

Duration of plastic mulch for potato growth under drip irrigation in an arid region

of Northwest China. Agric For Meteorol. 2010;150:115–21.

34.   Li, Wang ZH, Li SQ, Gao YJ, Tian XH. Effect of plastic sheet mulch, wheat

straw mulch, and maize growth on water loss by evaporation in dryland areas of

China. Agric Water Manag. 2013;116:39–49.

35. Dantas MSM, Grangeiro LC, Medeiros JF de, Cruz CA, Cunha APA da.

Rendimento e qualidade de melancia cultivada sob proteção de agrotêxtil

combinado com mulching plástico. Rev Bras Eng Agrícola e Ambient.

2013;17(8):824–9.

36. Igbadun HE, Ramalan AA, Oiganji E. Effects of regulated deficit irrigation and

mulch on yield , water use and crop water productivity of onion in Samaru ,

Nigeria. Agric Water Manag [Internet]. 2012;109:162–9. Available from:

http://dx.doi.org/10.1016/j.agwat.2012.03.006

37. Gomes DP, Carvalho DF De, Almeida WS De, Oliveira L, Guiherme J, Guerra

M. Organic carrot-lettuce intercropping using mulch and different irrigation

levels. 2014;323–8.

38. Raun WR, Solie JB, Stone ML, Martin KL, Freeman KW, Zhang H, et al. Optical

Sensor - Based Algorithm for Crop Nitrogen Fertilization. Commun Soil Sci

Plant Anal ISSN. 2007;3624:2759–81.

39. Grohs DS, Bredemeier C, Mundstock CM, Poletto N. Modelo para estimativa do

potencial produtivo em trigo e cevada por meio do sensor GreenSeeker. Eng

Agric. 2009;29(1):101–12.

40. Alam, M. S.; Mallik, S. A.; Costa, D. J.; Alam, M. S.; Alam A. Effect of

irrigation on the growth and yield of (Daucus carotassp. sativus) carrot in hill

valley. Bangladesh J Agril Res. 2010;35(June):323–9.

41. Dias DP, Marenco RA. Fotossíntese e fotoinibição em mogno e acariquara em

função da luminosidade e temperatura foliar. Pesq agropec bras. 2007;42(1):305–

11.

42.   Gates DM. Transpiration and leaf temperature. 1968;

43.   Nogueira RJMC, De moraes JAP V., Burity HA, Neto EB. Alterações na

resistência à difusão de vapor das folhas e relações hídricas em aceroleiras

submetidas a déficit de agua. R Bras Fisiol. 2001;13:75–87.

Fig 1. Carrot water consumption (mm) in situations of percentage of the actual water capacity in the soil (CRA) and soil cover.

Fig 2. Carrot (*Daucus carota* L.) diameter in percentages of soil water capacity

Fig 3. Vegetation Index of Normalized Differences (NDVI) in carrots (Daucus carota L.) submitted to percentages of soil water capacity

NDVI = 0.4373 + 0.0061 x - 0.00004 x^2 | R^2 = 0.71

Fig 4. Number of leaves in carrots (Daucus carota L.) submitted to percentages of soil water capacity

Fig 5. Leaf temperature in carrots (Daucus carota L.) submitted to percentages of soil water capacity