Automatic mapping of multiplexed social receptive fields

by deep learning and GPU-accelerated 3D videography

Christian L. Ebbesen[1,2],* & Robert C. Froemke[1,2],*

[1] Skirball Institute of Biomolecular Medicine, Neuroscience Institute, Departments of Otolaryngology,

Neuroscience and Physiology, New York University School of Medicine, New York, NY, 10016, USA.

[2] Center for Neural Science, New York University, New York, NY, 10003, USA.

* Correspondence to: C.L.E. (christian.ebbesen@nyumc.org) or R.C.F. (robert.froemke@med.nyu.edu)

Abstract

Social interactions powerfully impact the brain and the body, but high-resolution descriptions of these

important physical interactions are lacking. Currently, most studies rely on labor-intensive methods such

as manual annotation. Scalable and objective tracking methods are required to understand the neural cir-

cuits underlying social behavior. Here we describe a hardware/software system and analysis pipeline that

combines 3D videography, deep learning, physical modeling, and GPU-accelerated robust optimization,

with automatic analysis of neuronal receptive fields recorded in interacting mice. Our system is capable

of fully automatic multi-animal tracking with minimal errors (including in complete darkness) during

complex, spontaneous social encounters, together with simultaneous electrophysiological recordings. We

capture posture dynamics of multiple unmarked mice with high spatiotemporal precision (~2 mm, 60

frames/s). A generative model revealed the multiplexed 'social receptive field' of neurons in barrel cortex.

This approach could be broadly useful for neurobehavioral studies of multiple animals interacting in com-

plex low-light environments.

Introduction

Objective quantification of natural social interactions is difficult. The majority of our knowledge about

rodent social behavior comes from hand-annotation of videos, yielding ethograms of discrete social be-

haviors such as 'social following', 'mounting', or 'anogenital sniffing'[1]. It is widely appreciated that these

methods are susceptible to experimenter bias and have limited throughput. There is an additional problem

with these approaches, in that manual annotation of behavior yields limited information about movement

kinematics and physical body postures. This shortcoming is especially critical for studies relating neural

activity patterns or other physiological signals to social behavior. For example, neural activity in many

areas of the cerebral cortex are strongly modulated by movement and posture[2,3], and activity profiles in

somatosensory regions can be difficult to analyze without understanding the physics and high-resolution

dynamics of touch. Important aspects of social behavior, from gestures to light touch and momentary

glances can be transient and challenging to observe in most settings, but critical to capturing the details

and changes to social relationships and networks[4,5].

The use of deep convolutional networks to recognize objects in images has revolutionized computer vision,

and consequently, also led to major advances in behavioral analysis. Drawing upon these methodological

advances, several recent publications have developed algorithms for single animal[6–13] and multi-animal

tracking[14–21] . These methods function by detection of key-points in 2D videos, and estimation of 3D

postures is not straightforward in interacting animals, where some form of spatiotemporal regularization

is needed to ensure that tracking is stable and error-free, even when multiple animals are closely interacting.

During mounting or allo-grooming, for example, interacting animals block each other from the camera

view and tracking algorithms can fail. Having a large number of cameras film the animals from all sides

can solve these problems[22,23], but this has required extensive financial resources for equipment, laboratory

space and processing power, which renders widespread use infeasible.

Some recent single[24]- and multi-animal[17–19] tracking methods have bypassed the problem of estimating

the 3D posture of closely interacting animals by training a classifier to replicate human labeling discrete

behavioral categories, such as attack and mounting. This approach is very powerful for automatically

generating ethograms; however, to relating neural data to behavior, lack of detailed information about

movement and posture kinematics of interacting animals can be a critical drawback. In essentially every

brain region, neural activity is modulated by motor signals[25–28] and vestibular signals[2,3,29]. Thus, any ob-

served differences in neural activity between behavioral categories may be related instead to differences

in movements and postures made by the animals in those different categories. To reveal how neural circuits

process body language, touch and other social cues[21] during a social interaction, descriptions of neural

coding must be able to account for these important but complex motor- and posture-related activity pat-

terns or confounds.

In parallel with deep-learning based tracking methods, some studies have used depth-cameras for animal

tracking, by fitting a physical 3D body-model of the animal to 3D data[30–32]. These methods are powerful

because they can explicitly model the 3D movement and poses of multiple animals, throughout the social

interaction. However, due to technical limitations of depth imaging hardware (e.g., frame rate, resolution,

motion blur), to date it has been possible only to extract partial posture information about small and fast-

moving animals, such as lab mice. Consequently, when applied to mice, these methods are prone to track-

ing mistakes when interacting animals get close to each other and the tracking algorithms require contin-

uous manual supervision to detect and correct errors. This severely restricts throughput, making tracking

across long time scales infeasible.

Here we describe a novel system for multi-animal tracking and neuro-behavioral data analysis that com-

bines ideal features from both approaches. Our method fuses physical modeling of depth data and deep

learning-based analysis of synchronized color video to estimate 3D body postures, enabling us to reliably

track multiple mice during naturalistic social interactions. Our method is fully automatic (i.e., quantitative,

scalable, and free of experimenter bias), is based on inexpensive consumer cameras, and is implemented

in Python, a simple and widely used computing language. Our method is capable of tracking the animals

using only infrared video channels (i.e., in visual darkness for mice, a nocturnal species), is self-aligning

and requires only a few hundred labeled frames for training. We combine our tracking method with silicon

probe recordings of single-unit activity in barrel cortex to demonstrate the usefulness of a continuous 3D

posture estimation and an interpretable body model: We implement a full-automatic neural data analysis

pipeline (included along with the tracking code), that yields a population-level map of neural tuning to the

features of a social interaction (social touch, movements, postures, spatial location, etc.) directly from raw

behavior video and raw spike trains.

Results

Raw data acquisition

We built an experimental setup that allowed us to capture synchronized color images and depth images

from multiple angles, while simultaneously recording synchronized neural data (**Fig. 1a**). We used inex-

pensive, state-of-the-art 'depth cameras' for computer vision and robotics. These cameras contain several

imaging modules: one color sensor, two infrared sensors and an infrared laser projector (**Fig. 1b**). Imaging

data pipelines, as well as intrinsic and extrinsic sensor calibration parameters can be accessed over USB

through a C/C++ SDK with Python bindings. We placed four depth cameras, as well as four synchroniza-

tion LEDs around a transparent acrylic cylinder which served as our behavioral arena (**Fig. 1c**).

Each depth camera projects a static dot pattern across the imaged scene, adding texture in the infrared

spectrum to reflective surfaces (**Fig. 1d**). By imaging this highly-textured surface simultaneously with two

infrared sensors per depth camera, it is possible to estimate the distance of each pixel in the infrared image

to the depth camera by stereopsis (by locally estimating the binocular disparity between the textured im-

ages). Since the dot pattern is static and only serves to add texture, multiple cameras do not interfere with

each other and it is possible to image the same scene simultaneously from multiple angles. Simultaneous

capture from all angles is one key aspect of our method, not possible with depth imaging systems that rely

on actively modulated light (such as the Microsoft Kinect system and earlier versions of the Intel Re-

alsense cameras, where multi-view capture requires offset capture times).

Since mouse movement is fast (on a millisecond time scale[33]), it is vital to minimize motion blur in the

infrared images and thus the final 3D data ('point-cloud'). To this end, our method relies on two key

features. First, we use depth cameras where the infrared sensors have a global shutter (e.g., Intel D435)

rather than a rolling shutter (e.g., Intel D415). Using a global shutter reduces motion blur in individual

image frames, but also enables synchronized image capture across cameras. Without synchronization be-

tween cameras, depth images are taken at different times, which adds blur to the composite point-cloud.

We set custom firmware configurations in our recording program, such that all infrared sensors on all four

cameras are hardware-synchronized to each other by TTL-pulses via custom-built, buffered synchroniza-

tion cables (**Fig. 1b**).

We wrote a custom multithreaded Python program with online compression, that allowed us to capture the

following types of raw data from all four cameras simultaneously: 8-bit RGB images (320 x 210 pixels,

60 frames/s), 16-bit depth images (320 x 240 pixels, 60 frames/s) and the 8-bit intensity trace of a blinking

LED (60 samples/s, automatically extracted in real-time from the infrared images). Our program also

captures camera meta-data, such as hardware time-stamps and frame numbers of each image, which allows

us to identify and correct for possible dropped frames. On a standard desktop PC, the recording system

had very few dropped frames and the video recording frame rate and the imaging and USB image transfer

pipeline was stable (**Fig. 1e,f**).

Temporal stability and temporal alignment

In order to relate tracked behavioral data to neural recordings, we need precise temporal synchronization.

Digital hardware clocks are generally stable but their internal speed can vary, introducing drift between

clocks. Thus, even though all depth cameras provide hardware timestamps for each acquired image, for

long-term recordings, across behavioral time scales (hours to days), a secondary synchronization method

is required.

For synchronization to neural data, our recording program uses a USB-controlled Arduino microprocessor

to output a train of randomly-spaced voltage pulses during recording. These voltage pulses serve as TTL

triggers for our neural acquisition system (sampled at 30 kHz) and drive LEDs, which are filmed by the

depth cameras (**Fig. 1a**). The cameras sample an automatically detected ROI to sample the LED state at

60 frames/s, integrating across a full infrared frame exposure (**Fig. 1g**). We use a combination of cross-

correlation and robust regression to automatically estimate and correct for shift and drift between the depth

camera hardware clocks and the neural data. Since we use random pulse trains for synchronization, align-

ment is unambiguous and we can achieve super-frame-rate-precision. In a typical experiment, we esti-

mated that the depth camera time stamps drifted with ~49 µs/min. For each recording, we automatically

estimate and correct for this drift to yield stable residuals between TTL flips and depth frame exposures

(**Fig. 1h**). Note that the neural acquisition system is not required for synchronization and for a purely

behavioral study, we can run the same LED-based protocol to correct for potential shift and drift between

cameras by choosing one camera as a reference.

Detection of body key-points by deep learning

We preprocessed the raw image data to extract two types of information for the tracking algorithm: the

location in 3D in space of body key-points and the 3D point-cloud corresponding to the body surface of

the animals. We used a deep convolutional neural network to detect key-points in the RGB images, and

extracted the 3D point-cloud from the depth images (**Fig. 2a**). For key-point detection (nose, ears, base of

tail, and neural implant for implanted animals), we used a 'stacked hourglass network'[34]. This type of

encoder-decoder network architecture combines residuals across successive upsampling and downsam-

pling steps to generate its output, and has been successfully applied to human pose estimation[34] and limb

tracking in immobilized flies[35] (**Fig. 2b,** details of network architecture in **Supplementary Fig. 1**).

We used back-propagation to train the network to output four 'target maps', each indicating the pseudo-

posterior probability of each type of key-point, given the input image. The target maps were generated by

manually labeling the key-points in training frames, followed by down-sampling and convolution with

Gaussian kernels (**Fig. 2c**, 'targets'). We selected the training frames using image clustering to avoid re-

dundant training on very similar frames[8]. The manual key-point labeling can be done with any labeling

software. We customized a version of the lightweight, open source labeling GUI from the 'DeepPoseKit'

package[8] for the four types of key-points, which we provide as supplementary software (**Supplementary**

Fig. 2).

In order to improve key-point detection, we used two additional strategies. First, we also trained the net-

work to predict 'affinity fields'[36], which have been shown to improve human[36] and animal[8,15] body key-

point tracking. We used '1D' affinity fields[8], generated by convolving the path between labeled body key-

points that are anatomically connected in the animal. With our four key-points, we added seven affinity

fields (e.g., 'nose-to-ears', 'nose-to-tail'), that together form a skeletal representation of each body (**Fig.**

2c, 'affinity fields'). Thus, from three input channels (RGB pixels), the network predicts eleven output

channels (**Fig. 2d**). As the stacked hourglass architecture involves intermediate prediction, which feeds

back into subsequent hourglass blocks (repeated encoding and decoding, **Fig 2b**), prediction of affinity

fields feeds into downstream predictions of body key-points. This leads to improvement of downstream

key-point predictions, because the affinity fields give the network access to holistic information about the

body. The intuitive probabilistic interpretation is that instead of simply asking questions about the key-

points (e.g., 'do these pixels look like an ear?'), we can increase predictive accuracy by considering the

body context (e.g., 'these pixels sort of look like an ear, and those pixels sort of look like a nose – but does

this path between the pixels also look like the path from an ear to a nose?').

The second optimization approach was image data augmentation during training[37]. Instead of only training

the network on manually-labeled images, we also trained the network on morphed and distorted versions

of the labeled images (**Supplementary Fig. 3**). Training the network on morphed images (e.g., rotated or

enlarged), gives a similar effect to training on a much larger dataset of labeled images, because the network

then learns to predict many artificially generated, slightly different views of the animals. Training the

network on distorted images is thought to reduce overfitting on single pixels and reduce the effect of

motion blur[37].

Using a training set of 526 images, and by automatically adjusting learning rate during training, the net-

work was well-trained (plateaued) within one hour of training on a standard desktop computer (**Fig. 2e**),

yielding good predictions of both body key-points and affinity fields (**Fig. 2f**).

All-infrared tracking

As mice are nocturnal, we also developed a version of the tracking software that only relies on the infrared

video stream (i.e., in visual darkness for the mice). This facilitates the study of naturalistic social interac-

tions in darkness. For 'all-infrared' experiments, the arena was lit with infrared LED lamps, and the soft-

ware was changed to save only the infrared images (16-bit, 640 x 448, 60 frames/s). Detection of body

key-points by deep learning from in these images are made difficult by the prominent infrared laser dot

pattern (**Fig. 2g**). We trained the deep neural network to ignore the dot pattern by using a data augmenta-

tion strategy. We recorded and labeled body parts in a training data set (720 images), where the infrared

laser was turned off, and trained the network on labeled images augmented with a probabilistically gener-

ated noise pattern of white dots with a similar size and density to the 'real' laser pattern (**Fig. 2h**). A

network trained on these data allowed us to successfully detect body key-points in real images with the

infrared laser turned on (**Fig. 2i**).

To optimize the network architecture and estimate pseudo-posterior probability cutoffs in the network

output maps with a good tradeoff between missed body key-points, false positives and network training/in-

ference time, we profiled the network across the number of hourglass stacks (**Supplementary Figs. 4, 5**),

with and without various types of training data augmentation (**Supplementary Fig. 6**), and with and with-

out part affinity fields (**Supplementary Fig. 7**). Based on the hand-labeled validation data, we found that

3 hourglass stacks and a pseudo-posterior probability cutoff of 0.5 led to good performance (**Supplemen-**

tary Figs. 4-7).

Pre-processing of 3D video

By aligning the color images to the depth images, and aligning the depth images in 3D space, we could

assign three dimensional coordinates to the detected key-points. We pre-processed the depth data to ac-

complish two goals. First, we wanted to align the cameras to each other in space, so we could fuse their

individual depth images to one single 3D point-cloud. Second, we wanted to extract only points corre-

sponding to the animals' body surfaces from this composite point-cloud.

To align the cameras in space, we filmed the trajectory of a sphere that we moved around the behavioral

arena. We then used a combination of motion filtering, color filtering, smoothing, and thresholding to

detect the location of the sphere in the color frame, extracted the partial 3D surface from the aligned depth

data, and used a robust regression method to estimate the center coordinate (**Fig. 3a**). This procedure

yielded a 3D trajectory in the reference frame of each camera (**Fig. 3b**) that we could use to robustly

estimate the transformation matrices needed to bring all trajectories into the same frame of reference (**Fig.**

3c). This robust alignment is a key aspect of our method, as errors can easily be introduced by moving the

sphere too close to a depth camera or out of the field of view during recording (**Fig. 3b,c**, arrow). After

alignment, the median camera-to-camera difference in the estimate of the center coordinate of the 40-mm-

diameter sphere was only 2.6 mm across the entire behavioral arena (**Fig. 3d,e**).

We used a similar robust regression method to automatically detect the base of the behavioral arena. We

detected planes in composite point-cloud (**Fig. 3f**) and used the location and normal vector, estimated

across 60 random frames (**Fig. 3g**), to transform the point-cloud such that the base of the behavioral arena

laid in the *xy*-plane (**Fig. 3h**). To remove imaging artifacts stemming from light reflection and refraction

due to the curved acrylic walls, we automatically detected the location and radius of the acrylic cylinder

(**Fig. 3i**). With the location of both the arena base and the acrylic walls, we used simple logic filtering to

remove all points associated with the base and walls, leaving only points inside the behavioral arena (**Fig.**

3j). Note that if there is no constraint on laboratory space, an elevated platform can be used as a behavioral

arena, eliminating imaging artifacts associated with the acrylic cylinder.

Loss function design

The pre-processing pipeline described above takes color and depth images as inputs, and outputs two types

of data: a point-cloud, corresponding to the surface of the two animals, and the 3D coordinates of detected

body key-points (**Fig. 4a, Supplementary Video 1**). To track the body postures of interacting animals

across space and time, we developed an algorithm that incorporates information from both data types. The

basic idea of the tracking algorithm is that for every frame, we fit the mouse bodies by minimizing a loss

function of both the point-cloud and key-points, subject to a set of spatiotemporal regularizations.

For the loss function, we made a simple parametric model of the skeleton and body surface of a mouse.

The body model consists of two prolate spheroids (the 'hip ellipsoid' and 'head ellipsoid'), with dimen-

sions based on an average adult mouse (**Fig. 4b**). The head ellipsoid is rigid, but the hip ellipsoid has a

free parameter (s) modifying the major and minor axes to allow the hip ellipsoids to be longer and narrower

(e.g., during stretching, running, or rearing) or shorter and wider (e.g., when still or self-grooming). The

two ellipsoids are connected by a joint that allows the head ellipsoid to turn left/right and up/down within

a cone corresponding to the physical movement limits of the neck.

Keeping the number of degrees of freedom low is vital to make loss function minimization computation-

ally feasible[38]. Due to the rotational symmetry of the ellipsoids, we could choose a parametrization with

8 degrees of freedom per mouse body: the central coordinate of the hip ellipsoid (x, y, z), the rotation of

the major axis of the hip ellipsoid around the y- and z-axis (β, γ), the left/right and up/down rotation of the

head ellipsoid (θ, φ), and the stretch of the hip ellipsoids (s). For the implanted animal, we added an

additional sphere to the body model, approximating the surface of the head-mounted neural implant (**Fig.**

4b). The sphere is rigidly attached to the head ellipsoid and has one degree of freedom; a rotational angle

(ϕ) that allows the sphere to rotate around the head ellipsoid, capturing head tilt of the implanted animal.

Thus, in total, the joint pose (the body poses of both mice) was parametrized by only 17 variables.

To fit the body model, we adjusted these parameters to minimize a weighted sum of two loss terms: *(i)*

The shortest distance from every point in the point-cloud to body model surface. *(ii)* The distance from

detected key-points to their corresponding location on the body model surface (e.g., nose key-points near

the tip of one of the head ellipsoids, tail key-points near the posterior end of a hip ellipsoid).

We then used several different approaches for optimizing the tracking. First, for each of the thousands of

point in the point-cloud, we needed to calculate the shortest distance to the body model ellipsoids. Calcu-

lating these distances exactly is not computationally feasible, as this requires solving a six-degree polyno-

mial for every point[39]. As an approximation, we instead used the shortest distance to the surface, along a

path that passes through the centroid (**Supplementary Fig. 8a,b**). Calculating this distance could be im-

plemented as pure tensor algebra[40], which could be executed efficiently on a GPU in parallel for all points

simultaneously. Second, to reduce the effect of imaging artifacts in the color and depth imaging (which

can affect both the point-cloud or the 3D coordinates of the key-points), we clipped distance losses at 3

cm, such that distant 'outliers' do contribute and not skew the fit (**Supplementary Fig. 8c**). Third, because

pixel density in the depth images depends on the distance from the depth camera, we weighed the contri-

bution of each point in the point-cloud by the squared distance to the depth camera (**Supplementary Fig.**

8d). Fourth, to ensure that the minimization does not converge to unphysical joint postures (e.g., where

the mouse bodies are overlapping), we added a penalty term to the loss function if the body models overlap.

Calculating overlap between two ellipsoids is computationally expensive[41], so we computed overlaps be-

tween implant sphere and spheres centered on the body ellipsoids with a radius equal to the minor axis

(**Supplementary Fig. 8f**). Fifth, to ensure spatiotemporal continuity of body model estimates, we also

added a penalty term to the loss function, penalizing overlap between the mouse body in the current frame,

and other mouse bodies in the previous frame. This ensures that the bodies do not switch place, something

that could otherwise happen if the mice are in joint poses with certain mirror symmetries (**Supplementary**

Fig. 8g,h).

GPU-accelerated robust optimization

Minimizing the loss function requires solving three major challenges. The first challenge is computational

speed. The number of key-points and body parts is relatively low (~tens), but the number of points in the

point-cloud is large (~thousands), which makes the loss function computationally expensive. For minimi-

zation, we need to evaluate the loss function multiple times per frame (at 60 frames/s). If loss function

evaluation is not fast, tracking becomes unusably slow. The second challenge is that the minimizer has to

properly explore the loss landscape within each frame and avoid local minima. In early stages of develop-

ing this algorithm, we were only tracking interacting mice with no head implant. In that case, for the small

frame-to-frame changes in body posture, the loss function landscape was nonlinear, but approximately

convex, so we could use a fast, derivative-based minimizer to track changes in body posture (geodesic

Levenberg-Marquardt steps[38]). For use in neuroscience experiments, however, one or more mice might

carry a neural implant for recording or stimulation. The implant is generally at a right angle and offset

from the 'hinge' between the two hip and head ellipsoids, which makes the loss function highly non-

convex[42]. The final challenge is robustness against local minima in state space. Even though a body pos-

ture minimizes the loss in a single frame, it might not be an optimal fit, given the context of other frames

(e.g., spatiotemporal continuity, no unphysical movement of the bodies).

To solve these three challenges – speed, state space exploration, and spatiotemporal robustness – we de-

signed a custom GPU-accelerated minimization algorithm, which incorporates ideas from annealed parti-

cle filters[43] and online Bayesian filtering (**Fig. 4c**). To maximize computational speed, the algorithm was

implemented as pure tensor algebra in Pytorch, a high-performance GPU computing library[44]. Annealed

particle filters are suited to explore highly non-convex loss surfaces[43], which allowed us to avoid local

minima within each frame. Between frames, we used online filtering, to avoid being trapped in low-prob-

ability solutions given the context of the preceding tracking. For every frame, we first proposed the state

of the 17-parameters using a recursive least-squares ('RLS') filter bank trained on preceding frames. After

particle filter-based loss function minimization within a single frame, we updated the RLS filter bank, and

proposed a particle filter starting point for the next frame (**Fig. 4d-e**).

The 'two-layer' tracking strategy (particle filter within frames and RLS filter between frames) has three

major advantages. First, by proposing a solution from the RLS bank, we often already start the loss func-

tion minimization close to the new minimum. Second, if the RLS filter deems that the fit for a single frame

is unlikely (an outlier), based on the preceding frames, this fit will only weakly update the filter bank, and

thus only weakly perturb the upcoming tracking. This gives us a convenient way to balance the information

provided by the fit of a single frame, and the 'context' provided by previous frames. Third, the RLS filter-

based approach is only dependent on previously tracked frames, not future frames. This is in contrast to

other approaches to incorporating context that rely on versions of backwards belief propagation[5,16,35]. Note

that since our algorithm only relies on past data for tracking, it is possible – in future work – to optimize

our algorithm for real-time use in closed-loop experiments.

For each recording, we first automatically initiated the tracking algorithm: We automatically scanned for-

ward in the video to find a frame, where the mice were well separated (assessed by *k*-means clustering of

the 3D positions of the body key-points into two clusters, and by requiring that the 'cross-mouse' cluster

distance is at least 5 cm (**Supplementary Fig. 9**). From this starting point, we explored the loss surface

with 200 particles (**Fig. 4d**). We generated the particles by perturbing the proposed minimum by quasi-

random, low-discrepancy sampling[45] (**Supplementary Fig. 10**). We exploited the fact that the loss func-

tion structure allowed us to execute several key steps in parallel, across multiple independent dimensions,

and implemented these calculations as vectorizes tensor operations. This allowed us to leverage the power

of CUDA kernels for fast tensor algebra on the GPU[44]. Specifically, to efficiently calculate the point-cloud

loss (shortest distance from a point in the point-cloud to the surface of a body model), we calculated the

distance to all five body model spheroids for all points in the point-cloud and for all 200 particles, in

parallel (**Fig. 4c**). We then applied fast minimization kernels across the two body models, to generate a

smallest distance to either mouse, for all points in the point cloud. Because the mouse body models are

independent, we only had to apply a minimization kernel to calculate the smallest distance, for every point,

to 40,000 (200 x 200) joint poses if the two mice. These parallel computation steps are a key aspect of our

method, which allows our tracking algorithm to avoid the 'curse of dimensionality', by not exploring a

17-dimensional space, but rather explore the intersection of two independent 8-dim and 9-dim subspaces

in parallel. We found that our GPU-accelerated implementation of the filter increased the processing time

of a single frame by more than an order of magnitude compared to a fast CPU (e.g. ~16-fold speed increase

for 200 particles, **Fig. 4f**).

Tracking algorithm performance

To ensure that the tracking algorithm did not get stuck in suboptimal solutions, we forced the particle filter

to explore a large search space within every frame (**Supplementary Fig. 11a-c**). In successive iterations,

we gradually made perturbations to the particles smaller and smaller by annealing the filter[43]), to approach

the minimum. At the end of each iteration, we 'resampled' the particles by picking the 200 joint poses

with the lowest losses in the 200-by-200 matrix of losses. This 'top-k' resampling strategy has two ad-

vantages. First, it can be done without fully sorting the matrix[46], the most computationally expensive step

in resampling[47]. Second, it provides a type of 'importance sampling'. During resampling, some poses in

the next iteration might be duplicates (picked from the same row or column in the 200-by-200 loss matrix.),

allowing particles in each subspace to collapse at different rates (if the particle filter is very certain about

one body pose, but not the other, for example).

By investigating the performance of the particle filter across iterations, we found that the filter generally

converged sufficiently within five iterations (**Supplementary Fig. 11d, Supplementary Video 2**) to pro-

vide good tracking across frames (**Supplementary Fig. 11e**). In every frame, the particle filter fit yields a

noisy estimate of the 3D location of the mouse bodies. The transformation from the joint pose parameters

(e.g., rotation angles, spine scaling) to 3D space is highly nonlinear, so simple smoothing of the trajectory

in pose parameter space would distort the trajectory in real space. Thus, we filtered the tracked trajectories

by a combination of Kalman-filtering and maximum likelihood-based smoothing[48,49] and 3D rotation

smoothing in quaternion space[50] (**Supplementary Fig. 12, Supplementary Video 3**).

Representing the joint postures of the two animals with this parametrization was highly data efficient,

reducing the memory footprint from ~3.7 GB/min for raw color/depth image data, to ~0.11 GB/min for

pre-processed point-cloud/key-point data to ~1 MB/min for tracked body model parameters. On a regular

desktop computer with a single GPU, we could do key-point detection in color image data from all four

cameras in ~2x real time (i.e., it took 30 minute to process a 1 hr experimental session). Depth data pro-

cessing (point-cloud merging and key-point deprojection) ran at ~0.7x real time, and the tracking algo-

rithm ran at ~0.2x real time (if the filter uses 200 particles and 5 filter iterations per frame). Thus, for a

typical experimental session (~ hours), we would run the tracking algorithm overnight, which is possible

because the code is fully automatic.

Error detection

Error detection and correction is a critical component of behavioral tracking. Even if error rates are nom-

inally low, errors are non-random, and errors often happen exactly during the behaviors in which we are

most interested: interactions. In multi-animal tracking, two types of tracking error are particularly fatal as

they compound over time: identity errors and body orientation errors (**Supplementary Fig. 13a**). In con-

ventional tracking approaches using only 2D videos, it is often difficult to correctly track identities when

interacting mice are closely interacting, allo-grooming, or passing over and under each other. Although

swapped identities can be corrected later once the mice are well-separated again, this still leaves individual

behavior during the actual social interaction unresolved[5,16]. We found that our tracking algorithm was

robust against both identity swaps (**Supplementary Fig. 13b-e**) and body direction swaps (**Supplemen-**

tary Fig. 14). This observation agrees with the fact that tracking in 3D space (subject to our implemented

spatiotemporal regularizations) should in principle allow better identity tracking. In full 3D space it is

easier to determine who is rearing over whom during an interaction, for example.

To test our algorithm for subtler errors, we manually inspected 500 frames, randomly selected across an

example 21-minute recording session. In these 500 frames, we detected only a single tracking mistake,

corresponding to 99.8% correct tracking (**Supplementary Fig. 15a**). The identified tracking mistake was

visible as a large, transient increase in the point-cloud loss function (**Supplementary Fig. 15b**). After the

tracking mistake, the robust particle filter quickly recovered to correct tracking again (**Supplementary**

Fig. 15c). By detecting such loss function anomalies, or by detecting 'unphysical' postures or movements

in the body models, potential tracking mistakes can be automatically 'flagged' for inspection (**Supple-**

mentary Fig. 15c,d). After inspection, errors can be manually corrected or automatically corrected in

many cases, for example by tracking the particle filter backwards in time after it has recovered. As the

algorithm recovers after a tracking mistake, it is generally unnecessary to actively supervise the algorithm

during tracking, and manual inspection for potential errors can be performed after running the algorithm

overnight. We provide a GUI for viewing and quality control of tracked behavior (raw data, body skeleton,

ellipsoid surfaces and time trajectory) running in an interactive Jupyter notebook (**Supplementary Fig.**

2b, Supplementary Video 5).

Automated analysis of movement kinematics and social events

As a validation of our tracking method, we demonstrate that out methods can automatically extract both

movement kinematics and behavioral states (movement patterns, social events) during spontaneous social

interactions. Some unsupervised methods for discovering structure and states in behavioral data do not

rely on an explicit body model of the animal, and instead use statistical methods to detect behavioral states

directly from tracked features[6,33,51–53]. In an alternative approach, some supervised methods label behav-

ioral events of interest by hand on training data, and then train a classifier to find similar events in unla-

beled data[17–19] . Both of these types of analysis are compatible with our method (e.g., by running directly

on the time series data of the 17 dimensions that parametrize the body models of the two animals, **Sup-**

plementary Fig. 11). Our tracking system yields an easily interpretable 3D body model of the animals,

which makes two additional types of analyses straightforward as well: First, we can easily define 3D body

postures or multi-animal postures of interest as templates[16,30]. Second, we can use unsupervised methods

to discover behavioral states in the 3D reference frame of the animal's own body, making these models

and states straightforward to interpret and 'sanity check' (manually inspect for errors).

To demonstrate posture-template-based analysis, we defined social behaviors of interest as templates and

matched these templates to tracked data. We know that anogenital sniffing[54] and nose-to-nose touch[55] are

prominent events in rodent social behavior, so we designed a template to detect these events. In this tem-

plate, we exploited the fact that we could easily calculate both body postures and movement kinematics,

in the reference frame of each animal's own body. For every frame, we first extracted the 3D coordinates

of the body model skeleton (**Supplementary Fig. 12a**). From these skeleton coordinates, we calculated

the position (**Fig. 5a**) and a three-dimensional speed vector for each mouse ('forward speed', along the

hip ellipsoid, 'left speed' perpendicular the body axis and 'up speed' along the z-axis; **Fig. 5b**). We also

calculated three instantaneous 'social distances', defined as the 3D distance between the tip of each ani-

mal's noses ('nose-to-nose'; **Fig. 5b**), and from the tip of each animal's nose to the posterior end of the

conspecific's hip ellipsoid ('nose-to-tail'; **Fig. 5b**). From these social distances, we could automatically

detect when the mouse bodies were in a nose-to-nose or a nose-to-tail configuration (**Fig. 5c**). It is straight-

forward to further subdivide these social events by body postures and kinematics, in order to separate

stationary nose-to-tail configurations (anogenital sniffing/grooming) and nose-to-tail configurations dur-

ing locomotion (social following).

To demonstrate unsupervised behavioral state discovery, we used GPU-accelerated probabilistic program-

ming[56] and state space modeling to automatically detect and label movement states. To discover types

locomotor behavior, we fitted a 'sticky' multivariate hidden Markov model[57] to the two components of

the speed vector that lie in the *xy*-plane (**Supplementary Fig. 16a-h**). With five hidden states, this model

yielded interpretable movement patterns that correspond to known mouse locomotor 'syllables': resting

(no movement), turning left and right, and moving forward at slow and fast speeds (**Fig. 5d**). Fitting a

similar model with three hidden states to the z-component of the speed vector (**Supplementary Fig. 16i-**

n) yielded interpretable and known 'rearing syllables': rest, rearing up and ducking down (**Fig. 5e**). Using

the maximum *a posteriori* probability from these fitted models, we could automatically generate locomo-

tor ethograms and rearing ethograms for the two mice (**Fig. 5b**).

In line with previous observations, we found that movement bouts were short (medians,

rest/left/right/fwd/fast-forward: 0.83/0.50/0.52/0.45/0.68 s, a 'sub-second' timescale[33]). In the locomotion

ethograms, bouts of rest were longer than bouts of movement (all $p < 0.05$, Mann-Whitney U-test; **Fig. 5f**)

and bouts of fast forward locomotion was longer than other types of locomotion (all $p < 0.001$, Mann-

Whitney U-test; **Fig. 5f**). In the rearing ethograms, the distribution of rests was very wide, consisting of

both long (~seconds) and very short (~tenths of a second) periods of rest (**Fig. 5g**). As expected, by plotting

the rearing height against the duration of rearing syllables, we found that short rests in rearing were asso-

ciated with standing high on the hind legs (the mouse rears up, waits for a brief moment before ducking

back down), while longer rests happened when the mouse was on the ground ('rearing' and 'crouching',

Fig. 5h). Like the movement types and durations, the transition probabilities from the fitted hidden Mar-

kov models were also in agreement with known behavioral patterns. In the locomotion model, for example,

the most likely transition from "rest" was to "slow forward". From "slow forward", the mouse was likely

to transition to "turning left", "fast forward" or "turning right", it was unlikely to transition directly from

"fast forward" to "rest" or from "turning left" to "turning right, and so on (**Supplementary Fig. 16o,p**).

Automatic measurement of firing rate modulations during social touch

By combining our tracking system with silicon-probe recording of single unit activity, we could automat-

ically measure how neural activity is modulated during social interactions. As proof-of-concept for our

system, we implanted a male mouse with a 32-channel silicon probe electrode in barrel cortex (the primary

whisker representation in somatosensory cortex). In an example experiment, we simultaneously recorded

31 single units in barrel cortex while tracking the behavior of the implanted mouse interacting with a male

and a female conspecific for 20 minutes each. We then used the posture-template-based analysis to detect

three types of social touch events: nose-to-nose touch ("Nose ↔ Nose"), the implanted animal touching

the partner's anogenital region with its whiskers ("Nose0 → Tail1") and the partner animal touching the

implanted animal's anogenital region with its whiskers ("Nose1 → Tail0", **Fig. 6a**). The automatic pos-

ture-template-based analysis confirmed[58] that the duration of social touch events and inter-touch-intervals

spanned multiple orders of magnitude (from short millisecond touch events to longer touch events lasting

multiple seconds, **Fig 6b-d**).

Using a 'classic' peri-stimulus time histogram-based analysis, we found several single units that had a

significant firing modulation at the time of the detected social touch events (example neurons shown in

Fig. 6e, top row, labeled "naïve PSTH"). The firing rate modulations detected in the "naïve" approach

were surprisingly small (only a small 'bump' in the PSTH at the time of touch), and much smaller than

observed in 'classic' barrel cortex studies, where a controlled whisker stimulus is presented[59]. We won-

dered if the magnitude of firing rate modulation appeared small in the PSTHs, because during un-trained

and self-initiated behavior, the detected touch events occurred in close temporal proximity and/or were

overlapping with other touch events and postural changes[58]. To test the possibility that larger effects sizes

were masked by other touch events occurring in close temporal proximity, we also computed PSTHs where

we only included social touch events where no other social touch event was detected in the 'baseline'

period (4 seconds before the social touch). In these PSTHs with a "cleaned" baseline (**Fig. 6e,** bottom row,

labeled "cleaned PSTH"), we both observed a larger proportion of neurons with a significant change in

firing rate (**Fig. 6f**) and a larger effect size compared to the naïve PSTHs (**Fig. 6g**, the distributions of

effect sizes in the cleaned PSTH are "wider"). For example, the third neuron shown in **Figure 6e** showed

no firing rate modulation in the naïve PSTH, but instead showed a large, highly statistically significant

firing rate decrease around whisker touch in the "cleaned" PSTH.

Fully automatic mapping of 'social receptive fields'

Cleaning the PSTHs (by controlling for only three types of social touch) increased our estimates of the

magnitude of firing rate modulations associated with social touch events. However, a PSTH-based analysis

strategy has inherent drawbacks when analyzing naturalistic behavior. During free behavior, touch, move-

ment and postural changes happen simultaneously, as continuous and overlapping variables. Furthermore,

in line with "vicarious" somatosensory responses reported in human somatosensory cortex[60] and barrel

cortex responses observed just before touch[61], barrel cortex neurons may be related to the behavior of the

partner animal, in a kind of "mirror neuron"-like response.

To deal with these challenges, we drew inspiration from discovery of multiplexed spatial coding in hip-

pocampal circuits[62] and developed a fully-automatic python pipeline that can automatically discover 'so-

cial' receptive fields. Our tracking method is able to recover the 3D posture and head direction of both

animals: The head direction of the implanted animal was given by the skeleton of the body model (the

implant is fixed to the head). For computational efficiency, we exploited the rotational symmetry of the

body model of the non-implanted partner to decrease the dimensionality of the search space during track-

ing (**Fig. 4c**) and used the 3D coordinates of the detected 'ear' key-points to infer the 3D head direction

of the partner (**Supplementary Figs. 17,18**).

Using the full 3D body model of both animals, we designed our analysis pipeline to automatically extract

45 continuous features that might be associated with firing rate changes in a social interaction: social

"between-animal" features (nose-to-nose distance, nose-to-partner's-genitals distance, relative orientation

of the partner with respect to the implanted animal, and a temporal derivative of the distance between the

center of the two hip ellipsoids that measures if the animals are moving towards each other or away from

each other, **Fig. 7a**), postural features (head yaw/pitch/roll, etc.), spatial features (to detect 'spatial' activity,

such as place fields, border or head-direction activity), movement features (temporal derivatives of the

running trajectory, temporal derivatives of posture angles, etc.), and posture, space and movement features

of the partner animal (**Fig. 7b, Supplementary Fig. 19a**, detailed feature table in Methods).

We assumed the following generative model of the observed neuronal spike trains[62]: A neuron's spike

train is generated by a Poisson process, and the rate of this Poisson process is determined by a linear

combination of the behavioral predictors, each associated with their own tuning curve (**Fig. 7c**). To deter-

mine what behavioral features significantly contribute to the firing rate modulation of a neuron, and the

associated tuning curves, we used a model comparison approach: Starting from a null model where the

observed spikes are simply generated by a Poisson process with a constant rate, we iteratively added pre-

dictors that passed a cross-validated significance criterion (a significant increase in likelihood compared

to a simpler model). The tuning curves were regularized to be smooth and allowed to be re-fit with each

additional predictor added to the multiplexed code (details in Methods).

Using this analysis approach, we found several neurons with a multiplexed encoding of features of the

social interactions (**Fig. 7d-e**). Because of the 3D body models, the discovered neural coding schemes

were straightforward to interpret and compare to expected touch-related response patterns in barrel cor-

tex[59]. For example, the example neuron shown in **Fig. 7d** is strongly modulated by social facial touch

(strongly tuned to a low nose-to-nose distance) and strongly lateralized (the neuron is strongly tuned to

orientation angle, with a peak at $\sim -\pi/2$, i.e., when the partner is on the contralateral side of the animal's

face, relative to the implanted recording electrode). The example neuron shown in **Fig. 7e** was also

strongly tuned to social facial touch (tuned to a low nose-to-nose distance), was strongly tuned to a positive

head roll (i.e., when the head is turned such that the whisker field contralateral to the recording electrode

is in contact with the floor) and was strongly tuned to a positive temporal derivative of the hip ellipsoid

yaw (when the animal is running counterclockwise, e.g., along the edge of the arena, such that the contra-

lateral whisker field is brushing against the arena wall or other obstacles). Across the population, we found

that the neurons overwhelmingly encoded whisker touch and orientation angle (lateralization), and the

posture and movements of the implanted animal, but not the partner animal (**Fig. 7f**).

Mapping the network topology of social responses

To map how neurons across the population might also be tuned to features of social interactions, we ex-

tracted the estimated neural tuning curves of all features that were encoded by at least 4 neurons (**Fig. 8a**).

For some features, there was a clear pattern across the population, in line with known response patterns in

barrel cortex[59]: All neurons that were modulated by social touch increased their firing rate during touch

(tuned to a low nose-to-nose and nose-to-tail distance), were tuned to touch contralateral to the implanted

electrode (tuning peak at orientation angle $\approx -\pi/2$), and decreased firing rate during higher locomotion

speeds (negatively correlated with forward speed). For the remaining movement and posture features, the

tuning was more heterogeneous across the population (**Fig. 8a**).

Finally, our automatic tracking and tuning curve estimation pipeline makes it straightforward to determine

how features might be multiplexed together in the same neurons. In our example session, we found that

52% of the neurons encoded at least one behavioral feature, with a median number of five encoded features

(**Fig. 8b**). Using all neurons that encoded at least one feature, we computed a population "co-encoding

matrix", where the entries of the matrix is the probability that two features are encoded by the same neuron

(**Fig. 8c, Supplementary Fig. 19b**). This co-encoding matrix was structured, such that there was a large

overlap between neurons that encode nose-to-nose touch, neurons that encode nose-to-partner-genital

touch and neurons that had lateralized responses (modulated by the relative orientation angle of the ani-

mals, preferring touch to the contralateral whisker field, relative to the implanted recording electrode[59],

Fig. 8d). The co-encoding matrix specified a network graph of encoded features (**Fig. 8e**), which would

then be amenable to various methods of network topology analysis (e.g., locality, clustering, subgraph

motifs, etc.). Thus, our fully-automatic pipeline enables direct connections from raw behavioral videog-

raphy and spike train recordings to higher-order statistics about how features of a social interaction are

mapped onto a neural population during naturalistic behavior.

Discussion

We combined 3D videography, deep learning and GPU-accelerated robust optimization to estimate the

posture dynamics of multiple freely-moving mice, engaging in naturalistic social interactions. Our method

is cost-effective (requiring only inexpensive consumer depth cameras and a GPU), has high spatiotemporal

precision, is compatible with neural implants for continuous electrophysiological recordings, and tracks

unmarked animals of the same coat color (e.g., enabling behavioral studies in transgenic mice). Our

method is fully unsupervised, which makes the method scalable across multiple PCs or GPUs. Unsuper-

vised tracking allows us to investigate social behavior across long behavioral time scales beyond what is

feasible with manual annotation, in order to elucidate developmental trajectories, dynamics of social learn-

ing, or individual differences among animals[63,64], among other types of questions. Finally, our method

uses no message-passing from future frames, but only relies on past data, which makes the method a

promising starting point for real-time tracking. A major next step for future work is to apply such algo-

rithms to animal behavior in different conditions. For example, the algorithm can easily be adapted to

track other animal body shapes such as juvenile mice or other species, or movable, deformable objects

that might be important for foraging or other behaviors in complex environments.

Multi-animal body tracking and mirror neurons

In social interactions, rodents respond to the behavior of conspecifics, but we are only beginning to dis-

cover how the rodent brain encodes complex features such as gaze direction or body postures of oth-

ers[3,21,65,66]. Compared to our knowledge about sensorimotor mirror neurons in monkeys[67] and vicarious

sensory responses in human subjects[60] (both foundational to theories about human social cognition[68] and

empathy[69]), we still know very little about a putative rodent mirror neuron system[69]. For demonstration

and validation, we applied our analysis pipeline to barrel cortex neurons, and were able to recover expected

neural tuning to (lateralized) whisker touch and movement[59]. Our end-to-end tracking method and analysis

pipeline maps tuning to movements and postures of the partner's body, and is also ideally suited to detect

potential social interaction systems such as rodent 'mirror neuron' signals in other brain areas[70,71]. The 45

potential predictors that we have included in our analysis pipeline could be expanded to add additional

features of interest. Similar to multiplexed spatial tuning in parahippocampal cortices (e.g., "conjunctive"

grid- and head-direction cells[72]), we model multiplexed tuning as multiplicative[62]. It is straightforward to

modify our model comparison code to also consider other coding schemes, such as nonlinear or condi-

tional interactions between predictors. This is of particular interest to the social neuroscience of joint ac-

tion, where movements and postures can have particular social meaning when performed in coordination

with a social partner[21].

Automatic mapping of social phenotypes

Social dysfunctions can be devastating symptoms in a multitude of mental conditions, including autism

spectrum disorders, social anxiety, depression, and personality disorders[73]. Social interactions also pow-

erfully impact somatic physiology, and social interactions are emerging as a promising protective and

therapeutic element in somatic conditions, such as inflammation[74] and chronic pain[75]. Disorders charac-

terized by deficits in social interaction and communication generally lack effective treatment options,

largely because even the neurobiological basis of 'healthy' social behavior is poorly understood. In addi-

tion to relating behavior to neural activity, automated 3D body tracking can yield a high-fidelity readout

of behavioral changes associated with manipulations of neural activity, both at short (e.g., optogenetic),

medium (e.g., pharmacological) and long (e.g., gene knockout) time scales.

Long-term multi-animal behavior tracking has a particular advantage in comparative social neuroscience.

For example, human genomics have linked several genes to autism[2–4], but we still know little about *how*

these genetic changes increase the risk of autism. A 'computational ethology'[76] approach to social behavior

analysis based on automatic posture tracking (such as pioneered in laboratory studies of insects, worms

and fish[20,77–82] and in field ethology[83–86]) does not require us to *a priori* imagine how, e.g., autism-related

gene perturbations manifest in mice, and can identify subtle changes in higher-order behavioral statistics

without human observer bias. By recording days of social interactions, it may be possible to use methods

from computational topology to ask how the high-dimensional space defined by touch, posture and move-

ment dynamics is impacted by different genotypes or pathological conditions. The statistical power and

granularity of the long-term continuous 3D behavior data may allow us to identify what specific core

components of social behaviors are altered in different social relations, by various neuroactive drugs, and

in disease states[53], and hopefully identify novel therapies for alleviating social dysfunction in patients.

Moving towards real-time behavior tracking and electrophysiology

Our algorithm is automatic, does not use any message-passing from future frames, and robustly recovers

from tracking mistakes. Thus, it is possible in principle to run the algorithm in real-time. Currently, the

processing time per frame is higher than the camera frame rate (60 frames/s), but the algorithm is also not

yet fully optimized for speed. For example, in the current version of the algorithm, we first record the

images to disk, and then read and pre-process the images later. This is convenient for algorithm develop-

ment and exploration, but writing and reading the images to disk, and moving them onto and off a GPU

are time-intensive steps. Beyond speed optimizations, tracking at a lower frame rate would allow more

data processing time per frame. Going forward, it is important to explore ways to increase tracking ro-

bustness further, such as using the optical flow between video frames to link key-points together in multi-

animal tracking[15], using a 3D convolutional neural network to detect body key-points by considering 'up-

projected' views from all cameras around the behavioral arena simultaneously[10], real-time painting-in of

depth artifacts[87], and better online trajectory forecasting with a network trained to propose trajectories

based on previously tracked mouse movements. Experimentation and optimization is clearly needed, but

our algorithm – requiring data transfer from only a few cameras, with deep convolutional networks, phys-

ical modeling and particle filter tracking implemented as tensor algebra on the same GPU – is a promising

starting point for the development of real-time, multi-animal 3D tracking, compatible with head mounted

electrophysiology, e.g., for closed-loop experimental control triggered on behavioral and/or neural events.

659 References

1. Crusio, W. E., Sluyter, F. & Gerlai, R. T. Ethogram of the mouse. in *Behavioral Genetics of the*
Mouse 17–22 (Cambridge Univeristy Press, 2013). doi:10.1017/CBO9781139541022.004.
2. Angelaki, D. E. *et al.* A gravity-based three-dimensional compass in the mouse brain. *Nat. Com-*
mun. **11**, 1855 (2020).
3. Mimica, B., Dunn, B. A., Tombaz, T., Bojja, V. P. T. N. C. S. & Whitlock, J. R. Efficient cortical
coding of 3D posture in freely behaving rats. *Science* **362**, 584–589 (2018).
4. Shemesh, Y. *et al.* High-order social interactions in groups of mice. *eLife* **2**, e00759 (2013).
5. Weissbrod, A. *et al.* Automated long-term tracking and social behavioural phenotyping of animal
colonies within a semi-natural environment. *Nat. Commun.* **4**, 1–10 (2013).
6. Pereira, T. D. *et al.* Fast animal pose estimation using deep neural networks. *Nat. Methods* **16**, 117–
125 (2019).
7. Mathis, A. *et al.* DeepLabCut: markerless pose estimation of user-defined body parts with deep
learning. *Nat. Neurosci.* **21**, 1281–1289 (2018).
8. Graving, J. M. *et al.* DeepPoseKit, a software toolkit for fast and robust animal pose estimation us-
ing deep learning. *eLife* **8**, e47994 (2019).
9. Zhang, L., Dunn, T., Marshall, J., Olveczky, B. & Linderman, S. Animal pose estimation from video
data with a hierarchical von Mises-Fisher-Gaussian model. in *International Conference on Artificial*
Intelligence and Statistics 2800–2808 (PMLR, 2021).
10. Dunn, T. W. *et al.* Geometric deep learning enables 3D kinematic profiling across species and envi-
ronments. *Nat. Methods* **18**, 564–573 (2021).
11. Marshall, J. D. *et al.* Continuous Whole-Body 3D Kinematic Recordings across the Rodent Behav-
ioral Repertoire. *Neuron* **109**, 420-437.e8 (2021).
12. Wu, A. *et al.* Deep Graph Pose: a semi-supervised deep graphical model for improved animal pose
tracking. *bioRxiv* 2020.08.20.259705 (2020) doi:10.1101/2020.08.20.259705.
13. Liu, X. *et al.* OptiFlex: video-based animal pose estimation using deep learning enhanced by optical
flow. *bioRxiv* 2020.04.04.025494 (2020) doi:10.1101/2020.04.04.025494.
14. Lauer, J. *et al.* Multi-animal pose estimation and tracking with DeepLabCut. *bioRxiv*
2021.04.30.442096 (2021) doi:10.1101/2021.04.30.442096.
15. Pereira, T. D. *et al.* SLEAP: Multi-animal pose tracking. *bioRxiv* 2020.08.31.276246 (2020)
doi:10.1101/2020.08.31.276246.
16. Chaumont, F. de *et al.* Real-time analysis of the behaviour of groups of mice via a depth-sensing
camera and machine learning. *Nat. Biomed. Eng.* **3**, 930–942 (2019).
17. Hong, W. *et al.* Automated measurement of mouse social behaviors using depth sensing, video
tracking, and machine learning. *Proc. Natl. Acad. Sci.* **112**, E5351–E5360 (2015).
18. Nilsson, S. R. O. *et al.* Simple Behavioral Analysis (SimBA): an open source toolkit for computer
classification of complex social behaviors in experimental animals. *bioRxiv* 2020.04.19.049452
(2020) doi:10.1101/2020.04.19.049452.
19. Segalin, C. *et al.* The Mouse Action Recognition System (MARS): a software pipeline for auto-
mated analysis of social behaviors in mice. *bioRxiv* 2020.07.26.222299 (2020)
doi:10.1101/2020.07.26.222299.
20. Walter, T. & Couzin, I. D. TRex, a fast multi-animal tracking system with markerless identification,
2D body posture estimation and visual field reconstruction. *eLife* 10:e64000 (2021).
21. Ebbesen, C. L. & Froemke, R. C. Body language signals for rodent social communication. *Curr.*
Opin. Neurobiol. **68**, 91–106 (2021).
22. Nath, T. *et al.* Using DeepLabCut for 3D markerless pose estimation across species and behaviors.
Nat. Protoc. **14**, 2152–2176 (2019).
23. Bala, P. C. *et al.* OpenMonkeyStudio: Automated Markerless Pose Estimation in Freely Moving
Macaques. *bioRxiv* 2020.01.31.928861 (2020) doi:10.1101/2020.01.31.928861.
24. Batty, E. *et al.* BehaveNet: nonlinear embedding and Bayesian neural decoding of behavioral vid-
eos. in *Advances in Neural Information Processing Systems 32* (eds. Wallach, H. et al.) 15706–

15717 (Curran Associates, Inc., 2019).

25. Parker, P. R. L., Brown, M. A., Smear, M. C. & Niell, C. M. Movement-Related Signals in Sensory
Areas: Roles in Natural Behavior. *Trends Neurosci.* **43**, 581–595 (2020).

26. Kropff, E., Carmichael, J. E., Moser, M.-B. & Moser, E. I. Speed cells in the medial entorhinal cor-
tex. *Nature* **523**, 419–424 (2015).

27. Omrani, M., Kaufman, M. T., Hatsopoulos, N. G. & Cheney, P. D. Perspectives on classical contro-
versies about the motor cortex. *J. Neurophysiol.* **118**, jn.00795.2016-jn.00795.2016 (2017).

28. Georgopoulos, A. P., Kalaska, J. F., Caminiti, R. & Massey, J. T. On the relations between the direc-
tion of two-dimensional arm movements and cell discharge in primate motor cortex. *J. Neurosci.* **2**,
1527–1537 (1982).

29. Kalaska, J. F. The representation of arm movements in postcentral and parietal cortex. *Can. J. Phys-
iol. Pharmacol.* **66**, 455–463 (1988).

30. Matsumoto, J. *et al.* A 3D-Video-Based Computerized Analysis of Social and Sexual Interactions in
Rats. *PLOS ONE* **8**, e78460 (2013).

31. Nakamura, T. *et al.* A Markerless 3D Computerized Motion Capture System Incorporating a Skele-
ton Model for Monkeys. *PLOS ONE* **11**, e0166154 (2016).

32. Sheets, A. L., Lai, P.-L., Fisher, L. C. & Basso, D. M. Quantitative Evaluation of 3D Mouse Behav-
iors and Motor Function in the Open-Field after Spinal Cord Injury Using Markerless Motion
Tracking. *PLOS ONE* **8**, e74536 (2013).

33. Wiltschko, A. B. *et al.* Mapping Sub-Second Structure in Mouse Behavior. *Neuron* **88**, 1121–1135
(2015).

34. Newell, A., Yang, K. & Deng, J. Stacked Hourglass Networks for Human Pose Estimation.
ArXiv160306937 Cs (2016).

35. Günel, S. *et al.* DeepFly3D, a deep learning-based approach for 3D limb and appendage tracking in
tethered, adult Drosophila. *eLife* **8**, e48571 (2019).

36. Cao, Z., Simon, T., Wei, S.-E. & Sheikh, Y. Realtime Multi-Person 2D Pose Estimation using Part
Affinity Fields. *ArXiv161108050 Cs* (2017).

37. Shorten, C. & Khoshgoftaar, T. M. A survey on Image Data Augmentation for Deep Learning. *J.
Big Data* **6**, 60 (2019).

38. Transtrum, M. K., Machta, B. B. & Sethna, J. P. Geometry of nonlinear least squares with applica-
tions to sloppy models and optimization. *Phys. Rev. E* **83**, 036701 (2011).

39. Hart, J. C. Distance to an ellipsoid. in *Graphics Gems* (ed. Heckbert, P.) vol. 1994 113–119 (Aca-
demic Press).

40. Kleinsteuber, M. & Hüper, K. Approximate Geometric Ellipsoid Fitting: A CG-Approach. in *Recent
Advances in Optimization and its Applications in Engineering* (eds. Diehl, M., Glineur, F., Jarle-
bring, E. & Michiels, W.) 73–82 (Springer, 2010). doi:10.1007/978-3-642-12598-0_7.

41. Wang, W., Wang, J. & Kim, M.-S. An algebraic condition for the separation of two ellipsoids. *Com-
put. Aided Geom. Des.* **18**, 531–539 (2001).

42. Choset, H. M. *Principles of robot motion: theory, algorithms, and implementation.* (MIT Press,
2005).

43. Deutscher, J. & Reid, I. Articulated Body Motion Capture by Stochastic Search. *Int. J. Comput. Vis.*
61, 185–205 (2005).

44. Paszke, A. *et al.* PyTorch: An Imperative Style, High-Performance Deep Learning Library. in *Ad-
vances in Neural Information Processing Systems 32* (eds. Wallach, H. et al.) 8024–8035 (Curran
Associates, Inc., 2019).

45. Sobol, I. M. On the distribution of points in a cube and the approximate evaluation of integrals.
USSR Comput. Math. Math. Phys. **7**, 86–112 (1967).

46. Das, G. Top-k Algorithms and Applications. in *Database Systems for Advanced Applications* (eds.
Zhou, X., Yokota, H., Deng, K. & Liu, Q.) 789–792 (Springer, 2009). doi:10.1007/978-3-642-
00887-0_74.

47. Murray, L. M., Lee, A. & Jacob, P. E. Parallel Resampling in the Particle Filter. *J. Comput. Graph.
Stat.* **25**, 789–805 (2016).

48. Rauch, H. E., Tung, F. & Striebel, C. T. Maximum likelihood estimates of linear dynamic systems.
AIAA J. **3**, 1445–1450 (1965).
49. Simon, D. *Optimal State Estimation: Kalman, H∞, and Nonlinear Approaches*. (John Wiley &
Sons, Inc., 2006). doi:10.1002/0470045345.
50. Landis, M. F., Cheng, Y., Crassidis, J. L. & Oshman, Y. Averaging quaternions. *J. Guid. Control*
Dyn. **30**, 1193–1197 (2007).
51. Berman, G. J., Choi, D. M., Bialek, W. & Shaevitz, J. W. Mapping the stereotyped behaviour of
freely moving fruit flies. *J. R. Soc. Interface* **11**, 20140672 (2014).
52. Berman, G. J., Bialek, W. & Shaevitz, J. W. Predictability and hierarchy in Drosophila behavior.
Proc. Natl. Acad. Sci. **113**, 11943–11948 (2016).
53. Wiltschko, A. B. *et al.* Revealing the structure of pharmacobehavioral space through motion se-
quencing. *Nat. Neurosci.* 1–11 (2020) doi:10.1038/s41593-020-00706-3.
54. Barnett, S. A. *The rat: A study in behaviour*. xvi, 248 (Aldine, 1963).
55. Wolfe, J., Mende, C. & Brecht, M. Social facial touch in rats. *Behav. Neurosci.* **125**, 900–910
(2011).
56. Bingham, E. *et al.* Pyro: Deep Universal Probabilistic Programming. *ArXiv181009538 Cs Stat*
(2018).
57. Fox, E., Sudderth, E., Jordan, M. & Willsky, A. Bayesian Nonparametric Methods for Learning
Markov Switching Processes. *IEEE Signal Process. Mag.* 5563110 (2010)
doi:10.1109/MSP.2010.937999.
58. Ebbesen, C. L., Bobrov, E., Rao, R. P. & Brecht, M. Highly structured, partner-sex- and subject-sex-
dependent cortical responses during social facial touch. *Nat. Commun.* **10**, 1–16 (2019).
59. Petersen, C. C. H. Sensorimotor processing in the rodent barrel cortex. *Nat. Rev. Neurosci.* **20**, 533–
546 (2019).
60. Keysers, C., Kaas, J. H. & Gazzola, V. Somatosensation in social perception. *Nat. Rev. Neurosci.* **11**,
417–428 (2010).
61. Lenschow, C. & Brecht, M. Barrel Cortex Membrane Potential Dynamics in Social Touch. *Neuron*
85, 718–725 (2015).
62. Hardcastle, K., Maheswaranathan, N., Ganguli, S. & Giocomo, L. M. A Multiplexed, Heterogene-
ous, and Adaptive Code for Navigation in Medial Entorhinal Cortex. *Neuron* **94**, 375-387.e7 (2017).
63. Díaz López, B. When personality matters: personality and social structure in wild bottlenose dol-
phins, Tursiops truncatus. *Anim. Behav.* **163**, 73–84 (2020).
64. Tao, L., Ozarkar, S., Beck, J. M. & Bhandawat, V. Statistical structure of locomotion and its modu-
lation by odors. *eLife* **8**, e41235 (2019).
65. Concha-Miranda, M., Hartmann, K., Reinhold, A., Brecht, M. & Sanguinetti-Scheck, J. I. Play, but
not observing play, engages rat medial prefrontal cortex. *Eur. J. Neurosci.* **n/a**, (2020).
66. Carrillo, M. *et al.* Emotional Mirror Neurons in the Rat's Anterior Cingulate Cortex. *Curr. Biol.* **29**,
1301-1312.e6 (2019).
67. Kilner, J. M. & Lemon, R. N. What We Know Currently about Mirror Neurons. *Curr. Biol.* **23**,
R1057–R1062 (2013).
68. Hickok, G. Do mirror neurons subserve action understanding? *Neurosci. Lett.* **540**, 56–58 (2013).
69. Keysers, C. & Gazzola, V. Neural Correlates of Empathy in Humans, and the Need for Animal
Models. in *Neuronal Correlates of Empathy* 37–52 (Elsevier, 2018). doi:10.1016/B978-0-12-
805397-3.00004-8.
70. Tombaz T, Dunn BA, Hovde K, Cubero RJ, Mimica B, Mamidanna P, Roudi Y, & Whitlock JR. Ac-
tion representation in the mouse parieto-frontal network. *Sci Rep.* **10**:5559 (2020).
71. Carcea, I., et al. Oxytocin neurons enable social transmission of maternal behaviour. *Nature*
596:553-557 (2021).
72. Sargolini, F. *et al.* Conjunctive representation of position, direction, and velocity in entorhinal cor-
tex. *Science* **312**, 758–62 (2006).
73. Porcelli, S. *et al.* Social brain, social dysfunction and social withdrawal. *Neurosci. Biobehav. Rev.*
97, 10–33 (2019).

74. Uchino, B. N. *et al.* Social support, social integration, and inflammatory cytokines: A meta-analysis.
Health Psychol. **37**, 462–471 (2018).

75. Che, X., Cash, R., Ng, S. K., Fitzgerald, P. & Fitzgibbon, B. M. A Systematic Review of the Pro-
cesses Underlying the Main and the Buffering Effect of Social Support on the Experience of Pain.
Clin. J. Pain **34**, 1061–1076 (2018).

76. Anderson, D. J. & Perona, P. Toward a Science of Computational Ethology. *Neuron* **84**, 18–31
(2014).

77. Gal, A., Saragosti, J. & Kronauer, D. J. anTraX, a software package for high-throughput video
tracking of color-tagged insects. *eLife* **9**, e58145 (2020).

78. Bozek, K., Hebert, L., Portugal, Y., Mikheyev, A. S. & Stephens, G. J. Markerless tracking of an
entire honey bee colony. *Nat. Commun.* **12**, 1733 (2021).

79. Imirzian, N. *et al.* Automated tracking and analysis of ant trajectories shows variation in forager ex-
ploration. *Sci. Rep.* **9**, 13246 (2019).

80. Klibaite, U., Berman, G. J., Cande, J., Stern, D. L. & Shaevitz, J. W. An unsupervised method for
quantifying the behavior of paired animals. *Phys. Biol.* **14**, 015006 (2017).

81. Franks, N. R. *et al.* Social behaviour and collective motion in plant-animal worms. *Proc. R. Soc. B*
Biol. Sci. **283**, 20152946 (2016).

82. Rosenthal, S. B., Twomey, C. R., Hartnett, A. T., Wu, H. S. & Couzin, I. D. Revealing the hidden
networks of interaction in mobile animal groups allows prediction of complex behavioral contagion.
Proc. Natl. Acad. Sci. **112**, 4690–4695 (2015).

83. Adam, T. *et al.* Joint modelling of multi-scale animal movement data using hierarchical hidden
Markov models. *Methods Ecol. Evol.* **10**, 1536–1550 (2019).

84. Strandburg-Peshkin, A., Farine, D. R., Couzin, I. D. & Crofoot, M. C. Shared decision-making
drives collective movement in wild baboons. *Science* **348**, 1358–1361 (2015).

85. Patterson, T. A. *et al.* Statistical modelling of individual animal movement: an overview of key
methods and a discussion of practical challenges. *ArXiv160307511 Q-Bio Stat* (2017).

86. Smith, J. E. & Pinter-Wollman, N. Observing the unwatchable: Integrating automated sensing, natu-
ralistic observations and animal social network analysis in the age of big data. *J. Anim. Ecol.* **n/a**,
(2020).

87. Gillis, W. *et al.* Revealing elements of naturalistic reinforcement learning through closed-loop ac-
tion identification. in *2019 Neuroscience Meeting Planner* Program No. 146.17 (Society for Neuro-
science, 2019).

88. Kamada, T. & Kawai, S. An algorithm for drawing general undirected graphs. *Inf. Process. Lett.* **31**,
7–15 (1989).

89. Sayed, A. & Kailath, T. Recursive Least-Squares Adaptive Filters. in *Digital Signal Processing*
Fundamentals vol. 20094251 1–40 (CRC Press, 2009).

90. Blei, D. M., Kucukelbir, A. & McAuliffe, J. D. Variational Inference: A Review for Statisticians. *J.*
Am. Stat. Assoc. **112**, 859–877 (2017).

91. Franklin, K. B. J. & Paxinos, G. *The mouse brain in stereotaxic coordinates.* (2019).

92. Vöröslakos, M. *et al.* 3D-printed recoverable microdrive and base plate system for rodent electro-
physiology. (2021).

93. Siegle, J. H. *et al.* Open Ephys: an open-source, plugin-based platform for multichannel electro-
physiology. *J. Neural Eng.* **14**, 045003 (2017).

94. Yger, P. *et al.* A spike sorting toolbox for up to thousands of electrodes validated with ground truth
recordings in vitro and in vivo. *eLife* **7**, 1–23 (2018).

95. Rossant, C. *et al.* Spike sorting for large, dense electrode arrays. *Nat. Neurosci.* **19**, 634–641 (2016).

96. Larsson, J. eulerr: Area-Proportional Euler and Venn Diagrams with Ellipses. https://cran.r-pro-
ject.org/web/packages/eulerr/citation.html (2020).

97. Hagberg, A. A., Schult, D. A. & Swart, P. J. Exploring Network Structure, Dynamics, and Function
using NetworkX. 5 (2008).

Acknowledgements

This work was supported by The Novo Nordisk Foundation (C.L.E.), the NIH (DC012557, HD088411,

and NS107616 to R.C.F.), and a Howard Hughes Medical Institute Faculty Scholarship (R.C.F.). We thank

György Buzsáki, David Tingley, and Manuel Valero for help in establishing silicon probe recordings and

for the gift of 3D printed silicon drive parts.

Author Contributions

C.L.E. designed and implemented the system, performed experiments, analyzed the data, made figures,

and wrote the first version of the manuscript. R.C.F. supervised the study. C.L.E and R.C.F. wrote the

manuscript.

Competing Interests

The authors declare no competing interests.

Data and Code Availability

All code (the recording software and all analysis code) and an example dataset were submitted with this

manuscript. All code will be available in a dedicated Github repository before or upon publication, the

example dataset will be deposited on Zenodo.

Figures **and** **Legends**

Figure 1. Raw data acquisition, temporal alignment and recording stability. a, Schematic of recording

setup, showing flow of synchronization pulses and raw data. We use a custom Python program to record

RGB images, depth images, and state (on/off) of synchronization LEDs from all four cameras. Neural data

and TTL state of LEDs are recorded with a standard electrophysiology recording system. We use a custom

Python program to record video frames over USB (60 frames/s) and automatically deliver LED synchro-

nization pulses with randomized delays via Arduino microcontroller. **b,** Close-up images of the depth

cameras, showing the two infrared sensors, color sensor, and cables for data transfer and synchronization.

c, Photograph of recording setup, showing the four depth cameras, synchronization LEDs, and circular

behavioral arena (transparent acrylic, 12" diameter). **d,** Example raw data images (top left: single infrared

image with visible infrared laser dots; top right: corresponding automatically-generated mask image for

recording LED synchronization state (arrow, LED location); bottom left: corresponding depth image, es-

timated from binocular disparity between two infrared images; bottom right: corresponding color image).

e, Inter-frame-interval from four cameras (21 min of recording). Vertical ticks indicate 16.66 ms (corre-

sponding to 60 frames/s), individual cameras are colored and vertically offset. Frame rate is very stable

(jitter across all cameras: ± 26 μs). Arrow, example dropped frame. **f,** Number of dropped frames across

the example 21 min recording. **g,** Top row, LED state (on/off) as captured by one camera (the 8-bit value

of central pixel of LED ROI mask), at start of recording and after 20 minutes of recording. Bottom row,

aligned LED trace, as recorded by electrophysiology recording system. **h,** Temporal residuals between

recorded camera LED trace (**g**, top) and recorded TTL LED trace (**g**, bottom) are stable, but drift slightly

(49 μs/min, left panel). We can automatically detect and correct for this small drift (right panel).

Figure 2. Detection of body key-points with a deep convolutional neural network. a, Workflow for

pre-processing of raw image data. **b**, The 'stacked hourglass' convolutional network architecture. Each

'hourglass' block of the network uses pooling and upsampling to incorporate both fine (high-resolution)

and large-scale (low-resolution) information in the target prediction. The hourglass and scoring blocks are

repeated seven times (seven 'stacks'), such that intermediate key-point and affinity field predictions feed

into subsequent hourglass blocks. Both the intermediate and final target maps contribute to the training

loss, but only the final output map is used for prediction. **c**, Example training data for the deep convolu-

tional neural network. The network is trained to output four types of body key-points (Implant, Ears, Noses,

Tails) and seven 1-D affinity fields, connecting key-points within each body. **d**, Example of full training

target tensor. **e**, Convergence plot of example training set. Top, loss function for each mini-batch of the

training set (526 images) and validation set (50 images). Bottom, learning rate. Network loss is trained

(plateaued) after ~ 60 minutes. **f**, Network performance as function of training epoch for two example

917 images in the validation set. Left, input images; right, final output maps for key-points and affinity fields.

918 **g,** In an infrared frame (under infrared illumination), the clear view of the mice is 'obstructed' by the

919 infrared laser dot pattern. **h,** Example labeled training frame (with the laser turned off), showing the aug-

920 mentation strategy of applying a probabilistically generated 'fake' laser dot pattern during training. **i,** Ex-

921 ample network output of the trained network on a 'real' infrared frame with the infrared laser turned on.

Figure 3. Depth data alignment and pre-processing. a, Calibration ball detection pipeline. We use a combination of motion filtering, color filtering, and smoothing filters to detect and extract 3D ball surface. We estimate 3D location of the ball by fitting a sphere to the extracted surface. **b**, Estimated 3D trajectories of calibration ball as seen by the four cameras. One trajectory has an error (arrow) where ball trajectory was out of view. **c**, Overlay of trajectories after alignment in time and space. Our alignment pipeline uses a robust regression method and is insensitive to errors (arrow) in the calibration ball trajectory. **d**, Distribution of residuals, using cam 0 as reference. **e**, Estimated trajectory in 3D space, before and after alignment of camera data. **f**, Example frame used in automatic detection of the behavioral arena location. Show

are pixels from the four cameras, after alignment (green), estimated normal vectors to the behavioral plat-

form floor (red), the estimated rotation vector (blue), and the reference vector (unit vector along z-axis,

black). **g**, Estimated location (left) and normal vector (right) to the behavioral platform floor, across 60

random frames. **h**, Example frame, after rotating the platform into the xy-plane, and removing pixels be-

low and outside the arena. Inferred camera locations are indicated with stick and ball. **i**, Automatic detec-

tion of behavioral arena location. **j**, Example 3D frame, showing merged data from four cameras, after

automatic removal of the arena floor and imaging artifacts induced by the acrylic cylinder. Colors, which

camera captured the pixels.

Figure 4. Mouse body model and GPU-accelerated tracking algorithm. a, Full assembly pipeline for

a single pre-processed data frame, going from raw RGB and depth images (left columns) to assembled 3D

point-cloud (black dots, right) and body key-point positions in 3D space (colored dots, right). **b**, Schematic

depiction of mouse body model (grey, deformable ellipsoids) and implant model (grey sphere), fit to point-

cloud (black dots) and body key-points (colored dots). The loss function assigns loss to distance from the

point-cloud to the body model surface (black arrows) and from key-point locations to landmark locations

on the body model (e.g., from nose key-points to the tip of the nose ellipsoids; colored arrows). **c**, Sche-

matic of loss function calculation and tracking algorithm. All operations implemented as GPU-accelerated

tensor algebra. **d**, Example steps showing convergence of the particle filter on a single frame. **e**, Iteration

time of a particle filter step, as a function of particles, on a GPU and CPU. For 200 particles (i.e. 40.000

joint poses), the GPU-accelerated particle filter is ~16.5 times faster than the CPU **f**, Schematic depiction

of the two levels of the tracking algorithm: Within a single frame, the joint poses are estimated with the

particle filter. Between frames, the RLS filter bank incorporates information from multiple previous

frames to estimate and propose the minimum in 'pose space'.

Figure 5. Automatic classification of movement patterns and behavioral states during social inter-actions. a, Tracked position of both mice, across an example 21 min recording. **b**, Extracted behavioral features: three speed components (forward, left and up in the mice's egocentric reference frames), and three 'social distances' (nose-to-nose distance and two nose-to-tail distances). Colors indicate ethograms of automatically detected behavioral states. **c**, Examples of identified social events: nose-to-nose-touch,

and anogenital nose-contacts. **e**, Mean and covariance (3 standard deviations indicated by ellipsoids) for

each latent state for the forward/leftward running (dots indicate a subsample of tracked speeds, colored by

their most likely latent state) **e**, Mean and variance of latent states in the z-plane (shaded color) as well as

distribution of tracked data assigned to those latent states (histograms) **f**, Distribution of the duration of

the five behavioral states in the *xy*-plane. Periods of rest (blue) are the longest ($p < 0.05$, Mann-Whitney

U-test) and bouts of fast forward movement (green) are to be longer other movement bouts ($p < 0.001$,

Mann-Whitney U-test). **g**, Distribution of duration of the three behavioral states in the z-plane. Periods of

rest (light blue) are either very short or very long. **h**, Plot of body elevation against behavior duration.

Short periods of rest happen when the *z*-coordinate is high (the mouse rears up, waits for a brief moment

before ducking back down), whereas long periods of rest happen when the *z*-coordinate is low (when the

mouse is resting or moving around the arena, $\rho = -0.47$, $p < 0.001$, Spearman rank).

Figure 6. Automatic measurement of firing rate modulations during social touch. a, Automatically-detected social touch events in mouse implanted with silicon probe (Si-probe) with 31 single-units from barrel cortex during a single 20-minute behavioral session. Yellow, nose-to-nose; purple, implanted-nose-to-partner-tail; blue, partner-nose-to-implanted-tail. **b**, Distribution of touch durations with male (dashed) and female (solid) partner. **c**, Percentage of behavioral session classified as social touch events, by partner sex, for two behavioral sessions. **d**, Distribution of inter-touch-intervals for the two example behavioral sessions. **e**, Social touch PSTHs for four neurons. For each neuron, the top row shows 'naïve' PSTHs (aligned to social touch event) and the bottom row shows 'cleaned' PSTHs (we only include events where no other social touch event occurred in the –4 s to 0 s period before the detected social touch). The PSTHs in the bottom row have fewer trials, but show much larger effect sizes. **f**, Percentage of neurons that pass a p < 0.05 significance criterion, based on the 'naïve' and 'cleaned' PSTHs shown above. **g**, Distributions of effect size (measured as a firing rate modulation index), based on the 'naïve' and 'cleaned' PSTHs shown above.

Figure 7. Automatic mapping of neural receptive fields in a natural 'social situation'. a, Schematic depiction of automatically extracted social features (top: nose-to-nose and nose-to-tail distances, center-to-center velocity and head-center-to-head-center angle) and movement/posture features (bottom: rotation and movement of the body model ellipsoids). **b**, Names and example traces of extracted behavioral features: social features (red color) and movement (yellow), posture (blue) and spatial (green) features, for both the subject and partner animal. **c**, Schematic depiction of the generative model: We assume that every

behavioral feature ('predictor') is associated with a tuning curve and that spikes are generated by a Poisson

process. **d**, Model selection history (with associated p-values of each included predictor) for an example

neuron (average spike shape and ISI-histogram shown to the left). The 'raw' marginal firing rate distribu-

tion (bars), and the fitted multiplexed tuning curves (10 lines, one line for each data fold) of the identified

predictors are shown below. The barrel cortex neuron multiplexes five features, including nose-to-nose

distance (the neuron fires more when this is close to zero, i.e., when noses touch) and orientation angle

(the neuron fires most at roughly $-\pi/2$, i.e., when the partner is on the right side, the contralateral side

relative to the recording electrode). **e**, Another example neuron (same plots as in **d**). This barrel cortex

neuron multiplexes four features: during nose-to-nose touch, when turning or rolling the head to the right,

when partner's nose is tilted up, or when partner's nose is slightly downwards. **f**, Distribution of the num-

ber of neurons that encode the tested behavioral features (ordering as in **b**). The neurons mainly encoded

social touch features (nose-to-nose, implanted-nose-to-partner-tail and orientation angle) and move-

ment/posture features of the implanted animal itself (blue and yellow bars, above 'own behavior').

1005

Figure 8. Population tuning and co-encoding network structure in a social situation. a, Top, single

neuron tuning curves and 'population tuning curve' (average tuning, shaded area indicates standard devi-

ation) for all behavioral features encoded by more than three single neurons. Bottom, schematic depiction

of the physical interpretation of the population tuning, in relation to the 3D body models. **b,** Distribution

of the number of behavioral features that each single neuron multiplexes. The arrow indicated the median

number of features encoded by a neuron that encode at least one feature. **c,** Co-encoding matrix of the

neural population: The grayscale color in i'th and j'th bin in the heatmap indicates the number neurons

that encode both feature i and j (ordering and color on the axes as in **Fig. 7**). **d,** Euler diagram of a subset

of the co-encoding matrix: This shows the number of neurons that encode nose-to-nose touch, implanted-

nose-to-partner-tail touch and orientation angle (i.e. are lateralized). **e,** Network graph depiction of the full

co-encoding matrix. The size of the nodes indicates the number of neurons that encode a feature, the width

1017 of the edges indicates the number of neurons that co-encode a behavioral feature. The network is shown

1018 in the Kamada-Kawai projection[86] (the distance between nodes approximate their graph-theoretical dis-

1019 tance), with additional text labels on the network on the right.

1020 **Methods**
1021
1022 *Hardware*
1023
1024 Necessary hardware:
1025

Item	Recommendation	Price (USD)	N	Total (USD)
Depth cameras	Intel RealSense D435	179.00	4	716.00
Camera stands	Etubby 26" gooseneck webcam stand	24.96	4	99.84
PCIe card with 4 independent USB 3.0 controllers	Startech 4-port superspeed	83.54	1	83.54
Active, repeating USB 3.0 cables	UGREEN, USB 3.0 Active Repeater Cable	18.89	4	75.56
Arduino with USB cable	Arduino Uno R3	13.98	1	13.98
Pytorch-compatible GPU	Any NVIDIA card with CUDA support	500.00	1	500.00
Behavioral arena (acrylic cylinder or elevated platform)	12"-diameter, 5/32" thick acrylic cylinder	71.20	1	71.20
Depth camera GPIO pin connector (jumper)	JST ASSHSSH28K305	0.54	8	4.32
Depth camera GPIO pin connector (jumper housing)	JST SHR-09V-S	0.19	4	0.76
Colored ping-pong balls (for calibration)	Stiga 40 mm ITTF Regulation size	6.64	1	6.64
Total				1571.84

1026
1027 General lab electronics (tape, wire, soldering equipment, etc.) and:
1028

Item	N
Infrared or red LEDs	4
0.1" pin headers or jumper wires	2
20 kOhm resistors	4
22 nF capacitors	4
200 Ohm resistor (or same order of magnitude)	1
Stick (for moving ping-pong ball during calibration)	1

1029
1030
Software

Our system uses the following software: Linux (tested on Ubuntu 16.04 LTE, but should work on others,

https://ubuntu.com/), Intel Realsense SDK (https://github.com/IntelRealSense/librealsense), Python

(tested on Python 3.6, we recommend Anaconda, https://www.anaconda.com/distribution/). Required Py-

thon packages will be installed with PIP or conda (script in supplementary software). All required software

is free and open source.

1037

Animal welfare

All experimental procedures were performed according to animal welfare laws under the supervision of

local ethics committees. Animals were kept on a 12hr/12hr light cycle with ad libitum access to food and

water. Mice presented as partner animals were housed socially in same-sex cages, and post-surgery im-

planted animals were housed in single animal cages. Neural recordings electrodes were implanted on the

dorsal skull under isoflurane anesthesia, with a 3D-printed electrode drive and a hand-built mesh hous-

ing. All procedures were approved under NYU School of Medicine IACUC protocols.

1045

1046   *Computer hardware*

1047   All experiments and benchmarks were done on a desktop PC running Ubuntu 16.04 LTE on a 3.7 GHz

1048   6-core CPU (Intel i7-8700K), with 32 GB 2400 MHz RAM, and an Nvidia GeForce RTX 2080Ti GPU.

1049

Recording data structure

The Python program is set to pull raw images at 640 x 480 (color) and 640 x 480 (depth), but only saves

320 x 210 (color) and 320 x 240 (depth). We do this to reduce noise (multi-pixel averaging), save disk

space and reduce processing time. Our software also works for saving images up to 848 x 480 (color) and

848 x 480 (depth) at 60 frames/s, in case the system is to be used for a bigger arena, or to detect smaller

body parts (e.g., eyes, paws). Images were transferred from the cameras with the python bindings for the

Intel Realsense SDK (https://github.com/IntelRealSense/librealsense), and saved as 8-bit, 3-channel PNG

files with opencv (for color images) or as 16-bit binary files (for depth images).

1058

3D data structure

For efficient access and storage of the large datasets, we save all pre-processed data to hdf5 files. Because

the number of data points (point-cloud and key-points) per frame varies, we save every frame as a jagged

array. To this end, we pack all pre-processed data to a single array. If we detect N points in the point-cloud

and M key-points in the color images, we save a stack of the 3D coordinates of the points in the point-

cloud (Nx3, raveled to 3N), the weights (N), the 3D coordinates of the key-points (Mx3, raveled to 3M),

their pseudo-posterior (M), an index indicating key-point type (M), and the number of key-points (1).

Functions to pack and unpack the pre-processed data from a single line ('pack_to_jagged' and 'un-

pack_from_jagged') are provided.

1068

Temporal synchronization

LED blinks were generated with voltage pulses from an Arduino (on digital pin 12), controlled over USB

with a python interface for the Firmata protocol (https://github.com/tino/pyFirmata). To receive the Fir-

mata messages, the Arduino was flashed with the 'StandardFirmata' example, that comes with the standard

Arduino IDE. TTL pulses were 150 ms long and spaced by $\sim U(150,350)$ ms. We recorded the emitted

voltage pulses in both the infrared images (used to calculate the depth image) and on a TTL input on an

Open Ephys Acquisition System (https://open-ephys.org/). We detected LED blinks and TTL flips by

threshold crossing and roughly aligned the two signals by the first detected blink/flip. We first refined the

alignment by cross correlation in 10 ms steps, and then identified pairs of blinks/flips by detecting the

closest blink, subject to a cutoff (zscore < 2, compared to all blink-to-flip time differences) to remove

blinks missed by the camera (because an experimenter moved an arm in front of a camera to place a mouse

in the arena, for example). The final shift and drift was estimated by a robust regression (Theil-Sen esti-

mator) on the pairs of blinks/links.

1082

Deep neural network

We used a stacked hourglass network[34] implemented in Pytorch[44] (https://github.com/pytorch/pytorch).

The network architecture code is from the implementation in 'PyTorch-Pose'

(https://github.com/bearpaw/pytorch-pose). The full network architecture is shown in **Supplementary**

Figure 1. The Image augmentation during training was done with the 'imgaug' library

(https://github.com/aleju/imgaug). Our augmentation pipeline is shown in **Supplementary Figure 3**. The

'fake laser dot pattern' was generated using the 'snowflakes' generator in the imgaug routines for gener-

ating weather effects, tuned to look – by eye – to a similar dot size and density to the real laser dot pattern.

The network was trained by RMSProp ($\alpha = 0.99$, $\varepsilon = 10^{-8}$) with an initial learning rate of 0.00025. During

training, the learning rate was automatically reduced by a factor of 10 if the training loss decreased by less

than 0.1% for five successive steps (using the built-in learning rate scheduler in Pytorch). After training,

we used the final output map of the network for key-point detection, and used a maximum filter to detect

key-point locations as local maxima in network output images with a posterior pseudo-probability of at

least 0.5.

1097

Image labeling and target maps

For training the network to recognize body parts, we need to generate labeled frames by manual annotation.

For each frame, 1-5 body parts are labeled on the implanted animal and 1-4 body parts on the partner

animal. This can be done with any annotation software; we used a modified version of the free 'DeepPo-

seKit-Annotator'[8] (https://github.com/jgraving/DeepPoseKit-Annotator/) included in the supplementary

code. This software allows easy labeling of the necessary points, and pre-packages training data for use in

our training pipeline. Body parts are indexed by i/p for implanted/partner animal ('nose_p' is the nose of

the partner animal, for example). Target maps were generated by adding a Gaussian function ($\sigma = 3$ px for

implant, $\sigma = 1$ px for other body parts, scaled to peak value = 1) to an array of zeros (at 1/4th the resolution

of the input color image) at the location of every labeled body key-point. 1D part affinity maps were

created by connecting labeled key-points in an array of zeros with a 1 px wide line (clipped to max value

= 1), and blurring the resulting image with a Gaussian filter ($\sigma = 3$ px).

1110

Aligning depth and color data

The camera intrinsics (focal lengths, f, optical centers, p, depth scale, d_{scale}) and extrinsics (rotation matri-

ces, R, translation vectors, $\bar{t}$) for both the color and depth sensors can be accessed over the SDK. Depth

and color images were aligned to each other using a pinhole camera model. For example, the z coordinate

of a single depth pixel with indices (i_c, i_d) and 16-bit depth value, d_{ij}, is given by:

$$z_d = d_{ij} \cdot d_{scale}$$

And the x and y coordinates are given by:

$$\begin{bmatrix} x_d \\ y_d \end{bmatrix} = \begin{matrix} (j_d - p_{x,d}) \cdot z_d / f_{x,d} \\ (i_d - p_{y,d}) \cdot z_d / f_{y,d} \end{matrix}$$

Using the extrinsics between the depth and color sensors, we can move the coordinate to the reference

frame of the color sensor:

$$\begin{bmatrix} x \\ y \\ z \end{bmatrix}_c = R_{d \to c} \begin{bmatrix} x \\ y \\ z \end{bmatrix}_d + \bar{t}_{d \to c}$$

Using the focal length and optical center, we can project the pixel onto the color image:

$$\begin{bmatrix} i_c \\ j_c \end{bmatrix} = \begin{matrix} f_{y,c} \cdot y_c / z_c + p_{y,c} \\ f_{x,c} \cdot x_c / z_c + p_{x,c} \end{matrix}$$

For assigning color pixel values to depth pixels, we simply rounded the color pixel indices (i_c, i_d) to the

nearest integer and cloned the value. More computationally intensive methods based on ray-tracking exist

('rs2_project_color_pixel_to_depth_pixel' in the Librealsense SDK, for example), but the simple pinhole

camera approximation yielded good results (small jitter average out across multiple key-points) which

allowed us to skip the substantial computational overhead of ray tracing for our data pre-processing.

1129

Depth camera calibration, exposure and 3D alignment

To align the cameras in space, we first mounted a blue ping-pong ball on a stick and moved it around the

behavioral arena while recording both color and depth video. For each camera, we used a combination of

motion filtering, color filtering, smoothing and thresholding to detect the location of the ping-pong ball in

the color frame (details in code). We then aligned the color frames to depth frames and extracted the

corresponding depth pixels, yielding a partial 3D surface of the ping-pong ball. By fitting a sphere to this

partial surface, we could estimate the 3D coordinate of the center of the ping-pong ball (**Fig. 3a**). This

procedure yielded a 3D trajectory of the ping-pong ball in the reference frame of each camera (**Fig. 3b**).

We used a robust regression method (RANSAC routines to fit a sphere with a fixed radius of 40 mm,

modified from routines in <ins>https://github.com/daavoo/pyntcloud</ins>), insensitive to errors in the calibration

ball trajectory to estimate the transformation matrices needed to bring all trajectories into the same frame

of reference (**Fig. 3c**). The software includes a step-by-step recipe for performing the alignment procedure.

The depth cameras have a minimum working distance of 20 cm, so they must be placed at least this dis-

tance from the behavioral arena. The depth map is calculated from the infrared camera stream, so – as

with the RGB video – it is important that the image is not under- or over-exposed. The code includes a

tool for streaming live video from all cameras to verify that: (*i*) the whole arena is in view of all the

cameras and (*ii*) that the exposure is reasonable. The exposure settings can be changes in the config files,

that are loaded and applied when recording (the Intel RealSense SDK demo C application library also

includes a nice tool for testing different exposure settings). The 3D pixel density drops off with distance

from the camera (following the inverse-square law). In our tested use (standard neuroscience behavioral

arena, max. ~ 1 x 1 m), the exact relative placement of the four depth cameras does not matter (as they are

aligned by the calibration). However, for very large arenas, it may be necessary to add more depth cameras

(additional cameras mounted above the arena, for example). Adding more cameras will only affect the

pre-processing time (can be run in parallel – which can minimize the impact of more cameras), not the

actual body model fitting time (the slowest part of the algorithm). The body model fitting time is deter-

mined by the number of mice tracked (the particle filter sorting step scales exponentially with the number

of mice, because the algorithm evaluates multi-animal poses).

1157

1158   ***Body model***

1159 We model each mouse at two prolate ellipsoids. The model is specified by the 3D coordinate of the center

1160 of the hip ellipsoid, $\bar{c}_{hip} = [x, y, z]$, and the major and minor axis of the ellipsoids are scaled by a coordi-

1161 nate, $s \in [0,1]$ that can morph the ellipsoid from long and narrow to short and fat:

1162
$$a_{hip} = a_{hip,0} + a_{hip,\Delta} \cdot s$$

1163
$$b_{hip} = b_{hip,0} + b_{hip,\Delta} \cdot (1 - s)$$

1164 The 'neck' (the joint of rotation between the hip and nose ellipsoid) is sitting a distance, $d_{hip} = 0.75 \cdot$

1165 a_{hip}, along the central axis of the hip ellipsoid. In the frame of reference of the mouse body (taking $\bar{c}_{hip}$

1166 as the origin, with the major axis of the hip ellipsoid along the *x*-axis), a unit vector pointing to of the nose

1167 ellipsoid, from the 'neck' to the center of the nose ellipsoid along the major axis is:

1168
$$\bar{e}_{nose} = \begin{bmatrix} \cos\theta \\ \sin\theta \cos\phi \\ \sin\theta \sin\phi \end{bmatrix}$$

1169 In the frame of reference of the laboratory ('world coordinates'), we allow the hip ellipsoid to rotate around

1170 the *z*-axis ('left'/'right') and around the *y*-axis ('up'/'down', in the frame of reference of the mouse). We

1171 define $\mathbf{R}(\alpha_x, \alpha_y, \alpha_z)$ as a 3D rotation matrix specifying the rotation by an angle α around the three axes,

1172 and $\mathbf{R}(\bar{v}_1, \bar{v}_2)$ as a 3D rotation matrix that rotates the vector $\bar{v}_1$ onto $\bar{v}_2$. The we can define:

1173
$$\mathbf{R}_{hip} = \mathbf{R}(0, \beta, \gamma)$$

1174
$$\mathbf{R}_{head} = \mathbf{R}(\bar{e}_x, \bar{e}_{nose})$$

1175 , where $\bar{e}_x$ is a unit vector along the *x*-axis. In the frame of reference of the mouse body, the center of the

1176 nose ellipsoid is:

1177
$$\bar{c}_{nose,mouse} = \mathbf{R}_{head} \begin{bmatrix} d_{nose} \\ 0 \\ 0 \end{bmatrix} + \begin{bmatrix} d_{hip} \\ 0 \\ 0 \end{bmatrix}$$

1178 So, in world coordinates, the center is:

1179
$$\bar{c}_{nose,world} = \mathbf{R}_{hip} c_{nose,mouse} + \bar{c}_{hip}$$

1180 The center of the neural implant if offset from the center of the nose ellipsoid by a distance x_{impl} along

1181 the major axis of the nose ellipsoid, and a distance z_{impl} orthogonal to the major axis. We allow the im-

1182 plant to rotate around the nose ellipsoid by an angle, ψ. Thus, in the frame of reference of the mouse body,

1183 the center of the ellipsoid is:

1184
$$\bar{c}_{impl,mouse} = \mathbf{R}_{head} \begin{bmatrix} s_{impl} \\ d_{impl} \cdot \cos\psi \\ d_{impl} \cdot \sin\psi \end{bmatrix} + \begin{bmatrix} d_{hip} \\ 0 \\ 0 \end{bmatrix}$$

1185 And in world coordinates, same as the center of the nose ellipsoid:

1186
$$\bar{c}_{impl,world} = R_{hip} c_{impl,mouse} + \bar{c}_{hip}$$

1187 We calculated other skeleton points (tip of the nose ellipsoid, etc.) in a similar method. We can use the

1188 rotation matrices for the hip and the nose ellipsoids to calculate the characteristic ellipsoid matrices:

1189
$$\mathbf{Q}_{hip} = \mathbf{R}_{hip} \begin{bmatrix} 1/a_{hip}^2 & 0 & 0 \\ 0 & 1/b_{hip}^2 & 0 \\ 0 & 0 & 1/b_{hip}^2 \end{bmatrix} \left(\mathbf{R}_{hip}\right)^T$$

1190
$$\mathbf{Q}_{nose} = \mathbf{R}_{hip}\mathbf{R}_{head} \begin{bmatrix} 1/a_{nose}^2 & 0 & 0 \\ 0 & 1/b_{nose}^2 & 0 \\ 0 & 0 & 1/b_{nose}^2 \end{bmatrix} \left(\mathbf{R}_{hip}\mathbf{R}_{head}\right)^T$$

Calculating the shortest distance from a point to the surface of an 3D ellipsoid in 3 dimensions requires

solving a computationally-expensive polynomial[39]. Doing this for each of the thousands of points in the

point-cloud, multiplied by four body ellipsoids, multiplied by 200 particles pr. fitting step is not compu-

tationally tractable. Instead, we use the shortest distance to the surface, $\tilde{d}$, along a path that passes through

the centroid (**Supplementary Fig. 8a,b**). This is a good approximation to d (especially when averaged

over many points), and the calculation of $\tilde{d}$ can be implemented as pure vectorized linear algebra, which

can be calculated very efficiently on GPU[40]. Specifically, to calculate the distance from any point $\bar{p}$ in the

point-cloud, we just center the points on the center of an ellipsoid, and – for example – calculate:

1199
$$\bar{p}' = \bar{p} - \bar{c}_{hip}$$

$\tilde{d} = \left|1 - \|\bar{p}'\|_{Q_{hip}}^{-1}\right| \cdot \|\bar{p}'\|$ where $\|\bar{p}'\|_{Q_{hip}} = \sqrt{\langle\bar{p}',\bar{p}'\rangle}_{Q_{hip}} = \sqrt{(\bar{p}')^T Q_{hip}\, \bar{p}'}$

In fitting the model, we used the following constants: $a_{nose} = 2.00$ cm, $b_{nose} = 1.20$ cm, $a_{hip(min)} =$

0.50 cm, $a_{hip(max)} = 2.50$ cm, $b_{hip(min)} = 1.20$ cm, $b_{hip(max)} = 1.50$ cm, $d_{nose} = 1.00$ cm, $d_{hip} =$

$0.75 \cdot a_{hip}$, $r_{impl} = 0.9 \cdot b_{nose}$, $x_{impl} = d_{nose} + 0.5 \cdot a_{nose}$, $z_{impl} = 1.5 \cdot r_{impl}$. The code includes a pa-

rameter ('body_scale') that can be changed to scale the mouse body model (e.g. for other strains, or juve-

nile mice).

1206

Loss function evaluation and tracking

Joint position of the two mice is represented as a particle in 17-dimensional space. For each data frame,

we start with a proposal particle (leftmost green block, based on previous frames), from which we generate

200 particles by pseudo-random perturbation within a search space (next green block). For each proposal

particle, we calculate three types of weighted loss contributions: loss associated with the distance from

the point-cloud to the surface of the mouse body models (top path, green color), loss associated with body

key-points (middle path, key-point colors as in and loss associated with overlap of the two mouse body

models (bottom path, purple color). We broadcast the results in a way, which allows us to consider all

200x200 = 40.000 possible joint postures of the two mice. After calculation, we pick the top 200 joint

postures with the lowest overall loss, and anneal the search space, or – if converged – continue to the next

frame. When we continue to a new frame, we add the fitted frame to an online recursive filter bank, which

proposes the next position of the particle for the next frame, based on previous frame. All loss function

calculations, and recursive filter predictions are implemented as pure tensor algebra, fully vectorized and

executed on a GPU.

1221

Online recursive filtering

To propose a new location for the particle filter between frames, we use a recursive least squares filter [89],

with a time embedding of 5 steps, a forgetting factor of $\mu = 0.99$ and a regularization factor of $\varepsilon = 0.1$.

Our implementation ('rls_bank') is based on the implementation in the Padasip (Python Adaptive Signal

Processing) library (https://github.com/matousc89/padasip). For the first 150 frames, the filter is only

trained, but after frame 150, the filter is used for prediction. The code allows this filter to run across all

dimensions of the particle filter, but – in practical use – we found it sufficient to run it across the x-, y-

and z- coordinates of the center of the two mouse body models (i.e., we just assume that the angular and

stretch coordinates do not change from the last frame – this saves a few computations, and can be selected

by commenting in/out the relevant lines in the code).

1232

Regularizations

To regularize the particle filter algorithm, we imposed two hard rules ('barriers') on the movement of the

body models (shown in **Supplementary Figure 8**). The first barrier was implemented by adding a large

term to the particle filter's loss function, if the center of any ellipsoids from two different bodies were

closer than 0.8 times the sum of their short axes (this barrier allows a 20% overlap of spheres with a radius

equal to the ellipsoid's small axis, drawn in purple in **Supplementary Fig. 8f**). This barrier term prevents

'unphysical' overlaps between the body models of the two mice. The second barrier was implemented by

adding a large term to the particle filter's loss function, if the same condition was met between the current

position of a mouse body model and the interaction partners body model *in the preceding fram*e (**Supple-**

mentary Fig. 8h). This barrier term prevents 'flips' between the two mice (where the body models change

identity), as drawn in in **Supplementary Figure 8g**.

1244

1245   ***State space filtering of raw tracking data***

1246   After tracking, the coordinates of the skeleton points (c_{hip}, c_{nose}, etc.) were smoothed with a 3D kinematic

1247   Kalman filter tracking both the 3D position (p), velocity (v) and (constant) acceleration (a). For example,

1248   for the center of the hip coordinate:

1249
$$\bar{x} = \left[p_x, v_x, a_x, p_y, v_y, a_y, p_z, v_z, a_z\right]$$

1250
$$\bar{z} = \left[c_{hip,x}, c_{hip,y}, c_{hip,z}\right]$$

1251
$$\mathbf{F} = \begin{bmatrix} \mathbf{F'} & \mathbf{0} & \mathbf{0} \\ \mathbf{0} & \mathbf{F'} & \mathbf{0} \\ \mathbf{0} & \mathbf{0} & \mathbf{F'} \end{bmatrix}, \text{where } \mathbf{F'} = \begin{bmatrix} 1 & dt & \frac{1}{2}dt^2 \\ 0 & 1 & dt \\ 0 & 0 & 1 \end{bmatrix}$$

1252
$$\mathbf{H} = \begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 \end{bmatrix}$$

1253
$$\mathbf{P} = \mathbf{1}_{9\times9} \cdot \sigma_{cov}^2$$

1254
$$\mathbf{R} = \mathbf{I}_{3\times3} \cdot \sigma_{measurement}^2$$

1255
$$\mathbf{Q} = \begin{bmatrix} \mathbf{Q'} & \mathbf{0} & \mathbf{0} \\ \mathbf{0} & \mathbf{Q'} & \mathbf{0} \\ \mathbf{0} & \mathbf{0} & \mathbf{Q'} \end{bmatrix} \cdot \sigma_{process}^2$$

where **Q'** is the Q matrix for a discrete constant white noise model $\mathbf{Q'} = \begin{bmatrix} \frac{1}{4}dt^4 & \frac{1}{2}dt^3 & \frac{1}{2}dt^2 \\ \frac{1}{2}dt^3 & dt^2 & dt \\ \frac{1}{2}dt^2 & dt & 1 \end{bmatrix}$ and

$\sigma_{measurement} = 0.015$ m, $\sigma_{process} = 0.01$ m, $\sigma_{cov}^2 = 0.0011$ m². The σ's were the same for all points,

except the slightly more noisy estimate of the center of the implant, where we used. $\sigma_{measurement} =$

0.02 m, $\sigma_{process} = 0.01$ m, $\sigma_{cov}^2 = 0.0011$ m² From the frame rate (60 fps), $dt = \frac{1}{60}$ s. The maximum-

likelihood trajectory was estimated with the Rauch-Tung-Striebel method[48] with a fixed lag of 16 frames.

The filter and smoother was implemented using the 'filterpy' package (https://github.com/rlabbe/filterpy).

The spine scaling, *s*, was smoothed with a similar filter in 1D, except that we did not model acceleration,

only *s* and a (constant) *s* 'velocity', with $\sigma_{measurement} = 0.3$, $\sigma_{process} = 0.05$ m, $\sigma_{cov}^2 = 0.0011$.

After filtering the trajectories of the skeleton points, we recalculated the 3D rotation matrices of the hip

and head ellipsoid by the vectors pointing from c_{hip} to c_{mid} (from the middle of the hip ellipsoid to the

neck joint), and from c_{hip} to c_{nose} (from the neck joint to the middle of the nose ellipsoid). We then con-

verted the 3D rotation matrixes to unit quaternions, and smoothed the 3D rotations by smoothing the

quaternions with an 10-frame boxcar filter, essentially averaging the quaternions by finding the largest

eigenvalue of a matrix composed of the quaternions within the boxcar [50]. After smoothing the ellipsoid

rotations, we re-calculated the coordinates of the tip of the nose ellipsoid (c_{tip}) and the posterior end of

the hip ellipsoid (c_{tail}) from the smoothed central coordinates, rotations, and − for c_{tail} − the smoothed

spine scaling. A walkthrough of the state space filtering pipeline is shown in **Supplementary Figure 12**.

1273

Template matching

To detect social events, we calculated three social distances, from three instantaneous 'social distances',

defined as the 3D distance between the tip of each animal's noses ('nose-to-nose'), and from the tip of

each animal's nose to the posterior end of the conspecific's hip ellipsoid ('nose-to-tail'; **Fig. 5c**). From

these social distances, we could automatically detect when the mouse bodies were in a nose-to-nose (if

the nose-to-nose distance was < 2 cm and the nose-to-tail distance was > 6 cm) and in a nose-to-tail

configuration (if the nose-to-nose distance was > 6 cm and the nose-to-tail distance was > 2 cm). The

events were detected by the logic conditions, and then single threshold crossings due to noise were re-

moved by binary opening with a 3-frame kernel, followed by binary closing with a 30-frame kernel.

1283

State space modeling of mouse behavior

State space modeling of the locomotion behavior was performed in Pyro[56] a GPU-accelerated probabilistic

programming language built on top of Pytorch[44]. We modeled the (centered and whitened) locomotion

behavior as a hidden Markov model with discrete latent states, z, and associated transition matrix, $\mathbf{T}$.

$$z(t + 1) = \text{Categorical}(e_{z(t)}^T \cdot \mathbf{T})$$

$$\mathbf{T} = \begin{bmatrix} p_{ij} & \cdots \\ \vdots & \ddots \end{bmatrix}$$

To make the model 'sticky' (discourage fast switching between latent states) we draw the transition prob-

abilities, p_{ij} from a Dirichlet prior with a high mass near the 'edges' and initialize $\mathbf{T}_{init} = (1 - \eta)\mathbf{I} +$

η/n_{states} where $\eta = 0.05$.

$$p \sim \text{Diriclet}(0.5)$$

Each state emits a forward speed and a left speed, drawn from a two-dimensional Gaussian distribution

with a full covariance matrix.

$$\begin{bmatrix} v_{\text{fwd}} \\ v_{\text{left}} \end{bmatrix} \sim \text{MVNormal}(\mu, \mathbf{S})$$

We draw the mean of the states from a normal distribution and use a LKJ Cholesky prior for the covariance:

$$\mu \sim \text{Normal}(0,1)$$

1299
$$S = \begin{bmatrix} \sigma_{\text{fwd}} & 0 \\ 0 & \sigma_{\text{left}} \end{bmatrix} L \begin{bmatrix} \sigma_{\text{fwd}} & 0 \\ 0 & \sigma_{\text{left}} \end{bmatrix}$$

1300
$$\sigma \sim \text{LogNormal}(-1,1)$$

1301
$$L \sim \text{LKJcorr}(2)$$

The up speed was modeled in a similar way, except that the latent states were just a one-dimensional

normal distribution. The means and variances for the latent states was initialized by kmeans clustering of

the locomotion speeds. The model was fit in parallel to 600-frame snippets of a subset of the data by

stochastic variational inference[90]. We used an automatic delta guide function ('AutoDelta') and an evi-

dence lower bound (ELBO) loss function. The model was fitted by stochastic gradient descent with a

learning rate of 0.0005. After model fitting, we generated the ethograms by assigning latent states by

maximum a posteriori probability with a Viterbi algorithm.

1309

3D head direction estimation

We use the 3D position of the ear key-points to determine the 3d head direction of the partner animal. We

assign the ear key-points to a mouse body model by calculating the distance from each key-point to the

center of the nose ellipsoid of both animals (cutoff: closest to one mouse and < 3cm from the center of the

head ellipsoid, **Supplementary Fig 17a**). To estimate the 3D head direction, we calculate the unit rejection

(v_{rej}) between a unit vector along the nose ellipsoid (v_{nose}) and a unit vector from the neck joint (c_{mid})

to the average 3D position of the ear key-points that are associated with that mouse (v_ear_direction,

Supplementary Fig. 17b). If no ear key-points were detected in a frame, we linearly interpolate the aver-

age 3D position. To average out jitter, the estimates of the average ear coordinates and the center of the

nose coordinate were smoothed with a Gaussian ($\sigma = 3$ frames). The final head direction vector was also

smoothed with a Gaussian ($\sigma = 10$ frames).

1321

Extracellular recording and spike clustering

Extracellular recordings were made with sharpened 2-shank, 32-site NeuroNexus P2 profile silicon probes

(NeuroNexus Technologies, Inc., MI, USA). The silicon probes were implanted in barrel cortex using a

stereotax (1 mm posterior, 3.2 mm lateral to bregma[91]) under isoflurane anesthesia using a custom 3D

printed plastic microdrive and base plates for mice, shielded by a copper mesh and bound to the animal's

skull using dental cement[92]. The neural data was recorded using an Intan RHD 32-channel headstage with

accelerometer (Intan Technologies, CA, USA) connected to an Open Ephys Acquisition Board[93]

(https://open-ephys.org/) at 30 kHz/16 bit resolution. The neural data was pre-clustered using SpyKING

CIRCUS[94] (a custom probe geometry file for the P2 probe and the full clustering script with all parameters

is available in the supplementary code) and checked manually for cluster quality in KLUSTA[95]. Only well-

separated single units were included in the analysis.

1333

PSTH-based analysis of neural responses

For the PSTH-based analysis, we triggered on the three social events detected as described under 'Tem-

plate matching'. For the 'naïve' PSTH, we included all events, and for the 'cleaned' PSTH, we only in-

cluded events, where there was no other of the detected events occurring in the preceding 4 seconds.

Significant firing rate changes were detected by comparing the average firing rate, r_{pre} , between –4 s and

–2 s (relative to the start of the detected event) with the average firing rate, r_{post} , between –0.5 s and 0.5

s, using a Wilcoxon signed rank test, at $p < 0.05$. The firing rate modulation index was calculated using

the same firing rates and defined as:

1342
$$\text{Mod. idx.} = \frac{r_{post} - r_{pre}}{r_{post} + r_{pre}}$$

1343

Statistical modeling of neural tuning curves

Our spike train modeling approach is based on ref. [62] and our python code for model fitting and model

selection is based on the supplementary Matlab code from that study (available at

https://github.com/GiocomoLab/ln-model-of-mec-neurons). We calculated the following features of the

'social scene' (shown in the table below). In the table, we only list the variables associated with the pos-

ture, spatial location and movement of the implanted animal (subscript 0). We include identical features

for the partner animal (subscript 1). The bin rages were selected to span the physically possible values

(e.g., within the circular arena), or to span the observed values in the behavior (for movement speeds, for

example).

1353

1354

Class	Feature	Variable name in code	Definition	Binning	Unit	Tuning curve type
Social	Nose <-> Nose	d_n2n	Nose-to-nose distance	[0.01 ,0.29], Δbin = 0.02	m	Linear
	Nose0 -> Tail1	d_n0t1	Distance from the nose of the implanted animal to the tail base of the partner animal	[0.01 ,0.29], Δbin = 0.02	m	Linear
	Nose1 -> Tail0	d_n1t0	Distance from the nose of the partner animal to the tail base of the Implanted animal	[0.01 ,0.29], Δbin = 0.02	m	Linear
	d/dt[d_social]	diffd_social	Temporal derivative in the distance between the center (c_mid) of the two mice, convolved with a Gaussian (σ = 10 frames).	[−0.002,0.002], 15 bins	m/frame	Linear
	Orientation angle	a_gaze_mid	Relative orientation of the mice (with the implanted animal as the reference), defined as the angle between a vector along the nose ellipsoid of the implanted animal, and a vector along the body ellipsoid of the partner animal (both	[−π,π-(π/15)], 15 bins	rad	Circular

			vectors pro-jected into the xy-plane).			
Posture	Head yaw	a_nose_lr_0	Angle between a vector along the nose ellipsoid and a vector along the hip el-lipsoid, in the xy-plane)	[−π/3,π/3], 15 bins	rad	Linear
	Head pitch	a_nose_ud_0	The elevation angle of the nose ellipsoid, relative to the hip ellipsoid (The elevation angle between a vector along the nose ellipsoid and the xy-plane, minus the elevation angle of the hip ellip-soid).	[−0.9,0.9], 15 bins	rad	Linear
	Head roll	head_roll_0	Angle between a vector from the center of the nose ellipsoid to the 'top' of the head (the center of the implant for the im-planted animal, the center of the ears in the part-ner animal) and a vector along the z-axis.	[−2π/3,2π/3], 15 bins	rad	Linear
	Hip pitch	a_hip_eleva-tion_0	The elevation angle between a vector along the hip ellipsoid and the xy-plane.	[0,π/2], 15 bins	rad	Linear
	Spine stretch	s0	Stretch parame-ter of the hip el-lipsoid in the body model	[0.5,1.0], 15 bins	a.u.	Linear
Spatial	x	x_hip_0	x-component of the center of the hip ellipsoid (c_hip)	[−0.13,0.13], 15 bins	m	Linear

	y	y_hip_0	y-component of the center of the hip ellipsoid (c_hip)	[−0.13,0.13], 15 bins	m	Linear
	z	z_hip_0	z-component of the center of the hip ellipsoid (c_hip)	[0.02,0.05], 15 bins	m	Linear
	Distance to center	d_arena_0	Distance from the center of the hip ellipsoid to the center of the behavioral arena	[0.,0.14], 15 bins	m	Linear
	Head direction	a_nose_hd_0	Angle of the nose ellipsoid in the xy-plane	[−π,π-(π/15)], 15 bins	rad	Circular
Movement	v_fwd	fwd_0	Forward component (along the hip ellipsoid) of the speed vector, in the xy-plane	[−0.05,0.2], 15 bins	m/s	Linear
	v_left	left_0	Orthogonal component of the speed vector, in the xy-plane	[−.0.05,0.05], 11 bins	m/s	Linear
	v_up	up_0	z-component of the speed vector	[−0.04,0.05], Δbin = 0.01	m/s	Linear
	|v|	speed3D_0	Norm of the speed vector	[0.01,0.20], 15 bins	m/s	Linear
	d/dt[head yaw]	diffa_nose_lr_0	Derivative of the head yaw, convolved with a Gaussian ($\sigma = 10$ frames).	[−0.04,0.04], 15 bins	rad/frame	Linear
	d/dt[head pitch]	diffa_nose_ud_0	Derivative of the head pitch, convolved with a Gaussian ($\sigma = 10$ frames).	[−0.04,0.04], 15 bins	rad/frame	Linear
	d/dt[head roll]	diffhead_roll_0	Derivative of the head roll, convolved with a Gaussian ($\sigma = 10$ frames).	[−0.04,0.04], 15 bins	rad/frame	Linear
	d/dt[hip yaw]	diffa_hip_hd_0	Derivative of the hip yaw, convolved with a Gaussian ($\sigma = 10$ frames).	[−0.15,0.15], 15 bins	rad/frame	Linear
	d/dt[hip pitch]	diffa_hip_elevation_0	Derivative of the hip pitch,	[−0.3,0.3], 15 bins	rad/frame	Linear

			convolved with a Gaussian ($\sigma = 10$ frames).			
	d/dt[spine stretch]	diffs0	Derivative of the spine stretch, convolved with a Gaussian ($\sigma = 10$ frames).	[−0.1,0.1], 15 bins	1/frame	Linear

1355

We model the observed spike train as generated by the following process (**Fig. 7c**): The spikes are gener-

ated by a Poisson process. The rate of the Poisson process is determined by the features, in the following

way: Each feature is multiplied with a tuning curve (taking any real value), to generate a weight. The

weights of all features are summed, pass through an exponential nonlinearity (to clamp the rate of the

Poisson process to be positive). This means that in the spike rate space, the tuning to the features is mul-

tiplicative.

1362

1363 We convert each feature into binary dummy variables by binning (bins listed in the table above) to generate

1364 a time-by-bins matrix, A, where the i'th and j'th index is a binary variable indicating if the feature was in

1365 the j'th feature bin in the i'th frame. If we let $\bar{c}$ be a column vector with the values of the tuning curve for

1366 a single predictor, then our linear model says that the rate of the Poisson process generating the spikes, λ,

1367 depending on p predictors can be expressed as

1368
$$\bar{\lambda} = \exp\left(\sum_p A_p \bar{c}_p \right)/dt$$

1369 We fit the linear model by tuning the parameters of the tuning curves to maximize of the Poisson log-

1370 likelihood of the observed number of spikes, n, in each bin of the spike train. We include a regularization

1371 term, β, that ensures that the tuning curves are smooth (it is a loss term associated with the difference

1372 between c_i and c_{i+1}, with circular wrap-around for the circular features). Thus, the fitted tuning curves

1373 are:

1374
$$\hat{c} = \text{argmax}_c \sum_i \log P\left(n_i | \exp\left(\sum_p A_p \bar{c}_p \right) \right) - \sum_p \beta \left(\sum_i \frac{1}{2}(c_{p,i} - c_{p,i+1})^2 \right)$$

1375

1376   We fit the models using the Newton conjugate gradient trust-region algorithm ('trust-ncg' method in 'min-

1377   imize' in the SciPy optimize module, using the Taylor expansion approximation to the Jacobian and Hes-

1378   sian and a tolerance of 1e-3).

1379

To determine which features significantly contribute to the firing rate modulation of a neuron, we use a

cross-validated model comparison approach, and a greedy forward selection of features. First, we compare

a fitted 'baseline' model where the spikes are simply generated by a Poisson process with a constant rate

to 45 fitted models, that include only one feature. The comparison is cross-validated, such that we fit the

model on 90% of the data and evaluate on 10% held-out data (with 3 skips, i.e., we split the data in 30

chunks, fit to 27 and evaluate on 3). To compare each of the one-feature models to the baseline model, we

calculate the increase in log-likelihood of the test data, given the fitted one-feature models (relative to the

baseline model), across all 10 permutations of the 10-fold cross validation. We select the best candidate

feature (defined as the one with the highest average increase in log-likelihood, across the 10 folds), and

check if the increase in log-likelihood is significant by performing a one-sided Wilcoxon signed-rank test,

with a criterion of $p < 0.05$. If the best candidate feature is significant, we add that feature to a library of

features that we consider significant for that neuron. If we have the number of spikes in the spike train, $\bar{n}$,

and the maximum-likelihood fitted rate is $\bar{\lambda}(\hat{c})$, then the log-likelihood increase, $\Delta\mathcal{L}$ (in bits/spike) is:

1393
$$\mathcal{L}_{\text{model}} = \left(\sum_i \lambda_i - n_i \log(\lambda_i) + \log(n_i!) \right) / \sum_i n_i$$

1394
$$\mathcal{L}_{\text{constant}} = \left(\sum_i \langle n \rangle - n_i \log(\langle n \rangle) + \log(n_i!) \right) / \sum_i n_i$$

1395
$$\Delta\mathcal{L} = -\log(2) \cdot (\mathcal{L}_{\text{model}} - \mathcal{L}_{\text{constant}})$$

For all (N>1)-feature models (two features, three features, etc.), we use the same approach: We fit all

possible models that add one more feature to the library of N-1 significant features (all tuning curves of

all features in the library are re-fit every time), we select the best candidate feature, and use a one-sided

Wilcoxon signed-rank test between a model with N features and a model with N-1 features to determine

if that candidate feature is significant and should be added to the library. If the one-sided Wilcoxon signed-

rank test is not significant at $p < 0.05$, we stop the search for new features to add to the library.

1402

1403 ***Population structure analysis***

1404 The Euler diagram in Figure 8d was drawn in R using the eulerr package[96]. The network co-encoding

1405 graph shown in Figure 8e was drawn in the Kamada-Kawai projection[88] (the distance between nodes ap-

1406 proximate their graph-theoretical distance), using the NetworkX python package[97].