Two-pass alignment using machine-learning-filtered splice

junctions increases the accuracy of intron detection in long-

read RNA sequencing

Matthew T. Parker[1]*, Geoffrey J. Barton[1], Gordon G. Simpson[1,2]*

[1]School of Life Sciences, University of Dundee, Dow Street, Dundee, DD1 5EH, UK

[2]James Hutton Institute, Invergowrie, DD2 5DA, UK

*Correspondence: m.t.parker@dundee.ac.uk; g.g.simpson@dundee.ac.uk

Abstract

Transcription of eukaryotic genomes involves complex alternative processing of RNAs. Sequencing of full-length RNAs using long-reads reveals the true complexity of processing, however the relatively high error rates of long-read technologies can reduce the accuracy of intron identification. Here we present a two-pass approach, combining alignment metrics and machine-learning-derived sequence information to filter spurious examples from splice junctions identified in long-read alignments. The remaining junctions are then used to guide realignment. This method, available in the software package 2passtools (https://github.com/bartongroup/2passtools), improves the accuracy of spliced alignment and transcriptome annotation without requiring orthogonal information from short read RNAseq or existing annotations.

Background

Understanding eukaryotic genomes requires knowing not only the DNA sequence but also which RNAs are transcribed from it. Eukaryotic transcription by DNA-dependent RNA polymerase II is associated with multiple alternative RNA processing events that diversify the coding and regulatory potential of the genome. Alternative processing choices include distinct transcription start sites, the alternative splicing of different intron and exon combinations, alternative sites of cleavage and polyadenylation, and base modifications such as methylation of adenosine. Patterns of alternative processing can be extensive. For example, more than 90% of human protein-coding genes have at least two splice isoforms[1]. Changes in RNA processing can reflect the reprogramming of gene expression patterns during development or in response to stress or result from genetic mutation or disease. Consequently, the identification and quantification of different RNA processing events is crucial to understand not only what genomes encode but also the biology of whole organisms[2].

The sequencing of RNAs (RNAseq) can reveal gene expression patterns in specific cells, tissues or whole organism. The success of this approach depends upon sequencing methodology and the computational analyses used in interpreting the sequence data. High-throughput sequencing of RNA rarely involves direct RNA sequencing (DRS): instead, copies of complementary DNA (cDNA) produced by reverse transcription of RNA molecules are sequenced[2]. However, template strand switching by reverse transcriptase (RT) during the copying process can produce spurious splicing patterns and antisense RNA signals[3,4]. Three current technologies use RT-based RNA sequencing library preparation: Illumina, Pacific Biosciences (PacBio) and Oxford Nanopore Technologies (ONT). Illumina RNAseq can generate hundreds of millions of highly accurate short sequencing reads, each representing a 50–250 nt fragment of full-length RNA[2]. Methods exist for quantifying known alternative splicing events from short reads[5]. However, when the transcript models are unknown, for example in a non-model organism or a mutant or disease with altered RNA processing, new transcript models must be generated, either *de novo* or with the aid of the reference genome. Because Illumina reads are short, they are unlikely to overlap multiple splice junctions, meaning that phasing of splicing events is difficult and requires complex computational reconstruction[6-8]. PacBio and ONT can sequence full-length cDNA copies without fragmentation, thus allowing whole transcript isoforms to be identified unambiguously[2]. Most recently, ONT introduced a direct sequencing method for RNA[9-11]. Using this approach, it is now possible to capture information on the splicing, 5' and 3' ends, poly(A) tail length, and RNA modifications of full-length RNA molecules in a single experiment, without RT-associated artefacts[11].

The development of technologies for sequencing full-length RNA molecules makes the identification of

authentic processing events possible in principle, but software tools are also needed to interpret the

RNA processing complexity. PacBio and ONT sequencing reads have a higher error rate than Illumina[10-14].

Consequently, alignment accuracy for long sequence reads at splice junctions is often compromised[9-11].

This is a problem for genome-guided transcriptome annotation because the incorrect identification of

splice junctions leads to mis-annotated open reading frames and incorrectly truncated protein

predictions. In addition, if alignment errors are systematic (i.e. occur for transcripts with specific

characteristics), then quantification of transcripts will be compromised. Even with completely error-free

reads, alignment at splice junctions is often confounded by multiple equally plausible alternatives[15].

Accordingly, computational methods for improving the splice-aware alignment of long reads are

required.

Software tools for long and short RNAseq data analysis incorporate several approaches to address the

challenges presented by pre-mRNA splicing. Biologically relevant information can aid the alignment of

transcriptomic sequences to the genome. For example, the vast majority of eukaryotic splicing events

occur at introns bordered by GU and AG motifs. Making RNAseq read aligners aware of these sequence

features (as is the case for the commonly used spliced aligners STAR[16], HISAT2[17] and minimap2[18]) can

significantly improve the alignment of reads at splice junctions. In addition, where genome and

transcriptome annotations exist, many alignment tools allow users to provide sets of correct splice

junctions to guide alignment[16-19]. Introns containing these guide splice junctions are penalised less than

novel introns, resulting in fewer alignment errors. For long reads, software tools such as FLAIR[10] use

post-alignment correction to improve splice junction detection and quantification. Post-alignment

correction tools take long-read alignments and guide splice junctions from either a reference annotation

or set of accurate short RNAseq reads[10]. Introns from long-read alignments which are not supported by

the guide splice junction set are "corrected" to the nearest supported junction within a user-defined

range. It is unclear whether such post-alignment corrections confer any benefit over providing guide

splice junctions during alignment.

Two-pass alignment has also been used to improve splice junction detection and quantification[16,19,20]. In

a two-pass alignment approach, splice junctions detected in a first round of alignment are scored less

negatively in a second round, thereby allowing information sharing between alignments. This approach

has been useful for short-read data, where RNA fragmentation may occur close to splice junctions

during sequencing library preparation. The two-pass approach enables these short junction overhangs

to be aligned to splice junctions detected in other alignments[20]. Splice junctions detected in a first pass

may also be filtered to remove false positives before second-pass alignment. Existing tools for splice

junction filtering, such as finesplice and portcullis[21,22], use machine learning with training on a range of

junction metrics. A model is trained from high-confidence positive and negative examples from training

data and then applied to classify the remaining splice junctions at the decision boundary. Splice

junctions are then filtered to remove junctions predicted to be spurious. Subsequent second-pass

alignment guided by these filtered junctions can then improve the accuracy of alignment[22].

In this study, we develop a method for filtered two-pass alignment of the relatively high-error long reads

generated by techniques such as nanopore DRS. The resulting software, which we have named

2passtools, uses a rule-based approach to identify probable genuine and spurious splice junctions from

first-pass read alignments. These can then be used to train a logistic regression (LR) model to identify

the biological sequence signatures of genuine splice junctions. We found that integrating the alignment

and sequence information extracted in this manner produced the largest improvement in splice junction

alignment and subsequent genome-guided annotation. As a result, we can improve the utility of long-

read sequencing technologies in revealing the complexity of RNA processing and annotating newly

sequenced organisms.

Results and Discussion

Reference-splice-junction-aware alignment is more accurate than post-alignment junction correction

For sequencing experiments designed to interpret RNA from model organisms, a set of reference splice

junctions will already be available (e.g. from Ensembl). We therefore asked how providing these

reference splice junctions to minimap2 to guide alignment performed compared with post-alignment

correction of junctions with FLAIR[10]. For this, we used four nanopore DRS datasets generated from

Arabidopsis seedlings[11] and four datasets generated from human cell lines[10]. Several types of probable

alignment error were identifiable in these data, including failure to align terminal exons and short

internal exons, spurious terminal exons, and large insertions to the reference genome (Fig. 1). Because

these datasets are likely to contain novel splice junctions which do not appear in reference annotations,

we simulated full-length reads (i.e. with no 3' bias[11]) using the Arabidopsis and human reference

transcriptomes, AtRTD2[23] and GRCh38[24], respectively. Simulated reads were then mapped to the

corresponding reference genome using minimap2[18], either with or without guidance from reference

splice junctions. Alignments of simulated reads were found to have similar error profiles to genuine

nanopore DRS read alignments (Fig. S1A–C). Reads mapped without reference splice junctions were

then corrected using FLAIR with reference splice junctions.

Although nanopore DRS has some systematic errors in base-calling (particularly at homopolymers), the

majority of sequencing errors occur stochastically[25]. In contrast, we found that alignment errors were

often repeated at similar locations in the alignments of independent reads from equivalent mRNA

transcripts (Fig. 1, Fig. 2A). A common alignment error at splice junctions is failure of a short exon to

align correctly: instead, fragments of the exon are aligned to the ends of flanking exons, resulting in a

single incorrect intron. A clear example of such an alignment error was detected at the short (42 nt)

exon 6 of Arabidopsis *FLM* (*AT1G77080*; Fig. 2A). Minimap2 uses a modified form of the Smith–

Waterman algorithm for performing local alignment[18,26]. This method scores alignments using bonuses

for matches to the reference sequence and penalties for mismatches or the opening of insertions,

including introns. Incorrect alignment of *FLM* exon 6 is likely to occur because the bonus for aligning a

short exon with sequencing errors is not sufficient to overcome the penalty for opening the two flanking

introns[18]. Overall, we found that only 19.3% of simulated *FLM* reads aligned to the correct transcript

isoform. Because the sequence distance between the alignment and the genuine reference splice

junctions was so great, FLAIR was unable to perform post-alignment correction at *FLM* exon 6, resulting

in the reporting of incorrect introns (Fig. 2A). In all, 40.3% of simulated *FLM* reads were aligned to the

correct transcript isoform after FLAIR correction of splice junctions using the reference annotation.

However, providing reference splice junctions to minimap2 during alignment resulted in the correct

identification of *FLM* exons and introns in most cases: 92.1% of simulated *FLM* reads were aligned to the

correct transcript isoform. We conclude that for loci with complex splicing patterns, reference-splice-

junction-guided alignment performs better than post-alignment correction.

Without guidance from a reference annotation, we found that a median of 73.2% of Arabidopsis reads

and 44.4% of human reads mapped correctly to the splice junctions of the transcript they were

simulated from (Fig. 2B). The difference between the two organisms may be explained by biological

differences between the two species (e.g. in intron size, number of exons per transcript, number of

intronless transcripts). After post-alignment correction of splice junctions using FLAIR, the number of

correctly identified transcripts detected was improved (median of 87.9% and 63.6% for Arabidopsis and

human reads, respectively; Fig. 2B). This came at the cost of a small increase in alignment of reads to

incorrect reference transcript splice junctions: from a median of 1.79% to 2.62% for Arabidopsis and

from 3.86% to 5.45% for human (Fig. S2A). This misclassification may affect the relative quantification of

transcripts for some genes, with implications for differential transcript usage analysis. Reference

annotation-informed alignment with minimap2 performed better than FLAIR, with a median of 93.8% of

Arabidopsis reads and 73.2% of human reads aligning correctly at the splice junctions of the transcript

they were simulated from (Fig. 2B), albeit with misclassification rates of 2.61% and 5.49% respectively

(Fig. S2A). We conclude that there is a clear benefit to providing reference splice junctions during

alignment of long reads with relatively high sequence error rates, and that this is preferable to post-

alignment correction.

Alignment metrics enable identification of genuine splice junctions

In newly sequenced organisms or conditions with novel RNA processing events, suitable reference

annotations to guide alignment may not be available. We therefore asked how the spliced alignment of

nanopore DRS reads might be improved in the absence of reference annotation. Naive two-pass

alignment has been successfully used to improve the spliced alignment of short reads[20]. We applied this

approach with our real and simulated nanopore DRS reads. Splice junctions identified by a first-pass

alignment of reads were selected and used (without filtering) to inform a second-pass alignment. We

found that using this simple approach the median percentage of simulated Arabidopsis DRS alignments

which matched the splice junctions of the reference transcript they were simulated from could be

increased slightly from 73.2% to 75.8% (Fig. S2B). The increase was similar for reads simulated from

human DRS alignments: from 44.4% to 47.3% (Fig. S2B).

We next considered whether further improvements in two-pass alignment could be obtained by filtering

out likely false-positive splice junctions from first-pass alignments. This would allow us to provide more

refined guide junctions for second-pass alignment (Fig. 3A). A similar approach worked for short reads

when splice junctions were filtered by using junction metrics to train a classifier in the portcullis

software tool[22]. By using the presence or absence of a splice junction in the reference annotation as a

ground truth, we considered a range of novel or previously introduced junction metrics[21,22], including

junction alignment distance, supporting read count, intron motif and the presence/absence of nearby

splice donor and acceptor sites with higher supporting read counts (Fig. S3A-D).

The junction alignment distance (JAD) is defined as the minimum distance to the first mismatch,

insertion or deletion on either overhang of a read alignment splice junction. This metric is used by both

finesplice and portcullis software tools[21,22]. For the simulated nanopore DRS read alignment datasets

sequenced from Arabidopsis RNA, we found that 88.9% of splice junctions found in the reference

annotation had at least one read alignment with a JAD of 4 nt, compared with only 10.1% of

unannotated splice junctions (Fig. 3B). Consequently, using a threshold of at least one read with a JAD of

4 nt, we could identify annotated splice junctions with an F1 score of 0.902 (Fig. S3A). Despite the high

probability of at least some genuine unannotated splice junctions in the real Arabidopsis data[11], we

found that the same JAD threshold could discriminate between annotated and unannotated splice

junctions in real datasets to a similar degree (F1 score = 0.899). Similar results were also seen for

simulated human datasets, where the same JAD threshold could discriminate between spurious

unannotated and genuine annotated splice junctions (F1 score = 0.868). We conclude that the JAD

metric is a powerful discriminator of genuine splice junctions across nanopore DRS datasets from

different organisms.

Of the other metrics we tested, the read count was predictive of genuine splice junctions at a threshold

of >1 read (F1 score = 0.833; Fig. S3B). However, read count correlated strongly with the JAD

(Spearman's ρ = 0.776), suggesting that it does not provide more information. The presence/absence of

a canonical intron motif (i.e. GU/AG, GC/AG or AU/AG) had a very high recall, as 99.96% of annotated

introns in the simulated alignments were canonical (Fig. S3C). However, the precision was poorer (F1

score = 0.783). This is because in spliced alignment mode minimap2 prefers GU/AG motifs, meaning that

67.1% of spurious splice junctions are also aligned so as to use canonical motifs.

Finally, we developed a primary donor/acceptor metric similar to the one used in portcullis[22]. This is

calculated by identifying alternative donor or acceptor sites in a 20 nt window around each

donor/acceptor and then determining whether they have greater read support than the current site. In

case of a tie for read support (e.g. if all splice junctions have a read count of 1), the JAD is used to break

the tie, i.e. sites with the largest maximum per-read JAD are considered most likely to be genuine and

labelled as a primary site. We found that the primary donor and acceptor metrics were also predictive of

genuine splice junctions (F1 scores = 0.842 and 0.785 respectively). By combining the metrics to select

splice junctions which are both primary donors and acceptors, the F1 score can be increased to 0.918

(Fig. S3D). It is unclear why the primary donor score is more predictive than the primary acceptor score.

A possible reason is that minimap2 is more likely to produce alignment errors at the donor site of splice

junctions (e.g. in the case of failure to align small internal exons) or that there are more genuine

alternative acceptor sites than donor sites.

We used the identified metrics to create a simple decision tree model. A five-node tree using the JAD,

primary donor/acceptor and canonical intron motif metrics (Fig. 3C) was best able to predict genuine

Arabidopsis splice junctions (F1 score = 0.935; Fig. 3D). The same decision tree also performed well in

predicting genuine and spurious splice junctions from simulated human reads (F1 score = 0.934). This

indicates that the model might generalise across nanopore DRS datasets from different organisms,

despite their differences in splicing complexity.

A combination of splice junction alignment metrics and sequence information improves authentic splice

junction identification

Genuine splice junctions have sequence biases which are defined by their interactions with spliceosomal

uridylate-rich small nuclear RNAs[27]. We next asked whether machine learning models could identify

genuine splice junctions from the flanking genomic sequences alone. For example, genome sequence

information might help identify genuine splice junctions with low read alignment coverage that fail to

pass the JAD filter due to stochastic sequencing errors. We therefore extracted 128 nt sequences

centred on unique donor and acceptor sites and used these to train LR models with labels generated by

the first decision tree model (Fig. 4A). Using 6-fold cross-validation, we were able to train six models on

83.3% of the data each and use them to make predictions for the remaining 16.7%. Using this approach,

we could generate predictions for all splice junctions, with no junction being used for both training and

prediction from the same model.

At a prediction threshold of 0.5, the model overclassified positive splice junctions. False positives may be

sequences which could in principle act as splice junctions but do not in reality due to effects that the

model cannot capture. One such effect could be the presence of alternative splice junctions which are

preferentially processed. This is thought to occur under the "first-come-first-served" model of co-

transcriptional splicing[28,29]. The model is also unlikely to be able to correctly identify the intron

branchpoint motif because this can vary in position relative to the acceptor site[30]. Nevertheless, we

found that the LR model approach could predict genuine splice junctions from sequence data alone with

comparable accuracy to the metric-based decision tree (Fig S4A-C). For example, for the simulated

Arabidopsis datasets, using LR on donor and acceptor sequences (with a prediction threshold of 0.5)

yielded an F1 score of 0.904 (Fig S4C), which was similar to the F1 score obtained with the JAD or

primary donor/acceptor metrics.

We next tested whether the information from the junction metrics and reference sequence model was

complementary, i.e. if a combination of the two approaches could produce an improvement in splice

junction prediction over each individual approach. Use of a second decision tree model, this time

including the JAD metric, primary donor/acceptor metrics and new LR prediction scores (Fig. 4B), further

increased the F1 score on splice junctions identified from simulated Arabidopsis read alignments to

0.954 (Fig. 4C). For splice junctions from simulated human reads, we also saw an increase in the F1 score

to 0.957. We conclude that an ensemble approach incorporating both junction metrics and sequence

information works best for detecting and filtering spurious splice junctions from alignments.

Two-pass alignment with filtered splice junctions improves transcript identification

We next applied the two decision tree filtering methods to perform two-pass alignment of the simulated

reads with minimap2[18]. Using filtered splice junctions, the percentage of junctions identified in second-

pass alignments which matched annotated splice junctions could be increased over first-pass alignment

and naive two-pass alignment (Fig. 5A). For example, using the simulated Arabidopsis datasets, the

median percentage of read alignments matching the splice junctions of the reference transcript they

were simulated from increased from 73.2% in the first pass to 88.2% and 89.3% in a second pass using

the first and second decision tree methods respectively (Fig. 5A). Two-pass alignment rescued the large

misalignments of exon 6 seen at *FLM* (Fig. S5A): overall, 86.8% of simulated *FLM* reads aligned to the

correct reference transcript after filtered two-pass alignment compared with 19.3% for first-pass

alignments. A global improvement in correct alignment was also seen in the simulated human datasets:

from 44.4% in the first pass to 64.3% and 65.7% for the two decision tree methods, respectively

(Fig. 5A).

Although two-pass alignment improved the number of reads aligning to the correct transcript model, we

also detected a slight increase in the number of reads aligning to the wrong annotated transcript. In the

simulated Arabidopsis reads, reads aligned using the second decision tree model performed worst on

this metric: 2.74% of reads aligned to the wrong isoform compared with only 1.79% of reads after first-

pass alignment (Fig. S5B). To assess whether such misassignment affects the quantitation of transcripts,

we calculated Spearman's correlation coefficient (ρ) for estimated versus known transcript level read

counts for the simulated data (Fig. 5B). The results indicated that, despite this misassignment, two-pass

aligned reads could be quantified accurately, with an overall improvement in median Spearman's ρ for

one-pass versus two-pass of from 0.876 to 0.916 for simulated Arabidopsis reads (Fig. 5B) and from

0.778 to 0.859 for simulated human reads (Fig. 5B). However, there may be corner cases where

transcript misassignment could have consequences for transcript usage analysis. This should be

considered for experiments where quantification is important. Overall, we conclude that two-pass

alignment using filtered junctions can improve both the detection of correct splicing patterns and the

quantitation of nanopore DRS reads.

Filtered two-pass alignment improves reference-guided annotation

Summarising read alignments into annotations facilitates transcript level quantification of short and long

reads and aids the interpretation of RNA processing complexity. We therefore asked whether two-pass

alignment of spliced long reads with relatively high sequence error rates can improve the results of

genome-guided annotation tools. Several software tools designed to produce annotations from long

reads exist, including FLAIR[10] and pinfish (ONT), which were designed for nanopore DRS data; TAMA[31],

which was designed for PacBio IsoSeq data; and StringTie2[6], which was designed as a technology-

agnostic long-read assembly tool.

We benchmarked our methods using StringTie2 because it is reported to be faster and more accurate

than FLAIR on simulated nanopore DRS data[6]. Using full-length reads simulated from real Arabidopsis

and human nanopore DRS data, we could identify the intron-chain-level precision and recall of

annotations assembled from reads processed using either one-pass or two-pass alignment. Here,

precision is defined as the percentage of assembled transcripts whose combination of introns match a

transcript in the reference annotation; and recall is defined as the percentage of annotated transcripts

for which at least one read was simulated and whose combination of introns match a transcript

assembled from simulated reads. Reads aligned using guide splice junctions from the reference

annotation were also assessed as a positive control.

For both Arabidopsis and human datasets, two-pass alignment generally produced a clear improvement

in both precision and recall of StringTie2 transcript assembly over first-pass alignment (Fig. 6A). Of the

two decision tree methods produced, decision tree 2 (using junction sequence information) performed

best (median F1 score was 0.699 for the Arabidopsis data and 0.629 for the human data). There was a

particularly large increase in precision for reference annotation-guided alignment of at least 8.7% and

9.6% over one-pass alignment for all Arabidopsis and human samples, respectively (Fig. 6A).

We next considered whether two-pass alignment could improve the genome-guided transcriptome

assembly performance of Stringtie2 on real datasets, using current reference annotations as a ground

truth. However, it is important to note that there may be genuine transcript examples in the datasets

that are not yet included in the reference annotation; if so, this will affect the measurement of

precision. Furthermore, recall against the reference is likely to depend on the sequencing depth of

samples. We therefore report the number of annotated transcripts assembled for each sample, rather

than the recall.

Two-pass alignment improved both the precision and the number of transcripts assembled for

Arabidopsis, human and mouse samples[10,11,32] (Fig. 6B–D). This approach resulted in a median increase in

assembly precision compared with one-pass alignment of 7.1% for Arabidopsis samples, 3.5% for human

samples and 2.2% for mouse samples (median increase in annotated transcripts assembled per sample

of 478.5, 257.5 and 238, respectively). We conclude that for organisms with complex patterns of pre-

mRNA splicing, two-pass alignment can improve both the precision and number of correct (annotated)

transcripts assembled by StringTie2 from real nanopore DRS data.

When we applied the same approach to the yeast *Saccharomyces cerevisiae*, the results were very

different (Fig. 6E). In this species, two-pass alignment resulted in a median increase of only three more

annotated transcripts assembled per sample and an increased number of unannotated transcripts

assembled, resulting in a median decrease of 0.8% in assembly precision. Splicing complexity in

S. cerevisiae is relatively low: there are only 364 annotated introns in the Ensembl R64 annotation, most

genes are intronless, and most introns are constitutive[33]. This led to a high ratio of unannotated splice

junctions in first-pass alignments (the median number of junctions identified was 8,056), suggesting that

the vast majority of junctions in the dataset are spurious. Furthermore, most introns occur close to

mRNA 5' ends, resulting in typically short upstream exons that present challenges to alignment

software. Such a large ratio of spurious to genuine splice junctions is likely to affect the precision of

junction filtering. Notably, even when the reference annotation was used to guide alignment, precision

was only improved by a median of 1.9% (with a median of six more transcripts assembled correctly).

Intron-containing genes are generally more highly expressed (many encode ribosomal proteins) than

intronless genes[34]. This may mean that the coverage of annotated transcripts is already good and, thus,

that the number of true annotated transcripts assembled cannot be much improved. This result

suggests that both reference annotation-guided and two-pass alignment methods have limited use for

genome-guided transcriptome assembly in organisms with low complexity splicing.

Finally, we considered whether filtered two-pass alignment could improve genome-guided annotation of

nanopore DRS reads derived from sequencing cDNA copies and from PacBio IsoSeq data (Fig S6A-D). To

assess this, we used the recommended alignment parameters for minimap2[18] but with the splice

junction filtering parameters as were used for nanopore DRS data. Overall, the precision and recall of

transcripts assembled from both nanopore cDNA and PacBio IsoSeq data for human, mouse and

Arabidopsis samples could be improved using two-pass alignment. For human and mouse nanopore

cDNA samples, two-pass alignment resulted in a median increase of 3.85% and 2.3% in assembly

precision, respectively, compared with one-pass alignment (median increase in annotated transcripts

assembled per sample of 609.5 and 420.0, respectively; Fig. S6A,B). For Arabidopsis and human PacBio

IsoSeq samples, two-pass alignment resulted in a median increase of 8.45% and 1.35% in assembly

precision, respectively, compared with one-pass alignment (median increase in annotated transcripts

assembled per sample of 63 and 242.5, respectively; Fig. S6C,D). We conclude that a two-pass method

can improve genome-guided transcript assembly of the high-error long reads produced using a range of

technologies.

Conclusion

RNA sequencing is a fundamental tool for understanding what genomes really encode. Technological

approaches that directly sequence full-length RNA molecules substantially increase the useful

information that RNA sequencing can provide. The challenges that alternative splicing, in particular,

presents to the interpretation of high-throughput RNA sequencing data means that software

development needs to accompany progress in sequencing technology. In this way, knowledge gained

from ambitious genome sequencing programmes such as the Earth BioGenome Project, which aims to

characterise all eukaryotic life on Earth[35], can be maximised. In addition, we can deepen our

understanding of how gene expression changes in disease states, for example, in humans and other

well-characterised species. We have shown that a two-pass alignment approach, informed by splice

junction alignment metrics and machine learning of sequence features associated with splicing, can

improve the accuracy of intron detection in long-read data. Consequently, this approach can enhance

the utility and realise the potential of long-read RNA sequencing.

Acknowledgments

We thank Kasia Knop for comments on the manuscript, and James Abbott for testing the pipeline. This work was funded by the University of Dundee Global Challenges Research Fund.

Methods

Nanopore and PacBio data

Four replicates of nanopore DRS reads derived from Arabidopsis Col-0 RNA were used [11]. These datasets are available in FAST5 format from the European Nucleotide Archive under accession no. PRJEB32782. The first four listed replicates of DRS and cDNA sequencing reads derived from human cell line GM12878 were used: Birmingham DRS samples 1, 2, 3 and 5; Birmingham cDNA samples 1 and 2; Hopkins cDNA samples 1 and 2)[10]. DRS datasets were downloaded in FAST5 format and cDNA datasets in FASTQ format using the links provided on GitHub (http://s3.amazonaws.com/nanopore-human-wgs/rna/links/NA12878-DirectRNA_All.files.txt). Mouse DRS and cDNA datasets in FASTQ format [32] were downloaded from the European Nucleotide Archive (accession no. PRJEB27590). Yeast DRS datasets in FASTQ format [9] were downloaded from the European Nucleotide Archive (accession no. PRJNA408327). Human IsoSeq datasets in FASTQ format were downloaded from the PacBio AWS webserver (http://datasets.pacb.com.s3.amazonaws.com/2014/Iso-seq_Human_Tissues/list.html). Arabidopsis IsoSeq data in FASTQ format was downloaded from the European Nucleotide Archive (accession no. PRJNA371677).

Preliminary data processing

Pipelines for processing of data were written using snakemake version 5.10.0[36]. FAST5 data was re-basecalled locally using guppy version 2.3.1 (ONT). All alignments were performed using minimap2 version 2.17-r963[18]. Arabidopsis reads were aligned to the TAIR10 reference genome[37] and AtRTD2 reference transcriptome[23]. Human, mouse and yeast reads were aligned to the GRCh38, GRCm38 and R64–1-1 primary assemblies and to cDNA transcriptomes from Ensembl, respectively[24]. Alignments to reference genomes were performed using spliced parameters. For DRS datasets, these were: -k14 -w5 --splice -g2000 -A1 -B2 -O2,32 -E1,0 -C9 --splice-flank=yes -uf -z200 -L --cs=long. For nanopore cDNA and PacBio datasets the parameters used were -x splice -g2000 -L --cs=long. The maximum intron size (-G) was set at 10,000 nt for Arabidopsis samples, at 200,000 nt for human and mouse datasets and at

5,000 nt for yeast. For two-pass alignments using a guide splice junction set, a junction bonus of 12 was

also used. Alignments of DRS reads to the reference transcriptome were performed using splicing-free

parameters, namely: -k14 --for-only -L --cs=long.

Simulation of DRS reads

To provide a ground truth with a complete set of known splice sites, sequences were simulated from the

reference transcriptomes, with length and error profiles matching those of real DRS reads. This was

done by modelling the length, homopolymer error and other error profiles of real reads. Only primary

alignments were considered. The cs tags of reads aligned to the reference transcriptome were used to

recreate pairwise alignments between each read and the reference, ignoring refskips. Alignments were

inverted to match the $3' \to 5'$ sequencing direction of nanopore DRS. Aligned basecalls at reference

homopolymers of ≥5 nt in length were used to build a probability model of homopolymer calls given the

reference homopolymer. To prevent these error profiles being modelled multiple times, the reference

homopolymer was then replaced with the aligned basecall in the pairwise alignment. Next, the altered

alignment was used to create a Markov chain model of basecalled sequence given the reference

sequence. For each base in the reference sequence in the alignment, the aligned portion of the query

sequence was identified. The "state" of the alignment (i.e. match, mismatch, insertion or deletion) was

also identified. The probability of seeing a query sequence was calculated, given the current and

previous four bases of the reference and the previous four states of the alignment.

The reference transcriptome was also used to simulate data using these models. The number of primary

alignments in the real data for each reference transcript was used as the number of simulated reads per

transcript. To simulate basecall errors, sequences were inverted to the $3' \to 5'$ direction and reads were

generated using Markov chain Monte Carlo simulations with the basecall model. The reference

sequences were prepended with a 10 nt oligo(A) sequence to mimic a short poly(A) tail so that the initial

state of the Markov chain was always "AAAAA" and "====" (i.e. four matches). Homopolymers in the

simulated read were identified and replaced with randomly selected sequences from the homopolymer

model. The read was then reverted to the $5' \to 3'$ direction for mapping. Because we wanted to assess

the alignment of full-length reads, we did not model or simulate the 3' bias, which is inherent to

nanopore DRS data. However, 10 nt of simulated read were subtracted from the 5' end of reads to

simulate loss of signal at the end of sequencing.

Post-alignment splice junction correction with FLAIR

BAM files were converted to the BED12 format using bedtools[38]. BED12 files were then corrected using

the reference GTF annotation with FLAIR correct version 1.4 and default settings[10].

Junction metric calculations

Splice junctions and junction metrics were extracted from aligned reads using the long form cs tag

produced by minimap2 version 2.17[18] using pysam version 0.15.4. The per-read JAD was calculated as

the length of the shorter of the two match operations immediately flanking refskip (splicing) operations.

Where there were mismatches or indels immediately adjacent to refskips, a JAD of zero was assigned.

The per-splice junction JAD was calculated as the maximum of the per-read JADs. Intron motifs were

extracted from cs tags. For Arabidopsis, human and mouse samples, GU/AG, GC/AG and AU/AG splice

junctions were all considered canonical. For yeast samples, only GU/AG splice junctions were considered

canonical. To calculate the primary donor/acceptor metrics, interval trees of donor and acceptor sites

were constructed using NCLS[39]. Donors were assigned as primary donors if there were no alternative

donor sites within 20 nt with higher read counts. Likewise, acceptors were considered primary if there

were no alternative acceptors within 20 nt with higher read counts. Ties were broken using the JAD

metric, i.e. the splice junctions with higher JADs were assigned primary status. Where there were still

ties after read count and JAD comparisons, no splice junctions were assigned primary status. Splice

junctions extracted from four replicates of Arabidopsis or human DRS reads were used to build decision

tree models with scikit-learn version 0.22.1[40]. A minimum depth of 4, minimum number of samples

required to split a node of 1000, and minimum Gini impurity decrease required to split a node of 0.005

were used. The decision tree generated from Arabidopsis reads was a subtree of the human tree (i.e. it

could be created by pruning the human tree), indicating that the decision function can generalise across

samples.

Reference sequence filtering using LR models

Splice junctions obtained from a first-pass alignment were separated into lists of unique donor sites and

unique acceptor sites. These were labelled as positive training examples if they participated in at least

one donor/acceptor pair which passed the first decision tree function. Sequences of 128 nt for each

splice junction (centred on the donor or acceptor site) were extracted from the reference genome using

pysam version 0.15.4 and one hot encoded into four binary variables to create a 512-feature training

dataset. LR models were trained using 6-fold cross-validation with scikit-learn version 0.22.1[40]. For each

fold, the model was used to generate out-of-bag predictions on the held-out data. The probabilities

produced were then used in place of the canonical intron motif to produce the second decision tree,

using a maximum depth of 6, a minimum number of samples of 1,000 and a minimum Gini impurity

decrease of 0.003. Thresholds for splice scores in the tree were simplified to comprise only a high

confidence threshold of 0.6 (for rescuing splice junctions failing the JAD metric threshold) and a low

confidence threshold of 0.1 (for removing false positives from junctions passing the JAD metric

threshold).

Evaluation of splice junction models

Performance of the metrics and models was evaluated at splice junction level using the reference

annotation as a ground truth. For simulated datasets, annotation is the absolute ground truth because

all reads are simulated using only splice junctions in the annotation. For real datasets, some "false

positives" are likely to be genuine splice junctions and some junctions in the reference, which appear as

false negatives, are actually incorrectly annotated or not expressed. Precision is defined as the number

of true positives divided by the total number of positive predictions by the model, i.e. true positives ÷

(true positives + false positives). Recall is defined as the number of true positives divided by the total

number of real positive examples in the dataset, i.e. true positives ÷ (true positives + false negatives).

The F1 score is the harmonic mean of the precision and recall.

Evaluation of alignments

To evaluate alignments, we used the intron chain of reference transcripts as a ground truth. The intron

chain is the pattern of linked splicing in a transcript, disregarding the transcription start and termination

sites. Alignments of simulated reads were considered correct if they mapped correctly to the intron

chain of the reference transcript they were simulated from, with no mistakes. Simulated reads that were

mapped using intron chains not included in the reference or as being intron-less when they should have

splicing were considered novel spurious alignments. Simulated reads that were mapped using the intron

chain of a reference transcript other than the transcript they were simulated from were considered to

be misassigned. For measures of quantification accuracy, alignment counts for transcripts were

generated using the number of simulated reads that aligned with the same splice junctions as the

reference transcript. Spearman's correlation coefficients were then calculated against the known input

transcript counts for simulation.

Reference-guided assembly

Reference-guided transcriptome assemblies were produced using StringTie2[6] version 2.1.1 in long-read

mode, with otherwise default parameters.

Evaluation of assemblies

Reference-guided transcriptome assemblies were evaluated using the precision and recall of intron

chains calculated using gffcompare with default settings[41]. The input reference GTF files were filtered to

include only transcript models for which at least one read had been simulated.

Code availability

The methods used to filter splice junctions have been implemented in the "2passtools" python package,

which is available on GitHub in repository https://github.com/bartongroup/2passtools. The software

used to simulate reads is available on GitHub in repository https://github.com/bartongroup/yanosim.

The scripts, pipelines and notebooks used to perform benchmarking and generate figures are available

on GitHub in repository https://github.com/bartongroup/two_pass_alignment_pipeline. Basecalled and

simulated nanopore DRS datasets are available from Zenodo at https://zenodo.org/record/3773729.

References

1   Wang, E. T. *et al.* Alternative isoform regulation in human tissue transcriptomes. *Nature* **456**,
470-476, doi:10.1038/nature07509 (2008).
2   Stark, R., Grzelak, M. & Hadfield, J. RNA sequencing: the teenage years. *Nature Reviews Genetics*
20, 631-656, doi:10.1038/s41576-019-0150-2 (2019).
3   Mourão, K. *et al.* Detection and mitigation of spurious antisense expression with RoSA.
F1000Research **8**, doi:10.12688/f1000research.18952.1 (2019).
4   Houseley, J. & Tollervey, D. Apparent Non-Canonical Trans-Splicing Is Generated by Reverse
Transcriptase In Vitro. *PLoS ONE* **5**, doi:10.1371/journal.pone.0012271 (2010).
5   Zhang, C., Zhang, B., Lin, L.-L. & Zhao, S. Evaluation and comparison of computational tools for
RNA-seq isoform quantification. *BMC Genomics* **18**, doi:10.1186/s12864-017-4002-1 (2017).
6   Kovaka, S. *et al.* Transcriptome assembly from long-read RNA-seq alignments with StringTie2.
Genome Biology **20**, doi:10.1186/s13059-019-1910-1 (2019).
7   Pertea, M. *et al.* StringTie enables improved reconstruction of a transcriptome from RNA-seq
reads. *Nature Biotechnology* **33**, 290-295, doi:10.1038/nbt.3122 (2015).
8   Trapnell, C. *et al.* Transcript assembly and quantification by RNA-Seq reveals unannotated
transcripts and isoform switching during cell differentiation. *Nature Biotechnology* **28**, 511-515,
doi:10.1038/nbt.1621 (2010).
9   Garalde, D. R. *et al.* Highly parallel direct RNA sequencing on an array of nanopores. *Nature*
Methods **15**, 201-206, doi:10.1038/nmeth.4577 (2018).
10 Workman, R. E. *et al.* Nanopore native RNA sequencing of a human poly(A) transcriptome.
Nature Methods **16**, 1297-1305, doi:10.1038/s41592-019-0617-2 (2019).
11 Parker, M. T. *et al.* Nanopore direct RNA sequencing maps the complexity of Arabidopsis mRNA
processing and m6A modification. *eLife* **9**, doi:10.7554/eLife.49658 (2020).
12 Ardui, S., Ameur, A., Vermeesch, J. R. & Hestand, M. S. Single molecule real-time (SMRT)
sequencing comes of age: applications and utilities for medical diagnostics. *Nucleic Acids*
Research **46**, 2159-2168, doi:10.1093/nar/gky066 (2018).
13 Wick, R. R., Judd, L. M. & Holt, K. E. Performance of neural network basecalling tools for Oxford
Nanopore sequencing. *Genome Biology* **20**, doi:10.1186/s13059-019-1727-y (2019).
14 Wick, R. R., Judd, L. M. & Holt, K. E. Deepbinner: Demultiplexing barcoded Oxford Nanopore
reads with deep convolutional neural networks. *PLOS Computational Biology* **14**,
doi:10.1371/journal.pcbi.1006583 (2018).
15 Dehghannasiri, R., Szabo, L., Salzman, J. & Birol, I. Ambiguous splice sites distinguish circRNA and
linear splicing in the human genome. *Bioinformatics* **35**, 1263-1268,
doi:10.1093/bioinformatics/bty785 (2019).
16 Dobin, A. *et al.* STAR: ultrafast universal RNA-seq aligner. *Bioinformatics* **29**, 15-21,
doi:10.1093/bioinformatics/bts635 (2013).
17 Kim, D., Paggi, J. M., Park, C., Bennett, C. & Salzberg, S. L. Graph-based genome alignment and
genotyping with HISAT2 and HISAT-genotype. *Nature Biotechnology* **37**, 907-915,
doi:10.1038/s41587-019-0201-4 (2019).
18 Li, H. & Birol, I. Minimap2: pairwise alignment for nucleotide sequences. *Bioinformatics* **34**,
3094-3100, doi:10.1093/bioinformatics/bty191 (2018).
19 Liu, B. *et al.* deSALT: fast and accurate long transcriptomic read alignment with de Bruijn graph-
based index. *Genome Biology* **20**, doi:10.1186/s13059-019-1895-9 (2019).

20 Veeneman, B. A., Shukla, S., Dhanasekaran, S. M., Chinnaiyan, A. M. & Nesvizhskii, A. I. Two-pass
alignment improves novel splice junction quantification. *Bioinformatics* **32**, 43-49,
doi:10.1093/bioinformatics/btv642 (2016).
21 Gatto, A. *et al.* FineSplice, enhanced splice junction detection and quantification: a novel
pipeline based on the assessment of diverse RNA-Seq alignment solutions. *Nucleic Acids*
Research **42**, e71-e71, doi:10.1093/nar/gku166 (2014).
22 Mapleson, D., Venturini, L., Kaithakottil, G. & Swarbreck, D. Efficient and accurate detection of
splice junctions from RNA-seq with Portcullis. *GigaScience* **7**, doi:10.1093/gigascience/giy131
(2018).
23 Zhang, R. *et al.* A high quality Arabidopsis transcriptome for accurate transcript-level analysis of
alternative splicing. *Nucleic Acids Research* **45**, 5061-5073, doi:10.1093/nar/gkx267 (2017).
24 Schneider, V. A. *et al.* Evaluation of GRCh38 and de novo haploid genome assemblies
demonstrates the enduring quality of the reference assembly. *Genome Research* **27**, 849-864,
doi:10.1101/gr.213611.116 (2017).
25 Rang, F. J., Kloosterman, W. P. & de Ridder, J. From squiggle to basepair: computational
approaches for improving nanopore sequencing read accuracy. *Genome Biology* **19**,
doi:10.1186/s13059-018-1462-9 (2018).
26 Smith, T. F. & Waterman, M. S. Identification of common molecular subsequences. *Journal of*
Molecular Biology **147**, 195-197, doi:10.1016/0022-2836(81)90087-5 (1981).
27 Sheth, N. *et al.* Comprehensive splice-site analysis using comparative genomics. *Nucleic Acids*
Research **34**, 3955-3967, doi:10.1093/nar/gkl556 (2006).
28 Carrillo Oesterreich, F. *et al.* Splicing of Nascent RNA Coincides with Intron Exit from RNA
Polymerase II. *Cell* **165**, 372-381, doi:10.1016/j.cell.2016.02.045 (2016).
29 Reimer, K. A., Mimoso, C., Adelman, K. & Neugebauer, K. M. Rapid and Efficient Co-
Transcriptional Splicing Enhances Mammalian Gene Expression. *bioRxiv*,
doi:10.1101/2020.02.11.944595 (2020).
30 Mercer, T. R. *et al.* Genome-wide discovery of human splicing branchpoints. *Genome Research*
25, 290-303, doi:10.1101/gr.182899.114 (2015).
31 Kuo, R. I., Cheng, Y., Smith, J., Archibald, A. L. & Burt, D. W. Illuminating the dark side of the
human transcriptome with TAMA Iso-Seq analysis. *bioRxiv*, doi:10.1101/780015 (2019).
32 Sessegolo, C. *et al.* Transcriptome profiling of mouse samples using nanopore sequencing of
cDNA and RNA molecules. *Scientific Reports* **9**, doi:10.1038/s41598-019-51470-9 (2019).
33 Spingola, M., Grate, L., Haussler, D. & Ares, M. Genome-wide bioinformatic and molecular
analysis of introns in Saccharomyces cerevisiae. *Rna* **5**, 221-234,
doi:10.1017/s1355838299981682 (1999).
34 Ares, M., Grate, L. & Pauling, M. H. A handful of intron-containing genes produces the lion's
share of yeast mRNA. *Rna* **5**, 1138-1139, doi:10.1017/s1355838299991379 (1999).
35 Lewin, H. A. *et al.* Earth BioGenome Project: Sequencing life for the future of life. *Proceedings of*
the National Academy of Sciences **115**, 4325-4333, doi:10.1073/pnas.1720115115 (2018).
36 Koster, J. & Rahmann, S. Snakemake--a scalable bioinformatics workflow engine. *Bioinformatics*
28, 2520-2522, doi:10.1093/bioinformatics/bts480 (2012).
37 Initiative, T. A. G. Analysis of the genome sequence of the flowering plant Arabidopsis thaliana.
Nature **408**, 796-815, doi:10.1038/35048692 (2000).
38 Quinlan, A. R. & Hall, I. M. BEDTools: a flexible suite of utilities for comparing genomic features.
Bioinformatics **26**, 841-842, doi:10.1093/bioinformatics/btq033 (2010).
39 Stovner, E. B., Sætrom, P. & Hancock, J. PyRanges: efficient comparison of genomic intervals in
Python. *Bioinformatics*, doi:10.1093/bioinformatics/btz615 (2019).

40   Pedregosa, F. *et al.* Scikit-learn: Machine Learning in Python. *J Mach Learn Res* **12**, 2825-2830
(2011).
41   Pertea, M., Kim, D., Pertea, G. M., Leek, J. T. & Salzberg, S. L. Transcript-level expression analysis
of RNA-seq experiments with HISAT, StringTie and Ballgown. *Nature Protocols* **11**, 1650-1667,
doi:10.1038/nprot.2016.095 (2016).

Fig. 1. Assessment of alignment errors in nanopore DRS datasets. Nanopore DRS read alignments at Arabidopsis *AT5G05010* locus with different types of alignment error presented. Read alignments are shown in dark blue, with soft-clipped (unaligned) ends shown in light blue. Mismatches and indels of <30 nt are not shown. Insertions to the reference of > 30 nt are shown as orange carets.

Fig. 2. Improved spliced alignment of simulated reads using annotation-guided alignment. A
Reference-guided alignment improves the identification of small exons in nanopore DRS reads. Gene
track showing the alignment of a sample of simulated nanopore DRS reads at the Arabidopsis *FLM* gene.
AtRTD2 reference annotation, from which reads were simulated, is shown on top, with unguided
minimap2 alignments, FLAIR correction of unguided minimap2 alignments and reference-guided
minimap2 alignments shown below. Only reads where exon 6 failed to align in the initial unguided
alignment are shown. Each read alignment is coloured based on the reference transcript it was
simulated from, and reads are shown in the same order within each alignment method group.
Mismatches and indels are not shown. **B** Reference-guided alignment improves the identification of
correct transcripts globally. Boxplots with overlaid strip-plots showing the percentage of alignments

which map exactly to the splice junctions of the transcript from which they were simulated, for

unguided minimap2 alignments, FLAIR correction of unguided minimap2 alignments using reference

annotation, and reference annotation-guided minimap2 alignments. Reads simulated from intronless

transcripts which map correctly without splicing were not included in percentage calculations. Reads

were simulated from Arabidopsis (left) and human (right) nanopore DRS data aligned to the AtRTD2 and

GRCh38 reference transcriptomes, respectively.

Fig. 3 Junction metrics can identify genuine splice junctions. A Outline of the two-pass method. **B** The
JAD metric can discriminate between annotated and unannotated splice junctions in simulated
nanopore DRS reads. Inverse cumulative density plot showing the distribution of per-splice junction
maximum JAD values for annotated (blue) and unannotated (orange) splice junctions. **C** Flowchart
visualisation of the first decision tree model. Nodes (decisions) and leaves (outcomes) are coloured
based on the relative ratio of real and spurious splice junctions. **D** Confusion matrix showing the ratios of
correct and incorrect predictions of the first decision tree model on splice junctions extracted from
simulated Arabidopsis read alignments.

Fig. 4. Machine learned sequence information improves identification of genuine splice junctions. A
Outline of the LR model training process. Sequences from splice junctions were extracted from the
reference genome and used as training data (i.e. explanatory variables). Training labels (i.e. the response
variable) were generated by the first decision tree model. Independent models were trained for 5' donor
and 3' acceptor sites and cross-validation used to generate out-of-bag predictions for all sites. **B**
Flowchart visualisation of the second decision tree model. Nodes (decisions) and leaves (outcomes) are
coloured based on the relative ratio of real and spurious splice junctions. **C** Confusion matrix showing
the ratios of correct and incorrect predictions of the second decision tree model on splice junctions
extracted from simulated Arabidopsis read alignments.

Fig. 5. Filtered two-pass alignment improves the identification and quantification of correct transcripts without a reference annotation. A Boxplots with overlaid strip-plots showing the percentage of alignments which map exactly to the splice junctions of the transcript from which they were simulated, for one-pass unguided minimap2 alignments, two-pass alignments using splice junctions filtered by decision trees one and two, and reference-annotation-guided minimap2 alignments. Reads were simulated from Arabidopsis TAIR10 + AtRTD2 (left) and human GRCh28 (right) nanopore DRS data. **B** Boxplots with overlaid strip-plots showing the Spearman's correlation coefficient for actual transcript level counts from simulated data against counts produced by the alignment methods described in A. Reads were simulated from Arabidopsis (left) and human (right) nanopore DRS data aligned to the AtRTD2 and GRCh38 reference transcriptomes, respectively.

Fig. 6. Filtered two-pass alignment improves genome-guided annotation. A Scatterplot showing

precision against recall for intron chains in genome-guided transcriptome annotations generated from

alignments using StringTie2. Precision and recall scores were calculated against reference annotations

filtered to include only transcripts for which at least one read was simulated. Reads were simulated

from Arabidopsis (left) and human (right) nanopore DRS data aligned to the AtRTD2 and GRCh38

reference transcriptomes, respectively. **B–E** Boxplots showing the number of correct transcripts

assembled (left panels) and precision of transcripts assembled (right panels) for genome-guided

transcriptome assembly using StringTie2. Two-pass alignment improved the precision and number of

transcripts assembled for real nanopore DRS data for **B** Arabidopsis, **C** human, **D** mouse and **E** yeast. For

all boxplots, overlaid strip-plots are shown for individual samples. Each sample was assigned a unique

marker so that the changes in each sample could be tracked between the one-pass, two-pass and

reference-guided alignments.

Fig. S1. Simulation of nanopore DRS read alignments. A Violin plot showing the distribution of
sequence identity scores for real and simulated Arabidopsis nanopore DRS reads. Simulated reads match
the median sequence identity of real reads, although they do not capture the tails of high- and low-
quality reads. **B** Insertion and deletion length distributions for real and simulated nanopore DRS reads.
C Mismatch profiles for real and simulated nanopore DRS reads.

Fig. S2. Annotation-guided alignment improves spliced alignment of simulated reads. A Boxplots with
overlaid strip-plot showing the percentage of alignments which do not map correctly to the splice
junctions of the transcript from which they were simulated, for one-pass unguided minimap2
alignments, FLAIR-corrected alignments and reference annotation-guided minimap2 alignments. Reads
that align to unannotated splice junctions or combinations of junctions are shown in orange. Reads
which align to the incorrect annotated combination of splice junctions are shown in green. Reads were
simulated from Arabidopsis (left) and human (right) nanopore DRS data aligned to the AtRTD2 and
GRCh38 reference transcriptomes, respectively. **B** Boxplots with overlaid strip-plot showing the
percentage of alignments which map correctly to the splice junctions of the transcript from which they
were simulated, for one-pass unguided minimap2 alignments, two-pass minimap2 alignment and
reference annotation-guided minimap2 alignments. Reads were simulated from Arabidopsis (left) and
human (right) nanopore DRS data aligned to the AtRTD2 and GRCh38 reference transcriptomes,
respectively.

Fig. S3. Junction metrics can identify genuine splice junctions. A-D Confusion matrices showing the

ratios of correct and incorrect predictions using: **A** a JAD threshold of 4 nt; **B** a count threshold of 1 nt; **C**

the presence of a canonical U2 GU/AG, U12 GC/AG or U12 AU/AG intron motif; and **D** the primary

donor/acceptor metric, defined as whether there are no alternate donor or acceptor sites with greater

support (i.e. higher count or JAD) within 20 nt.

Fig. S4. Machine-learned sequence information can identify genuine splice junctions. A-C Confusion

matrices showing the ratios of correct and incorrect predictions using: **A** an LR prediction threshold of

0.5 for splice site strength predictions made on donor site sequences; **B** an LR prediction threshold of 0.5

for splice site strength predictions made on acceptor site sequences; **C** a minimum prediction threshold

of 0.5 for both splice donor and acceptor site sequences.

Fig. S5. Filtered two-pass alignment improves the identification and quantification of correct transcripts without a reference annotation. A Gene track showing alignment of a sample of simulated nanopore DRS reads at the Arabidopsis *FLM* gene. The AtRTD2 reference annotation, from which reads were simulated, is shown on top, with unguided minimap2 alignments, two-pass minimap2 alignments using the second decision tree classification, and reference-annotation-guided alignments shown below. Only reads where exon 6 failed to align in the initial unguided alignment are shown. Each read alignment is coloured based on the reference transcript it was simulated from, and reads are in the same order

within each alignment method group. Mismatches and indels are not shown. **B** Boxplots with overlaid

strip-plots showing the percentage of alignments which do not map correctly to the splice junctions of

the transcript from which they were simulated, for one-pass unguided minimap2 alignments, two-pass

alignment with decision trees one and two, and reference annotation-guided minimap2 alignments.

Reads that align to unannotated splice junctions or combinations of junctions are shown in orange.

Reads which align to annotated combinations of splice junctions which they were not simulated from

are shown in green. Reads were simulated from Arabidopsis (left) and human (right) nanopore DRS data

aligned to the AtRTD2 and GRCh38 reference transcriptomes, respectively.

Fig. S6. Filtered two-pass alignment improves genome-guided annotation. A–D Boxplots showing the number of correct transcripts assembled (left panels) and precision of transcripts assembled (right panels) for genome-guided transcriptome assembly using StringTie2. Two-pass alignment improved the precision and number of transcripts assembled for real: **A** human nanopore cDNA; **B** mouse nanopore cDNA; **C** Arabidopsis PacBio IsoSeq; and **D** human PacBio IsoSeq data. For all boxplots, overlaid strip-plots are shown for individual samples. Each sample was assigned a unique marker so that changes in the metrics could be tracked between the one-pass, two-pass and reference-guided alignments.