# Clarifying the role of high-level cortices in resolving perceptual ambiguity using Ultra High Field fMRI

Logan Dowdle[1*], Geoffrey Ghose[1], Kamil Ugurbil[1], Essa Yacoub[1], Luca Vizioli[1*]

1. Center for Magnetic Resonance Research, University of Minnesota 2021 6th St SE, Minneapolis, MN 55455

* Luca Vizioli and Logan Dowdle

**Email:** luca.vizioli1@gmail.com; logan.dowdle@gmail.com

Subject Area

Neuroscience

Keywords

Top-down; fMRI; Ultra High Field; Cognitive Neuroscience; Vision; Perception; Cortical Network; Task modulations;

Author Contributions

L.V. designed and conducted the experiment; L.V. and L.D. performed the analyses, wrote the manuscript and generated the figures. E.Y. and K.U. provided guidance on choice and optimization of MR acquisition sequences; G.G. provided guidance on conceptual framework; E.Y., K.U. and G.G. contributed to manuscript formulation and writing.

## Abstract

The brain is organized into distinct, flexible networks. Within these networks, cognitive variables such as attention can modulate sensory representations in accordance with moment-to-moment behavioral requirements. These modulations can be studied by varying task demands; however, the tasks employed are often incongruent with the postulated functions of a sensory system, limiting the characterization of the system in relation to natural behaviors. Here we combine domain-specific task manipulations and ultra-high field fMRI to study the nature of top-down modulations. We exploited faces, a visual category underpinned by a complex cortical network, and instructed participants to perform either a stimulus-relevant/domain-specific or a stimulus-irrelevant task in the scanner. We found that 1. top-down modulations in higher-level cortices can be explained in terms of perceptual ambiguity (i.e. difficulty of achieving a stable percept); 2. the right inferior-temporal lobe is active under challenging conditions and uniquely encodes trial-by-trial variability in perception.

## Introduction

Decades of human and animal research has demonstrated that cortical areas are functionally and anatomically linked to form distinct brain networks. Understanding the distinct contributions of individual areas within these networks has been challenging in part because of the rich and reciprocal pattern of connections between brain areas (Alexander et al., 1986; Felleman and Van Essen, 1991; Moeller et al., 2008). Discrimination is further confounded by the low latencies with which signals travel between areas (Laughlin and Sejnowski, 2003; Wang et al., 2008), substantial overlaps in the functional sensitivities of neurons of different areas (Arcaro and Livingstone, 2017; Haxby et al., 2001; Vogels and Orban, 1994), and the flexibility of connections necessary to maintain function across a range of tasks and environments (Bassett et al., 2011; Gonzalez-Castillo and Bandettini, 2018; Kabbara et al., 2017). A critical component of this flexibility in sensory systems is top-down control, in which cognitive variables such as attention, value, and memory can alter sensory representations in accordance with behavioral demands. Yet this flexibility also is a major challenge to experimental studies, because it implies that the nature of signal processing both within and between brain areas of a network is not fixed and very much depends on the behavioral context and goals of the subject.

While many humans and animal studies have demonstrated the ability of task manipulations to modulate sensory evoked responses, in most cases these studies have employed tasks that are not specific to the domain of the stimulus that was presented. For example, numerous electrophysiological and imaging studies suggest that attending to a particular location in visual space increases the responses of neurons whose receptive fields lie within the attended location irrespective of the selectivities of those receptive fields (Cohen and Maunsell, 2011; Liu et al., 2015; Martinez-Trujillo and Treue, 2004). Similarly, perceptual tasks involving working memory often result in a broad distribution of enhanced signals in sensory areas (Druzgal and D'Esposito, 2003, 2001; Kay and Yeatman, 2017; Leung

and Alain, 2011; Pessoa et al., 2002). By contrast, top-down modulation from domain-specific tasks can

be far more targeted, selectively enhancing only those neurons whose receptive field responses are

consistent with behavioral demands (De Martino et al., 2015; Zhang and Kay, 2020). Accordingly, the use

of appropriate domain specific tasks is likely to highlight those neurons with relevant selectivities and

reveal how they contribute to perception. For example, contrasting the activity elicited by identical face

stimuli in an N-back and a fixation task may reveal working memory related modulations that are

unspecific to face processing and therefore fail to elucidate the changes related to the specialized

processing of faces.

Establishing how different areas within a network contribute to perception requires sampling the

entire network and then identifying the particular areas that can best explain task performance.

However, technical limitations have precluded this approach. Invasive electrophysiological studies are

necessarily highly targeted and unable to sample across an entire brain network. In addition, these

techniques are frequently performed in non-human primates, with tasks that fail to capture the cognitive

sophistication available to humans. Moreover, even whole brain studies, such as those relying upon

functional magnetic resonance imaging, are often highly biased in their sampling because of the difficulty

of imaging particular areas. For example, a number of high-level areas – crucial for human cognition –

are located in cortical loci that are traditionally difficult to image (e.g. due to low SNR and their proximity

to air cavities (Chen et al., 2003; Devlin et al., 2000)). These limitations also constrain our ability to

establish appropriate animal models for invasive measurements and manipulations because of the

possibility that human areas homologous to those in animals studies cannot be sampled by fMRI

(Rajimehr et al., 2009). Signal to noise issues have also limited the ability of fMRI to establish trial-to-trial

behavioral covariance, which is a critical requirement for understanding the neural basis of perception

(Parker and Newsome, 1998) and has been extensively employed by electrophysiology studies

(Desimone et al., 1984; Hubel and Wiesel, 1959; Martinez-Trujillo and Treue, 2004; Perrett et al., 1982).

This is a particularly important consideration because, by definition, all areas within a network are co-

activated, but, given the richness of connectivity within the network, that co-activation does not

necessarily imply perceptual relevance.

These concerns can be mitigated with ultra-high field magnets (UHF i.e. 7T and above), which

yield significantly higher SNR characteristics, however researchers generally trade these SNR gains for

higher resolutions (e.g. submillimeter). In this paper we instead select a lower resolution (i.e. 1.6 mm$^3$)

and leverage the improved SNR available in UHF fMRI to study the entire ensemble of brain areas

associated with a behaviorally important high-level perceptual task, namely the detection of faces in

poor visibility. We choose faces as these are a well-studied, cross species visual category that is highly

meaningful and therefore ideal for investigating high-level, top-down neural modulations. The human

face processing network has however proved challenging to study (Kanwisher et al., 1997; Kanwisher

and Yovel, 2006; McCarthy et al., 1997) (see Grill-Spector & Weiner (Grill-Spector and Weiner, 2014) for

review), because many of its areas, due to their proximity to air cavities, are heavily affected by the

aforementioned fMRI signal difficulties. Moreover, domain-specific attentional tasks, such as those

focused on high-level face analysis, which are most likely to highlight the distinctive role of particular

neuronal populations have seldom been employed. Specifically, we varied the visibility of face stimuli by

modulating their phase coherence (Figure 1) and instructed the subjects to perform 2 tasks in the

scanner: a *domain-specific, stimulus relevant* task Involving perceptual judgment of the visual stimuli (i.e.

face detection); *and, stimulus irrelevant* fixation task.

## Results

Through this work, the prefixes "l" and "r" preceding the name of a ROI will refer to its

hemispheric lateralization.

*Localizer Task.*

Using the separate face-localizer task, we identified a total of twelve ROIs. This included typical

regions, such as the fusiform face area (FFA, MNI Centers of Mass [L: -41 -52 -19, R: 40 -54 -17]), occipital

face area (OFA [L: -44 -83 -13, R:43 -76 -11]), posterior superior temporal sulcus (STS [L: -48 -68 10, R: 50

-57 18]) as well as the amygdalae [L: -21 -7 -15, R: 20 -6 -15]. In addition, we identified ROIs for more

difficult regions, including an ROI proximal to the perirhinal cortex, which we are referring to more

generally as the anterior inferior temporal (AIT [L: -34 -9 -34, R:32 -6 -39]) cortex as well as an ROI in H-

shaped sulcus, which we refer to as the HFA (H-shaped sulcus Face Area, [L: -32 33 -15, R: 30 33 -14]).

ROIs identification and all subsequent analyses were carried out in native subject space, but to compare

their locations across participants and to relate these locations to previous studies, we converted and

report their coordinates in MNI space. All cortical regions and their overlap across participants are shown

in Figure 2A.

**Figure 1**. Event Related Stimuli and Tasks. **A)** Example stimuli associated with the 5 phase coherence levels used. **B)** The Stimulus Relevant Face detection task. Stimuli appeared for 2 seconds, with an inter-trial interval of 2 seconds. The fixation cross changed color with a frequency of 2Hz and was visible throughout all experimental procedures. Participants indicated "face" or "no face" using an MRI response hand pad. Blank trials were randomly inserted during each fMRI run. **C)** The Stimulus Irrelevant Fixation task. Timing is identical to B. Participants indicated when the fixation cross changed to the color red.

**Figure 2**. Results from the face preferential localizer. **A)** All subject's ROIs combined in MNI template space, highlighting the consistent overlap between subjects and between hemispheres. **B)** Average BOLD responses across all subjects, in units of percent signal change, for each ROI in response to faces, objects and scrambled images. Standard Error of the Mean shown with shading. **C)** Example results from two single subjects showcasing reliability even within a single subject's ROIs.

Figure 2B shows ROIs average BOLD time courses, constructed from FIR models. All regions,

including areas associated with low SNR (AIT, HFA), yield plausible hemodynamic responses.

Furthermore, these responses remain HRF-like even at the single subject level (Figure 2C), indicating high

data quality.

*Behavioral Responses and Ambiguity Scores*

The right panel in Figure 3A portrays the face detection group average reaction times. Subjects

responded with an average RT of 760 +/- 120 ms. Reaction times indicate that, in reporting their

percepts, participants were slowest at the lower end of the phase coherence spectrum (i.e. 0% and 10%),

becoming increasingly faster as a function of phase coherence.

Figure 3A, left panel, shows the average perceived "faceness", that is the proportion of the time

that participants reported seeing a face. By calculating the inverse of the absolute distance from the

inflection point (see section 4.4.4.) of the faceness sigmoid, we derive the ambiguity scores (Figure 3A,

middle panel), which peaked at 20% phase coherence. Reaction times were shortest for the highest

phase coherence (Figure 3A, right panel).

Figure 3. **A)** Behavioral Responses to Stimulus Relevant Task. **Left panel:** The group average of perceived "faceness", where 0 represents consistently reporting no face, and 1 represents consistently reporting the presence of a face. **Central Panel:** The group averaged ambiguity curve, showing that stimuli at 20% were most ambiguous, i.e., were most inconsistently categorized. Ambiguity was computed according to the equation shown in the middle panel, where $S_i$ is the $i$th point of the faceness sigmoid, $S_k$ is the theoretical midpoint of the faceness sigmoid and min(A) is the minimum value of the ambiguity function. **Right Panel:** Group averaged reaction times during the face detection task. For all panels, error bars represent standard errors across subjects. **B)** Percent Signal change during event related tasks in all ROIs. In blue, the BOLD responses to the stimulus relevant, domain specific task, in red to the stimulus irrelevant task. For the majority of ROIs, the stimulus relevant BOLD responses are larger across all phase levels relative to the stimulus irrelevant task. The green curve represents the differences between tasks.

*Face and Fixation fMRI analyses*

*ANOVA Results*

The subjects mean percent signal change in response to each condition, for each ROI, is shown

in Figure 3B.

The main effect of the task was significant ($p < 0.05$) in the lFFA ($F_{1,9} = 20.559$), rFFA ($F_{1,9} =$

13.131), lOFA ($F_{1,9} = 48.595$), rOFA ($F_{1,9} = 14.304$) and the rSTS ($F_{1,9} = 9.182$), with face detection driving

larger BOLD responses relative to the fixation task.

There was a significant ($p < 0.05$) main effect of the condition (phase coherence level) in the lFFA

($F_{4,36} = 13.136$), rFFA ($F_{4,36} = 35.567$), lOFA ($F_{4,36} = 7.56$), rOFA ($F_{4,36} = 22.866$), lSTS ($F_{4,36} = 7.98$), rSTS ($F_{4,36}$

$= 5.637$), the rAIT ($F_{4,36} = 4.174$). For these ROIs, paired sample post-hoc t-test ($p < .05$, corrected) showed

that the 40% phase coherence is always significantly larger than 0%.

There was a significant ($p < 0.05$) task by condition interaction term in the lFFA ($F_{4,36} = 4.96$), rFFA

($F_{4,36} = 3.311$), the rSTS ($F_{4,36} = 3.620$) and the rAIT ($F_{4,36} = 3.84$), indicating that amplitude increase during

detection relatively to fixation was different for different phase coherence levels. Post-hoc t-tests carried

out across tasks, within each condition revealed that for these ROIs only the 20% phase coherence

conditions were always significantly ($p < .05$ corrected) larger than all other conditions. The t-values (lFFA

($t(9) = 4.407$), rFFA ($t(9) = 4.132$), rSTS ($t(9) = 4.684$) and the rAIT ($t(9) = 3.376$)) and related effect sizes

(Hedges g*: lFFA: 1.361; rFFA: 1.795; rSTS: 1.791; and rAIT: 1.151) further indicate reliable and replicable

effects with the current N = 10.

*Functional Connectivity Measures*

Functional connectivity significantly increased (p <0.05, corrected) between multiple areas

during the face detection task relative to fixation in multiple core face processing areas. Specifically, we

found significant increases in functional connectivity between the 1) lFFA and the rFFA, right and lOFA,

rSTS and rAIT, 2) rFFA and rOFA, rSTS and rAIT, 3) the lOFA and the rSTS 4) the rOFA and the rSTS

(symmetrical connectivity between regions not repeated).

**Figure 4.** Dynamic Reconfiguration of Face Network as a function of Task **Top Row**: Connectivity
Matrices for Stimulus Relevant Face Detection Task (Left) and Stimulus Irrelevant Fixation Task (Right).
Asterisks indicate correlation coefficients that significantly (p<0.05) difference between tasks and are
identical between matrices for visualization purposes. **Bottom Row.** Classic Multidimensional Scaling for
connectivity matrices highlights the higher proximity of the rAIT to the core face areas as a function of
increased connectivity during face detection relative to the fixation task. ROIs in grey text indicate those
regions with no significant connectivity modulations across tasks.

Multidimensional scaling (MDS), which is a dimensionality reduction technique that allows

visualizing the level of similarity amongst data points, was used to summarize task demands related

modulations in connectivity. MDS spatial arrangement, where proximity amongst point indicates

similarity of responses, highlights how the rAIT is more closely located to the FFAs (i.e. significantly more

correlated) during face detection relative to fixation (see Figure 4 Bottom; multidimensional space of

fixation rotated onto that of detection using Procrustes transformation).

*Brain-Behavior Correlations*

Figure 5A shows the correlation between the ambiguity score and the difference in the measured

brain activity between the SR and SI tasks. Correlations where significant ($p < 0.05$, corrected) in the

bilateral FFA and OFAs and the rAIT.

**Figure 5. A)** Brain-Behavior Correlations in FFAs, OFAs and rAIT. **Top.** The Pearson correlation
coefficient between the ambiguity score and the difference in task BOLD responses. **Bottom.** For the
regions reaching significance (p<0.05), the left and right FFAs and OFAs, and rAIT, the t values are
plotted. **B)** Average BOLD response to 20% phase coherence (i.e. the most ambiguous stimulus) for the
trials in which participants reported a face percept (yellow) and no face percept (magenta). Responses
are reported for the regions that showed a significant (p<.05 corrected) task by condition interaction.
Star symbol indicates significantly (p<.05 corrected) difference in amplitude.

*Perceptual analysis*

For the 20% phase coherence condition only (i.e. the most ambiguous percept) we further

separated the activity elicited by each trial according to participants perceptual response, creating 2 new

conditions: "face percept" and "no face percept". We investigated amplitude differences between these

2 conditions for those ROIs that showed a significant task x condition interaction. While all areas showed

slightly larger BOLD amplitude for the face compared to the non-face percept, paired sample t-tests

indicated significant amplitude differences as a function of percept in the rAIT only (t(9) = 6.365 p<.05

corrected; see figure 5B). Moreover, paired sample t-tests contrasting the activation of each condition

for all ROIs against 0 further indicated significant (p<.05 corrected) above baseline activation for all ROIs

and conditions, except for the "no face percept" response in the rAIT, which did not significantly differ

from baseline.

## 230 Discussion

*Task Modulations & Ambiguity*

Straightforward manipulation of task demands can produce changes in the amplitude of BOLD

response in higher level areas, such as the FFA (Druzgal and D'Esposito, 2001; Kay and Yeatman, 2017;

Vuilleumier et al., 2001; Wojciulik et al., 1998) or STS (Narumoto et al., 2001). Traditionally, however,

these tasks manipulations are often indirectly related to the neural processing of the stimuli at hand, as

they serve a more general purpose of directing attention towards (e.g. N-back) or away from the stimuli

(e.g. fixation tasks, see (Bokde et al., 2005; Druzgal and D'Esposito, 2001; Egner and Hirsch, 2005; Kay

and Yeatman, 2017; Wojciulik et al., 1998)). Changes in neural responses to identical visual inputs related

to these unspecific changes in task demands often reveal broad contributions from attentional networks,

including frontal and parietal regions (Szczepanski et al., 2013). While these manipulations can shed light

upon the neural basis of general, non-specific top-down mechanisms, such as awareness, working

memory demands or vigilance, they may fail to reveal fine-grained top-down modulations pertaining to

the processing of a specific stimulus category. The approach used here instead builds on task

manipulations that tap into a relevant stimulus dimension. This disambiguates the contributions of

various regions *within* dedicated networks (here, the face processing network), by modulating the

difficulty within a stimulus relevant task. In the context of this work, we will be referring to the

modulatory forces that direct attention towards (e.g. N-Back) or away from (e.g. observe fixation) the

stimuli as *"non-specific top-down";* and to the task-specific modulations, as they pertain to task difficulty

or cognitive load, as *"domain-specific top-down"*.

*Task modulations: differentiating domain-specific vs non-specific top-down*

Our finding that the specificity of task-related modulations is dependent on the nature of the

task is consistent with a large body of literature highlighting the conceptual and anatomical differences

between different types of attention. Posner and Peterson (Posner and Petersen, 1990) delineated 3

attention subsystems devoted to orienting, detection, and alertness. *Our results suggest that a design*

*in which domain-specificity difficulty is varied is capable of revealing the distinct modulation associated*

*with different attentional subsystems.* The significant (p<.05 corrected) main effect of task, indicates, in

accordance with previous reports (Druzgal and D'Esposito, 2001; Kay and Yeatman, 2017; Vuilleumier et

al., 2001; Wojciulik et al., 1998) that BOLD amplitude is on average larger during the stimulus relevant

(SR) relative to stimulus irrelevant (SI) task in canonical face processing areas: the bilateral FFA, OFA and

the rSTS. In line with previous work, (Druzgal and D'Esposito, 2001; Kay and Yeatman, 2017; Ress et al.,

2000), we suggest that these increases reflect broad top-down contributions relating to increased

vigilance and awareness of the stimuli, which have previously been shown to improve decoding

performance (Dobs et al., 2018).

By contrast, there are a specific subset of areas that show an interaction between task and

stimulus: the bilateral FFA as well as the rAIT and rSTS. Of these only the rAIT showed only the significant

interaction, driven by the activity elicited by the 20% phase coherence images being larger during the SR

compared to the SI. This result indicates that, at least within the context of this work, this region's

responses are *exclusively domain-specific top-down modulations*. In this region in fact, other than for the

20% phase coherence, task demands do not alter BOLD amplitude to any other condition (Figure 3B).

Finally, a large number of regions, specifically the FFAs, OFAs, STS, and rAIT showed a main effect

of condition, driven by larger amplitude for the 40% phase relative to the 0% phase. As this comparison

is equivalent to a classical 'face vs scrambled face' linear contrast (Chen et al., 2007; Rossion et al., 2012)

used to define stimulus selectivity, and consistent with the preferentiality of these regions for this

stimulus category, this result is unsurprising and won't be discussed further.

*Ambiguity*

Post-hoc t-tests carried out on the significant task x condition interactions revealed that in all

cortical regions exhibiting specific top-down modulations, the stimulus relevant task amplitude increases

were always significant *only* for 20% phase coherence. Behaviorally, this condition was also found to be

the most perceptually ambiguous, i.e. the condition with the largest reported number of contrasting

percepts (i.e. "face" and "no face"). In the context of this study we mathematically defined ambiguity as

the inverse of the absolute difference from the inflection point of the sigmoid that describes the face

percept/detection behavioral responses (see Equation 1). Both extremes of the phase coherence

continuum therefore represent non-ambiguous percepts. That is, at low phase coherence (e.g. 0%)

participants consistently reported no face percept and at high coherence (40%) participants consistently

reported the presence of a face (Figure 3A). At the maximally ambiguous, 20% condition, the percept

was at its most unstable and thus most difficult to categorize, leading to a larger amplitude response.

This relative increase is consistent with prior work showing that task difficulty can modulate the BOLD

response not only in frontal or parietal regions (Culham et al., 2001; Gould et al., 2003) but also in these

category sensitive visual areas (Druzgal and D'Esposito, 2001).

Notably, the reaction times measured in this study do not appear to capture this difficulty

increase (Figure 3A). This disconnect between reaction time and experimental performance has been

noted before in relation to accuracy and attentional cueing (van Ede et al., 2012) or to task difficulty

across a wide range of N-back conditions (Lamichhane et al., 2020). In our data, this likely reflects a

disconnect between the idea of "task difficulty" and "difficulty in categorization" which may provide

separate contributions to total reaction time.

*Top-down driven network reconfiguration*

To understand how top-down/context modulated the inter-regional neural communication and

thus the connectivity within specialized cortical networks (here, the face network), we compared

functional connectivity between tasks (see paragraph 4.6.2). By computing functional connectivity on

concatenated FIR curves, we: 1) discard the contribution of ongoing activity (which is not the focus of

this specific work); and 2) increase statistical power and thus the reliability of our correlational metric.

Broadly speaking, connectivity was significantly greater in core and extended regions (i.e. between FFAs,

OFAs and rSTS) during the stimulus relevant task, indicating greater communication among these areas,

presumably to fulfill task demands. In particular, we observed significantly (p<.05 corrected) greater

connectivity between the rAIT and the FFAs during the face task relative to the fixation (Figure 4). A

number of studies have suggested a functional differentiation between the right and lFFA (Meng et al.,

2012; Rossion et al., 2000), with the former being more involced in holistic processing and the latter in

featural processing. It is therefore likely that the degraded stimuli used here (Figure 1) drive both

individual feature detection as well as holistic face processing; or that subjects flexibly adapt their

strategy depending on the available information, switching from featural (e.g. looking for eyes) to holistic

detection, thus engaging both FFAs.

Within the current experimental settings, our data suggest that, during face processing, the rAIT

can be recruited by the cortical face network to add an additional resource to resolve ambiguous

percepts. These results are consistent with the functional differentiation between core and extended

cortical face networks, according to which the core system mediates the representation of more basic

aspects of face processing, while the extended system is involved in higher level cognitive functions and

can be selectively recruited to act in concert with the regions in the core system (Haxby et al., 2000).

Moreover, our results suggest that network connectivity is not static, but flexibly adapts to the

contextual demands. This is in line with an ever growing body of literature advocating the plastic nature

of functional connectivity during task and at rest (Allen et al., 2014; Cribben et al., 2013; Debener et al.,

2006; Doucet et al., 2012; Hutchison et al., 2013; Sadaghiani et al., 2009) in response to cognitive and

behavioral demands (Gratton et al., 2018; Hutchison and Morton, 2016). Our results further expand

these views, indicating that even subtle changes in task demands, as those implemented here, can have

a dramatic impact over local network reconfigurations.

*Using Stimulus Ambiguity to Differentiate Functional Architecture*

Though it is challenging to establish causality, taken together, our results suggest that the rAIT is

the source of top-down modulation. First, the correlation between the difference of the BOLD signal

between tasks, and each participant's behavior (ambiguity score) was only significant in the bilateral

FFAs and OFAs and the rAIT. By using task differences in BOLD responses to identical stimuli, we sought

to highlight task specific top-down effects. This finding, indicating correspondence between the

ambiguity function and the difference in BOLD amplitude across tasks within these ROIs, suggests that

this ambiguity signal originates from one of these regions. As the rAIT is further along the information

hierarchy, it is the plausible source of this signal. Moreover, functional connectivity analysis shows

increased connectivity between the rAIT and both FFAs, between OFAs and FFAs, but not between the

rAIT and either of the OFAs. In addition, the FFAs show both non-specific (significant main effect of task)

and domain-specific (significant task x condition interaction) top-down effects, while the rAIT shows only

the task-specific, ambiguity related, top-down effects (significant interaction).

Though prior work has often implicated frontal regions or parietal areas as being a source for

these top-down signals when detecting objects such as faces or houses (Baldauf and Desimone, 2014;

Kay and Yeatman, 2017), these studies used indirect methods (i.e. 1-back; house or face) to examine

face detection. By manipulating difficulty within the context of face detection, we uncover a different,

within-network source of top-down modulation by directly stressing the face processing system. This

approach is similar to prior work finding modulation within the ventral temporal cortex when viewing

degraded facial stimuli (Fan et al., 2020).

Furthermore, there is evidence that the AIT is involved in resolving difficult stimuli in both

macaques and humans. For the former, prior work has implicated this region in learning ambiguous

stimulus rules related to concurrent discrimination (Bussey et al., 2002). Increases in ambiguity were

associated with worse performance in the macaques with perirhinal cortex (i.e. anterior inferior

temporal lobe) lesions. In humans, there is evidence that the AIT is associated with discriminating

individual face identities (Nasr and Tootell, 2012; Zhang et al., 2016), however these studies employed

tasks that did not necessarily tap directly into stimulus-specific dimensions. Though these studies offer

support for our findings, they are unable to disambiguate the relationship between behavior and

perception, as they either used a memory task, in which subjects could have used an image matching

strategy (Nasr and Tootell, 2012), or used only a fixation task (Zhang et al., 2016). Additional evidence

for the involvement of the AIT in ambiguous or difficult stimuli comes from outside the face perception

literature: this area is active when integrating conceptual and perceptual information (Martin et al.,

2018) and it is associated with identifying confusable objects (Clarke and Tyler, 2014; Tyler et al., 2013).

We therefore argue that the results presented here and those reported in previous work represent

indication that the ambiguity-related top-down signal during face detection originates in the rAIT, is fed

back to the FFAs and, from there, to the OFAs. Future work can explicitly assess this using specifically

tailored research methods that provide better evidence of causality, such as depth dependent fMRI

analyses (Huber et al., 2017), intracranial EEG or fMRI with dynamic causal modeling (Friston et al., 2019).

*Neural Correlate of Perception*

While FFAs and rSTS show both a main effect of task and a task by condition interaction, only the

latter was significant in the rAIT. To better understand these differences and further characterize the

response profile of these regions, we grouped BOLD responses according to each participant's percept

during the most ambiguous condition (i.e. 20% phase coherence). This analysis shows that, *for the rAIT*

*only*, responses elicited by face percepts are significantly larger than those elicited by no face percepts

(Figure 5B), indicating a high correspondence between neural and behavioral responses. Moreover,

unlike FFAs and rSTS, showing significant above baseline activation for the no face percept condition,

the rAIT shows no significant activation when participants failed to perceive a face (Figure 5B). Taken

together, these findings represent evidence for a direct link between the rAIT and subjective perception.

These observations are consistent with the idea that anterior temporal regions are involved in subjective

awareness (Li et al., 2014) and with reports that the AIT organizes visual objects according to their

semantic interpretations (Price et al., 2017). These findings are also consistent with the data form the

face localizer (Figure 1) in which the rAIT shows the most preferential face response amongst these 4

regions, with objects and scrambled images not being significantly different from zero.

The significant activation for the no face percept condition in the FFAs and rSTS can be related to

the bottom-up physical properties of the stimulus: regardless of the perceptual state, the 20% phase

coherence images always contained a face stimulus. Alternatively, this result can be due to the

contextual top-down induced by task demands (here a face detection task). That is, as tasks were blocked

by run, during SR runs, participants expected having to resolve perceptual judgment of an ambiguous

stimulus, and therefore looked for a face or a face feature in every trial. This is consistent with the

observation that, in the absence of a face, the FFA can be activated from contextual cues alone (Cox et

al., 2004).

Past work using ambiguous facial stimuli in the form of Mooney faces (MOONEY, 1957)

have found amplitude differences in the FFA (Andrews and Schluppeck, 2004) or latency differences in

the rOFA (Fan et al., 2020). Alternative approaches using bistable perception, such as the face/vase

illusion also report that the FFA shows greater activation when faces are perceived (Andrews et al., 2002;

Hasson et al., 2001). With binocular rivalry, in which alternative images are shown to each eye, the FFA

also increases in activity when faces are perceived (Tong et al., 1998). In our present work we found that

the FFA did show a larger, however, non-significant increase when subjects reported seeing a face. This

apparent discrepancy with prior reports can be explained by differences in experimental paradigms.

Unlike Mooney faces, or face-related bistable stimuli, the 20% phase coherence stimuli used here always

have a physical face present. For binocular rivalry, the perceptual ambiguity is similar to bistable

perception, however binocular rivalry is ecologically implausible. The defining characteristic of these

probes is a dynamic switching amongst percepts despite identical visual input. Here, we have instead

focused on the ambiguity of the initial percept, which is more similar to approaches using degraded or

partially occluded static stimuli (Flounders et al., 2019; Frühholz et al., 2011). With our stimuli and

experimental manipulations, *we isolate a unique and distinctive signal only in the rAIT that distinguishes*

*the subjective perception of a face.*

Another important implication of the findings presented is their interpretation in relation to non-

human primate research. Similar to humans, macaque monkeys possess a specialized cortical network

in inferotemporal cortex dedicated to processing faces (e.g. (Tsao et al., 2003)), however the exact

correspondence between human and macaque face-selective areas is still unclear (Tsao et al., 2008a,

2006, 2003). While a degree of structural and functional correspondence has been achieved with regards

to the core regions (e.g. macaque middle face patches to human FFA (Rajimehr et al., 2009; Tsao et al.,

2008a)), identifying a human homologues of the macaque anterior medial (AM) patch (the anterior most

patch) has been challenging. Tsao, Moeller, et al. (Tsao et al., 2008a) for example, failed to uncover a

comparable region in humans, attributing such failure to suceptibility related signal drop out due the

putative proximity of this area to the ear canal. Rajimehr and colleagues (Rajimehr et al., 2009)

uncovered a face specific region in human AIT in 5 out of 10 participants, but were unable to elucidate

the nature of its response properties. Here not only were we able to identify a human face selective

region in AIT in all subjects, but, importantly, we were able to define its response profile. Our results,

linking the function of the face AIT to subjective perception, are in line with recent electrophysiology

reports, showing that activity in the AM face patch is related to the animal's individual ability to detect

a face (Moeller et al., 2017).

*Benefits of High Field Imaging*

As briefly mentioned in the above paragraph, much of the difficulty in imaging regions such as

the AIT relates to low SNR associated because of susceptibility artifacts and inefficient RF transmit fields

in the ventral temporal lobes (Devlin et al., 2000). Moreover, areas such as the AIT are typically difficult

to image at more conventional (3T) field strengths and are often not located in every individual (e.g. 50%

in Rajimehr et al., 2009), nor do they show large deviation from expected hemodynamic responses (e.g.

Ramon et al., 2015). These issues can persist independent of field strength.

Here we used UHF fMRI to capitalize on higher SNR, CNR, and acceleration performance

maximizing fMRI sensitivity in these regions. _For all our participants_ we report consistent and

corresponding regions in the anterior inferior temporal cortex on both the left and right that

preferentially respond to faces and that are modulated by task demands. This increased sensitivity that

led to large effect size and ROI identification in all subjects, stems from a combination of parameters

optimization. Specifically, in addition to the increased SNR that accompanies UHF strength, unlike 3T

acquisitions, where no effort has been put forward to for optimizing B0 and flip angles, we manually

adjusted B0 inhomogeneity and flip angles to maximize SNR for each subject. Moreover, relative to

previous human work, where functional voxels measured > 3 mm iso (e.g. (Rajimehr et al., 2009; Ramon

et al., 2015)), here, we used 1.6 mm iso voxels, minimizing partial volume effects and spin dephasing,

ultimately reducing signal loss in dropout regions (Thanh Vu et al., 2017).

_Beyond the ventral temporal lobe: future directions_

Beyond the ventral temporal lobe, there have been reports of face sensitive regions in lateral

orbital regions in macaques (Barat et al., 2018; Hadj-Bouziane et al., 2008; Tsao et al., 2008b). However,

evidence for the existence of these areas in humans has been mixed, uncovering such regions in

approximately half (Troiani et al., 2016) or one-third of the study population (Troiani et al., 2019; Tsao

et al., 2008a). In the current work, we are able to identify these areas in all subjects during the localizer

portion of the study. Activation was proximal to the H-Shaped sulci, consistent with both prior reports

(Troiani et al., 2019) and across subjects, as visualized after normalization to MNI space (Figure 2). Like

the other ROIs in the face preferential cortical network, these regions exhibited positive responses to

faces and significantly (p< .05) greater activity to faces relative to scrambled stimuli or objects (See

Methods).

Although we did not observe meaningful stimulus relevant task modulations we did observe an

interesting, although non-significant, separation of 2 areas, with regard to their functional connectivity

during face detection: the rHFA exhibited a non-significant increase in activation, while its left

counterpart exhibited a non-significant decrease. These areas have been suggested to be involved in

social and emotional aspects of face processing in non-human primates (Barat et al., 2018), aspects that,

within the current task context, are irrelvant. Our failure to find task modulations is therefore consistent

with the more complex evaluative role of the frontal cortices (Noonan et al., 2012) and its engagement

in social perception tasks (Barat et al., 2018; Beer et al., 2006; Freeman et al., 2010; Mah et al., 2004).

Given the enlarged frontal cortices among primate species and in particular the highly developed frontal

areas in humans, it will be essential to perform further research that manipulates context, value and/or

salience in order to elucidate the functional role of the HFAs during face processing.

## Conclusion

Using faces, a well-studied stimulus underpinned by a dedicated, complex cortical network, in

this study we combined high SNR fMRI with domain-specific attention and observed 2 types of top-down

scaling mechanisms: 1) a broad gain effect related to drawing attention to the stimuli, manifesting as an

unspecific amplitude increase across conditions; and 2) an additional scaling of specific conditions

dictated by domain-specific task requirements. We explain the latter in terms of perceptual ambiguity

and suggest that the ambiguity signal originates in the rAIT. Importantly, only in the rAIT is both

preferentially active under challenging conditions and predictive of the subjects' perceptual judgments.

We further show that subtle changes in task demands can lead to dramatic changes in network

reconfigurations. Our results suggest that the combination of ecologically relevant tasks with low noise

fMRI capable of resolving previously inaccessible regions of the human brain may be the only way to

understand the changes underlying human cognitive flexibility

## 479 **Materials and Methods**

*Participants*

10 (5 females) healthy right-handed subjects (age range: 18-31) participated in the study. Of

these, 1 participant was re-scanned due to excessive motion during scanning. All subjects had normal,

or corrected vision and provided written informed consent. The local IRB at the University of Minnesota

approved the experiments.

*Stimuli and procedure*

The experimental procedure consisted of a standard block design face localizer and a fast event-

related face paradigm. For both experiments, the stimuli were centered on background of average

luminance (25.4 cd/m2, 23.5-30.1). Stimuli were presented on a Cambridge Research Systems

BOLDscreen 32 LCD monitor positioned at the head of the 7T scanner bed (resolution 1920, 1080 at 120

Hz; viewing distance ~89.5 cm) using a Mac Pro computer. Stimulus presentation was controlled using

Psychophysics Toolbox (3.0.15) based code. Participants viewed the images though a mirror placed in

the head coil. Behavioral responses were recorded using Cambridge Research Systems button box and

Psychophysics Toolbox.

*Face localizer*

*Stimuli*

All visual stimuli used for the face localizer consisted of grayscale photographs depicting 20

different faces (10 identities × 2 genders) and objects (both taken from (Stigliani et al., 2015)) and

textures of noise.

The experiment consisted of the presentation of grayscale stimuli drawn from different stimulus

categories. There were 11 categories, grouped into 3 stimulus domains: faces (adult, child), no face

objects (including characters (word, number), body parts (body, limb), places (corridor, house), and

objects (car, instrument)) and phase scrambled faces, computed by randomly scrambling the phase

coherence of the face stimuli. Each stimulus was presented on a scrambled background (different

backgrounds for different stimuli) and occupied a square region with dimensions 10° × 10°. Noise texture

stimuli were created by randomly scrambling the phase of the face images (i.e. 0% phase coherence).

The stimuli were equated in terms of luminance, contrast and spatial frequency content by taking

the Fourier spectra across stimuli and ensuring that the rotational average amplitudes for a given spatial

frequency were equated across images while preserving the amplitude distribution across orientations

(Willenbockel et al., 2010). The root mean square contrast (i.e. the standard deviation of pixel intensity)

was also kept constant across stimuli.

*Visual presentation paradigm*

Face localizer runs involved presentation of blocks of faces, objects and noise textures. Each run

began with presentation of a black fixation cross displayed on a grey background for 12 sec and consisted

of 9 randomly presented blocks of images. Each block (3 blocks/category; separated by a 12 sec fixation)

involved presentation of 10 different stimuli randomly presented for 800 ms, separated by a 400 ms

interstimulus interval (ISI). To ensure that participants' attention was maintained throughout the

localizer we implemented a 1-back task, where subjects were instructed to respond to the repetition of

2 identical stimuli (representing about 10% of the trials), by pressing a button on a response pad held in

their right hand. All participants completed two runs of the block design face localizer, where each block

occurred 3 times within a run, for a total run duration of 228 seconds.

*Event related experiment.*

*Stimuli*

We used grayscale images of faces (20 male and 20 female). We manipulated the phase

coherence of each face, from 0% to 40% in steps of 10%, resulting in 200 images (5 visual conditions x

20 identities x 2 genders). We equated the amplitude spectrum across all images. Stimuli approximately

subtended 9° of visual angle. Faces were cropped to remove external features by centering an elliptical

window with uniform gray background to the original images. The y diameter of the ellipse spanned the

full vertical extent of the face stimuli and the x diameter spanned 80% of the horizontal extent. Before

applying the elliptical window to all face images, we smoothed the edge of the ellipse by convolving with

an average filter (constructed using the "fspecial" function with "average" option in MATLAB – see Figure

1A). This procedure was implemented to prevent participants from performing edge detection, rather

than the face detection task, by reacting to the easily identifiable presence of hard edges in the face

images.

Like for the localizer experiment, here too we equated amplitude spectrum across the whole

stimulus set. We controlled the Fourier spectra across stimuli, ensuring that the rotational average

amplitudes for a given spatial frequency were equated across images while preserving the amplitude

distribution across orientations (Willenbockel et al., 2010). The root mean square contrast (i.e. the

standard deviation of pixel intensity) was also kept constant across stimuli.

*Tasks*

In the scanner, participants were instructed to maintain fixation on a central cross throughout

the run and to perform one of 2 tasks: one domain-specific face detection task, involving perceptual

judgment of the visual stimuli; and a second, difficult, non-specific attention fixation task that required

responding to a specific color change (i.e. red) of the fixation cross.

In the former, participants were instructed to respond as quickly as possible by pressing one of 2

buttons on their button box to indicate whether they perceived a face. Subjects' instructions were

carefully delivered to indicate that there were no correct answers and that we were instead interested

in the subjects' perception only (Figure 1B).

The latter was designed to isolate bottom-up stimulus-driven responses. In order to ensure this,

we piloted the fixation task to maximize task difficulty and direct the attention away from the face stimuli

on 4 participants that were not included in the experimental subject pool. Based on participants'

feedback, the fixation tasks entailed pressing a button every time the fixation turned red. Every 500 ms,

the fixation changed to one of five colors — specifically red, blue, green, yellow and cyan — in a

pseudorandom fashion, avoiding consecutive presentations of the same color (Figure 1C). The color

change occurred out of sync with the stimulus presentation onset and frequency of button presses was

kept constant across tasks. Visual stimuli were identical across tasks to ensure that any differences

observed were related solely to top-down processes. Tasks were blocked by run and counterbalanced

across participants.

*Visual presentation paradigm.*

We acquired 3 runs per task. Each run lasted approximately 3 mins and 22 secs and began and

ended with a 12-second fixation period. Within each run, we showed 40 images (5 phase coherence

levels x 4 identities x 2 genders) presented for 2000 ms, with a 2000 ms interstimulus interval (ISI).

Importantly, we introduced 10% blank trials (i.e. 4000 ms of fixation period) randomly interspersed

amongst the 40 images, effectively jittering the ISI. Stimulus presentation was pseudorandomized across

runs, with the only constraint being the non-occurrence of 2 consecutive presentations of the same

phase coherence level. Behavioral metrics, including reaction time and responses to face stimuli

indicating participants' perceptual judgments (i.e. face or no face) were generated per subject and then

averaged.

*Ambiguity Calculation*

For the face detection task, we calculated the average face response percentage to each

phase condition, averaged across runs. These values vary from 0 to 100%, representing consistent non-

face to consistent face response respectively. Within each subject, this produces a sigmoidal shaped

curve. We mathematically define the ambiguity score, on a subject by subject basis, as the inverse of the

absolute distance from the inflection point on the sigmoid that fit this curve This is shown in Equation 1:

Eq 1.   $(|S_i - S_k| \times -1) + \min(A)$

where $S_i$ is the *i*th point of the faceness sigmoid, $S_k$ is the theoretical midpoint of the faceness

sigmoid and min(A) is the minimum value of the ambiguity function.

*MR Imaging Acquisition and Processing*

All functional MRI data were collected with a 7T Siemens Magnetom System with a 1 by 32-

channel NOVA head coil. T2*-weighted images were collected using sequence parameters (TR 1.6s,

Multiband 5, GRAPPA 2 , 7/8ths Partial Fourier, 1.6mm isotropic, TE 22ms, Flip Angle 51.6°, Bandwidth

1923Hz) matched to the Human Connectome 7T protocol (Thanh Vu et al., 2017).

For each participant we manually shimmed the B0 field to maximize homogeneity over ventral

and anterior-temporal regions. Moreover, we optimized flip angles across the brain to maximize SNR.

T1-weighted anatomical images were obtained using an MPRAGE sequence (192 slices; TR, 1900

ms; FOV, 256 x 256 mm; flip angle, 9°; TE, 2.52 ms; spatial resolution, .8 mm isotropic voxels) which were

collected with a 3T Siemens Magnetom Prisma$^{fit}$ system. Anatomical images were used for visualization

purposes only.

*Functional Image Processing*

Dicom files were converted using dcm2niix (Li et al., 2016). Subsequence functional image

processing was performed in AFNI version 19.2.10 (Cox, 1996). Conventional processing steps were used,

including despiking, slice timing correction, distortion and motion correction, and alignment to each

participant's anatomical image. With each task type, the target for time series and anatomical alignment

was the Single Band Reference (SBRef) image which is acquired to calibrate coil sensitively profiles prior

to the multiband acquisition and has no slice acceleration or $T_1$-saturation, yielding high contrast (Smith

et al., 2013). In order to improve localizer and task alignment, an additional nonlinear transform was

computed between the task SBRef and localizer SBRef. All spatial transforms were concatenated and

applied in a single step to reduce image blurring, and functional images were inspected to confirm

successful registration to anatomical targets.

*Localizer Task Analyses*

For the functional localizer, the data then smoothed with a Gaussian kernel with FWHM of 2

voxels (3.2mm), and each run scaled to have mean 100. Nuisance regressors included high-pass filtered

using a Fourier basis set of three cycles per run (including linear trend) and the 6 estimated rigid-body

motion parameters.

*Functional ROI Definition*

Using 3dDeconvolve, the data were passed through a GLM in order to determine the response

to faces, objects and noise. Each event was modeled as a 12s box car, convolved with AFNI's SPMG1 HRF

estimation. Rather than select face patches by comparing face activation to the average of objects and

noise, we instead constrained the statistical map in the following ways: 1) Betas to faces were positive,

2) the T-stat used for thresholding was the minimum positive T-stat from faces > objects or faces > noise.

In other words, we selected voxels that were significant for faces greater than objects, in conjunction

with faces greater than scrambled. Regions of interest (ROIs) were derived in volume space, and all

consisted of contiguous clusters made up of 20 or more voxels. Statistical thresholding was adjusted to

obtain consistency between subjects, no voxels above $p<0.05$ were considered. In addition, to

supplement the statistical parametric maps, we used finite impulse response (FIR) deconvolution, with

20 bins, to estimate HRFs in response to each localizer condition (face, scrambled, object). These HRFs

were also used to inspect data quality for each ROI.

*Face Detection and Fixation Color Tasks Analyses*

For the Face/Fix detection tasks, the data were only scaled following initial processing, no

smoothing was used. As we were interested in BOLD responses across the whole brain, and we know

that hemodynamic response functions differ across cortical regions (Handwerker et al., 2004; Lewis et

al., 2018; Taylor et al., 2018), we performed a GLM based finite impulse response (FIR) deconvolution

analyses, which does not make assumptions regarding the shape of the HRF. This was done using AFNI's

TENTZero method, estimating responses with 1s bins out to 15s post stimulus. Deconvolution was

performed separately for each task (face detection and fixation) and phase coherence condition,

generating 5 FIR curves for the fixation task and 5 for the face detection task. For each task and

independently per subject, ROI, run and condition, we averaged all FIR curves across all voxels. To avoid

the contribution of extreme voxels, we trimmed 5% of the values falling at each extreme of the

distribution tail to compute the 10% trimmed mean. We then extracted the 4 timepoints corresponding

to 4, 5, 6 and 7 seconds after stimulus onset, i.e. those with the largest amplitude within a time window

spanning from 2 to 10 TRs after stimulus onset. The 12 extracted amplitudes (4 timepoints per run) were

then averaged within experimental tasks to obtain one percent signal change value per subject, ROI, task

and condition.

*Statistical Analyses*

To test for statistically significant differences between conditions (i.e. phase coherence levels)

and tasks, we carried out the following statistical tests.

*Task and Condition Analyses*

Independently per ROI, we performed a 2 (tasks) by 5 (phase coherence levels) repeated

measures ANOVA with the mean BOLD response as a dependent variable. To control for family wise error

rate (FWER), we implemented the following multiple comparison correction procedure: we began by

centering the data on the group mean for each condition and task. This procedure effectively put the

data under the ideal H0 hypothesis of no difference between the means. We then sampled with

replacement the subjects and performed the same 2 x 3 repeated measures ANOVA and stored all F

values for the relevant main effects and interactions. We repeated this procedure 10,000 times and

selected the 95% largest F values. We used these F values as our new thresholds and considered

statistical significance only when p values for the original ANOVA were smaller than .05 *and* the

connected F values were larger than their centered counterpart (e.g. (Wilcox, 2005))

When appropriate (i.e. for comparisons entailing more than 2 factors), we further performed

post-hoc paired sample t-tests on significant (as defined above) main effects and interactions. The same

FWER control procedure described above for the ANOVA test was implemented to account for multiple

comparisons.

Additionally, we performed power analyses to determine effect size and the sample size required

to achieve adequate power (see results). Specifically, we computed Hedges' g (Freeman et al., 1986;

Hedges, 1981). This choice was motivated by the fact that, unlike Cohen's d, which, especially for small

samples (i.e. n < 20), tends to provide positively biased estimators of population effect sizes (Freeman

et al., 1986; Lakens, 2013), Hedges' g tends to be unbiased (Cumming, 2012).

*Functional connectivity analyses.*

To determine the extent to which task demands modulate functional connectivity amongst face

ROIs, we carried out the following analysis. Independently per subject, task and ROI, we averaged (mean)

all FIR response curves amongst voxels and concatenated the time courses elicited by each condition to

produce a single time course. The concatenation was done to maximize statistical power, as the resulting

time course contained 80 timepoints (i.e. 16 FIR timepoints x 5 conditions). For each subject and task,

we then computed Pearson's correlation coefficient between the concatenated time courses of all

possible pairs of ROIs. This procedure lead to the formulation of 2 connectivity matrices (12 ROIs x 12

ROIs) per subject (1 per task) summarizing the similarity of BOLD responses between all pairs of ROIs. To

convert the skewed sampling distribution of Pearson's r into a normal distribution we computed Fisher's

z transformation (Fisher, 1915). We therefore proceeded to carry out paired sample t-tests between the

connectivity estimated obtained for the 2 tasks. To control for FWER, we implemented the same

bootstrap procedure on centered data described in the previous paragraphs (see paragraph 4.6.1). For

display purposes only, after computing the mean between the Fisher z-normalized connectivity matrices,

we computed the inverse of such transformation on the group average connectivity matrices to convert

these scores back into meaningful and interpretable Pearson's r.

To better visualize the results of our functional connectivity analysis, we further performed

classic multidimensional scaling (MDS - using the function "cmdscale" in MATLAB) on the participants

average dissimilarity matrix (i.e. 1- Pearson's r). MDS was performed independently per task. For ease

of visual comparison, the MDS arrangements of the 2 tasks were aligned by means of linear

transformations (including translation, reflection, orthogonal rotation, and scaling) using Procrustes

rotations (this was implemented with the "procrustes" function in MATLAB) with the sum of squared

errors as stress metric.

MDS is a useful data driven approach to visualize the data projected into a new space whose

dimensions are the first (in this case 2) eigenvectors (i.e. those explaining most of the variance in the

data) without any prior hypotheses. MDS is therefore a dimension reduction technique that highlights

the dominant features in the data. Results are shown in Figure 4; distance between the points indicate

dissimilarity of responses.

*Brain-behavior correlation.*

Next for each ROI, we wanted to assess the relationship between behavioral responses and top-

down BOLD modulations. To this end, for each subject and ROI, we computed Pearson's correlation

coefficients amongst the ambiguity scores at each phase coherence level and the task difference in

average BOLD amplitudes elicited by each condition. We then performed Fisher z transform (see

paragraph above) on Pearson's r and carried out one sample t-test for each ROI to determine whether

the average group correlation was significantly larger than 0. To control the family wise error rate

(FWER), we implemented the same bootstrap procedure on centered data described in the previous

paragraphs (see paragraph 4.6.1). For display purposes only, after computing the mean between the

Fisher z-normalized correlation scores, we computed the inverse of such transformation on the group

average to convert these scores back into meaningful and interpretable Pearson's r.

*Perception-Based Analyses*

We performed additional analyses to assess BOLD amplitude modulations as a function

of percept. For the most ambiguous condition (i.e. 20% phase coherence, see results), stimulus grouping

was determined on the basis of each participants reported percept. We allocated each trial to one of 2

new conditions: "*face percept*" and "*no face percept*". We then repeated the analysis described in

section 2.5.4 to estimate BOLD amplitudes of these 2 conditions.

## 720 Acknowledgments

721     Funding for this study was provided by National Institutes of Health Grants RF1 MH117015

722 (Ghose), RF1 MH116978 (Yacoub), and P30 NS076408 (Ugurbil). The authors would also like to thank Dr.

723 Kendrick Kay for conceptual discussions regarding stimulus ambiguity and feedback.

## 725 Competing Interests

726     The authors have no financial or non-financial competing interests associated with this work.

## 728 References

Alexander GE, DeLong MR, Strick PL. 1986. Parallel Organization of Functionally Segregated Circuits

Linking Basal Ganglia and Cortex. *Annu Rev Neurosci* **9**:357–381.

doi:10.1146/annurev.ne.09.030186.002041

Allen EA, Damaraju E, Plis SM, Erhardt EB, Eichele T, Calhoun VD. 2014. Tracking whole-brain connectivity

dynamics in the resting state. *Cereb Cortex* **24**:663–676. doi:10.1093/cercor/bhs352

Andrews TJ, Schluppeck D. 2004. Neural responses to Mooney images reveal a modular representation

of faces in human visual cortex. *Neuroimage* **21**:91–98. doi:10.1016/j.neuroimage.2003.08.023

Andrews TJ, Schluppeck D, Homfray D, Matthews P, Blakemore C. 2002. Activity in the Fusiform Gyrus

Predicts Conscious Perception of Rubin's Vase–Face Illusion. *Neuroimage* **17**:890–901.

doi:10.1006/nimg.2002.1243

Arcaro MJ, Livingstone MS. 2017. Retinotopic organization of scene areas in macaque inferior temporal

cortex. *J Neurosci* **37**:7373–7389. doi:10.1523/JNEUROSCI.0569-17.2017

Baldauf D, Desimone R. 2014. Neural mechanisms of object-based attention. *Science (80- )* **344**:424–427.

doi:10.1126/science.1247003

Barat E, Wirth S, Duhamel JR. 2018. Face cells in orbitofrontal cortex represent social categories. *Proc*

*Natl Acad Sci U S A* **115**:E11158–E11167. doi:10.1073/pnas.1806165115

Bassett DS, Wymbs NF, Porter MA, Mucha PJ, Carlson JM, Grafton ST. 2011. Dynamic reconfiguration of

human brain networks during learning. *Proc Natl Acad Sci U S A* **108**:7641–7646.

doi:10.1073/pnas.1018985108

Beer JS, John OP, Scabini D, Knight RT. 2006. Orbitofrontal cortex and social behavior: Integrating self-

monitoring and emotion-cognition interactions. *J Cogn Neurosci* **18**:871–879.

doi:10.1162/jocn.2006.18.6.871

Bokde ALW, Dong W, Born C, Leinsinger G, Meindl T, Teipel SJ, Reiser M, Hampel H. 2005. Task difficulty

in a simultaneous face matching task modulates activity in face fusiform area. *Cogn Brain Res*

**25**:701–710. doi:10.1016/j.cogbrainres.2005.09.016

Bussey TJ, Saksida LM, Murray EA. 2002. Perirhinal cortex resolves feature ambiguity in complex visual

discriminations. *Eur J Neurosci* **15**:365–374. doi:10.1046/j.0953-816x.2001.01851.x

Chen CC, Kao KLC, Tyler CW. 2007. Face configuration processing in the human brain: The role of

symmetry. *Cereb Cortex* **17**:1423–1432. doi:10.1093/cercor/bhl054

Chen NK, Dickey CC, Yoo SS, Guttmann CRG, Panych LP. 2003. Selection of voxel size and slice orientation

for fMRI in the presence of susceptibility field gradients: Application to imaging of the amygdala.

*Neuroimage* **19**:817–825. doi:10.1016/S1053-8119(03)00091-0

Clarke A, Tyler LK. 2014. Object-specific semantic coding in human perirhinal cortex. *J Neurosci* **34**:4766–

4775. doi:10.1523/JNEUROSCI.2828-13.2014

Cohen MR, Maunsell JHR. 2011. Using Neuronal Populations to Study the Mechanisms Underlying Spatial

and Feature Attention. *Neuron* **70**:1192–1204. doi:10.1016/j.neuron.2011.04.029

Cox D, Meyers E, Sinha P. 2004. Contextually Evoked Object-Specific Responses in Human Visual Cortex.

*Science (80- )* **304**:115–117. doi:10.1126/science.1093110

Cox RW. 1996. AFNI: Software for analysis and visualization of functional magnetic resonance

neuroimages. *Comput Biomed Res* **29**:162–173. doi:10.1006/cbmr.1996.0014

Cribben I, Wager TD, Lindquist MA. 2013. Detecting functional connectivity change points for single-

subject fMRI data. *Front Comput Neurosci* **7**. doi:10.3389/fncom.2013.00143

Culham JC, Cavanagh P, Kanwisher NG. 2001. Attention response functions: Characterizing brain areas

using fMRI activation during parametric variations of attentional load. *Neuron* **32**:737–745.

doi:10.1016/S0896-6273(01)00499-8

Cumming G. 2012. Understanding the new statistics: Effect sizes, confidence intervals, and meta-

analysis, Understanding the new statistics: Effect sizes, confidence intervals, and meta-analysis.

New York, NY, US: Routledge/Taylor & Francis Group.

De Martino F, Moerel M, Ugurbil K, Goebel R, Yacoub E, Formisano E. 2015. Frequency preference and

attention effects across cortical depths in the human primary auditory cortex. *Proc Natl Acad Sci U*

*S A* **112**:16036–16041. doi:10.1073/pnas.1507552112

Debener S, Ullsperger M, Siegel M, Engel AK. 2006. Single-trial EEG-fMRI reveals the dynamics of

cognitive function. *Trends Cogn Sci* **10**:558–563. doi:10.1016/j.tics.2006.09.010

Desimone R, Albright TD, Gross CG, Bruce C. 1984. Stimulus-selective properties of inferior temporal

neurons in the macaque. *J Neurosci* **4**:2051–2062. doi:10.1523/jneurosci.04-08-02051.1984

Devlin JT, Russell RP, Davis MH, Price CJ, Wilson J, Moss HE, Matthews PM, Tyler LK. 2000. Susceptibility-

induced loss of signal: Comparing PET and fMRI on a semantic task. *Neuroimage* **11**:589–600.

doi:10.1006/nimg.2000.0595

Dobs K, Schultz J, Bülthoff I, Gardner JL. 2018. Task-dependent enhancement of facial expression and

identity      representations      in      human      cortex.      *Neuroimage*      **172**:689–702.

doi:10.1016/j.neuroimage.2018.02.013

Doucet G, Naveau M, Petit L, Zago L, Crivello F, Jobard G, Delcroix N, Mellet E, Tzourio-Mazoyer N,

Mazoyer B, Joliot M. 2012. Patterns of hemodynamic low-frequency oscillations in the brain are

modulated    by    the    nature    of    free    thought    during    rest.    *Neuroimage*    **59**:3194–3200.

doi:10.1016/j.neuroimage.2011.11.059

Druzgal TJ, D'Esposito M. 2003. Dissecting contributions of prefrontal cortex and fusiform face area to

face working memory. *J Cogn Neurosci* **15**:771–784. doi:10.1162/089892903322370708

Druzgal TJ, D'Esposito M. 2001. Activity in fusiform face area modulated as a function of working memory

load. *Cogn Brain Res* **10**:355–364. doi:10.1016/S0926-6410(00)00056-2

Egner T, Hirsch J. 2005. Cognitive control mechanisms resolve conflict through cortical amplification of

task-relevant information. *Nat Neurosci* **8**:1784–1790. doi:10.1038/nn1594

Fan X, Wang F, Shao H, Zhang P, He S. 2020. The bottom-up and top-down processing of faces in the

human occipitotemporal cortex. *Elife* **9**. doi:10.7554/eLife.48764

Felleman DJ, Van Essen DC. 1991. Distributed hierarchical processing in the primate cerebral cortex.

*Cereb Cortex* **1**:1–47. doi:10.1093/cercor/1.1.1

Fisher RA. 1915. Frequency Distribution of the Values of the Correlation Coefficient in Samples from an

Indefinitely Large Population. *Biometrika* **10**:507. doi:10.2307/2331838

Flounders MW, González-García C, Hardstone R, He BJ. 2019. Neural dynamics of visual ambiguity

resolution by perceptual prior. *Elife* **8**. doi:10.7554/eLife.41861

Freeman JB, Rule NO, Adams RB, Ambady N. 2010. The neural basis of categorical face perception:

Graded representations of face gender in fusiform and orbitofrontal cortices. *Cereb Cortex*

**20**:1314–1322. doi:10.1093/cercor/bhp195

Freeman PR, Hedges L V., Olkin I, Freeman PR, Hedges L V., Olkin I, Rosenbaum PR, Hedges L V., Olkin I,

Freeman PR, Hedges L V., Olkin I. 1986. Statistical Methods for Meta-Analysis, Biometrics. Academic

Press. doi:10.2307/2531069

Friston KJ, Preller KH, Mathys C, Cagnan H, Heinzle J, Razi A, Zeidman P. 2019. Dynamic causal modelling

revisited. *Neuroimage* **199**:730–744. doi:10.1016/j.neuroimage.2017.02.045

Frühholz S, Godde B, Lewicki P, Herzmann C, Herrmann M. 2011. Face recognition under ambiguous

visual stimulation: fMRI correlates of "encoding styles." *Hum Brain Mapp* **32**:1750–1761.

doi:10.1002/hbm.21144

Gonzalez-Castillo J, Bandettini PA. 2018. Task-based dynamic functional connectivity: Recent findings

and open questions. *Neuroimage* **180**:526–533. doi:10.1016/j.neuroimage.2017.08.006

Gould RL, Brown RG, Owen AM, Ffytche DH, Howard RJ. 2003. fMRI BOLD response to increasing task

difficulty during successful paired associates learning. *Neuroimage* **20**:1006–1019.

doi:10.1016/S1053-8119(03)00365-3

Gratton C, Laumann TO, Nielsen AN, Greene DJ, Gordon EM, Gilmore AW, Nelson SM, Coalson RS, Snyder

AZ, Schlaggar BL, Dosenbach NUF, Petersen SE. 2018. Functional Brain Networks Are Dominated by

Stable Group and Individual Factors, Not Cognitive or Daily Variation. *Neuron* **98**:439-452.e5.

doi:10.1016/j.neuron.2018.03.035

Grill-Spector K, Weiner KS. 2014. The functional architecture of the ventral temporal cortex and its role

in categorization. *Nat Rev Neurosci* **15**:536–548. doi:10.1038/nrn3747

Hadj-Bouziane F, Bell AH, Knusten TA, Ungerleider LG, Tootell RBH. 2008. Perception of emotional

expressions is independent of face selectivity in monkey inferior temporal cortex. *Proc Natl Acad*

*Sci U S A* **105**:5591–5596. doi:10.1073/pnas.0800489105

Handwerker DA, Ollinger JM, D'Esposito M. 2004. Variation of BOLD hemodynamic responses across

subjects and brain regions and their effects on statistical analyses. *Neuroimage* **21**:1639–1651.

doi:10.1016/j.neuroimage.2003.11.029

Hasson U, Hendler T, Bashat D Ben, Malach R. 2001. Vase or face? A neural correlate of shape-selective

grouping processes in the human brain. *J Cogn Neurosci* **13**:744–753.

doi:10.1162/08989290152541412

Haxby J V., Gobbini MI, Furey ML, Ishai A, Schouten JL, Pietrini P. 2001. Distributed and overlapping

representations of faces and objects in ventral temporal cortex. *Science (80- )* **293**:2425–2430.

doi:10.1126/science.1063736

Haxby J V., Hoffman EA, Gobbini MI. 2000. The distributed human neural system for face perception.

*Trends Cogn Sci* **4**:223–233. doi:10.1016/S1364-6613(00)01482-0

Hedges L V. 1981. Distribution Theory for Glass's Estimator of Effect Size and Related Estimators. *J Educ*

*Stat* **6**:107. doi:10.2307/1164588

Hubel DH, Wiesel TN. 1959. Receptive fields of single neurones in the cat's striate cortex. *J Physiol*

**148**:574–591. doi:10.1113/jphysiol.1959.sp006308

Huber L, Handwerker DA, Jangraw DC, Chen G, Hall A, Stüber C, Gonzalez-Castillo J, Ivanov D, Marrett S,

Guidi M, Goense J, Poser BA, Bandettini PA. 2017. High-Resolution CBV-fMRI Allows Mapping of

Laminar Activity and Connectivity of Cortical Input and Output in Human M1. *Neuron* **96**:1253-

1263.e7. doi:10.1016/j.neuron.2017.11.005

Hutchison RM, Morton JB. 2016. It's a matter of time: Reframing the development of cognitive control

as a modification of the brain's temporal dynamics. *Dev Cogn Neurosci*, Flux Congress 2014 **18**:70–

77. doi:10.1016/j.dcn.2015.08.006

Hutchison RM, Womelsdorf T, Gati JS, Everling S, Menon RS. 2013. Resting-state networks show dynamic

functional connectivity in awake humans and anesthetized macaques. *Hum Brain Mapp* **34**:2154–

2177. doi:10.1002/hbm.22058

Kabbara A, EL Falou W, Khalil M, Wendling F, Hassan M. 2017. The dynamic functional core network of

the human brain at rest. *Sci Rep* **7**:2936. doi:10.1038/s41598-017-03420-6

Kanwisher N, McDermott J, Chun MM. 1997. The fusiform face area: A module in human extrastriate

cortex specialized for face perception. *J Neurosci* **17**:4302–4311. doi:10.1523/jneurosci.17-11-

04302.1997

Kanwisher N, Yovel G. 2006. The fusiform face area: A cortical region specialized for the perception of

faces. *Philos Trans R Soc B Biol Sci* **361**:2109–2128. doi:10.1098/rstb.2006.1934

Kay KN, Yeatman JD. 2017. Bottom-up and top-down computations in word- and face-selective cortex.

*Elife* **6**:e22341. doi:10.7554/eLife.22341

Lakens D. 2013. Calculating and reporting effect sizes to facilitate cumulative science: A practical primer

for t-tests and ANOVAs. *Front Psychol* **4**:863. doi:10.3389/fpsyg.2013.00863

Lamichhane B, Westbrook A, Cole MW, Braver TS. 2020. Exploring brain-behavior relationships in the N-

back task. *Neuroimage* **212**:116683. doi:10.1016/j.neuroimage.2020.116683

Laughlin SB, Sejnowski TJ. 2003. Communication in neuronal networks. *Science (80- )* **301**:1870–1874.

doi:10.1126/science.1089662

Leung AWS, Alain C. 2011. Working memory load modulates the auditory "What" and "Where" neural

networks. *Neuroimage* **55**:1260–1269. doi:10.1016/j.neuroimage.2010.12.055

Lewis LD, Setsompop K, Rosen BR, Polimeni JR. 2018. Stimulus-dependent hemodynamic response

timing across the human subcortical-cortical visual pathway identified through high spatiotemporal

resolution 7T fMRI. *Neuroimage* **181**:279–291. doi:10.1016/j.neuroimage.2018.06.056

Li Q, Hill Z, He BJ. 2014. Spatiotemporal dissociation of brain activity underlying subjective awareness,

objective performance and confidence. *J Neurosci* **34**:4382–4395. doi:10.1523/JNEUROSCI.1820-

13.2014

Li X, Morgan PS, Ashburner J, Smith J, Rorden C. 2016. The first step for neuroimaging data analysis:

DICOM to NIfTI conversion. *J Neurosci Methods* **264**:47–56. doi:10.1016/j.jneumeth.2016.03.001

Liu B, Zhu T, Zhong J. 2015. Comparison of quality control software tools for diffusion tensor imaging.

*Magn Reson Imaging* **33**:276–285. doi:10.1016/j.mri.2014.10.011

Mah L, Arnold MC, Grafman J. 2004. Impairment of social perception associated with lesions of the

prefrontal cortex. *Am J Psychiatry* **161**:1247–1255. doi:10.1176/appi.ajp.161.7.1247

Martin CB, Douglas D, Newsome RN, Man LLY, Barense MD. 2018. Integrative and distinctive coding of

visual and conceptual object features in the ventral visual stream. *Elife* **7**:e31873.

doi:10.7554/eLife.31873

Martinez-Trujillo JC, Treue S. 2004. Feature-based attention increases the selectivity of population

responses in primate visual cortex. *Curr Biol* **14**:744–751. doi:10.1016/j.cub.2004.04.028

McCarthy G, Puce A, Gore JC, Allison T. 1997. Face-specific processing in the human fusiform gyrus. *J

Cogn Neurosci* **9**:605–610. doi:10.1162/jocn.1997.9.5.605

Meng M, Cherian T, Singal G, Sinha P. 2012. Lateralization of face processing in the human brain. *Proc R

Soc B Biol Sci* **279**:2052–2061. doi:10.1098/rspb.2011.1784

Moeller S, Crapse T, Chang L, Tsao DY. 2017. The effect of face patch microstimulation on perception of

faces and objects. *Nat Neurosci* **20**:743–752. doi:10.1038/nn.4527

Moeller S, Freiwald WA, Tsao DY. 2008. Patches with links: A unified system for processing faces in the

macaque temporal lobe. *Science (80- )* **320**:1355–1359. doi:10.1126/science.1157436

MOONEY CM. 1957. Age in the development of closure ability in children. *Can J Psychol* **11**:219–226.

doi:10.1037/h0083717

Narumoto J, Okada T, Sadato N, Fukui K, Yonekura Y. 2001. Attention to emotion modulates fMRI activity

in human right superior temporal sulcus. *Cogn Brain Res* **12**:225–231. doi:10.1016/S0926-

6410(01)00053-2

Nasr S, Tootell RBH. 2012. Role of fusiform and anterior temporal cortical areas in facial recognition.

*Neuroimage* **63**:1743–1753. doi:10.1016/j.neuroimage.2012.08.031

Noonan MP, Kolling N, Walton ME, Rushworth MFS. 2012. Re-evaluating the role of the orbitofrontal

cortex in reward and reinforcement. *Eur J Neurosci* **35**:997–1010. doi:10.1111/j.1460-

9568.2012.08023.x

Parker AJ, Newsome WT. 1998. SENSE AND THE SINGLE NEURON: Probing the Physiology of Perception.

*Annu Rev Neurosci* **21**:227–277. doi:10.1146/annurev.neuro.21.1.227

Perrett DI, Rolls ET, Caan W. 1982. Visual neurones responsive to faces in the monkey temporal cortex.

*Exp Brain Res* **47**:329–342. doi:10.1007/BF00239352

Pessoa L, Gutierrez E, Bandettini P, Ungerleider L. 2002. Neural correlates of visual working memory:

fMRI amplitude predicts task performance. *Neuron* **35**:975–987. doi:10.1016/S0896-

6273(02)00817-6

Posner MI, Petersen SE. 1990. The Attention System of the Human Brain. *Annu Rev Neurosci* **13**:25–42.

doi:10.1146/annurev.ne.13.030190.000325

Price AR, Bonner MF, Peelle JE, Grossman M. 2017. Neural coding of fine-grained object knowledge in

perirhinal cortex. *bioRxiv* **194829**:1–18. doi:doi.org/10.1101/194829

Rajimehr R, Young JC, Tootell RBH. 2009. An anterior temporal face patch in human cortex, predicted by

macaque maps. *Proc Natl Acad Sci U S A* **106**:1995–2000. doi:10.1073/pnas.0807304106

Ramon M, Vizioli L, Liu-Shuang J, Rossion B. 2015. Neural microgenesis of personally familiar face

recognition. *Proc Natl Acad Sci U S A* **112**:E4835–E4844. doi:10.1073/pnas.1414929112

Ress D, Backus BT, Heeger DJ. 2000. Activity in primary visual cortex predicts performance in a visual

detection task. *Nat Neurosci* **3**:940–945. doi:10.1038/78856

Rossion B, Dricot L, Devolder A, Bodart JM, Crommelinck M, De Gelder B, Zoontjes R, Gelder B De,

Zoontjes R. 2000. Hemispheric asymmetries for whole-based and part-based face processing in the

human fusiform gyrus. *J Cogn Neurosci* **12**:793–802. doi:10.1162/089892900562606

Rossion B, Hanseeuw B, Dricot L. 2012. Defining face perception areas in the human brain: A large-scale

factorial fMRI face localizer analysis. *Brain Cogn* **79**:138–157. doi:10.1016/j.bandc.2012.01.001

Sadaghiani S, Hesselmann G, Kleinschmidt A. 2009. Distributed and antagonistic contributions of ongoing

activity fluctuations to auditory stimulus detection. *J Neurosci* **29**:13410–13417.

doi:10.1523/JNEUROSCI.2592-09.2009

Smith SM, Beckmann CF, Andersson J, Auerbach EJ, Bijsterbosch J, Douaud G, Duff E, Feinberg DA,

Griffanti L, Harms MP, Kelly M, Laumann T, Miller KL, Moeller S, Petersen S, Power J, Salimi-

Khorshidi G, Snyder AZ, Vu AT, Woolrich MW, Xu J, Yacoub E, Uğurbil K, Van Essen DC, Glasser MF.

2013. Resting-state fMRI in the Human Connectome Project. *Neuroimage*, Mapping the

Connectome **80**:144–168. doi:10.1016/j.neuroimage.2013.05.039

Stigliani A, Weiner KS, Grill-Spector K. 2015. Temporal processing capacity in high-level visual cortex is

domain specific. *J Neurosci* **35**:12412–12424. doi:10.1523/JNEUROSCI.4822-14.2015

Szczepanski SM, Pinsk MA, Douglas MM, Kastner S, Saalmann YB. 2013. Functional and structural

architecture of the human dorsal frontoparietal attention network. *Proc Natl Acad Sci U S A*

**110**:15806–15811. doi:10.1073/pnas.1313903110

Taylor AJ, Kim JH, Ress D. 2018. Characterization of the hemodynamic response function across the

majority of human cerebral cortex. *Neuroimage* **173**:322–331.

doi:10.1016/j.neuroimage.2018.02.061

Thanh Vu A, Jamison K, Glasser MF, Smith SM, Coalson T, Moeller S, Auerbach EJ, Uğurbil K, Yacoub E.

2017. Tradeoffs in pushing the spatial resolution of fMRI for the 7T Human Connectome Project.

*Neuroimage*, Cleaning up the fMRI time series: Mitigating noise with advanced acquisition and

correction strategies **154**:23–32. doi:10.1016/j.neuroimage.2016.11.049

Tong F, Nakayama K, Vaughan JT, Kanwisher N. 1998. Binocular rivalry and visual awareness in human

extrastriate cortex. *Neuron* **21**:753–759. doi:10.1016/S0896-6273(00)80592-9

Troiani V, Dougherty CC, Michael AM, Olson IR. 2016. Characterization of face-selective patches in

orbitofrontal cortex. *Front Hum Neurosci* **10**:1–14. doi:10.3389/fnhum.2016.00279

Troiani V, Patti MA, Adamson K. 2019. The use of the orbitofrontal H-sulcus as a reference frame for

value signals. *Eur J Neurosci* **n/a**:ejn.14590. doi:10.1111/ejn.14590

Tsao DY, Freiwald WA, Knutsen TA, Mandeville JB, Tootell RBH. 2003. Faces and objects in macaque

cerebral cortex. *Nat Neurosci* **6**:989–995. doi:10.1038/nn1111

Tsao DY, Freiwald WA, Tootell RBH, Livingstone MS. 2006. A cortical region consisting entirely of face-

selective cells. *Science (80- )* **311**:670–674. doi:10.1126/science.1119983

Tsao DY, Moeller S, Freiwald WA. 2008a. Comparing face patch systems in macaques and humans. *Proc*

*Natl Acad Sci U S A* **105**:19514–19519. doi:10.1073/pnas.0809662105

Tsao DY, Schweers N, Moeller S, Freiwald WA. 2008b. Patches of face-selective cortex in the macaque

frontal lobe. *Nat Neurosci* **11**:877–879. doi:10.1038/nn.2158

Tyler LK, Chiu S, Zhuang J, Randall B, Devereux BJ, Wright P, Clarke A, Taylor KI. 2013. Objects and

categories: Feature statistics and object processing in the ventral stream. *J Cogn Neurosci* **25**:1723–

1735. doi:10.1162/jocn_a_00419

van Ede F, de Lange FP, Maris E. 2012. Attentional cues affect accuracy and reaction time via different

cognitive and neural processes. *J Neurosci* **32**:10408–10412. doi:10.1523/JNEUROSCI.1337-12.2012

Vogels R, Orban GA. 1994. Activity of inferior temporal neurons during orientation discrimination with

successively presented gratings. *J Neurophysiol* **71**:1428–1451. doi:10.1152/jn.1994.71.4.1428

Vuilleumier P, Armony JL, Driver J, Dolan RJ. 2001. Effects of attention and emotion on face processing

in the human brain: An event-related fMRI study. *Neuron* **30**:829–841. doi:10.1016/S0896-

6273(01)00328-2

Wang SSH, Shultz JR, Burish MJ, Harrison KH, Hof PR, Towns LC, Wagers MW, Wyatt KD. 2008. Functional

trade-offs in white matter axonal scaling. *J Neurosci* **28**:4047–4056. doi:10.1523/JNEUROSCI.5559-

05.2008

Wilcox R. 2005. Introduction to Robust Estimation and Hypothesis Testing, Technometrics. Academic

Press. doi:10.1198/tech.2005.s334

Willenbockel V, Sadr J, Fiset D, Horne GO, Gosselin F, Tanaka JW. 2010. Controlling low-level image

properties: The SHINE toolbox. *Behav Res Methods* **42**:671–684. doi:10.3758/BRM.42.3.671

Wojciulik E, Kanwisher N, Driver J. 1998. Covert visual attention modulates face-specific activity in the

human fusiform gyrus: fMRI study. *J Neurophysiol* **79**:1574–1578. doi:10.1152/jn.1998.79.3.1574

Zhang H, Japee S, Nolan R, Chu C, Liu N, Ungerleider LG. 2016. Face-selective regions differ in their ability

to classify facial expressions. *Neuroimage* **130**:77–90. doi:10.1016/j.neuroimage.2016.01.045

Zhang RY, Kay K. 2020. Flexible top-down modulation in human ventral temporal cortex. *Neuroimage*

**218**:116964. doi:10.1016/j.neuroimage.2020.116964