Large-scale color biases in the retinotopic functional architecture are region specific and shared across human brains

Michael M. Bannert[1,2,3,4,5] and Andreas Bartels[1,2,3,4,5]

1. Werner Reichardt Centre for Integrative Neuroscience, University of Tübingen,

72076 Tübingen, Germany

2. Max Planck Institute for Intelligent Systems, 72076 Tübingen, Germany

3. Max Planck Institute for Biological Cybernetics, 72076 Tübingen, Germany

4. Bernstein Center for Computational Neuroscience Tübingen, 72076 Tübingen,

Germany

5. Department of Psychology, University of Tübingen, 72076 Tübingen, Germany

Correspondence:

michael.bannert@tuebingen.mpg.de or andreas.bartels@tuebingen.mpg.de

Number of pages   :   75

Number of figures, tables   :   14

Number of words in abstract   :   196

Number of words in introduction   :   663

Number of words in discussion   :   1515

Conflict of interest: The authors declare no competing financial interests.

Acknowledgments: This work was supported by the German Excellence Initiative of

the German Research Foundation (DFG) grant number EXC307, by the Max Planck

Society, Germany, and by DFG grant SFB 1233, Robust Vision: Inference Principles

and Neural Mechanisms, project 9, project number: 276693517.

Abstract

Despite the functional specialization in visual cortex, there is growing evidence that the processing of chromatic and spatial visual features is intertwined. While past studies focused on visual field biases in retina and behaviour, large-scale dependencies between coding of color and retinotopic space are largely unexplored in the cortex. Here we asked whether spatial color biases are shared across different human observers, and whether they are idiosyncratic for distinct areas. We tested this by predicting the color a person was seeing using a linear classifier that has never been trained on chromatic responses from that same brain, solely by taking into account: (1) the chromatic responses in other individuals' brains and (2) commonalities between the spatial coding in brains used for training and the test brain. We were able to predict the color (and luminance) of stimuli seen by an observer based on other subjects' activity patterns in areas V1-V3, hV4 and LO1. In addition, we found that different colors elicited systematic, large-scale retinotopic biases that were idiosyncratic for distinct areas and common across brains. The area-specific spatial color codes and their conservation across individuals suggest functional or evolutionary organization pressures that remain to be elucidated.

Significance statement

Does a color elicit comparable neural activity in two different observers? We addressed these questions, which involved the central test to predict what color someone is seeing based on their brain activity if it is only known how other brains respond to color. We estimated the commonalities across brains in the way they respond to achromatic, spatial stimulation, which allowed us to retinotopically align different brain responses to each other in a common response space. In this space derived without any color responses we could decode across brains what color an observer was seeing and found that spatial color biases differed between areas. Our results demonstrate systematic dependencies between chromatic and visual field representations that are area-specific and preserved across observers.

Introduction

It is known that the primate visual cortex contains multiple representations of the visual field in different functional areas (Felleman & Van Essen, 1991; Sereno et al., 1995; Wandell et al., 2007). This multiplicity has been explained in terms of differences between areas in what cognitive and behavioral purpose their computations fulfill (Goodale & Milner, 1992; Mishkin & Ungerleider, 1982), what perceptual processes they reflect (Gauthier et al., 2000), what content or object properties they encode (Kanwisher et al., 1997; Malach et al., 1995; Tanaka, 1993; Zeki et al., 1991).

While differences between brain areas are widely accepted, within-area variability that can be explained by the underlying cortical retinotopy received less attention (Freeman et al., 2011, 2013; Roth et al., 2018; Sasaki et al., 2006). Since these few studies focused on orientation tuning only, even less is known about color.

Traditionally, human color vision has been thought to be mediated by functionally segregated mechanisms already at earliest processing stages (De Valois & Jacobs, 1968; Derrington et al., 1984; Field & Chichilnisky, 2007; Schiller et al., 1990; Zeki, 1973). Independent processing could explain dissociations in LGN and visual cortex, with a specialization for color processing in the cytochrome-oxidase rich "blob" and "thin stripe" regions in areas V1 and V2, respectively (Denison et al., 2014; Livingstone & Hubel, 1984, 1988; Lu & Roe, 2008; Nasr et al., 2016; Schiller et al., 1990; Ts'o & Gilbert, 1988), and in V4 (Bartels & Zeki, 2000; Beauchamp et al., 1999; Lueck et al., 1989; Zeki, 1978, 1980; Zeki et al., 1991), especially its "globs" (Conway et al., 2007; Conway & Tsao, 2009).

There are a few neuroimaging experiments investigating how color processing in the

cortex differs across the visual field, but unfortunately they have been limited to V1 and

investigated the radial field coordinate only (Mullen et al., 2007; Vanni et al., 2006).

This may surprise considering the inhomogeneities in retinal cone distributions

(Roorda & Williams, 1999) and psychophysical evidence for differences in chromatic

sensitivity as a function of visual space (Danilova & Mollon, 2009; Horiguchi et al.,

2013; Levine & McAnany, 2005; Mullen, 1991; Mullen & Kingdom, 2002).

Computational analysis furthermore suggested that the difference in color statistics

between objects and surrounding background contributes to color tuning in object

recognition regions (Rosenthal et al., 2018). It thus makes sense that objects, which

are typically foveated, might benefit from different chromatic processing than the

peripheral background. Finally, simulations showed that, to explain visual performance

differences across the visual field, retinal factors are insufficient, suggesting cortical

contributions are plausible (Kupers et al., 2019).

Our research aim was to examine functional differences in color processing as a

function of visual space in retinotopic areas. Specifically, we were interested to learn

how consistent such dependencies would be across different brains.

We addressed these questions by aligning subject-specific fMRI response spaces to

each other using shared response modeling. In contrast to previous similar cross-

subject alignment approaches (Guntupalli et al., 2016; Haxby et al., 2011), we used

brain responses evoked by the spatially changing position of slowly moving achromatic

checkerboard stimuli used for retinotopic mapping. Individual brain activity was hence

sampled in response to a highly restricted subset of stimulus inputs comprised of

purely spatial variability in the absence of chromatic stimulation. This ensured that the

stimulus properties that were used for the estimation of shared neural responses were

based solely on spatial information. If neural co-representations of space and color are

indeed shared across observers, it should be possible to predict from an observer's

pattern of brain activity what color the person was seeing using a classifier that was

trained solely on other observers' brain responses to color, i.e., to classify color across

the brains of different participants. Our findings showed this to be true, and further

suggest that the observed between-subject decoding is mediated by common spatio-

chromatic representations that are at least partially embodied by large-scale retinotopic

biases shared between brains yet idiosyncratic for distinct regions in the visual

processing hierarchy.

Materials and Methods

Participants

We analyzed fMRI data from N = 15 (2 male, 13 female) participants aged between 22 and 35 years (mean: 25.5) who took part in a previously published fMRI study about color vision (Bannert & Bartels, 2018). We only selected participants from that study for which the cortical retinotopic representations of the visual field were measured along both the polar and the eccentricity axis of the visual field (see below). All participants had normal or corrected-to-normal visual acuity and were tested for normal color vision using Ishihara color plates (Ishihara, 2011). Each participant gave written informed consent before the first study session. The experiment was approved by the local ethics committee of the Tübingen University Hospital.

Experimental setup

All stimuli were shown to the volunteers while they were lying in the scanner using a projector (NEC PE401H) that was gamma-calibrated with a Photo Research PR-670 spectroradiometer running the Psychtoolbox-3 display calibration script. Experimental stimuli were presented at a resolution of 800×600 pixels and a refresh rate of 60 Hz. The display on the projection screen had a size of 21.8° by 16.2° of visual angle. Stimuli were presented using Psychtoolbox-3 (Kleiner et al., 2007) and MATLAB running on Windows XP.

Color Stimuli

Brain responses obtained from a retinotopic mapping session and a color vision experiment were used for the present analysis. Stimuli of both sessions have been

described in detail before (Bannert & Bartels, 2018), and are again briefly described

below.

In the color vision experiment, we showed stimuli with each belonging to one of three

different color categories: red (mean chromaticities x = 0.39, y = 0.35), green (mean

chromaticities x = 0.34, y = 0.41), yellow (mean chromaticities x = 0.41, y = 0.43). Each

color category was shown at a high or low luminance, resulting in a total of six trial

types. Each stimulus consisted of concentric rings presented against a mid-level gray

background (154 cd/m²). Stimulus intensities were psychophysically matched (see

below) for the high and low luminance conditions, respectively, yielding mean

luminance values (SD in brackets) of 241.7 (19.8) cd/m² and 199.8 (9.0) cd/m² for red,

242.4 (11.4) cd/m² and 190.0 (8.8) cd/m² for green, 230,4 (11.6) cd/m² and 179.6 (9.8)

cd/m² for yellow. Transparency of the stimulus color was sinusoidally modulated as a

function of radial distance from the center (thereby conferring the appearance of

multiple concentric rings). The radius of the largest ring was 8.61° of visual angle and

the cycle size of the modulation was 2.16° of visual angle with its phase changing

continuously at a speed of 2.47°/s in an outward direction. To ensure that the three

colors appeared isoluminant, we used the minimum flicker method (Kaiser, 1991)

inside the scanner prior to data acquisition: a color rectangle of size 3.28° by 2.46° of

visual angle in vertical and horizontal directions from a given color category was shown

foveally to the participant while continuously replacing it every second frame with an

achromatic reference stimulus of a given luminance. By adjusting the luminance of the

color patch by button press in steps of 11 – 12 cd/m², the participant chose the stimulus

intensity that minimized the amount of perceived flicker. Since the three color

conditions were presented in either low or high luminance (151.3 cd/m² or 184.9

cd/m²), each participant individually performed adjustments with reference stimuli at

two different luminance levels. Our color experiment thus had a 3-by-2 factorial design.

Experimental design and task

The observers had to foveate the fixation dot in the middle of the screen while paying

attention to the expanding color rings. Each stimulus was presented for 8.5 s followed

by an inter-trial-interval (ITI) of 1.5 s. There were 36 trials per imaging run for a total of

216 trials presented across the six runs. The trial sequence was pseudo-randomized

across runs to ensure that each of the 6 conditions was preceded equally often by

every condition (Brooks, 2012). The last trial in every run was repeated at the beginning

of the subsequent run to ensure that the trial sequence remained counterbalanced

across all runs. The first trial of each run was excluded from the analysis.

The task was to indicate by button press the occurrence of a brief (0.3 s) luminance

increment or decrement of the color stimulus. Specifically, when presenting a high

luminance color stimulus, the target was the low luminance stimulus and vice versa.

Observers were instructed to respond as quickly and accurately as possible and

received visual feedback about mean reaction time (RT) and errors at the end of each

imaging run.

Retinotopic mapping details

In the retinotopic mapping experiment each participant underwent four runs of polar

angle and two runs of eccentricity mapping following standard protocol (Sereno et al.,

1995; Wandell & Winawer, 2011). In polar runs observers viewed an achromatic

contrast-reversing checkerboard stimulus through a wedge-shaped aperture in a mid-

level gray layer occluding the checkerboard. The wedge had an angle of 45 degrees

and extended to the edge of the display. The aperture slowly rotated in a clockwise

direction in half of the runs or counter-clockwise direction in the remaining half. In the

two eccentricity runs the checkerboard stimulus was viewed through an annulus that

cyclically expanded in one run whereas it contracted in the other. The check sizes in

the polar and eccentricity runs as well as the annulus width increased logarithmically

with radial distance to accommodate cortical magnification. Participants were

instructed to keep their eyes on the fixation cross in the middle of the screen while

paying attention to the wedge or annulus apertures, respectively, and to press a button

each time a red dot briefly appeared randomly anywhere in the visible checkerboard.

Per run, most participants saw 10 cycles of the rotating wedge and expanding or

contracting annulus with each cycle lasting 55.68 s. For subjects 2, 8, and 14, the

stimulus period was 50.46 s and 12 cycles were presented. Subject 1 saw only 9

cycles. To be able to use shared response modeling (see below), we made sure that

the stimulus input was the same for each time point across participants by including

only fMRI measurements for the first 9 cycles and temporally resampling data from

subjects, 2, 8, and 14 to obtain 576 fMRI volumes for each participant. However, we

used each participant's original dataset to define retinotopic regions-of-interest (ROIs)

and determine polar coordinates for each voxel.

fMRI scan details

Imaging was carried out on a Siemens Prisma scanner at 3 T magnetic field strength

using a 64 channel head coil. The 56 slices were positioned, without gaps between

them, approximately parallel to the AC-PC line for whole brain coverage. We employed

a multi-band factor 2 and GRAPPA factor 2 to obtain a four-fold accelerated parallel

imaging sequence. T2*-weighted functional images were recorded at a repetition time

(TR) of 0.87 s and an in-plane matrix resolution of 96×96. Slice thickness and voxel

size were 2 mm isotropic. Echo time (TE) was 30 ms and flip angle was 57°. Anatomical

images were recorded for each participant at a voxel size of 1 mm isotropic using a T1

weighted MP-RAGE ADNI sequence. To correct for magnetic field inhomogeneities,

we measured gradient field maps which were included in the motion correction step of

the fMRI preprocessing pipeline.

fMRI data preprocessing

Data   from   the   main   experiment   were   preprocessed   using   SPM8

(https://www.fil.ion.ucl.ac.uk/spm) running on MATLAB 2014b (The Mathworks, Inc.,

Natick, MA, USA). We excluded the first 11 images of each run to allow the magnetic

field to reach equilibrium. To correct for head motion, each participant's functional

images were realigned to the first recorded image. The gradient field maps were used

to unwarp the image sequence in order to take into account magnetic field distortions.

We corrected for differences in slice acquisition times by shifting the phase of each

frequency in the signal's Fourier representation to the middle of the volume. Every

participant's image sequence was then co-registered to their respective anatomical

scan. Anatomical scans were spatially normalized to MNI space using SPM's

segmentation-based method and the ensuing transformations were also applied to

normalize functional images to MNI space.

The data from the retinotopic mapping experiment were motion-corrected, co-

registered, and slice-time-corrected with SPM8 in the same way as the data from the

main   experiment.   We   used   FreeSurfer's   recon-all   pipeline

(https://surfer.nmr.mgh.harvard.edu) to reconstruct each participant's cortical surface

from their individual anatomical scan (Fischl, 2012). The functional images were then

spatially smoothed on the cortical surface with a 4 mm Gaussian kernel.

Retinotopic ROI definition

We used standard retinotopic procedures to functionally identify visual areas in each

participant separately (Sereno et al., 1995; Wandell & Winawer, 2011). After applying

Fourier-transformation to the time series of each vertex, we plotted the corresponding

phase of each vertex at the frequency of the polar angle mapping stimulus onto the

inflated cortex. The reversals in the angle map indicate the boundaries between visual

areas. In this way, we delineated boundaries for areas V1, V2, V3, hV4, VO1, LO1,

and LO2.

Pattern estimation and preparation

To extract patterns of brain activity we fit each voxel time series with a general linear

model (GLM) in SPM8. The design matrix contained one boxcar regressor for each of

the 216 trials (36 trials per run, six runs in total), a regressor each for the first trials in

every run, which were excluded from the analysis, a constant intercept for each run,

and the six parameters from the motion correction step to model out motion-induced

artifacts in the voxel time series. To account for the hemodynamic lag of the BOLD

response, we shifted each boxcar 5 s forward in time. The beta weights were obtained

using restricted maximum likelihood estimation and were then used to form vectors of

brain responses to their respective color stimulus. Finally, before a sequence of vectors

were entered into pattern classification analyses, each voxel time series within this

sequence was – for each run separately – temporally detrended by removing the fit of

a second-order polynomial (effectively high-pass filtering the data), followed by scaling

to zero mean and unit variance

Pattern classification

Pattern classification was performed in Python 3 using scikit-learn 0.19.1 (Pedregosa

et al., 2012). We used Linear Discriminant Analysis (LDA) to train classifiers based on

a shrinkage estimate of the covariance matrix (Ledoit & Wolf, 2004). In a first step, we

tested how well color (and luminance) information could be decoded from brain signals

when the training and test data came from the same participant. In the second step,

we examined how well color (or luminance) patterns generalized across participants.

We refer to the analyses in the first and second steps as within-subject classification

(WSC) and between-subject classification (BSC), respectively (Haxby et al., 2011).

In WSC analyses, we trained LDA classifiers to predict from vectors of neural

responses from which of the three color categories (or the two luminance conditions in

the luminance classification) they came. We obtained unbiased estimates of

classification performance by cross-validating them following a leave-one-run-out

cross-validation procedure. There were 6 runs with 36 response vectors each. The

classifier was thus trained on 180 vectors (5 times 36) and tested on 36 vectors in

every iteration. Each vector element corresponded to the response estimate of a single

voxel within a given ROI. Individual results were averaged across all participants.

In BSC analyses, however, we were interested to learn how well color (or luminance)

responses generalized across participants. Rather than cross-validating classifiers

across runs (within each participant separately) and then averaging results over

participants we now cross-validated across participants and obtained a single value

for the whole group. Another difference was that vector elements used for classification

came from the *k*-dimensional common space estimated through shared response

modeling (see below) (instead of voxels used in WSC) for each ROI. With 216

response vectors for each of our 15 participants, this leave-one-participant-out cross-

validation approach resulted in classifiers being trained on 3024 (14 times 216)

response vectors and tested on the 216 response vectors of the left-out participant in

every iteration. The *k* vector elements corresponded to the common space dimensions,

i.e. weighted sums of the voxel estimates from individual observers' ROIs. The value

of *k* was determined via grid search on the training set for each ROI (see **Shared**

response modeling). Since shared response modeling implicitly already performs

dimensionality reduction, we did not use any additional feature selection such as

recursive feature elimination.

Since color decoding was a three-way classification whereas luminance decoding was

a two-way classification, classification accuracies were transformed to z-values using

the normal approximation to the binomial distribution:

317
$$z = \frac{n(a - p)}{\sqrt{np(1 - p)}}$$

Equation 1

n is the number of predictions in the classification problem (i.e., Bernoulli trials), *a* is

the fraction of correct predictions, and p is the probability of a correct prediction

expected by chance, i.e. the reciprocal of the number of classes. Intuitively, this

transformation simply expresses the extent to which classification accuracy exceeded

chance, scaled by the standard deviation expected by chance. After z-transformation

chance level for both classification problems was hence zero.

Shared response modeling (SRM)

Our hypothesis was that the purely achromatically defined functional retinotopic

architecture shared across brains also contained color representations that were

equally shared across participants. We therefore used shared response modeling

(SRM) (Anderson et al., 2016; Chen et al., 2015; Cohen et al., 2017) to identify the

shared functional architecture from responses to the achromatic retinotopic mapping

stimulus. For all our SRM analyses we used the implementation that is part of the Brain

Imaging Analysis Kit, https://brainiak.org (version 0.7.1). An important advantage of

SRM over a related method called hyperalignment (Guntupalli et al., 2016; Haxby et

al., 2011) is that it allows for different dimensionalities of individual data matrices (i.e.,

number of voxels per ROI). This is because SRM estimates linear mappings between

X_i and S whereas hyperalignment uses Procrustes transformation to align

representational spaces by rotating and scaling vectors between voxel spaces of the

same dimensionality. For intelligibility of this manuscript, in the following we briefly

describe the mathematical concept of the SRM implementation used.

Let X_i be a v-by-d matrix of fMRI responses ($X_i \in \mathbb{R}^{v \times d}$) measured for participant i

with v denoting the number of voxels (e.g., within a ROI) and d the number of

measurements (in our case number of volumes recorded in the retinotopic mapping

experiment). In SRM each participant's response matrix X_i is then modeled as a linear

transformation of a common response ($S \in \mathbb{R}^{k \times d}$) that is shared by all participants:

$$X_i = W_i S + E_i$$

Equation 2

k is the number of components in the shared common space. $W_i \in \mathbb{R}^{v \times k}$ is the

transformation matrix that describes the relationship between the shared responses in

the common space S and each individual's original response space with matrix $E_i \in$

$\mathbb{R}^{v \times d}$ modeling the error between fitted and observed individual data.

SRM estimates the common space matrix S and individual transformation matrices W_1,

$W_2,...\ ,\ W_i,...\ ,\ W_m$ for each of the m participants such that they minimize the

Frobenius norm $\|\cdot\|_F$ of each error matrix E_i summed over all participants:

357
$$\min_{W_i,S} \sum_{i=1}^{m} \|X_i - W_i S\|_F^2$$

358
$$s.t.\ \ W_i{}^T W_i = I_k$$

Equation 3

This optimization is performed subject to an orthonormality constraint on each

transformation matrix W_i. The estimated solutions for W_i are therefore similar in

interpretation to orthogonality in PCA. Importantly, we can use W_i to map patterns of

fMRI responses between individual spaces and the common space.

We fit SRMs to data from the retinotopic mapping experiment (Figure 1). This yielded

one transformation matrix W_i per participant and ROI describing the linear mappings

between each individual dataset and the common space of shared responses to purely

achromatic, spatially defined stimulation. Let $D_i \in \mathbb{R}^{v \times 216}$ be the matrix of v-

dimensional patterns of responses to the color and luminance stimuli from the main

experiment. The transformation matrices $W_i \in \mathbb{R}^{v \times k}$ for participant i can then be used

to map the individual color responses to the k-dimensional common space as $W_i{}^T D_i$.

We repeatedly trained LDA classifiers to distinguish between color (or luminance)

categories leaving out one participant's transformed dataset each time for

generalization and then averaging generalization scores across iterations. We

obtained confidence intervals for the averaged values from the permuted null

distributions (see **Statistical inference** below). The number of common space

dimensions k for each ROI was chosen by grid-searching a range of 9 candidate values

that were evenly spaced on a base-10 logscale from $10^0 = 1$ to $10^2 = 100$ (rounded).

Values above 100 dimensions resulted in prohibitively slow model fitting. During cross-

validation, each candidate value was applied exclusively to the training set of each

iteration and the value resulting in optimal prediction accuracy was used for the final

prediction of the withheld test set. The choice of k was thus independent from the test

set.

Within-subject preference maps: color & luminance

Since we observed significant classification accuracy of both color and luminance

across different brains, we were interested to see whether these representational

biases for color and for luminance would be readily visible on the cortical surface of

individual brains. This would allow a direct comparison with retinotopic layout of

individual visual areas at a single-subject level. If, for instance, there is a preference

for a given stimulus class near the visual field meridian, one would expect stronger

responses to that class near the visual area boundaries.

We hence estimated the responses to each stimulus class for color and luminance

using two separate GLMs in SPM. The time series were modeled in each brain's

individual anatomical space using one predictor for every class and using the same

boxcar regressors shifted by 5 s in time (see also **Pattern estimation and**

preparation). The resulting maps of stimulus class responses were mapped to the

vertices of the individual cortical surface space using FreeSurfer's estimated

registration mapping. For every vertex with a positive (i.e., above-mean) response to

any of the stimulus classes, we determined which class was associated with its

strongest response. The results were plotted in FreeSurfer's inflated surface

reconstructions with every vertex colored according to the stimulus class with the

strongest response.

Dependence of between-subject classification on number of shared features

The number of shared features assumed in fitting the SRM determines the dimensionality of common space representations. Note that, in the main analysis (see **Shared response modeling**) the value for this parameter was chosen by grid search using only the training data to learn the optimal value in an unbiased fashion. The BSC analysis was repeated with values for the number of shared features that ranged from 1 to 100 to understand how this affects classification accuracy and how much variance the shared features explain in the data. For each parameter value, we calculated the variance of every voxel time series in the original datasets from the retinotopic mapping session and the main experiment and summed them over voxels and brains. After mapping each participant's responses from the common space back into original space (using the estimated transformation matrix), the same calculation was conducted on the resulting datasets thereby representing how much variance was explained by the model. Explained variance was quantified as the percentage of this variance relative to the variance computed using the original data. Classification accuracy was calculated as detailed in the paragraph describing the BSC analysis. The 95 % confidence bands are determined as Jeffreys intervals.

Dependence of BSC accuracy on number of voxels

Classification accuracies may differ between visual areas because they are different in size and hence contain different numbers of voxels. In order to check to what extent classification accuracies are robust against these differences, we repeated the BSC analysis using the same number of voxels across visual areas. This meant that the number of voxels had to be reduced because the smaller areas impose an upper limit on the maximum number of voxels that can be used for classification. To decide which

voxels to select, all voxels were ranked per ROI based on their signal strength in the

Fourier analysis of the retinotopic mapping data. The F-value of the test comparing

voxel amplitude at the frequency of stimulus presentation to the remaining amplitudes

was used as an index for the visual sensitivity of a voxel. All voxels were ranked in a

descending order and the top 50, 100, …, 500 voxels (i.e, in steps of 50) were selected.

Note that, for any visual area, the smallest ROI across observers limited the largest

number of voxels that could be selected from each participant. Thus only areas V1,

V2, V3 contained 500 voxels in every participant for example. The number of multiple

comparisons that needed to be corrected for accordingly was sometimes lower than in

the original BSC procedure. Otherwise it was identical to the main BSC analysis

described above.

SRM searchlight analysis

In addition to ROI analyses, we also applied SRM in a whole-brain analysis to local

patterns at every location in the brain normalized to MNI standard space. The purpose

of this analysis was to test how specific the shared commonalities were to the exact

individual locations of visual areas compared to anatomically aligned patterns of brain

responses. Please note that anatomical alignment here refers to the alignment of

response patterns which are then subjected to SRM. We do not assume that

anatomically aligned voxels already exhibit similar stimulus tunings. Rather, we were

interested in determining the difference between modeling shared responses between

retinotopically versus anatomically aligned patterns of brain activity.

We used SRM in combination with a searchlight technique that analyzed only local

patterns of brain activity within a radius of 3 voxels (``searchlight sphere'') at every

location in the whole brain (Kriegeskorte et al., 2006). The number of SRM components

k was 50 in every searchlight sphere or, if the total number of voxels within the sphere

was smaller (e.g. near edges in the brain mask), the number of available voxels. LDA

was then used in the same manner as in the BSC ROI analyses to calculate an

unbiased estimate of classification performance for every location in the brain, which

was then assigned to the center voxel of the sphere. The resulting brain map was then

spatially smoothed with a Gaussian kernel of size 6 mm FWHM.

Voxel preference prediction across subjects

Here we ask the following question: can we predict color (or luminance) preferences

of single voxels of an individual observer based only on the responses to those colors

in the remaining brains?

Note that the BSC described above similarly made predictions, but for voxel-response

patterns – in contrast, here we aim to predict preferences for individual voxels.

This analysis extends previous research showing that the location of category-

selective visual regions FFA and PPA could be predicted across brains using a

common model space (Haxby et al., 2011) in that it examines the generalizability for

more fine-grained visual information than basic level concept distinctions (houses vs.

faces).

We pursued this voxel prediction using two approaches:

Voxel preference prediction: based on SRM
As in the BSC analysis, SRMs were fit to the retinotopic mapping data of the whole

group of brains. The goal is to predict, for each brain's ROI, the stimulus preferences

for all individual voxels in a leave-one-brain-out cross-validation procedure. To this

end, the individual mean patterns of responses to every stimulus class from all training

brains were mapped into the common space using the individual transformation

matrices from the SRM. The transformed patterns were then averaged per stimulus

class yielding one group average vector per class. The vector dimensionality depended

on the optimal number of shared features as determined by grid-search (see **Shared**

response modeling). The group averages were transformed into the individual voxel

space of the left-out test brain. The predicted stimulus preference for a voxel was the

stimulus class with the largest predicted value, which could then be compared to its

true preference based on the main experiment data from that brain, which was used

at no point in the prediction pipeline. We refer to this approach as "SRM uni" because

it regards preference in terms of which stimulus class causes the maximum univariate

response in each voxel. In a variation of this approach referred to as "SRM multi", we

repeated this procedure except that instead of transforming mean vectors of responses

to each category, we used the classification weights for each stimulus class estimated

using shrinkage LDA. This tested for the possibility that classification-based response

patterns may generalize better across brains. Note that also this SRM multi approach

predicted preferences for individual voxels.

Voxel preference prediction: based on cartesian visual field coordinates

In addition to the above SRM-based approach, we wanted to examine how well a more

traditional across-subject voxel-preference prediction approach would fare, and

compare this with the above SRM approach. We used phase maps from the polar

angle mapping experiment in combination with the phase maps from the eccentricity

mapping experiment to obtain the preferred visual field location of every voxel, which

we converted to a Cartesian coordinate system with its origin centered on the fovea. A

leave-one-brain-out cross-validation procedure was then employed in which all voxels

in a given ROI from all but the test brain were assigned a target label based on which

stimulus category (e.g., green, red, or yellow) elicited the strongest activation (GLM

analysis as described in **Preference maps: color & luminance**). In every cross-

validation iteration we fit a k nearest-neighbor classifier to the training data, which

consisted of as many samples as there were voxels in the ROIs summed over training

brains. Each sample consisted of that voxel's Cartesian x, y visual field coordinates

and its target label, which color it preferred. The parameter k ranged from 1, 2, …, 9

and was optimized via grid-search using a random split-half cross-validation approach

on all training voxels. Nine candidates were considered because there were also nine

candidate values for the number of SRM features. The resulting model was cross-

validated on the voxels of the left-out test brain by comparing its coordinate-based

predicted stimulus preference with its true stimulus preference. Figure 8 shows an

illustration of the methods.

Prediction accuracy was quantified using a balanced score metric because the

preference for a given color in a ROI's voxels could not be assumed to be balanced

across classes (see `balanced_accuracy_score` in scikit-learn). We tested which

of the methods, nearest-neighbor classification without SRM or SRMs using univariate

mean responses or classification weights, would do a better job at generalizing across

brains (see **Statistical inference** for details).

Voxel preference: visualization
Finally, we visualized the dependence of stimulus preference and retinotopic location.

The voxel preference predictions from each cross-validation fold were subjected to

Gaussian kernel density estimation (KDE, using Scott's rule to choose bandwidth) to

obtain a 2-dimensional density function per stimulus class expressing preference for

that class for any visual field location. To obtain a probabilistic interpretation of stimulus

preference at any location, we applied a softmax function to the values of each function

per stimulus class. This resulted in a probability distribution for every location over the

stimulus categories describing how likely it was that a voxel in that location would prefer

a given stimulus. We subtracted from each value the probability that a given stimulus

class would be preferred under the assumption of a uniform probability distribution,

i.e., 1/3 and ½ everywhere for color and luminance, respectively. After converting the

probability differences to percentages, a value of x therefore means that the probability

of a given class being preferred at this location is increased by x % points. Note that

the preference maps are based on predictions that are cross-validated across brains.

The prediction of voxel preferences in a given brain therefore requires that any spatial

biases in color or luminance processing are reliable across brains used for fitting the

model and the brain used for model testing. As an additional check, we performed an

odd-even split on the sample of participants and created the same maps based on

independent subsets of data to assess split-half reliability. The visualization was

performed for the SRM-uni based approach as this obtained the highest scores across

ROIs.

ROI-specificity of SRMs for voxel preference prediction

Since SRMs trained on retinotopic mapping data could successfully be used to predict

stimulus preference across different brains, this indicated that they captured to some

extent the relationship between retinotopy and color/luminance representation. How

specific are these relationships to individual visual areas? Do SRMs trained on different

visual areas capture these relationships differently?

To answer these questions, we repeated the voxel preference prediction analysis

detailed above using the SRM approach based on the mean patterns of univariate

responses to each category. This time, however, we used SRMs that were fit either on

data from the same or different ROIs. More precisely, the transformation matrices used

to, on the one hand, map individual patterns from individual spaces into the common

space, and, on the other hand, to predict stimulus preference in the space of the left-

out test brain were based on SRMs fit on data from either the same or different ROIs.

All combinations of ROIs were examined for the transformation of the training and test

brains and the classification accuracy between congruent (SRMs fit on the same ROI)

and incongruent (SRMs fit on different ROIs) were compared. For the incongruent

condition, the accuracies were averaged across all combinations where SRMs came

from different ROIs. It was tested if the resulting accuracies were significantly larger

than chance and if they differed between congruency conditions.

Statistical inference

Within-subject and between-subject classification

All our statistical decisions were based on permutation tests. For WSC we tested the

one-tailed null hypothesis that the sample average across all participants' classification

accuracies was equal to or below chance. Since there were three classes in the color

classification problem, chance level was $1/3$. Likewise, chance level in the luminance

classification was $1/2$ as there were two luminance levels.

We created 2000 new label assignments in the following way: For every participant the

sequence of training labels was shuffled with the restrictions that labels were only

permuted within cross-validation folds, i.e., functional runs, and that permutations were

identical across ROIs. Both restrictions were implemented by setting the `groups` and

`random_state` arguments in scikit-learn's `permutation_test_score` accordingly.

A group average of classification accuracies was calculated for each ROI and iteration.

This way we obtained a null distribution of average classification accuracies expected

under the hypothesis that there was no relationship between labels and neural activity

patterns.

It was important that permutations were identical across ROIs because they

constituted the test family for which we controlled the family wise error (FWE). We

formed a new null distribution for all ROIs by taking the maximum of group average

classification accuracies across ROIs in every iteration (Nichols & Holmes, 2002). P

values were computed as the fraction of permutations that resulted in accuracies that

were larger than or equal to the observed classification accuracy. We declared results

significant if p was below .05, thereby keeping the type I error probability of falsely

rejecting at least one null hypothesis at α = 0.05. For each ROI, the lower and upper

limits of the 95 % confidence interval (CI) were calculated parametrically using the

standard error of the mean. In the BSC analysis, upper CI limits were obtained by

adding the difference between the mean of the (uncorrected) null distribution and its

2.5th percentile to the observed accuracy. Lower CI limits were obtained by subtracting

the difference between the 97.5th percentile and the mean from the observed

accuracy.

The permutation test for BSC was identical to that for WSC. However, since data from

all participants were now combined in the *k*-dimensional functional common space,

classifiers were now cross-validated leaving out one participant at a time. Again, labels

were permuted only within cross-validation folds, which in this analysis were individual

participants.

Voxel preference prediction & ROI-specificity analysis

We tested how well different analytical procedures could predict the preference of

voxels for different stimulus classes and whether there was a difference in prediction

accuracy depending on whether the SRMs used for the training and test brains came

from the same or different ROIs (congruent vs. incongruent). In both analyses, it was

first tested for each ROI and analysis method whether classification accuracy was

significantly larger than chance (1 divided by number of classes) using binomial tests.

For pairwise comparisons between analysis methods, we used independent z-tests

(Python module statsmodels 0.11.0). The resulting p values for each comparison

(against chance and pairwise) were corrected for multiple comparisons across 7 ROIs

using Holm-Šidák correction.

Retinotopic weight analysis

In this analysis we tested for each ROI whether we could predict from the Cartesian

visual field coordinates which color (or luminance level) was preferred by a voxel using

a nearest neighbor classifier. Voxel labels were permuted 1000 times, separately

within cross-validation folds (participants), and p values were obtained from the null

distribution of each ROI. CIs were calculated in the same way as for BSC results. Since

there was no correspondence between voxels from different ROIs, we could not control

the FWE using the same max statistic approach as in the previous ROI analyses and

therefore used Holm-Šidák correction instead to keep α at .05. In order to make sure

that the prediction of the highest classification weight was not merely driven by specific

pairs of the three colors, we furthermore repeated the same analysis for each pair

separately.

SRM searchlight analysis

The searchlight analysis yielded a brain map of cross-validated estimates of

classification accuracies. In order to test if classification accuracies were significantly

larger than what would be expected by chance, we used a one-tailed binomial test

instead of a t-test because the classification accuracies from each leave-one-

participant-out cross-validation were not independent. The number of correctly

classified trials were assumed to come from a sequence of 216 × 15 = 3240 Bernoulli

trials with success probability equal to one divided by the number of classes. We

applied multiple comparisons correction to the resulting map of p values by keeping

the false discovery rate at q = .05 (Benjamini & Hochberg, 1995).

Behavioral control analysis

Our classification analysis of neural representations of color assumes that the fMRI

data were collected under conditions that differed in color (or luminance) exclusively.

In order to rule out the possibility that neural differences were related to differences in

task performance between conditions, we therefore conducted a two-way repeated-

measures ANOVA of the observers' reaction times (RT) in the target detection task

under the three color and two luminance fixed-effect conditions (3-by-2 design)

specifying subject as random factor. A major disadvantage of classical ANOVA is that

it only considers empirical evidence *against* the null hypothesis (i.e. indicating that

"RTs are different across conditions") but not against the alternative hypothesis (i.e.

indicating that "RTs do not differ across conditions"). Bayesian statistics, however,

simultaneously take into account evidence in support of the null *and* alternative

hypothesis in a balanced way. Hence we used Bayesian ANOVA (Morey & Rouder,

2018; Rouder et al., 2017) where Bayes factors (BF) quantify the compatibility of the

observed data with the alternative hypothesis relative to the null. Specifically, each

effect was tested by computing the BF ratio of the globally best fitting model with the

best model lacking the effect in question (Rouder et al., 2017). If the globally best

model did not include a given effect, the ratio was taken with respect to the best model

that did include the effect in question (resulting in BFs favoring the null). As an

example, a BF of 3 means that the data are three times more likely to have occurred

under the alternative hypothesis than the null. Fixed-effect priors were specified for

"medium" sizes by applying the default r scale of .5. Normality assumptions were

checked with Shapiro-Wilk's tests and by visual inspection of Q-Q plots of the residuals

(not shown). Sphericity was tested using Mauchly's test.

Retinotopic binning analysis

The present paper shows results from a novel analysis testing for a dependency

between retinotopic properties of fMRI voxels and their selectivity for different colors.

By identifying the shared responses to visual stimulation by both color and purely

retinotopically defined input, it allowed us to visualize this dependency by mapping the

classification weights of the shared responses to visual field maps.

Given its novelty, we assured ourselves of the validity of our conclusions from our

analysis by complementing it with a more conventional procedure that had been

applied previously to test for retinotopic biases (Beckett et al., 2012; Freeman et al.,

2011; Larsson et al., 2017) and for which our conclusions – if true – make testable

predictions as well. In this procedure WSC of color is conducted as follows: all voxels

in a given ROI are binned into a certain number of bins and the voxel responses to the

colors are averaged per bin. The dimensionality of each response pattern in a ROI

containing v voxels binned into b bins is thus reduced from v to b. Now, to test for a

retinotopic bias in this scenario, binning is carried out in two different ways. In one

analysis, the phase in which voxels respond to the retinotopic mapping stimulus (polar

angle or eccentricity) and which ranges from 0 to 2π is used to assign voxels into bins

consisting only of voxels with similar phases. This preserves some aspect of the

retinotopic structure in the data. In the control analysis, voxels are binned randomly. If

classification is mediated at least in part by retinotopic bias, one would expect that

retinotopy preserving binning yields higher classification accuracy than random

binning.

The two analyses are conducted for several values of b chosen from a base-10

logarithmic scale ranging from 0 to 3 in steps of .2: $b \in [10^0, 10^{.2}, ..., 10^b, ..., 10^3]$. The

analysis was carried out separately for every participant and ROI. If b exceeded the

number of voxels in any of the participants in a given ROI, this binning step was

skipped. We statistically compared retinotopic and random binning with paired t-tests

corrected per ROI for multiple comparisons across 15 binning steps (or fewer, see

above) using the Holm-Šidák procedure.

700
701

Results

The goals of the experiment were to examine whether representations of chromatic signals were shared with a spatial neural code, whether spatial color specificity was shared across human brains, and whether this was area specific. For this reason, we used brain responses to achromatic, spatial stimuli to construct a neural space that was shared between observers (Figure 1). We then tested whether this neural space generalized to decode color responses in specific, individual brains from color responses in other observers' brains -- in other words -- to predict color across brains. We then tested whether an area-agnostic common space across participants allows predicting colors only within a given area or across areas.

Within-subject classification of color and luminance (WSC)

Decoding color across different brains requires that color can be decoded within one and the same individual brain. For this reason, we first performed pattern classification analyses on fMRI activity from ROIs at the level of individual subjects. The same logic applied to luminance decoding. Figure 2 shows classification accuracies z-transformed ($n = 216$) individually and then averaged across participants ($n = 15$). Color as well as luminance could be decoded significantly better than chance in all ROIs under investigation (permutation tests, each $p < .01$, FWE-corrected for seven ROIs). For color (chance level: 33 %), the following classification accuracies applied for each ROI, averaged across participants. V1: 57 % ($z = 7.38$, 95 % CI [6.51, 8.25]), V2: 55.4 % ($z = 6.89$, 95 % CI [5.94, 7.84]), V3: 52.84 % ($z = 6.08$, 95 % CI [5.13, 7.03]), hV4: 51.2 % ($z = 5.56$, 95 % CI [4.21, 6.91]), VO1: 46.3 % ($z = 4.03$, 95 % CI [3.01, 5.05]), LO1: 44.8 % ($z = 3.56$, 95 % CI [2.66, 4.46]), LO2: 42.5 % ($z = 2.86$, 95 % CI [1.72, 4]). For luminance (chance level: 50 %), classification accuracies were as follows. V1: 61.9 %

(z = 3.51, 95 % CI [2.32, 4.7]), V2: 65 % (z = 4.41, 95 % CI [2.81, 6.01]), V3: 66.7 %

(z = 4.92, 95 % CI [3.45, 6.38]), hV4: 59.1 % (z = 2.67, 95 % CI [1.84, 3.5]), VO1: 56.7

% (z = 1.98, 95 % CI [1.16, 2.8]), LO1: 63.5 % (z = 3.96, 95 % CI [2.71, 5.22]), LO2:

59.9 % (z = 2.9, 95 % CI [1.69, 4.11]). Individual response patterns in every ROI thus

were reliable enough across fMRI runs to linearly predict color and luminance

condition.

Between-subject classification of color and luminance (BSC)

Next, we quantified how consistent chromatic neural processing was across individual

brains within a neural space that was shared across subjects and defined by responses

elicited by a solely achromatic and spatially defined retinotopic mapping stimulus.

Individual color responses were mapped from independent measurements to that

shared response space, and the classifiers were trained to predict the color (or

luminance) of the stimulus a person was seeing. In contrast to WSC, fitted

classification models were cross-validated across participants instead of runs. As can

be seen in Figure 3, accuracies for luminance and color classification across different

brains significantly exceeded chance in areas V1-V3. Additionally, color could be

decoded across participants significantly better than chance in areas hV4 and LO1

(permutation tests, p < .01, FWE-corrected for seven ROIs). For each ROI, significant

BSC accuracies for color were as follows. V1: 44.7 % (z = 13.7, 95 % CI [8.23, 19.0]),

V2: 39.8 % (z = 7.75, 95 % CI [4.23, 11.09]), V3: 39.6 % (z = 7.57, 95 % CI [4.11,

10.75]), hV4: 39.5 % (z = 7.42, 95 % CI [3.27, 11.47]), LO1: 38.8 % (z = 6.6, 95 % CI

[2.1, 10.9]). Accuracy in VO1 was 34.0 % (z = 0.78, 95 % CI [-2.11, 3.6], p = .873, FWE

corrected) and thus not significant. In LO2 accuracy was 36.0 % but did not survive

FWE correction (p = .021, uncorrected): z = 3.17, 95 % CI [.14, 6.14], p = .285, FWE

corrected. For luminance, significant classification accuracies were as follows. V1: 56.2

% (z = 7.03, 95 % CI [2.9, 11.36]), V2: 56.4 % (z = 7.24, 95 % CI [4.23, 11.09]), V3:

55.2 % (z = 5.94, 95 % CI [22.22, 9.46]). This suggests that measurements of how

purely spatially defined stimulation activates the brains of different individuals is

sufficient to predict colors and luminance from brain activity in any one of them using

a classifier trained on data from the remaining participants.

Individual preference maps: color and luminance

To check for the possibility that any retinotopic biases might be readily visible from the

inspection of the response maps on the cortical surface reconstructions, we

transformed the mean responses to every stimulus class to surface space and

determined which of them caused the strongest response at each cortical location.

Figure 4 shows the results of this analysis for the classification of color. At the individual

level, no systematic relationship between cortical location and color that is consistent

across brains is apparent from the maps. Figure 5 shows the same maps for the

classification of luminance. Preference for high intensity luminance is shown in yellow,

preference for low intensity luminance is shown in blue. Likewise, no consistent

relationship between preference and location can be observed. The dependence of

color representation upon cortical location thus appears to be too subtle to be apparent

by visual inspection from individual brains.

Dependence of between-subject classification on number of shared features

Shared response modeling requires a parameter that controls the dimensionality of the

shared common space. To understand how much variance needs to be explained by

the model to enable above-chance BSC accuracy, we repeated the analysis using

different numbers of shared components between 1 and 100. Figure 6 shows results

for the classification of color (top panel) and luminance (bottom panel). The blue curves

show how much variance is explained by the SRM components as a function of number

of features, for retinotopic mapping data (solid lines) and for data of the main

experiment (dashed lines). The former are generally higher than the latter because the

model features are determined based on the retinotopic mapping data. More

components naturally explain more variance in the training set. This also applies to the

data from the main experiment, which were not used to fit the components.

Classification accuracies (orange lines) increase with the number of shared features

but plateau or decrease slightly from typically between 10 to 20 features onwards. The

peak of classification (orange) hence occurs approximately where 15 to 30 % variance

are explained in the training data (blue curve). This is also where a weakly pronounced

"elbow" in the blue curves is visible. The results indicate that using more features does

not necessarily lead to better classification accuracy and that accuracy peaks are

typically found with low numbers of features that explain between 15 and 30 % of the

variance in the training set. The dependence of classification accuracy on the number

of features emphasizes the need for an unbiased selection procedure of this parameter

like the one we used in the main analysis.

Dependence of BSC accuracy on number of voxels

We examined to which extent the results from the BSC analysis were robust against

changes in the number of voxels used for classification. That way the number of voxels

could be held equal across ROIs, which otherwise typically differ due to differences in

size between visual areas. Figure 7 shows the results for BSC of color (top) and

luminance (bottom). Descriptively, classification accuracies tend to be lower compared

to the results from the original BSC analysis (Figure 3), as can be expected given the

lower number of voxels. Classification accuracy in V1 is fairly robust in that it is

significantly larger than chance across all numbers of voxels tested. In the majority of

selection steps classification accuracy was likewise significantly larger than chance in

hV4 (4 out of 7) and LO1 (6 out of 7). Classification accuracy was more dependent on

the number of voxels in V2 and V3. It exceeded chance level at a more lenient

uncorrected significance threshold (V2: 6 out of 10; and V3: 5 out of 10). Accuracy was

not above chance at any selection step in VO1 and in LO2 only at one step

(uncorrected). BSC accuracy was thus largely robust across selection levels in V1,

hV4, and LO1. In V2 and V3 above-chance classification was also possible with fewer

voxels but it was more contingent on the number of voxels used for the analysis.

As for luminance, classification accuracy in V1 similarly exceeds chance significantly

at 9 out of 10 selection steps. In V2 it is significantly above chance in 6 out of 10. V3

showed less robustness with accuracy surpassing a more lenient uncorrected

significance threshold at 5 out of 10 steps. In hV4 significant classification was

observed at 3 out of 7 and in LO2 at 1 out of 9 voxel selection steps (uncorrected).

Decoding thus was robust across selection steps in V1 and V2, whereas V3 decoding

required larger numbers of voxels.

Voxel preference prediction: large-scale retinotopic color biases.

Since our BSC results were based on shared responses to retinotopic mapping

experiments, we were interested in a closer examination of any large-scale retinotopic

biases mediating across-subject color decoding. We therefore tested how accurately

we could predict to which color (or to which luminance level) each voxel in every ROI

of a given test brain would respond most strongly, i.e., which it would prefer.

Importantly, this prediction would be based only on the retinotopic mapping data and

on color/luminance data from brains that were independent from the test brain. We

compared different methods, which are illustrated in Figure 8 A and B. The first relied

on SRMs, the second on traditional cartesian retinotopic projections combined with

kNN classification.

As Figure 9 (left) shows, **color preference** could be predicted significantly better than

chance using several of the approaches tested. Importantly this means that individual

areas do indeed have large scale, retinotopically mapped color biases, and that these

can robustly be revealed using distinct approaches. In more detail, we found that the

number of ROIs where accuracy was significantly above chance was largest for the

SRM-uni approach (5 out of 7) compared to "SRM multi" (2 out of 7) and the nearest

neighbor approach (3 out of 7). The five ROIs significant in SRM-uni were the same

as those where significant classification of color across brains (BSC) was observed (all

$p < .01$): V1 (38.4 %, 95 % CI [37.8 %, 39 %]), V2 (36 %, 95 % CI [35.4 %, 36.6 %]),

V3 (36.9 %, 95 % CI [36.2 %, 37.5 %]), hV4 (35.3 %, 95 % CI [34.4 %, 36.2 %]), and

LO1 (37.7 %, 95 % CI [36.7 %, 38.7 %]). There was no ROI where the "SRM uni"

accuracy was significantly surpassed by either SRM-multi or the nearest neighbor

approach. In contrast, "SRM uni" accuracy was significantly larger than the two other

methods in LO1 (nearest neighbor: $p < .05$, SRM-multi: $p < .01$), V3 (both $p < .01$). In

V1 it exceeded that of SRM-multi (nearest neighbor: $p = .2392$, SRM-multi: $p < .01$)

and in V2 that of the nearest neighbor approach (nearest neighbor: $p < .01$, SRM-multi:

$p = .249$). In hV4 SRM-uni was the only method to show accuracy that was significantly

above chance ($p < .01$, nearest neighbor: $p = .3383$, SRM-multi: $p = .2407$). In sum,

while color preference could be predicted using different methods, the SRM approach

based on mass univariate patterns of color responses yielded the highest

generalization accuracy across brains.

As for **luminance classification** (Figure 9, right), both SRM-uni and nearest neighbor

approaches yielded accuracies that were significantly above chance in the same four

ROIs, V1, V2, hV4, LO1 (all p < .01). SRM-multi accuracies were significantly better

than chance only in V1, V2, and V3 (all p < .01). However, SRM-uni outperformed both

other approaches in V1 and V2 and SRM-multi in LO1 but neither of them in hV4. Only

in V3 SRM-multi was the only method with above-chance classification accuracy,

which exceeded those of the remaining approaches. Although there was good

agreement between all methods in V1 and V2, only SRM-multi showed preference

prediction in V3 whereas the other two methods instead showed significant accuracies

in hV4 and LO1. With the exception of V3, SRM-uni, however, showed the highest

accuracies at generalizing luminance preference across brains.

Since across-subject commonalities in retinotopic voxel preferences were detected

most robustly with SRM-uni, we proceeded with this method to map stimulus

preference across the visual field.

Stimulus preference across the visual field

Given the above statistical evidence for large scale, retinotopically mapped color

biases in individual visual areas, we aimed to visualize them as illustrated in figure 8C.

We visualized the predictions that the SRMs made for individual voxels at different

locations across the visual field by applying KDE on the cross-validated predictions

made for each brain (see Methods: Voxel preference prediction across subjects) and

converting them to probabilities using a softmax operation.

Color preference maps can be seen in Figure 10. The maps in the large polar plots are

based on the whole sample of brains. Note that these maps are based on models that

were fit to and evaluated on independent datasets and that successful prediction of

voxel preferences presupposes that regional biases are reliable across datasets. The

small plots serve as an additional assessment of reliability. They are based only on

data from the two halves of the sample after an odd-even split and therefore visualize

split-half reliability. Descriptively, the results from the whole sample showed a

systematic relationship between visual field location and color preference. In V3 for

instance voxels representing parafoveal locations showed a preference for yellow. At

intermediate eccentricities along the horizontal meridian the analysis revealed a

preference for green. More peripherally, our analysis showed a preference for red in

the upper and lower visual fields. Visual inspection of the pairs of maps resulting from

the odd-even split show good agreement in the ROIs where above-chance BSC was

observed (Figure 3), indicating sufficient reliability.

Importantly, the maps differed between ROIs. For example, whereas in V3 the yellow

stimulus was preferred at parafoveal locations, this was not the case in V1, where

preference for yellow was more pronounced at more peripheral locations. These

results speak against inheritance of large-scale color-biases along the processing

hierarchy and for area-specific properties, which will be examined in more detail in the

following section.

Figure 11 shows the same results for luminance. Preference maps again differed

across brain regions: While in V1 and V2 the preference for stimulation at high

luminance decreased with increasing eccentricity for instance, the preference for high

luminance stimulation in V3 was more pronounced in the lower visual field than in the

upper visual field.

In sum, the results showed that voxels at different retinotopic locations were predicted

to prefer different stimulus classes. These differences were on the order of a few

percent points. These results indicate a systematic relationship between a voxel's

retinotopic spatial preference and its response pattern to color and luminance that

could at least partially mediate between-subject classification.

ROI-specificity of SRMs for voxel preference prediction

The topographies presented in Figures 10 and 11 showed variability between the

different ROIs. This raises the question to what extent the retinotopic biases in stimulus

preference captured by the SRMs were unique to each visual area and to what extent

they were of a more generic nature and therefore interchangeable across areas for the

prediction of stimulus preference. We examined this by comparing two analyses that

used SRMs trained on retinotopic data: in the first, the SRMs used to transform the

training brain data into the common space and to transform the predictions into the

individual space of the left-out test brain differed in terms of the ROIs they were trained

on, and results from all combinations of ROIs were averaged (incongruent condition).

In the second, the SRMs for both transformations were trained on the same ROI

(congruent condition – identical to our original analysis).

If SRMs were specific to each visual area, one would expect that the prediction of voxel

stimulus preferences is better when SRMs from the same ROI were used for both

transformations (congruent condition) than when each were based on SRMs from

different ROIs (incongruent condition). If the models merely capture general retinotopic

biases, one would expect that prediction accuracies would not differ. As is evident from

Figure 12 (left), prediction accuracies for color were significantly higher when using

congruent SRM pairings than when using incongruent ones (all $p < .01$) in all ROIs

where prediction accuracies were significantly better than chance. The only exception

to this was hV4 where, although the pair-wise test was not significant (p = .1653),

accuracy was significantly better than chance only for congruent pairings (p < .01) but

not incongruent pairings (p = .0695). V2 was the only ROI where color preference

prediction was significantly better than chance also for incongruent pairings (p < .01)

while all remaining ROIs showed no significant accuracies. The same pattern of results

was obtained for luminance (Figure 12, right). In all ROIs where luminance preference

prediction was significantly above chance, accuracy was also significantly lower when

incongruent SRM pairings were used (p < .01). Area hV4 again differed in this regard

because, although the two conditions did not significantly differ (p = .2905), preference

prediction accuracy was only significantly better than chance in the congruent condition

(p < .01), but not the incongruent condition (p = .2218). For luminance, there was no

ROI with significant prediction accuracy.

The discrepancies in prediction accuracies between congruent and incongruent SRM

pairings demonstrate that SRMs capture retinotopic biases in stimulus preferences that

are largely specific to individual visual areas.

SRM searchlight BSC analysis

We next tested how well common shared responses could be estimated from only

anatomically aligned activity patterns for subsequent BSC (in contrast to our ROI BSC

analysis where visual areas had been delineated functionally through retinotopy).

Individual datasets were warped to MNI space separately and SRM was fit to only local

patterns of retinotopic mapping responses in a searchlight analysis to estimate

common space representations for every brain location. After transforming individual

color responses to this common space, BSC could be carried out on those local

patterns. This approach had the additional advantage that BSC could be applied to the

whole brain.

Applying a false discovery rate of q < .05, we found that classification accuracies in a

region within the early visual cortex was significantly larger than chance (one-tailed

binomial test based on 3240 Bernoulli trials). Figure 13 shows the location of this region

relative to the hV4 group ROI. This ROI comprised all the voxels that were identified

as being part of individual hV4 ROIs in at least 25 % of the participants. As can be

seen, the voxels where classification was significantly better than chance were located

near the calcarine sulcus but did not overlap with the hV4 group ROI.

In sum, the searchlight analysis suggests that while anatomical alignment of voxels

was sufficiently high for BSC of color in early visual cortex this alignment was too

coarse in more anterior regions.

Behavioral control analysis

In order to ascertain that the classification results were not driven by differences in task

performance we performed a Bayesian two-way repeated-measures ANOVA (Rouder

et al., 2017) of the reaction time data under the factorially crossed three-level factor

color and the two-level factor luminance. Reaction time datasets from participants 2

and 9 were not complete due to programming error and had to be discarded from the

analysis, yielding 13 participants in total. Residuals were normally distributed (six

Shapiro-Wilk's tests, smallest test statistic across six conditions: $W = .925$, $p = .2931$)

and no violation of sphericity was detected (Mauchly's test, $p = .0845$ for color, $p =$

.6332 for the interaction). The Bayes analysis suggested that behavioral data were not

affected by color or luminance: the resulting Bayes factors indicated that the data were

BF_{10} = 1.273 times more compatible with the model assuming a main effect of color

relative to no effect (red: M = .574 s, SD = .052 s, green M = .582 s, SD = .058 s,

yellow: M = .601 s (SD = .067 s). As for luminance, the data were BF_{10} = 1.523 more

likely to have occurred under the model assuming a difference between conditions

compared to no difference (high: M = .595 s, SD = .054 s, low: M = .576 s, SD = .064

s). The data provided BF_{01} = 1.478 times more support to the model without interaction.

Thus, even if a difference between color (and likewise luminance) conditions existed,

it is too small for the present data to detect with sufficient certainty (1/3 < BF < 3 are

considered "anecdotal evidence" (Jeffreys, 1961).

Retinotopic binning analysis

Finally, we carried out a more traditional analysis that had previously been used to test

whether retinotopic bias might partially underlie the accuracy with which sensory input

can be decoded from patterns of fMRI signals (Beckett et al., 2012; Freeman et al.,

2011; Larsson et al., 2017). We therefore repeated the WSC analysis of color yet this

time binned voxels based on (a) their eccentricity preference and (b) their polar angle

preference, each of which preserves to some extent the retinotopic structure in the

respective coordinates. Voxel values were averaged within bins and classification was

carried out on these bin averages. Accuracies were compared with accuracies

obtained with random binning of voxels.

1005

Figure 14A shows that for binning based on eccentricity, decoding accuracies were

significantly better for at least some binning steps in all examined ROIs except VO1

compared to random binning. For binning based on polar angle (Figure 14B), we

observed significantly higher classification accuracies in V1 and V2 only. We note that

these retinotopic binning-based results are overall consistent with those of the SRM

analysis shown in Figure 3. In particular, all ROIs where prediction of color from shared

response patterns was significantly better than chance also showed better

classification after retinotopic binning than random binning, be it based on polar angle,

on eccentricity, or on both. Retinotopic binning yielded stronger results only in LO2

where classification accuracy was higher than random binning at two binning steps

(after correction) whereas SRM-based results in LO2 between brains was not

significantly better than chance after FWE correction across ROIs. To conclude,

retinotopic binning analysis is in good agreement with the results from our BSC

analysis and confirms the presence of spatial retinotopic biases in color and luminance

encoding in the human brain.

1021

1022

Discussion

Shared response modeling allows experimenters to test for between-subject commonalities in the neural representations of sensory stimuli. Typical applications involve sampling large neural response spaces from individual observers by presenting them with a vast variety of stimulus input (e.g., movies). Knowing how different brains respond to such stimulation makes it possible to match idiosyncratic response spaces to each other and to identify neural representations that are shared across observers. We applied SRM to brain activity measured while observers viewed simple retinotopic mapping stimuli, not movies. We show that controlling for how different brains respond to the same, purely spatially defined mapping stimulus is sufficient to preserve color responses across brains while being specific for distinct areas across the visual processing hierarchy. Our results suggest a relationship between visual space and color that is shared across observers and unique to each visual area. This conclusion is supported by three key observations.

First, we fit SRMs to retinotopic mapping data to map individual fMRI patterns into a shared common space. Classification analysis in this space showed that, in areas V1, V2, V3, hV4, and LO1, it was possible to predict what color an observer was seeing even though classifiers were trained exclusively on responses from other observers' brains (Figure 3). We found no behavioral differences between stimulus conditions that could explain these results. When constraining our analysis to subsets of voxels, V1, hV4, and LO1 showed the largest degree of robustness across voxel selections in accordance with their important role for color vision (Bartels & Zeki, 2000; Beauchamp et al., 1999, p. 1999; Brouwer & Heeger, 2009; Engel et al., 1997; Lueck et al., 1989). In conclusion, this demonstrates that aligning individual response spaces across brains

with respect to their retinotopic functional organization is sufficient to afford

classification of color in multiple visual areas across different brains.

Second, we hypothesized that the systematic relationship between retinotopic and

color responses captured by SRMs would allow them to predict how individual voxels

would respond to the color stimuli in an fMRI dataset recorded from a completely

independent brain. Similar methods had previously been used to predict broader brain

topographies like the location of FFA and PPA (Haxby et al., 2011). SRM-based

prediction accuracies at this task were indeed above chance in various ROIs (Figure

9) although no consistent preference pattern is discernible when inspecting color

preferences of voxels projected onto individual inflated hemispheres (Figures 4 and 5).

Similarly, a previous study presenting "color-preference images (similar to the

orientation-preference maps of Kamitani and Tong (2005)" found no evidence for

regional bias either (Figure 11, Parkes et al., 2009). This seemingly contradicts our

observation that voxel preferences could be predicted across brains. This disparity is

easily explained if one considers that SRM separates individual participants' fMRI

responses into shared and idiosyncratic components. While retinotopic biases exist in

the shared component, it is conceivable that at the individual level they remain

obscured by idiosyncratic response characteristics. Likewise, retinotopic biases as an

explanation of orientation decoding (Freeman et al., 2011) were demonstrated with an

analysis like our binning test (Figure 14) whereas they had not been apparent from

individual weight maps (Kamitani & Tong, 2005).

Third, we quantitatively investigated if the relationships between retinotopy and color

responses captured by SRMs were specific to different ROIs. We therefore compared

how accurately voxel responses to color could be predicted when transformation

matrices from SRMs belonging to either the same or different areas were used for

model fitting and prediction, respectively. We found that prediction accuracies dropped

considerably when SRMs based on different visual areas were used (Figure 12). This

specificity is consistent with visual inspection showing marked differences between

topographies from different brain areas (Figure 10). These inter-area differences are

important as they rule out alternative explanations like artefactual spatial

inhomogeneities, e.g., in the stimulus projection, because, in that case, one would

expect identical topographies across ROIs.

1080

The decreasing preference for red and green stimuli in V1 at larger eccentricity is

consistent with previous fMRI findings reporting decreasing responsiveness to

modulations in the red/green direction in color space, but not for the blue/yellow

direction (Mullen et al., 2007; Vanni et al., 2006). Similarly, behavioral measurements

showed that, compared to blue-yellow and achromatic mechanisms, contrast

sensitivities of the red-green cone mechanism are highest at the fovea, yet show the

strongest decline as eccentricity increases (Hansen et al., 2009; Mullen, 1991; Mullen

& Kingdom, 2002). Although our stimuli did not systematically sample color space and

did not include blue, our V1 findings are compatible with behavior. Such eccentricity

differences may be related to the observation that cone density decreases with

eccentricity (Curcio et al., 1990a), or that S cones are not found in the fovea (Roorda

& Williams, 1999), or that a fourth (melanopsin) photopigment may contribute to

peripheral color vision (Horiguchi et al., 2013). However, the distributions of L and M

cones (in contrast to S cones) show large variability across individuals (Brainard, 2015)

so that commonalities at the receptor level likely cannot fully explain the cortical effects.

1096

V2, unlike V1, shows no preference for green in the fovea but only to the left and the

right of it around the horizontal meridian while green is relatively less preferred along

the upper vertical meridian and yellow is less preferred along the horizontal meridian.

In V3, the fovea has less preference for green while, in every quadrant, there is a patch

each surrounding it where green is preferred. The opposite pattern is found for red

and, to lesser extent, for yellow, which are both more preferred in the center and more

peripheral regions of the visual field. Area hV4 shows higher preference for red than

green or yellow in the center, which drops off ventrally and to its left and right where

yellow and green are preferred. Finally, LO1 shows more heterogeneity in preference

in the upper visual field. These descriptive differences between visual areas are

consistent with our finding that stimulus preference can be predicted more accurately

when SRMs from the same visual area are used to train models and derive predictions.

1109

Similar variability between areas has been observed using fMRI with respect to spatial

sensitivity for chromatic and achromatic input which differentially covaries with

eccentricity (Welbourne et al., 2018). In addition to eccentricity, human neuroimaging

studies – although not specifically addressing color vision – demonstrated that polar

angle influences visual processing (Benson et al., 2012; Liu et al., 2006; Silson et al.,

2018; Silva et al., 2018). It is hence conceivable that the topographies in extrastriate

areas are related to different behavioral and cone mechanisms than V1, involving a

combination of both eccentricity and polar angle differences. While it is known that

visual perception of spatial frequency and orientation depends on polar angle

(Jóhannesson et al., 2018; Karim & Kojima, 2010), the empirical findings for color are

mixed (Danilova & Mollon, 2009; Levine & McAnany, 2005). At the retinal level, cone

densities change depending on polar angle in that they are higher along the horizontal

than the vertical meridians (Curcio et al., 1990b; Song et al., 2011). But at least for

orientation discrimination, simulations suggested that these cone differences cannot

fully explain that polar angle affects visual performance (Kupers et al., 2019).

1125

The color biases presented here complement similar fMRI findings involving other

visual features like orientation (Beckett et al., 2012; Freeman et al., 2011, 2013;

Larsson et al., 2017; Sasaki et al., 2006) and we predict that retinotopy-based SRM

would also allow between-subject classification of these features. Concerning color,

spatial biases in the visual system are known from research on mice in which stimuli

appearing above or below the horizon carry different behavioral meaning (Baden et

al., 2013; Denman et al., 2018; Rhim et al., 2017). Environmental regularities like the

chromaticities of natural daylight (Lafer-Sousa et al., 2012) or of objects versus their

backgrounds (Rosenthal et al., 2018) shape color vision in primates, too. Which

environmental adaptations may underlie our findings requires further research.

1136

We point out that our stimuli do not only probe the retinotopic layout of cortical field

maps. That is because they are composed of more low-level spatial features like

contrast, motion, and orientation, which may have shared representations with color

(Friedman et al., 2003; Garg et al., 2019; Johnson et al., 2001, 2008; Leventhal et al.,

1995; Sincich & Horton, 2005). SRM may therefore also exploit commonalities in the

co-representations of these features, thereby contributing to our results.

1143

Finally, it has been demonstrated that response biases for orientation can be changed

by embedding a grating stimulus in a modulator, which could render the orientation

either radial or tangential (Roth et al., 2018). Color vision, on the other hand, shows

some robustness in that different colors elicit patterns of brain activity that are similar

between sensory-driven colors and memory colors (Bannert & Bartels, 2013;

Teichmann et al., 2019; Vandenbroucke et al., 2016) and across tasks (Bannert &

Bartels, 2018; Serences et al., 2009). In sum, given the evidence for both flexibility

and stability of color representations, it would be interesting for future studies to

probe the plasticity of the observed large-scale response biases.

References

Anderson, M. J., Capota, M., Turek, J. S., Zhu, X., Willke, T. L., Wang, Y., Chen, P.-H., Manning, J. R., Ramadge, P. J., & Norman, K. A. (2016). Enabling factor analysis on thousand-subject neuroimaging datasets. *2016 IEEE International Conference on Big Data (Big Data)*, 1151–1160. https://doi.org/10.1109/BigData.2016.7840719

Baden, T., Schubert, T., Chang, L., Wei, T., Zaichuk, M., Wissinger, B., & Euler, T. (2013). A tale of two retinal domains: Near-Optimal sampling of achromatic contrasts in natural scenes through asymmetric photoreceptor distribution. *Neuron*, *80*(5), 1206–1217. https://doi.org/10.1016/j.neuron.2013.09.030

Bannert, M. M., & Bartels, A. (2013). Decoding the yellow of a gray banana. *Current Biology*, *23*(22), 2268–2272. https://doi.org/10.1016/j.cub.2013.09.016

Bannert, M. M., & Bartels, A. (2018). Human V4 Activity Patterns Predict Behavioral Performance in Imagery of Object Color. *The Journal of Neuroscience*, *38*(15), 3657–3668. https://doi.org/10.1523/JNEUROSCI.2307-17.2018

Bartels, A., & Zeki, S. (2000). The architecture of the colour centre in the human visual brain: New results and a review. *European Journal of Neuroscience*, *12*(1), 172–193.

Beauchamp, M. S., Haxby, J. V, Jennings, J. E., & DeYoe, E. A. (1999). An fMRI version of the Farnsworth-Munsell 100-Hue test reveals multiple color-selective areas in human ventral occipitotemporal cortex. *Cerebral Cortex*, *9*(3), 257–263.

Beckett, A., Peirce, J. W., Sanchez-Panchuelo, R. M., Francis, S., & Schluppeck, D. (2012). Contribution of large scale biases in decoding of direction-of-motion from high-resolution fMRI data in human early visual cortex. *NeuroImage*, *63*(3), 1623–1632. https://doi.org/10.1016/j.neuroimage.2012.07.066

Benjamini, Y., & Hochberg, Y. (1995). Controlling the False Discovery Rate: A Practical and

Powerful Approach to Multiple Testing. *Journal of the Royal Statistical Society: Series*

B (Methodological), *57*(1), 289–300. https://doi.org/10.1111/j.2517-

6161.1995.tb02031.x

Benson, N. C., Butt, O. H., Datta, R., Radoeva, P. D., Brainard, D. H., & Aguirre, G. K. (2012).

The retinotopic organization of striate cortex is well predicted by surface topology.

Current Biology, *22*(21), 2081–2085. https://doi.org/10.1016/j.cub.2012.09.014

Brainard, D. H. (2015). Color and the Cone Mosaic. *Annual Review of Vision Science*, *1*(1),

519–546. https://doi.org/10.1146/annurev-vision-082114-035341

Brooks, J. (2012). Counterbalancing for serial order carryover effects in experimental

condition orders. *Psychological Methods*, 1–54.

Brouwer, G. J., & Heeger, D. J. (2009). Decoding and Reconstructing Color from Responses in

Human Visual Cortex. *Journal of Neuroscience*, *29*(44), 13992–14003.

https://doi.org/10.1523/JNEUROSCI.3577-09.2009

Chen, P.-H. (Cameron), Chen, J., Yeshurun, Y., Hasson, U., Haxby, J., & Ramadge, P. J. (2015).

A Reduced-Dimension fMRI Shared Response Model. *Neural Information Processing*

Systems Conference (NIPS), 460–468.

Cohen, J. D., Daw, N., Engelhardt, B., Hasson, U., Li, K., Niv, Y., Norman, K. A., Pillow, J.,

Ramadge, P. J., Turk-Browne, N. B., & Willke, T. L. (2017). Computational approaches

to fMRI analysis. *Nature Neuroscience*, *20*(3), 304–313.

https://doi.org/10.1038/nn.4499

Conway, B. R., Moeller, S., & Tsao, D. Y. (2007). Specialized color modules in macaque

extrastriate cortex. *Neuron*, *56*(3), 560–573.

https://doi.org/10.1016/j.neuron.2007.10.008

Conway, B. R., & Tsao, D. Y. (2009). Color-tuned neurons are spatially clustered according to

color preference within alert macaque posterior inferior temporal cortex.

Proceedings of the National Academy of Sciences, *106*(42), 18034–18039.

https://doi.org/10.1073/pnas.0810943106

Curcio, C. A., Sloan, K. R., Kalina, R. E., & Hendrickson, A. E. (1990a). Human photoreceptor

topography. *Journal of Comparative Neurology*, *292*(4), 497–523.

https://doi.org/10.1002/cne.902920402

Curcio, C. A., Sloan, K. R., Kalina, R. E., & Hendrickson, A. E. (1990b). Human photoreceptor

topography. *Journal of Comparative Neurology*, *292*(4), 497–523.

https://doi.org/10.1002/cne.902920402

Danilova, M. V., & Mollon, J. D. (2009). The symmetry of visual fields in chromatic

discrimination. *Brain and Cognition*, *69*(1), 39–46.

https://doi.org/10.1016/j.bandc.2008.05.003

De Valois, R. L., & Jacobs, G. H. (1968). Primate color vision. *Science*, *162*(3853), 533–540.

Denison, R. N., Vu, A. T., Yacoub, E., Feinberg, D. A., & Silver, M. A. (2014). Functional

mapping of the magnocellular and parvocellular subdivisions of human LGN.

NeuroImage, *102*(P2), 358–369. https://doi.org/10.1016/j.neuroimage.2014.07.019

Denman, D. J., Luviano, J. A., Ollerenshaw, D. R., Cross, S., Williams, D., Buice, M. A., Olsen, S.

R., & Reid, R. C. (2018). Mouse color and wavelength-specific luminance contrast

sensitivity are non- uniform across visual space. *ELife*, *7*, 1–16.

https://doi.org/10.7554/eLife.31209

Derrington, A. M., Krauskopf, J., & Lennie, P. (1984). Chromatic mechanisms in lateral

geniculate nucleus of Macaque. *The Journal of Physiology*, *357*, 241–265.

https://doi.org/10.1113/jphysiol.1984.sp015499

Engel, S., Zhang, X., & Wandell, B. A. (1997). Colour tuning in human visual cortex measured

with functional magnetic resonance imaging. *Nature*, *388*(6637), 68–71.

https://doi.org/10.1038/40398

Felleman, D. J., & Van Essen, D. C. (1991). Distributed hierarchical processing in the primate

cerebral cortex. *Cerebral Cortex*, *1*(1), 1–47. https://doi.org/10.1093/cercor/1.1.1

Field, G. D., & Chichilnisky, E. J. (2007). Information processing in the primate retina:

Circuitry and coding. *Annual Review of Neuroscience*, *30*, 1–30.

https://doi.org/10.1146/annurev.neuro.30.051606.094252

Fischl, B. (2012). FreeSurfer. *NeuroImage*, *62*(2), 774–781.

https://doi.org/10.1016/j.neuroimage.2012.01.021

Freeman, J., Brouwer, G. J., Heeger, D. J., & Merriam, E. P. (2011). Orientation decoding

depends on maps, not columns. *Journal of Neuroscience*, *31*(13), 4792–4804.

https://doi.org/10.1523/JNEUROSCI.5160-10.2011

Freeman, J., Heeger, D. J., & Merriam, E. P. (2013). Coarse-scale biases for spirals and

orientation in human visual cortex. *Journal of Neuroscience*, *33*(50), 19695–19703.

https://doi.org/10.1523/JNEUROSCI.0889-13.2013

Friedman, H. S., Zhou, H., & von der Heydt, R. (2003). The coding of uniform colour figures in

monkey visual cortex. *Journal of Physiology*, *548*(Pt 2), 593–613.

https://doi.org/10.1113/jphysiol.2002.033555

Garg, A. K., Li, P., Rashid, M. S., & Callaway, E. M. (2019). Color and orientation are jointly

coded and spatially organized in primate primary visual cortex. *Science*, *364*(6447),

1275–1279. https://doi.org/10.1126/science.aaw5868

Gauthier, I., Skudlarski, P., Gore, J. C., & Anderson, A. W. (2000). Expertise for cars and birds

recruits brain areas involved in face recognition. *Nature Neuroscience*, *3*(2), 191–197.

https://doi.org/10.1038/72140

Goodale, M. A., & Milner, A. D. (1992). Separate visual pathways for perception and action.

Trends in Neurosciences, *15*(1), 20–25. https://doi.org/10.1016/0166-2236(92)90344-

8

Guntupalli, J. S., Hanke, M., Halchenko, Y. O., Connolly, A. C., Ramadge, P. J., & Haxby, J. V.

(2016). A Model of Representational Spaces in Human Cortex. *Cerebral Cortex*, *26*(6),

2919–2934. https://doi.org/10.1093/cercor/bhw068

Hansen, T., Pracejus, L., & Gegenfurtner, K. R. (2009). Color perception in the intermediate

periphery of the visual field. *Journal of Vision*, *9*(4), 1–12.

https://doi.org/10.1167/9.4.26

Haxby, J. V., Guntupalli, J. S., Connolly, A. C., Halchenko, Y. O., Conroy, B. R., Gobbini, M. I.,

Hanke, M., & Ramadge, P. J. (2011). A Common, High-Dimensional Model of the

Representational Space in Human Ventral Temporal Cortex. *Neuron*, *72*(2), 404–416.

https://doi.org/10.1016/j.neuron.2011.08.026

Horiguchi, H., Winawer, J., Dougherty, R. F., & Wandell, B. A. (2013). Human trichromacy

revisited. *Proceedings of the National Academy of Sciences*, *110*(3), E260–E269.

https://doi.org/10.1073/pnas.1214240110

Ishihara, S. (2011). *Ishihara's tests for colour deficiency* (38 Plates). Kanehara Trading Inc.

Jeffreys, H. (1961). *Theory of Probability* (3rd ed.). Oxford University Press.

Jóhannesson, Ó. I., Tagu, J., & Kristjánsson, Á. (2018). Asymmetries of the visual system and

their influence on visual performance and oculomotor dynamics. *European Journal of*

Neuroscience, *48*(11), 3426–3445. https://doi.org/10.1111/ejn.14225

Johnson, E. N., Hawken, M. J., & Shapley, R. (2001). The spatial transformation of color in the

primary visual cortex of the macaque monkey. *Nature Neuroscience*, *4*(4), 409–416.

https://doi.org/10.1038/86061

Johnson, E. N., Hawken, M. J., & Shapley, R. (2008). The Orientation Selectivity of Color-

Responsive Neurons in Macaque V1. *Journal of Neuroscience*, *28*(32), 8096–8106.

https://doi.org/10.1523/JNEUROSCI.1404-08.2008

Kaiser, P. K. (1991). Flicker as a function of wavelength and heterochromatic flicker

photometry. In J. J. Kulikowski, V. Walsh, & I. J. Murray (Eds.), *Limits of Vision* (pp.

171–190). MacMillan.

Kamitani, Y., & Tong, F. (2005). Decoding the visual and subjective contents of the human

brain. *Nature Neuroscience*, *8*(5), 679–685. https://doi.org/10.1038/nn1444

Kanwisher, N., McDermott, J., & Chun, M. M. (1997). The fusiform face area: A module in

human extrastriate cortex specialized for face perception. *The Journal of*

Neuroscience, *17*(11), 4302–4311.

Karim, A. K. M. R., & Kojima, H. (2010). The *what* and *why* of perceptual asymmetries in the

visual domain. *Advances in Cognitive Psychology*, *6*(1), 103–115.

https://doi.org/10.2478/v10053-008-0080-6

Kleiner, M., Brainard, D. H., & Pelli, D. G. (2007). "What's new in Psychtoolbox-3?" In

Perception 36 ECVP Abstract Supplement.

Kriegeskorte, N., Goebel, R., & Bandettini, P. (2006). Information-based functional brain

mapping. *Proceedings of the National Academy of Sciences*, *103*(10), 3863–3868.

https://doi.org/10.1073/pnas.0600244103

Kupers, E. R., Carrasco, M., & Winawer, J. (2019). Modeling visual performance differences

'around' the visual field: A computational observer approach. *PLoS Computational*

Biology, *15*(5), 1–29. https://doi.org/10.1371/journal.pcbi.1007063

Lafer-Sousa, R., Liu, Y. O., Lafer-Sousa, L., Wiest, M. C., & Conway, B. R. (2012). Color tuning

in alert macaque V1 assessed with fMRI and single-unit recording shows a bias

toward daylight colors. *Journal of the Optical Society of America A*, *29*(5), 657.

https://doi.org/10.1364/JOSAA.29.000657

Larsson, J., Harrison, C., Jackson, J., Oh, S.-M., & Zeringyte, V. (2017). Spatial scale and

distribution of neurovascular signals underlying decoding of orientation and eye of

origin from fMRI data. *Journal of Neurophysiology*, *117*(2), 818–835.

https://doi.org/10.1152/jn.00590.2016

Ledoit, O., & Wolf, M. (2004). Honey, I Shrunk the Sample Covariance Matrix. *The Journal of*

Portfolio Management, *30*(4), 110–119. https://doi.org/10.3905/jpm.2004.110

Leventhal, A. G., Thompson, K. G., Liu, D., Zhou, Y., & Ault, S. J. (1995). Concomitant

sensitivity to orientation, direction, and color of cells in layers 2, 3, and 4 of monkey

striate cortex. *Journal of Neuroscience*, *15*(3 Pt 1), 1808–1818.

Levine, M. W., & McAnany, J. J. (2005). The relative capabilities of the upper and lower visual

hemifields. *Vision Research*, *45*(21), 2820–2830.

https://doi.org/10.1016/j.visres.2005.04.001

Liu, T., Heeger, D. J., & Carrasco, M. (2006). Neural correlates of the visual vertical meridian

asymmetry. *Journal of Vision*, *6*(11), 1294–1306. https://doi.org/10.1167/6.11.12

Livingstone, M. S., & Hubel, D. H. (1984). Anatomy and physiology of a color system in the

primate visual cortex. *Journal of Neuroscience*, *4*(1), 309–356.

Livingstone, M. S., & Hubel, D. H. (1988). Segregation of form, color, movement, and depth:

Anatomy, physiology, and perception. *Science*, *240*(4853), 740–749.

Lu, H. D., & Roe, A. W. (2008). Functional organization of color domains in V1 and V2 of

Macaque monkey revealed by optical imaging. *Cerebral Cortex*, *18*(3), 516–533.

https://doi.org/10.1093/cercor/bhm081

Lueck, C. J., Zeki, S., Friston, K. J., Deiber, M. P., Cope, P., Cunningham, V. J., Lammertsma, A.

A., Kennard, C., & Frackowiak, R. S. (1989). The colour centre in the cerebral cortex of

man. *Nature*, *340*(6232), 386–389. https://doi.org/10.1038/340386a0

Malach, R., Reppas, J. B., Benson, R. R., Kwong, K. K., Jiang, H., Kennedy, W. A., Ledden, P. J.,

Brady, T. J., Rosen, B. R., & Tootell, R. B. (1995). Object-related activity revealed by

functional magnetic resonance imaging in human occipital cortex. *Proceedings of the*

National Academy of Sciences of the United States of America, *92*(18), 8135–8139.

Mishkin, M., & Ungerleider, L. G. (1982). Contribution of striate inputs to the visuospatial

functions of parieto-preoccipital cortex in monkeys. *Behavioural Brain Research*, *6*(1),

57–77. https://doi.org/10.1016/0166-4328(82)90081-X

Morey, R., & Rouder, J. N. (2018). *BayesFactor 0.9.12-4.2*. Comprehensive R Archive

Network. https://cran.r-project.org/web/packages/BayesFactor/index.html

Mullen, K. T. (1991). Colour vision as a post-receptoral specialization of the central visual

field. *Vision Research*, *31*(1), 119–130. https://doi.org/10.1016/0042-6989(91)90079-

K

Mullen, K. T., Dumoulin, S. O., McMahon, K. L., De Zubicaray, G. I., & Hess, R. F. (2007).

Selectivity of human retinotopic visual cortex to S-cone-opponent, L/M-cone-

opponent and achromatic stimulation. *European Journal of Neuroscience*, *25*(2), 491–

502. https://doi.org/10.1111/j.1460-9568.2007.05302.x

Mullen, K. T., & Kingdom, F. A. A. (2002). Differential distributions of red-green and blue-

yellow cone opponency across the visual field. *Visual Neuroscience*, *19*(1), 109–118.

https://doi.org/10.1017/S0952523802191103

Nasr, S., Polimeni, J. R., & Tootell, R. B. H. (2016). Interdigitated Color- and Disparity-

Selective Columns within Human Visual Cortical Areas V2 and V3. *Journal of*

Neuroscience, *36*(6), 1841–1857. https://doi.org/10.1523/JNEUROSCI.3518-15.2016

Nichols, T. E., & Holmes, A. P. (2002). Nonparametric permutation tests for functional

neuroimaging: A primer with examples. *Human Brain Mapping*, *15*(1), 1–25.

https://doi.org/10.1016/B978-012264841-0/50048-2

Parkes, L. M., Marsman, J.-B. C., Oxley, D. C., Goulermas, J. Y., & Wuerger, S. M. (2009).

Multivoxel fMRI analysis of color tuning in human primary visual cortex. *Journal of*

Vision, *9*(1), 1.1-13. https://doi.org/10.1167/9.1.1

Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M.,

Müller, A., Nothman, J., Louppe, G., Prettenhofer, P., Weiss, R., Dubourg, V.,

Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., & Duchesnay, É.

(2012). Scikit-learn: Machine Learning in Python. *Journal of Machine Learning*

Research, *12*, 2825–2830. https://doi.org/10.1007/s13398-014-0173-7.2

Rhim, I., Coello-Reyes, G., Ko, H. K., & Nauhaus, I. (2017). Maps of cone opsin input to mouse

V1 and higher visual areas. *Journal of Neurophysiology*, *117*(4), 1674–1682.

https://doi.org/10.1152/jn.00849.2016

Roorda, A., & Williams, D. R. (1999). The arrangement of the three cone classes in the living

human eye. *Nature*, *397*(6719), 520–522. https://doi.org/10.1038/17383

Rosenthal, I., Ratnasingam, S., Haile, T., Eastman, S., Fuller-Deets, J., & Conway, B. R. (2018).

Color statistics of objects, and color tuning of object cortex in macaque monkey.

Journal of Vision, *18*(11), 1–21. https://doi.org/10.1167/18.11.1

Roth, Z. N., Heeger, D. J., & Merriam, E. P. (2018). Stimulus vignetting and orientation

selectivity in human visual cortex. *ELife*, *7*, 1–19. https://doi.org/10.7554/eLife.37241

Rouder, J. N., Morey, R. D., Verhagen, J., Swagman, A. R., & Wagenmakers, E. J. (2017).

Bayesian analysis of factorial designs. *Psychological Methods*, *22*(2), 304–321.

https://doi.org/10.1037/met0000057

Sasaki, Y., Rajimehr, R., Kim, B. W., Ekstrom, L. B., Vanduffel, W., & Tootell, R. B. H. (2006).

The Radial Bias: A Different Slant on Visual Orientation Sensitivity in Human and

Nonhuman Primates. *Neuron*, *51*(5), 661–670.

https://doi.org/10.1016/j.neuron.2006.07.021

Schiller, P. H., Logothetis, N. K., & Charles, E. R. (1990). Functions of the colour-opponent

and broad-band channels of the visual system. *Nature*, *343*(6253), 68–70.

https://doi.org/10.1038/343068a0

Serences, J. T., Ester, E. F., Vogel, E. K., & Awh, E. (2009). Stimulus-specific delay activity in

human primary visual cortex. *Psychological Science*, *20*(2), 207–214.

https://doi.org/10.1111/j.1467-9280.2009.02276.x

Sereno, M. I., Dale, A. M., Reppas, J. B., Kwong, K. K., Belliveau, J. W., Brady, T. J., Rosen, B.

R., & Tootell, R. B. (1995). Borders of multiple visual areas in humans revealed by

functional magnetic resonance imaging. *Science*, *268*(5212), 889–893.

Silson, E. H., Reynolds, R. C., Kravitz, D. J., & Baker, C. I. (2018). Differential sampling of visual

space in ventral and dorsal early visual cortex. *Journal of Neuroscience*, *38*(9), 2294–

2303. https://doi.org/10.1523/JNEUROSCI.2717-17.2018

Silva, M. F., Brascamp, J. W., Ferreira, S., Castelo-Branco, M., Dumoulin, S. O., & Harvey, B.

M. (2018). Radial asymmetries in population receptive field size and cortical

magnification factor in early visual cortex. *NeuroImage*, *167*(September 2016), 41–

52. https://doi.org/10.1016/j.neuroimage.2017.11.021

Sincich, L. C., & Horton, J. C. (2005). The circuitry of V1 and V2: Integration of color, form,

and motion. *Annual Review of Neuroscience*, *28*, 303–326.

https://doi.org/10.1146/annurev.neuro.28.061604.135731

Song, H., Chui, T. Y. P., Zhong, Z., Elsner, A. E., & Burns, S. A. (2011). Variation of cone

photoreceptor packing density with retinal eccentricity and age. *Investigative*

Ophthalmology and Visual Science, *52*(10), 7376–7384.

https://doi.org/10.1167/iovs.11-7199

Tanaka, K. (1993). Neuronal mechanisms of object recognition. *Science*, *262*(5134), 685–688.

https://doi.org/10.1126/science.8235589

Teichmann, L., Grootswagers, T., Carlson, T. A., & Rich, A. N. (2019). Seeing versus knowing:

The temporal dynamics of real and implied colour processing in the human brain.

NeuroImage, *200*, 373–381. https://doi.org/10.1016/j.neuroimage.2019.06.062

Ts'o, D. Y., & Gilbert, C. D. (1988). The organization of chromatic and spatial interactions in

the primate striate cortex. *Journal of Neuroscience*, *8*(5), 1712–1727.

Vandenbroucke, A. R. E., Fahrenfort, J. J., Meuwese, J. D. I., Scholte, H. S., & Lamme, V. A. F.

(2016). Prior Knowledge about Objects Determines Neural Color Representation in

Human Visual Cortex. *Cerebral Cortex*, *26*(4), 1401–1408.

https://doi.org/10.1093/cercor/bhu224

Vanni, S., Henriksson, L., Viikari, M., & James, A. C. (2006). Retinotopic distribution of

chromatic responses in human primary visual cortex. *European Journal of*

Neuroscience, *24*(6), 1821–1831. https://doi.org/10.1111/j.1460-9568.2006.05070.x

Wandell, B. A., Dumoulin, S. O., & Brewer, A. a. (2007). Visual Field Maps in Human Cortex.

Neuron, *56*(2), 366–383. https://doi.org/10.1016/j.neuron.2007.10.012

Wandell, B. A., & Winawer, J. (2011). Imaging retinotopic maps in the human brain. *Vision*

Research, *51*(7), 718–737. https://doi.org/10.1016/j.visres.2010.08.004

Welbourne, L. E., Morland, A. B., & Wade, A. R. (2018). Population receptive field (pRF)

measurements of chromatic responses in human visual cortex using fMRI.

NeuroImage, *167*(November 2017), 84–94.

https://doi.org/10.1016/j.neuroimage.2017.11.022

Zeki, S. (1973). Colour coding in rhesus monkey prestriate cortex. *Brain Research*, *53*(2),

422–427. https://doi.org/10.1016/0006-8993(73)90227-8

Zeki, S. (1978). Functional specialisation in the visual cortex of the rhesus monkey. *Nature*,

274(5670), 423–428. https://doi.org/10.1038/274423a0

Zeki, S. (1980). The response properties of cells in the middle temporal area (area MT) of owl

monkey visual cortex. *Proceedings of the Royal Society of London - Biological*

Sciences, *207*(1167), 239–248. https://doi.org/10.1098/rspb.1980.0022

Zeki, S., Watson, J., Lueck, C., Friston, K., Kennard, C., & Frackowiak, R. (1991). A direct

demonstration of functional specialization in human visual cortex. *The Journal of*

Neuroscience, *11*(3), 641–649. https://doi.org/10.1523/JNEUROSCI.11-03-

00641.1991

1429

1430

Figures and Tables

Figure 1

Shared response modeling procedure. Retinotopic mapping data (top) were recorded while participants watched a rotating wedge or an expanding/contracting ring stimulus. Datasets from every participant's ROI were resampled to the same temporal resolution and entered into a shared response model (Chen2015, Anderson2016). SRM estimates a transformation matrix W_n for every participant that maps voxel response spaces from individual ROIs into a 50-dimensional common space (see **Materials and Methods**). Note that only retinotopic mapping data were used to estimate transformation matrices. Color responses (bottom) were measured with fMRI from participants performing a luminance change detection task on red, green, and yellow ring stimuli presented at two luminance levels. Stimuli were shown for 8.5 s with ITI = 1.5 s (see **Materials and Methods**). These fMRI color responses, which were recorded independently from the retinotopic mapping data, were mapped from individual response spaces into the common space using the W_n matrices for every ROI and participant.

Figure 2

Multivoxel pattern classification results for within-subject classification. For every ROI and

participant, cross-validated (leave-one-run-out) classification accuracies were obtained for

the prediction of color (dark dots) and luminance (light dots). Accuracies are transformed to

z-values using the normal approximation to the binomial distribution (n = 216) so that both

classifications share the same y-axis and accuracies expected by chance is 0 in both cases.

Black diamonds indicate mean accuracy averaged across participants and error bars represent

the parametric 95 % CI. Asterisks mark accuracies with p values below .01 (permutation tests,

2000 iterations, FWE corrected across 7 ROIs). As shown, classification accuracies were

significantly larger than chance for both color and luminance classification.

1456

Figure 3

Multivoxel pattern classification results for between-subject classification. Individual

responses were transformed to the common space. Transformation matrices were estimated

using the shared response model fit to the independent set of retinotopic mapping data.

Classification accuracies were cross-validated by leaving out the participant during classifier

training whose data were used for testing (leave-one-subject-out). The normal approximation

to the binomial distribution was used to convert accuracies to z-values (n = 3240). Note that

prediction accuracies are represented as bars rather than individual dots (see **Figure 2**)

because the prediction accuracies for individual participants are no longer independent. Error

bars denote the 2.5th and the 97.5th percentile of the permuted null distributions. Asterisks

and plus sign denote accuracies significantly exceeding chance at $p < .01$ and $p < .05$,

respectively (permutation tests, 2000 iterations, FWE corrected across 7 ROIs). Both color and

luminance could be predicted across subjects from areas V1-V3. Additionally, color could be

predicted from hV4 and LO1.

1471

Figure 4

Color preference maps. To check if any retinotopic response biases were already evident from

the pattern of univariate responses, the univariate voxel GLM coefficients for each color

category were projected onto each participant's inflated cortical surfaces of the left and right

hemispheres. Each vertex was painted in the color of a given stimulus if its GLM coefficient

was positive and larger than the coefficients for all remaining colors. There is no obvious

correspondence between preference maps across participants.

1479

1479   *Figure 4*

1480   *Figure 5*

1481   **Luminance preference maps.** Same as Figure 4 except that surface maps here show vertex

1482   preference for high luminance in yellow and for low luminance in blue. Again, there is no

1483   obvious correspondence between preference maps across participants.

1484
1485

Figure 5

Luminance preference maps. Same as Figure 4 except that surface maps here show vertex

Figure 6

Dependence of BSC accuracy on number of shared features. Top: explained variance and

decoding accuracy for the color data. **Bottom:** same for luminance data. The x-axis denotes

the number features used for the SRMs' fit to the retinotopic mapping data. The left y-axis

(blue) denotes the percent variance explained by the features of the fitted models for the

retinotopic mapping dataset (solid blue lines) and the color (luminance) responses from the

main experiment (dashed blue lines). The right y-axis (orange) denotes the accuracy of the

between-subject classification of color (luminance) and its 95 % CI (Jeffreys interval) (solid

orange, see also Figure 3). Chance level is indicated by the dotted orange line. A higher number

of shared features resulted in more explained variance for the retinotopic dataset. This applies

to the main experiment as well although it was not used for model fitting. Classification

accuracy only increased with more shared features for low values but shows a downward

trend beyond approximately 10 to 20 features. This turning point coincides with a weakly

pronounced "elbow" in the explained variance curves. Few shared features are thus sufficient

to capture the information shared across observers. Note that the number of shared features

in the main analysis (Figure 3) was selected by grid-search on the training set.

1502

Figure 7

Dependence of BSC accuracy on number of voxels. Since ROIs differ in terms of the number

of voxels they contain, an analysis was conducted with different numbers of voxels. Voxels

within ROIs were ranked according to signal quality (F value from the Fourier-based analysis

of the retinotopic mapping data) and only the best few voxels were included in the analysis.

Curves represent classification accuracies as the mean percent correct classifications across

the group and confidence bands are the 95 % CI. Asterisks mark accuracies that are

significantly larger than chance (p < .05, Holm-Šidák corrected for the number of ROIs, which

could be smaller than seven because some ROIs did not contain enough voxels in all tested

subjects) and daggers denote p < .05 (uncorrected).

Figure 7

Figure 8

Preference prediction analysis. Illustration of two methods to predict stimulus preferences

(color or luminance) of individual voxels within a ROI in an independent, withheld brain based

on activity observed in the remaining brains. **(A)** Prediction based on traditional cartesian

retinotopic voxel locations coupled to kNN response preference classification. All voxels from

a given ROI were extracted from all but one observer's brains (leave-one-subject-out cross-

validation). Each voxel was labeled according to which of the stimulus category (e.g., green,

red, or yellow) elicited its strongest response, i.e., its target variable. A nearest-neighbor

classifier was trained to predict the target from the Cartesian retinotopic coordinates of that

voxel. The classifier was then cross-validated on the left-out brain where the predicted voxel

preferences based on the retinotopic coordinates were compared to the true voxel

preferences. **(B)** Prediction based on SRM (common space). SRM provides direct mappings

between individual and common space representations of brain activity. The retinotopic

mapping data were used to obtain a shared response model for the whole group of

participants. The **W** matrices obtained from the SRM were used to map every vector of voxel

responses for each stimulus category from all individual ROI voxel spaces to the common

space. The vectors in common space were averaged across participants for each category and

the result was mapped into the individual ROI voxel space of the left-out brain. The preference

prediction for each voxel in the test brain was determined as the stimulus category with the

strongest predicted response. In a second version of this model, instead of the mean

univariate responses to each stimulus category, the multivariate classification weights for

each stimulus category were used for prediction. **(C)** Visualization of predictions. To visualize

the stimulus preference across retinotopic space, we estimated the preference for each visual

field location from the predicted voxel preferences using kernel density estimation (KDE). This

yielded one 2D density function per stimulus category. At each visual field location, a softmax

function was applied to the different function values from each category to obtain a

probabilistic interpretation in percent of stimulus preference at that location. Finally, the

baseline percentage (100 % / number of categories) was subtracted from each value to

facilitate the distinction between positive and negative deviations from uniformity.

1542

Figure 9

Preference prediction results. Comparison of the two procedures with and one without SRM

to predict voxel preferences across different brains for color (left) and luminance (right).

Accuracy is the fraction of correctly classified voxels across all brains and error bars represent

95 % CIs. Binomial tests were used to test if preference prediction accuracy was significantly

larger than chance. Pair-wise comparisons were made using independent z-tests. Asterisks

denote significance at $p < .05$, Holm-Šidák corrected for seven ROIs. While different methods

could be used to predict stimulus preference with above-chance accuracy, the SRM approach

with univariate measures of voxel preference frequently outperformed its alternatives.

1552

Figure 10

Color preference across the visual field. Color preference was visualized as explained in **Figure**

8 (C). Each of the three columns indicate the probability of a voxel to prefer the green, red,

yellow stimulus for every visual field location. SRM-uni based maps are shown as it achieved

highest scores (see Figure 9). The plotted values are the difference between this probability

and the "baseline probability", i.e., the probability that would be expected if it were

distributed uniformly across the three stimulus categories, i.e., 33.3 %. Positive (colored)

values thus represent regions where the preference probability for a given color is larger than

baseline, negative (gray) values represent regions where it is lower. Large plots show results

for analysis using all participants' datasets, small plots show results using only subsets of the

data based on an odd-even split. Visual areas show characteristic dependencies between

retinotopic location and color preference: V1 for instance exhibits a preference for green or

red near the fovea and less for yellow while the opposite is true at higher eccentricities.

Figure 10

Figure 11

Luminance preference across the visual field. Same conventions as in **Figure 10** except that

preference is shown for high versus low intensity luminance. Since classification was binary,

there is only a single column. Hot areas mark regions in the visual field where high luminance

was preferred and gray areas mark regions where low luminance was preferred. In early areas

V1-V3 for instance, luminance preference changed as a function of eccentricity. Note that

although VO1 showed a difference between left and right visual field descriptively, preference

classification in this area was not significant **(Figure 9)**.

1574
1575

Figure 12

ROI-specificity of SRMs for preference prediction. To examine whether the retinotopic biases

captured in SRMs were specific for individual visual areas, we repeated the voxel preference

prediction analysis (**Figure 8 B**) but compared transformation matrices from all visual areas in

the test brain with respect to how well they could predict voxel preference in a given area.

Dark bars show how well voxel preference could be classified when the transformation from

the SRM of the same visual area was used for prediction ("congruent", same as mid-gray bar

in **Figure 9**). Light bars show accuracy averaged across all classifications in which

transformation into the individual space of the test brain was based on an SRM from a

different visual area ("incongruent"). Accuracy is the fraction of correctly classified voxels

across all brains and error bars represent 95 % CIs. Binomial tests were used to test if observed

accuracies exceeded chance, z-tests were used for comparisons between congruency

conditions (asterisks denote p < .05, Holm-Šidák corrected for seven ROIs).

Figure 13

SRM searchlight map. SRMs were fit to patterns within local spheres (3 voxel radius) of brain

responses to the retinotopic mapping stimulus. After transforming every participant's dataset

into the common space, classifiers were used to predict the color of the viewed image using

only the information in the local activity pattern (BSC). Cross-validation was performed by

leaving out data from a different participant for testing on every iteration. Classification

accuracies are shown in warm colors on a standard MNI template for brain regions that

survived the whole-brain significance threshold of a binomial test (q < .05, FDR corrected).

Green marks all voxels falling within area hV4 in at least 25 % of the participants. The regions

where BSC of color yielded accuracies significantly above chance, namely near the calcarine

sulcus, were distinctly different from the location of hV4. This indicates that anatomical

alignment was not sufficient beyond earliest visual areas for BSC (e.g. in hV4).

1601

Figure 14

Binning analysis. Voxels within a ROI were assigned into a number of bins based on their polar

coordinates, i.e., either eccentricity or polar angle. Bin limits were chosen such that they were

equally spaced across the range of voxel coordinates. Different numbers of bins were used.

Within-subject classification was performed except that, instead of training and testing

classifiers on vectors of voxel responses, vectors of bin-wise averages of voxel responses were

used. In a control analysis voxels were randomly assigned to the bins. If a retinotopic bias

exists, one would expect that retinotopically based binning would yield higher classification

accuracy than random binning. Paired t-tests (df = 14) were used and error bands represent

95 % bootstrapped CI. Asterisks denote significance at $p < .05$ (Holm-Šidák corrected for 15

binning steps). In all ROIs where color could successfully be classified across subjects in the

BSC analysis also the binning analysis also showed a retinotopic bias when binning based on

eccentricity or polar angle (or both, see V1 and V2), thus confirming the results from our own

analysis. In addition, retinotopic binning yielded higher accuracies than random binning also

in LO2.

1617

1618

color classification across participants using limited number of voxels

luminance classification across participants using limited number of voxels

probability difference / %

probability difference / %