Leveraging non-structural data to predict structures of protein–ligand complexes

Joseph M. Paggi*[1,2,3,4], Julia A. Belk*[1,2,3,4], Scott A. Hollingsworth*[1,2,3,4], Nicolas Villanueva[6], Alexander S. Powers[1,2,3,4,5], Mary J. Clark[6], Augustine G. Chemparathy[1,2,3,4], Jonathan E. Tynan[1,2,3,4], Thomas K. Lau[1,2,3,4], Roger K. Sunahara[6], Ron O. Dror[1,2,3,4,†]

1. Department of Computer Science, Stanford University, Stanford, CA 94305, USA.
2. Department of Molecular and Cellular Physiology, Stanford University School of Medicine, Stanford, CA 94305, USA.
3. Department of Structural Biology, Stanford University School of Medicine, Stanford, CA 94305, USA.
4. Institute for Computational and Mathematical Engineering, Stanford University, Stanford, CA 94305, USA.
5. Department of Chemistry, Stanford University, Stanford, CA 94305, USA.
6. Department of Pharmacology, University of California San Diego School of Medicine, La Jolla, CA 92093, USA.

* These authors contributed equally to this work.
† Corresponding author. Email: ron.dror@stanford.edu

Abstract

Over the past fifty years, tremendous effort has been devoted to computational methods for predicting properties of ligands that bind macromolecular targets, a problem critical to rational drug design. Such methods generally fall into two categories: physics-based methods, which directly model ligand interactions with the target given the target's three-dimensional (3D) structure, and ligand-based methods, which predict ligand properties given experimental measurements for similar ligands. Here we present a rigorous statistical framework to combine these two sources of information. We develop a method to predict a ligand's pose—the 3D structure of the ligand bound to its protein target—that leverages a widely available source of information: a list of other ligands that are known to bind the same target but for which no 3D structure is available. This combination of physics-based and ligand-based modeling improves upon state-of-the-art pose prediction accuracy across all major families of drug targets. As an illustrative application, we predict binding poses of antipsychotics and validate the results experimentally. Our statistical framework and results suggest broad opportunities to predict diverse ligand properties using machine learning methods that draw on physical modeling and ligand data simultaneously.

Introduction

Binding of small-molecule ligands to proteins is one of the most fundamental processes in biology, and the great majority of drugs are ligands that exert their effects by binding to a target protein. Predicting properties of protein–ligand interactions—including three-dimensional (3D) structures, binding affinities, binding kinetics, selectivity, and functional effects—is critical both to the rational design of effective medicines and to solving major problems in molecular biology. An enormous amount of work has thus focused on the development of computational methods to predict these properties (1, 2).

Such computational methods generally fall into two categories. "Physics-based" approaches use a 3D structure of the target protein and exploit an understanding of the physics of protein–ligand interactions (3). "Ligand-based" approaches use experimental measurements for many ligands of a given property (e.g., affinity) at a given target and employ pattern matching to predict the corresponding property for other ligands (4, 5).

Can one combine these two paradigms, and the orthogonal sources of information they leverage, in a systematic, principled manner? This has proven challenging, particularly when making predictions for ligands substantially different from those for which experimental data is available. It is especially difficult when one wishes to predict properties different from those measured experimentally—e.g., to predict ligand properties that are difficult to determine experimentally by exploiting experimental data that is easy to collect.

Here we present a method, ComBind, that overcomes these obstacles to substantially improve prediction of a ligand's binding pose at a given target protein. Determining a ligand's binding pose—the three-dimensional coordinates of the ligand's atoms when bound to the target—is critical to structure-based optimization of the ligand's pharmacological properties, as well as to understanding how it influences its target. Indeed, knowledge of a ligand's binding pose is so advantageous that researchers in industry and academia often spend months or years to solve an experimental structure of a particular ligand in complex with a target protein.

Because experimental structure determination is time-consuming, expensive, and sometimes impossible, tremendous effort has been invested in the development of *in silico* "docking" methods for predicting ligand binding poses (6-15). These are physics-based approaches: given a structure of the target protein, they sample many candidate poses of a ligand and rank these poses using scoring functions that approximate the energetic favorability of each pose, typically by capturing interatomic interactions such as hydrogen bonds and van der Waals forces (**Fig. 1A**). Despite the development of dozens of docking software packages over the past 40 years, binding pose predictions are typically correct less than half the time for ligands substantially different from those in the experimental structures used for docking (**Supplementary Table 1**).

ComBind improves binding pose prediction by exploiting a widely available type of non-structural data: the identities of other ligands known to bind the same target (**Fig. 1B**). Collecting such data is typically far easier than structure determination. Indeed, such data is routinely collected in drug development campaigns and is already available in public databases such as ChEMBL for the vast majority of recognized drug targets (16).

How can a list of other ligands that bind to the target protein—but whose binding poses are unknown—be used to improve pose prediction? Medicinal chemists have long recognized that distinct ligands tend to bind a given protein in similar poses; even ligands sharing no common

substructure often form similar interactions with the target protein (**Fig. 2A**). This intuition has a
sound basis in physics. For example, the energetic favorability of a protein–ligand hydrogen
bond depends on the mobility of the protein atoms involved and their ability to form hydrogen
bonds with water in the absence of the ligand (17). These factors contribute similarly to binding
of different ligands but are difficult to predict from a static protein structure alone.

To develop ComBind, we first use a large set of experimentally determined structures to quantify
the medicinal chemist's intuition—in particular, to determine the probability that binding poses
for different ligands will share various features. We use the results to define a scoring function
that predicts the favorability of a set of binding poses comprising one pose for each ligand
known to bind the target protein. By contrast to the ComBind scoring function, scoring functions
typically utilized by docking software assign a score to the pose of a single ligand at a time; we
thus refer to them as per-ligand scoring functions. The ComBind scoring function takes into
account the similarities and differences between the poses of different ligands as well as the
energetic favorability of each ligand's pose, as evaluated by a per-ligand scoring function.

We benchmark ComBind by comparing its results to 245 experimentally determined ligand
binding poses across 30 proteins representing all major families of drug targets. ComBind
improves the pose prediction accuracy of state-of-the-art docking software for all major drug
target families. For G-protein-coupled receptors (GPCRs), which are of particular interest both
because they represent the largest family of drug targets and because their structures are
notoriously difficult to determine experimentally, ComBind selects a correct binding pose over
60% more frequently, increasing the probability of correct prediction from 47% to 76%.
ComBind's results could be improved further by utilizing proprietary data generated as part of a
drug discovery project (e.g., additional ligands found to bind the target).

We also illustrate the use of ComBind to predict the previously unknown binding poses of
several antipsychotics at the D_2 dopamine receptor (D_2R), an important drug target for which
experimental structure determination has proven difficult. We validate ComBind's predictions—
which differ from those of state-of-the-art docking software—using mutagenesis experiments.
The results reveal structural motifs determining the potency and subtype-selectivity of D_2R-
targeted drugs.

ComBind provides a rigorous statistical foundation for combining physics-based structural
modeling of protein-ligand interactions with inference based on experimental data for other
ligands. It effectively leverages data on ligands that share no common scaffold or substructure
with the ligand whose pose is predicted. It allows prediction of a difficult-to-determine ligand
property based on a completely different type of data for other ligands. This method thus
suggests a broad range of possibilities for combining physics-based and ligand-based approaches
to improve prediction of various ligand properties by exploiting diverse sources of data.

Results

Overview of method

Given several ligands known to bind a target, ComBind solves for all their binding poses
simultaneously. We use per-ligand docking software to generate a list of candidate poses for
each ligand. ComBind then selects a set of poses—one for each ligand—that optimizes the

ComBind scoring function. The ComBind scoring function considers both the favorability of
each ligand's pose, as assessed by a per-ligand scoring function, and the likelihood that a set of
poses sharing a given level of similarity will be correct or incorrect.

Here we use the commercial docking software package Glide (9, 10) to generate candidate poses
and assign a per-ligand score to each. We selected Glide because it is widely used in the
pharmaceutical industry and because it ranks among the most accurate docking packages in
comparative studies (18, 19). We emphasize, however, that the ComBind approach can utilize
any per-ligand scoring function and pose sampling strategy, including those implemented in any
per-ligand docking package.

Quantifying the similarity of binding poses for distinct ligands

We begin by quantifying the medicinal chemist's intuition that different ligands tend to adopt
structurally similar poses when binding the same target protein. We wish not only to measure the
similarity of correct poses of different ligands, but also to compare the similarity of correct poses
to that of other poses ranked highly by per-ligand docking software. We consider two notions of
similarity: similarity of protein–ligand interactions and similarity in position of common ligand
substructures.

We compiled a set of 385 protein–ligand complex structures for 28 target proteins representing
all major classes of small-molecule drug targets (**Supplementary Table 2**) (20). We docked
each of the ligands using Glide and selected the 100 most highly ranked poses for each ligand.
To reflect practical application of docking, we docked each ligand into an experimental structure
solved in the presence of a ligand distinct from any of those being docked ("cross-docking"; see
Methods). Our docking procedure did not utilize the experimentally determined poses of ligands
in any way.

For all pairs of ligands for each target protein, we compute the similarity between each pose of
one ligand and each pose of the other ligand. We use this data to calculate a probability
distribution over similarity values; we refer to this distribution as the reference distribution.

We also compute similarities between each pair of correct poses (again, one pose per ligand),
where a pose is considered correct if it is within 2.0 Å root mean squared deviation (RMSD) to
the experimentally determined pose. We use these data to calculate a second probability
distribution over similarity values, the native distribution. When calculating the native
distribution, we use correct poses from the lists generate by Glide instead of using the
experimentally determined poses directly, such that the similarity statistics we calculate will be
most applicable to candidate poses considered during computational pose prediction.

We evaluate pose similarity separately for different types of protein–ligand interactions:
hydrogen bonds, salt bridges, and hydrophobic contacts (**Fig. 2B, Supplementary Fig. 1A**).
Given a pair of poses, we evaluate the similarity for each interaction type by cataloging the set of
protein residues with which each ligand forms an interaction of the given type and then
comparing the sizes of the intersection and union of these sets. Their ratio (the Tanimoto
coefficient (21)) increases when shared interactions are formed and decreases when either ligand
forms an unshared interaction. To make this metric well-defined when neither ligand forms any
interactions of a particular type, we add pseudo counts. For all interaction types, the native
distribution exhibits higher similarity than the reference distribution—that is, pairs of correct

poses form more similar interactions than other pairs of poses ranked highly by the per-ligand
scoring function (**Fig. 2B**).

We define substructure similarity as the RMSD of atom positions of the largest chemical
substructure shared by a pair of ligands (**Supplementary Fig. 1B**). We evaluated substructure
similarity for pairs of ligands that shared a substructure at least half the size of the smaller ligand.
For this similarity metric, too, the native distribution exhibits higher similarity than the reference
distribution, indicating that the common substructure tends to be more similarly positioned in
pairs of correct poses than in other pairs of poses ranked highly by the per-ligand scoring
function (**Fig. 2C**).

These results suggest that the similarity of correct poses is not adequately captured by a state-of-
the-art per-ligand scoring function. In further support of this point, we also calculated probability
distributions of similarity between the poses that the per-ligand scoring function ranks first for
each ligand (**Supplementary Fig. 2**). We found that these distributions also exhibited lower
similarity than the corresponding native distributions.

Derivation of a statistical potential for sets of binding poses

We used the similarity distributions described in the previous section to derive a statistical
potential that—instead of acting on features of a single pose, as in previous docking software—
acts on a set of hypothesized poses, one for each ligand known to bind the target protein.

$E^{\text{ComBind}}(\text{Poses for a set of ligands}) =$

$(n-1) \sum_{\text{ligands}} E^{\text{dock}}(\text{pose})$

$+ \sum_{\text{ligand pairs}} \sum_{\substack{\text{similarity} \\ \text{types}}} -\log \dfrac{\text{frequency of pose pair similarity in native distribution}}{\text{frequency of pose pair similarity in reference distribution}},$

where n is the total number of ligands.

The first component evaluates the energetic favorability of each ligand's pose individually using
a per-ligand scoring function E^{dock} (e.g., a scoring function used in Glide or another docking
software package). The summation is over ligands known to bind the target protein, with "pose"
referring to the hypothesized pose for each ligand.

The second component rewards sets of poses with a degree of similarity that is more often
observed in correct poses than in other poses ranked highly by the per-ligand scoring function.
Here the outer summation is over pairs of distinct ligands known to bind the target protein, and
the inner summation is over the similarity measures shown in **Fig. 2B and 2C**: hydrogen bond
similarity, salt bridge similarity, hydrophobic contact similarity, and substructure similarity.
"Pose pair similarity" refers to the calculated similarity value of the given type for the
hypothesized poses of the given ligand pair. The "native distribution" and "reference
distribution" for each similarity type are determined as described above. The resulting negative
log likelihood ratios have the mathematical properties of an energy, namely that an additive
decrease in energy corresponds to a multiplicative increase in likelihood ratio, allowing for
straightforward integration with standard per-ligand docking scores, which are typically in units
of energy (**Supplementary Fig. 3**). For pairs of ligands that do not share a substructure at least

half the size of the smaller ligand, the substructure similarity term is not included in the
summation.

The second component acts as a correction to the first. If the per-ligand scoring function were
perfect, in the sense that it could perfectly distinguish correct poses from incorrect ones, the
terms in the second component would consistently assume values of zero. Because per-ligand
scoring functions remain imperfect—and, in particular, tend to underpredict the likelihood that a
set of ligands will adopt similar poses—the second component typically assumes non-zero
values.

Structure prediction informed by non-structural data

The ComBind pose prediction method identifies a set of binding poses—one for each of a set of
ligands known to bind the target protein—that minimizes the ComBind potential. More
specifically, given a target protein and a query ligand whose binding pose we wish to predict, we
proceed as follows:

1. Compile a set of other ligands known to bind the target protein (e.g., from a public
database such as ChEMBL or from ligands tested as part of a drug discovery project). We
refer to these as helper ligands.
2. Dock the query ligand and each helper ligand individually to the target protein (with a
per-ligand docking software package), generating many candidate poses and associated
docking scores for each ligand.
3. Determine the set of poses—one per ligand—that minimizes the ComBind potential. We
use an expectation-maximization algorithm for this purpose (see Methods).

As an illustrative example, we apply ComBind to predict binding poses for ligands at the β_1-
adrenergic receptor (β_1AR), the primary target of the beta blocker drugs that are widely used to
treat heart attack, heart failure, and hypertension. We selected 11 diverse ligands known to bind
β_1AR, including both beta blockers and beta agonists. We docked 11 distinct ligands to a
crystallographic β_1AR structure using Glide, producing up to 100 candidate poses for each
ligand. We then solved for a set of poses—one per ligand—that minimizes the ComBind
potential (**Fig. 3A**). The crystallographic β_1AR structure used for docking was determined in
complex with a ligand distinct from any of the 11 docked ligands. Crystallographic ligand poses
were not used in any way by Glide or ComBind.

Glide's top-ranked pose was correct for 4 of 11 ligands, whereas the pose selected by ComBind
was correct for 10 of 11 ligands (**Fig. 3B).** In ComBind's selected poses—as in experimentally
determined poses—most of the ligands form a salt bridge with D121 and hydrogen bonds with
S211 and N329 (**Fig. 3C**). In comparison, the poses ranked most highly by Glide's per-ligand
scoring function exhibited more varied hydrogen bonds and salt bridges (**Fig. 3C**).

We emphasize that ComBind does not require that all ligands adopt similar poses or form similar
interactions. ComBind correctly predicts, for example, that two of these β_1AR ligands do not
form a hydrogen bond with S211.

ComBind outperforms a state-of-the-art method on a diverse benchmark set

238 We benchmarked ComBind on a set of 245 protein–ligand complexes representing all major
239 families of drug targets. We took several steps to mimic a real-world use case. First, when
240 predicting the binding pose of a query ligand with ComBind, we used helper ligands selected

from the public ChEMBL database (16). We did not use any experimental information on poses of helper ligands; indeed, for the vast majority of helper ligands selected, poses have not been determined experimentally. Second, we never used a target protein structure determined in the presence of a ligand that shares a chemical scaffold with the query ligand, ensuring that we performed only "cross-docking" and avoided the easier but less practically relevant case of "self-docking" (see Methods). Finally, when predicting ligand binding poses at a given target protein, we omitted all structures involving that protein when constructing the distributions used to define the ComBind potential.

We evaluated two ways of choosing, from ChEMBL, helper ligands for use in ComBind: (1) a diverse set of ligands with the highest binding affinity ("high affinity"), and (2) the ligands sharing the largest substructure with the query ligand ("congeneric"). Both of these selection criteria lead to substantial performance improvements over Glide (**Fig 4**, **Supplementary Fig. 4**), indicating that ComBind could be applied effectively using either a diverse set of ligands identified from a high-throughput screen or a congeneric series of ligands generated during lead optimization.

ComBind's performance improves with the use of more helper ligands (up to 20, the maximum number we tested) (**Fig. 4B**, **Supplementary Fig. 4B**). Interestingly, ComBind substantially outperforms Glide even when using only a single helper ligand.

In the ComBind benchmark results described below (**Fig. 4A**), we used 20 helper ligands for each query ligand, selected from ChEMBL by the high-affinity criterion. When computing overall results, we averaged across target families, weighted the performance for each family by the fraction of FDA-approved drugs targeting that family (20).

On average, ComBind selects a correct pose for 57% of all ligands and 70% of ligands for which at least one correct pose was included among the list of candidates considered—a 30% improvement over Glide in both cases (**Supplementary Table 1**). ComBind improves pose prediction performance for all target families considered. Even at the individual target level, we find that use of ComBind hardly ever degrades performance: ComBind only reduced performance for one of the 30 targets considered, and this performance reduction was minor.

Removing any of the similarity types from the ComBind potential reduced ComBind's performance (**Supplementary Fig. 5**). In particular, both protein–ligand interaction similarity and substructure similarity contribute substantially to ComBind's accuracy. Protein–ligand interaction similarity is the more important of the two, particularly when using a diverse set of helper ligands.

Predicting binding poses of antipsychotics at the D_2 dopamine receptor

To illustrate the practical application of ComBind, we predicted the binding poses of three antipsychotic drugs—pimozide, benperidol, and spiperone—at their target, the D_2 dopamine receptor (D_2R). Knowledge of these binding poses could aid ongoing efforts to develop antipsychotics with improved pharmacological properties, including ligands that bind selectively to D_2R over other dopamine receptors (Butini et al., 2016; Moritz et al., 2018). Solving experimental structures of D_2R has proven difficult, despite decades of effort (Wang et al., 2018, Yin et al., 2020). At the time we made these predictions, the only available D_2R structure was for D_2R bound to risperidone (22), a ligand substantially different from those whose poses we wished to predict.

We predicted binding poses for pimozide, benperidol and spiperone, as well as the tool
compound mespiperone, using both Glide and ComBind (see Methods). For spiperone and
mespiperone, ComBind and Glide predict similar poses. For pimozide and benperidol, however,
ComBind's predictions are different from Glide's: a fluorobenzene ring of each compound is
positioned near the top of the binding pocket by Glide and near the bottom by ComBind (Fig.
5A,B, Supplementary Fig. 6A, B).

To test ComBind's predictions, we designed mutagenesis experiments. First, we tested a series of
mutations of Ser193 (S193), which is positioned uncomfortably close to the second
fluorobenzene ring of pimozide in ComBind's predicted pose but not in Glide's (Fig. 5C).
Indeed, mutating S193 to a larger residue (Val or Leu) decreases pimozide's affinity, while
mutating S193 to a smaller residue (Ala) increases pimozide's affinity. Such effects are not
observed for benperidol, which is identical to pimozide except that it lacks the fluorobenzene
ring that contacts S193 in pimozide (Fig. 5D). Indeed, benperidol's affinity actually increases
when S193 is mutated to a larger residue. These results are consistent with ComBind's predicted
poses but not with Glide's: Glide predicts that pimozide and benperidol position nearly identical
chemical groups in essentially identical positions near S193. Additional experiments involving
mutation of residues surrounding the top and bottom of the binding pocket also support
ComBind's predictions (Supplementary Fig. 6C).

Shortly before submission of this manuscript, a haloperidol-bound D_2R crystal structure
appeared (Fan et al., 2020). Haloperidol shares a common substructure with the ligands we
considered, and this substructure is positioned similarly in in the crystal structure and in
ComBind's predictions, further supporting the accuracy of these predictions.

Our results highlight a structural motif contributing to potent and selective binding to D_2R. The
antipsychotics we studied have picomolar affinity at D_2R and bind more tightly to D_2R than to
the D_3 dopamine receptor (D_3R). Haloperidol, by contrast, binds with weaker (nanomolar)
affinity and is not selective for D_2R over D_3R. Comparison of the binding poses reveals that the
primary difference in the protein–ligand interactions is that all of the antipsychotics we studied—
but not haloperidol—place a ring structure in the "extracellular vestibule," located above the
orthosteric site where dopamine binds. The extracellular vestibule has much higher sequence
diversity among the different dopamine receptors than does the orthosteric site, supporting the
hypothesis that ligand interactions with this region contribute to selectivity. Optimizing ligands
to strengthen these interactions could lead to drugs with greater selectivity for D_2R.

Discussion

We have introduced a statistical potential that acts on a set of structures for different protein-
ligand complexes, rather than on a single structure. We have used this potential to develop
ComBind, a method that increases the accuracy of binding pose prediction by simultaneously
considering the poses of multiple ligands known to bind the target.

Importantly, ComBind does not assume that all ligands considered bind in similar poses. Instead,
it considers both the favorability of each individual ligand's pose, as evaluated by a per-ligand
scoring function, and the tendency of different ligands to adopt similar poses, as determined by
analysis of hundreds of experimental structures. ComBind often predicts correctly that two

ligands position their common scaffold differently, or that they form substantially different
interactions with the binding pocket (**Supplementary Figs. 7 and 8**).

Applicability and robustness

ComBind is broadly applicable. When benchmarking ComBind, we simply selected, from the
ChEMBL database, helper ligands that bind to the same target as the query ligand, without
requiring that these ligands be similar in any way. For most major drug targets, numerous
binders have already been identified. Even for a completely novel target, several binders would
typically be identified in the very early stages of a drug discovery project by high-throughput
screening.

Binding pose prediction is important in many areas beyond drug discovery. These include the
study of biological phenomena such as cellular signaling (e.g., binding of hormones and
neurotransmitters), sensation (e.g., binding of odorants and flavorants), enzyme function (e.g.,
binding of nutrients and other metabolic substrates), and defense mechanisms (e.g., binding of
toxins and antibiotics). Pose prediction is also important to understanding the effects of genetic
variation on responses to both naturally occurring ligands and drugs, which is essential to
personalized medicine (23). In each of these cases, multiple ligands are typically known to bind
the targets of interest, and ComBind may thus be used to improve binding pose prediction.

ComBind is highly robust. This is illustrated by its accuracy in our benchmarks, which used
helper ligands selected automatically according to approximate affinity values listed in the
ChEMBL database. This data is noisy, not only because ligand affinities were measured by many
labs using different assays, but also because the data often includes values that were inputted
incorrectly (24, 25). In addition, ligands selected automatically from ChEMBL sometimes bind
to completely different binding pockets on the same target.

ComBind generally produces an accurate prediction for the query ligand even when no correct
candidate poses are generated for many helper ligands. **Supplementary Table 3** shows an
example in which the majority of the ligands considered had no correct candidate pose;
ComBind nevertheless outperformed per-ligand docking.

The per-ligand docking software used to generate and score individual ligand poses in our
current implementation of ComBind treats the protein as rigid. Nevertheless, ComBind generally
proves effective even when considering a set of ligands that bind diverse protein conformations.
For example, the β_1AR ligands considered in **Fig. 3** include both agonists, which bind
preferentially to the protein's active conformation, and inverse agonists, which bind
preferentially to its inactive conformation (**Supplementary Table 4**).

Relationship to previous work

ComBind builds upon several methods that combine ligand-based and physics-based information
in more limited settings. Three-dimensional quantitative structure-activity relationship (3D
QSAR) techniques, including field-based methods and 3D pharmacophore methods, are ligand-
based approaches that consider potential 3D conformations of many ligands (26-28). These
methods attempt to align ligands in three dimensions, but they do not require a structure of the
target protein, and even when such a structure is available, it is typically used only in a limited
way—e.g., to define excluded volume (29). 3D QSAR methods require data for a large number
of binders and are generally not applied to pose prediction.

ComBind also draws inspiration from previous methods that predict binding poses of multiple
known binders simultaneously. Some of these methods consider a congeneric series of ligands
and require that the shared scaffold is similarly placed (30, 31). Others use either the number of
similarly placed functional groups (32) or the number of shared interactions (33) between a set of
docked ligands as a scoring function, assuming that the ligands adopt maximally similar poses.
ComBind goes beyond these techniques in that it not only applies to any set of ligands but also
provides a principled method to combine information from per-ligand docking scores with
information on pose similarity across multiple ligands. This is essential to ComBind's success in
cases where ligands form substantially different interactions or position shared substructures
very differently (34). Likewise, ComBind provides a principled method to combine multiple
metrics of pose similarity. Indeed, ComBind's performance drops substantially if one omits per-
ligand docking scores, substructure similarity, or interaction similarity from its scoring function
(**Supplementary Fig. 5**).

ComBind, like many ligand-based approaches, may also be viewed as a machine learning
method (35). Most recent innovations in machine learning for drug discovery, including deep
learning methods, involve complex models with many parameters that are able to fit extremely
general functions. But this generality comes at a cost: such methods are typically effective only
in cases where ligand data is abundant. ComBind is designed to make efficient use of any
available ligand data by leveraging the physical priors encoded in structure-based approaches.
This allows ComBind to improve upon the performance of a state-of-the-art docking method
even when the list of other known binders is limited to a single ligand.

Performance

Our extensive benchmarks show that ComBind outperforms a state-of-the-art per-ligand pose
prediction method across all major families of drug targets. For individual targets, ComBind
often substantially improves pose prediction accuracy and hardly ever degrades it. Using
ComBind thus has little if any downside.

ComBind performs particularly well for certain families of targets. Its 60% improvement over
Glide for GPCRs is especially noteworthy, not only because GPCRs represent the targets of one-
third of all approved drugs—and a very large fraction of current drug discovery efforts—but also
because experimentally determining structures of GPCRs in complex with lead compounds is
often extremely difficult. Almost all experimentally determined structures of GPCRs are bound
to ligands that were carefully selected for their very high affinities and residence times, often
after structure determination with other ligands failed. More generally, ComBind appears to
deliver an especially large improvement in pose prediction accuracy for ligands that bind to
transmembrane domains of proteins, perhaps reflecting the deep, well-defined nature of these
binding pockets. Experimental structure prediction tends to be particularly challenging for
transmembrane proteins, highlighting ComBind's utility.

ComBind's performance could undoubtedly be improved further through use of curated or in-
house data. In particular, a careful human curator could (1) identify ligands that can most
confidently be classified as binders (e.g., based on multiple reports or on particularly reliable
data sources), (2) identify ligands demonstrated to bind in the same binding pocket (e.g., by
competition binding assays), and (3) remove data that was inputted incorrectly to a database. For
a major drug discovery project focused on a particular target, a substantial amount of additional
in-house data will often be available on ligands found to bind the target, and that data will

typically have been collected in a more uniform and consistent manner than data extracted from
multiple publications.

Skilled chemists can often improve the overall success rate of docking through careful manual
preparation of the protein structure—for example, by diligent placement of waters or
consideration of side chain rotamers. Such a procedure is subjective and was thus not employed
in our performance benchmarks. In our experience, however, careful manual preparation of
target structures improves ComBind's results even more than those of per-ligand docking
methods, because such preparation increases the accuracy of the helper ligand poses and thus the
value of the information gleaned from them.

A variety of "flexible docking" methods have been developed that allow deformation of the
target protein when sampling ligand poses (19, 36, 37). These methods have proven highly
valuable in cases where the user knows in advance that protein flexibility is important to binding
of the query ligand. When used as fully automated pose prediction methods without such prior
information, however, flexible docking methods generally underperform rigid docking methods
such as Glide, as observed in our benchmarks of the popular Induced Fit Docking method (36)
(**Supplementary Table 1)** and reported previously for other flexible docking methods (37). Such
methods are more likely to sample a correct pose but also more likely to sample incorrect poses
that outscore correct poses. The ComBind scoring function might address this problem by more
effectively selecting a correct pose from among the incorrect poses; this is a potential area for
future research.

Extensibility and future work

Because ComBind can use any per-ligand docking method for pose generation and scoring of
individual ligands, it will be able to take advantage of improvements to these methods. For
example, several recent methods use machine learning to fit scoring functions (38-40), and
others allow for binding pocket flexibility when generating candidate poses (8, 36).

Likewise, ComBind can be used with any pairwise pose similarity metric or combination thereof.
ComBind's performance could potentially be improved by using more fine-grained interaction
descriptors (41, 42) or by using similarity metrics based on field-based methods developed for
virtual screening (28, 43).

The statistical potential used by ComBind is sufficiently general that the method could be
extended to exploit other types of data, ranging from multiple experimental structures of the
protein in complex with different ligands to effects of protein mutation on ligand binding.
Likewise, future work might exploit the affinity of each known binder; we have not done so here
to avoid obscuring the general applicability of our method, as the affinity estimates available in
public databases are often determined by different techniques and thus difficult to compare to
one another.

Beyond binding pose prediction, our work suggests rich opportunities to improve prediction of
diverse ligand properties by combining physics-based and ligand-based modeling. For example,
both physics-based and ligand-based approaches are currently used to predict or rank ligand
binding affinities in order to enable virtual ligand screening. Physics-based approaches require
the use of various approximations that introduce error, while ligand-based approaches are limited
in their ability to predict affinities of ligands very different from those for which experimental
data is available. A careful combination of the two, perhaps based on the ComBind scoring

function, might outperform either one alone. Physical modeling allows ligand data to be used
more efficiently by facilitating representation of the ligands in terms of specific interactions they
form with the target, a level of abstraction where even chemically diverse ligands share features.
Indeed, such approaches might prove effective even for predicting functional activity values
whose physical basis is not known a priori. Further work will be necessary to explore these
possibilities.

Acknowledgements

461 We thank B. Kelly, N. Latorraca, A. Venkatakrishnan, and N. Sohoni for advice and guidance in
462 the early stages of the project, all members of the Dror lab for insightful comments, and J.
463 Javitch for providing materials for mutagenesis experiments. This work was supported by
464 National Institutes of Health grants R01 GM127359 (to R.O.D.), R01-GM083118 (to R.K.S.)
465 and U19-GM106990 (to R.K.S.), and by a Stanford Graduate Fellowship (to J.M.P.).

References

1. W. Yu, A. D. MacKerell, Jr., Computer-Aided Drug Design Methods. *Methods Mol Biol* **1520**, 85-106 (2017).

2. G. Sliwoski, S. Kothiwale, J. Meiler, E. W. Lowe, Jr., Computational methods in drug discovery. *Pharmacol Rev* **66**, 334-395 (2013).

3. J. Li, A. Fu, L. Zhang, An Overview of Scoring Functions Used for Protein-Ligand Interactions in Molecular Docking. *Interdiscip Sci* **11**, 320-328 (2019).

4. S. P. Leelananda, S. Lindert, Computational methods in drug discovery. *Beilstein J Org Chem* **12**, 2694-2718 (2016).

5. A. Cherkasov *et al.*, QSAR modeling: where have you been? Where are you going to? *Journal of medicinal chemistry* **57**, 4977-5010 (2014).

6. K. E. B. Platzer, F. Momany, H. Scheraga, CONFORMATIONAL ENERGY CALCULATIONS OF ENZYME-SUBSTRATE INTERACTIONS. II. Computation of the Binding Energy for Substrates in the Active Site of α-Chymotrypsin. *International Journal of Peptide and Protein Research* **4**, 201-219 (1972).

7. I. D. Kuntz, J. M. Blaney, S. J. Oatley, R. Langridge, T. E. Ferrin, A geometric approach to macromolecule-ligand interactions. *J Mol Biol* **161**, 269-288 (1982).

8. A. N. Jain, Surflex: fully automatic flexible molecular docking using a molecular similarity-based search engine. *Journal of medicinal chemistry* **46**, 499-511 (2003).

9. R. A. Friesner *et al.*, Extra precision glide: docking and scoring incorporating a model of hydrophobic enclosure for protein-ligand complexes. *Journal of medicinal chemistry* **49**, 6177-6196 (2006).

10. R. A. Friesner *et al.*, Glide: a new approach for rapid, accurate docking and scoring. 1. Method and assessment of docking accuracy. *Journal of medicinal chemistry* **47**, 1739-1749 (2004).

11. O. Trott, A. J. Olson, AutoDock Vina: improving the speed and accuracy of docking with a new scoring function, efficient optimization, and multithreading. *J Comput Chem* **31**, 455-461 (2010).

12. G. Jones, P. Willett, R. C. Glen, A. R. Leach, R. Taylor, Development and validation of a genetic algorithm for flexible docking. *Journal of molecular biology* **267**, 727-748 (1997).

13. M. Rarey, B. Kramer, T. Lengauer, G. Klebe, A fast flexible docking method using an incremental construction algorithm. *Journal of molecular biology* **261**, 470-489 (1996).

14.   W. J. Allen *et al.*, DOCK 6: Impact of new features and current docking performance. *J Comput Chem* **36**, 1132-1156 (2015).

15.   C. M. Venkatachalam, X. Jiang, T. Oldfield, M. Waldman, LigandFit: a novel method for the shape-directed rapid docking of ligands to protein active sites. *J Mol Graph Model* **21**, 289-307 (2003).

16.   A. Gaulton *et al.*, The ChEMBL database in 2017. *Nucleic Acids Res* **45**, D945-D954 (2017).

17.   C. Bissantz, B. Kuhn, M. Stahl, A medicinal chemist's guide to molecular interactions. *Journal of medicinal chemistry* **53**, 5061-5084 (2010).

18.   Z. Wang *et al.*, Comprehensive evaluation of ten docking programs on a diverse set of protein-ligand complexes: the prediction accuracy of sampling power and scoring power. *Phys Chem Chem Phys* **18**, 12964-12975 (2016).

19.   N. S. Pagadala, K. Syed, J. Tuszynski, Software for molecular docking: a review. *Biophys Rev* **9**, 91-102 (2017).

20.   R. Santos *et al.*, A comprehensive map of molecular drug targets. *Nature reviews. Drug discovery* **16**, 19-34 (2017).

21.   D. Bajusz, A. Rácz, K. Héberger, Why is Tanimoto index an appropriate choice for fingerprint-based similarity calculations? *J Cheminform* **7**, 20-20 (2015).

22.   S. Wang *et al.*, Structure of the D2 dopamine receptor bound to the atypical antipsychotic drug risperidone. *Nature* **555**, 269-273 (2018).

23.   A. S. Hauser *et al.*, Pharmacogenomics of GPCR Drug Targets. *Cell* **172**, 41-54.e19 (2018).

24.   C. Kramer, T. Kalliokoski, P. Gedeck, A. Vulpetti, The experimental uncertainty of heterogeneous public K(i) data. *Journal of medicinal chemistry* **55**, 5165-5173 (2012).

25.   G. Papadatos, A. Gaulton, A. Hersey, J. P. Overington, Activity, assay and target data curation and quality in the ChEMBL database. *Journal of computer-aided molecular design* **29**, 885-896 (2015).

26.   J. Verma, V. M. Khedkar, E. C. Coutinho, 3D-QSAR in drug design--a review. *Curr Top Med Chem* **10**, 95-115 (2010).

27.   R. D. Cramer, D. E. Patterson, J. D. Bunce, Comparative molecular field analysis (CoMFA). 1. Effect of shape on binding of steroids to carrier proteins. *J Am Chem Soc* **110**, 5959-5967 (1988).

28.   G. M. Sastry, S. L. Dixon, W. Sherman, Rapid shape-based ligand alignment and virtual
530   screening method based on atom/feature-pair similarities and volume overlap scoring.
531   *Journal of chemical information and modeling* **51**, 2455-2466 (2011).

532   29.   S. Alam, F. Khan, 3D-QSAR, Docking, ADME/Tox studies on Flavone analogs reveal
533   anticancer activity through Tankyrase inhibition. *Sci Rep* **9**, 5414-5414 (2019).

534   30.   D. Y. Fu, J. Meiler, RosettaLigandEnsemble: A Small-Molecule Ensemble-Driven Docking
535   Approach. *ACS omega* **3**, 3655-3664 (2018).

536   31.   M. Vieth, D. J. Cummins, DoMCoSAR: a novel approach for establishing the docking
537   mode that is consistent with the structure-activity relationship. Application to HIV-1
538   protease inhibitors and VEGF receptor tyrosine kinase inhibitors. *Journal of medicinal*
539   *chemistry* **43**, 3020-3032 (2000).

540   32.   I. Wallach, R. Lilien, Predicting multiple ligand binding modes using self-consistent
541   pharmacophore hypotheses. *Journal of chemical information and modeling* **49**, 2116-
542   2128 (2009).

543   33.   S. Renner, S. Derksen, S. Radestock, F. Morchen, Maximum common binding modes
544   (MCBM): consensus docking scoring using multiple ligand information and interaction
545   fingerprints. *Journal of chemical information and modeling* **48**, 319-332 (2008).

546   34.   S. Malhotra, J. Karanicolas, When Does Chemical Elaboration Induce a Ligand To Change
547   Its Binding Mode? *Journal of medicinal chemistry* **60**, 128-145 (2017).

548   35.   N. Fleming, How artificial intelligence is changing drug discovery. *Nature* **557**, S55-s57
549   (2018).

550   36.   W. Sherman, T. Day, M. P. Jacobson, R. A. Friesner, R. Farid, Novel procedure for
551   modeling ligand/receptor induced fit effects. *Journal of medicinal chemistry* **49**, 534-553
552   (2006).

553   37.   P. A. Ravindranath, S. Forli, D. S. Goodsell, A. J. Olson, M. F. Sanner, AutoDockFR:
554   Advances in Protein-Ligand Docking with Explicitly Specified Binding Site Flexibility. *PLoS*
555   *Comput Biol* **11**, e1004586 (2015).

556   38.   M. Ragoza, J. Hochuli, E. Idrobo, J. Sunseri, D. R. Koes, Protein-Ligand Scoring with
557   Convolutional Neural Networks. *Journal of chemical information and modeling* **57**, 942-
558   957 (2017).

559   39.   V. Chupakhin, G. Marcou, I. Baskin, A. Varnek, D. Rognan, Predicting ligand binding
560   modes from neural networks trained on protein-ligand interaction fingerprints. *Journal*
561   *of chemical information and modeling* **53**, 763-772 (2013).

562   40.   J. Lim *et al.*, Predicting Drug-Target Interaction Using a Novel Graph Neural Network
563   with 3D Structure-Embedded Graph Representation. *Journal of chemical information*
564   *and modeling* **59**, 3981-3988 (2019).

565   41.   C. Da, D. Kireev, Structural protein-ligand interaction fingerprints (SPLIF) for structure-
566   based virtual screening: method and benchmark study. *Journal of chemical information*
567   *and modeling* **54**, 2555-2561 (2014).

568   42.   P. Gainza *et al.*, Deciphering interaction fingerprints from protein molecular surfaces
569   using geometric deep learning. *Nat Methods* **17**, 184-192 (2020).

570   43.   A. E. Cleves, A. N. Jain, Quantitative surface field analysis: learning causal models to
571   predict ligand binding affinity and pose. *Journal of computer-aided molecular design*
572   10.1007/s10822-018-0126-x (2018).

573   44.   R. Wang, X. Fang, Y. Lu, C.-Y. Yang, S. Wang, The PDBbind database: methodologies and
574   updates. *Journal of medicinal chemistry* **48**, 4111-4119 (2005).

575   45.   M. C. Jones, Simple boundary correction for kernel density estimation. *Statistics and*
576   *Computing* **3**, 135-146 (1993).

577   46.   M. J. Sippl, Boltzmann's principle, knowledge-based mean fields and protein folding. An
578   approach to the computational determination of protein structures. *Journal of*
579   *computer-aided molecular design* **7**, 473-501 (1993).

580   47.   M. J. Sippl, Calculation of conformational ensembles from potentials of mean force. An
581   approach to the knowledge-based prediction of local structures in globular proteins. *J*
582   *Mol Biol* **213**, 859-883 (1990).

583   48.   R. Das, D. Baker, Automated de novo prediction of native-like RNA tertiary structures.
584   *Proc Natl Acad Sci U S A* **104**, 14664-14669 (2007).

585   49.   D. J. Hand, K. Yu, Idiot's Bayes: Not So Stupid after All? *International Statistical Review /*
586   *Revue Internationale de Statistique* **69**, 385-398 (2001).

Methods

Assembly of data for use in learning the ComBind scoring function

Curation of experimental protein–ligand complex structures

In order to learn the ComBind scoring function, we curated a set of protein–ligand complex structures representing each of the major drug targets catalogued by Santos *et al.*, 2017 (**Supplementary Table 2**). This set of target proteins was chosen through a combination of manual curation and adaptation of the PDBbind refined set (44). For each target, we included up to 21 structures, each with a distinct ligand bound, selecting the structures with alphabetically lowest PDB code when more than 21 were available. Structures with duplicate ligands, mutant proteins, or no small molecule in the orthosteric site were excluded.

Generation of docked poses

For all of the results presented in this study, we performed "cross-docking." Specifically, for each target, we chose the structure with the alphabetically first PDB code as the input 3D structure of the protein and then docked other ligands to this reference structure. This simulates a real-world application where only one structure of the target protein is available, and the user wants to predict poses for ligands not present in that structure.

To prepare protein structures for use in docking, we first prepared structures using the Schrodinger suite. All waters were removed, the tautomeric state of the ligand present in the experimentally determined structure was assigned using Epik at pH 7.0 +/– 2.0, hydrogen bonds were optimized, and energy minimization was performed with non-hydrogen atoms constrained to an RMSD of less than 0.3 Å from the initial structure. The ligand was then removed.

For ligands to be docked, the tautomeric state was assigned using Epik tool at target pH 7.0 +/– 2.0. The single most favorable state was considered for docking. Torsion angles were randomized before docking.

Ligands were docked using default Glide SP settings except that "Enhanced Sampling" was set to 4, quadrupling the number of ligand conformers considered. For each ligand, we produced up to the 100 most highly ranked poses (for some ligands fewer than 100 poses passed Glide's internal filters). We also considered using Glide XP but found that Glide XP produced a correct candidate pose substantially less often than Glide SP (**Supplementary Table 1**). Glide XP and SP performed similarly in terms of how frequently the top-ranked pose is correct. Additionally, we considered using Induced Fit Docking (IFD). While IFD produced at least one correct candidate pose more often than Glide SP, the performance in terms of how often the top-ranked pose is correct was worse.

Determining the quality of docked poses

The accuracy of each pose was quantified by the non-hydrogen-atom RMSD from the experimentally determined pose. To compute the RMSD, each complex was aligned to the structure used for docking based on non-hydrogen-atoms within 15 Å of the ligand, and the RMSD was then computed between the docked pose and the same ligand's pose in the aligned complex. We denote poses at most 2.0 Å RMSD from their aligned experimentally determined pose as being "near-native" or "correct."

Quantifying the similarity of binding poses for distinct ligands

Protein–ligand interaction similarity

Three interaction types were considered: hydrogen bonds, salt bridges, and hydrophobic
contacts. We designed quantitative measures to assess the presence of these interactions between
the ligand and a given protein residue (**Supplementary Table 5**). The hydrogen bond and salt
bridge interaction measures were designed to give a value of 1 for interactions meeting
established criteria (17). A soft boundary was added to give borderline cases values between 0
and 1, in order to prevent discontinuities. The hydrophobic contact measure approximates the
hydrophobic surface contact area by considering the number of protein–ligand atom pairs in
contact with each other. Again, a soft boundary (in this case, between an atom pair being or not
being in contact) was used to prevent very similar poses from leading to very different values.
We denote the interaction value for interaction type k, for pose ℓ_i of ligand i, with protein
residue r as $X_r^{(k)}(\ell_i)$.

Interaction similarities for a pair of poses (for two different ligands bound to the same target
protein) were computed separately for each interaction type. The interactions made between the
ligand and each residue of the target protein residue were tabulated and then the similarity
between the resulting lists for each pose was measured by the Tanimoto coefficient (21). The
Tanimoto coefficient was modified by the addition of pseudo counts, which serve to make the
metric well defined if neither ligand forms a particular type of interaction and to reward poses
that share larger numbers of interactions in absolute terms. We define the interaction similarity,
for interaction type k between a pair of poses ℓ_i, ℓ_j (for ligands i and j, respectively), as

649
$$s^{(k)}(\ell_i, \ell_j) = \frac{1 + \sum_{r \in R} \sqrt{X_r^{(k)}(\ell_i) X_r^{(k)}(\ell_j)}}{2 + \sum_{r \in R}\left[X_r^{(k)}(\ell_i) + X_r^{(k)}(\ell_j)\right] - \sum_{r \in R} \sqrt{X_r^{(k)}(\ell_i) X_r^{(k)}(\ell_j)}},$$

where R is the set of all protein residues.

When computing hydrogen bond similarity, a case where a given protein residue acts as a
hydrogen bond donor for one ligand and a hydrogen bond acceptor for another ligand is not
considered a shared interaction.

Substructure similarity

To compute the substructure similarity for a pair of candidate poses, the maximum common
substructure of the two ligands is identified using Canvas (Schrodinger LLC) and then mapped
onto each candidate pose. Finally, the RMSD between these two sets of atoms is computed and
used as the measure of substructure similarity. We defined custom atom and bond types for
computation of the common scaffold (**Supplementary Table 6**). Scaffold similarity is not
considered for pairs of ligands with a maximum common substructure of less than half the size
of the smaller ligand. Hydrogen atoms were not included in the substructure nor when
determining the total number of atoms in each ligand.

Computation of similarity statistics

Using the set of protein–ligand complex structures described above, we characterized the extent
to which distinct ligands binding a common target adopt similar poses, as quantified by the

interaction and substructure similarity metrics described above. (We note that the three ion
channel targets were not included in these statistics because they were added after the rest of our
study had been completed.)

When computing these statistics, we docked the ligands using Glide and then identified poses
that are near-native among the candidate poses ranked in the top 100 by Glide. We used these
docked poses, as opposed to the experimentally determined pose, in order to ensure that the
statistics will be applicable to the scoring of candidate poses generated by Glide. We computed
the empirical distribution of each similarity type across all pairs of near-native poses using a
Gaussian kernel density estimate with standard deviation of 0.03 for interaction similarities and
0.18 for substructure similarities. To reduce bias near the boundaries, we applied reflected
boundary conditions(45). We capped substructure similarities at 6 Å (that is, substructure
similarities greater than 6 Å were set to 6 Å), as the sparsity of near-native pose pairs for higher
values led to overly rough distributions. We denote the similarity distribution over near-native
poses for interaction type k as $f_k(x; \text{Native})$.

We computed equivalent similarity distributions using all pairs of candidate poses produced by
Glide, regardless of whether they are near-native. We denote the resulting distributions as
$f_k(x; \text{Reference})$.

To combine the distributions for the four similarity types into a single joint distribution, we
assume that the interaction types are conditionally independent and express the joint distribution
as a product of the distributions for each interaction type. That is:

686
$$f\big(s(\ell_i, \ell_j); \text{Native}\big) = \prod_k f_k\big(s^{(k)}(\ell_i, \ell_j); \text{Native}\big), \text{ and}$$

687
$$f\big(s(\ell_i, \ell_j); \text{Reference}\big) = \prod_k f_k\big(s^{(k)}(\ell_i, \ell_j); \text{Reference}\big).$$

where $s(\ell_i, \ell_j)$ is the vector of $s^{(k)}(\ell_i, \ell_j)$'s for each similarity type k.

Description of the ComBind method

The ComBind score

We describe a hypothesized set of binding poses of a set of n ligands as $L = \ell_1, \ell_2, \dots, \ell_n$, where
ℓ_i specifies the hypothesized pose for ligand i.

Per-ligand scoring functions, which consider each ligand independently, would determine an
optimal set of poses $\hat{L}$ by choosing the binding pose with minimum docking score for each ligand
or, equivalently, by minimizing

696
$$E^{\text{dock}}(L) = \sum_{i=1}^{n} E^{\text{dock}}(\ell_i)$$

697   where $E^{\text{dock}}(\ell_i)$ is the output of a per-ligand scoring function (such as that reported by Glide)
698   for pose ℓ_i of ligand i.

699   In our method, we add pairwise terms that tend to favor sets of similar poses:

700
$$E^{\text{ComBind}}(L) = (n-1)E^{\text{dock}}(L) + \sum_{(i,j), i \neq j} -\log \frac{f\big(s(\ell_i, \ell_j); \text{Native}\big)}{f\big(s(\ell_i, \ell_j); \text{Reference}\big)}.$$

Intuitively, these pairwise terms reward pose pairs with similarity values more often observed in
near-native (correct) pose pairs than in reference pose pairs (i.e., pose pairs chosen at random
from among all candidates). The idea of comparing the distribution of features in correct
solutions to the distribution in all possible solutions has been used in statistical potentials for
biomolecular structure prediction(46-48) and in the naïve Bayes machine learning model(49).
We weight the docking scores by the number of ligands minus 1, in order to hold the relative
contribution of singleton and pairwise terms constant for different numbers of helper ligands.

Consistent with their reported units of kcal/mol, we find that Glide scores have the mathematical
properties of an energy; namely, the negative log likelihood ratio of a pose being near-native is
linear in its Glide score (**Supplementary Fig. 3**). By construction, the pairwise terms we
introduce in this study also have this property. This congruence implies that these singleton and
pairwise terms can be additively combined (as this is the equivalent of multiplying likelihood
ratios).

In general, it could be that the per-ligand docking scores need to be scaled by a constant factor in
order to be consistent with the pairwise terms. For example, if the docking scores were on
average 10 times the negative log likelihood ratio of a pose being near-native, they would need
to be scaled by 1/10. This constant factor can be identified by performing logistic regression with
the docking scores as features and whether each pose is near-native as the response. For Glide
scores, the appropriate constant is close to 1 ($1/0.9 = 1.1$) (**Supplementary Fig. 3**), and we chose
to set it to 1 for simplicity.

Optimization procedure

We use coordinate descent to compute a set of poses that minimizes the ComBind score. At first,
L is randomly initialized. L is then iteratively improved by iterating through the ligands, in a
random order, and updating the selected ligand's pose to the argument minimum of
$E^{\mathrm{ComBind}}(L)$ assuming that the other poses in L are correct. This procedure is repeated until no
more updates can be made. Each update can be computed efficiently because it depends only on
the partial contribution of the selected ligand's pose to the ComBind score:

$$
728 \quad \hat{\ell}_q = \operatorname*{argmin}_{\ell_q} \left[(n-1)E^{\mathrm{dock}}(\ell_q) + \sum_{i \neq q} -\log \frac{f\big(s(\ell_q, \ell_i); \text{Native}\big)}{f\big(s(\ell_q, \ell_i); \text{Reference}\big)} \right].
$$

In order to account for the non-convex nature of the ComBind score, we repeat this algorithm
from 500 initial configurations, explicitly including the initial configuration corresponding to the
generic scoring function predictions at least once and return the best scoring configuration.
Empirically this procedure converges to the same result over multiple runs.

Benchmarking

We evaluated the performance of ComBind on the 30 target proteins listed in **Supplementary**
Table 2. We only considered ligands that have less than 50% scaffold overlap with the ligand
that was originally present in the experimental structure used for docking. We found that ligands
with higher scaffold overlap were substantially easier to dock, likely due to the binding pocket
being well shaped to accommodate the similar ligand (**Supplementary Table 1**). Additionally,
we only consider ligands for which there is at least one correct candidate pose, since only in
these cases is it possible for either ComBind or Glide to make a correct prediction. Importantly,

this subsetting was only done for the query ligands, not the helper ligands downloaded from
ChEMBL described below.

For each of the 245 unique ligands meeting these criteria, we identified other ligands known to
bind the respective target protein from the ChEMBL database and then used ComBind to jointly
predict their binding poses. Importantly, when evaluating the performance of our method on a
particular target protein, we excluded the data for that target protein from the similarity statistics.

Selection of helper ligands

For all targets, we downloaded K_i or IC_{50} data (whichever was more numerous) from ChEMBL
(16). We removed ligands that did not meet the following criteria: a ChEMBL confidence score
of 9 (the highest value), molecular weight < 800 Da, and K_i or IC_{50} < 1 µM. Ligand structures
were generated from the SMILES strings provided by ChEMBL.

We benchmarked two criteria for selecting which ChEMBL ligands to use as helper ligands for
each query ligand: (1) the highest affinity binders that do not share a chemical scaffold, and (2)
the ligands that share the largest chemical substructure with the query ligand. To define the size
of the common substructure, we used the same maximum common substructure definition as that
used to compute substructure similarity. For selection method (1), we added helper ligands in
order of affinity, not adding a ligand if it has greater than 80% substructure overlap with any
ligand already in the selected set of helpers.

The benchmarking results presented in the figures were obtained using the following ligand
selection criteria and number of helper ligands: **Fig. 4A** and **Supplementary Fig. 5A**: 20 helper
ligands selected using criterion (1); **Fig. 4B**: the indicated number of ligands selected using
criterion (1); **Supplementary Fig. 4A** and **Supplementary Fig. 5B**: 20 helper ligands selected
using criterion (2); and **Supplementary Fig. 4B**: the indicated number of ligands selected using
criterion (2). For a handful of targets, fewer than 20 helper ligands were available meeting our
criteria. In these cases, we used the minimum of the indicated number of ligands and the number
of available ligands. Targets with only one ligand are omitted from **Fig. 4A** and **Supplementary
Fig. 4A**.

Performance evaluation

769 We developed an overall performance metric to represent the expected performance in drug
770 development campaigns. For each protein family, we computed the average performance, then
771 weighted each by the fraction of FDA-approved drugs targeting the protein family, as reported in
772 Santos *et al.*, 2017.

Prediction of binding poses of antipsychotics at the D_2R

Execution of the ComBind method

We predicted binding poses for the typical antipsychotics spiperone, mespiperone, benperidol,
and pimozide at the D_2 dopamine receptor (D_2R). We prepared the ligands using the Schrodinger
ligprep tool, considering the unprotonated tautomer and both inversions of the protonated
tautomer. The same docking protocol was used as described above, except that the top 300 poses
were considered by ComBind, in order to account for the use of the 3 tautomeric states of the
ligand.

D_2 Dopamine receptor mutagenesis

Wild type (wt) human D_2R in pcDNA3.1 was kindly provided by the laboratory of Jonathan
Javitch (Columbia University, New York, NY). Mutations were introduced through of a
modified QuikChange (Stratagene, La Jolla, CA) mutagenesis protocol using the following
primers V91F: 5'-GGTCATGCCCTGGTTTGTCTACCTGG-3', S193A:
5'CGTGGTCTACGCCTCCATCGTCTCC-3', S193V: 5'-
CGTGGTCTACGTCTCCATCGTCTCC-3', S193L: 5'-
CGTGGTCTACCTCTCCATCGTCTCC-3', W100L: 5'-
GGTAGGTGAGTTGAAATTCAGCAGG-3', C118M: 5'-
GGACGTCATGATGATGACGGCGAGC-3', W386F: 5'-
CGTGTTCATCATCTGCTTTCTGCCCTTCTTC-3', F389L: 5'-
GCTGGCTGCCCTTATTCATCACACACATCC-3'.

Membrane preparation and radioligand binding

Membranes were isolated from HEK293T cells transiently transfected with D_2R(wt) or D_2R-
mutants. Briefly, cells were harvested 48 hr post-transfection (with Lipofectamine 2000), rinsed
with PBS, lifted with harvesting buffer (0.68 mM EDTA, 150 mM NaCl, 20 mM HEPES, pH
7.4), and centrifuged at 200 x g for 3 min. The cells were resuspended in ice cold homogenizing
buffer (10 mM HEPES, pH 7.4, 100 mM NaCl, 0.5 mM EGTA), homogenized using a Tissue
Tearer (BioSpec, Bartlesville, OK) for 30 sec, and centrifuged at 20,000 x g for 20 min.
Membranes were resuspended in Binding Buffer (20 mM HEPES, pH 7.4, 100 mM NaCl) using
a Dounce glass homogenizer , flash frozen in liquid N_2 and stored at –80ºC.

For saturation binding assays, cell membranes (0.6–20 μg per well, depending on the mutant)
were incubated for 1.5 hr at 30ºC with [^{3}H]-spiperone (Perkin Elmer, Waltham, MA) (0.02–12
nM, depending on the Kd of the D_2R mutant) in Binding Buffer containing 0.001% BSA, 1 mM
ascorbic acid, and 100 nM GDP with or without 20 μM (+)butaclamol (to determine non-
specific binding). For competition binding assays, cell membranes (0.6–20 μg, depending on the
D_2R mutant) were incubated for 1.5 h at 30ºC with [^{3}H]-spiperone (0.05–0.6 nM, depending on
the Kd of the D_2R mutant) in Binding Buffer containing 0.001% BSA, 1 mM ascorbic acid, 100
nM GDP and 0–0.1 nM test compound (purchased from Millipore-Sigma, St Louis, MO), or 20
μM (+)butaclamol (to determine non-specific binding). Sample membranes were harvested by
vacuum filtration on 96-well GF/C filter plates, washed with ice cold binding buffer to remove
unbound radioligand, and allowed to dry before adding Microscint 0 (Perkin Elmer, Waltham,
MA) for counting in a Top Count Scintillation Counter (Perkin Elmer/Packard, Waltham, MA).
Data were fit to a one site binding curve to determine Kd for [^{3}H]-spiperone saturations, or to a
one-site competition binding curve to calculate Ki of test compounds using Prism (GraphPad,
San Diego CA).

Figures

Figure 1: ComBind leverages non-structural data to improve ligand binding pose
predictions. (A) Standard docking methods take as input the chemical structure of the query
ligand and the 3D structure of the target protein and predict a binding pose using a per-ligand
scoring function. (B) ComBind additionally considers other ligands known to bind the target
protein (whose binding poses are not known), resulting in more accurate predictions. For clarity,
hydrogen and fluorine atoms are not shown in the 3D renderings.

A Distinct ligands tend to form similar interactions with the target

Per-ligand docking underestimates the structural similarity of distinct ligands' binding poses

Figure 2: Distinct ligands that bind to a given target protein often adopt similar binding poses and do so more frequently than predicted by a state-of-the-art per-ligand docking method. (A) Chemically distinct ligands share key interactions with the mineralocorticoid receptor (PDB IDs: 2AA2, 5L7E, 5MWP). (B) Across a set of 3115 ligand pairs, interaction similarities are generally higher in pairs of correct poses than in pairs including all poses ranked highly by a per-ligand scoring function. Shading depicts the per-target standard error of the mean. (C) Across a set of 690 ligand pairs with a shared substructure, the substructure tends to be placed more similarly in correct poses than in other poses ranked highly by a per-ligand scoring function. Substructure similarity for a pose pair was defined as the root mean square deviation (RMSD) between the largest substructure shared by the ligands (see Methods).

Figure 3: ComBind discovers and rewards key interactions shared by distinct ligands. (A) Whereas per-ligand docking considers each ligand individually, ComBind jointly selects poses for all ligands, optimizing for poses that are individually favorable according to a per-ligand scoring function and together form a coherent set of protein–ligand interactions. (B) We tested the ability of ComBind to predict the poses of 11 ligands that bind β_1AR. Each dot corresponds to a single ligand, with the dot's position indicating the error in the predicted pose (RMSD from the experimentally determined pose) for ComBind and for state-of-the art per-ligand docking software (Glide). A pose is considered correct if its RMSD is $\leq$ 2.0 Å (dashed lines). ComBind predicts a substantially more accurate pose than Glide for 7 of the 11 ligands. (C) The set of residues with which each ligand forms salt bridges or hydrogen bonds when positioned in its experimentally determined pose (top), the pose predicted by per-ligand docking (left), and the pose predicted by ComBind (right).

Figure 4: ComBind outperforms per-ligand docking on a diverse benchmark set.
Performance of ComBind, as compared to a per-ligand scoring function, using helper ligands
selected automatically from ChEMBL. All results are for "cross-docking" (the query ligand is
docked into a structure determined in the presence of a distinct ligand). (A) Performance per
target protein, target protein family (GPCRs, ion channels, etc.), and overall. Green disks and
black circles indicate performance (fraction of ligands whose pose is predicted correctly) for
ComBind and a state-of-the art per-ligand docking software package (Glide), respectively. (B)
Performance as a function of the number of helper ligands. When using no helper ligands,
ComBind is equivalent to Glide (dashed horizontal line).

Figure 5: Prediction and validation of the binding poses of antipsychotics at the D$_2$ dopamine receptor. Glide (A) and ComBind (B) predict very different binding poses for pimozide (and for benperidol; see **Supplementary Fig. 6**). (C) Mutagenesis experiments validate ComBind's predictions. In ComBind's predicted pose for pimozide, its "extra" ring is uncomfortably close to S193, such that decreasing the size of residue 193 (S193A) increases pimozide's binding affinity and increasing the size of residue 193 (S193V and S193L) decreases pimozide's binding affinity. WT represents the wild-type (unmutated) receptor. (D) As a control, we verified that benperidol—which lacks this "extra" ring but is otherwise identical to pimozide—does not exhibit the same trend. Error bars show standard error of the mean. See **Supplementary Fig. 6** for additional data.

Supplementary Figures

Supplementary Figure 1: Examples of interaction similarity and substructure similarity computation. (A) Comparison of interactions formed by two ligands bound to *PLK1*, for a pair of correct poses (top) and randomly chosen poses (bottom). (B) Overlays of two ligands that share a common substructure bound to *BRD4* for correct docked poses (top) and randomly chosen highly ranked docked poses (bottom).

Supplementary Figure 2: A state-of-the-art per-ligand scoring function (Glide) underestimates the similarity of binding poses of different ligands binding to the same target protein. (A) and (B) are identical to Fig. 2C and D, respectively, except that the black curves in this figure are computed using only the pose ranked first by Glide for each ligand.

y = 0.9x + 7.5

Supplementary Figure 3: The output of Glide's per-ligand scoring functions is in units of energy similar to those of ComBind's pairwise potential. A quantile plot showing the relationship between Glide scores and the negative log likelihood ratio of a pose being correct. For each of the docked poses of each ligand in our benchmark set, we computed the Glide score and determined whether the pose was correct. We split all of the resulting data into quantiles based on Glide scores, with each quantile containing 100 poses. Each point in the plot represents the mean Glide score and negative log likelihood ratio for a given quantile. The red line shows the best-fit linear relationship between these two quantities as determined by logistic regression.

A Performance of ComBind vs. per-ligand docking

892 **Supplementary Figure 4: ComBind performance using a congeneric series of ligands.** This
893 figure corresponds to **Fig. 4,** but with helper ligands selected from ChEMBL ligands according
894 to the "congeneric" criterion (i.e., ligands that share the greatest common substructure with the
895 query) instead of the "high affinity" criterion.

Supplementary Figure 5: Importance of components of the ComBind scoring function.
Performance using various components of the ComBind scoring function when using helper
ligands chosen by either the high-affinity (A) or congeneric (B) ChEMBL ligand selection
criterion. ComBind uses per-ligand docking scores, similarity scores based on interactions, and
similarity scores based on relative positions of shared substructures. "Per-ligand docking"
(Glide) omits all similarity scores. The remaining bars ("No Per-Ligand Scores," "No
Substructure," and "No Interactions") show the effects of omitting per-ligand scores,
substructure position similarity scores, and protein–ligand interaction similarity scores,
respectively, from the ComBind potential.

907
Supplementary Figure 6: Prediction and validation of the binding poses of antipsychotics
at the D$_2$ dopamine receptor—additional data. (A) Binding poses of pimozide, benperidol,
spiperone, and mespiperone as predicted by Glide. (B) Binding poses of the same ligands, as
predicted by ComBind. (C) Results of mutagenesis studies designed to test ComBind's binding
pose predictions. Ligands are color-coded as in panel A. Error bars show standard error of the
mean. S193 was mutated to A, S, V and L; these results are discussed in the main text. Unlike
Glide, ComBind predicts that all four ligands will position a fluorobenzene ring at the bottom of
the binding pocket, packing favorably against Trp386 (W386). Indeed, mutating W386 to a
smaller residue (Phe) reduced affinity to a similar extent for all of the ligands, with a slightly
smaller effect for pimozide, which packs less tightly against W386 according to ComBind's
prediction. At the top of the ligand binding pocket, near Val91 (V91) and Trp100 (W100),
ComBind predicts that the pimozide and benperidol will place identical functional groups that
differ somewhat from those of spiperone and mespiperone. Indeed, mutation of these residues
affects pimozide and benperidol slightly differently from spiperone and mespiperone.

A   Experimental pose for ligand 1   **B**   Experimental pose for ligand 2

C   ComBind predicted pose for ligand 1   **D**   ComBind predicted pose for ligand 2

Supplementary Figure 7: Example of a case where ComBind correctly predicts that a
shared chemical scaffold is placed differently for different ligands. We show two ligands that
bind the kinase CDK2. These ligands share a common scaffold but adopt significantly different
binding poses. In A and B, we show their experimentally determined poses (PDB: 1JSV and
PDB: 1DI8, respectively). In C and D, we show the poses predicted by ComBind for the two
ligands. The shared scaffold is shown in the thicker sticks and parts of the ligands that differ are
shown in the thinner lines.

A Experimental pose for ligand 1   **B** Experimental pose for ligand 2

C ComBind's predicted pose for ligand 1   **D** ComBind's predicted pose for ligand 2

E Candidate pose for ligand 1 that forms salt bridge matching ligand 2

Supplementary Figure 8: Example of a case where ComBind correctly predicts that ligands form distinct interactions with the protein. We ran ComBind for 20 ligands that bind F10. While most of the ligands have a positively charged group, only some of them position it to form a salt bridge with D189 (e.g., ligand 1, shown in panel A) while others orient it in the complete opposite direction (e.g., ligand 2, shown in panel B). ComBind correctly predicts both binding poses (C, D). (E) One of the candidate poses for ligand 1 forms the same salt bridge as ligand 2. ComBind correctly avoided choosing this pose, even though choosing it would have led to more similar interactions between ligands.

Supplementary Tables

Supplementary Table 1: Performance of Glide SP and Glide XP on our benchmark set. The data presented in this table does not include ligands that share a substantially sized chemical scaffold with the ligand present in the experimental structure used for docking. Including such ligands increases the success rate for both Glide SP and Glide XP (to 49%, 53%, 47%, respectively).

# Ligands	Is the top-ranked pose correct?			Is any candidate pose correct?		
	SP	*XP*	*IFD*	*SP*	*XP*	*IFD*
327	44%	45%	40%	81%	63%	81%

Supplementary Table 2: Structural data used for benchmarking ComBind. From left to
right, columns represent: Protein family, protein name, Uniprot ID, ChEMBL target ID, number
of ligands, number of ligands that do not share a scaffold with the ligand present in the
experimental structure used for docking, and number of ligands that do not share a scaffold with
the ligand present in the experimental structure used for docking and have at least one correct
candidate pose. The right-most column corresponds to the number of ligands included in our
benchmarks for each target protein.

PROTEIN FAMILY	PROTEIN	UNIPROT	CHEMBL	# TOTAL LIGANDS	# DIVERSE LIGANDS	# DIVERSE LIGANDS WITH AT LEAST ONE CORRECT CANDIDATE POSE
GPCR	5-HT$_{2B}$	P41595	CHEMBL1833	5	5	5
	β$_1$AR	P07700	CHEMBL213	11	6	6
	β$_2$AR	P07550	CHEMBL210	7	4	4
	mGluR5	P41594	CHEMBL2564	4	3	1
	Smo	Q99835	CHEMBL5971	4	3	2
ION CHANNEL	GluN1/2A	Q05586 Q12879	CHEMBL1907604	8	6	4
	GluR-2	P19491	CHEMBL3503	15	7	6
	GluK1	P22756	CHEMBL2919	18	18	15
TRANSPORTER	DAT	Q7K4Y6	CHEMBL238	8	8	7
	SERT	P31645	CHEMBL228	4	4	4
	GLUT1	P11166	CHEMBL2535	2	1	1
NUCLEAR RECEPTOR	ER	P03372	CHEMBL206	20	14	12
	GR	P04150	CHEMBL2034	16	10	8
	MR	P08235	CHEMBL1994	12	10	9
	AR	P10275	CHEMBL1871	19	12	10
	VDR	P11473	CHEMBL1977	20	3	3
PROTEASE	F2	P00734	CHEMBL204	20	19	15
	F10	P00742	CHEMBL244	20	19	12
	PLAU	P00749	CHEMBL3286	20	20	19
	P00760	P00760	CHEMBL3769	20	19	16
	BACE1	P56817	CHEMBL4822	20	19	7

PHOSPHORYLASE	PYGM	P00489	CHEMBL4696	20	5	4
PHOSPHATASE	PTPN1	P18031	CHEMBL335	20	19	8
TRANSCRIPTION FACTOR	BRD4	O60885	CHEMBL1163125	16	13	7
CHAPERONE	HSP90-α	P07900	CHEMBL3880	20	16	10
PHOSPHO-DIESTERASE	PDE10A	Q9Y233	CHEMBL4409	20	19	17
RECEPTOR	σ1	Q99720	CHEMBL287	4	4	3
ELATASE	ELANE	P08246	CHEMBL248	8	1	1
REDUCTASE	DHFR	P00374	CHEMBL202	20	20	15
KINASE	Cdk2	P24941	CHEMBL301	20	20	17

Ligand

	a	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r	s	t
Is any candidate pose correct?	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N	N	N	N	N	N	N	N	N
Is Glide's predicted pose correct?	Y	Y	Y	Y	Y	Y	Y	N	N	N	N	N	N	N	N	N	N	N	N	N
Is ComBind's predicted pose correct?	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N	N	N	N	N	N	N	N	N

966 **Supplementary Table 4: Ligands used in predictions for the β1 adrenoceptor.** From left to
967 right, columns represent: index of ligand (a–k are as shown in **Fig. 3**; xtal denotes the
968 cocrystallized ligand in the protein structure used for docking**)**, name of ligand, mode of action,
969 and PDB ID of the experimental structure.

Index	Ligand	Mode of action	Structure
xtal	cyanopindolol	antagonist	2VT4
a	dobutamine	partial agonist	2Y00
b	carmoterol	partial agonist	2Y02
c	isoprenaline	full agonist	2Y03
d	salbuterol	partial agonist	2Y04
e	carazolol	inverse agonist	2YCW
f	iodocyanopindolol	antagonist	2YCZ
g	4-(piperazin-1- yl)-1H-indole	antagonist	3ZPQ
h	4-methyl-2-(piperazin-1-yl) quinoline	antagonist	3ZPR
i	bucindolol	antagonist	4AMI
j	carvedilol	inverse agonist	4AMJ
k	methylcyanopindolol	inverse agonist	5A8E

Supplementary Table 5: Definitions for the measures used to quantity the presence of each
of the three interaction types considered in this study.

Hydrogen Bond

A = a hydrogen bond acceptor; D = a hydrogen bond donor; H = the associated hydrogen

$$\text{distance term} = \begin{cases} 1 & \text{if distance}(H, A) \leq 2.5 \text{ Å} \\ \dfrac{3.0 \text{ Å} - \text{distance}(H,A)}{0.5 \text{ Å}} & \text{if } 2.5 \text{ Å} < \text{ distance}(H, A) \leq 3.0 \text{ Å} \end{cases}$$

$$\text{angle term} = \begin{cases} 1 & \text{if angle}(D, H, A) \geq 120°. \\ \dfrac{\text{angle}(D,H,A) - 90°}{30°} & \text{if } 90° \leq \text{ angle}(D, H, A) < 120° \end{cases}$$

hydrogen bond value = distance term * angle term

Salt Bridge

N = an atom with a negative formal charge; P = an atom with a positive formal charge

$$\text{salt bridge value} = \begin{cases} 1 & \text{if distance}(N, P) \leq 4.0 \text{ Å} \\ \dfrac{5.0 \text{ Å} - \text{distance}(N,P)}{1.0 \text{ Å}} & \text{if } 4.0 \text{ Å} < \text{ distance}(N, P) \leq 5.0 \text{ Å} \end{cases}$$

Hydrophobic Contact

$A_1, A_2, \ldots, A_n$ = all carbon or halogen atoms in the ligand; $B_1, B_2, \ldots, B_m$ = all carbon atoms in the given protein residue

distance term for A_i and B_j =

$$\begin{cases} 1 & \text{if distance}(A_i, B_j) \leq 1.25\, r_{ij} \\ \dfrac{1.75\, r_{ij} - \text{distance}(A_i, B_j)}{0.5\, r_{ij}} & \text{if } 1.25\, r_{ij} < \text{distance}(A_i, B_j) \leq 1.75\, r_{ij} \end{cases}$$

where r_{ij} is the sum of the van der Waals radii of A_i and B_j

hydrophobic contact value = $\sum_{i=1}^{n} \sum_{j=1}^{m}$ distance term for A_i and B_j

974 **Supplementary Table 6: Atom types used in maximum common substructure definition.**
975 SMARTS pattern and intuitive description of each atom type used when searching for common
976 substructures. Each atom in a molecule is assigned the most specific atom type (lowest in the
977 table) that applies to it.

SMARTS	Description
(*)	Any Atom
(#1)	Hydrogen
(#6)	Carbon
(#6; r5; CX4) (#6; r6)	Saturated carbon in 5-member ring Carbon in 6-member ring
c1ccccc1	Carbon-only aromatic ring
(CR0)	Carbon not in a ring
(#7)	Nitrogen
(#7; r5)	Nitrogen in 5-member ring
(#8)	Oxygen
O=*	Ketone Oxygen
(#8; r5)	Oxygen in 5-member ring
(#15)	Phosphorus
(#16)	Sulphur
(#16; r5)	Sulphur in 5-member ring
(#9, #17, #35, #53)	Halogens