**Increasing flow rate reduces biofouling and colonization by filamentous**

**bacteria in drippers fed with reclaimed wastewater**

Kévin Lequette[1-2], Nassim Ait-Mouheb[2] and Nathalie Wéry[1]

*[1]LBE, University of Montpellier, INRA, 102, Avenue des Etangs, 11100 Narbonne, France;*

*[2]IRSTEA, UMR G-EAU, University of Montpellier, Avenue Jean-François Breton, 34000*

*Montpellier, France*

Correspondence: kevin.lequette@gmail.com

Tel.: +33 (0)4 68 42 51 82

**Nomenclature**

OCT : Optical coherence tomography

RWW : Reclaimed wastewater

s-COD : soluble Chemical Oxygen Demand

CFD : Computational fluid dynamic

TS : Total solid

**Abstract**

The clogging of drippers due to the development of biofilms reduces the benefits and is

an obstacle to the implementation of drip irrigation technology. The geometry of the dripper

channel has an impact on the flow behaviours and head loss. The objective of this study was to

analyse the influence of hydrodynamic parameters of three types of drippers (flow rates of 1, 2

and 4 l.h$^{-1}$) fed by reclaimed wastewater on biofilm development kinetics and on the bacterial

community. Using optical coherence tomography, we demonstrated that the inlet of the drippers

(mainly the first baffle) and vortex zones are the most sensitive area for biofouling. Drippers

with the lowest flow rate (1 l.h$^{-1}$) and the smallest channel section were the favourable areas to

biofouling. The low inlet velocity (0.34 m.s$^{-1}$) in this type of dripper compared to 2 l.h$^{-1}$ (0.61

m.s$^{-1}$) and 4 l.h$^{-1}$ (0.78 m.s$^{-1}$) drippers can favour the deposition and development of biofilms.

In addition, the water velocity influenced the structure of the bacterial communities in the

biofilm. Low velocity (0.34 m.s$^{-1}$) favoured the presence of *Hydrogenophaga* and

*Pseudoxanthomonas* genera at the early stage of biofilm formation and filamentous bacteria

belonging to Chloroflexi phylum at the end. So, maintaining a high flow rate and using drippers

with a large flow cross-section is an effective way to control the development of biofilms by

limiting the presence of filamentous bacteria.

Keywords: Drip irrigation; biofilm; CFD; flow behaviours; Optical Coherence

Tomography; High-throughput DNA sequencing

## 36    1.  Introduction

The scarcity of water resources is driving the development of water-saving irrigation techniques

that enable integrated management of water resources. The reuse of reclaimed wastewater

(RWW) is an appropriate way to alleviate the problem of scarce water resources especially in

arid and semi-arid regions (Worako, 2015). Using RWW has several advantages including

reducing pressure on freshwater resources and on the need for nutrients (e.g. nitrogen,

phosphorus) for plant growth (Lazarova and Bahri, 2005) and can improve crop yields (Wang

et al., 2013). Drip irrigation is the most water efficient (up to >90%) and safest technique for

irrigation using RWW  (Lamm et al., 2007). Drippers are usually composed of a labyrinth-

channel and an outlet basin compartment. The geometry of the channel promotes the dissipation

of the turbulent kinetic energy due to the zigzag flow path. However, the labyrinth channel is

narrow (cross-section of around 1 mm) and the flow is thus sensitive to clogging (Liu and

Huang, 2009; Niu et al., 2013), which reduces irrigation uniformity (Dosoretz et al., 2010) and

requires more frequent maintenance (e.g. cleaning, replacing irrigation lines).

The process leading to clogging of the drippers is complex and the phenomenon is

influenced by several parameters including water quality (concentration of suspended solids,

chemical composition) (Lamm et al., 2007), the geometry of the dripper (Wei, 2011) as well as

biological processes (Katz et al., 2014), the latter are the most difficult to control when RWW

is used (Lamm et al., 2007). Previous studies have shown that flow velocity has an impact on

the growth of biofilm in both drip-irrigation pipes (Li et al., 2012; Mahfoud et al., 2009) and in

drippers (Gamri et al., 2014). The design of the geometry flow path influences the

hydrodynamic flow and hence the development of biofilm (Bounoua et al., 2016).

Computational studies of fluid dynamics have shown that the flow in the labyrinth-channel

consisted of a main high velocity flow and vortex zones (Al-Muhammad et al., 2016) and that

the development of biofilm is favoured in vortex areas due to reduced velocities and shear forces

(Ait-Mouheb et al., 2018; Qian et al., 2017).

Flow behaviour not only influences the development of biofilms but also the microbial

composition of the biofilms. Previous research on drinking water biofilms has shown that

hydrodynamic conditions can drive the microbial community of the biofilms (Besemer, 2015;

Rickard et al., 2004). However, in the context of the use of RWW, few authors have examined

the influence of dripper parameters (i.e. flow rate, cross section, and geometry of the milli-

channel) on microbial composition. Previous studies have described the microbial communities

present in biofilms of different drippers by analysing phospholipid-derived fatty acids (PLFAs)

(Yan et al., 2010, 2009; Zhou et al., 2017). These authors showed that three to seven types of

PLFAs associated with Gram-negative bacteria were common in biofilms inside drippers,

suggesting a significant role for these bacteria in biofilm development. However, in order to

develop effective biofilm control strategies, deeper community characterization is required.

Recent study used high-throughput sequencing to describe the bacterial communities present in

dripper biofilms to improve knowledge on clogging (Lequette et al., 2019; Song et al., 2019).

Optical methods (i.e. scanning electron microscopy) are commonly used to investigate

the structure and the composition of  biofilms at a local scale (Yan et al., 2009). But these

studies underlined the importance of studying biofilm at mesoscale (millimetre range) in order

to better understand the structure of biofilm, its function and the mechanisms behind its

development (Morgenroth and Milferstedt, 2009).  Recent studies used Optical coherence

tomography (OCT) makes it possible to monitor biofilm formation non-invasively at a

mesoscale and without staining (Derlon et al., 2012; Dreszer et al., 2014; Qian et al., 2017;

West et al., 2016).

The objectives of the present study were to determine the effect of hydraulic parameters

(1) on biofouling along the channel, (2) on the microbial communities in biofilms formed in

irrigation systems fed by RWW. A non-destructive microscopic time-monitoring observation

system was developed to study biofilms in commercial drippers with different flow rates (1, 2

and 4 l.h$^{-1}$) with known cross-sections. The combined use of the OCT method and high-

throughput sequencing made it possible to monitor the development of the biofilm under

different hydraulic conditions while assessing the impact of these conditions on microbial

composition.

**2.  Materials and Methods**

***2.1. Experimental setup***

*2.1.1.  Experimental setup and irrigation procedure*

Non-pressure-compensating (NPC) drippers (model D2000, Rivulis Irrigation SAS,

Lespinasse, France) with different flow rates (1, 2 and 4 l.h-1) were selected (Table 1). The

development of biofilm in commercial drippers cannot be observed over time because the

drippers are walled inside opaque irrigation pipes (black polyethylene tubes). The NPC drippers

were therefore placed in a transparent tube (internal diameter 15mm, TubClair, Vitry-le-

François, France), allowing us to see biofilm development along the channel over time. A solid

tube with an internal diameter of 19mm (ABS+, Stratasys U-print SE plus, Stratasys Ltd, Eden

Prairie, Minnesota, US) pressed the dripper against the walls of the transparent tube (Figure

1.A). The water flowed through the dripper grids connected to the milli-channel. Finally, an

outlet hole (internal diameter 2mm) was pierced in the transparent tube above the outlet basin.

Nine drippers were connected to each type of dripper using polyethylene tubing (length 10cm,

internal diameter 20mm) and valves (internal diameter 20mm) (total length 3m). The valves

were used to keep the drippers under water when they were disconnected from the irrigation

line for analysis. Each of the three lines was connected to a separate tank (total volume 60l) and

a pump (JetInox 82M, DAB, Saint-Quentin-Fallavier, France) (Figure 1.B). A disk filter (mesh

size 0.13mm) was installed to reduce the physical clogging of emitters following the technical

recommendations of this type of dripper. The inlet pressure was set at 0.08 MPa with a pressure

gauge. A gutter was installed below each lateral line to collect the water discharged from the

drippers during the experiments. The gutters returned the discharged RWW to the respective

tanks, enabling the recycling of water. The lines were supplied twice a day five days out of

seven for 1h, with an interval of 6h off. The outlet flow rate from the drippers was measured

weekly to evaluate emitter performance. Drippers are considered clogged when there is a

decrease of at least 25% in the expected flow rate. The system was not flushed during the entire

four-month experiment (from April to August 2018).

**Figure 1. Dripper system (A) and test bench (B). The drippers were placed in a**
**transparent tube to enable optical measurements. The test bench was composed of 1. a**
**tank (60l); 2. a water pump; 3. a 0.13mm mesh screen filter; 4. a pressure reducer; 5. a**
**pressure gauge; 6. the drip line with an emitter system located at 10-cm intervals; 7. a**
**collector; 8. a gutter.**

Table 1 lists the dripper characteristics. The flow regimes were characterised by a Reynolds

number (Re). The Reynolds number (Re) was computed using the following formula:

$$Re = \frac{\rho v D}{\mu} \qquad (1)$$

where $\rho$ is water density (kg.m$^{-3}$), $v$ the water velocity across the pipe (m.s$^{-1}$), $D$ the internal

diameter (m), and $\mu$ the water viscosity (Pa s).

**Table 1. Dripper parameters**

| q (l.h$^{-1}$) | $L$ (mm) | $W$ (mm) | $h$ (mm) | $D_h$ | Total labyrinth volume (mm$^3$) | Re (inlet) | v (m.s$^{-1}$) | Emitter |
|---|---|---|---|---|---|---|---|---|
| 1 | 103.4 | 1.01 | 0.8 | 1.02 | 127 | 305 | 0.34 | |
| 2 | 94.1 | 1.03 | 0.9 | 1.12 | 142 | 579 | 0.60 | |
| 4 | 47.4 | 1.35 | 1.1 | 1.17 | 129 | 926 | 0.78 | |

132 $L$: length of the flow path, $W$: width of the flow path, $h$: depth of the flow path, q: flow rate, $D_h$:
133 hydraulic diameter

### 2.1.2. Computational fluid dynamic

The hydrodynamic profiles along the labyrinth channel were investigated using CFD.

The numerical simulations were performed using the commercial CFD solver COMSOL

Multiphysics. The geometry includes inlet and outlet channels, an outlet basin and various

baffles depending on the type of dripper used (Table 1). The dimensions and channel geometries

were based on the characteristics of the experimental drippers. The inlet mesh of drippers and

the roughness of the walls were not included in these simulation studies. The computations

were performed using a Tetrahedron grid. The influence of mesh size was tested in order to

choose the appropriate computation grid. The k-ε turbulence model was used in this study.

Steady state, turbulent, single-phase and incompressible fluid conditions were assumed. The

fluid used was pure liquid water and was assumed not to be subject to gravity forces. Boundary

conditions for both configurations were as follows: uniform pressure was imposed at the inlet

(P=0.08 MPa). Atmospheric pressure was chosen for the outflow. The turbulent intensity and

the hydraulic diameter were chosen for the turbulence specification method to calculate the

turbulence effect (for further information on Computational Fluid Dynamics, see Pope, 2000).

### 2.1.3. Physical-chemical and microbiological quality of the RWW

The irrigation lines were supplied with reclaimed wastewater from the Murviel-Les-

Montpellier in the South of France, (43.605034° N, 3.757292° E). The wastewater treatment

plant is designed around stabilisation ponds with three successive lagoons (13 680 $m^3$, 4784 $m^3$

and 2700 $m^3$) and a nominal capacity of 1,500 Inhabitant Equivalent. The RWW was placed in

a 60l tank and changed twice a week to maintain the quality close to that of the wastewater from

the treatment plant. Each week (n=16), several physical-chemical and microbiological analyses

were performed to evaluate the RWW quality. Chemical oxygen demand (COD), ammonia,

nitrate, and phosphorus concentrations (mg $l^{-1}$) were measured with a spectrophotometer

(DR1900, Hach Company, Loveland, CO, USA) using Hach reagents[®]. Conductivity and pH

were measured with probes (TetraCon® 925 and pH-Electrode Sentix® 940, WTW, Wilhelm,

Germany). Faecal coliforms, *E. coli,* and *Enterococci* were quantified using the IDEXX method

(Colilert18 and Enterolert, IDEXX Laboratories, Westbrook, ME) according to the supplier's

recommendations. The main effluent properties are listed in Table 2.

**Table 2. Physical-chemical and microbiological characteristics of the RWW**

| Characteristics | Units | Mean (n=24) | SD |
|---|---|---|---|
| Soluble COD | mg l$^{-1}$ | 70.3 | 7.6 |
| Total suspended solids | mg l$^{-1}$ | 61 | 24.2 |
| Ammonia | mg l$^{-1}$ | 25.7 | 7.8 |
| Nitrate | mg l$^{-1}$ | 0.7 | 0.1 |
| Phosphorus | mg l$^{-1}$ | 4.9 | 0.9 |
| Conductivity | µS cm$^{-1}$ | 1101.4 | 51.5 |
| TS | mg l$^{-1}$ | 60.9 | 24.3 |
| Dissolved oxygen | mg l$^{-1}$ | 6.8 | 1.5 |
| pH | | 6.9 | 0.8 |
| Total coliforms | MPN/100ml | 6.1x10$^5$ | 6.4x10$^5$ |
| *Escherichia coli* | MPN/100ml | 5.8x10$^4$ | 5.1x10$^4$ |
| *Enterococci* | MPN/100ml | 3.2x10$^4$ | 4.6 x10$^4$ |

**2.2. Image acquisition and processing**

2.2.1. Image acquisition

Optical coherence tomography (OCT) was used to study the biofilm kinetics in drippers and

along the milli-channel throughout the experimental period. The measurements were performed

in situ and non-invasively through the transparent tube. Three-dimensional OCT measurements

were acquired using a Thorlabs GANYMEDE II OCT (LSM03 lens; Thorlabs GmbH, Lübeck,

Germany). OCTs have a centre wavelength of 930 nm. Due to the length of the drippers, the

labyrinth channel was divided into eight parts (inlet, part 2, part 3, return, part 6, part 7, and

end; Table S1 in Supplementary material) to study biofouling in different parts of the channels

(Figure 2).

**Figure 2. Schematic diagram of the geometric channel from the drippers. The dotted boxes correspond to the study areas. The length and width (in mm) of each baffle are listed in the table associated with Figure S1 in Supplementary material.**

2.2.2. Image processing

First, 3-D OCT datasets were processed in Fiji (running on ImageJ version 1.50b, Schindelin et al., (2009)) and converted into 8-bit grayscales. The datasets were resliced from top to bottom into image stacks and regions of interest (inlet and return areas) were selected. The remaining parts were allocated to the background (black). Secondly, an in-house code was used to detect the pixels associated with the plastic tube and removed using MATLAB R2018r (MathWorks ®, version 2018b). A threshold (adapted to each dataset) was applied to binarize the dataset and the region above the interface was quantified as biofilm. For each position (x, y), the pixels associated with the biofilm (up to the threshold) were summed (on z) to obtain

the thickness of the biofilm. The biofilm volume (%) was calculated for each baffle according

to Equation 2:

$$Volumetric\ Coverage\ \% = \frac{V_{biofilm}}{V_{baffle}} \times 100 \qquad (2)$$

where $V_{biofilm}$ is the biofilm volume and $V_{baffle}$ is the volume of the baffle.

**2.3. Analysis of the microbial communities**

*2.3.1.  Sampling the biofilm and reclaimed wastewater*

Once a month, three drippers in each line were chosen and replaced by new ones to

ensure the functioning of the system. However, these new drippers have not been analyzed.

Each dripper in the transparent tube was extracted with sterile clamps, placed in a sterile tube

and stored at -20°C until DNA extraction. RWW was filtered (15 to 30 mL) each week through

0.2 µm (Supor® 200 PES Membrane Disc Filter, Pall Corporation) to analyse the bacterial

community in the reclaimed wastewater. Filters were stored at -20°C until DNA extraction.

*2.3.2.  DNA extraction*

DNA was extracted using the PowerWater® DNA Isolation Kit (Qiagen, Hilden, Germany).

Samples (drippers or filters) were placed in 5 mL tubes containing beads. The manufacturer's

instructions were then followed.  The DNA concentration was measured, and purity checked

by spectrophotometry (Infinite NanoQuant M200, Tecan, Austria). Extracted DNA was stored

at -20°C.

*2.3.3.  Bacterial quantification by qPCR*

Total bacterial quantification was performed by qPCR on biofilms from drippers targeting the

V9 region from 16S rDNA. The amplification reactions were performed in triplicate, and at two

dilutions to check for the absence of inhibition of the PCR reaction. Reaction mixes (12µl)

contained 2.5µl of water, 6.5µl of Super Mix qPCR (Invitrogen), 100nM forward primer

BAC338 (5'-ACTCCTACGGGAGGCAG-3'), 250nM of reverse primer BAC805 (5'-

GACTACCAGGGTATCTAAT CC-3') and 50nM of probe BAC516 (Yakima Yellow-

TGCCA GCAGC CGCGG TAATA C –TAMRA) (Yu et al., 2005). The cycling parameters

were 2 min at 95°C for pre-incubation of the DNA template, followed by 40 cycles at 95°C for

15 sec for denaturation and 60°C for 60 sec for annealing and amplification.

*2.3.4. Illumina sequencing*

PCR amplified the V4-V5 region of 16S rRNA genes with 30 cycles (annealing temperature

65°C) using the primers 515U (5′-GTGYCAGCMGCCGCGGTA-3′) and 928U (5′-

CCCCGYCAATTCMTTTRAGT-3′) (Wang and Qian, 2009). Adapters were added for

multiplexing samples during the second amplification step of the sequencing. The resulting

products were purified and loaded onto the Illumina MiSeq cartridge for sequencing of paired

300 bp reads according to the manufacturer's instructions (v3 chemistry). Sequencing and

library preparation was performed at the Genotoul Lifescience Network Genome and

Transcriptome Core Facility in Toulouse, France (get.genotoul.fr). Mothur (version 1.39.5)

(Schloss et al., 2009) was used to associate forward and reverse sequences and clustering at

four different nucleotides over the length of the amplicon. Uchime (Edgar et al., 2011) was used

to identify and remove chimera. Sequences that appeared less than three times in the entire data

set were removed. In all, 16S rRNA sequences were aligned using SILVA SSURef NR99

version 128 (Schloss et al., 2009). Finally, sequences with 97% similarity were sorted into

operational taxonomic units (OTUs) (Nguyen et al., 2016). The chloroplast sequences were

removed from the raw data. Finally, BLAST (http://www.ncbi.nlm.nih.gov/BLAST/) was used

to locate publicly available sequences closely related to the sequences obtained from the

samples. A total of 11,357,162 reads were grouped in 7730 OTUs at the 97% similarity level.

The rarefaction curves indicated that the sequencing depths of all samples were adequate

(Figure S2 in Supplementary material).

*2.4. Statistical analyses*

The kinetics of biofilm development were evaluated by modelling the biofilm formation rate

using linear and spline models. The sequencing data were processed under R v3.4 (www.r-

project.org) using the R-Studio (http://www.rstudio.com/) phyloseq package (McMurdie and

Holmes, 2012). Kruskal-Wallis tests were performed to compare diversity and richness indices

over time and between the dripper types. For the comparison of bacterial community structure,

a dissimilarity matrix (Bray-Curtis) was performed and visualised using principal coordinate

analysis (PCoA). A one-way analysis of similarities (ANOSIM) was used to identify significant

differences in community assemblage structure between samples based on the origin of the

sample (Clarke, 1993). The OTUs that contributed most to the divergence between two types

of dripper were identified using Similarity Percentage (SIMPER) analysis (Clarke, 1993).

**3. Results**

*3.1. Areas favourable for the development of biofilm*

During the four month experiment, all the drippers maintained the expected flow rates, and the

drippers never became clogged. In the first two weeks, the thickness of the biofilm was too low

to be measured and the first measurements were made after one month. Based on OCT analysis

(Figure S1, S2 and S3 in Supplemental material), the highest volume of biofilm ($mm^3$) was

observed in two areas: at the dripper inlet (all drippers; 2.45, 3.32 and 2.19 $mm^3$ for 1, 2 and 4

$l.h^{-1}$ drippers respectively) and in the return areas of the 1 and 2 $l.h^{-1}$ dripper channels (with 1.62

and 2 $mm^3$ of biofilm respectively, there is no return area in 4 $l.h^{-1}$). Figure 3 shows the increase

in clogging thickness in the inlet and return dripper areas at one and four months. Over time,

biological fouling at the inlet area increased and gradually spread to the following baffles. The

biofilm thickness in the return area increased after the large bend (B7) in both types of drippers

(Figure 3C).

The mean velocity was lower at the inlet channel (Figure 4, baffle B1), as demonstrated

by the CFD simulations. This low fluid velocity is the result of the rotation of the flow direction

and streamline detachment, which explains why biofilm accumulated in this zone (Figure 3).

Biofilm also developed in the vortex regions of the first baffles (Figure 3). According to the

numerical results, low velocity (around 0.2 m.s$^{-1}$, Figure 4) and low turbulent kinetic energy (k)

values prevailed in this part of channel providing favourable conditions for the development of

biofilm. Conversely, areas where k and shear stress values were higher (from the 3$^{rd}$ baffle on)

were subject to limited biofilm development.

Figure 3. Biofilm thickness at the inlet of 1, 2 l.h-1 dripper (A) and 4 l.h-1 dripper (B) and in the return areas of drippers (C) measured after 1 and 4 months.

Figure 4. Mean velocity fields obtained numerically along the labyrinth channel at z=0
with an inlet pressure of 0.8MPa

278
279

The volume of the baffles differed with the dripper. Therefore, to compare the level of

clogging between drippers, the biofouling volume was normalized by the volume of the

corresponding baffle (Equation 2). Mean clogging of the inlet baffles increased over time in all

three types of drippers (Figure 5). The level of biofouling were significantly influenced by the

type of dripper (Chi²=115, p-value < 0.05) and the time (Chi²=54, p-value < 0.05). The level of

biofouling increased more rapidly in 1 and 2 l.h$^{-1}$ drippers than in 4 l.h$^{-1}$ drippers (Wald test, p-

value < 0.05).

There was no statistical effect of baffles on volumetric coverage over time. However,

the volume of biofouling in the first baffle was significantly higher in 1 l.h$^{-1}$ drippers than in 2

l.h$^{-1}$ and 4 l.h$^{-1}$ drippers after four months with a mean volumetric coverage of 22.6%, 15.8%

and 14.1 % for 1 l.h$^{-1}$, 2 l.h$^{-1}$ and 4 l.h$^{-1}$ drippers, respectively (Kruskal test, p-value < 0.05).

The mean increase in biofouling in the 1 l.h$^{-1}$ drippers presented a sinusoidal dynamic with up

and down phases at the inlet baffle. This could mean several detachment events occurred. The

same cycle was observed in the 2 and 4 l.h$^{-1}$ but only in the first baffle. The detachment event

occurred at ~ 3 months in the 4 l.h$^{-1}$ drippers whereas the first event appeared at 1 month in the

2 l.h$^{-1}$ drippers. After this baffle, the increase in biofouling was linear. At the return zone in 1

and 2 l.h$^{-1}$ drippers, the volumetric coverage increased over time but was heterogeneous. Thus

it was not possible to define kinetic models.

The type of dripper (flow rate and flow cross-section) influenced the level of clogging

of the labyrinth with a higher clogging rate in 1 l.h$^{-1}$ drippers (lower flow rate and narrower

flow cross-section).

Figure 5. Mean volumetric biofilm coverage at the inlet of the drippers 1 l.h⁻¹ (A) and 2 l.h⁻¹ (B) and 4 l.h⁻¹ (C) over time. The lines and confidence interval (95% of associated variance) correspond to the spline and linear model used for each dripper type (Baffle B4 from 2 l.h⁻¹ was not included due to the too low regression value (R²<0.25).

### *3.2. Microbial diversity differed between dripper biofilms and reclaimed*
### *wastewater*

The structure of the bacterial communities in biofilms collected in the three types of drippers

were compared using 16S rDNA Illumina sequencing. The bacterial communities in the

biofilms were also compared with the communities present in reclaimed wastewater. The

chloroplast sequences were removed from the raw data and represented 1.6% and 5.4% of the

total sequences in biofilms and in RWW samples, respectively. Microscopic observations of

the biofilms in the pipes (data not shown) also revealed the presence of eukaryotic

microorganisms (bacterial predators) but the biofilms were still mainly composed of bacteria.

The biofouling of the drippers increased over time in all three types of drippers as shown

by the increase in DNA concentration. (Table 3). On the other hand, the number of bacteria

remained unchanged over time in the three types of drippers and already reached $10^9$ copies of

16S rDNA/dripper at 32 days in all three types of dripper.

**Table 3. DNA concentration and quantification of bacteria by qPCR in dripper biofilms**

| Sampling time (days) | Dripper flow rate (l.h$^{-1}$) | Mean DNA concentration (µg/µl) | Mean n° of bacteria /dripper (16S copies/dripper) |
|---|---|---|---|
| 32 | 1 | $137.4\pm67.9^a$ | $6.2\pm0.9 \times 10^{9a}$ |
| | 2 | $113.9\pm42.7^a$ | $5.7\pm0.6 \times 10^{9a}$ |
| | 4 | $118.1\pm26.8^a$ | $9.9\pm1.2 \times 10^{9a}$ |
| 72 | 1 | $220.4\pm34.6^a$ | $9.2\pm0.5 \times 10^{9a}$ |
| | 2 | $287.4\pm113.8^a$ | $1.2\pm0.05 \times 10^{10a}$ |
| | 4 | $194.4\pm20.2^a$ | $4.3\pm2.3 \times 10^{9a}$ |
| 115 | 1 | $325.2\pm70.8^a$ | $8.7\pm0.4 \times 10^{9a}$ |
| | 2 | $387.8\pm164.1^a$ | $1.4\pm0.5 \times 10^{10a}$ |
| | 4 | $346.1\pm34.5^a$ | $5.4\pm1.4 \times 10^{9a}$ |

322 Kruskal-test and Wilcoxon ad hoc tests were performed on each sampling occasion to compare
323 the values between the drippers (n= 3 for each type of dripper on each sampling event); letters
324 show Wilcoxon test results.
325

326 The richness and diversity indices of the biofilms did not significantly differ between

327 the three types of drippers, but increased over time in all three (Table 6). The richness and

diversity indices of RWW were lower than those in the dripper biofilms (Table 4). The majority

of operational taxonomic units (OTUs) were shared by all the biofilms (Figure S5 in

Supplemental material). Some OTUs and bacterial genera were specific to the dripper flow, but

their relative abundance was less than 0.1% (Table S2 in Supplementary material).

**Table 4. Estimated species richness and diversity indices according to the dripper flow rate and the RWW**

| Samples | Flow rate $(l.h^{-1})$ | Age (Days) | Richness indices | | Diversity indices | |
| --- | --- | --- | --- | --- | --- | --- |
| | | | Estimated OTUs | | | |
| | | | Observed | Chao1 | Shannon | 1/Simpson |
| Dripper | 1 (n=3) | 32 | $786 \pm 36^a$ | $786 \pm 36^a$ | $4.7 \pm 0.1^a$ | $40 \pm 7^a$ |
| | | 72 | $1215 \pm 18^b$ | $1215 \pm 18^b$ | $5.5 \pm 0.1^b$ | $88.4 \pm 15.8^b$ |
| | | 115 | $1640 \pm 135^c$ | $1640 \pm 135^c$ | $5.9 \pm 0.1^c$ | $149.5 \pm 17.4^c$ |
| | 2 (n=3) | 32 | $752 \pm 61^a$ | $752 \pm 61^a$ | $4.7 \pm 0.1^a$ | $42.3 \pm 2.7^a$ |
| | | 72 | $1286 \pm 188^b$ | $1286 \pm 188^b$ | $5.5 \pm 0^b$ | $90.3 \pm 6.6^b$ |
| | | 115 | $1758 \pm 92^c$ | $1758 \pm 92^c$ | $5.8 \pm 0.1^c$ | $114.2 \pm 9.4^c$ |
| | 4 (n=3) | 32 | $783 \pm 54^a$ | $783 \pm 54^a$ | $4.6 \pm 0.1^a$ | $40.4 \pm 7.7^a$ |
| | | 72 | $1360 \pm 23^b$ | $1360 \pm 23^b$ | $5.6 \pm 0^b$ | $106.7 \pm 3.9^b$ |
| | | 115 | $1726 \pm 30^c$ | $1726 \pm 30^c$ | $5.8 \pm 0^c$ | $116.6 \pm 3.3^c$ |
| RWW (n= 11) | - | | $836 \pm 310$ | $836 \pm 310$ | $4.2 \pm 0.7$ | $32.6 \pm 22.9$ |

Kruskal test and the Wilcoxon ad hoc test were performed for each dripper (n= 3 at each
sampling); the letters show the results of the Wilcoxon test.

Proteobacteria, Bacteroidetes, Firmicutes and Chloroflexi were the main phyla in the

dripper biofilms (Figure 6A). The main phyla found in RWW were Proteobacteria (25-55%)

mainly composed of β-Proteobacteria (10-34%) and γ-Proteobacteria (2-34%), followed by

Bacteroidetes (22-40%) and Actinobacteria (7-14%) (Figure 6B). These differences indicate

that among bacteria in the reclaimed wastewater, bacteria able to attach to the surface of the

dripper under the corresponding flow regime were selected, especially among Firmicutes and

Chloroflexi (Figure 7). From 49 days onwards, cyanobacteria phylum appeared in reclaimed

wastewater, explaining the increase in cyanobacteria in the drippers on the second sampling

occasion (72 days). The same observation was made concerning Spirochaetae and Chlorobi

phyla. Thus, RWW influenced the bacterial composition of the dripper biofilms. The structure

of the biofilms in the drippers evolved over time according to changes in the microbial diversity

in the reclaimed wastewater, and with the selection of some adapted taxa able to adhere to the

surfaces, such as filamentous Chloroflexi bacteria.

**Figure 6. Relative abundance of bacterial phyla (>1%) in dripper biofilms (A) and in**
**reclaimed wastewater (B).**

*3.3. The dripper flow parameters influenced the composition of the bacterial*
*communities*

The impact of flow parameters on the structure of bacterial communities was first

investigated at the phyla and familly taxonomic levels. Proteobacteria phylum was the most

abundant phylum in the biofilms (Figure 6) and was mainly composed of α-Proteobacteria, β-

Proteobacteria (mainly composed of members of the Comamonadaceae family), γ-

Proteobacteria and δ-Proteobacteria. At 32 days, the mean abundance of Proteobacteria was

similar in all dripper types, with 49, 47 and 45% in the 1, 2 and 4 l.h$^{-1}$ dripper biofilms,

respectively (Kruskal-test, p-value $> 0.05$). At 115 days, the mean relative abundance of

Proteobacteria (and more specifically β-Proteobacteria) was significantly lower in the 1 l.h$^{-1}$

dripper biofilms than in the 2 and 4 l.h$^{-1}$ dripper biofilms (Kruskal-test, p-value $< 0.05$) and

decreased significantly until 28% vs 33 and 37% for the 2 and 4 l.h$^{-1}$ dripper biofilms,

respectively.

The phylum of Bacteroidetes was mainly composed of Sphingobacteriia

(Chitinophagaceae, Lentimicrobiaceae, Saprospiraceae and Sphingobacteriaceae class

members), Bacteroidia (mainly Draconibacteriaceae and Rikenellaceae member families) and

Bacteroidetes_vadinHA17. There was no effect of the type of dripper on the mean relative

abundance of Bacteroidetes (~ 30% over time in each dripper type, Kruskal test, p-value $>$

$0.05$). Over time, the relative abundance of Sphingobacteriia and Bacteroidia decreased while

the relative abundance of Bacteroidetes_vadinHA17 increased in the three types of drippers.

The mean relative abundance of Chloroflexi (mainly composed of Anaerolineaceae and

Caldilineaceae member family) increased significantly over time and was significantly higher

in 1 l.h$^{-1}$ dripper biofilms after 115 days (16% versus 14% and 10% for 1, 2 and 4 l.h$^{-1}$ dripper

biofilms, respectively, Kruskal test, p-value $< 0.05$). At 115 days, the mean relative abundance

of the Anaerolineaceae family was significantly higher in 1 l.h$^{-1}$ dripper biofilms than in the 4

l.h$^{-1}$ dripper biofilms (Kruskal test, p-value $< 0.05$). There were no significant differences in the

Firmicutes phylum (mainly represented by Christensenellaceae, Clostridiaceae and

Ruminococcaceae), according to the dripper types or over time (Kruskal test, p-value $> 0.05$).

The impact of flow rates on bacterial communities was then investigated at the genus level.

Table 5 lists the 10 top genera found in all the dripper biofilms over time.

At 32 days, the 1 l.h$^{-1}$ dripper biofilms were dominated by the Comamonadaceae family

(6%) including *Hydrogenophaga* genus (9%) and *Pseudoxanthomonas* (3%). The mean relative

abundance of the *Hydrogenophaga* genus was significantly influenced by the flow rate (Kruskal

test, p-value $< 0.05$) and was higher in the 1 l.h$^{-1}$ dripper biofilms (3% and 4% for 2 and 4 l.h$^{-1}$

dripper biofilm, respectively). Over time, the mean relative abundance of members of the

Comamonadaceae family and of the *Hydrogenophaga* genus decreased significantly in the 1

l.h$^{-1}$ (Kruskal test, p-value $< 0.05$), close to the relative abundance in 2 and 4 l.h$^{-1}$ dripper

biofilms at the end (Kruskal test, p-value $> 0.05$). The relative abundance of

Bacteroidetes_vadinHA17 and members of the Lentimicrobiaceae family, which belong to

Bacteroidetes, increased significantly over time in each dripper type (Kruskal test, p-value $<$

$0.05$) and dominated in all three drippers at 115 days (Kruskal test, p-value $> 0.05$).

Even if the majority of the genera were the same in the different drippers and on the

sampling occasions, some genera with low abundance ($<1\%$) depended specifically on the

dripper flow rate and the sampling time (Table 8, Supplementary Figure 9). For instance, only

*Vulcaniibacterium* and *Microvirga* genera were found in the 1 l.h$^{-1}$ dripper on each sampling

time. This means that hydrodynamic conditions influenced both the dominant and less abundant

bacterial taxa.

**Table 5. Ten most abundant genera found in dripper biofilms according to the sampling time. '_un': For unclassified genus ('_un'), the taxonomic affiliation is given at family level _ge: uncultured bacteria identified at the genus level by molecular studies.**

| Sampling time (days) | 1l.h⁻¹ | | 2l.h⁻¹ | | 4l.h⁻& | |
|---|---|---|---|---|---|---|
| | Taxonomic affiliation | % | Taxonomic affiliation | % | Taxonomic affiliation | % |
| **32** | *Hydrogenophaga* | 9.48 | *Comamonadaceae_un* | 8.49 | *Comamonadaceae_un* | 9.61 |
| | *Comamonadaceae_un* | 6.56 | Bacteroidetes _M2PB4-65_ge | 4.97 | *Hydrogenophaga* | 4.22 |
| | *Pseudoxanthomonas* | 3.87 | *Oxalobacteraceae_un* | 4.45 | *Thiocapsa* | 3.43 |
| | *Thiocapsa* | 3.47 | *Dechloromonas* | 4.39 | Bacteroidetes _M2PB4-65_ge | 3.43 |
| | Bacteroidetes _M2PB4-65_ge | 3.44 | *Hydrogenophaga* | 3.30 | *Sphingobacteriales_un* | 3.00 |
| | Bacteroidetes _vadinBC27 | 3.16 | *Thiocapsa* | 3.21 | *Christensenellaceae_un* | 2.98 |
| | *Fusibacter* | 3.05 | *Sphingobacteriales_un* | 3.03 | *Thermomonas* | 2.63 |
| | *Sphingobacteriales_un* | 2.33 | *Aquabacterium* | 2.70 | *Lentimicrobiaceae_ge* | 1.97 |
| | *Aquabacterium* | 2.32 | *Christensenellaceae_un* | 2.50 | *Dechloromonas* | 1.85 |
| | *Dechloromonas* | 2.21 | *Aquimonas* | 2.45 | *Rhodobacteraceae_un* | 1.79 |
| **72** | *Hydrogenophaga* | 4.65 | *Comamonadaceae_un* | 5.74 | *Comamonadaceae_un* | 5.55 |
| | *Comamonadaceae_un* | 3.99 | *Rhodocyclaceae_un* | 4.42 | *Dechloromonas* | 3.37 |
| | *Desulfobacter* | 3.83 | *Dechloromonas* | 3.66 | Bacteroidetes_vadinHA17 | 3.31 |
| | *Dechloromonas* | 2.98 | *Lentimicrobiaceae_ge* | 2.56 | *Lentimicrobiaceae_ge* | 3.03 |
| | Cyanobacteria_FamilyI_un | 2.41 | Cyanobacteria_FamilyI_un | 2.36 | *Lentimicrobium* | 2.74 |
| | Bacteroidetes_vadinHA17 | 2.39 | *Desulfobacter* | 2.32 | *Zoogloea* | 2.09 |
| | *Lentimicrobiaceae_ge* | 1.99 | *Lentimicrobium* | 2.29 | *Sphingobacteriales_un* | 1.92 |
| | *Lentimicrobium* | 1.97 | Bacteroidetes_vadinHA17 | 2.24 | *Hydrogenophaga* | 1.88 |
| | *Terrimonas* | 1.87 | *Zoogloea* | 1.93 | *Christensenellaceae_un* | 1.84 |
| | *Thauera* | 1.85 | *Haliangium* | 1.89 | Proteobacteria_Run-SP154_ge | 1.80 |
| **115** | Bacteroidetes_vadinHA17 | 5.79 | Bacteroidetes_vadinHA17 | 4.94 | Bacteroidetes_vadinHA17 | 6.31 |
| | *Lentimicrobiaceae_ge* | 2.82 | *Lentimicrobium* | 2.55 | Candidatus_Competibacter | 4.47 |
| | *Anaerolineaceae_un* | 2.75 | *Terrimonas* | 2.37 | *Lentimicrobiaceae_ge* | 2.74 |
| | Chloroflexi_SJA-15_ge | 2.40 | *Lentimicrobiaceae_ge* | 2.37 | *Lentimicrobium* | 2.61 |
| | *Lentimicrobium* | 2.38 | Candidatus_Competibacter | 2.04 | *Comamonadaceae_un* | 2.40 |
| | *Desulfobacter* | 2.04 | *Anaerolineaceae_un* | 1.95 | *Rhodocyclaceae_un* | 2.18 |
| | *Terrimonas* | 1.91 | *Dechloromonas* | 1.91 | *Terrimonas* | 1.89 |
| | *Rhodocyclaceae_un* | 1.83 | *Comamonadaceae_un* | 1.70 | *Aquabacterium* | 1.84 |
| | *Gelria* | 1.60 | Chloroflexi_SJA-15_ge | 1.65 | *Dechloromonas* | 1.80 |
| | *Syntrophomonadaceae_ge* | 1.51 | *Rhodocyclaceae_un* | 1.57 | *Anaerolineaceae_un* | 1.67 |

### 3.4. Dripper hydraulic properties impact bacterial community structure

PCoA was performed to compare the structure of bacterial communities between the three types of dripper over time and confirmed that the bacterial community in the dripper biofilms changed depending on the type of dripper and over time (Figure 7). At 31 days, the bacterial populations in 2 and 4 l.h$^{-1}$ were clustered (one-way ANOSIM, R=0.71, p < 0.05). The bacterial communities in the 1 l.h$^{-1}$ dripper biofilms formed a second cluster (Figure 7, A). This means that the hydraulic conditions had little influence on the structure of the microbial community in 2 and 4 l.h$^{-1}$ compared to that in the 1 l.h$^{-1}$ dripper biofilms at the first stage of development. At the end of the experiment (Figure 7, C) the bacterial community in 2 and 4 l.h$^{-1}$ diverged and formed specific groups (one-way ANOSIM, R=0.65, p<0.05).

The main contributors (those explaining 50% of the global bacterial divergence are indicated in Figure 7) of the bacterial community were identified using SIMPER analyses and were shown to change over time. Those explaining 50% of the global bacterial divergence are indicated in Figure 7. At 32 days, 11 OTUs played a significant role in bacterial community divergence. *Pseudoxanthomonas* (OTU 25), *Hydrogenophaga* (OTU 5) and *Fusibacter* genera (OTU 60) were the main contributors and were associated with the 1l.h$^{-1}$ drippers. These genera were also the main genera found in 1 l.h$^{-1}$ dripper biofilms at 32 days (Table 4). At 115 days, 23 OTUs significantly contributed to divergence. Hydrogenophaga (OTU 5) and *Pseudoxanthomonas* (OTU 25) were still strong contributors associated with 1 l.h-1 dripper biofilms. *Aquabacterium* (OTU 10), *Ideonella* (OTU 15) and Bacteroidetes members (OTU 19, OTU 85) were associated with the 4l.h$^{-1}$ dripper biofilms, whereas Sphingobacteriales family members (OTU 3, OTU 136) and *Terrimonas* genus (OTU 24) were associated with 2l.h$^{-1}$ dripper biofilms.

**Figure 7. PCoA ordination plot of bacterial communities found in 1 l.h-1 (●), 2 l.h-1 (▲) and 4 l.h-1 (■) dripper biofilms at 32 days (A), 72 days (B) and 115 days (C). The analysis was based on Bray-Curtis similarity coefficients. Arrows indicate the orientation and contribution of the OTUs (most significant contributors explaining 50% of the global bacterial divergence).**

## 4. Discussion

The main problem with the use of the drip irrigation supplied with reclaimed wastewater is biofouling. Understanding the development of biofilms is the only way to limit the clogging of drip irrigation systems. In this study, a laboratory experiment was performed to investigate the kinetics of biological clogging and changes in the bacterial communities over time as a function of the hydrodynamic parameters (flow rate, cross-section) of the drippers. Three types of commercial flat drippers used in agriculture with specific channel geometry and different flow rates (1, 2 and 4 $l.h^{-1}$) were installed on a test bench and supplied with treated urban wastewater.

Based on OCT results, the thickness and the volume of biofilm were higher in the inlet of the channel (mostly in the first baffle) in all the drippers and close to the return areas of the labyrinths in 1 and 2 $l.h^{-1}$ drippers (Figure 3 and Figure 5). Simulation of the flow of the milli-channel showed that the fluid velocity and kinetic turbulence energy were lower in these areas (Figure 4). This is consistent with the results obtained by Liu et al., (2019) who analysed the effect of water velocity and nutrient concentration on the development of biofilms in a microchannel device. These authors showed that an increase in velocity from 1.66 $m.s^{-1}$ to 4.17 $m.s^{-1}$ gradually decreased the coverable biofilm over time, increased the nutrient uptake to the biofilm and created a thinner biofilm. The reduction in the velocity at the inlet and return areas can facilitate adhesion and deposition on the surface of the wall (Ait-Mouheb et al., 2018), explaining the sensitivity to clogging of these areas. High shear stress and high-water velocity thus reduce the biofilm maturation process. Biofouling was also more abundant at the corners of the milli-channel from the inlet (Figure 3), where the water velocities and shear stress were lower (Figure 4). It is interesting to note that biofouling also decreased in the vortex zones along the channel even though there was no change in flow behaviours. Flow velocity can influenced the mass transfer (nutrients) and shear stress (Araújo et al., 2016; Liu et al., 2019) along the channel. Monitoring the diffusion of nutrients to the biofilm along the milli-channel from

drippers fed with RWW would improve our understanding of the formation and development of clogging.

The biofouling of the dripper increased over time in all three dripper types tested here but the 1 l.h$^{-1}$ drippers were more sensitive than the 2 and 4 l.h$^{-1}$ drippers (Figure 5). The cross-section of 1 l.h$^{-1}$ drippers (1.02 mm²) is smaller than that of the two others (2 l.h$^{-1}$= 1.12 mm² and 4 l.h$^{-1}$ = 1.17 mm²). Previous studies have shown that a high flow rate and large cross-section reduced clogging of the drippers (Duran-Ros et al., 2009; Ravina et al., 1992). Qian et al. (2017) investigated the development of biofouling of a milli-channel system fed with different quality treated wastewater (secondary, tertiary) and observed that the global growth of biofouling increased linearly over time. In the present study, clogging was monitored by OCT in each baffle of the inlet channel. Thus, we saw for the first time that dripper clogging can alternate between up and down phases, mainly in the first inlet baffles. The down phases may be linked with detachment events (Flemming and Wingender, 2010).

Detachment events appeared to occur more frequently in the 1 l.h$^{-1}$ drippers (Figure 5). The flow characteristic (water velocity, shear stress) could explain the detachment events. Araújo et al., (2016) noted that *Pseudomonas fluorescens* species increased the production of extracellular polymeric substances (EPS) with an increase in water flow velocity (0.1 m.s$^{-1}$ to 0.8 m.s$^{-1}$), which resulted in thinner and denser biofilms. EPS are essential to ensure the maintenance and stability of the biofilm on a surface. Biofilms grown under low velocities are subject to lower shear stress forces which favour faster growth (Melo and Vieira, 1999). However, biofilms subjected to low flow constraints have limited mechanical strength and are more prone to sloughing than those formed at higher flows (Teodósio et al., 2011). Even if the regime was turbulent in all three types of drippers studied here, differences in the Reynolds number and in the water velocities at the channel inlet can influence EPS production and may explain the differences in detachment events observed between the drippers. Biological

processes including effect of bacterial predators can also cause detachment of the biofilm

(Dawn Parry, 2004). Further research on the effect of the internal forces on the biofilm structure

(density, porosity), EPS production and microbial composition will advance our understanding

of biofilm growth phenomena in drippers.

The structure of bacterial community of the RWW has a direct influence on the

composition of the biofilms. Members of the Comamonadaceae family (β-Proteobacteria

including *Hydrogenophaga* genus) dominated in the biofilm samples taken at 32 and 72 days,

but were replaced by the Bacteroidetes_VadinHA17 wastewater sludge group belonging to

Bacteroidetes at the end (Table 5). This non-motile anaerobic Gram-negative group is often

found in sludge and indicated that over time, bacteria commonly found in wastewater settled

and became the majority in communities. Comamonadaceae member family, which includes

many denitrifier members, were also commonly found in wastewater treatment plants and were

involved in the first phases of clogging of membrane bioreactors fed with wastewater (Ziegler

et al., 2016). Other phyla such as Spirochaetae and Cholorobi appeared in the RWW over time

and eventually in the biofilms (Figure 6).  The RWW used in this study was obtained after

treatment by lagooning and the treatment process can affect the structure and bacterial

composition of biofilms. Further research is then needed to study the effect of the

differentwastewater treatments on biofilm composition in irrigation lines in order to improve

management of biofilm development in the drippers.

Diversity and richness did not influenced by hydraulic parameters of the drippers. This

is not consistent with Shi et al. (2019) who studied the effect of hydraulic regime on biofilm

evolved in pipes from drinking water distribution systems. However, these authors used a wider

range of flow rates (120 to 600 $l.h^{-1}$). The differences between the drippers in terms of flow rate

may not be sufficient to observe an effect on these indices.

Although bacterial diversity was not influenced by the hydraulic parameters, the structure of the bacterial community was. This is in agreement with the results of previous studies (Ai et al., 2016; He et al., 2019; Saur et al., 2017). The level of clogging decreased with an increase in water velocity (0.34, 0.61 and 0.78 m.s$^{-1}$ for 1, 2 and 4 l.h$^{-1}$ drippers respectively) and shear stress in the channel. However the structure of bacterial communities appeared to be less affected by water velocity above 0.61 m.s$^{-1}$ (2 l.h$^{-1}$ dripper). Even though previous studies have shown that the increase in velocity and shear forces influence the spatial organization and structure of the bacterial community (Saur et al., 2017), the differences between the 2 and 4 l.h$^{-1}$ drippers may not be sufficient to influence this community in the first phases of biofilm development. This could explain the similarities in the structure of the bacterial communities sampled in 2 and 4 l.h$^{-1}$ drippers compared to the 1 l.h$^{-1}$ dripper biofilms until 115 days.

Proteobacteria, Bacteroidetes, Firmicutes and Chloroflexi were the most abundant phyla in all three types of dripper (Figure 6). These phyla have been already been described in drippers supplied by treated wastewater (Lequette et al., 2019; Song et al., 2019; Zhou et al., 2013) and play a key role in biofilm development. Over time, the relative abundance of Proteobacteria and more specifically β-Proteobacteria decreased significantly in 1 l.h$^{-1}$ dripper biofilms compared to 2 and 4 l.h$^{-1}$ dripper biofilms. β-Proteobacteria have been reported to be a dominant group in both drinking water biofilms (Douterelo et al., 2013) and wastewater biofilms (Biswas and Turner, 2012; Ma et al., 2013) and could play an important role in the formation of biofilm in drippers. This group can easily attach to surfaces and can withstand high water velocity and high shear force (Douterelo et al., 2013), which may explain their dominance in drippers 2 and 4 l.h$^{-1}$. Chloroflexi and Bacteroidetes phyla were also in the majority in dripper biofilms. These phyla are commonly found in activated sludge of wastewater treatment plants and include filamentous bacteria as Anaerolineaceae family members (Chloroflexi) or Saprospiraceae family members (Bacteroidetes).

Research has shown that filamentous bacteria are essential for the formation of activated

sludge but that, in too high a concentration, they are responsible for foaming and bulking events

(Kragelund et al., 2008, 2007; Nielsen et al., 2009) and for clogging membrane bioreactors in

wastewater treatment plants (Li et al., 2008). Thus, we showed for the first time that filamentous

bacteria have a key role in the biofouling of the drippers. The relative abundance of filamentous

bacteria was also influenced by hydraulic properties as the flow rate of the drippers.

Anaerolineaceae family members (Chloroflexi) were more abundant in 1 l.h$^{-1}$ dripper biofilms

at the end than in 2 and 4 l.h$^{-1}$ drippers and could have a key role in biofouling of drippers.

The increase of Chloroflexi over time can also be explained by the interaction with other

bacteria. Chloroflexi and *Hydrogenophaga* spp (Proteobacteria phylum), mainly found in 1 l.h$^{-1}$

drippers, were also observed by Ziegler et al. (2016) who studied the biofouling of a pilot-

scale membrane bioreactor fed with wastewater. From a physiological point of view,

*Hydrogenophaga* spp. are able to synthesise polymeric substances (Calderer et al., 2014).

Filamentous Chloroflexi produces a complex of enzymes able to degrade EPS, in turn, enabling

the cells to use EPS as substrate to maintain their activities (Kragelund et al., 2007). EPS

produced by *Hydrogenophaga* spp could facilitate fouling due to filamentous bacteria and flow

parameters. Thus, the increase in Chloroflexi abundance over time could be explained by a

sufficient EPS rate and by the presence of *Hydrogenophaga* spp at the early stage biofilm

formation.

The divergence between the 1 l.h$^{-1}$ drippers and the 2 and 4 l.h$^{-1}$ drippers prevailed over

time and was mainly driven by *Hydrogenophaga* and *Pseudoxanthomonas* genera (Figure 7).

Although no clear information is available on the effect of hydraulic conditions on the

installation of these two bacterial genera, they are often found in biofilms associated with

membrane reactor clogging supplied by wastewater (Zheng et al., 2018; Ziegler et al., 2016).

Contrary to the 1 l.h$^{-1}$ dripper biofilms, biofilms from the 4 l.h$^{-1}$ dripper were mainly driven by

*Aquabacterium* (Proteobacteria) and *Ideonella* (Proteobacteria, Comamonadaceae family)

genera after 4 months. These genera were already found associated to wastewater biofilms

(Lequette et al., 2019; Luo et al., 2017; McCormick et al., 2016) and included species able to

metabolize plasticizers used in plastics (Kalmbach et al., 1999; Tanasupawat et al., 2016). Thus

the type of material and the hydraulic parameters of the drippers could influence the presence

of bacteria with specific metabolic activities over time.

**5.  Conclusion**

The combined use of OCT and high throuput sequencing highlighted the influence of

hydrodynamic parameters (flow rate, cross-section) of the drippers supplied with RWW on

biofilm development and bacterial communities:

1) Biofouling was facilitated close to the inlet and in the vortex zones of the dripper

channels, more specifically in $1l.h^{-1}$ drippers, due to lower turbulence kinetic energy

and water velocity.

2) The water velocity influenced the structure of bacterial communities in biofilms.

However, the slight differences between 2 and 4 $l.h^{-1}$ would explain the similarities

in the structure of the bacterial community compared to those of the 1 $l.h^{-1}$ dripper

biofilms.

3) The low flow velocities in the 1 $l.h^{-1}$ drippers seemed to favour the presence of

*Hydrogenophaga* and *Pseudoxanthomonas* genera in the first stage of biofilm

development and the installation of filamentous bacteria belonging to Chloroflexi

phylum at the end.

Water velocity evolves along the channel with low velocities at the inlet and in the vortex zones.

These changes can influence the transport of nutrients to the biofilm along the channel. Further

studies on nutrient transport and on the structure of the bacterial community of the biofilms

along the drippers should increase our understanding of clogging phenomena in sensitive areas.

**Acknowledgements**

The authors gratefully acknowledge the financial support of the French Water Agency, project

"Experimental platform for the reuse of reclaimed wastewater in irrigation, Murviel-lès-

Montpellier". We thank Guillaume Guizard (LBE-INRA, Narbonne, France) and Jean-François

Bonicel (IRSTEA, Montpellier, France) for their contribution to the development of the dripper

system, Annabelle Mange (IRSTEA, Montpellier, France) and Valérie Bru-Adam (LBE-INRA,

Narbonne, France) for their assistance in the field and at laboratory.

**Disclosure statement**

No potential conflict of interest was reported by the authors. Authors have approved the final

article.

**References**

Ai, H., Xu, J., Huang, W., He, Q., Wang, Y., Ni, B., 2016. Mechanism and kinetics of biofilm

growth process influenced by shear stress in sewers. Water Sci. Technol. 73, 1572–1582.

https://doi.org/10.2166/wst.2015.633

Ait-Mouheb, N., Schillings, J., Al-Muhammad, J., Bendoula, R., Tomas, S., Amielh, M.,

Anselmet, F., 2018. Impact of hydrodynamics on clay particle deposition and biofilm

development in a labyrinth-channel dripper. Irrig. Sci. 0, 0.

https://doi.org/10.1007/s00271-018-0595-7

Al-Muhammad, J., Tomas, S., Anselmet, F., 2016. Modeling a weak turbulent flow in a

narrow and wavy channel: case of micro-irrigation. Irrig. Sci. 34, 361–377.

https://doi.org/10.1007/s00271-016-0508-6

Araújo, P.A., Malheiro, J., Machado, I., Mergulhão, F., Melo, L., Simões, M., 2016. Influence

of Flow Velocity on the Characteristics of Pseudomonas fluorescens Biofilms. J.

Environ. Eng. 142, 04016031. https://doi.org/10.1061/(ASCE)EE.1943-7870.0001068

Besemer, K., 2015. Biodiversity, community structure and function of biofilms in stream

ecosystems. Res. Microbiol. 166, 774–781. https://doi.org/10.1016/j.resmic.2015.05.006

Biswas, K., Turner, S.J., 2012. Microbial community composition and dynamics of moving

bed biofilm reactor systems treating municipal sewage. Appl. Environ. Microbiol. 78,

855–864. https://doi.org/10.1128/AEM.06570-11

Bounoua, S., Tomas, S., Labille, J., Molle, B., Granier, J., Haldenwang, P., Izzati, S.N., 2016.

Understanding physical clogging in drip irrigation: in situ, in-lab and numerical

approaches. Irrig. Sci. 34, 327–342. https://doi.org/10.1007/s00271-016-0506-8

Calderer, M., Martí, V., de Pablo, J., Guivernau, M., Prenafeta-Boldú, F.X., Viñas, M., 2014.

Effects of enhanced denitrification on hydrodynamics and microbial community

structure in a soil column system. Chemosphere 111, 112–119.

https://doi.org/10.1016/j.chemosphere.2014.03.033

Clarke, K.R., 1993. Non-parametric multivariate analyses of changes in community structure.

Aust. J. Ecol. 18, 117–143. https://doi.org/10.1071/WR9840181

Dawn Parry, J., 2004. Protozoan Grazing of Freshwater Biofilms. Adv. Appl. Microbiol. 54.

Derlon, N., Peter-Varbanets, M., Scheidegger, A., Pronk, W., Morgenroth, E., 2012.

Predation influences the structure of biofilm developed on ultrafiltration membranes.

Water Res. 46, 3323–3333. https://doi.org/10.1016/j.watres.2012.03.031

Dosoretz, C.G., Tarchitzky, J., Katz, I., Kenig, E., Chen, Y., 2010. Fouling in Microirrigation

Systems Applying Treated Wastewater Effluents. Treat. Wastewater Agric. Use Impacts

Soil Environ. Crop. 328–350. https://doi.org/10.1002/9781444328561.ch10

Douterelo, I., Sharpe, R.L., Boxall, J.B., 2013. Influence of hydraulic regimes on bacterial

community structure and composition in an experimental drinking water distribution

system. Water Res. 47, 503–516. https://doi.org/10.1016/j.watres.2012.09.053

Dreszer, C., Wexler, A.D., Drusová, S., Overdijk, T., Zwijnenburg, A., Flemming, H.C.,

Kruithof, J.C., Vrouwenvelder, J.S., 2014. In-situ biofilm characterization in membrane

systems using Optical Coherence Tomography: Formation, structure, detachment and

impact of flux change. Water Res. 67, 243–254.

https://doi.org/10.1016/j.watres.2014.09.006

Duran-Ros, M., Puig-Bargués, J., Arbat, G., Barragán, J., Cartagena, F.R. de, 2009. Effect of

filter, emitter and location on clogging when using effluents. Agric. Water Manag. 96,

67–79. https://doi.org/10.1016/j.agwat.2008.06.005

Edgar, R.C., Haas, B.J., Clemente, J.C., Quince, C., Knight, R., 2011. UCHIME improves

sensitivity and speed of chimera detection. Bioinformatics 27, 2194–2200.

https://doi.org/10.1093/bioinformatics/btr381

Flemming, H., Wingender, J., 2010. The biofilm matrix. Nat. Rev. Microbiol. 8, 623–33.

https://doi.org/10.1038/nrmicro2415

Gamri, S., Soric, A., Tomas, S., Molle, B., Roche, N., 2014. Biofilm development in micro-

irrigation emitters for wastewater reuse. Irrig. Sci. 32, 77–85.

https://doi.org/10.1007/s00271-013-0414-0

He, Q., Chen, L., Zhang, S., Chen, R., Wang, H., 2019. Hydrodynamic shear force shaped the

microbial community and function in the aerobic granular sequencing batch reactors for

low carbon to nitrogen (C/N) municipal wastewater treatment. Bioresour. Technol. 271,

48–58. https://doi.org/10.1016/j.biortech.2018.09.102

Kalmbach, S., Manz, W., Wecke, J., Szewzyk, U., 1999. Aquabacterium gen. nov., with

description of Aquabacterium citratiphilum sp. nov., Aquabacterium parvum sp. nov.

and Aquabacterium commune sp. nov., three in situ dominant bacterial species from the

Berlin drinking water system. Int. J. Syst. Bacteriol. 49, 769–777.

https://doi.org/10.1099/00207713-49-2-769

Katz, S., Dosoretz, C., Chen, Y., Tarchitzky, J., 2014. Fouling formation and chemical control

in drip irrigation systems using treated wastewater. Irrig. Sci. 32, 459–469.

https://doi.org/10.1007/s00271-014-0442-4

Kragelund, C., Levantesi, C., Borger, A., Thelen, K., Eikelboom, D., Tandoi, V., Kong, Y.,

Krooneman, J., Larsen, P., Thomsen, T.R., Nielsen, P.H., 2008. Identity, abundance and

ecophysiology of filamentous bacteria belonging to the Bacteroidetes present in activated

sludge plants. Microbiology 154, 886–894. https://doi.org/10.1099/mic.0.2007/011684-0

Kragelund, C., Levantesi, C., Borger, A., Thelen, K., Eikelboom, D., Tandoi, V., Kong, Y.,

Van Der Waarde, J., Krooneman, J., Rossetti, S., Thomsen, T.R., Nielsen, P.H., 2007.

Identity, abundance and ecophysiology of filamentous Chloroflexi species present in

activated sludge treatment plants. FEMS Microbiol. Ecol. 59, 671–682.

https://doi.org/10.1111/j.1574-6941.2006.00251.x

Lamm, F.R., Ayars, J.E., Nakayama, F.S., 2007. Maintenance, in: Lamm, F.R., Ayars, J.E.,

Nakayama, F.S. (Eds.), Microirrigation for Crop Production: Design, Operation, and

Management, 13th Edn. Elsevier B.V., Amsterdam, pp. 1–643.

Lazarova, V., Bahri, A., 2005. Water Reuse for Irrigation. CRC Press;, Boca Raton.

Lequette, K., Ait-Mouheb, N., Wéry, N., 2019. Drip irrigation biofouling with treated

wastewater: bacterial selection revealed by high-throughput sequencing. Biofouling 35,

217–229. https://doi.org/10.1080/08927014.2019.1591377

Li, G.B., Li, Y.K., Xu, T.W., Liu, Y.Z., Jin, H., Yang, P.L., Yan, D.Z., Ren, S.M., Tian, Z.F.,

2012. Effects of average velocity on the growth and surface topography of biofilms

attached to the reclaimed wastewater drip irrigation system laterals. Irrig. Sci. 30, 103–

113. https://doi.org/10.1007/s00271-011-0266-4

Li, J., Li, Y., Ohandja, D.G., Yang, F., Wong, F.S., Chua, H.C., 2008. Impact of filamentous

bacteria on properties of activated sludge and membrane-fouling rate in a submerged

MBR. Sep. Purif. Technol. 59, 238–243. https://doi.org/10.1016/j.seppur.2007.06.011

Liu, H., Huang, G., 2009. Laboratory experiment on drip emitter clogging with fresh water

and treated sewage effluent. Agric. Water Manag. 96, 745–756.

https://doi.org/10.1016/j.agwat.2008.10.014

Liu, N., Skauge, T., Landa-Marbán, D., Hovland, B., Thorbjørnsen, B., Radu, F.A., Vik, B.F.,

Baumann, T., Bødtker, G., 2019. Microfluidic study of effects of flow velocity and

nutrient concentration on biofilm accumulation and adhesive strength in the flowing and

no-flowing microchannels. J. Ind. Microbiol. Biotechnol. 46, 855–868.

https://doi.org/10.1007/s10295-019-02161-x

Luo, J., Lv, P., Zhang, J., Fane, A.G., McDougald, D., Rice, S.A., 2017. Succession of

biofilm communities responsible for biofouling of membrane bioreactors (MBRs). PLoS

One 12, 1–23. https://doi.org/10.1371/journal.pone.0179855

Ma, J., Wang, Z., Zou, X., Feng, J., Wu, Z., 2013. Microbial communities in an anaerobic

dynamic membrane bioreactor (AnDMBR) for municipal wastewater treatment:

Comparison of bulk sludge and cake layer. Process Biochem. 48, 510–516.

https://doi.org/10.1016/j.procbio.2013.02.003

Mahfoud, C., El Samrani, A., Mouawad, R., Hleihel, W., El Khatib, R., Lartiges, B.S.,

Ouaïni, N., 2009. Disruption of biofilms from sewage pipes under physical and chemical

conditioning. J. Environ. Sci. 21, 120–126. https://doi.org/10.1016/S1001-

0742(09)60021-8

McCormick, A.R., Hoellein, T.J., London, M.G., Hittie, J., Scott, J.W., Kelly, J.J., 2016.

Microplastic in surface waters of urban rivers: Concentration, sources, and associated

bacterial assemblages. Ecosphere 7. https://doi.org/10.1002/ecs2.1556

McMurdie, P., Holmes, S., 2012. PHYLOSEQ: a biocondutor package for handling and

analysis of high-throughput phylogenetic sequence data. Pac Symp Biocomput 235–246.

Melo, L.F., Vieira, M.J., 1999. Physical stability and biological activity of biofilms under

turbulent flow and low substrate concentration. Bioprocess Eng. 20, 363–368.

https://doi.org/10.1007/s004490050604

Morgenroth, E., Milferstedt, K., 2009. Biofilm engineering: Linking biofilm development at

different length and time scales. Rev. Environ. Sci. Biotechnol. 8, 203–208.

https://doi.org/10.1007/s11157-009-9163-1

Nguyen, N.-P., Warnow, T., Pop, M., White, B., 2016. A perspective on 16S rRNA

operational taxonomic unit clustering using sequence similarity. npj Biofilms

Microbiomes 2, 16004. https://doi.org/10.1038/npjbiofilms.2016.4

Nielsen, P.H., Kragelund, C., Seviour, R.J., Nielsen, J.L., 2009. Identity and ecophysiology of

filamentous bacteria in activated sludge. FEMS Microbiol. Rev. 33, 969–998.

https://doi.org/10.1111/j.1574-6976.2009.00186.x

Niu, W., Liu, L., Chen, X., 2013. Influence of fine particle size and concentration on the

clogging of labyrinth emitters. Irrig. Sci. 31, 545–555. https://doi.org/10.1007/s00271-

012-0328-2

Pope, S.B., 2000. Turbulent Flows, Measurement Science and Technology.

https://doi.org/10.1088/0957-0233/12/11/705

Qian, J., Horn, H., Tarchitzky, J., Chen, Y., Katz, S., Wagner, M., 2017. Water quality and

daily temperature cycle affect biofilm formation in drip irrigation devices revealed by

optical coherence tomography. Biofouling 7014, 1–11.

https://doi.org/10.1080/08927014.2017.1285017

Ravina, I., Paz, E., Sofer, Z., Marcu, A., Shisha, A., Sagi, G., 1992. Control of emitter

clogging in drip irrigation with reclaimed wastewater. Irrig. Sci. 13, 129–139.

https://doi.org/10.1007/BF00191055

Rickard, A.H., Mcbain, A.J., Stead, A.T., Gilbert, P., 2004. Shear Rate Moderates

Community Diversity in Freshwater Biofilms Shear Rate Moderates Community

Diversity in Freshwater Biofilms. Society 70, 7426–7435.

https://doi.org/10.1128/AEM.70.12.7426

Saur, T., Morin, E., Habouzit, F., Bernet, N., Escudié, R., 2017. Impact of wall shear stress on

initial bacterial adhesion in rotating annular reactor. PLoS One 12, 1–19.

https://doi.org/10.1371/journal.pone.0172113

Schindelin, J., Arganda-Carrera, I., Frise, E., Verena, K., Mark, L., Tobias, P., Stephan, P.,

Curtis, R., Stephan, S., Benjamin, S., Jean-Yves, T., Daniel, J.W., Volker, H., Kevin, E.,

Pavel, T., Albert, C., 2009. Fiji - an Open platform for biological image analysis. Nat.

Methods 9, 241. https://doi.org/10.1038/nmeth.2019.Fiji

Schloss, P.D., Westcott, S.L., Ryabin, T., Hall, J.R., Hartmann, M., Hollister, E.B.,

Lesniewski, R.A., Oakley, B.B., Parks, D.H., Robinson, C.J., Sahl, J.W., Stres, B.,

Thallinger, G.G., Van Horn, D.J., Weber, C.F., 2009. Introducing mothur: open-source,

platform-independent, community-supported software for describing and comparing

microbial communities. Appl. Environ. Microbiol. 75, 7537–41.

https://doi.org/10.1128/AEM.01541-09

Shi, Y., Babatunde, A., Bockelmann-Evans, B., Webster, G., 2019. Influence of hydraulic

regimes and Cl 2 /NH 3 -N mass ratios on the bacterial structure and composition in an

experimental flow cell chloraminated drinking water system. Environ. Sci. Water Res.

Technol. 5, 977–992. https://doi.org/10.1039/c9ew00015a

Song, P., Zhou, B., Feng, G., Brooks, J.P., Zhou, H., Zhao, Z., Liu, Y., Li, Y., 2019. The

influence of chlorination timing and concentration on microbial communities in labyrinth

channels: implications for biofilm removal. Biofouling 1–15.

https://doi.org/10.1080/08927014.2019.1600191

Tanasupawat, S., Takehana, T., Yoshida, S., Hiraga, K., Oda, K., 2016. Ideonella sakaiensis

sp. nov., isolated from a microbial consortium that degrades poly(ethylene terephthalate).

Int. J. Syst. Evol. Microbiol. 66, 2813–2818. https://doi.org/10.1099/ijsem.0.001058

Teodósio, J.S., Simões, M., Melo, L.F., Mergulhão, F.J., 2011. Flow cell hydrodynamics and

their effects on E. coli biofilm formation under different nutrient conditions and

turbulent flow. Biofouling 27, 1–11. https://doi.org/10.1080/08927014.2010.535206

Wang, J., Gong, S., Xu, D., Yu, Y., Zhao, Y., 2013. Impact of drip and level-basin irrigation

on growth and yield of winter wheat in the North China Plain. Irrig. Sci. 31, 1025–1037.

https://doi.org/10.1007/s00271-012-0384-7

Wang, Y., Qian, P.Y., 2009. Conservative fragments in bacterial 16S rRNA genes and primer

design for 16S ribosomal DNA amplicons in metagenomic studies. PLoS One 4.

https://doi.org/10.1371/journal.pone.0007401

Wei, Z., 2011. Application of RP and Manufacturing to Water-Saving Emitters, in: Advanced

Applications of Rapid Prototyping Technology in Modern Engineering. InTech.

https://doi.org/10.5772/22401

West, S., Wagner, M., Engelke, C., Horn, H., 2016. Optical coherence tomography for the in

situ three-dimensional visualization and quantification of feed spacer channel fouling in

reverse osmosis membrane modules. J. Memb. Sci. 498, 345–352.

https://doi.org/10.1016/j.memsci.2015.09.047

Worako, A.W., 2015. Evaluation of the water quality status of Lake Hawassa by using water

quality index , Southern Ethiopia. Int. J. Water Resour. Environ. Eng. 7, 58–65.

https://doi.org/10.5897/IJWREE2014.

Yan, D., Bai, Z., Rowan, M., Gu, L., Shumei, R., Yang, P., 2009. Biofilm structure and its

influence on clogging in drip irrigation emitters distributing reclaimed wastewater. J.

Environ. Sci. 21, 834–841. https://doi.org/10.1016/S1001-0742(08)62349-9

Yan, D., Yang, P., Rowan, M., Ren, S., Pitts, D., 2010. Biofilm Accumulation and Structure

in the Flow Path of Drip Emitters Using Reclaimed Wastewater. Trans. Asabe 53, 751–

758. https://doi.org/10.13031/2013.30080

Yu, Y., Lee, C., Kim, J., Hwang, S., 2005. Group-specific primer and probe sets to detect

methanogenic communities using quantitative real-time polymerase chain reaction.

Biotechnol. Bioeng. 89, 670–679. https://doi.org/10.1002/bit.20347

Zheng, L., Yu, D., Wang, G., Yue, Z., Zhang, C., Wang, Y., Zhang, J., Wang, J., Liang, G.,

Wei, Y., 2018. Characteristics and formation mechanism of membrane fouling in a full-

scale RO wastewater reclamation process: Membrane autopsy and fouling

characterization. J. Memb. Sci. 563, 843–856.

https://doi.org/10.1016/j.memsci.2018.06.043

Zhou, B., Li, Y., Pei, Y., Liu, Y., Zhang, Z., Jiang, Y., 2013. Quantitative relationship

between biofilms components and emitter clogging under reclaimed water drip

irrigation. Irrig. Sci. 31, 1251–1263. https://doi.org/10.1007/s00271-013-0402-4

Zhou, B., Wang, T., Li, Y., Bralts, V., 2017. Effects of microbial community variation on bio-

clogging in drip irrigation emitters using reclaimed water. Agric. Water Manag. 194,

139–149. https://doi.org/10.1016/j.agwat.2017.09.006

Ziegler, A.S., McIlroy, S.J., Larsen, P., Albertsen, M., Hansen, A.A., Heinen, N., Nielsen,

P.H., 2016. Dynamics of the fouling layer microbial community in a membrane

bioreactor. PLoS One 11, 1–14. https://doi.org/10.1371/journal.pone.0158811