PeskAAS: A near-real-time, open-source monitoring and analytics system
for small-scale fisheries

Alexander Tilley[a]*, Shaun P. Wilkinson[bc]

[a]WorldFish, Jalan Batu Maung, Batu Maung, 11960 Bayan Lepas, Penang, Malaysia

[b]School of Biological Sciences, Victoria University of Wellington. P.O. Box 600, Wellington, New
Zealand

[c]Wilderlab, Wellington, New Zealand

*Corresponding author
E-mail: alex.tilley@gmail.com

Abstract

Small-scale fisheries are responsible for half of the global fish catch, and fisheries-dependent data

underpin scientific guidance of management and conservation, yet we have almost no data on their

activities and production over time and space. We use open source software components including

the *Shiny* R package to build `peskAAS`, an adaptable and scalable digital workflow to collate, classify,

integrate, analyse and visualise small-scale fisheries data. The main features of `peskAAS` are: (i) it is

fully open-source and free to deploy and use (ii) it is component-based to be flexible for integration

of vessel tracking data and existing catch documentation elements; (iii) it provides spatial and

temporal filtering of relative fishing productivity by fishing method and habitat (iv) it integrates

FishBase open-source and regularly updated species-based growth parameters (v) the end user click-

button dashboard is specifically co-designed for easy interpretation of fisheries production data. With

limited training and code adaptation, the `peskAAS` workflow can be deployed for use by fisheries

stakeholders, managers and scientists as a platform for high resolution, near-real-time production

data from small-scale fisheries for the first time.

INTRODUCTION

Approximately half of the global catch of fish is landed in small-scale fisheries (SSF), yet the ability for

science to guide the sustainable exploitation of these resources is inhibited by a massive data gap.

There are 40 million people actively fishing in inland and coastal systems worldwide, yet due to the

challenges involved in collecting data in such dispersed, informal and diverse contexts of SSF, the

contributions of this fish food system to livelihoods and food security are hidden and undersold [1].

As a result, fish has been largely absent in the development of food-based approaches for greater food

security and nutrition [2]. However, recent research shows that nutrient quality of fish is determined

by species composition not quantity [3], so for many countries whose populations suffer from

inadequate nutrient intake, fish-based food strategies could be an effective strategy.

To improve fisheries management, and realise the nutritional and food security potential of fish we

require data on fish production over time and space, but most small-scale fishing occurs in low-income

countries that lack the resources and capacity to collect, store or analyse these data [4]. Even with

adequate data, fisheries management relies on statistical models and analytics that were developed

for single species fisheries, rather than biodiverse tropical reef fisheries [5]. Many valuable tools have

been developed for single species stocks (see [6], but very few exist to assist in the analysis and

management of mixed species fisheries. This leads to a situation where management and policies are

built on poor government estimates or reconstructed trade and consumption statistics which are

often not relevant at the local scale, and hence are highly susceptible to governance and management

failures [7].

Over the past two decades the proliferation of information and communication technologies (ICTs)

has revolutionised the collection, communication and storage of data in the industrial fishing sector,

as well as more broadly in agriculture [8] through design and development of mobile smartphone

applications and digital survey forms [9]. There are some examples of applications and tools to collect

fisheries data on a small scale, the most successful of which are generally 'high touch', meaning they

involve significant contextual development that cannot easily be scaled to other systems or

geographies (see [10–13]. The danger in developing scalable technologies is that they are often

imposed as prescribed 'solutions' on low-income countries, and can merely reinforce the capacity gap,

alienate managers and stakeholders, and be ill-suited to the contextual reality [14,15]. There is an

urgent need for a light touch, scalable and integrated approach to data collection and analytics, but

thus far this has been elusive in terms of getting simple, usable data in the hands of fisheries managers.

Here, we describe a new digital pipeline called `peskAAS` - a pseudo-acronym for fisheries (*peskas*)

in the national language of Timor-Leste, Tetum, combined with Automated Analytics System.

`PeskAAS` connects open source programs to collect, communicate, analyse and visualise SSF

movement and catch data. This application was designed to test how scripted analytics can assist

fisheries management by generating digestible, summarised information rapidly for decision-making

in data-deficient and low capacity systems. We provide examples to illustrate the types of analytics

and machine learning that the system can be used to carry out. Our test site of Timor-Leste was chosen

due to the very limited level of fisheries development, the paucity of information, and the limited

fisheries governance capacity.

`peskAAS` **OVERVIEW**

PeskAAS is an interactive web-hosted R *Shiny* application developed to facilitate data exploration and

decision-making processes in small-scale fisheries. This application accesses the 'peskaDAT' database

in real-time using the `DBI` and `RMySQL` R packages [16,17], and pulls landing records into a web-

based interactive R session (hosted by https://www.shinyapps.io), from which users can apply

dynamic location, gear, habitat and date-range filters to create informative plots for catch per unit

effort (CPUE), total catch, species composition and total national catch estimates (Figure 1).

Figure 1. Screenshot from the interactive PeskAAS Shiny platform developed to visualise near-real

time fish landings data in Timor-Leste. https://worldfish.shinyapps.io/peskAAS/

The user interface incorporates tick-box widgets for dynamic selection of sites, fishing habitats and

gear types, and a slider widget is included for users to fit splines to the CPUE data and dynamically

adjust the smoothing parameter to aid in visualization. Users also have an option to download a

month-aggregated summary table in .csv format for further analysis, using a download-button widget.

The application is hosted remotely by shinyapps.io (https://www.shinyapps.io/) on the free pricing

tier, which currently allows 25 active hours of use per month. Users can also run the application locally,

by cloning the repository from GitHub and launching the application from a local R session, or by

installing RStudio Shiny Server (https://www.rstudio.com/products/shiny/shiny-server/) and hosting

the application on a local machine.

The digital analysis pipeline consists of a network of freely available components for data collection,

storage, manipulation and analysis, catering for humanitarian organizations with low usage

requirements (< 25 active hours per month) (Figure 2). The pipeline is scalable for higher usage levels

with modest subscription levies for KoBo toolbox, Shiny (https://www.shinyapps.io), Heliohost

(https://www.heliohost.org) and Google Cloud Platform (GCP; https://cloud.google.com).

Figure 2. Automated digital analytics pipeline for Timor-Leste fisheries catch data

<u>Catch documentation at landing sites</u>

Fisheries catch data were collected on 3G-enabled tablets using a digital survey form developed in

KoBo toolbox (http://www.**kobotoolbox**.org/), by locally-employed data collectors at 25 key landing

sites across 11 coastal districts in Timor-Leste (figure 3). One collector was hired in each coastal

municipality. Atauro Island to the north of Dili falls within the municipality of Dili, and is a

disproportionately important area for national fisheries with a high population of fishers so 3

collectors record landings across 12 small landing sites. Collectors interview individual fishers on a

daily basis to collect data on transport type (boat type/shore), gear type, habitat type where fishing

took place (reef, fish aggregating device, deep, shore or mangrove), number of fishers (men, women

and children), trip duration, species or species group[1], size and number caught by species or species

group, and sale price if applicable. The landings form evolved through time to integrate a growing list

of fishers and identified species, and in response to various feedback mechanisms.

---

[1] All except the most important species landed in the fishery were grouped by ISSCAAP groups within families, (FAO International Standard Statistical Classification of Aquatic Animals and Plants), or by family (see Supplementary information 2).

Figure 3. Map of Timor-Leste illustrating landing sites where small-scale fisheries catch was recorded

using tablets.

<u>peskaDAT database</u>

We developed a cloud-based MySQL database of filtered landings records called 'peskaDAT', to host

cleaned and checked fisheries landings data, geo-located boat tracks and ancillary tables such as

species, boat, gear and habitat information in an easily accessible and mutable format (Supplementary

information 1). This database is hosted by Heliohost, a free hosting platform with several MySQL

relational database servers. A monthly database backup is created and stored locally in `.rds` format

(an R binary data file) in a Dropbox folder to ensure data perpetuity and backwards compatibility.

<u>peskaPARSE.R script</u>

To automatically access landing records from KoBo toolbox, and filter, manipulate and submit the

cleaned records to the peskaDAT database on a regular (daily) basis, we developed an R script called

'peskaPARSE.R' (supplementary file 2) that is scheduled on a daily cron job (a command to a server to

be executed at a specified time) run on a GCP virtual machine. The script first accesses the KoBo

toolbox API (application programming interface - that allows access to the data) and pulls the new

catch records into the R environment. The catch weight for each new record is estimated using von

Bertalanffy growth function (VBGF) parameters obtained from FishBase (www.fishbase.org) using the

rfishbase R package [18]. Several filters are applied, including species-specific length, number of

individuals, weight and price boundary checks, formatting error checks, and invalid gear/habitat

combination checks. Suspect entries are flagged for curation by a moderator, and their values are

automatically suppressed from contributing to downstream applications (including the `peskAAS`

data exploration tool described below) until records are amended in the KoBo toolbox dashboard. This

is achieved *via* prompt follow-up clarification with field-based observers, to ascertain whether data

entry errors were made during form submission or whether the record in question is a genuine outlier.

To automatically run the peskaPARSE.R script on a daily basis, we deployed a free Ubuntu 18.04

minimal virtual machine (VM) instance on the Google Cloud Platform (GCP), transferred the script to

a convenient user directory (specified by the [address] argument below), and scheduled a 24-hourly

cron job by appending the following line to the /etc/crontab file:

```
0 * * * root Rscript -e  'source("[address]")'
```

133   where `[address]` is replaced by the web location of the R script. In our case we stored the script in

134   a publicly available dropbox directory and modified the public link to terminate with `download=1`

135   to enable direct sourcing. See the GitHub repository at https://github.com/shaunpwilkinson/peskAAS

136   for further details. For the script to successfully import the raw trip- and species-landing records from

137   the KoBo and Pelagic Data Systems APIs, and deposit the filtered records in the peskaDAT MySQL

138   database, three authorization files must be stored in the same directory as the peskaPARSE.R file: a

139   single-line text file named KoBo-auth.txt containing the KoBo toolbox username and password,

140   delimited by a colon operator, and similarly-formatted files containing log-on credentials for the

141   Pelagic Data Systems dashboard (PDS-auth.txt) and the peskaDAT MySQL database (peskaDB-auth.txt;

142   user with SELECT privileges). The regular gleaning and filtering of new landings records ensures that

143   the data available for analysis and visualization are timely and trustworthy.

144   <u>Geospatial vessel tracking</u>

145   Shore-based data collectors are, of course, unable to sample catch from all fishing trips exhaustively,

146   so to extrapolate fish production from individual trips to community, municipal and national levels,

147   and to visualise geospatial fishing effort, we installed tamperproof solar-powered GPS units developed

148   by Pelagic Data Systems Inc. (San Francisco, CA) on to 5-15 boats per landing site (N = 437). Trackers

149   recorded point location data every 5 seconds and communicated those data when in range of a cellular

150   network (Figure 4). Vessel tracks were also linked to the trip's catch data, where available, using the

151   unique GPS unit ID, allowing us to train a model to predict unknown variables for trips with GPS data

152   only, such as gear and habitat type).

154   **Figure 4**. The relative effort heat map of small-scale fishing vessel tracks between August 2018 and

155   February 2020 in Timor-Leste from the `peskAAS` dashboard

156   Fisheries analytics

157   To quantify relative fishing success over time and space, the catch-per-unit-effort (CPUE) is used as a

158   metric for relative fish abundance, and to track the response of fish stocks to fishing pressure. For

159   CPUE, a standard unit of *effort* is required. For `peskAAS`, we use raw CPUE, with effort standardized

160   into the unit of *fisher-hours* on each fishing trip, calculated as the trip duration in hours multiplied by

161   the number of fishers on board[2].

162   To generate accurate regional and national catch and CPUE estimates, it is necessary to estimate the

163   frequency and duration of fishing trips for each boat type, known as a vessel activity coefficient (VAC).

164   To generate an accurate VAC accounting for differences in boat type, vessel tracks were used to

165   generate monthly VAC values according to motorized and non-motorized vessels, and were used to

166   calculate the first accurate national scale estimates of fish production in Timor-Leste (equation 1).

167   The national monthly catch (in tons; C) is estimated as:

168      $$C = \sum_b \quad CPUE_b \times EPT_b \times VAC_b \times N_b \times 0.001 \qquad \text{(Equation 1)}$$

169   where b refers to the boat type (canoe or motor-powered), $CPUE$ is the monthly catch per unit effort

170   (averaged across all sites, in Kg per hour), EPT is the median effort per trip (person-hours), VAC is the

171   vessel activity coefficient (average number of trips per month) and N_b is the total number of boats of

172   type b in the national fleet (national fisher and boat census data obtained from the Timor-Leste

173   Ministry of Agriculture and Fisheries).

174   <u>Supervised prediction of missing trip attributes</u>

175   The integration of shore-based observer data with high-resolution geo-located vessel fishing tracks

176   from on-board GPS units from *Pelagic Data Systems* Inc. allowed us to validate a supervised

177   classification approach for predicting gear and habitat types in the case where only GPS data are

178   available (i.e. trips that are tracked but not directly observed). For each tracked but unobserved trip,

179   a donor trip was selected from the subset of trips for which both GPS and observer data are available,

---

[2] The complexity of more robust CPUE standardization (see [19]) of multiple gear types in tropical, multi-habitat, mixed species fisheries makes it impractical in a livelihoods context, so fisher hours is used as a unit applicable across all fisheries and scales.

180   based on spatial nearest-neighbour analysis. To achieve this, ten temporally-spaced, two-dimensional

181   GPS points from each trip were used to generate training- and query-data matrices for input into the

182   `nn2` function in the `RANN` R package [20]. Donor trips were assigned based on minimum Euclidean

183   distance and were only assigned if the distance was < 0.20. To validate this approach we randomly

184   allocated the linked trip set to 80% training data and 20% query data, and tested the predictive success

185   rate in terms of number of gear and habitat types correctly predicted in the query set. The nearest-

186   neighbour classification approach correctly predicted 81% of gear types and 90% of habitat types

187   based on a 491 observation training set and a 120 observation query set.

188   **RESULTS & DISCUSSION**

189   `peskAAS` was developed concurrently with the co-generation of a national database of SSF landings

190   with the Timor-Leste National Fisheries Directorate. As of February 2020, 45,737 fishing trips have

191   been geotracked, representing 560,000 km travelled over 350,000 hours. Catch data was recorded for

192   22,375 of these trips, resulting in 34,440 species level landings records representing a total catch

193   weight of 1076 tonnes. This system has already been utilised to test the effectiveness of fish

194   aggregating devices at boosting catch rates by nearshore artisanal fishers [21], and to calculate the

195   first national fisheries production estimates for the Timor-Leste SSF fleet based on landings [22]. In

196   May 2019, the Timorese government adopted and launched this technology as their official national

197   fisheries monitoring system, so on a national level, has passed an important test of legitimacy, and

198   shows potential for sustainability.

199   `PeskAAS` was designed to be a free, online data exploration tool to enable rapid development of

200   simple, near-real time fisheries monitoring systems to generate accurate and timely fish production

201   data to use in adaptive, evidence-based management of fisheries resources. The tracking hardware

202   and data service from Pelagic Data Systems is an optional extra and represents additional costs to

203   users that must be considered in terms of sustainability for users. However, the ability to add spatial

204   context to fisheries data is paramount, and facilitates coastal zone planning that is increasingly

205   politicised in the development of the blue economy.

206   Our initial case study from Timor-Leste indicates that this type of solution is very much needed in

207   situations of low management capacity and resources to track dispersed fisheries. The catch form and

208   scripted analytics require no specialised equipment and the dashboard is displayed in a web browser.

209   However, we acknowledge that `peskAAS` has several limitations. Most notably, the scripted nature

210   of the tool limits its use to those with programming expertise, or implies a need to hire help. Therefore,

211   ongoing work to scale up `peskAAS` will develop its modularity and customisation through templates

212   for catch forms, analytics and dashboards displays, to allow for more flexibility to other fish production

213   systems and countries.

214   The co-design of `peskAAS` with fisheries managers was crucial in building a financially and

215   institutionally sustainable system. Hence, in scaling this tool to other countries and contexts, the need

216   to build local legitimacy and a feeling of ownership among stakeholders will necessitate a process of

217   co-design. The technical capacity in Timor-Leste for digital systems is improving, but as in most low-

218   income country governments the long term maintenance of the system will still require external

219   support. Also, further capacity building is necessary to ensure `peskAAS` outputs are being correctly

220   interpreted to inform policy and guide extension services for fishing communities in Timor-Leste. It

221   remains to be seen if other low-income countries will independently adapt the script to deploy the

222   system for fisheries monitoring elsewhere.

223   In conclusion, `peskAAS` has already influenced national fisheries policy in Timor-Leste as a result of

224   its inclusion in the newly drafted National Fisheries Strategy and revised Fisheries Decree law. We

225   believe it will be an important resource for government and non-government managers, researchers

226   and students looking for a low cost solution to collect and automate the analysis and visualisation of

227   SSF data over space and time.

228 **Acknowledgements**

229 We are very grateful to the Timorese fishers and community members who collaborated with us and

230 Timor-Leste's Ministry of Agriculture and Fisheries in this project, and particularly to WorldFish team

231 members Joctan Dos Reis Lopes, Mario Gomes, Mario Pereira, Pedro Rodrigues and Agustinha Duarte

232 who have provided important local insights throughout the co-design process. The development of

233 `peskAAS` was funded by the Royal Norwegian Embassy in Jakarta and the CGIAR Big Data Platform

234 Inspire Challenge 2018.

235 **Funding statement**

236 This work was undertaken as part of the CGIAR Research Program on Fish Agri-Food Systems (FISH)

237 led by WorldFish. The program is supported by contributors to the CGIAR Trust Fund. Funding support

238 was provided by an Inspire Challenge grant from the CGIAR Research Program on Big Data led by CIAT

239 and IFPRI, and the Fisheries Sector Support Program funded by the Royal Norwegian Embassy in

240 Jakarta.

241 **Author contributions**

242 A.T. conceived and designed the study. S.P.W. coded the various elements of the `peskAAS` pipeline.

243 A.T. and S.P.W. contributed equally to this manuscript.

244 **Data Accessibility**

245 The `peskAAS` catch questionnaire, R script and data used to test the application in this study are

246 archived in Dataverse https://doi.org/10.7910/DVN/TVGIJJ [23]. The `peskAAS` code and

247 documentation is also hosted at https://github.com/shaunpwilkinson/peskAAS.

248 **References**

249 1. Mills DJ, Westlund L, Graaf G de, Kura Y, Willman R, Kelleher K. Under-reported and
250 undervalued: small-scale fisheries in the developing world. In: Pomeroy RS, Andrew NL, editors.
251 Small-scale fisheries management: frameworks and approaches for the developing world.
252 Wallingford: CABI; 2011. pp. 1–15. doi:10.1079/9781845936075.0001

253 2. FAO. The state of world fisheries and aquaculture: Meeting the sustainable development goals.

254   Rome: The Food and Agriculture Organisation of the UN (FAO); 2018.

255   3.   Hicks CC, Cohen PJ, Graham NAJ, Nash KL, Allison EH, D'Lima C, et al. Harnessing global fisheries
256   to tackle micronutrient deficiencies. Nature. 2019;574: 95–98. doi:10.1038/s41586-019-1592-6

257   4.   Kolding J, Béné C, Bavinck M. Small-scale fisheries: Importance, vulnerability and deficient
258   knowledge. Governance of Marine Fisheries and Biodiversity Conservation: Interaction and Co-
259   evolution. 2014; 317–331. doi:10.1002/9781118392607.ch22

260   5.   Kolding J, Van Zwieten PAM. The Tragedy of Our Legacy: How do Global Management
261   Discourses Affect Small Scale Fisheries in the South? Forum Dev Stud. 2011;38: 267–297.
262   doi:10.1080/08039410.2011.577798

263   6.   Mildenberger TK, Taylor MH, Wolff M. TropFishR : an R package for fisheries analysis with
264   length-frequency data. Price S, editor. Methods Ecol Evol. 2017;8: 1520–1527.
265   doi:10.1111/2041-210X.12791

266   7.   Gutiérrez NL, Hilborn R, Defeo O. Leadership, social capital and incentives promote successful
267   fisheries. Nature. 2011;470: 386–389. doi:10.1038/nature09689

268   8.   E-Agriculture Strategy Guide. FAO; 2017. http://www.fao.org/3/a-i5564e.pdf

269   9.   Information and Communications Technologies Benefit Fishing Communities: New Directions in
270   Fisheries - A series of Policy Briefs on Development Issues. Rome: FAO; 2007. Report No.: 7.
271   Available: http://www.fao.org/3/a-a0991e.pdf

272   10.   Jeffers VF, Humber F, Nohasiarivelo T, Botosoamananto R, Anderson LG. Trialling the use of
273   smartphones as a tool to address gaps in small-scale fisheries catch data in southwest
274   Madagascar. Mar Policy. 2019;99: 267–274. doi:10.1016/j.marpol.2018.10.040

275   11.   Petrik, M. & Raemaekers, D.R.S. 2018. The case for supporting small-scale fisheries governance
276   through ICT. No. 177. SAIIA. (available at https://www.africaportal.org/publications/case-
277   supporting-small-scale-fisheries-governance-through-ict/).

278   12.   Tilley A, Roscher MB, Eds. ICT4SSF: The role of Information & Communication Technologies in
279   achieving the objectives of the small-scale fisheries guidelines. FAO/WorldFish; (in press).

280   13.   James M, Mendo T, Jones EL, Orr K, McKnight A, Thompson J. AIS data to inform small scale
281   fisheries management and marine spatial planning. Mar Policy. 2018;91: 113–121.
282   doi:10.1016/j.marpol.2018.02.012

283   14.   Mallalieu KI, Rocke S. Selecting Sustainable ICT Solutions for Pro-poor Intervention: Latin
284   American and Caribbean Perspectives. Digital Poverty: Latin American and Caribbean
285   Perspectives. 2007. pp. 115–136.

286   15.   Donnelly M. Implementing ICTs in Indonesia's Small-Scale Fisheries Development Paradigms
287   that Shape Them. Masters Thesis. Malmo University. 2018.
288   http://muep.mau.se/handle/2043/24803

289   16.   R Special Interest Group on Databases (R-SIG-DB), Wickham H, Müller K. DBI: R Database
290   Interface. 2018. Available: https://CRAN.R-project.org/package=DBI

291   17.   Ooms J, James D, DebRoy S, Wickham H, Horner J. RMySQL: Database Interface and "MySQL"
292   Driver for R. 2019. Available: https://CRAN.R-project.org/package=RMySQL

293   18. Boettiger C, Lang DT, Wainwright PC. rfishbase: exploring, manipulating and visualizing FishBase
294   data from R. J Fish Biol. 2012;81: 2030–2039. doi:10.1111/j.1095-8649.2012.03464.x

295   19. Maunder MN, Punt AE. Standardizing catch and effort data: a review of recent approaches. Fish
296   Res. 2004;70: 141–159. doi:10.1016/j.fishres.2004.08.002

297   20. Arya S, Mount D, Kemp SE, Jefferis G. RANN: Fast Nearest Neighbour Search (Wraps ANN
298   Library) Using L2 Metric. 2019. Available: https://CRAN.R-project.org/package=RANN

299   21. Tilley A, Wilkinson SP, Kolding J, López-Angarita J, Pereira M, Mills DJ. Nearshore Fish
300   Aggregating Devices Show Positive Outcomes for Sustainable Fisheries Development in Timor-
301   Leste. Frontiers in Marine Science. 2019;6: 487. doi:10.3389/fmars.2019.00487

302   22. López-Angarita J, Hunnam KJ, Pereira M, Mills DJ, Pant J, Teoh SJ, et al. Fisheries and
303   aquaculture of Timor-Leste in 2019: Current knowledge and opportunities. Penang, Malaysia:
304   WorldFish; 2019. https://digitalarchive.worldfishcenter.org/handle/20.500.12348/3737

305   23. Tilley A. PeskAAS - National Fisheries Monitoring System of Timor-Leste. Harvard Dataverse;
306   2016. doi:10.7910/DVN/TVGIJJ

307