`PeskAAS`: A near-real-time, open-source monitoring and analytics system
for small-scale fisheries

Alexander Tilley[a]*, Shaun P. Wilkinson[bc]

[a]WorldFish, Jalan Batu Maung, Batu Maung, 11960 Bayan Lepas, Penang, Malaysia

[b]School of Biological Sciences, Victoria University of Wellington. P.O. Box 600, Wellington, New
Zealand

[c]Wilderlab, Wellington, New Zealand

*Corresponding author
E-mail: alex.tilley@gmail.com
10
11

Abstract

Small-scale fisheries are responsible for landing half of world's fish catch, yet there are very sparse

data on these fishing activities and associated fisheries production in time and space. Fisheries-

dependent data underpin scientific guidance of management and conservation of fisheries systems,

but it is inherently difficult to generate robust and comprehensive data for small-scale fisheries,

particularly given their dispersed and diverse nature. In tackling this challenge, we use open source

software components including the *Shiny* R package to build `PeskAAS`; an adaptable and scalable

digital application that enables the collation, classification, analysis and visualisation of small-scale

fisheries catch and effort data. We piloted and refined this system in Timor-Leste; a small island

developing nation. The features that make `PeskAAS` fit for purpose are that it is: (i) fully open-source

and free to use (ii) component-based, flexible and able to integrate vessel tracking data with catch

records; (iii) able to perform spatial and temporal filtering of fishing productivity by fishing method

and habitat; (iv) integrated with species-specific length-weight parameters from *FishBase;* (v)

controlled through a click-button dashboard, that was co-designed with fisheries scientists and

government managers, that enables easy to read data summaries and interpretation of context-

specific fisheries data. With limited training and code adaptation, the `PeskAAS` workflow has been

used as a framework on which to build and adapt systematic, standardised data collection for small-

scale fisheries in other contexts. Automated analytics of these data can provide fishers, managers and

researchers with insights into a fisher's experience of fishing efforts, fisheries status, catch rates,

economic efficiency and geographic preferences and limits that can potentially guide management

and livelihood investments.

INTRODUCTION

Approximately half of the global catch of fish is landed in small-scale fisheries (SSF) [1], yet the ability

for science to guide the sustainable exploitation of these resources is inhibited by substantial data

gaps. There are 40 million people actively fishing in inland and coastal environments worldwide, yet

due to the challenges involved in collecting data in dispersed, informal and diverse fisheries, the contributions of SSF to livelihoods, and food and nutrition security, are frequently hidden and poorly accounted for [2]. As a result, fisheries solutions are underrepresented in investments and policies to address food and nutrition security [3]. Recent research has shown that the nutrients qualities and quantities of fish already caught would be sufficient to address major micronutrient deficiencies for many countries [4], and that fish-based food strategies hold untapped potential to address nutrition short falls.

Refinements to the management of fisheries towards sustainability and food and nutrition security goals can be supported, amongst other things, by higher quality and more comprehensive fisheries and value chain data. Addressing these gaps with small-scale fisheries in low-income countries requires sensitivity to the limits of resources and capacity to collect, store, analyse and respond to these data [5]. Even with adequate data, much fisheries science relies on statistical models and analytics that were developed for single species fisheries, rather than biodiverse tropical fisheries where multiple species frequently comprise the harvests from diverse and biodiverse habitats [6]. Many diagnostic and statistical tools have been developed to support fisheries decision-making or stock assessment in data-poor contexts, e.g., FishPath [7] or TropFishR [8]. However, very few solutions provide end-to-end integration from data collection at the point of fishing or landing, to visualisation of data summaries for managers and fishing communities. This leads to a situation where management and policies are built on poor government estimates or reconstructed trade and consumption statistics that are often not relevant at the local scale, and hence are highly susceptible to governance and management failures [9].

Over the past two decades, the proliferation of information and communication technologies (ICTs) has revolutionised the collection, communication and storage of data in food production sectors, including in the industrial fishing sector [10]. These ICTs innovations commonly include design and development of mobile smartphone applications and digital survey forms [11]. There are some

examples of applications and tools to collect fisheries data on a small scale, the most successful of

which are generally 'high touch', meaning they involve significant contextual development that cannot

easily be scaled to other systems or geographies (see [12–15]). The danger in developing scalable

technologies is that they are often imposed as prescribed 'solutions' on low-income countries, and

can merely reinforce the capacity gap, alienate managers and stakeholders, and be ill-suited to the

contextual reality [16,17]. There is an urgent need for a light touch, scalable and integrated approach

to data collection and analytics, but thus far, this has been elusive in terms of getting simple, usable

data in the hands of fisheries managers.

Here, we describe a new digital application called `PeskAAS` - a pseudo-acronym for fisheries (*peskas*)

in the national language of Timor-Leste, Tetum, combined with Automated Analytics System.

`PeskAAS` connects open source programs to collect, communicate, analyse and visualise SSF

movement and catch data. We piloted `PeskAAS` to determine how scripted analytics can assist

fisheries management by generating digestible, summarised information rapidly for decision-making

in data-deficient and low capacity systems. We provide examples to illustrate the types of analytics

and machine learning that the system can be used to carry out. Our test site of Timor-Leste was chosen

due to the very limited level of fisheries development, the paucity of information, and the limited

fisheries governance capacity.

`PeskAAS` **OVERVIEW**

`PeskAAS` is an interactive web-hosted R *Shiny* application developed to facilitate data exploration

and decision-making processes in small-scale fisheries. This application accesses the 'peskaDAT'

database in real-time using the `DBI` and `RMySQL` R packages [18,19], and pulls catch records collected

by enumerators at landing sites into a web-based interactive R session (hosted by

https://www.shinyapps.io). From this dashboard, users can apply dynamic location, gear, habitat and

date-range filters to create informative plots for catch per unit effort (CPUE), total catch, species

composition and total national catch estimates (Figure 1).

Figure 1. Screenshot from the interactive `PeskAAS` dashboard developed to visualise near-real time

fish landings data in Timor-Leste. https://worldfish.shinyapps.io/`PeskAAS`/

The user interface incorporates tick-box widgets for dynamic selection of municipalities, fishing

habitats, gear types and boat type, and a slider widget is included for users to fit cubic smoothing

splines weighted by trip effort to the CPUE data with a user defined smoothing parameter that is

dynamically adjustable to aid in visualization. Users also have an option to download a month-

aggregated summary table in .csv format for further analysis, using a download-button widget.

The `PeskAAS` application is hosted remotely by shinyapps.io (https://www.shinyapps.io/) on the

free pricing tier, which currently allows 25 active hours of use per month. Users can also run the

application locally, by cloning the repository from GitHub and launching the application from a local R

session, or by installing RStudio Shiny Server (https://www.rstudio.com/products/shiny/shiny-

server/) and hosting the application on a local machine.

The `PeskAAS` application consists of a network of freely available components for data collection,

storage, manipulation and analysis, catering for humanitarian organizations with low usage

requirements (< 25 active hours per month) (Figure 2). The application is scalable for higher usage

levels with modest subscription levies for KoBo toolbox, Shiny (https://www.shinyapps.io), Heliohost

(https://www.heliohost.org) and Google Cloud Platform (GCP; https://cloud.google.com).

Figure 2. A diagrammatic representation of the `PeskAAS` application. From bottom left, the catch

from a fishing vessel is entered into a KoboCollect survey form on a smartphone. These data are

uploaded to the KoboToolbox database (DB). The PesksPARSE.R script pulls these data along with the

movement track of the fishing trip from PDS via an application-programming interface (API) every 24

hours. These data are then checked and filtered, and uploaded to the PeskaDAT database. The

`PeskAAS` Shiny web app queries PeskaDAT and displays near-real-time graphics and analytics.

METHODS

We developed and piloted PeskAAS in Timor-Leste from 2016 to 2019. In May 2019, the Timorese

Government adopted and launched this technology as their official national fisheries monitoring

system.

<u>Catch documentation at landing sites</u>

Fisheries catch data were collected on 3G-enabled android tablets using a digital survey form

developed in KoBo toolbox (http://www.kobotoolbox.org/) a free suite of tools for field data

collection. One data enumerator was hired in each of the 11 coastal districts to cover 25 landing sites

across Timor-Leste (figure 3). Atauro Island to the north of Dili (the national administrative centre)

falls within the municipality of Dili, and is a disproportionately important area for national fisheries

with a high population of fishers, so three enumerators are responsible to record landings across 12

small landing sites. Enumerators interview individual fishers (i.e., the names of fishers are collected,

and their catch profile directly associated to them) when they return from fishing. Data collected

include transport type (motor, canoe, on foot), gear type (gill net, seine net, beach seine, hand line,

long line, spearfishing, trap, gleaning), habitat type where fishing took place (reef, fish aggregating

device, deep, shore or mangrove), number of fishers (i.e., number of men, women and children

engaged in that fishing trip), trip duration (rounded to nearest hour), species or species group, sizes

(fork length to nearest cm) of all fish landed and number caught by species or species group, and the

sale price per kg or per number of fish, if the catch was destined for market. The catch survey form

evolved through time to integrate a growing list of fishers and identified species, and in response to

various feedback mechanisms. Species of particular local importance were selected based on index of

relative importance analysis on Timor-Leste fisheries [20] and these are retained at species level. All

other species captured in the fishery are classified by family, or aggregated further into one of the

nine groups of species constituting the Marine Fishes division of the FAO International Standard

Statistical Classification of Aquatic Animals and Plants [21] (Supplementary information 1).

All research was authorised and conducted in partnership with the Timor-Leste Ministry of Agriculture

and Fisheries. All catch data collection was carried out with the verbal consent of the fisher. All

participation in catch data monitoring and vessel tracking was voluntary, and fishers not willing to

participate were not prejudiced against in any way.

Figure 3. Map of Timor-Leste illustrating landing sites where small-scale fisheries catch was recorded

using smartphones or tablets.

<u>peskaDAT database</u>

We developed a cloud-based MySQL database of filtered landings records called 'peskaDAT', to host

cleaned and checked fisheries landings data, geo-located boat tracks and ancillary tables such as

species, boat, gear and habitat information in an easily accessible and mutable format (Supplementary

information 2). This database is hosted by Heliohost, a free hosting platform with several MySQL

relational database servers. A monthly database backup is created and stored locally in `.rds` format

(an R binary data file) in a Dropbox folder to ensure data perpetuity and backwards compatibility.

<u>peskaPARSE.R script</u>

To automatically access landing records from KoBo toolbox, and filter, manipulate and submit the

cleaned records to the peskaDAT database on a regular (daily) basis, we developed an R script called

'peskaPARSE.R' (supplementary information 3) that is scheduled on a daily cron job (a command to a

server to be executed at a specified time) run on a Google Cloud Platform virtual machine. The script

first accesses the KoBo toolbox API (application programming interface - that allows access to the

data) and pulls the new catch records into the R environment. The catch weight for each new record

is estimated using length-weight parameters obtained from FishBase (www.fishbase.org) using the

rfishbase R package [22]. Several filters are applied according to thresholds including species- or

group-specific length, number of individuals, weight and price boundary checks, formatting error

checks, and invalid gear/habitat combination checks. Suspect entries are flagged for curation by a

moderator, and their values are automatically suppressed from contributing to downstream

applications (including the `PeskAAS` dashboard in figure 1) until records are amended in the KoBo

toolbox dashboard. This is achieved via prompt follow-up clarification with field-based observers, to

ascertain whether data entry errors were made during form submission or whether the record in

question is a genuine outlier.

To automatically run the peskaPARSE.R script on a daily basis, we deployed a free Ubuntu 18.04

minimal virtual machine (VM) instance on the Google Cloud Platform, transferred the script to a

convenient user directory (specified by the [address] argument below), and scheduled a 24-hourly

cron job by appending the following line to the /etc/crontab file:

`0 0 * * * root Rscript -e  'source("[address]")'`

where `[address]` is replaced by the web location of the R script. In our case we stored the script in

a publicly available Dropbox directory and modified the public link to terminate with `download=1`

to enable direct sourcing (see https://github.com/shaunpwilkinson/PeskAAS for further details).

For the script to successfully import the raw trip- and landing records from the KoBo and Pelagic Data

Systems APIs, and deposit the filtered records in the peskaDAT MySQL database, three authorization

files must be stored in the same directory as the peskaPARSE.R file: a single-line text file named KoBo-

auth.txt containing the KoBo toolbox username and password, delimited by a colon operator, and

similarly-formatted files containing log-on credentials for the Pelagic Data Systems dashboard (PDS-

auth.txt) and the peskaDAT MySQL database (peskaDB-auth.txt; user with SELECT privileges). The

regular cleaning and filtering of new landings records ensures that the data available for analysis and

visualization are timely and trustworthy.

<u>Geospatial vessel tracking</u>

To visualise geospatial fishing effort and extrapolate fishing effort from individual trips to community,

municipal and national levels, we installed tamperproof solar-powered GPS units (PDS v1.25c)

developed by Pelagic Data Systems Inc. (San Francisco, CA) on to 5-15 boats per landing site (N = 437).

Tracking was voluntary and fishers bore no costs. Trackers record point location data automatically

every 5 seconds and communicate those data when in range of a cellular network (Figure 4). Vessel

tracks were also linked to the trip's catch data, where available, using the unique GPS unit ID, allowing

us to train a model to predict unknown variables for trips with GPS data only, such as gear and habitat

type.

Figure 4. The relative effort heat map of small-scale fishing vessel tracks between August 2018 and

February 2020 in Timor-Leste from the `PeskAAS` dashboard. Red shading represents areas of

highest effort (near to homeports and shore), and orange to yellow shading shows areas fished with

decreasing effort further from shore. Basemap obtained from Esri ArcGIS via leaflet [23]. Sources:

Esri, DigitalGlobe, GeoEye, i-cubed, USDA FSA, USGS, AEX, Getmapping, Aerogrid, IGN, IGP, swisstopo,

and the GIS User Community.

<u>Fisheries analytics</u>

To quantify how catch volume varied over time and space, the catch-per-unit-effort (CPUE) is used as

a metric for relative fish abundance, and to track the response of fish stocks to fishing pressure [24].

For CPUE, a standard unit of *effort* is required. For `PeskAAS`, we use raw CPUE, with effort

standardized into the unit of *fisher-hours* on each fishing trip, calculated as the trip duration in hours

multiplied by the number of people who were actively fishing on that boat during that trip[1].

To generate accurate regional and national catch and CPUE estimates, it is necessary to estimate the

frequency and duration of fishing trips for each boat type, known as a vessel activity coefficient (VAC).

To generate an accurate VAC accounting for differences in boat type, vessel tracks were used to

generate monthly VAC values according to motorized and non-motorized vessels, and were used to

calculate the first national scale estimates of fish production based on SSF landings in Timor-Leste

(equation 1).

The national monthly catch (in tons; C) is estimated as:

212
$$C = \sum_b \quad CPUE_b \times EPT_b \times VAC_b \times N_b \times 0.001 \qquad \text{(Equation 1)}$$

where b refers to the boat type (canoe or motor-powered; shore based fishing accounted for < 2% of

reported landings and was hence omitted from the analysis); $CPUE$ is the monthly catch per unit

effort (averaged across all sites, in kg per fisher-hour); EPT is the median effort per trip (fisher-hours);

VAC is the vessel activity coefficient (average number of trips per month); and N_b is the total number

of boats of type b in the national fleet (national fisher and boat census data obtained from the Timor-

Leste Ministry of Agriculture and Fisheries).

<u>Supervised prediction of missing trip attributes</u>

---

[1] The complexity of more robust CPUE standardization (see [24]) of multiple gear types in tropical, multi-habitat, mixed species fisheries makes it impractical in a livelihoods context, so fisher hours is used as a unit applicable across all fisheries and scales.

The integration of shore-based observer data with high-resolution geo-located vessel fishing tracks

from on-board GPS units from *Pelagic Data Systems* Inc. allowed us to validate a supervised

classification approach for predicting gear and habitat types in the case where only GPS data are

available (i.e. trips that are tracked but catch is not recorded by enumerators). For each tracked but

unobserved trip, a donor trip is selected from the subset of trips for which both GPS and observer data

are available, based on spatial nearest-neighbour analysis [25]. To achieve this, ten GPS vectors from

each trip spaced at even time intervals are used to generate training- and query-data matrices for

input into the `nn2` function in the `RANN` R package [26]. Donor trips are assigned based on minimum

Euclidean distance and are only assigned if the distance is < 0.20. To validate this approach, we

randomly allocated the linked trip set available as at 31 July to 80% training data and 20% query data,

and tested the success rate in terms of number of gear and habitat types correctly predicted in the

query set over 100 iterations. The nearest-neighbour classification approach correctly predicted 83.4%

(SD = 0.023%) of gear types and 91.9% (SD = 0.021%) of habitat types based on 741 training

observations and 183 query observations.

RESULTS & DISCUSSION

At the pilot's inception in 2016, the Timor-Leste government and fishers had very sparse quantitative

data with which to characterise fisheries or determine production trends over time. `PeskAAS` was

developed concurrently with the co-generation of a national database of SSF landings with the Timor-

Leste National Fisheries Directorate. As of 31 July 2020, 59,000 fishing trips have been geotracked,

representing 810,000 km travelled over 313,000 hours. Catch data was recorded for 29,251 trips,

resulting in 32,872 landings records representing a total catch weight of 298.5 tonnes. `PeskAAS` has

already been utilised to test the effectiveness of fish aggregating devices at the boosting catch rates

of nearshore artisanal fishers [27] and enabled the first calculation of national fisheries production for

the Timor-Leste SSF fleet [20]. The full adoption of `PeskAAS` as the official national fisheries

monitoring system of the Timorese government in 2019 suggests legitimacy and the potential for

sustainability on a national level.

`PeskAAS` was designed to be a free, online data exploration tool to enable rapid development of

simple, near-real time fisheries monitoring systems for accurate and timely fish production data to

use in adaptive, evidence-based management of fisheries resources. The tracking hardware and data

service from Pelagic Data Systems is an optional extra and represents additional costs to governments

that must be considered in terms of sustainability. All the analytics of `PeskAAS` relating to CPUE are

done without PDS data. We found effort estimations that fishers provided if asked were sufficiently

accurate, and a VAC can be calculated from this by averaging all trip durations recorded from certain

fishers. The specific values of the vessel tracking functionality were 1) an understanding of effort and

activity distribution and, 2) the ability to calibrate effort through dynamic VAC calculation over time,

and 3) in certain contexts (not tested here) may provide a safety at sea function.

If collected and managed in inclusive processes with fishers, fishing location data can be used by

fishers to better argue and prove tenure and/or use rights (i.e., in line with the FAO Voluntary

Guidelines on fisheries [28] and tenure [29]), for example in marine spatial planning processes that

can otherwise ignore complex socio-political inequalities [30]. This value was realised in the case of

the TS Taipei container ship grounding in Taiwan, where spatial and catch records from small-scale

fishers were utilised to leverage fair reparations to fishers from the shipping company [14]. To date

the spatial information obtained from combined vessel tracking with `PeskAAS` has not been used

for coastal zone management, but protecting the rights of Timorese fishers to marine areas is a key

commitment in the new draft National Fisheries Strategy (2018) that the `PeskAAS` data and team

helped to inform. In other contexts, there are concerns that such data might work against fisher

livelihoods, i.e. in nations and regions where exclusive no take zones and top down compliance are

preferred strategies [31,32]. The intended and unintended implications of data innovations should be

considered from the outset of any such pilot and subsequent scaling out phases.

The co-design of `PeskAAS` with fisheries managers was crucial in building a financially and

institutionally sustainable system. This same user-centred design process ensured that the `PeskAAS`

analytical workflow was not initially too complex, and only included statistics and insights that could

be readily interpreted by fisheries management users. Hence, in scaling this tool to other countries

and contexts, the need to build local legitimacy and a feeling of ownership amongst government

stakeholders will necessitate a process of co-design. The technical capacity in Timor-Leste for digital

systems is improving, but as in most low-income country governments, the long-term maintenance of

the system will still require external support. Ongoing work on `PeskAAS` will develop its modularity

and customisation through templates for catch forms, analytics package integrations (such as

TropFishR [8]) and dashboard tutorials to guide managers, to allow for more flexibility to other fish

production systems, countries and capacities.

`PeskAAS` was developed as an open source script to make it highly adaptable to different fisheries

contexts and strategic objectives. The catch form and scripted analytics require no specialised

equipment and the dashboard is displayed in a web browser. However, we acknowledge that the

scripted nature of `PeskAAS` limits its use to those with programming expertise, or implies a need to

hire help that may be uncommon or unavailable in low-income countries. Rather than be an off-the-

shelf solution, we envisage `PeskAAS` to be a software framework that external NGOs or multilateral

agencies can utilise to establish a highly contextualised, user-centred system for obtaining and using

data from small-scale fisheries to guide decision-making. Data generated by `PeskAAS` were used to

show how fishing technology could improve fisher incomes and fish availability in Timor-Leste [27],

which substantiates government investment in interventions that are more cognisant and sensitive to

SSF. Future work will focus on developing modules and templates that can be populated by local actors

in new fisheries contexts to reduce the coding workload and streamline implementation, but we

anticipate some level of technical assistance will continue to be required.

`PeskAAS` in Timor-Leste is open access and publicly available. In theory, anyone with access to a

computer, tablet or smartphone, and an internet connection, are able to see the data aggregated to

the municipal level. The reality is that in Timor-Leste, as in many low-income countries, there are still

substantial barriers (e.g., cost of technology, digital literacy, formal identification) to digital inclusion

(the access to and use of ICTs) that limit the extent to which fishers can access and benefit from such

data. Addressing these limitations represents challenges for future pilots where participatory action

research principles would be relevant [33] and where initiative objectives include empowering

individual fishers in management decision-making, or improving their livelihoods through fisher-level

business planning. This was beyond the scope of the pilot we describe here.

Further capacity building is also necessary to ensure `PeskAAS` outputs are being correctly

interpreted to inform policy and guide extension services delivered by government actors to and for

fishing communities in Timor-Leste. Better data systems can only drive informed decision-making if

the information is available and understandable. Currently, this PeskAAS is suited to boat-based

fisheries, compounding the unawareness and exclusion of foot fisheries often conducted by women

[34]. To get a full picture of SSF and enable local legitimacy and sustainability, Timor-Leste must build

on initial successes with co-management [35] as a platform on which to base a range of data collection

methods and strategies. This will ensure stakeholders are included in contributing local ecological

knowledge and forming shared understanding and strategies for stewardship of their aquatic

resources.

In conclusion, the pilot of `PeskAAS` enabled system refinements, illuminated limitations and

developed preliminary data for decision makers. The data have been taken into consideration in

national-level fisheries governance, through the new draft National Fisheries Strategy (2018) and

revised Fisheries Decree Law (2019). The application has potential for government and non-

government managers, researchers and students looking for a low cost solution to address SSF data

gaps.

Acknowledgements

We are very grateful to the Timorese fishers and community members who collaborated with us and

Timor-Leste's Ministry of Agriculture and Fisheries in this project. Particular thanks go to: Joctan Dos

Reis Lopes for leading the `PeskAAS` team on the ground; to the WorldFish Timor-Leste team

members Dave Mills, Mario Gomes, Mario Pereira and Agustinha Duarte for providing important local

insights throughout the co-design process; to Pedro Rodrigues, Lucas Soares and the Fisheries

Directorate staff for helping us to build from the ground up; and to Pip Cohen for insight and

comments on this manuscript.

Funding statement

This work was undertaken as part of the CGIAR Research Program on Fish Agri-Food Systems (FISH)

led by WorldFish, and the CGIAR Big Data Platform Inspire Challenge 2018 led by CIAT and IFPRI. These

programs are supported by contributors to the CGIAR Trust Fund. `PeskAAS` was established under

the Fisheries Sector Support Program funded by the Royal Norwegian Embassy in Jakarta. The funders

provided support in the form of salary for authors [A.T.] and field costs, but did not have any additional

role in the study design, data collection and analysis, decision to publish, or preparation of the

manuscript. Wilderlab is a recent, unassociated affiliation for S.P.W. and did not contribute funding

towards the study. The specific roles of these authors are articulated in the 'author contributions'

section.

Author contributions

A.T. conceived and designed the study. S.P.W. coded the various elements of the `PeskAAS`

application. A.T. and S.P.W. contributed equally to this manuscript.

Data Accessibility

The `PeskAAS` catch questionnaire, R script and data used to test the application in this study are

archived in Dataverse https://doi.org/10.7910/DVN/TVGIJJ [36]. The `PeskAAS` code and

documentation is also hosted at https://github.com/shaunpwilkinson/PeskAAS.

References

1. Kelleher K, Westlund L, Hoshino E, Mills D, Willmann R, de Graaf G, et al. Hidden harvest: The global contribution of capture fisheries. Worldbank ; WorldFish; 2012. Available: https://play.google.com/store/books/details?id=AQktDgAAQBAJ

2. Mills DJ, Westlund L, Graaf G de, Kura Y, Willman R, Kelleher K. Under-reported and undervalued: small-scale fisheries in the developing world. In: Pomeroy RS, Andrew NL, editors. Small-scale fisheries management: frameworks and approaches for the developing world. Wallingford: CABI; 2011. pp. 1–15. doi:10.1079/9781845936075.0001

3. FAO. The State of World Fisheries and Aquaculture 2018 - Meeting the sustainable development goals. Rome: The Food and Agriculture Organisation of the UN (FAO); 2018 p. 227. doi:978-92-5-130562-1

4. Hicks CC, Cohen PJ, Graham NAJ, Nash KL, Allison EH, D'Lima C, et al. Harnessing global fisheries to tackle micronutrient deficiencies. Nature. 2019;574: 95–98. doi:10.1038/s41586-019-1592-6

5. Kolding J, Béné C, Bavinck M. Small-scale fisheries: Importance, vulnerability and deficient knowledge. Governance of Marine Fisheries and Biodiversity Conservation: Interaction and Co-evolution. 2014; 317–331. doi:10.1002/9781118392607.ch22

6. Kolding J, Van Zwieten PAMM. The Tragedy of Our Legacy: How do Global Management Discourses Affect Small Scale Fisheries in the South? Forum Dev Stud. 2011;38: 267–297. doi:10.1080/08039410.2011.577798

7. Dowling NA, Wilson JR, Rudd MB, Babcock EA, Caillaux M, Cope J, et al. FishPath: a decision support system for assessing and managing data- and capacity-limited fisheries. In: Quinn TJ II, Armstrong JL, Baker MR, Heifetz J, Witherell D, editors. Assessing and Managing Data-Limited Fish Stocks. Alaska Sea Grant, University of Alaska Fairbanks; 2016. Available: http://doi.org/10.4027/amdlfs.2016.03

8. Mildenberger TK, Taylor MH, Wolff M. TropFishR : an R package for fisheries analysis with length-frequency data. Price S, editor. Methods Ecol Evol. 2017;8: 1520–1527. doi:10.1111/2041-210X.12791

9. Gutiérrez NL, Hilborn R, Defeo O. Leadership, social capital and incentives promote successful fisheries. Nature. 2011;470: 386–389. doi:10.1038/nature09689

10. FAO, ITU. E-Agriculture in Action. FAO and ITU; 2017.

11. FAO. Information and communication technologies benefit fishing communities. Policies to support improved communications for development. New Directions in Fisheries. A Series of Policy Briefs on Development Issues. Rome: FAO; 2007. Report No.: 7. Available: http://www.fao.org/3/a-a0991e.pdf

12. Jeffers VF, Humber F, Nohasiarivelo T, Botosoamananto R, Anderson LG. Trialling the use of
smartphones as a tool to address gaps in small-scale fisheries catch data in southwest
Madagascar. Mar Policy. 2019;99: 267–274. doi:10.1016/j.marpol.2018.10.040

13. Petrik M, Raemaekers DRS. The case for supporting small-scale fisheries governance through
ICT. SAIIA; 2018. Report No.: 177. Available: https://www.africaportal.org/publications/case-
supporting-small-scale-fisheries-governance-through-ict/

14. Tilley A, Roscher MB, editors. ICT4SSF: The role of information and communication technologies
in achieving the objectives of the Small-Scale Fisheries Guidelines. FAO & WorldFish; 9/2020.

15. James M, Mendo T, Jones EL, Orr K, McKnight A, Thompson J. AIS data to inform small scale
fisheries management and marine spatial planning. Mar Policy. 2018;91: 113–121.
doi:10.1016/j.marpol.2018.02.012

16. Mallalieu KI, Rocke S. Selecting Sustainable ICT Solutions for Pro-Poor Intervention. Digital
Poverty. Practical Action Publishing; 2007. pp. 119–140. doi:10.3362/9781780441115.006

17. Donnelly M. Implementing ICTs in Indonesia's Small-Scale Fisheries: Identifying Common
Implementation Challenges and the Development Paradigms that Shape Them. Masters
Communication for Development, Malmö universitet. 2018. Available:
http://muep.mau.se/handle/2043/24803

18. R Special Interest Group on Databases (R-SIG-DB), Wickham H, Müller K. DBI: R Database
Interface. 2018. Available: https://CRAN.R-project.org/package=DBI

19. Ooms J, James D, DebRoy S, Wickham H, Horner J. RMySQL: Database Interface and "MySQL"
Driver for R. 2019. Available: https://CRAN.R-project.org/package=RMySQL

20. López-Angarita J, Hunnam KJ, Pereira M, Mills DJ, Pant J, Teoh SJ, et al. Fisheries and
aquaculture of Timor-Leste in 2019: Current knowledge and opportunities. Penang, Malaysia:
WorldFish; 2019.

21. Food, Agriculture Organization of the United Nations (FAO-UN). FAO Fisheries & Aquaculture
ASFIS List of Species for Fishery Statistics Purposes, Overview. 2 Nov 2006 [cited 27 Aug 2020].
Available: http://www.fao.org/fishery/collection/asfis/en

22. Boettiger C, Lang DT, Wainwright PC. rfishbase: exploring, manipulating and visualizing FishBase
data from R. J Fish Biol. 2012;81: 2030–2039. doi:10.1111/j.1095-8649.2012.03464.x

23. Cheng J, Karambelkar B, Xie Y. Leaflet: Create interactive web maps with the javascript 'leaflet'
library. 2019. Available: https://CRAN.R-project.org/package=leaflet

24. Maunder MN, Punt AE. Standardizing catch and effort data: a review of recent approaches. Fish
Res. 2004;70: 141–159. doi:10.1016/j.fishres.2004.08.002

25. Cover T, Hart P. Nearest neighbor pattern classification. IEEE Trans Inf Theory. 1967;13: 21–27.
doi:10.1109/TIT.1967.1053964

26. Arya S, Mount D, Kemp SE, Jefferis G. RANN: Fast Nearest Neighbour Search (Wraps ANN
Library) Using L2 Metric. 2019. Available: https://CRAN.R-project.org/package=RANN

27. Tilley A, Wilkinson SP, Kolding J, López-Angarita J, Pereira M, Mills DJ. Nearshore Fish
Aggregating Devices Show Positive Outcomes for Sustainable Fisheries Development in Timor-

Leste. Frontiers in Marine Science. 2019;6: 487. doi:10.3389/fmars.2019.00487

28. Food and Agriculture Organization of the United Nations. Voluntary Guidelines for Securing
Sustainable Small-Scale Fisheries in the Context of Food Security and Poverty Eradication. Food
& Agriculture Org.; 2018. Available:
https://play.google.com/store/books/details?id=zGl6DwAAQBAJ

29. FOOD AND AGRICULTURE ORGANIZATION OF THE UNITED NATIONS. Voluntary guidelines on
the responsible governance of tenure of land fisheries and forests in the context of national
food security. FAO; 2014. Available: http://www.fao.org/3/i2801e/i2801e.pdf

30. Flannery W, Healy N, Luna M. Exclusion and non-participation in Marine Spatial Planning. Mar
Policy. 2018;88: 32–40. doi:10.1016/j.marpol.2017.11.001

31. Garcia SM, Boncoeur J, Gascuel D. Les aires marines protégées et la pêche Bioécologie,
socioéconomie et gouvernance. hal.archives-ouvertes.fr; 2013. Available: https://hal.archives-
ouvertes.fr/hal-01904070/

32. Stacey N, Acciaioli G, Clifton J, Steenbergen DJ. Impacts of marine protected areas on
livelihoods and food security of the Bajau as an indigenous migratory people in maritime
Southeast Asia. Marine protected areas: Interactions with fishery livelihoods and food security.
2017; 113–126. Available:
https://books.google.co.uk/books?hl=en&lr=&id=ckV3DwAAQBAJ&oi=fnd&pg=PA113&dq=Imp
acts+of+marine+protected+areas+on+livelihoods+and+food+security+of+the+Bajau+as+an+indi
genous+migratory+people+in+maritime+Southeast+Asia&ots=3wXpvo9cMm&sig=bHIyW7VC4S
L9sGkAZmKRI8lYAjI

33. Apgar JM, Cohen PJ, Ratner BD, de Silva S, Buisson M-C, Longley C, et al. Identifying
opportunities to improve governance of aquatic agricultural systems through participatory
action research. Ecol Soc. 2017;22. Available: http://www.jstor.org/stable/26270053

34. Tilley A, Burgos A, Duarte A, Dos Reis Lopes J, Eriksson H, Mills D. Contribution of women's
fisheries substantial, but overlooked, in Timor-Leste. Ambio. 2020. doi:10.1007/s13280-020-
01335-7

35. Tilley A, Hunnam K, Mills D, Steenbergen D, Govan H, Alonso-Poblacion E, et al. Evaluating the
fit of co-management for small-scale fisheries governance in Timor-Leste. Frontiers in Marine
Science. 2019;6: 392. doi:10.3389/fmars.2019.00392

36. Tilley A. PeskAAS - National Fisheries Monitoring System of Timor-Leste. Harvard Dataverse;
2016. doi:10.7910/DVN/TVGIJJ

Supplementary information 1. List of species, species groups and family categories used for recording

catch along with a and b parameters used to calculate weight from length measurements.

Supplementary Information 2. MySQL relational database schema with cascading foreign keys

shown by dashed arrows. Figure generated in MySQL Workbench (Oracle Corp.).

Supplementary information 3. PeskaPARSE.R' script file. The PeskaPARS.R script scheduled on a
daily cron job, run on a Google Cloud Platform virtual machine.