The neural basis of intelligence in fine-grained cortical topographies

Ma Feilong[1], J. Swaroop Guntupalli[2], James V. Haxby[1]*

[1]Center for Cognitive Neuroscience, Dartmouth, Hanover NH

[2]Vicarious AI, Union City CA

*Address correspondence to JVH (james.v.haxby@dartmouth.edu)

Summary

Intelligent thought is the product of efficient neural information processing. Previous work on the neural basis of intelligence has focused on coarse-grained features of brain anatomy and function, even though information is encoded in fine-grained, topographically-organized population responses. We hypothesized that individual differences in fine-grained cortical architecture would provide stronger predictions of general intelligence. Using hyperalignment, we were able to model these fine-grained architectural differences by resolving idiosyncratic interindividual variation of fine-grained topographies of functional connectivity. We found that predictions of general intelligence based on fine-grained patterns of connectivity were markedly stronger than predictions based on coarse-grained patterns, especially in the cortical systems associated with self-generated thought. Previous work overlooked fine-grained architecture because existing methods couldn't resolve idiosyncratic topographies, preventing investigation where the keys to the neural basis of intelligence are more likely to be found.

Key words

Introduction

Intelligent thought is a product of brain activity, but the neural architecture that

makes some brains capable of quick wit and deep insight, while others struggle with

simple problems, remains an open question. Previous investigations of the neural basis

of general intelligence have focused on large-scale features, such as the size and shape

of the brain and its parts (e.g., Cox et al., 2019; Schmitt et al., 2019; Kong et al., 2019)

or the size and strength of connections between large cortical fields (e.g., Dubois et al.,

2018; Finn et al., 2015; Luders et al., 2007). Intelligence, however, involves effective

manipulation of information, which is encoded in *fine-grained* cortical topographies

(Haxby et al., 2001, 2014). Different brains encode the same information in

idiosyncratic topographic patterns (Guntupalli et al., 2016, 2018; Haxby et al., 2011).

Prior to the development of hyperalignment—a computational framework that models

how shared information is encoded in idiosyncratic, fine-grained topographies (Feilong

et al., 2018; Guntupalli et al., 2016, 2018; Haxby et al., 2011, 2020)—no principled

method allowed investigation of how the information embedded in these topographies

differs across individuals. Consequently, brain differences at this scale of organization

have not been examined.

Here we apply connectivity hyperalignment (Guntupalli et al., 2018) to investigate

whether fine-scale patterns of connectivity better predict general intelligence than do

coarse-scale patterns. Connectivity hyperalignment remixes the connectivity profiles of

loci in a cortical field to maximize the similarity across brains in fine-grained, vertex-by-

vertex patterns. Individual variations around common fine-grained patterns are more

reliable than individual variations around common coarse-grained patterns (Feilong et

al., 2018). Here we show that these variations in fine-scale patterns are markedly better

predictors of general intelligence, and the most predictive regions are largely in the

default mode and frontoparietal systems. Our results indicate that information

embedded in fine-grained topographies in the cortical systems for self-generated

cognition plays a central role in the neural basis of intelligent thought.

Results

We used data from 876 participants of the Human Connectome Project (HCP;

Van Essen et al., 2013). Each participant had about 47 minutes of task fMRI data,

collected during the performance of seven tasks, one hour of resting-state fMRI data,

and scores on 10 cognitive tests. We used connectivity hyperalignment (Guntupalli et

al., 2018) to factor out idiosyncrasies in fine-grained topographies and model

information encoded in local functional connectivity patterns that is shared across

brains. We hyperaligned both the HCP task fMRI and resting fMRI datasets.

Connectivity hyperalignment projects idiosyncratic cortical topographies for individual

brains into a common model connectivity space in which the patterns of connectivity

across features in a cortical field with connectivity targets elsewhere in the brain are

maximally similar across brains. We measured general intelligence (Spearman, 1904) as

a general factor based on 10 cognitive test scores included in the HCP database

(Dubois et al., 2018).

For each of 360 cortical regions, from a parcellation tailored to the HCP dataset

(Glasser et al., 2016), we computed fine-grained task fMRI and resting fMRI

connectivity profiles for each individual (Figure 1). The connectivity profile for each

feature (cortical vertex) differs from profiles for other features in the region with a

granularity in the common model space that is equivalent to spatial variation across

cortical loci within individual brains (Guntupalli et al., 2018). We factored out the effect

of coarse-grained connectivity by subtracting the mean connectivities between pairs of

regions (coarse-grained connectivity profiles; Figure 1, middle row) from the vertex-

wise connectivities (full fine-grained connectivity profiles; Figure 1, top row), to

examine the predictive power of fine-grained connectivity unconfounded with

prediction based on coarse-grained connectivity. We calculated coarse-grained

connectivity on the same hyperaligned data used for calculation of fine-grained

connectivity (see Supplemental Figure S2).

Figure 1. Schematic illustration of coarse- and fine-grained functional connectivity. Each brain region (e.g. area 150 shown here) comprises multiple brain features (on average 165 cortical vertices). Correlations between their time series and time series for all 59,412 vertices in the whole cortex form that region's full fine-grained connectivity matrix (top row). The fine-grained connectivity profiles for 360 brain regions each have approximately 10 million such correlations. The coarse-grained connectivity profile for the same region (middle row) comprises the average functional connectivity between all of the vertices in that region and all of the vertices in each of the 360 brain regions. Thus, the coarse-grained connectivity

profiles for 360 brain regions each have 360 mean correlations. The residual fine-grained connectivity profile (bottom row) for each region is obtained by subtracting the mean correlation for a pair of regions (e.g. region 1 and region 150) from the full fine-grained connectivity profile for that pair, and is, thus, unconfounded with coarse-grained functional connectivities. We refer to these unconfounded profiles as fine-grained connectivity profiles for short.

We built prediction models based on regional connectivity profiles using cross-validated principal component regression with ridge regularization. We divided the data into test participants from one family (k = 1 to 6) and the remaining 876-k training set participants.   We assessed the performance of these models using a coefficient of determination (R^2), which denotes the percent of intelligence score variance accounted for (VAF) by the prediction models. We made separate prediction models for hyperaligned fine-scale task and resting connectivity, for coarse-grained task and resting connectivity, and for non-hyperaligned fine-scale task and resting connectivity.

Hyperaligned fine-grained versus coarse-grained connectivity profiles

Regional hyperaligned fine-grained connectivity profiles were highly predictive of general intelligence (Figures 2A and 3A). On average across regions, prediction models based on hyperaligned fine-grained task fMRI connectivity accounted for 27.3% of variance in general intelligence (min: 11.2%, max: 38.9%). By contrast,

prediction models based on coarse-grained task fMRI connectivity (Figure 2B)

accounted on average for only 14.5% of variance (min: 0.0%, max: 25.8%; 53.2% (95%

CI: [47.8%, 57.4%] of VAF by hyperaligned fine-grained connectivity overall). VAF by

hyperaligned fine-grained task connectivity was higher than VAF by coarse-grained

connectivity in all 360 ROIs (Figure 2C). These results suggest that the information

encoded in fine-grained interaction patterns between brain regions affords markedly

stronger predictors of intelligence than information in coarse-grained patterns.

The 30 most predictive regions (Figure 2D and 2E; 33.8% to 38.9% VAF) were in

bilateral inferior parietal cortex (15 regions), bilateral medial and superior prefrontal

cortex (11 regions), bilateral medial parietal (2 regions), and bilateral posterior lateral

temporal cortex (2 regions). The cortices in these regions were predominantly part of

the default mode and frontoparietal systems (38.9% and 34.5% of cortical vertices,

respectively) with small portions in the ventral and dorsal attention systems (11.3% and

10.6%, respectively; Figure 2D and 2E; Yeo et al., 2011).

Prediction based on task fMRI functional connectivity

Fig 2. Predicting general intelligence based on regional hyperaligned fine-grained

(A) and coarse-grained (B) task fMRI connectivity profiles, assessed by the variance

in general intelligence accounted for by prediction models. The scatter plot (C)

shows that predictions based on hyperaligned fine-grained profiles accounted for

more variance in all 360 ROIs. Prediction models based on each region's fine-

grained hyperaligned task functional connectivity profile accounted for 1.88 (95%

CI: [1.74, 2.09]) times more variance in general intelligence on average than did

models based on coarse-grained functional connectivity profiles. Each circle is a

cortical region, and the color of each circle corresponds to the cortical system

where it resides, using the same color scheme as in (E). Dashed lines denote

average difference in R^2 (gray), or identical R^2 (black). (D) The thirty regions whose

hyperaligned fine-grained connectivity best predicted general intelligence are

colored as in panels A and B. The default mode network (Yeo et al., 2011) is

outlined in red, and the frontoparietal network is outlined in orange. (E) Proportion

of vertices in these regions that are in seven cortical systems delineated with

resting state fMRI functional connectivity (Yeo et al., 2011).

Prediction of general intelligence based on resting fMRI connectivity showed a

similar advantage for hyperaligned fine-grained profiles, relative to coarse-grained

profiles (Figure 3), but performance was substantially lower than for task fMRI

connectivity, consistent with previous reports (Greene et al., 2018; Jiang et al., 2020).

Models based on hyperaligned fine-grained resting fMRI connectivity accounted on

average for 19.7% of variance (Figure 3A; min: 2.9%, max: 31.2%), whereas models

based on coarse-grained connectivity accounted on average for 7.7% of variance

(Figure 3B; min: -0.4%, max: 17.4%; 39.0% [CI: 32.4%, 43.9%] of VAF by hyperaligned

fine-grained connectivity). Hyperaligned fine-grained resting fMRI connectivity, as

compared to coarse-grained resting fMRI connectivity, accounted for more variance in

359 of 360 ROIs (Figure 3C). The vertices of 30 regions whose resting hyperaligned

fine-grained connectivity was most predictive of general intelligence (25.3% to 31.2%

VAF) had a distribution that was similar to that for hyperaligned task connectivity,

sharing 68.3% of cortical vertices (compare Figures 2D and 3D), with vertices mostly in

the default mode network (49.0%) and smaller parts in the frontoparietal (19.4%),

dorsal attention (15.8%) and ventral attention (10.0%) systems.

Prediction based on resting fMRI functional connectivity

Fig 3. Predicting general intelligence based on regional hyperaligned fine-grained

(A) and coarse-grained (B) resting fMRI connectivity profiles. The scatter plot (C)

shows that regional predictions based on hyperaligned fine-grained profiles

accounted for more variance in all 360 ROIs. Prediction models based on each

region's fine-grained hyperaligned resting functional connectivity profile accounted

for 2.57 (95% CI: [2.28, 3.08]) times more variance in general intelligence on

average than did models based on coarse-grained functional connectivity profiles.

Each circle is a cortical region, and the color of each circle corresponds to the

cortical system where it resides, using the same color scheme as in (E). Dashed

lines denote average difference in R^2 (gray), or identical R^2 (black). (D) The thirty

regions whose hyperaligned fine-grained connectivity best predicted general

intelligence are colored as in panels A and B. The default mode network (Yeo et

al., 2011) is outlined in red, and the frontoparietal network is outlined in orange.

(E) Proportion of vertices in these regions that are in seven cortical systems

delineated with resting state fMRI functional connectivity (Yeo et al., 2011).

Consistent with previous reports (Greene et al., 2018; Jiang et al., 2020),

hyperaligned task fMRI connectivity was significantly more predictive of general

intelligence than was resting fMRI connectivity for both hyperaligned fine-grained data

(difference = 7.7% VAF; 95% CI: 5.4% to 9.9%) and coarse-grained data (difference =

6.9% VAF; 95% CI: 5.1% to 8.6%). Task connectivity accounted for more variance than

did resting connectivity in 358 of 360 ROIs for hyperaligned fine-grained data and in

340 of 360 ROIs for coarse-grained data (Supplementary Figure S1).

Hyperaligned versus MSM-aligned fine-grained connectivity profiles

         To test the efficacy of hyperalignment for revealing predictive individual

differences in fine-grained connectivity topographies, we trained another set of models

based on fine-grained functional connectivity of data without hyperalignment. These

data were aligned with Multimodal Surface Matching (MSM; Robinson et al., 2014).

Models based on MSM-aligned fine-grained task connectivity and resting connectivity

accounted for, on average across ROIs, 17.5% (min: 4.8%; max: 28.7%) and 10.9% (min:

0.6%; max: 22.6%), respectively, of variance in general intelligence, which was 64.2%

(95% CI: [59.7%, 68.1%]) and 55.6% (95% CI: [49.1%, 61.2%]) of that accounted for by

models using hyperaligned data (Figure 4). Predictions based on hyperaligned fine-

grained task connectivity were better than predictions based on MSM-aligned fine-

grained connectivity in all 360 regions (Figure 4C). Predictions based on hyperaligned

fine-grained resting connectivity were better than predictions based on MSM-aligned

fine-grained connectivity in 357 of 360 regions (Figure 4D). The difference in model

performance was larger for brain regions with more functional topographic idiosyncrasy

for both task and resting connectivity (r = 0.460 and 0.395, respectively, $p < 10^{-14}$, with

two- to three-fold increases in VAF in the most idiosyncratic regions). As for

hyperaligned fine-scale connectivity and for coarse-scale connectivity, MSM-aligned

fine-scale task connectivity was more predictive of intelligence than was MSM-aligned

fine-scale resting connectivity (difference = 6.6% VAF; 95% CI: [5.1%, 8.1%];

Supplemental Figure S1C). Consistent with our previous findings (Feilong et al., 2018),

these results show that hyperalignment factors out idiosyncrasies in functional

topography to reveal how individuals differ in information encoded in fine-grained

cortical functional architecture.

Prediction based on MSM-aligned fine-grained connectivity

Figure 4. Predicting general intelligence based on MSM-aligned fine-grained task

fMRI (A) and resting fMRI (B) connectivity. Scatterplots compare regional

predictions based on MSM-aligned versus hyperaligned task connectivity (C) and

resting connectivity (D) data (comparison to results in Figures 2A and 3A).

Discussion

The results show that individual differences in fine-grained patterns of functional

connectivity are a markedly better predictor of general intelligence than are coarse-

grained patterns, indicating that differences in cortical architecture that underlie inter-

individual variation in the efficiency of information processing are more evident at the

same spatial scale as topographic patterns that encode information. Discovering the

dominant role of fine-grained connectivity patterns in the neural basis of intelligence

required a method that resolves individual differences in these idiosyncratic patterns, a

method that was not available prior to hyperalignment (Feilong et al., 2018; Guntupalli

et al., 2016, 2018; Haxby et al., 2011, 2020; Nastase et al., 2020).

Differences in intelligence are indexed by tests of the ability to understand and

manipulate information embedded in the meanings of words, logical relations, and

visual patterns. We predicted that differences in performance would be more related

to the fine-grained topographic patterns that represent these kinds of information than

to coarse-grained patterns that blur fine distinctions. The results confirm our

hypothesis. Hyperaligned, fine-grained, vertex-by-vertex connectivity patterns

accounted for 1.88 to 2.57 times more variance in general intelligence than did coarse-grained, region-to-region connectivity patterns.

To examine the predictive power of fine-grained connectivity unconfounded with coarse-grained connectivity, we built models using the residual fine-grained connectivity profiles. In separate analyses we built models on the full fine-grained patterns and found that adding coarse-grained information contributed little to VAF (Supplemental Figure S2), underscoring the stronger role that fine-grained cortical architecture plays in the neural basis of intelligence than that played by coarse-grained architecture.

Functional connectivity shows fine-grained variation vertex-by-vertex within a cortical field (Guntupalli et al., 2018) and even neuron-by-neuron within an fMRI voxel (Park et al., 2017). Transmission of information between cortical fields, therefore, involves more than simple synchronization of global activity. Information is transformed, as evidenced by changes in the representational geometries that are embedded in the fine-grained structure of local topographies (Connolly et al., 2016; Guntupalli et al., 2017; Kriegeskorte et al., 2008). Our results indicate that investigating the efficiency of information processing should focus on fine-grained patterns of connectivity that support these transformations.

Previous work could not reveal the role that information embedded in fine-scale topographies plays in the neural basis of intelligence because individual differences in

information were concealed by idiosyncrasies in fine-scale topographies that could not

be aligned with prior methods. Hyperalignment resolves the shared information

embedded in idiosyncratic topographies, making it possible to investigate these

individual differences (Feilong et al., 2018). Fine-grained information in hyperaligned

data accounted for 1.56 to 1.80 times more individual variation in intelligence than did

fine-grained information in non-hyperaligned data.

Results also show that fMRI data collected during performance of cognitive tasks

better predict intelligence than resting state fMRI data, consistent with previous reports

(Greene et al., 2018; Jiang et al., 2020). Previous studies used whole-brain, coarse-

grained connectivity for prediction. Here we show that the added predictive power of

task fMRI data, relative to resting fMRI data, extends to both hyperaligned and MSM-

aligned fine-grained connectivity patterns.

Our results show further that the neural basis of intelligence resides mostly in the

fine-grained structure of connectivity in the default mode and frontoparietal networks.

Small parts of the most predictive regions were in the dorsal and ventral attention

networks, and an even smaller proportion was in the visual system. The most

predictive brain regions did not encroach on the systems for auditory, somatosensory,

motor, or limbic function. The predominance of the default mode network was found

for both task connectivity and resting connectivity, suggesting that the efficiency of

these connections is evident in both. A strong role for the frontoparietal network was

more evident in task connectivity, suggesting that efficiency of this system's

connections is better revealed during performance of tasks that increase its activity.

The predominant role of the default and frontoparietal systems in our results

suggests that intelligence rests on self-generated and stimulus-independent thinking

(Andrews-Hanna et al., 2014; Buckner et al., 2008; Dixon et al., 2018) for finding correct

solutions to problems and generating novel insights. The functions of the default

system are mostly ill-defined because it does not respond to features of external stimuli

in a consistent way (Andrews-Hanna et al., 2014; Buckner et al., 2008; Golland et al.,

2007). Although default system activity during movie watching and in the resting state

is idiosyncratic, it is highly correlated across default areas (Buckner et al., 2008; Golland

et al., 2007) and has a fine-scale structure that can be modeled with hyperalignment

(Feilong et al., 2018; Guntupalli et al., 2018), indicating that this activity has structure

and meaning. It has been associated with thinking about others' mental states

(Buckner et al., 2008; Frith and Frith, 1999; Gobbini et al., 2007; Saxe and Kanwisher,

2003), activation of person knowledge about familiar others (Gobbini and Haxby,

2007), autobiographical memory and envisioning the future (Addis et al., 2007; Buckner

et al., 2008), as well as other aspects of internally-driven cognition. The most

predictive regions overlapped only a portion of the default network involving primarily

the dorsal medial subsystem with smaller parts in the core subsystem (Andrews-Hanna

et al., 2010, 2014). The dorsal medial subsystem has been associated with mentalizing,

social cognition, story comprehension, and semantic conceptual processing (Andrews-

Hanna et al., 2014).

The frontoparietal system may similarly reflect the role of self-directed thought

in the neural basis of general intelligence. Dixon et al. (2018) have identified a

subdivision of the frontoparietal network that interacts primarily with the default mode

system. They propose that this part of the frontoparietal system is involved in the

regulation of introspective processes.

The efficiency of the default system apparently rests more on fine-grained

features of its functional connectivity than on coarse-grained functional connectivity.

The bases for the organization of its fine-grained topographies and the transformations

of representational geometries between default regions are unknown, but the keys to

understanding the neural basis of intelligent thought may reside in the information

processing embedded in these topographies.

Acknowledgements

We would like to thank Guo Jiahui and Maria Ida Gobbini for helpful comments,

suggestions, and discussion. We would like to thank Yaroslav Halchenko for support

with software.

This work was supported with funds from NSF grants 1607845 and 1835200.

Author contributions

Conceptualization, M.F., J.V.H; Methodology, M.F., J.S.G., J.V.H.; Software, M.F.,

J.S.G.; Formal analysis, M.F.; Resources, J.V.H; Writing - original draft, M.F., J.V.H.;

Writing - review and editing, M.F., J.S.G., J.V.H.; Visualization, M.F., J.V.H.; Supervision

and Funding acquisition, J.V.H.

Declarations of interests

The authors declare no competing interests.

References

Addis, D.R., Wong, A.T., and Schacter, D.L. (2007). Remembering the past and

imagining the future: common and distinct neural substrates during event

construction and elaboration. Neuropsychologia *45*, 1363–1377.

Andrews-Hanna, J.R., Reidler, J.S., Sepulcre, J., Poulin, R., and Buckner, R.L. (2010).

Functional-anatomic fractionation of the brain's default network. Neuron *65*, 550–

562.

Andrews-Hanna, J.R., Smallwood, J., and Spreng, R.N. (2014). The default network and

self-generated thought: component processes, dynamic control, and clinical

relevance. Ann. N. Y. Acad. Sci. *1316*, 29–52.

Buckner, R.L., Andrews-Hanna, J.R., and Schacter, D.L. (2008). The brain's default

network: anatomy, function, and relevance to disease. Ann. N. Y. Acad. Sci. *1124*,

1–38.

Connolly, A.C., Sha, L., Guntupalli, J.S., Oosterhof, N., Halchenko, Y.O., Nastase, S.A.,

Castello, M.V. di O., Abdi, H., Jobst, B.C., Gobbini, M.I., et al. (2016). How the

Human Brain Represents Perceived Dangerousness or "Predacity" of Animals. J.

Neurosci. *36*, 5373–5384.

Cox, S.R., Ritchie, S.J., Fawns-Ritchie, C., Tucker-Drob, E.M., and Deary, I.J. (2019).

Structural brain imaging correlates of general intelligence in UK Biobank.

Intelligence *76*, 101376.

Dixon, M.L., Vega, A.D.L., Mills, C., Andrews-Hanna, J., Spreng, R.N., Cole, M.W., and

Christoff, K. (2018). Heterogeneity within the frontoparietal control network and its

relationship to the default and dorsal attention networks. PNAS *115*, E1598–

E1607.

Dubois, J., Galdi, P., Paul, L.K., and Adolphs, R. (2018). A distributed brain network

predicts general intelligence from resting-state human neuroimaging data.

Philosophical Transactions of the Royal Society B: Biological Sciences *373*,

20170284.

Feilong, M., Nastase, S.A., Guntupalli, J.S., and Haxby, J.V. (2018). Reliable individual

differences in fine-grained cortical functional architecture. Neuroimage *183*, 375–

386.

Finn, E.S., Shen, X., Scheinost, D., Rosenberg, M.D., Huang, J., Chun, M.M.,

Papademetris, X., and Constable, R.T. (2015). Functional connectome

fingerprinting: identifying individuals using patterns of brain connectivity. Nat.

Neurosci. *18*, 1664–1671.

Frith, C.D., and Frith, U. (1999). Interacting minds--a biological basis. Science *286*,

1692–1695.

Glasser, M.F., Coalson, T.S., Robinson, E.C., Hacker, C.D., Harwell, J., Yacoub, E.,

Ugurbil, K., Andersson, J., Beckmann, C.F., Jenkinson, M., et al. (2016). A multi-

modal parcellation of human cerebral cortex. Nature *536*, 171–178.

Gobbini, M.I., and Haxby, J.V. (2007). Neural systems for recognition of familiar faces.

Neuropsychologia *45*, 32–41.

Gobbini, M.I., Koralek, A.C., Bryan, R.E., Montgomery, K.J., and Haxby, J.V. (2007).

Two takes on the social brain: a comparison of theory of mind tasks. J Cogn

Neurosci *19*, 1803–1814.

Golland, Y., Bentin, S., Gelbard, H., Benjamini, Y., Heller, R., Nir, Y., Hasson, U., and

Malach, R. (2007). Extrinsic and intrinsic systems in the posterior cortex of the

human brain revealed during natural sensory stimulation. Cereb. Cortex *17*, 766–

777.

Guntupalli, J.S., Hanke, M., Halchenko, Y.O., Connolly, A.C., Ramadge, P.J., and

Haxby, J.V. (2016). A Model of Representational Spaces in Human Cortex. Cereb.

Cortex *26*, 2919–2934.

Guntupalli, J.S., Wheeler, K.G., and Gobbini, M.I. (2017). Disentangling the

Representation of Identity from Head View Along the Human Face Processing

Pathway. Cereb. Cortex *27*, 46–53.

Guntupalli, J.S., Feilong, M., and Haxby, J.V. (2018). A computational model of shared

fine-scale structure in the human connectome. PLOS Computational Biology *14*,

e1006120.

Haxby, J.V., Gobbini, M.I., Furey, M.L., Ishai, A., Schouten, J.L., and Pietrini, P. (2001).

Distributed and overlapping representations of faces and objects in ventral

temporal cortex. Science *293*, 2425–2430.

Haxby, J.V., Guntupalli, J.S., Connolly, A.C., Halchenko, Y.O., Conroy, B.R., Gobbini,

M.I., Hanke, M., and Ramadge, P.J. (2011). A common, high-dimensional model

of the representational space in human ventral temporal cortex. Neuron *72*, 404–

416.

Haxby, J.V., Connolly, A.C., and Guntupalli, J.S. (2014). Decoding neural

representational spaces using multivariate pattern analysis. Annu. Rev. Neurosci.

37, 435–456.

Haxby, J.V., Guntupalli, J.S., Nastase, S.A., and Feilong, M. (2020). Hyperalignment:

Modeling shared information encoded in idiosyncratic cortical topographies.

ELife.

Kong, R., Li, J., Orban, C., Sabuncu, M.R., Liu, H., Schaefer, A., Sun, N., Zuo, X.-N.,

Holmes, A.J., Eickhoff, S.B., et al. (2019). Spatial Topography of Individual-Specific

Cortical Networks Predicts Human Cognition, Personality, and Emotion. Cereb.

Cortex *29*, 2533–2551.

Kriegeskorte, N., Mur, M., and Bandettini, P. (2008). Representational similarity analysis

- connecting the branches of systems neuroscience. Front Syst Neurosci *2*, 4.

Luders, E., Narr, K.L., Bilder, R.M., Thompson, P.M., Szeszko, P.R., Hamilton, L., and

Toga, A.W. (2007). Positive correlations between corpus callosum thickness and

intelligence. Neuroimage *37*, 1457–1464.

Nastase, S.A., Liu, Y.-F., Hillman, H., Norman, K.A., and Hasson, U. (2020). Leveraging

shared connectivity to aggregate heterogeneous datasets into a common

response space. Neuroimage 116865.

Park, S.H., Russ, B.E., McMahon, D.B.T., Koyano, K.W., Berman, R.A., and Leopold,

D.A. (2017). Functional Subpopulations of Neurons in a Macaque Face Patch

Revealed by Single-Unit fMRI Mapping. Neuron *95*, 971-981.e5.

Robinson, E.C., Jbabdi, S., Glasser, M.F., Andersson, J., Burgess, G.C., Harms, M.P.,

Smith, S.M., Van Essen, D.C., and Jenkinson, M. (2014). MSM: a new flexible

framework for Multimodal Surface Matching. Neuroimage *100*, 414–426.

Saxe, R., and Kanwisher, N. (2003). People thinking about thinking people. The role of

the temporo-parietal junction in "theory of mind." Neuroimage *19*, 1835–1842.

Schmitt, J.E., Neale, M.C., Clasen, L.S., Liu, S., Seidlitz, J., Pritikin, J.N., Chu, A.,

Wallace, G.L., Lee, N.R., Giedd, J.N., et al. (2019). A Comprehensive Quantitative

Genetic Analysis of Cerebral Surface Area in Youth. J. Neurosci. *39*, 3028–3040.

Spearman, C. (1904). "General Intelligence," Objectively Determined and Measured.

The American Journal of Psychology *15*, 201–292.

Van Essen, D.C., Smith, S.M., Barch, D.M., Behrens, T.E.J., Yacoub, E., Ugurbil, K., and

WU-Minn HCP Consortium (2013). The WU-Minn Human Connectome Project: an

overview. Neuroimage *80*, 62–79.

RESOURCE AVAILABILITY

Lead Contact

James V. Haxby (james.v.haxby@dartmouth.edu)

Data and Code Availability

The behavioral and fMRI data used are from the Human Connectome Project

(https://db.humanconnectome.org/data/projects/HCP_1200).

The analysis code will be released as part of the PyMVPA package

(http://www.pymvpa.org/) (Hanke et al., 2009).

METHOD DETAILS

Dataset

We used data from the Human Connectome Project (HCP) (Van Essen et al., 2013) for

our analysis. The final S1200 data release of the HCP Young Adult dataset contains

multi-modal MR imaging and behavioral data from 1206 participants that are 22-35

years old. This includes about one hour of resting-state fMRI data (4 runs, 14.5 minutes

each), 47 minutes of task fMRI data (7 tasks, 2 runs each), and extensive cognitive tests

for each participant. Out of the 1206 participants, 888 have complete task and resting

fMRI data, 1181 have complete scores of 10 cognitive tests, and 876 participants have

both. In our analysis, we always used as many participants with complete data as

possible to maximize statistical power. That is, we used data from the 1181

participants to derive general intelligence score, data from the 888 participants to

derive hyperalignment models and compute topographic idiosyncrasy, and data from

the overlapping 876 participants for prediction analysis.

Measuring General Intelligence

General intelligence is a common factor, often referred to as g, underlying all cognitive

abilities (Spearman, 1904), and it can be accurately and consistently identified through

different test batteries (Johnson et al., 2004, 2008). In this study, we measured general

intelligence as the general factor obtained based on 10 cognitive test scores using a

factor analysis with a bi-factor model (Dubois et al., 2018). These cognitive tests (Barch

et al., 2013) include those from the NIH Toolbox for Assessment of Neurological and

Behavioral Function (http://www.nihtoolbox.org) and additional computerized tests

(Bilker et al., 2012; Gur et al., 2010), covering a range of memory, attention, language,

and reasoning abilities.

MRI Acquisition

MRI data were acquired with a Siemens 3 T Skyra MRI scanner and a 32-channel head

coil. The scanner was customized with a gradient coil and gradient power. Each

subject has 2 T1w and 2 T2w scans with 0.7 mm isotropic voxels, which were used to reconstruct high-resolution cortical surfaces.

Functional MRI data were acquired with a TR of 0.72 s, 2 mm isotropic voxels, and a multi-band acceleration factor of 8. Every volume comprised 72 slices with 208 × 180 mm² FOV each. Half of the fMRI runs were scanned with the LR phase encoding direction, and the other half were with RL. Spin-echo field maps were collected along with the fMRI data that allow susceptibility distortion correction.

Resting fMRI data were acquired with 4 runs of 1200 TRs each. Each of the 7 tasks were acquired with 2 runs, and the duration of each run varied across tasks (min: 176 TRs, max: 405 TRs). In total, for each participant, 57.6 minutes of resting fMRI data and 46.6 minutes of task fMRI data were acquired. See (Uğurbil et al., 2013) for additional details of MRI acquisition.

MRI Preprocessing

We used the same standard procedure to preprocess fMRI data for all task and resting fMRI data. Our preprocessing was based on the minimally preprocessed version of the dataset (Glasser et al., 2013), where data had been corrected for distortion and head motion, and aligned to a standard cortical surface mesh using Multimodal Surface Matching (MSM) (Robinson et al., 2014), which aims to match multimodal properties

across individuals while preserving topology. These data were labeled as "MSMAll" in

the HCP data files, and we refer to them as "MSM" for short.

We first normalized all fMRI data to percent signal change units, then used linear

regression to remove nuisance components from them. These nuisance components

include 6 motion parameters and their derivatives, 5 principal components from white

matter and cerebrospinal fluid (Behzadi et al., 2007), global signal, and polynomial

trends up to the 3rd order. The whilte matter and cerebrospinal fluid components

were extracted from volumetric data based on eroded anatomical masks. Both the

regressors and data were low-pass filtered with a Gaussian kernel (standard deviation =

1 TR) prior to regression. These preprocessing steps were analogous to previous work

(Dubois et al., 2018; Finn et al., 2015; Greene et al., 2018).

Hyperalignment

We used connectivity hyperalignment (Guntupalli et al., 2018) to align fine-grained

cortical functional architecture across individuals. We used regional average time

series of the 360-region multi-modal cortical parcellation (Glasser et al., 2016) as

connectivity targets. For each of the 59,412 cortical vertices, we computed its

connectivity profile as the correlations between its own time series and the 360

regional average time series. Therefore, each connectivity profile is a vector

comprising 360 correlation coefficients. In each brain region, we derived a

transformation matrix for each individual using these connectivity profiles, which remixes each individual's vertices into a common set of model dimensions through an improper rotation of a high-dimensional space. Each model dimension has similar functional properties across individuals instead of the same anatomical position, and these model dimensions together constitute a common model space. The common model space is usually instantiated as a reference brain, where each vertex corresponds to a model dimension. The information content in each individual's data — the configuration of connectivity vectors in the high-dimensional feature space — is perfectly preserved during the rotation, whereas how and where this information is encoded in idiosyncratic topographies is factored out into the transformation matrix. We used the HCP task fMRI dataset to derive the hyperalignment common model and transformations (i.e., to train hyperalignment) when we analyzed the task fMRI data, and resting fMRI dataset when we analyzed the resting fMRI data. Therefore, the task and resting fMRI datasets remain independent throughout the analysis. It is possible to train hyperalignment using one dataset and apply it to another, and such results are summarized in Figure S2.

Functional Connectivity Profiles

We used functional connectivity profiles to depict a brain region's functional

interactions with the entire cerebral cortex. These connectivity profiles are different

from the connectivity profiles used in connectivity hyperalignment as described above.

For each of 360 cortical regions, we computed a fine-grained connectivity matrix for

each participant (Figure 1, top row), which comprises pairwise interactions between all

vertices in the region (165 vertices on average) and all vertices of the cerebral cortex

(59,412 vertices). We vectorized this connectivity matrix to form a long vector

comprising millions of connectivity strengths (9.8 million on average across all regions),

which we refer to as the participant's full fine-grained connectivity profile of the region.

This fine-grained connectivity profile depicts in detail the region's information

exchange with the rest of the cortex, and it contains information encoded in fine-

grained connectivity patterns up to the same resolution as the input fMRI data (2 mm

for this dataset).

To separate information encoded in different spatial scales, we split the full fine-

grained connectivity profile into a coarse-grained connectivity profile and a residual

fine-grained connectivity profile. The coarse-grained connectivity profile for a given

region is a vector comprising 360 elements, where each element is the average

connectivity strength between all cortical vertices in this region and all vertices in

another region (Figure 1, middle row). Similar to previous work (Dubois et al., 2018;

Finn et al., 2015; Shen et al., 2017), coarse-grained connectivity profiles depict the

information exchange between a pair of regions with a single connectivity strength. A

residual fine-grained connectivity profile comprises pattern residuals obtained by

subtracting the mean connectivity with each region (an element of the coarse-grained

connectivity profile) from each element of the vertex-by-vertex connectivity pattern

with the region (part of the full fine-grained connectivity profile). Similar to a full fine-

grained connectivity profile, a residual fine-grained connectivity profile comprises

millions of elements, and the only difference is that these elements are connectivity

residuals instead of connectivities. In other words, a residual fine-grained connectivity

profile contains only fine-scale information, instead of combined fine- and coarse-scale

information.

The analysis involves data aligned in 3 different ways: MSM, hyperalignment based on

task fMRI data, and hyperalignment based on resting fMRI data. For each alignment

method, we computed these 3 kinds of connectivity profiles for each participant and

each region. The results of fine-grained connectivity profiles reported in the main text

are based on residual fine-grained connectivity profiles, and similar results were

obtained using full fine-grained connectivity profiles (Figure S2).

Topographic Idiosyncrasy

We measured the idiosyncrasy of each region's functional topography as the average

dissimilarity of hyperalignment transformation matrices across participant pairs, after

correcting for region size. The dissimilarity between two matrices was quantified as the

Frobenius norm of their difference. Because the regions differ in size, and the average

matrix dissimilarity was predominantly determined by the square root of region size (r >

0.9999), we fit a linear regression model between them, and used the residual

dissimilarity as the heterogeneity of a region's functional topography across individuals.

We performed hyperalignment twice in our analysis — once using task fMRI data, once

using resting fMRI data — and therefore obtained two sets of transformation matrices

for each region. Topographic idiosyncrasy indices based on each of the two sets are

essentially identical (r = 0.960, p = 4×10^{-200}). When we analyzed task fMRI data, we

used topographic idiosyncrasy based on task fMRI (Figure 4C), and when we analyzed

resting fMRI data, we used that based on resting fMRI (Figure 4D).

Cross-Validation Scheme

We used leave-one-family-out cross-validation (Dubois et al., 2018) to assess prediction

models. The 876 participants were from 411 families, and each family had 2.13

members on average (range: 1–5; with 103 participants with no other family members

and 177, 107, 22, and 2 families with 2 to 5 participants, respectively). Therefore, this

cross-validation scheme divided the entire dataset into 411 folds. Each time we leave

out a family of k individuals (i.e., related to each other) as test data, and use the

remaining 876 - k individuals (i.e., not related to test participants) as training data to

train the model. We repeated this procedure, each time using a different family as test

data. Therefore, after looping through all families, each individual's general

intelligence score was predicted by a model trained with unrelated individuals.

For each cross-validation fold (i.e., each family as test data), we further split the training

data into three sub-folds and used nested cross-validation to choose the optimal

model parameters. In other words, model parameters were always chosen based only

on training data.

Regression Models

We used principal component regression with ridge regularization to predict general

intelligence based on functional connectivity. First, we used principal component

analysis (PCA) to derive a certain number of principal components (PCs) from functional

connectivity patterns based on training data. Dimensions in the PC space capture

principal ways that individuals' connectivity profiles differ. Thus, the fine-grained

functional connectivity for a region in each training set participant was transformed into

a set of scores across PC dimensions. Then, we trained a ridge regression model to

predict general intelligence based on these PC scores. The PCA and ridge regression

models were then applied to test data to obtain the model predicted general

intelligence scores. Model parameters (the number of PCs and the regularization

parameter) were always chosen using nested cross-validation as stated above.

QUANTIFICATION AND STATISTICAL ANALYSIS

Coefficient of Determination

We evaluated our models using the cross-validated coefficient of determination (R^2). R^2

denotes the percent of variance in general intelligence that was accounted for (VAF) by

prediction models. The formula is

$$R^2 = 1 - \frac{\sum_i (y_i - \hat{y}_i)^2}{\sum_i (y_i - \bar{y}_{i,train})^2}$$

where y_i is the measured score for subject i, $\hat{y}_i$ is the model predicted score for subject

i, and $\bar{y}_{i,train}$ is the prediction by the null model. The prediction of the null model is

simply the average score of all training data, and thus it doesn't use any information

from the features (fine- or coarse-grained functional connectivity in this case) at all. R^2

maximizes at 100%, which means perfect prediction; 0 means model performance is

only the same as the null model. In rare cases, cross-validated R^2 can also be negative,

which suggests the model performance is even worse than the null model.

Estimating Confidence Intervals

We used bootstrap tests to estimate confidence intervals (CIs) for contrasts between

VAF by different prediction models. In each of 1,000,000 repetitions, we randomly

sampled a group of 876 individuals used for model evaluation by sampling with

replacement from the 876 original individuals. In other words, in each bootstrapped

sample, a participant might be selected once, multiple times, or not selected at

all. For each bootstrapped sample, we computed VAF differences and VAF ratios. The

95% CI of a difference or ratio is estimated as the 2.5th and 97.5th percentiles of the

difference or ratio from the bootstrapped samples (i.e., the sampling distribution of the

difference or ratio estimated by bootstrapping participants).

Pearson Correlation

We used the Pearson correlation coefficient to assess the relationship between regional

topographic idiosyncrasy and the difference in prediction performance based on

hyperaligned and MSM-aligned data (Figure 4, panels C and D), and the relationship

between the square root of a region's size and the average transformation matrix

dissimilarity. In both cases, n (the number of regions) is always 360, and the degrees of

freedom is always 358.

Dice Coefficient

We used the Dice similarity coefficient (Dice, 1945) to quantify the amount of overlap between the 30 most predictive regions based on task fMRI data and those based on resting fMRI data. The formula is

$$DSC = \frac{2|A \cap B|}{|A| + |B|},$$

where A is the set of vertices covered by the 30 most predictive regions based on task fMRI data, and B is that based on resting fMRI data. |·| denotes set cardinality. DSC is short for Dice similarity coefficient.

Overlap with Cortical Systems

The cerebral cortex can be divided into 7 cortical systems based on functional connectivity (Yeo et al., 2011). For each of the 360 regions, we computed the percentage of vertices belonging to each of the 7 systems as the number of vertices belonging to the system divided by the total number of vertices in the region. For the 30 most predictive regions, we computed the percentage of vertices across all 30 regions that belonged to each system (Figures 2E and 3E). In the scatter plots (Figures 2C and 3C), each region was assigned to one of the cortical systems, which is the system that had the largest amount of vertices in the region.

Software Used

We implemented our analysis using Python and Python packages including NumPy

(https://numpy.org/), SciPy (https://www.scipy.org/), and NiBabel

(https://nipy.org/nibabel/). The code for performing hyperalignment and nuisance

regression was adapted from PyMVPA (http://www.pymvpa.org/) (Hanke et al., 2009).

References

Barch, D. M., Burgess, G. C., Harms, M. P., Petersen, S. E., Schlaggar, B. L., Corbetta,

M., Glasser, M. F., Curtiss, S., Dixit, S., Feldt, C., Nolan, D., Bryant, E., Hartley,

T., Footer, O., Bjork, J. M., Poldrack, R., Smith, S., Johansen-Berg, H., Snyder, A.

Z., & Van Essen, D. C. (2013). Function in the human connectome: Task-fMRI

and individual differences in behavior. NeuroImage, 80, 169–189.

https://doi.org/10.1016/j.neuroimage.2013.05.033

Behzadi, Y., Restom, K., Liau, J., & Liu, T. T. (2007). A component based noise

correction method (CompCor) for BOLD and perfusion based fMRI.

NeuroImage, 37(1), 90–101. https://doi.org/10.1016/j.neuroimage.2007.04.042

Bilker, W. B., Hansen, J. A., Brensinger, C. M., Richard, J., Gur, R. E., & Gur, R. C.

(2012). Development of Abbreviated Nine-Item Forms of the Raven's Standard

Progressive Matrices Test. Assessment, 19(3), 354–369.

https://doi.org/10.1177/1073191112446655

Dice, L. R. (1945). Measures of the Amount of Ecologic Association Between Species.

Ecology, 26(3), 297–302. https://doi.org/10.2307/1932409

Dubois, J., Galdi, P., Paul, L. K., & Adolphs, R. (2018). A distributed brain network

predicts general intelligence from resting-state human neuroimaging data.

Philosophical Transactions of the Royal Society B: Biological Sciences,

373(1756), 20170284. https://doi.org/10.1098/rstb.2017.0284

Finn, E. S., Shen, X., Scheinost, D., Rosenberg, M. D., Huang, J., Chun, M. M.,

Papademetris, X., & Constable, R. T. (2015). Functional connectome

fingerprinting: Identifying individuals using patterns of brain connectivity. Nature

Neuroscience, 18(11), 1664–1671. https://doi.org/10.1038/nn.4135

Glasser, M. F., Coalson, T. S., Robinson, E. C., Hacker, C. D., Harwell, J., Yacoub, E.,

Ugurbil, K., Andersson, J., Beckmann, C. F., Jenkinson, M., Smith, S. M., & Van

Essen, D. C. (2016). A multi-modal parcellation of human cerebral cortex.

Nature, 536(7615), 171–178. https://doi.org/10.1038/nature18933

Glasser, M. F., Sotiropoulos, S. N., Wilson, J. A., Coalson, T. S., Fischl, B., Andersson,

J. L., Xu, J., Jbabdi, S., Webster, M., Polimeni, J. R., Van Essen, D. C., &

Jenkinson, M. (2013). The minimal preprocessing pipelines for the Human

Connectome Project. NeuroImage, 80, 105–124.

https://doi.org/10.1016/j.neuroimage.2013.04.127

Greene, A. S., Gao, S., Scheinost, D., & Constable, R. T. (2018). Task-induced brain

state manipulation improves prediction of individual traits. Nature

Communications, 9(1), 1–13. https://doi.org/10.1038/s41467-018-04920-3

Guntupalli, J. S., Feilong, M., & Haxby, J. V. (2018). A computational model of shared

fine-scale structure in the human connectome. PLOS Computational Biology,

14(4), e1006120. https://doi.org/10.1371/journal.pcbi.1006120

Gur, R. C., Richard, J., Hughett, P., Calkins, M. E., Macy, L., Bilker, W. B., Brensinger,

C., & Gur, R. E. (2010). A cognitive neuroscience-based computerized battery for efficient measurement of individual differences: Standardization and initial construct validation. Journal of Neuroscience Methods, 187(2), 254–262. https://doi.org/10.1016/j.jneumeth.2009.11.017

Hanke, M., Halchenko, Y. O., Sederberg, P. B., Hanson, S. J., Haxby, J. V., & Pollmann, S. (2009). PyMVPA: A Python Toolbox for Multivariate Pattern Analysis of fMRI Data. Neuroinformatics, 7(1), 37–53. https://doi.org/10.1007/s12021-008-9041-y

Johnson, W., Bouchard, T. J., Krueger, R. F., McGue, M., & Gottesman, I. I. (2004). Just one g: Consistent results from three test batteries. Intelligence, 32(1), 95–107. https://doi.org/10.1016/S0160-2896(03)00062-X

Johnson, W., Nijenhuis, J. te, & Bouchard, T. J. (2008). Still just 1 g: Consistent results from five test batteries. Intelligence, 36(1), 81–95. https://doi.org/10.1016/j.intell.2007.06.001

Robinson, E. C., Jbabdi, S., Glasser, M. F., Andersson, J., Burgess, G. C., Harms, M. P., Smith, S. M., Van Essen, D. C., & Jenkinson, M. (2014). MSM: A new flexible framework for Multimodal Surface Matching. NeuroImage, 100, 414–426. https://doi.org/10.1016/j.neuroimage.2014.05.069

Shen, X., Finn, E. S., Scheinost, D., Rosenberg, M. D., Chun, M. M., Papademetris, X., & Constable, R. T. (2017). Using connectome-based predictive modeling to predict individual behavior from brain connectivity. Nature Protocols, 12(3), 506–

518. https://doi.org/10.1038/nprot.2016.178

Spearman, C. (1904). "General Intelligence," Objectively Determined and Measured.

The American Journal of Psychology, 15(2), 201–292.

https://doi.org/10.2307/1412107

Uğurbil, K., Xu, J., Auerbach, E. J., Moeller, S., Vu, A. T., Duarte-Carvajalino, J. M.,

Lenglet, C., Wu, X., Schmitter, S., Van de Moortele, P. F., Strupp, J., Sapiro, G.,

De Martino, F., Wang, D., Harel, N., Garwood, M., Chen, L., Feinberg, D. A.,

Smith, S. M., … Yacoub, E. (2013). Pushing spatial and temporal resolution for

functional and diffusion MRI in the Human Connectome Project. NeuroImage,

80, 80–104. https://doi.org/10.1016/j.neuroimage.2013.05.012

Van Essen, D. C., Smith, S. M., Barch, D. M., Behrens, T. E. J., Yacoub, E., & Ugurbil, K.

(2013). The WU-Minn Human Connectome Project: An overview. NeuroImage,

80, 62–79. https://doi.org/10.1016/j.neuroimage.2013.05.041

Yeo, B. T. T., Krienen, F. M., Sepulcre, J., Sabuncu, M. R., Lashkari, D., Hollinshead, M.,

Roffman, J. L., Smoller, J. W., Zöllei, L., Polimeni, J. R., Fisch, B., Liu, H., &

Buckner, R. L. (2011). The organization of the human cerebral cortex estimated

by intrinsic functional connectivity. Journal of Neurophysiology, 106(3), 1125–

1165. https://doi.org/10.1152/jn.00338.2011

Supplemental figures

Comparison of predictions based on task fMRI and resting fMRI data

Supplemental Figure S1. Scatterplots comparing VAF by regional prediction models using task fMRI and resting fMRI connectivity. A. Hyperaligned, fine-grained connectivity. B. Coarse-grained connectivity. C. MSM-aligned connectivity. Each circle represents one region. The color of each circle corresponds to the cortical system that each region is part of (based on a plurality of vertices), using the same color scheme as in Figures 2D and 3D. Results showed that task fMRI data produced better predictions of general intelligence than did resting fMRI for hyperaligned residual fine-grained, coarse-grained, and MSM-aligned residual fine-grained connectivity.

Comparison of alignments

Supplemental Figure S2. Histograms of VAF by predictions of general intelligence using

different fMRI connectivity datasets and different alignment methods. A. Prediction based

on residual fine-grained connectivity. B. Predictions based on coarse-grained connectivity.

C. Predictions based on full fine-grained connectivity, which includes information in both fine-grained and coarse-grained patterns. CHA is short for connectivity hyperalignment.

Connectivity hyperalignment based on task fMRI data produced stronger predictions of general intelligence based on task connectivity than did connectivity based on resting fMRI data. Predictions based on resting connectivity were equivalent for connectivity hyperalignment based on task fMRI and resting fMRI. Prediction based on hyperaligned residual fine-grained connectivity and on hyperaligned full fine-grained connectivity profiles (A and C) were essentially identical.

Hyperalignment transformations remix the time series for cortical vertices, which alters the mean of correlations between the vertices of two regions - namely, the coarse-scale functional connectivity between these regions (B). Analyses of hyperaligned fine-grained connectivity profiles all used the coarse-grained connectivity profiles calculated on the same hyperaligned data for comparison. In practice the effect of calculating coarse-grained connectivity profiles on task hyperaligned task fMRI, hyperaligned resting fMRI, and MSM-aligned fMRI is small and does not affect the results of these analyses (Supplemental Figure S2).

Predicting intelligence based on connectivity during single tasks

Prediction based on connectivity during single tasks

Supplemental Figure S3. Histograms of VAF by regional models prediction models based on connectivity calculated from fMRI during single tasks. For every single fMRI task (4.2 to 9.7 min) fine-scale hyperaligned connectivity data produced better predictions of general intelligence than did coarse-scale connectivity. The strongest predictions from single task fMRI were obtained from data during performance of the working memory (WM), language, and social cognition tasks.