1   **The neural basis of intelligence in fine-grained cortical topographies**

2   Ma Feilong[1], J. Swaroop Guntupalli[2], James V. Haxby[1]*

3   [1]Center for Cognitive Neuroscience, Dartmouth, Hanover NH

4   [2]Vicarious AI, Union City CA

5   *Address correspondence to JVH (james.v.haxby@dartmouth.edu)

6   **Abstract**

Intelligent thought is the product of efficient neural information processing, which is

embedded in fine-grained, topographically-organized population responses and supported by

fine-grained patterns of connectivity among cortical fields. Previous work on the neural basis

of intelligence, however, has focused on coarse-grained features of brain anatomy and

function, because cortical topographies are highly idiosyncratic at a finer scale, obscuring

individual differences in fine-grained connectivity patterns. We used a computational

algorithm, hyperalignment, to resolve these topographic idiosyncrasies, and found that

predictions of general intelligence based on fine-grained (vertex-by-vertex) connectivity

patterns were markedly stronger than predictions based on coarse-grained (region-by-region)

patterns. Intelligence was best predicted by fine-grained connectivity in the default and

frontoparietal cortical systems, both of which are associated with self-generated thought.

Previous work overlooked fine-grained architecture because existing methods couldn't resolve

idiosyncratic topographies, preventing investigation where the keys to the neural basis of

intelligence are more likely to be found.

21   **Introduction**

Intelligent thought is the product of efficient neural information processing, but the neural

architecture that makes some brains capable of quick wit and deep insight, while others

struggle with simple problems, remains an open question. Previous work on the neural basis of

intelligence has focused on coarse-grained features of brain anatomy and function, such as the

size and shape of the brain and its parts (e.g., Cox et al., 2019; Luders et al., 2007; Schmitt et

al., 2019) or the size and strength of connections between large cortical fields (e.g., Dubois et

al., 2018; Finn et al., 2015; Kong et al., 2019; Shen et al., 2017). Neural information processing,

however, is embedded in fine-grained, topographically-organized population responses

(Haxby et al., 2014, 2001). Functional connectivity varies vertex-by-vertex (Guntupalli et al.,

2018), and even neuron-by-neuron (Park et al., 2017), to support such information processing.

Therefore, fine-grained functional connectivity depicts in detail how information is exchanged

and processed between cortical regions, in contrast to coarse-grained region-by-region

connectivity, which depicts the overall synchronization between regions. We investigated

whether individual differences in general intelligence are a function of information embedded

in fine-grained cortical architecture.

37   Fine-grained patterns of activity and connectivity can be studied with functional

magnetic resonance imaging (fMRI), but the topographies of these patterns are idiosyncratic,

impeding study of their role in the neural basis of individual differences in cognitive ability. We

used hyperalignment (Feilong et al., 2018; Guntupalli et al., 2018, 2016; Haxby et al., 2020,

2011) to resolve the interindividual variation of fine-grained topographies of functional

connectivity. Hyperalignment remixes the connectivity profiles of loci in a cortical field into a

high-dimensional common space to maximize the similarity across brains in fine-grained,

vertex-by-vertex patterns. Individual variation in the residuals around common fine-grained

patterns are more reliable than individual variations around common coarse-grained patterns,

after resolving idiosyncratic topographies with hyperalignment (Feilong et al., 2018). We

found that predictions of general intelligence based on fine-grained (vertex-by-vertex)

patterns of connectivity were markedly stronger than predictions based on coarse-grained

(region-by-region) patterns. Intelligence was best predicted by fine-grained connectivity in the

default and frontoparietal cortical systems, both of which are associated with self-generated

thought. These results demonstrate that the neural mechanisms of intelligence reside more in

fine-grained interactions of cortical regions than in synchronization of oscillations in large

cortical fields.

54   **Results**

We used data from 876 participants of the Human Connectome Project (HCP) (Van Essen et al.,

2013). Each participant had about 47 minutes of task fMRI data, collected during the

performance of seven tasks, one hour of resting-state fMRI data, and scores on 10 cognitive

tests. We used connectivity hyperalignment (Guntupalli et al., 2018) to factor out

idiosyncrasies in fine-grained topographies and model information encoded in local functional

connectivity patterns that is shared across brains. We hyperaligned both the HCP task fMRI

and resting fMRI datasets. Connectivity hyperalignment projects idiosyncratic cortical

topographies for individual brains into a common model connectivity space in which the

patterns of connectivity across vertices in a cortical field with connectivity targets elsewhere in

the brain are maximally similar across brains. We measured general intelligence (Spearman,

1904) as a general factor based on 10 cognitive test scores included in the HCP database

(Dubois et al., 2018).

For each of 360 cortical regions, from a parcellation tailored to the HCP dataset

(Glasser et al., 2016), we computed fine-grained task fMRI and resting fMRI connectivity

profiles for each individual (Figure 1). The connectivity profile for each cortical vertex differs

from profiles for other vertices in the region with a granularity in the common model space

that is equivalent to spatial variation across cortical loci within individual brains (Guntupalli et

al., 2018). We factored out the effect of coarse-grained connectivity by subtracting the mean

connectivities between pairs of regions (coarse-grained connectivity profiles; Figure 1, middle

row) from the vertex-wise connectivities (full fine-grained connectivity profiles; Figure 1, top

row), to examine the predictive power of fine-grained connectivity unconfounded with

prediction based on coarse-grained connectivity. These residual fine-grained connectivity

profiles were used throughout the analysis, and we refer to them as fine-grained connectivity

profiles for short. Results based on these residual profiles were very similar to those based on

full fine-grained connectivity profiles (Supplementary Figure S2). We calculated coarse-

grained connectivity on the same hyperaligned data used for calculation of fine-grained

connectivity (see Supplementary Figure S2).

Figure 1. Schematic illustration of coarse- and fine-grained functional connectivity.
Each brain region (e.g., area 150 shown here) comprises multiple cortical vertices (on
average 165). Correlations between their time series and time series for all 59,412 vertices
in the whole cortex form that region's full fine-grained connectivity matrix (top row). The
fine-grained connectivity profiles for 360 brain regions each have approximately 10 million
such correlations. The coarse-grained connectivity profile for the same region (middle row)
comprises the average functional connectivity between all of the vertices in that region and
all of the vertices in each of the 360 brain regions. Thus, the coarse-grained connectivity
profiles for 360 brain regions each have 360 mean correlations. The residual fine-grained
connectivity profile (bottom row) for each region is obtained by subtracting the mean
correlation for a pair of regions (e.g., region 1 and region 150) from the full fine-grained

connectivity profile for that pair and is, thus, unconfounded with coarse-grained functional

connectivities. We refer to these unconfounded profiles as fine-grained connectivity

profiles for short.

We built prediction models based on regional connectivity profiles using cross-

validated principal component regression with ridge regularization. We divided the data into k

test participants from one family (k = 1 to 6) and the remaining 876-k training set participants

(Figure 2). Thus, each test participant's intelligence was predicted using regression weights

derived from other participants' data. We assessed the performance of these models using a

coefficient of determination (R^2), which denotes the percent of intelligence score variance

accounted for (VAF) by the prediction models. We made separate prediction models for

hyperaligned fine-scale task and resting connectivity, for coarse-grained task and resting

connectivity, and for non-hyperaligned fine-scale task and resting connectivity.

Figure 2. Schematic illustration of analysis pipeline. We used a leave-one-family-out

cross-validation scheme. For each data fold, we built a prediction model based on the

training subjects' data (yellow color) to predict general intelligence (g) from the

connectivity profile of a cortical region, and applied the model to test subjects' connectivity

profiles to predict their general intelligence scores (Steps 1 and 2). We aggregated

predicted and actually measured g across all cross-validation folds to assess model

performance with cross-validated R^2 (Step 3), and repeated this procedure for other cortical

regions' connectivity profiles (Step 4). After the entire pipeline, we obtained an R^2 for each

of the 360 cortical regions, which stands for the amount of variance in g that can be

accounted for by the region's connectivity profile. We repeated the pipeline for different

kinds of connectivity profiles (spatial granularity, dataset, and alignment method) and

compared them systematically (Figures 3–5), and these repetitions only differ in the

connectivity profiles fed into the pipeline.

Hyperaligned fine-grained versus coarse-grained connectivity profiles

Regional hyperaligned fine-grained task and resting connectivity profiles were highly

predictive of general intelligence (Figures 3A and 4A) and accounted for twice as much

variance in general intelligence as compared to coarse-grained connectivity profiles (Figures

3B, 3C, 4B, and 4C).

Prediction of intelligence based on task fMRI connectivity profiles

On average across all cortical regions, prediction models based on hyperaligned fine-

grained task fMRI connectivity accounted for 27.3% of variance in general intelligence (min:

11.2%, max: 38.9%). In other words, the correlation between predicted and measured

intelligence scores ranged from r = 0.34 in the least predictive brain region to r = 0.62 in the

most predictive brain region. By contrast, prediction models based on coarse-grained task

fMRI connectivity (Figure 3B) accounted on average for only 14.9% of variance (min: 3.3%,

max: 26.5%), which is only 54.2% (95% CI: [48.7%, 58.8%]) of VAF by hyperaligned fine-

grained connectivity overall. VAF by hyperaligned fine-grained task connectivity was higher

than VAF by coarse-grained connectivity in all 360 ROIs (Figure 3C). These results suggest that

the information encoded in fine-grained interaction patterns between brain regions affords

markedly stronger predictions of intelligence than information in coarse-grained patterns.

The 30 most predictive regions (Figure 3D and 3E; 33.8% to 38.9% VAF) were in bilateral

inferior parietal cortex (15 regions), bilateral medial and superior prefrontal cortex (11 regions),

bilateral medial parietal (2 regions), and bilateral posterior lateral temporal cortex (2 regions).

The cortices in these regions were predominantly part of the default mode and frontoparietal

systems (38.9% and 34.5% of cortical vertices, respectively) with small portions in the ventral

and dorsal attention systems (11.3% and 10.6%, respectively; Figure 3D and 3E) (Yeo et al.,

2011). Assignment to cortical systems in a different parcellation tailored to the Glass

parcellation (Ji et al., 2019) similarly revealed the dominant role played by the default and

frontoparietal systems (Supplementary Figure S11).

Prediction based on task fMRI functional connectivity

Figure 3. Predicting general intelligence based on regional task fMRI connectivity profiles.

Prediction based on hyperaligned fine-grained (**A**) and coarse-grained (**B**) connectivity

profiles, assessed by the variance in general intelligence accounted for. The scatter plot (**C**)

shows that predictions based on hyperaligned fine-grained profiles accounted for more

variance in all 360 ROIs. Prediction models based on each region's fine-grained

hyperaligned task functional connectivity profile accounted for 1.85 (95% CI: [1.70, 2.05])

times more variance in general intelligence on average than did models based on coarse-

grained functional connectivity profiles. Each circle is a cortical region, and the color of

each circle corresponds to the cortical system where it resides, using the same color

scheme as in (**E**). Dashed lines denote average difference in R^2 (gray), or identical R^2

(black). (**D**) The thirty regions whose hyperaligned fine-grained connectivity best predicted

general intelligence are colored as in panels A and B. The default mode network is outlined

in red, and the frontoparietal network is outlined in orange (Yeo et al., 2011). (**E**)

Proportion of vertices in these regions that are in seven cortical systems delineated with

resting state fMRI functional connectivity (Yeo et al., 2011).

Prediction of intelligence based on resting fMRI connectivity profiles

163   Prediction of general intelligence based on resting fMRI connectivity showed a similar

advantage for hyperaligned fine-grained profiles, relative to coarse-grained profiles (Figure 4),

but performance was substantially lower than for task fMRI connectivity, consistent with

previous reports (Greene et al., 2018; Jiang et al., 2020). Models based on hyperaligned fine-

grained resting fMRI connectivity accounted on average for 19.8% of variance (Figure 4A; min:

4.7%, max: 31.2%), whereas models based on coarse-grained connectivity accounted on

average for 8.1% of variance (Figure 4B; min: -1.2%, max: 17.4%), which is only 40.5% [CI:

34.2%, 45.8%] of VAF by hyperaligned fine-grained resting connectivity. Hyperaligned fine-

grained resting fMRI connectivity, as compared to coarse-grained resting fMRI connectivity,

accounted for more variance in all 360 ROIs (Figure 4C). The vertices of 30 regions whose

resting hyperaligned fine-grained connectivity was most predictive of general intelligence

(25.3% to 31.2% VAF) had a distribution that was similar to that for hyperaligned task

connectivity, sharing 68.3% of cortical vertices (compare Figures 3D and 4D), with vertices

mostly in the default mode network (49.0%) and smaller parts in the frontoparietal (19.4%),

dorsal attention (15.8%) and ventral attention (10.0%) systems (Figure 4E; see also

Supplementary Figure S11).

Prediction based on resting fMRI functional connectivity

Figure 4. **Predicting general intelligence based on regional hyperaligned resting fMRI**

connectivity profiles. Prediction based on fine-grained (**A**) and coarse-grained (**B**)

connectivity profiles. The scatter plot (C) shows that regional predictions based on

hyperaligned fine-grained profiles accounted for more variance in all 360 ROIs. Prediction

models based on each region's fine-grained hyperaligned resting functional connectivity

profile accounted for 2.48 (95% CI: [2.18, 2.93]) times more variance in general intelligence

on average than did models based on coarse-grained functional connectivity profiles. Each

circle is a cortical region, and the color of each circle corresponds to the cortical system

where it resides, using the same color scheme as in (**E**). Dashed lines denote average

difference in R^2 (gray), or identical R^2 (black). (**D**) The thirty regions whose hyperaligned

fine-grained connectivity best predicted general intelligence are colored as in panels A and

B. The default mode network is outlined in red, and the frontoparietal network is outlined

in orange (Yeo et al., 2011). (**E**) Proportion of vertices in these regions that are in seven

cortical systems delineated with resting state fMRI functional connectivity (Yeo et al.,

2011).

Consistent with previous reports (Greene et al., 2018; Jiang et al., 2020), task fMRI

connectivity was significantly more predictive of general intelligence than was resting fMRI

connectivity for both hyperaligned fine-grained data (difference = 7.6% VAF; 95% CI: 5.3% to

9.9%) and coarse-grained data (difference = 6.8% VAF; 95% CI: 5.0% to 8.6%). Task

connectivity accounted for more variance than did resting connectivity in 358 of 360 ROIs for

hyperaligned fine-grained data and in 343 of 360 ROIs for coarse-grained data (Supplementary

Figure S1).

Hyperaligned versus MSM-aligned fine-grained connectivity profiles

To test the efficacy of hyperalignment for revealing predictive individual differences in

fine-grained connectivity topographies, we trained another set of models based on fine-

grained functional connectivity of data without hyperalignment. These data were aligned with

Multimodal Surface Matching (MSM) (Robinson et al., 2014). Models based on MSM-aligned

fine-grained task connectivity and resting connectivity accounted for, on average across ROIs,

17.6% (min: 5.1%; max: 28.7%) and 11.1% (min: 0.8%; max: 22.5%), respectively, of variance in

general intelligence, which was 64.3% (95% CI: [59.9%, 68.3%]) and 56.0% (95% CI: [49.7%,

61.7%]) of that accounted for by models using hyperaligned data (Figure 5). Predictions based

on hyperaligned fine-grained task connectivity were better than predictions based on MSM-

aligned fine-grained connectivity in all 360 regions (Figure 5C). Predictions based on

hyperaligned fine-grained resting connectivity were better than predictions based on MSM-

aligned fine-grained connectivity in 357 of 360 regions (Figure 5D). The difference in model

performance was larger for brain regions with more functional topographic idiosyncrasy for

both task and resting connectivity (r = 0.435 and 0.425, respectively, $p < 10^{-14}$), with two- to

three-fold increases in VAF in the most idiosyncratic regions. As for hyperaligned fine-scale

connectivity and for coarse-scale connectivity, MSM-aligned fine-scale task connectivity was

more predictive of intelligence than was MSM-aligned fine-scale resting connectivity

(difference = 6.5% VAF; 95% CI: [5.0%, 8.0%]; Supplementary Figure S1C). Consistent with our

previous findings (Feilong et al., 2018), these results show that hyperalignment factors out

idiosyncrasies in functional topography to reveal how individuals differ in information encoded

in fine-grained cortical functional architecture.

Prediction based on MSM-aligned fine-grained connectivity

Figure 5. **Predicting general intelligence based on MSM-aligned fine-grained**

connectivity profiles. Prediction based on task fMRI (**A**) and resting fMRI (**B**) connectivity.

Scatterplots compare regional predictions based on MSM-aligned to predictions based on

228   hyperaligned task connectivity (**C**) and resting connectivity (**D**) data (comparison to results

229   in Figures 3A and 4A).

Discussion

The results show that individual differences in fine-grained patterns of functional

connectivity are a markedly better predictor of general intelligence than are coarse-grained

patterns, indicating that differences in cortical architecture that underlie inter-individual

variation in the efficiency of information processing are more evident at the same spatial scale

as topographic patterns that encode information. Discovering the dominant role of fine-

grained connectivity patterns in the neural basis of intelligence required a method that

resolves individual differences in these idiosyncratic patterns, a method that was not available

prior to hyperalignment (Feilong et al., 2018; Guntupalli et al., 2018, 2016; Haxby et al., 2020,

2011; Nastase et al., 2020).

Differences in intelligence are indexed by tests of the ability to understand and

manipulate information embedded in the meanings of words, logical relations, and visual

patterns. We predicted that differences in performance would be more related to the fine-

grained topographic patterns that represent these kinds of information than to coarse-grained

patterns that blur fine distinctions. The results confirm our hypothesis. Hyperaligned, fine-

grained, vertex-by-vertex connectivity patterns accounted for 1.85 to 2.48 times more variance

in general intelligence than did coarse-grained, region-to-region connectivity patterns.

To examine the predictive power of fine-grained connectivity unconfounded with

coarse-grained connectivity, we built models using the residual fine-grained connectivity

profiles. In separate analyses we built models on the full fine-grained patterns and found that

adding coarse-grained information contributed little to VAF (Supplementary Figure S2),

underscoring the stronger role that fine-grained cortical architecture plays in the neural basis

of intelligence than that played by coarse-grained architecture.

Functional connectivity shows fine-grained variation vertex-by-vertex within a cortical

field (Guntupalli et al., 2018) and even neuron-by-neuron within an fMRI voxel (Park et al.,

2017). Transmission of information between cortical fields, therefore, involves more than

simple synchronization of global activity. Information is transformed, as evidenced by changes

in the representational geometries that are embedded in the fine-grained structure of local

topographies (Connolly et al., 2016; Guntupalli et al., 2017; Kriegeskorte et al., 2008). Our

results indicate that investigating the efficiency of information processing should focus on fine-

grained patterns of connectivity that support information processing.

Hyperalignment resolves functional topographic idiosyncrasies at both coarse and fine

spatial scales (see Jiahui et al., 2020 for an example of aligning functional topographies), which

is critical for assessing individual differences in information processing. Alternatively,

individualized parcellations (e.g., Kong et al., 2019; Glasser et al., 2016) can be used to resolve

coarse-scale topographic idiosyncrasies, which also improves prediction performance (Kong et

al., 2021). However, the improvement for coarse-grained functional connectivity was smaller

than for fine-grained functional connectivity in predicting general intelligence (Supplementary

Figure S2).

Previous work could not reveal the role that information embedded in fine-scale

topographies plays in the neural basis of intelligence because individual differences in

information were concealed by idiosyncrasies in fine-scale topographies that could not be

aligned with prior methods. Hyperalignment resolves the shared information embedded in

idiosyncratic topographies, making it possible to investigate these individual differences

(Feilong et al., 2018). Fine-grained information in hyperaligned data accounted for 1.56 to 1.79

times more individual variation in intelligence than did fine-grained information in non-

hyperaligned data.

Results also show that fMRI data collected during performance of cognitive tasks better

predict intelligence than resting state fMRI data, consistent with previous reports (Greene et

al., 2018; Jiang et al., 2020). Previous studies used whole-brain, coarse-grained connectivity

for prediction. Here we show that the added predictive power of task fMRI data, relative to

resting fMRI data, extends to both hyperaligned and MSM-aligned fine-grained connectivity

patterns.

Our results show further that the neural basis of intelligence resides mostly in the fine-

grained structure of connectivity in the default mode and frontoparietal networks (Buckner et

al., 2008; Raichle et al., 2001; Yeo et al., 2011). Small parts of the most predictive regions were

in the dorsal and ventral attention networks, and an even smaller proportion was in the visual

system. The most predictive brain regions did not encroach on the systems for auditory,

somatosensory, motor, or limbic function. The predominance of the default mode network

was found for both task connectivity and resting connectivity, suggesting that the efficiency of

these connections is evident in both. A strong role for the frontoparietal network was more

evident in task connectivity, suggesting that efficiency of this system's connections is better

revealed during performance of tasks that increase its activity.

The predominant role of the default and frontoparietal systems in our results suggests

that intelligence rests on self-generated and stimulus-independent thinking (Andrews-Hanna

et al., 2014; Buckner et al., 2008; Dixon et al., 2018; Raichle et al., 2001), or on the apperceptive

mass that provides the foundation and context for perception and thought (Raichle, 2006), for

finding correct solutions to problems and generating novel insights. The functions of the

default system are mostly ill-defined because it does not respond to features of external

stimuli in a consistent way (Andrews-Hanna et al., 2014; Buckner et al., 2008; Golland et al.,

2007). Although default system activity during movie watching and in the resting state is

idiosyncratic, it is highly correlated across default areas (Buckner et al., 2008; Golland et al.,

2007) and has a fine-scale structure that can be modeled with hyperalignment (Feilong et al.,

2018; Guntupalli et al., 2018), indicating that this activity has structure and meaning. It has

been associated with thinking about others' mental states (Buckner et al., 2008; Frith and

Frith, 1999; Gobbini et al., 2007; Saxe and Kanwisher, 2003), activation of person knowledge

about familiar others (Gobbini and Haxby, 2007), autobiographical memory and envisioning

the future (Addis et al., 2007), as well as other aspects of internally-driven cognition. The most

predictive regions overlapped only a portion of the default network involving primarily the

dorsal medial subsystem with smaller parts in the core subsystem (Andrews-Hanna et al.,

2014, 2010). The dorsal medial subsystem has been associated with mentalizing, social

cognition, story comprehension, and semantic conceptual processing (Andrews-Hanna et al.,

2014).

The frontoparietal system may similarly reflect the role of self-directed thought in the

neural basis of general intelligence. Dixon et al. (2018) have identified a subdivision of the

frontoparietal network that interacts primarily with the default mode system. They propose

that this part of the frontoparietal system is involved in the regulation of introspective

processes.

The efficiency of the default system apparently rests more on fine-grained features of

its functional connectivity than on coarse-grained functional connectivity. The bases for the

organization of its fine-grained topographies and the transformations of representational

geometries between default regions are unknown, but the keys to understanding the neural

basis of intelligent thought may reside in the information processing embedded in these

topographies.

Acknowledgements

We would like to thank Guo Jiahui, Samuel Nastase, Jeremy Huckins, and Maria Ida Gobbini for helpful comments, suggestions, and discussion. We would like to thank Yaroslav Halchenko for support with software.

Data were provided by the Human Connectome Project, WU-Minn Consortium (Principal Investigators: David Van Essen and Kamil Ugurbil; 1U54MH091657) funded by the 16 NIH Institutes and Centers that support the NIH Blueprint for Neuroscience Research; and by the McDonnell Center for Systems Neuroscience at Washington University.

This work was supported with funds from NSF grants 1607845 and 1835200.

Author contributions

Conceptualization, M.F., J.V.H; Methodology, M.F., J.S.G., J.V.H.; Software, M.F., J.S.G.; Formal analysis, M.F.; Resources, J.V.H; Writing - original draft, M.F., J.V.H.; Writing - review and editing, M.F., J.S.G., J.V.H.; Visualization, M.F., J.V.H.; Supervision and Funding acquisition, J.V.H.

Declarations of interests

The authors declare no competing interests.

340   **Methods**

Dataset

We used data from the Human Connectome Project (HCP) (Van Essen et al., 2013) for

our analysis. The final S1200 data release of the HCP Young Adult dataset contains multi-

modal MR imaging and behavioral data from 1206 participants that are 22-35 years old. This

includes about one hour of resting-state fMRI data (4 runs, 14.5 minutes each), 47 minutes of

task fMRI data (7 tasks, 2 runs each), and extensive cognitive tests for each participant. Out of

the 1206 participants, 888 have complete task and resting fMRI data, 1181 have complete

scores of 10 cognitive tests, and 876 participants have both. In our analysis, we always used as

many participants with complete data as possible to maximize statistical power. That is, we

used data from the 1181 participants to derive the general intelligence score, data from the 888

participants to derive hyperalignment models and compute topographic idiosyncrasy, and

data from the overlapping 876 participants for prediction analysis.

We used a multi-modal cortical parcellation tailored to this dataset (Glasser et al., 2016)

to delineate cortical regions and compute connectivity targets for hyperalignment as described

below. This parcellation is usually labeled as "Q1-Q6_RelatedParcellation210" or "210P" in the

HCP dataset, and sometimes referred to as HCP MMP 1.0.

Measuring general intelligence

General intelligence is a common factor, often referred to as g, underlying all cognitive

abilities (Spearman, 1904). In this study, we measured general intelligence as the general

factor obtained based on 10 cognitive test scores using a factor analysis with a bi-factor model

(Dubois et al., 2018). These cognitive tests (Barch et al., 2013) include those from the NIH

Toolbox for Assessment of Neurological and Behavioral Function (http://www.nihtoolbox.org)

and additional computerized tests (Bilker et al., 2012; Gur et al., 2010), covering a range of

memory, attention, language, and reasoning abilities. General intelligence can be accurately

and consistently identified through different test batteries (Johnson et al., 2008, 2004), and our

findings are robust over choices of intelligence measures (Supplementary Figures S6 and S7).

For this dataset, the general factor of intelligence was derived from the code of Dubois et al.,

(2018), and it accounts for 58% of the covariance structure of cognitive tasks (Dubois et al.,

2018).

MRI acquisition

MRI data were acquired with a Siemens 3 T Skyra MRI scanner and a 32-channel head

coil at Washington University (Van Essen et al., 2013). The scanner was customized with a

gradient coil and gradient power. Each subject has 2 T1w and 2 T2w scans with 0.7 mm

isotropic voxels, which were used to reconstruct high-resolution cortical surfaces.

Functional MRI data were acquired with a TR of 0.72 s, 2 mm isotropic voxels, and a

multi-band acceleration factor of 8. Every volume comprised 72 slices with 208×180 mm^2

FOV each. Half of the fMRI runs were scanned with the LR phase encoding direction, and the

other half were with RL. Spin-echo field maps were collected along with the fMRI data that

allow susceptibility distortion correction.

Resting fMRI data were acquired with 4 runs of 1200 TRs each. Each of the 7 tasks were

acquired with 2 runs, and the duration of each run varied across tasks (min: 176 TRs, max: 405

TRs). In total, for each participant, 57.6 minutes of resting fMRI data and 46.6 minutes of task

fMRI data were acquired. See (Uğurbil et al., 2013) for additional details of MRI acquisition.

MRI preprocessing

We used the same standard procedure to preprocess fMRI data for all task and resting

fMRI data. Our preprocessing was based on the minimally preprocessed version of the dataset

(Glasser et al., 2013), where data had been corrected for distortion and head motion, and

aligned to a standard cortical surface mesh using Multimodal Surface Matching (MSM)

(Robinson et al., 2014), which aims to match multimodal properties across individuals while

preserving topology. These data were labeled as "MSMAll" in the HCP data files, and we refer

to them as "MSM" for short.

We first normalized all fMRI data to percent signal change units, then used linear

regression to remove nuisance components from them. These nuisance components include 6

motion parameters and their derivatives, 5 principal components from white matter and

cerebrospinal fluid (Behzadi et al., 2007), global signal, and polynomial trends up to the 3rd

order. The white matter and cerebrospinal fluid components were extracted from volumetric

data based on eroded anatomical masks. Both the regressors and data were low-pass filtered

with a Gaussian kernel (standard deviation = 1 TR) prior to regression. These preprocessing

steps were analogous to previous work (Dubois et al., 2018; Finn et al., 2015; Greene et al.,

2018; Shen et al., 2017).

Hyperalignment

We performed hyperalignment using these preprocessed data to align the fine-grained

cortical functional architecture across individuals, and obtained two sets of hyperaligned data

(one based on task fMRI data, one based on resting fMRI data) besides the original MSM-

aligned dataset. Specifically, we used connectivity hyperalignment (Guntupalli et al., 2018) to

align fine-grained cortical functional architecture across individuals. We used regional average

time series of the 360-region multi-modal cortical parcellation (Glasser et al., 2016) as

connectivity targets. For each of the 59,412 cortical vertices, we computed its connectivity

profile as the correlations between its own time series and the 360 regional average time

series. Therefore, each connectivity profile is a vector comprising 360 correlation coefficients.

In each brain region, we derived a transformation matrix for each individual using these

connectivity profiles, which remixes each individual's vertices into a common set of model

dimensions through an improper rotation of a high-dimensional space. Each model dimension

has similar functional properties across individuals instead of the same anatomical position,

and these model dimensions together constitute a common model space. The common model

space is usually instantiated as a reference brain, where each vertex corresponds to a model

dimension. The information content in each individual's data — the configuration of

connectivity vectors in the high-dimensional feature space — is perfectly preserved during the

rotation, whereas how and where this information is encoded in idiosyncratic topographies is

factored out into the transformation matrix.

In this study, hyperalignment was performed for each brain region separately (i.e., in a

similar manner to Haxby et al., 2011 rather than Guntupalli et al., 2016), and the

transformation was constrained to be an improper rotation (i.e., rotation that allows reflection)

with no scaling. This was to strictly ensure that the information content within a brain region

was identical before and after hyperalignment, and only the cortical topography of the

information was changed (i.e., better aligned). Searchlight hyperalignment (Guntupalli et al.,

2016) allows information to be moved in and out of a brain region to some extent, which is

preferable in general, because the same function doesn't always reside in the same anatomical

region for all participants (Eickhoff et al., 2018). However, in this case it can make it difficult to

interpret the results. For example, an improvement of prediction performance after

searchlight hyperalignment can be caused by better alignment of information in a region, but

it can also be caused by additional information moved into the region or noise moved out of

the region.

We used the HCP task fMRI dataset to derive the hyperalignment common model and

transformations (i.e., to train hyperalignment) when we analyzed the task fMRI data, and

resting fMRI dataset when we analyzed the resting fMRI data. Therefore, the task and resting

fMRI datasets remain independent throughout the analysis. It is possible to train

hyperalignment using one dataset and apply it to another, and such results are summarized in

Supplementary Figure S2.

Functional connectivity profiles

We used functional connectivity profiles to depict a brain region's functional

interactions with the entire cerebral cortex. These connectivity profiles are different from the

connectivity profiles used in connectivity hyperalignment as described above.

For each of 360 cortical regions, we computed a fine-grained connectivity matrix for

each participant (Figure 1, top row), which comprises pairwise interactions between all vertices

in the region (165 vertices on average) and all vertices of the cerebral cortex (59,412 vertices).

We vectorized this connectivity matrix to form a long vector comprising millions of

connectivity strengths (9.8 million on average across all regions), which we refer to as the

participant's full fine-grained connectivity profile of the region. This fine-grained connectivity

profile depicts in detail the region's information exchange with the rest of the cortex, and it

contains information encoded in fine-grained connectivity patterns up to the same resolution

as the input fMRI data (2 mm for this dataset).

To separate information encoded in different spatial scales, we split the full fine-

grained connectivity profile into a coarse-grained connectivity profile and a residual fine-

grained connectivity profile. The coarse-grained connectivity profile for a given region is a

vector comprising 360 elements, where each element is the average connectivity strength

between all cortical vertices in this region and all vertices in another region (Figure 1, middle

row). Similar to previous work (Dubois et al., 2018; Finn et al., 2015; Shen et al., 2017), coarse-

grained connectivity profiles depict the information exchange between a pair of regions with a

single connectivity strength. A residual fine-grained connectivity profile comprises pattern

residuals obtained by subtracting the mean connectivity with each region (an element of the

coarse-grained connectivity profile) from each element of the vertex-by-vertex connectivity

pattern with the region (part of the full fine-grained connectivity profile). Because a coarse-

grained connectivity profile is comprised of region-by-region averages of the corresponding

fine-grained connectivity profile, a regression model using coarse-grained connectivity profile

(expanded to the same size as the fine-grained connectivity profile) as the independent

variable and fine-grained connectivity profile as the dependent variable will always have a

slope of 1. Therefore, the difference between the two profiles is also the residual of the

regression model. Similar to a full fine-grained connectivity profile, a residual fine-grained

connectivity profile comprises millions of elements, and the only difference is that these

elements are connectivity residuals instead of connectivities. In other words, a residual fine-

grained connectivity profile contains only fine-scale information, instead of combined fine- and

coarse-scale information.

The analysis involves data aligned in 3 different ways: MSM, hyperalignment based on

task fMRI data, and hyperalignment based on resting fMRI data. For each alignment method,

we computed these 3 kinds of connectivity profiles for each participant and each region. The

results of fine-grained connectivity profiles reported in the main text are based on residual

fine-grained connectivity profiles, and similar results were obtained using full fine-grained

connectivity profiles (Supplementary Figure S2).

Topographic idiosyncrasy

We measured the level of each region's functional topographic idiosyncrasy as the

average dissimilarity of hyperalignment transformation matrices across participant pairs for

that region, after correcting for region size. Specifically, for each brain region, we computed

the Frobenius norm of the difference between the two transformation matrices for each pair of

participants, and averaged it across all participant pairs to obtain an average matrix

dissimilarity (i.e., average difference matrix norm) for the region. The 360 cortical regions

differ in size (measured as the number of vertices in each region). As a result, transformation

matrices also differ in size for different regions, and the average matrix norm was

predominantly determined by region size. Across all 360 regions, the average matrix norm and

the square root of region size had a correlation of $r > 0.9999$. To remove the confounding

effects of region size, we fit a linear regression model across the 360 regions using sqrt(region

size) as the independent variable and the average matrix dissimilarity as the dependent

variable. We used the residual of the linear regression model to depict the heterogeneity of a

region's functional topography across individuals.

We performed hyperalignment twice in our analysis — once using task fMRI data, once

using resting fMRI data — and therefore obtained two sets of transformation matrices for each

region. Topographic idiosyncrasy indices based on each of the two sets are essentially

identical ($r = 0.960$, $p = 4 \times 10^{-200}$). When we analyzed task fMRI data, we used topographic

idiosyncrasy based on task fMRI (Figure 5C), and when we analyzed resting fMRI data, we used

that based on resting fMRI (Figure 5D).

Cross-validation scheme

We used leave-one-family-out cross-validation (Dubois et al., 2018) to assess prediction

models. The 876 participants were from 411 families, and each family had 2.13 members on

average (range: 1–5; with 103 participants with no other family members and 177, 107, 22, and

2 families with 2 to 5 participants, respectively). Therefore, this cross-validation scheme

divided the entire dataset into 411 folds. Each time we leave out a family of k individuals (i.e.,

related to each other) as test data, and use the remaining 876 - k individuals (i.e., not related to

test participants) as training data to train the model. We repeated this procedure, each time

using a different family as test data. Therefore, after looping through all families, each

individual's general intelligence score was predicted by a model trained with unrelated

individuals.

For each cross-validation fold (i.e., each family as test data), we further split the training

data into three sub-folds and used nested cross-validation to choose the optimal model

parameters. In other words, model parameters were always chosen based only on training

data.

To test the robustness of our prediction models against particular ways of splitting

data, we replicated our analysis using an alternative cross-validation scheme. Instead of the

leave-one-family-out cross-validation, we repeated 10-fold cross-validation 50 times, and each

time the data was split randomly into 10 chunks in a different way. To accommodate the

family structure of the dataset, we ensured that each time individuals from the same family

were always in the same chunk. The average model performance across the 50 repetitions was

highly similar to that based on leave-one-family-out cross-validation across all regions and

connectivity profile types (Supplementary Figure S8), suggesting our prediction model

performance evaluation was accurate and unbiased.

Regression models

We used principal component regression with ridge regularization to predict general

intelligence based on functional connectivity. First, we used principal component analysis

(PCA) to derive principal components (PCs) from functional connectivity patterns based on

training data. Dimensions in the PC space capture principal ways that individuals' connectivity

profiles differ. Thus, the connectivity profile for a region in each training set participant was

transformed into a set of scores across PC dimensions. Then, we trained a ridge regression

model to predict general intelligence based on these PC scores. The PCA and ridge regression

models were then applied to test data to obtain the model predicted general intelligence

scores. Model parameters (the number of PCs and the regularization parameter) were always

chosen using nested cross-validation as stated above. Candidate model parameters were

distributed evenly on a logarithmic scale. Choices for the number of PCs were 10, 20, 40, 80,

160, 320, and all PCs (i.e., no dimensionality reduction). The maximum number of PCs was

usually 360 for coarse-grained connectivity profile and 876-k for fine-grained connectivity

profile. Choices for the regularization parameter α were 81 values from 10^{-20} to 10^{20}.

Model evaluation

We evaluated our models using the cross-validated coefficient of determination (R^2). R^2

denotes the percent of variance in general intelligence that was accounted for (VAF) by

prediction models. The formula is

$$R^2 = 1 - \frac{\sum_i (y_i - \hat{y}_i)^2}{\sum_i (y_i - \bar{y}_{i,train})^2}$$

where is the measured score for subject i, ˆis the model predicted score for subject i, and

$\bar{y}_{i,train}$ is the prediction by the null model. The prediction of the null model is simply the

average score of all training data, and thus it doesn't use any information from the features

(fine- or coarse-grained functional connectivity in this case) at all. R^2 maximizes at 100%,

which means perfect prediction; 0 means model performance is only the same as the null

model. In rare cases, cross-validated R^2 can also be negative, which suggests the model

performance is even worse than the null model.

To assess model performance against chance, we used permutation testing to create a

null distribution of R^2. The HCP dataset has subjects that are from the same family, and they

are more likely to have similar general intelligence scores compared with non-related subjects

(Plomin and Deary, 2015). Therefore, the subject labels are not fully exchangeable, and we

used multi-level block permutation (Winkler et al., 2015) to resolve the issue. With this

hierarchical permutation approach, the data exchangeability is properly modeled, providing

more accurate estimates of false positive rates.

For each of the 2160 conditions (360 brain regions × 3 connectivity profile types × 2

fMRI data types), we ran a permutation test by training and evaluating prediction models 100

times based on shuffled subject labels. Each time, we permuted general intelligence scores

across the entire dataset in the beginning, and re-ran the entire prediction pipeline with these

permuted scores. That is, for each cross-validation fold, we chose the optimized parameters

using a nested cross-validation based on the training participants and their permuted scores,

and used these parameters to train a new model based on the entire training set, which was

used to predict the scores of the left-out family. After looping through all cross-validation

folds (i.e., all families), we assessed model performance based on the permuted scores. In

other words, we repeated the entire process — including parameter optimization, prediction,

and model evaluation — using permuted general intelligence score as the target variable

instead of the original general intelligence score.

Across conditions (Supplementary Figure S4) the maximum R^2 of all 100 permutations

was less than the value obtained with the prediction model (i.e., $p < 0.01$) for all models based

on hyperaligned fine-grained connectivity or on MSM-aligned fine-grained task connectivity

and for all models based on coarse-scale connectivity or on MSM-aligned fine-grained resting

connectivity that had a R^2 over 1.3%.

Estimating confidence intervals

We used bootstrap tests to estimate confidence intervals (CIs) for contrasts between

VAF by different prediction models. In each of 1,000,000 repetitions, we randomly sampled a

group of 876 individuals used for model evaluation by sampling with replacement from the 876

original individuals. In other words, in each bootstrapped sample, a participant might be

selected once, multiple times, or not selected at all. For each bootstrapped sample, we

computed VAF differences and VAF ratios. The 95% CI of a difference or ratio is estimated as

the 2.5th and 97.5th percentiles of the difference or ratio from the bootstrapped samples (i.e.,

the sampling distribution of the difference or ratio estimated by bootstrapping participants).

The bootstrapping procedure used here only affects the participants used for model evaluation

(i.e., the test set), and the model used to predict a participant's score was always trained with

the same training set (i.e., participants who are not from the same family as the test

participant). This was because prediction performance depends on training sample size

(Supplementary Figure S8), and duplicate instances in the training data don't have the same

effect on machine learning algorithms as "real" new data (e.g., noise from two duplicate

instances are not independent), which makes the bootstrapped sample no longer

representative of the population. Therefore, we only bootstrapped the participants used for

model evaluation, so that the sampling distribution is not biased by training sample size or

dependency.

Pearson correlation

We used the Pearson correlation coefficient to assess the relationship between regional

topographic idiosyncrasy and the difference in prediction performance based on hyperaligned

and MSM-aligned data (Figure 5, panels C and D), and the relationship between the square

root of a region's size and the average transformation matrix dissimilarity. In both cases, n (the

number of regions) is always 360, and the degrees of freedom is always 358.

Dice coefficient

We used the Dice similarity coefficient (Dice, 1945) to quantify the amount of overlap

between the 30 most predictive regions based on task fMRI data and those based on resting

fMRI data. The formula is

$$ = \frac{2| \cap |}{|| + ||}$$

where A is the set of vertices covered by the 30 most predictive regions based on task fMRI

data, and B is that based on resting fMRI data. |⬚| denotes set cardinality. *DSC* is short for Dice

similarity coefficient.

Overlap with cortical systems

The cerebral cortex can be divided into 7 cortical systems based on functional

connectivity (Yeo et al., 2011). For each of the 360 regions, we computed the percentage of

vertices belonging to each of the 7 systems as the number of vertices belonging to the system

divided by the total number of vertices in the region. For the 30 most predictive regions, we

computed the percentage of vertices across all 30 regions that belonged to each system

(Figures 3E and 4E). Similar results were found with an alternative division into 12 cortical

systems by Ji et al. (2019) (see Supplementary Figure S11). In the scatter plots (Figures 3C and

4C), each region was assigned to one of the cortical systems, which is the system that had the

largest amount of vertices in the region.

Software used

We implemented our analysis using Python and Python packages including NumPy

(https://numpy.org/), SciPy (https://www.scipy.org/), and NiBabel (https://nipy.org/nibabel/).

The code for performing hyperalignment and nuisance regression was adapted from PyMVPA

(http://www.pymvpa.org/) (Hanke et al., 2009).

Supplemental material

Comparison of predictions based on task fMRI and resting fMRI data

Supplementary Figure S1. Scatterplots comparing VAF by regional prediction models using task fMRI and resting fMRI connectivity. A. Hyperaligned, fine-grained connectivity. B. Coarse-grained connectivity. C. MSM-aligned fine-grained connectivity. Each circle represents one region. The color of each circle corresponds to the cortical system that each region is part of (based on a plurality of vertices), using the same color scheme as in Figures 3D and 4D.

Results showed that task fMRI data produced better predictions of general intelligence than did resting fMRI for hyperaligned residual fine-grained, coarse-grained, and MSM-aligned residual fine-grained connectivity.

Comparison of alignments and predictions based on single task connectivity

Supplementary Figure S2. Histograms of VAF by predictions of general intelligence using different
fMRI connectivity datasets and different alignment methods. A. Prediction based on residual fine-
grained connectivity. B. Predictions based on coarse-grained connectivity. C. Predictions based on
full fine-grained connectivity, which includes information in both fine-grained and coarse-grained
patterns. CHA is short for connectivity hyperalignment.

Connectivity hyperalignment based on task fMRI data produced stronger predictions of general
intelligence based on task connectivity than did connectivity hyperalignment based on resting fMRI
data. Predictions based on resting connectivity were equivalent for connectivity hyperalignment based
on task fMRI and resting fMRI. Prediction based on hyperaligned residual fine-grained connectivity and
on hyperaligned full fine-grained connectivity profiles (A and C) were essentially identical.

Hyperalignment transformations remix the time series for cortical vertices, which alters the mean of
correlations between the vertices of two regions - namely, the coarse-scale functional connectivity
between these regions (B). Analyses of hyperaligned fine-grained connectivity profiles all used the
coarse-grained connectivity profiles calculated on the same hyperaligned data for comparison. In
practice the effect of calculating coarse-grained connectivity profiles on task hyperaligned task fMRI,
hyperaligned resting fMRI, and MSM-aligned fMRI is small and does not affect the results of these
analyses (Supplementary Figure S2).

Predicting intelligence based on connectivity during single tasks

Supplementary Figure S3. Histograms of VAF by regional prediction models based on connectivity
calculated from fMRI during single tasks. For every single fMRI task (4.2 to 9.7 min) fine-scale
hyperaligned connectivity data produced better predictions of general intelligence than did coarse-
scale connectivity. The strongest predictions from single task fMRI were obtained from data during
performance of the working memory (WM), language, and social cognition tasks.

Null distribution of model performance based on permutation testing

A   <u>Permutation results based on task fMRI data</u>

B   <u>Permutation results based on resting fMRI data</u>

Supplementary Figure S4. Permutation testing. For each of the 2160 conditions (360 brain regions
× 3 connectivity profile types × 2 fMRI data types), we ran a permutation test by training and
evaluating prediction models 100 times based on shuffled subject labels. For 2148 out of 2160
conditions (99.4%), the actual R^2 was larger than all 100 permuted R^2's. For the remaining 12
conditions, the actual R^2 was close to 0 (all < 1.3%). In other words, for any model that had a R^2 of at
least 1.3%, it's also larger than the maximum R^2 of all 100 permutations (i.e., $p < 0.01$).

Distribution of model parameter choices based on nested cross-validation

Supplementary Figure S5. Distribution of regularization parameters α and number of PCs for
prediction models. For each kind of fMRI data (Panel A: task fMRI; Panel B: resting fMRI) and each
kind of connectivity profile (hyperaligned fine-grained, MSM-aligned fine-grained, coarse-grained),
we summarize the distribution of model parameters (the regularization parameter, ⍺, and the
number of PCs) across all cross-validation folds (411 families × 360 regions = 147,960). The
maximum number of PCs was usually 360 for coarse-grained connectivity profile and close to 876
for fine-grained connectivity profile (depending on training sample size). Models trained on fine-
grained connectivity profiles (left and middle columns) tend to use less regularization (smaller
alphas) and more PCs compared with models trained on coarse-grained connectivity profiles (right
column), especially models trained on hyperaligned fine-grained connectivity profiles. More PCs
used by the model suggests that there are more dimensions in the connectivity profiles that are

related to general intelligence, and less regularization suggests these PCs contain more signal
relative to noise.
686

Predicting alternative measures of intelligence

Supplementary Figure S6. Predicting alternative measures of intelligence based on connectivity profiles. Our prediction models and connectivity profiles can also be trained to predict other measures of intelligence, such as fluid intelligence measured with the Penn Matrices (Panel A, variable "PMAT24_A_CR" in the dataset) and general intelligence measured as the Cognitive Function Composite score of the NIH Toolbox (Panel B, "CogTotalComp_Unadj"). Similar to the results of the main paper (shown here as Panel C for comparisons), predictions based on fine-grained hyperaligned connectivity profiles account for approximately 2 times more variance in intelligence compared with coarse-grained connectivity profiles for task fMRI data, and 3 times more for resting fMRI data. The 4 columns on the left side are based on connectivity profiles computed from task fMRI data, and the 4 on the right from resting fMRI data. For each kind of data, we computed fine-grained connectivity profiles based on 3 different alignment methods (MSM, hyperalignment based on resting fMRI data, and hyperalignment based on task fMRI data),

701   which we colored as blue, orange, and red respectively. The orange and red colors denote the kind

702   of data used to derive hyperalignment transformations. In the results shown in this figure, they

703   may not be the same as data used to compute connectivity profiles.

Fluid intelligence as Penn Matrices score

General intelligence as NIH Toolbox Cognitive Function Composite score

Supplementary Figure S7. Predicting alternative intelligence measures based on regional
hyperaligned fine-grained task fMRI connectivity profiles. Regional connectivity profiles that were
more predictive of factor analysis-based general intelligence scores were more likely to be more
predictive of matrix reasoning-based fluid intelligence scores (top row, r = 0.92) and NIH Toolbox-
based general intelligence scores (bottom row, r = 0.96). This suggests our results were robust over
intelligence measure choices.

Alternative cross-validation schemes and the effect of training sample size

Task fMRI functional connectivity

Resting fMRI functional connectivity

Supplementary Figure S8. Comparison between cross-validation schemes. We replicated our
analysis using the 10-fold cross-validation scheme (repeated for 50 times), and compared model
performance based on 10-fold cross-validation (average across 50 repetitions) with that based on
leave-one-family-out cross-validation (Panels A and C). Each dot denotes a brain region, and error
bars denote the standard deviation of $R2$ across the 50 repetitions. All dots were close to the
identity line (gray dotted line), which indicates that model performance was highly similar for
leave-one-family-out cross-validation and 10-fold cross-validation. On average across all regions,
model performance based on leave-one-family-out cross-validation was slightly higher than that
based on 10-fold cross-validation, which was likely driven by the difference in training sample size
(i.e., approximately 90% versus 99.8% of the entire dataset). This was confirmed by additional
analysis showing further reduction of model performance based on smaller k values and
correspondingly smaller training sample sizes (Panels B and D; k = 2, 3, or 5 for k-fold cross-
validation; training data was 50%, 66.7%, and 80% of the entire dataset respectively).

Task fMRI functional connectivity

Resting fMRI functional connectivity

Supplementary Figure S9. Overestimation of model performance due to lack of data independence. We trained new prediction models based on the k-fold cross-validation scheme, but without controlling for family structure. That is, for each testing participant, other members from the same family might be in training data. Compared with the k-fold results that controlled for family structure (Supplementary Figure S8; dashed lines in this Figure), results without controlling for family structure consistently overestimate model performance (average R^2 difference across regions: 0.9% to 2.1%; solid lines in this Figure). This demonstrates the necessity of ensuring data independence between training and testing data to avoid biased model evaluations (see Varoquaux et al., 2017 for a similar issue with leave-one-trial-out). Specifically, training and testing data should not have members from the same family.

The effect of hyperparameter choices on model performance

Supplementary Figure S10. The effect of hyperparameter choices on prediction performance.
Besides using fine-tuned hyperparameters based on nested cross-validation (rightmost columns in
gray), we trained prediction models based on another 8 sets of hyperparameter choices. These 8
sets of hyperparameters are combinations of 4 levels of dimensionality reduction (80 PCs, 160 PCs,
320 PCs, or all PCs) and 2 levels of regularization ($\alpha = 0.1$ or $\alpha = 10^{-20}$). These hyperparameter levels
are the levels most frequently chosen based on nested cross-validation (Supplementary Figure S5).
The histograms denote R2 distribution across brain regions, and horizontal bars are the average R2
across regions. For prediction models based on coarse-grained connectivity profiles, regularization
is critical for prediction model performance, and with insufficient regularization models overfit
dramatically with more PCs. When the regularization is large enough, the model performance
slightly increases with higher number of PCs. For prediction models based on fine-grained
connectivity profiles, model performance is hardly affected by regularization level, and
consistently increases with higher number of PCs. This suggests PCs based on fine-grained
connectivity profiles contain more information related to individual differences in intelligence and
less noise. Note that even with only 80 PCs, prediction models based on hyperaligned fine-grained

connectivity profiles still account for approximately two times more variance than those based on
coarse-grained connectivity profiles.

Alternative definition of cortical networks

Supplementary Figure S11. Proportion of vertices of the 30 most predictive regions in 12 cortical
networks defined in Ji et al. (2019). (A) The 30 regions that are most predictive of general
intelligence based on hyperaligned fine-grained task fMRI connectivity are in the default (34.0% of
vertices in the 30 regions), frontoparietal (33.0%), cingulo-opercular (20.2%), dorsal attention
(5.7%), and visual 2 (6.7%) networks. (B) The 30 regions that are most predictive of general
intelligence based on hyperaligned fine-grained resting fMRI connectivity are in the default
(39.3%), frontoparietal (22.5%), cingulo-opercular (14.4%), dorsal attention (13.9%), visual 2
(4.9%), language (2.8%) and visual 1 (1.7%) networks. The 12 cortical networks are defined based
on Ji et al. (2019). Note that different cortical network parcellations are in agreement with each
other in general, and the proportion of cortical vertices in these 12 networks are similar to the
proportion in the 7 cortical systems based on Yeo et al. (2011). Most of the vertices are in default,
frontoparietal, and dorsal attention networks based on both Yeo et al. (2011) and Ji et al. (2019);
some regions in the ventral attention network based on Yeo et al. (2011) are labeled as cingulo-
opercular in Ji et al. (2019).

Assessing the effects of head motion

The level of in-scanner head motion (usually measured as framewise displacement, or FD for
short) is correlated with many subject measures, and participants who move more in the
scanner are more likely to have lower cognitive test scores (Siegel et al., 2017). Therefore,
when the connectivity pattern is affected by motion-related artifacts, it is possible for prediction
models to take advantage of these spurious patterns and predict these subject measures to
some extent. For the dataset used in this study, the correlation between g and FD is $r(874) = -$
0.29, $p < 10^{-18}$, which means a perfect head motion predictor can account for 8.6% of variance
in general intelligence (Supplementary Figure S12 A). To assess the influence of head motion
on our prediction models, we performed two additional analyses.

In the first analysis, we created a low motion sub-sample of the dataset, and evaluated
prediction performance based on this sub-sample. This sub-sample comprises participants
whose average FD is less than 0.15 mm across all fMRI runs, and has a sample size of 437.
Because sample size has a great influence on prediction performance (Supplementary Figure
S8), we created 10 control sub-samples. These control sub-samples have the same sample
size and almost identical mean and standard deviation of g as the low-motion sub-sample
(Supplementary Figure S12, Panel D), but have the full spectrum of head motion (Panel C).
Therefore, if the prediction models take advantage of the correlation between g and head
motion to predict g, we expect the model performance based on the control sub-samples to
outperform the low motion sub-sample.

Across all 3 kinds of connectivity profiles (coarse-grained, MSM-aligned fine-grained,
hyperaligned fine-grained) and 2 kinds of fMRI data (task fMRI, resting fMRI), we observed no
difference in prediction performance between models based on the low-motion sub-sample and
models based on control sub-samples (all p > 0.11; Supplementary Figure S12 Panel E). This
suggests that head motion has little influence on the performance of our prediction models.

Supplementary Figure S12. Prediction performance based on a low head motion sub-sample.
General intelligence has a moderate correlation with head motion (Panel A), and a "motion
detector" can predict general intelligence to some extent. To assess the effect of head motion
variation on prediction performance, we trained another set of models based on a sub-sample of
participants with minimal head motion (FD < 0.15 mm, n = 437, Panel B), and another 10 sets of
models based on control sub-samples (see Panel C for an example control sub-sample). The
control sub-samples had similar general intelligence variation but larger head motion variation

806   compared with the low motion sub-sample (Panel D). Prediction performance was similar between
807   the low motion sub-sample and the control sub-samples (Panel E), suggesting larger variation in
808   head motion level (while keeping sample size constant) has little effect on the prediction
809   performance for general intelligence.
810
Note that in the low motion sub-sample, small variation in head motion still exists
(Supplementary Figure S12, Panel D), and is slightly correlated with g (r = -0.14). Therefore, it
is possible for a prediction model to take advantage of motion-related connectivity patterns, and
account for up to 1.9% of variance in g if it can detect motion from functional connectivity
perfectly. To further assess the effect of head motion, we performed a second analysis in a
more strict way.

In the second analysis, we regressed out FD from functional connectivity profiles, and used the
residual profiles to build our prediction models. This allows us to completely remove the
variance in functional connectivity that covariates with head motion. Traditionally certain
preprocessing pipelines are used to mitigate the effects of head motion on functional
connectivity and reduce the prediction performance overestimation caused by head motion
(Siegel et al., 2017; Ciric et al., 2017, 2018). However, it is unclear which preprocessing
pipeline is most effective in removing motion-related artifacts in fine-grained connectivity, and
it's practically challenging to compute fine-grained functional connectivity using multiple
preprocessing pipelines. Therefore, we chose to use regression to remove covariation between
functional connectivity and head motion. Note that regression is an aggressive approach and
will also remove variance in "true" functional connectivity that covariates with FD. As a result,
the maximal possible R2 is no longer 100% but rather 91.4%, because the 8.6% of variance in g
that covaries with FD can never be accounted for by these residual profiles.

To account for the effect of the new R2 ceiling, we trained another 100 sets of prediction
models, where each set was based on functional connectivity residuals after regressing out a
random variable that had the same level of correlation with g (i.e., r = 0.29), and therefore had
the same R2 ceiling. For simplicity, we will refer to these models as control models and the
models based on regressing out FD as FD-residual models. With these models, it is possible to
separate the effect of R2 ceiling by comparing original models and control models, and the
effect specific to head motion by comparing control models with FD-residual models.

Compared with the original models, control models had lower R2, and the difference was 2.8%,
3.1%, and 4.2% for coarse-grained, MSM-aligned fine-grained, and hyperaligned fine-grained
connectivity profiles respectively based on task fMRI data; the difference was 1.9%, 2.5%, 3.9%
respectively based on resting fMRI data. This demonstrates that regressing out variables
correlating with g from functional connectivity profiles will reduce model performance in general.
Note that the R2 difference was larger for connectivity profiles that are more predictive of g
(e.g., hyperaligned fine-grained connectivity profiles for both task and resting fMRI data),
suggesting that high-performance models are more influenced by the R2 ceiling, probably
because their performances are closer to the ceiling.

FD-residual models had lower R^2 compared with these control models, and the
difference was 2.5%, 2.8%, and 2.7% respectively based on task fMRI data, and 1.3%, 2.0%,
1.1% respectively based on resting fMRI data (Supplementary Figure S13). These results
suggest that head motion has a small (1.1% to 2.8%) but statistically significant effect on
predicting g based on functional connectivity. Based on resting fMRI data, the effect of head
motion was smaller for fine-grained connectivity profiles that are hyperaligned compared with
those MSM-aligned ($\Delta R^2 = 0.9\%$, $p = 0.01$). This suggests using functional connectivity based
on hyperaligned data may reduce the influence of head motion on prediction models.
854

Task fMRI functional connectivity

Resting fMRI functional connectivity

Supplementary Figure S13. Regressing out head motion from functional connectivity. We
regressed out head motion (measured as framewise displacement) from functional connectivity
profiles and built prediction models based on the residual connectivity profiles, and compared their
performance with 100 sets of control models. Each dot is a brain region, and error bars denote the
standard deviation across 100 control model sets. For each set of control models, a random
variable that has the same level of correlation with g was regressed out from functional
connectivity profiles instead of head motion to control for the effect of lower R^2 ceiling caused by
regression. Compared with the control models, models based on regressing out head motion had
slightly lower performance (range: 1.1% to 2.8%), as demonstrated by that the dots are slightly

below the diagonal in general. This difference suggests that the shared variance between

functional connectivity and head motion may cause a slight overestimation of model performance.

However, the effect is small and cannot explain the difference between models based on different

types of connectivity profiles.

869   **References**

870   Addis DR, Wong AT, Schacter DL. 2007. Remembering the past and imagining the future:
871   common and distinct neural substrates during event construction and elaboration.
872   *Neuropsychologia* **45**:1363–1377. doi:10.1016/j.neuropsychologia.2006.10.016
873   Andrews-Hanna JR, Reidler JS, Sepulcre J, Poulin R, Buckner RL. 2010. Functional-anatomic
874   fractionation of the brain's default network. *Neuron* **65**:550–562.
875   doi:10.1016/j.neuron.2010.02.005
876   Andrews-Hanna JR, Smallwood J, Spreng RN. 2014. The default network and self-generated
877   thought: component processes, dynamic control, and clinical relevance. *Ann N Y Acad*
878   *Sci* **1316**:29–52. doi:10.1111/nyas.12360
879   Barch DM, Burgess GC, Harms MP, Petersen SE, Schlaggar BL, Corbetta M, Glasser MF,
880   Curtiss S, Dixit S, Feldt C, Nolan D, Bryant E, Hartley T, Footer O, Bjork JM, Poldrack R,
881   Smith S, Johansen-Berg H, Snyder AZ, Van Essen DC, WU-Minn HCP Consortium.
882   2013. Function in the human connectome: task-fMRI and individual differences in
883   behavior. *Neuroimage* **80**:169–189. doi:10.1016/j.neuroimage.2013.05.033
884   Behzadi Y, Restom K, Liau J, Liu TT. 2007. A Component Based Noise Correction Method
885   (CompCor) for BOLD and Perfusion Based fMRI. *Neuroimage* **37**:90–101.
886   doi:10.1016/j.neuroimage.2007.04.042
887   Bilker WB, Hansen JA, Brensinger CM, Richard J, Gur RE, Gur RC. 2012. Development of
888   abbreviated nine-item forms of the Raven's standard progressive matrices test.
889   *Assessment* **19**:354–369. doi:10.1177/1073191112446655
890   Buckner RL, Andrews-Hanna JR, Schacter DL. 2008. The brain's default network: anatomy,
891   function, and relevance to disease. *Ann N Y Acad Sci* **1124**:1–38.
892   doi:10.1196/annals.1440.011
893   Ciric, R., Rosen, A. F. G., Erus, G., Cieslak, M., Adebimpe, A., Cook, P. A., Bassett, D. S.,
894   Davatzikos, C., Wolf, D. H., & Satterthwaite, T. D. (2018). Mitigating head motion artifact
895   in functional connectivity MRI. *Nature Protocols, 13*(12), 2801–2826.
896   https://doi.org/10.1038/s41596-018-0065-y
897   Ciric, R., Wolf, D. H., Power, J. D., Roalf, D. R., Baum, G. L., Ruparel, K., Shinohara, R. T.,
898   Elliott, M. A., Eickhoff, S. B., Davatzikos, C., Gur, R. C., Gur, R. E., Bassett, D. S., &
899   Satterthwaite, T. D. (2017). Benchmarking of participant-level confound regression
900   strategies for the control of motion artifact in studies of functional connectivity.
901   *NeuroImage, 154*, 174–187. https://doi.org/10.1016/j.neuroimage.2017.03.020
902   Connolly AC, Sha L, Guntupalli JS, Oosterhof N, Halchenko YO, Nastase SA, Castello MV di O,
903   Abdi H, Jobst BC, Gobbini MI, Haxby JV. 2016. How the Human Brain Represents
904   Perceived Dangerousness or "Predacity" of Animals. *J Neurosci* **36**:5373–5384.
905   doi:10.1523/JNEUROSCI.3395-15.2016
906   Cox SR, Ritchie SJ, Fawns-Ritchie C, Tucker-Drob EM, Deary IJ. 2019. Structural brain imaging
907   correlates of general intelligence in UK Biobank. *Intelligence* **76**:101376.
908   doi:10.1016/j.intell.2019.101376
909   Dice LR. 1945. Measures of the Amount of Ecologic Association Between Species. *Ecology*
910   **26**:297–302. doi:10.2307/1932409
911   Dixon ML, Vega ADL, Mills C, Andrews-Hanna J, Spreng RN, Cole MW, Christoff K. 2018.
912   Heterogeneity within the frontoparietal control network and its relationship to the default
913   and dorsal attention networks. *PNAS* **115**:E1598–E1607. doi:10.1073/pnas.1715766115
914   Dubois J, Galdi P, Paul LK, Adolphs R. 2018. A distributed brain network predicts general
915   intelligence from resting-state human neuroimaging data. *Philosophical Transactions of*
916   *the Royal Society B: Biological Sciences* **373**:20170284. doi:10.1098/rstb.2017.0284
Eickhoff, S. B., Constable, R. T., & Yeo, B. T. T. (2018). Topographic organization of the

cerebral cortex and brain cartography. *NeuroImage, 170*, 332–347.
https://doi.org/10.1016/j.neuroimage.2017.02.018
Feilong M, Nastase SA, Guntupalli JS, Haxby JV. 2018. Reliable individual differences in fine-
grained cortical functional architecture. *Neuroimage* **183**:375–386.
doi:10.1016/j.neuroimage.2018.08.029
Finn ES, Shen X, Scheinost D, Rosenberg MD, Huang J, Chun MM, Papademetris X, Constable
RT. 2015. Functional connectome fingerprinting: identifying individuals using patterns of
brain connectivity. *Nat Neurosci* **18**:1664–1671. doi:10.1038/nn.4135
Frith CD, Frith U. 1999. Interacting minds--a biological basis. *Science* **286**:1692–1695.
doi:10.1126/science.286.5445.1692
Glasser MF, Coalson TS, Robinson EC, Hacker CD, Harwell J, Yacoub E, Ugurbil K, Andersson
J, Beckmann CF, Jenkinson M, Smith SM, Van Essen DC. 2016. A multi-modal
parcellation of human cerebral cortex. *Nature* **536**:171–178. doi:10.1038/nature18933
Glasser MF, Sotiropoulos SN, Wilson JA, Coalson TS, Fischl B, Andersson JL, Xu J, Jbabdi S,
Webster M, Polimeni JR, Van Essen DC, Jenkinson M, WU-Minn HCP Consortium.
2013. The minimal preprocessing pipelines for the Human Connectome Project.
Neuroimage **80**:105–124. doi:10.1016/j.neuroimage.2013.04.127
Gobbini MI, Haxby JV. 2007. Neural systems for recognition of familiar faces. *Neuropsychologia*
45:32–41. doi:10.1016/j.neuropsychologia.2006.04.015
Gobbini MI, Koralek AC, Bryan RE, Montgomery KJ, Haxby JV. 2007. Two takes on the social
brain: a comparison of theory of mind tasks. *J Cogn Neurosci* **19**:1803–1814.
doi:10.1162/jocn.2007.19.11.1803
Golland Y, Bentin S, Gelbard H, Benjamini Y, Heller R, Nir Y, Hasson U, Malach R. 2007.
Extrinsic and intrinsic systems in the posterior cortex of the human brain revealed during
natural sensory stimulation. *Cereb Cortex* **17**:766–777. doi:10.1093/cercor/bhk030
Greene AS, Gao S, Scheinost D, Constable RT. 2018. Task-induced brain state manipulation
improves prediction of individual traits. *Nature Communications* **9**:1–13.
doi:10.1038/s41467-018-04920-3
Guntupalli JS, Feilong M, Haxby JV. 2018. A computational model of shared fine-scale structure
in the human connectome. *PLOS Computational Biology* **14**:e1006120.
doi:10.1371/journal.pcbi.1006120
Guntupalli JS, Hanke M, Halchenko YO, Connolly AC, Ramadge PJ, Haxby JV. 2016. A Model
of Representational Spaces in Human Cortex. *Cereb Cortex* **26**:2919–2934.
doi:10.1093/cercor/bhw068
Guntupalli JS, Wheeler KG, Gobbini MI. 2017. Disentangling the Representation of Identity from
Head View Along the Human Face Processing Pathway. *Cereb Cortex* **27**:46–53.
doi:10.1093/cercor/bhw344
Gur RC, Richard J, Hughett P, Calkins ME, Macy L, Bilker WB, Brensinger C, Gur RE. 2010. A
cognitive neuroscience-based computerized battery for efficient measurement of
individual differences: standardization and initial construct validation. *J Neurosci*
Methods **187**:254–262. doi:10.1016/j.jneumeth.2009.11.017
Hanke M, Halchenko YO, Sederberg PB, Hanson SJ, Haxby JV, Pollmann S. 2009. PyMVPA: A
python toolbox for multivariate pattern analysis of fMRI data. *Neuroinformatics* **7**:37–53.
doi:10.1007/s12021-008-9041-y
Haxby JV, Connolly AC, Guntupalli JS. 2014. Decoding neural representational spaces using
multivariate pattern analysis. *Annu Rev Neurosci* **37**:435–456. doi:10.1146/annurev-
neuro-062012-170325
Haxby JV, Gobbini MI, Furey ML, Ishai A, Schouten JL, Pietrini P. 2001. Distributed and
overlapping representations of faces and objects in ventral temporal cortex. *Science*
293:2425–2430. doi:10.1126/science.1063736
Haxby JV, Guntupalli JS, Connolly AC, Halchenko YO, Conroy BR, Gobbini MI, Hanke M,

Ramadge PJ. 2011. A common, high-dimensional model of the representational space in
human ventral temporal cortex. *Neuron* **72**:404–416. doi:10.1016/j.neuron.2011.08.026
Haxby JV, Guntupalli JS, Nastase SA, Feilong M. 2020. Hyperalignment: Modeling shared
information encoded in idiosyncratic cortical topographies. *eLife* **9**:e56601.
doi:10.7554/eLife.56601
Ji, J. L., Spronk, M., Kulkarni, K., Repovš, G., Anticevic, A., & Cole, M. W. (2019). Mapping the
human brain's cortical-subcortical functional network organization. *NeuroImage, 185*,
35–57. https://doi.org/10.1016/j.neuroimage.2018.10.006
Jiahui, G., Feilong, M., Visconti di Oleggio Castello, M., Guntupalli, J. S., Chauhan, V., Haxby,
J. V., & Gobbini, M. I. (2019). Predicting individual face-selective topography using
naturalistic stimuli. *NeuroImage*, 116458.
https://doi.org/10.1016/j.neuroimage.2019.116458
Jiang R, Zuo N, Ford JM, Qi S, Zhi D, Zhuo C, Xu Y, Fu Z, Bustillo J, Turner JA, Calhoun VD,
Sui J. 2020. Task-induced brain connectivity promotes the detection of individual
differences in brain-behavior relationships. *NeuroImage* **207**:116370.
doi:10.1016/j.neuroimage.2019.116370
Johnson W, Bouchard TJ, Krueger RF, McGue M, Gottesman II. 2004. Just one g: Consistent
results from three test batteries. *Intelligence* **32**:95–107. doi:10.1016/S0160-
2896(03)00062-X
Johnson W, Nijenhuis J te, Bouchard TJ. 2008. Still just 1 g: Consistent results from five test
batteries. *Intelligence* **36**:81–95. doi:10.1016/j.intell.2007.06.001
Kong R, Li J, Orban C, Sabuncu MR, Liu H, Schaefer A, Sun N, Zuo X-N, Holmes AJ, Eickhoff
SB, Yeo BTT. 2019. Spatial Topography of Individual-Specific Cortical Networks
Predicts Human Cognition, Personality, and Emotion. *Cereb Cortex* **29**:2533–2551.
doi:10.1093/cercor/bhy123
Kong, R., Yang, Q., Gordon, E., Xue, A., Yan, X., Orban, C., Zuo, X.-N., Spreng, N., Ge, T.,
Holmes, A., Eickhoff, S., & Yeo, B. T. T. (2021). Individual-Specific Areal-Level
Parcellations Improve Functional Connectivity Prediction of Behavior. *BioRxiv*,
2021.01.16.426943. https://doi.org/10.1101/2021.01.16.426943
Kriegeskorte N, Mur M, Bandettini P. 2008. Representational similarity analysis - connecting the
branches of systems neuroscience. *Front Syst Neurosci* **2**:4.
doi:10.3389/neuro.06.004.2008
Luders E, Narr KL, Bilder RM, Thompson PM, Szeszko PR, Hamilton L, Toga AW. 2007.
Positive correlations between corpus callosum thickness and intelligence. *Neuroimage*
37:1457–1464. doi:10.1016/j.neuroimage.2007.06.028
Nastase SA, Liu Y-F, Hillman H, Norman KA, Hasson U. 2020. Leveraging shared connectivity
to aggregate heterogeneous datasets into a common response space. *Neuroimage*
116865. doi:10.1016/j.neuroimage.2020.116865
Park SH, Russ BE, McMahon DBT, Koyano KW, Berman RA, Leopold DA. 2017. Functional
Subpopulations of Neurons in a Macaque Face Patch Revealed by Single-Unit fMRI
Mapping. *Neuron* **95**:971-981.e5. doi:10.1016/j.neuron.2017.07.014
Plomin R, Deary IJ. 2015. Genetics and intelligence differences: five special findings. *Molecular
Psychiatry* **20**:98–108. doi:10.1038/mp.2014.105
Raichle ME. 2006. The Brain's Dark Energy. *Science* **314**:1249–1250. doi:10.1126/science.
1134405
Raichle ME, MacLeod AM, Snyder AZ, Powers WJ, Gusnard DA, Shulman GL. 2001. A default
mode of brain function. *Proc Natl Acad Sci U S A* **98**:676–682.
Robinson EC, Jbabdi S, Glasser MF, Andersson J, Burgess GC, Harms MP, Smith SM, Van
Essen DC, Jenkinson M. 2014. MSM: a new flexible framework for Multimodal Surface
Matching. *Neuroimage* **100**:414–426. doi:10.1016/j.neuroimage.2014.05.069
Saxe R, Kanwisher N. 2003. People thinking about thinking people. The role of the temporo-

parietal junction in "theory of mind." *Neuroimage* **19**:1835–1842. doi:10.1016/s1053-
8119(03)00230-1
Schmitt JE, Neale MC, Clasen LS, Liu S, Seidlitz J, Pritikin JN, Chu A, Wallace GL, Lee NR,
Giedd JN, Raznahan A. 2019. A Comprehensive Quantitative Genetic Analysis of
Cerebral Surface Area in Youth. *J Neurosci* **39**:3028–3040.
doi:10.1523/JNEUROSCI.2248-18.2019
Shen X, Finn ES, Scheinost D, Rosenberg MD, Chun MM, Papademetris X, Constable RT.
2017. Using connectome-based predictive modeling to predict individual behavior from
brain connectivity. *Nat Protoc* **12**:506–518. doi:10.1038/nprot.2016.178
Siegel, J. S., Mitra, A., Laumann, T. O., Seitzman, B. A., Raichle, M., Corbetta, M., & Snyder, A.
Z. (2017). Data quality influences observed links between functional connectivity and
behavior. *Cerebral Cortex, 27*(9), 4492–4502. https://doi.org/10.1093/cercor/bhw253
Spearman C. 1904. "General Intelligence," Objectively Determined and Measured. *The*
American Journal of Psychology **15**:201–292. doi:10.2307/1412107
Uğurbil K, Xu J, Auerbach EJ, Moeller S, Vu A, Duarte-Carvajalino JM, Lenglet C, Wu X,
Schmitter S, Van de Moortele PF, Strupp J, Sapiro G, De Martino F, Wang D, Harel N,
Garwood M, Chen L, Feinberg DA, Smith SM, Miller KL, Sotiropoulos SN, Jbabdi S,
Andersson JL, Behrens TE, Glasser MF, Van Essen D, Yacoub E. 2013. Pushing spatial
and temporal resolution for functional and diffusion MRI in the Human Connectome
Project. *Neuroimage* **80**:80–104. doi:10.1016/j.neuroimage.2013.05.012
Van Essen DC, Smith SM, Barch DM, Behrens TEJ, Yacoub E, Ugurbil K, WU-Minn HCP
Consortium. 2013. The WU-Minn Human Connectome Project: an overview.
Neuroimage **80**:62–79. doi:10.1016/j.neuroimage.2013.05.041
Varoquaux, G., Raamana, P. R., Engemann, D. A., Hoyos-Idrobo, A., Schwartz, Y., & Thirion,
B. (2017). Assessing and tuning brain decoders: Cross-validation, caveats, and
guidelines. *NeuroImage, 145*, 166–179.
https://doi.org/10.1016/j.neuroimage.2016.10.038
Winkler AM, Webster MA, Vidaurre D, Nichols TE, Smith SM. 2015. Multi-level block
permutation. *NeuroImage* **123**:253–268. doi:10.1016/j.neuroimage.2015.05.092
Yeo BTT, Krienen FM, Sepulcre J, Sabuncu MR, Lashkari D, Hollinshead M, Roffman JL,
Smoller JW, Zöllei L, Polimeni JR, Fischl B, Liu H, Buckner RL. 2011. The organization
of the human cerebral cortex estimated by intrinsic functional connectivity. *J*
Neurophysiol **106**:1125–1165. doi:10.1152/jn.00338.2011