The neural basis of intelligence in fine-grained cortical topographies

Ma Feilong[1], J. Swaroop Guntupalli[2], James V. Haxby[1]*

[1]Center for Cognitive Neuroscience, Dartmouth, Hanover NH

[2]Vicarious AI, Union City CA

*Address correspondence to JVH (james.v.haxby@dartmouth.edu)

Abstract

Intelligent thought is the product of efficient neural information processing, which is

embedded in fine-grained, topographically-organized population responses and

supported by fine-grained patterns of connectivity among cortical fields. Previous work

on the neural basis of intelligence, however, has focused on coarse-grained features of

brain anatomy and function, because cortical topographies are highly idiosyncratic at a

finer scale, obscuring individual differences in fine-grained connectivity patterns. We

used a computational algorithm, hyperalignment, to resolve these topographic

idiosyncrasies, and found that predictions of general intelligence based on fine-grained

(vertex-by-vertex) connectivity patterns were markedly stronger than predictions based

on coarse-grained (region-by-region) patterns. Intelligence was best predicted by

fine-grained connectivity in the default and frontoparietal cortical systems, both of

which are associated with self-generated thought. Previous work overlooked

fine-grained architecture because existing methods couldn't resolve idiosyncratic

topographies, preventing investigation where the keys to the neural basis of

intelligence are more likely to be found.

Introduction

Intelligent thought is the product of efficient neural information processing, but the

neural architecture that makes some brains capable of quick wit and deep insight, while

others struggle with simple problems, remains an open question. Previous work on the

neural basis of intelligence has focused on coarse-grained features of brain anatomy

and function, such as the size and shape of the brain and its parts (e.g., Cox et al.,

2019; Luders et al., 2007; Schmitt et al., 2019) or the size and strength of connections

between large cortical fields (e.g., Dubois et al., 2018; Finn et al., 2015; Kong et al.,

2019; Shen et al., 2017). Neural information processing, however, is embedded in

fine-grained, topographically-organized population responses (Haxby et al., 2014,

2001). Functional connectivity varies vertex-by-vertex (Guntupalli et al., 2018), and

even neuron-by-neuron (Park et al., 2017), to support such information processing.

Therefore, fine-grained functional connectivity depicts in detail how information is

exchanged and processed between cortical regions, in contrast to coarse-grained

region-by-region connectivity, which depicts the overall synchronization between

regions. We investigated whether individual differences in general intelligence are a

function of information embedded in fine-grained cortical architecture.

Fine-grained patterns of activity and connectivity can be studied with functional

magnetic resonance imaging (fMRI), but the topographies of these patterns are

idiosyncratic, impeding study of their role in the neural basis of individual differences in

cognitive ability. We used hyperalignment (Feilong et al., 2018; Guntupalli et al., 2018,

2016; Haxby et al., 2020, 2011) to resolve the interindividual variation of fine-grained

topographies of functional connectivity. Hyperalignment remixes the connectivity profiles of loci in a cortical field into a high-dimensional common space to maximize the similarity across brains in fine-grained, vertex-by-vertex patterns. Individual variation in the residuals around common fine-grained patterns are more reliable than individual variations around common coarse-grained patterns, after resolving idiosyncratic topographies with hyperalignment (Feilong et al., 2018). We found that predictions of general intelligence based on fine-grained (vertex-by-vertex) patterns of connectivity were markedly stronger than predictions based on coarse-grained (region-by-region) patterns. Intelligence was best predicted by fine-grained connectivity in the default and frontoparietal cortical systems, both of which are associated with self-generated thought. These results demonstrate that the neural mechanisms of intelligence reside more in fine-grained interactions of cortical regions than in synchronization of oscillations in large cortical fields..

Results

We used data from 876 participants of the Human Connectome Project (HCP) (Van Essen et al., 2013). Each participant had about 47 minutes of task fMRI data, collected during the performance of seven tasks, one hour of resting-state fMRI data, and scores on 10 cognitive tests. We used connectivity hyperalignment (Guntupalli et al., 2018) to factor out idiosyncrasies in fine-grained topographies and model information encoded in local functional connectivity patterns that is shared across brains. We hyperaligned both the HCP task fMRI and resting fMRI datasets. Connectivity hyperalignment projects idiosyncratic cortical topographies for individual brains into a common model

connectivity space in which the patterns of connectivity across vertices in a cortical field with connectivity targets elsewhere in the brain are maximally similar across brains. We measured general intelligence (Spearman, 1904) as a general factor based on 10 cognitive test scores included in the HCP database (Dubois et al., 2018).

For each of 360 cortical regions, from a parcellation tailored to the HCP dataset (Glasser et al., 2016), we computed fine-grained task fMRI and resting fMRI connectivity profiles for each individual (Figure 1). The connectivity profile for each cortical vertex differs from profiles for other vertices in the region with a granularity in the common model space that is equivalent to spatial variation across cortical loci within individual brains (Guntupalli et al., 2018). We factored out the effect of coarse-grained connectivity by subtracting the mean connectivities between pairs of regions (coarse-grained connectivity profiles; Figure 1, middle row) from the vertex-wise connectivities (full fine-grained connectivity profiles; Figure 1, top row), to examine the predictive power of fine-grained connectivity unconfounded with prediction based on coarse-grained connectivity. We calculated coarse-grained connectivity on the same hyperaligned data used for calculation of fine-grained connectivity (see Supplemental Figure S2).

Figure 1. Schematic illustration of coarse- and fine-grained functional connectivity.

Each brain region (e.g. area 150 shown here) comprises multiple cortical vertices

(on average 165). Correlations between their time series and time series for all

59,412 vertices in the whole cortex form that region's full fine-grained connectivity

matrix (top row). The fine-grained connectivity profiles for 360 brain regions each

have approximately 10 million such correlations. The coarse-grained connectivity

profile for the same region (middle row) comprises the average functional

connectivity between all of the vertices in that region and all of the vertices in each

of the 360 brain regions. Thus, the coarse-grained connectivity profiles for 360

brain regions each have 360 mean correlations. The residual fine-grained

connectivity profile (bottom row) for each region is obtained by subtracting the mean correlation for a pair of regions (e.g. region 1 and region 150) from the full fine-grained connectivity profile for that pair and is, thus, unconfounded with coarse-grained functional connectivities. We refer to these unconfounded profiles as fine-grained connectivity profiles for short.

We built prediction models based on regional connectivity profiles using cross-validated principal component regression with ridge regularization. We divided the data into k test participants from one family (k = 1 to 6) and the remaining 876-k training set participants. Thus, each test participant's intelligence was predicted using regression weights derived from other participants' data.   We assessed the performance of these models using a coefficient of determination (R^2), which denotes the percent of intelligence score variance accounted for (VAF) by the prediction models. We made separate prediction models for hyperaligned fine-scale task and resting connectivity, for coarse-grained task and resting connectivity, and for non-hyperaligned fine-scale task and resting connectivity.

Figure 2. Schematic illustration of analysis pipeline. We used a leave-one-family-out cross-validation scheme. For each data fold, we built a prediction model based on the training subjects' data (yellow color) to predict general intelligence (g) from the connectivity profile of a cortical region, and applied the model to testing subjects' connectivity profiles to predict their general intelligence scores (Steps 1 and 2). We aggregated predicted and actually measured g across all cross-validation folds to assess model performance with cross-validated R^2 (Step 3), and repeated this procedure for other cortical regions' connectivity profiles (Step 4). After the entire pipeline, we obtained a R^2 for each of the 360 cortical regions, which stands for the amount of variance in g that can be accounted for by the region's connectivity profile. We repeated the pipeline for different kinds of connectivity profiles (spatial granularity, dataset, and alignment method) and compared them systematically (Figures 3–5), and these repetitions only differ in the connectivity profiles fed into the pipeline.

Hyperaligned fine-grained versus coarse-grained connectivity profiles

Regional hyperaligned fine-grained task and resting connectivity profiles were highly predictive of general intelligence (Figures 3A and 4A) and accounted for twice as much variance in general intelligence as compared to coarse-grained connectivity profiles (Figures 3B, 3C, 4B, and 4C).

Prediction of intelligence based on task fMRI connectivity profiles

On average across all cortical regions, prediction models based on hyperaligned fine-grained task fMRI connectivity accounted for 27.3% of variance in general intelligence (min: 11.2%, max: 38.9%). In other words, the correlation between predicted and measured intelligence scores ranged from r = 0.34 in the least predictive brain region to r = 0.62 in the most predictive brain region. By contrast, prediction models based on coarse-grained task fMRI connectivity (Figure 3B) accounted on average for only 14.5% of variance (min: 0.0%, max: 25.8%), which is only 53.2% (95% CI: [47.8%, 57.4%]) of VAF by hyperaligned fine-grained connectivity overall. VAF by hyperaligned fine-grained task connectivity was higher than VAF by coarse-grained connectivity in all 360 ROIs (Figure 3C). These results suggest that the information encoded in fine-grained interaction patterns between brain regions affords markedly stronger predictors of intelligence than information in coarse-grained patterns.

The 30 most predictive regions (Figure 3D and 3E; 33.8% to 38.9% VAF) were in bilateral inferior parietal cortex (15 regions), bilateral medial and superior prefrontal cortex (11 regions), bilateral medial parietal (2 regions), and bilateral posterior lateral temporal cortex (2 regions). The cortices in these regions were predominantly part of

the default mode and frontoparietal systems (38.9% and 34.5% of cortical vertices, respectively) with small portions in the ventral and dorsal attention systems (11.3% and 10.6%, respectively; Figure 3D and 3E) (Yeo et al., 2011).

Figure 3. Predicting general intelligence based on regional task fMRI connectivity profiles. Prediction based on hyperaligned fine-grained (A) and coarse-grained (B) connectivity profiles, assessed by the variance in general intelligence accounted for. The scatter plot (C) shows that predictions based on hyperaligned fine-grained profiles accounted for more variance in all 360 ROIs. Prediction models based on each region's fine-grained hyperaligned task functional connectivity profile accounted for 1.88 (95% CI: [1.74, 2.09]) times more variance in general intelligence on average than did models based on coarse-grained functional connectivity profiles. Each circle is a cortical region, and the color of each circle corresponds to the cortical system where it resides, using the same color scheme as in (E). Dashed lines denote average difference in R^2 (gray), or identical R^2 (black). (D) The thirty regions whose hyperaligned fine-grained connectivity best predicted general intelligence are colored as in panels A and B. The default mode network is outlined in red, and the frontoparietal network is outlined in orange (Yeo et al., 2011). (E) Proportion of vertices in these regions that are in seven cortical systems delineated with resting state fMRI functional connectivity (Yeo et al., 2011).

Prediction of intelligence based on resting fMRI connectivity profiles

Prediction of general intelligence based on resting fMRI connectivity showed a similar advantage for hyperaligned fine-grained profiles, relative to coarse-grained profiles (Figure 4), but performance was substantially lower than for task fMRI connectivity, consistent with previous reports (Greene et al., 2018; Jiang et al., 2020). Models based on hyperaligned fine-grained resting fMRI connectivity accounted on

average for 19.7% of variance (Figure 4A; min: 2.9%, max: 31.2%), whereas models

based on coarse-grained connectivity accounted on average for 7.7% of variance

(Figure 4B; min: -0.4%, max: 17.4%), which is only 39.0% [CI: 32.4%, 43.9%] of VAF by

hyperaligned fine-grained resting connectivity. Hyperaligned fine-grained resting fMRI

connectivity, as compared to coarse-grained resting fMRI connectivity, accounted for

more variance in 359 of 360 ROIs (Figure 4C). The vertices of 30 regions whose resting

hyperaligned fine-grained connectivity was most predictive of general intelligence

(25.3% to 31.2% VAF) had a distribution that was similar to that for hyperaligned task

connectivity, sharing 68.3% of cortical vertices (compare Figures 3D and 4D), with

vertices mostly in the default mode network (49.0%) and smaller parts in the

frontoparietal (19.4%), dorsal attention (15.8%) and ventral attention (10.0%) systems

(Figure 4E).

Prediction based on resting fMRI functional connectivity

Figure 4. Predicting general intelligence based on regional hyperaligned resting fMRI connectivity profiles. Prediction based on fine-grained (A) and coarse-grained (B) connectivity profiles. The scatter plot (C) shows that regional predictions based

on hyperaligned fine-grained profiles accounted for more variance in all 360 ROIs.

Prediction models based on each region's fine-grained hyperaligned resting

functional connectivity profile accounted for 2.57 (95% CI: [2.28, 3.08]) times more

variance in general intelligence on average than did models based on

coarse-grained functional connectivity profiles. Each circle is a cortical region, and

the color of each circle corresponds to the cortical system where it resides, using

the same color scheme as in (E). Dashed lines denote average difference in R^2

(gray), or identical R^2 (black). (D) The thirty regions whose hyperaligned

fine-grained connectivity best predicted general intelligence are colored as in

panels A and B. The default mode network is outlined in red, and the frontoparietal

network is outlined in orange (Yeo et al., 2011). (E) Proportion of vertices in these

regions that are in seven cortical systems delineated with resting state fMRI

functional connectivity (Yeo et al., 2011).

Consistent with previous reports (Greene et al., 2018; Jiang et al., 2020), task

fMRI connectivity was significantly more predictive of general intelligence than was

resting fMRI connectivity for both hyperaligned fine-grained data (difference = 7.7%

VAF; 95% CI: 5.4% to 9.9%) and coarse-grained data (difference = 6.9% VAF; 95% CI:

5.1% to 8.6%). Task connectivity accounted for more variance than did resting

connectivity in 358 of 360 ROIs for hyperaligned fine-grained data and in 340 of 360

ROIs for coarse-grained data (Supplementary Figure S1).

Hyperaligned versus MSM-aligned fine-grained connectivity profiles

To test the efficacy of hyperalignment for revealing predictive individual differences in fine-grained connectivity topographies, we trained another set of models based on fine-grained functional connectivity of data without hyperalignment. These data were aligned with Multimodal Surface Matching (MSM) (Robinson et al., 2014). Models based on MSM-aligned fine-grained task connectivity and resting connectivity accounted for, on average across ROIs, 17.5% (min: 4.8%; max: 28.7%) and 10.9% (min: 0.6%; max: 22.6%), respectively, of variance in general intelligence, which was 64.2% (95% CI: [59.7%, 68.1%]) and 55.6% (95% CI: [49.1%, 61.2%]) of that accounted for by models using hyperaligned data (Figure 5). Predictions based on hyperaligned fine-grained task connectivity were better than predictions based on MSM-aligned fine-grained connectivity in all 360 regions (Figure 5C). Predictions based on hyperaligned fine-grained resting connectivity were better than predictions based on MSM-aligned fine-grained connectivity in 357 of 360 regions (Figure 5D). The difference in model performance was larger for brain regions with more functional topographic idiosyncrasy for both task and resting connectivity (r = 0.460 and 0.395, respectively, $p < 10^{-14}$), with two- to three-fold increases in VAF in the most idiosyncratic regions. As for hyperaligned fine-scale connectivity and for coarse-scale connectivity, MSM-aligned fine-scale task connectivity was more predictive of intelligence than was MSM-aligned fine-scale resting connectivity (difference = 6.6% VAF; 95% CI: [5.1%, 8.1%]; Supplemental Figure S1C). Consistent with our previous findings (Feilong et al., 2018), these results show that hyperalignment factors out

idiosyncrasies in functional topography to reveal how individuals differ in information

encoded in fine-grained cortical functional architecture.

Figure 5. Predicting general intelligence based on MSM-aligned fine-grained

connectivity profiles. Prediction based on task fMRI (A) and resting fMRI (B)

connectivity. Scatterplots compare regional predictions based on MSM-aligned to

predictions based on hyperaligned task connectivity (C) and resting connectivity (D)

data (comparison to results in Figures 3A and 4A).

Discussion

The results show that individual differences in fine-grained patterns of functional

connectivity are a markedly better predictor of general intelligence than are

coarse-grained patterns, indicating that differences in cortical architecture that underlie

inter-individual variation in the efficiency of information processing are more evident at

the same spatial scale as topographic patterns that encode information. Discovering

the dominant role of fine-grained connectivity patterns in the neural basis of

intelligence required a method that resolves individual differences in these

idiosyncratic patterns, a method that was not available prior to hyperalignment

(Feilong et al., 2018; Guntupalli et al., 2018, 2016; Haxby et al., 2020, 2011; Nastase et

al., 2020).

Differences in intelligence are indexed by tests of the ability to understand and

manipulate information embedded in the meanings of words, logical relations, and

visual patterns. We predicted that differences in performance would be more related

to the fine-grained topographic patterns that represent these kinds of information than

to coarse-grained patterns that blur fine distinctions. The results confirm our

hypothesis. Hyperaligned, fine-grained, vertex-by-vertex connectivity patterns

accounted for 1.88 to 2.57 times more variance in general intelligence than did coarse-grained, region-to-region connectivity patterns.

To examine the predictive power of fine-grained connectivity unconfounded with coarse-grained connectivity, we built models using the residual fine-grained connectivity profiles. In separate analyses we built models on the full fine-grained patterns and found that adding coarse-grained information contributed little to VAF (Supplemental Figure S2), underscoring the stronger role that fine-grained cortical architecture plays in the neural basis of intelligence than that played by coarse-grained architecture.

Functional connectivity shows fine-grained variation vertex-by-vertex within a cortical field (Guntupalli et al., 2018) and even neuron-by-neuron within an fMRI voxel (Park et al., 2017). Transmission of information between cortical fields, therefore, involves more than simple synchronization of global activity. Information is transformed, as evidenced by changes in the representational geometries that are embedded in the fine-grained structure of local topographies (Connolly et al., 2016; Guntupalli et al., 2017; Kriegeskorte et al., 2008). Our results indicate that investigating the efficiency of information processing should focus on fine-grained patterns of connectivity that support information processing.

Previous work could not reveal the role that information embedded in fine-scale topographies plays in the neural basis of intelligence because individual differences in information were concealed by idiosyncrasies in fine-scale topographies that could not be aligned with prior methods. Hyperalignment resolves the shared information

embedded in idiosyncratic topographies, making it possible to investigate these individual differences (Feilong et al., 2018). Fine-grained information in hyperaligned data accounted for 1.56 to 1.80 times more individual variation in intelligence than did fine-grained information in non-hyperaligned data.

Results also show that fMRI data collected during performance of cognitive tasks better predict intelligence than resting state fMRI data, consistent with previous reports (Greene et al., 2018; Jiang et al., 2020). Previous studies used whole-brain, coarse-grained connectivity for prediction. Here we show that the added predictive power of task fMRI data, relative to resting fMRI data, extends to both hyperaligned and MSM-aligned fine-grained connectivity patterns.

Our results show further that the neural basis of intelligence resides mostly in the fine-grained structure of connectivity in the default mode and frontoparietal networks (Buckner et al., 2008; Raichle et al., 2001; Yeo et al., 2011). Small parts of the most predictive regions were in the dorsal and ventral attention networks, and an even smaller proportion was in the visual system. The most predictive brain regions did not encroach on the systems for auditory, somatosensory, motor, or limbic function. The predominance of the default mode network was found for both task connectivity and resting connectivity, suggesting that the efficiency of these connections is evident in both. A strong role for the frontoparietal network was more evident in task connectivity, suggesting that efficiency of this system's connections is better revealed during performance of tasks that increase its activity.

The predominant role of the default and frontoparietal systems in our results suggests that intelligence rests on self-generated and stimulus-independent thinking (Andrews-Hanna et al., 2014; Buckner et al., 2008; Dixon et al., 2018; Raichle et al., 2001), or on the apperceptive mass that provides the foundation and context for perception and thought (Raichle, 2006), for finding correct solutions to problems and generating novel insights. The functions of the default system are mostly ill-defined because it does not respond to features of external stimuli in a consistent way (Andrews-Hanna et al., 2014; Buckner et al., 2008; Golland et al., 2007). Although default system activity during movie watching and in the resting state is idiosyncratic, it is highly correlated across default areas (Buckner et al., 2008; Golland et al., 2007) and has a fine-scale structure that can be modeled with hyperalignment (Feilong et al., 2018; Guntupalli et al., 2018), indicating that this activity has structure and meaning. It has been associated with thinking about others' mental states (Buckner et al., 2008; Frith and Frith, 1999; Gobbini et al., 2007; Saxe and Kanwisher, 2003), activation of person knowledge about familiar others (Gobbini and Haxby, 2007), autobiographical memory and envisioning the future (Addis et al., 2007), as well as other aspects of internally-driven cognition. The most predictive regions overlapped only a portion of the default network involving primarily the dorsal medial subsystem with smaller parts in the core subsystem (Andrews-Hanna et al., 2014, 2010). The dorsal medial subsystem has been associated with mentalizing, social cognition, story comprehension, and semantic conceptual processing (Andrews-Hanna et al., 2014).

The frontoparietal system may similarly reflect the role of self-directed thought in the neural basis of general intelligence. Dixon et al. (2018) have identified a subdivision of the frontoparietal network that interacts primarily with the default mode system. They propose that this part of the frontoparietal system is involved in the regulation of introspective processes.

The efficiency of the default system apparently rests more on fine-grained features of its functional connectivity than on coarse-grained functional connectivity. The bases for the organization of its fine-grained topographies and the transformations of representational geometries between default regions are unknown, but the keys to understanding the neural basis of intelligent thought may reside in the information processing embedded in these topographies.

Acknowledgements

We would like to thank Guo Jiahui, Samuel Nastase, and Maria Ida Gobbini for helpful comments, suggestions, and discussion. We would like to thank Yaroslav Halchenko for support with software.

Data were provided by the Human Connectome Project, WU-Minn Consortium (Principal Investigators: David Van Essen and Kamil Ugurbil; 1U54MH091657) funded by the 16 NIH Institutes and Centers that support the NIH Blueprint for Neuroscience Research; and by the McDonnell Center for Systems Neuroscience at Washington University.

This work was supported with funds from NSF grants 1607845 and 1835200.

Author contributions

Conceptualization, M.F., J.V.H; Methodology, M.F., J.S.G., J.V.H.; Software, M.F., J.S.G.; Formal analysis, M.F.; Resources, J.V.H; Writing - original draft, M.F., J.V.H.; Writing - review and editing, M.F., J.S.G., J.V.H.; Visualization, M.F., J.V.H.; Supervision and Funding acquisition, J.V.H.

Declarations of interests

The authors declare no competing interests.

Methods

Dataset

We used data from the Human Connectome Project (HCP) (Van Essen et al., 2013) for our analysis. The final S1200 data release of the HCP Young Adult dataset contains multi-modal MR imaging and behavioral data from 1206 participants that are 22-35 years old. This includes about one hour of resting-state fMRI data (4 runs, 14.5 minutes each), 47 minutes of task fMRI data (7 tasks, 2 runs each), and extensive cognitive tests for each participant. Out of the 1206 participants, 888 have complete task and resting fMRI data, 1181 have complete scores of 10 cognitive tests, and 876 participants have both. In our analysis, we always used as many participants with complete data as possible to maximize statistical power. That is, we used data from the 1181 participants to derive the general intelligence score, data from the 888 participants to derive hyperalignment models and compute topographic idiosyncrasy, and data from the overlapping 876 participants for prediction analysis.

Measuring general intelligence

General intelligence is a common factor, often referred to as *g*, underlying all cognitive abilities (Spearman, 1904). In this study, we measured general intelligence as the general factor obtained based on 10 cognitive test scores using a factor analysis with a bi-factor model (Dubois et al., 2018). These cognitive tests (Barch et al., 2013) include those from the NIH Toolbox for Assessment of Neurological and Behavioral Function (http://www.nihtoolbox.org) and additional computerized tests (Bilker et al.,

2012; Gur et al., 2010), covering a range of memory, attention, language, and reasoning abilities. General intelligence can be accurately and consistently identified through different test batteries (Johnson et al., 2008, 2004), and our findings are robust over choices of intelligence measures (Supplementary Figures S6 and S7).

MRI acquisition

MRI data were acquired with a Siemens 3 T Skyra MRI scanner and a 32-channel head coil. The scanner was customized with a gradient coil and gradient power. Each subject has 2 T1w and 2 T2w scans with 0.7 mm isotropic voxels, which were used to reconstruct high-resolution cortical surfaces.

Functional MRI data were acquired with a TR of 0.72 s, 2 mm isotropic voxels, and a multi-band acceleration factor of 8. Every volume comprised 72 slices with 208 × 180 mm^2 FOV each. Half of the fMRI runs were scanned with the LR phase encoding direction, and the other half were with RL. Spin-echo field maps were collected along with the fMRI data that allow susceptibility distortion correction.

Resting fMRI data were acquired with 4 runs of 1200 TRs each. Each of the 7 tasks were acquired with 2 runs, and the duration of each run varied across tasks (min: 176 TRs, max: 405 TRs). In total, for each participant, 57.6 minutes of resting fMRI data and 46.6 minutes of task fMRI data were acquired. See (Uğurbil et al., 2013) for additional details of MRI acquisition.

MRI preprocessing

We used the same standard procedure to preprocess fMRI data for all task and resting fMRI data. Our preprocessing was based on the minimally preprocessed

version of the dataset (Glasser et al., 2013), where data had been corrected for distortion and head motion, and aligned to a standard cortical surface mesh using Multimodal Surface Matching (MSM) (Robinson et al., 2014), which aims to match multimodal properties across individuals while preserving topology. These data were labeled as "MSMAll" in the HCP data files, and we refer to them as "MSM" for short.

We first normalized all fMRI data to percent signal change units, then used linear regression to remove nuisance components from them. These nuisance components include 6 motion parameters and their derivatives, 5 principal components from white matter and cerebrospinal fluid (Behzadi et al., 2007), global signal, and polynomial trends up to the 3rd order. The whilte matter and cerebrospinal fluid components were extracted from volumetric data based on eroded anatomical masks. Both the regressors and data were low-pass filtered with a Gaussian kernel (standard deviation = 1 TR) prior to regression. These preprocessing steps were analogous to previous work (Dubois et al., 2018; Finn et al., 2015; Greene et al., 2018; Shen et al., 2017).

Hyperalignment

We used connectivity hyperalignment (Guntupalli et al., 2018) to align fine-grained cortical functional architecture across individuals. We used regional average time series of the 360-region multi-modal cortical parcellation (Glasser et al., 2016) as connectivity targets. For each of the 59,412 cortical vertices, we computed its connectivity profile as the correlations between its own time series and the 360 regional average time series. Therefore, each connectivity profile is a vector comprising 360 correlation coefficients. In each brain region, we derived a

transformation matrix for each individual using these connectivity profiles, which remixes each individual's vertices into a common set of model dimensions through an improper rotation of a high-dimensional space. Each model dimension has similar functional properties across individuals instead of the same anatomical position, and these model dimensions together constitute a common model space. The common model space is usually instantiated as a reference brain, where each vertex corresponds to a model dimension. The information content in each individual's data — the configuration of connectivity vectors in the high-dimensional feature space — is perfectly preserved during the rotation, whereas how and where this information is encoded in idiosyncratic topographies is factored out into the transformation matrix.

We used the HCP task fMRI dataset to derive the hyperalignment common model and transformations (i.e., to train hyperalignment) when we analyzed the task fMRI data, and resting fMRI dataset when we analyzed the resting fMRI data. Therefore, the task and resting fMRI datasets remain independent throughout the analysis. It is possible to train hyperalignment using one dataset and apply it to another, and such results are summarized in Supplementary Figure S2.

Functional connectivity profiles

We used functional connectivity profiles to depict a brain region's functional interactions with the entire cerebral cortex. These connectivity profiles are different from the connectivity profiles used in connectivity hyperalignment as described above.

For each of 360 cortical regions, we computed a fine-grained connectivity matrix for each participant (Figure 1, top row), which comprises pairwise interactions between

all vertices in the region (165 vertices on average) and all vertices of the cerebral cortex (59,412 vertices). We vectorized this connectivity matrix to form a long vector comprising millions of connectivity strengths (9.8 million on average across all regions), which we refer to as the participant's full fine-grained connectivity profile of the region. This fine-grained connectivity profile depicts in detail the region's information exchange with the rest of the cortex, and it contains information encoded in fine-grained connectivity patterns up to the same resolution as the input fMRI data (2 mm for this dataset).

To separate information encoded in different spatial scales, we split the full fine-grained connectivity profile into a coarse-grained connectivity profile and a residual fine-grained connectivity profile. The coarse-grained connectivity profile for a given region is a vector comprising 360 elements, where each element is the average connectivity strength between all cortical vertices in this region and all vertices in another region (Figure 1, middle row). Similar to previous work (Dubois et al., 2018; Finn et al., 2015; Shen et al., 2017), coarse-grained connectivity profiles depict the information exchange between a pair of regions with a single connectivity strength. A residual fine-grained connectivity profile comprises pattern residuals obtained by subtracting the mean connectivity with each region (an element of the coarse-grained connectivity profile) from each element of the vertex-by-vertex connectivity pattern with the region (part of the full fine-grained connectivity profile). Similar to a full fine-grained connectivity profile, a residual fine-grained connectivity profile comprises millions of elements, and the only difference is that these elements are connectivity

residuals instead of connectivities. In other words, a residual fine-grained connectivity profile contains only fine-scale information, instead of combined fine- and coarse-scale information.

The analysis involves data aligned in 3 different ways: MSM, hyperalignment based on task fMRI data, and hyperalignment based on resting fMRI data. For each alignment method, we computed these 3 kinds of connectivity profiles for each participant and each region. The results of fine-grained connectivity profiles reported in the main text are based on residual fine-grained connectivity profiles, and similar results were obtained using full fine-grained connectivity profiles (Supplementary Figure S2).

Topographic idiosyncrasy

We measured the idiosyncrasy of each region's functional topography as the average dissimilarity of hyperalignment transformation matrices across participant pairs, after correcting for region size. The dissimilarity between two matrices was quantified as the Frobenius norm of their difference. Because the regions differ in size, and the average matrix dissimilarity was predominantly determined by the square root of region size ($r > 0.9999$), we fit a linear regression model between them, and used the residual dissimilarity as the heterogeneity of a region's functional topography across individuals.

We performed hyperalignment twice in our analysis — once using task fMRI data, once using resting fMRI data — and therefore obtained two sets of transformation matrices for each region. Topographic idiosyncrasy indices based on

each of the two sets are essentially identical ($r = 0.960$, $p = 4 \times 10^{-200}$). When we analyzed task fMRI data, we used topographic idiosyncrasy based on task fMRI (Figure 5C), and when we analyzed resting fMRI data, we used that based on resting fMRI (Figure 5D).

Cross-validation scheme

We used leave-one-family-out cross-validation (Dubois et al., 2018) to assess prediction models. The 876 participants were from 411 families, and each family had 2.13 members on average (range: 1–5; with 103 participants with no other family members and 177, 107, 22, and 2 families with 2 to 5 participants, respectively). Therefore, this cross-validation scheme divided the entire dataset into 411 folds. Each time we leave out a family of k individuals (i.e., related to each other) as test data, and use the remaining 876 - k individuals (i.e., not related to test participants) as training data to train the model. We repeated this procedure, each time using a different family as test data. Therefore, after looping through all families, each individual's general intelligence score was predicted by a model trained with unrelated individuals.

For each cross-validation fold (i.e., each family as test data), we further split the training data into three sub-folds and used nested cross-validation to choose the optimal model parameters. In other words, model parameters were always chosen based only on training data.

Regression models

We used principal component regression with ridge regularization to predict general intelligence based on functional connectivity. First, we used principal

component analysis (PCA) to derive principal components (PCs) from functional

connectivity patterns based on training data. Dimensions in the PC space capture

principal ways that individuals' connectivity profiles differ. Thus, the connectivity

profile for a region in each training set participant was transformed into a set of scores

across PC dimensions. Then, we trained a ridge regression model to predict general

intelligence based on these PC scores. The PCA and ridge regression models were

then applied to test data to obtain the model predicted general intelligence scores.

Model parameters (the number of PCs and the regularization parameter) were always

chosen using nested cross-validation as stated above. Candidate model parameters

were distributed evenly on a logarithmic scale. Choices for the number of PCs were

10, 20, 40, 80, 160, 320, and all PCs (i.e., no dimensionality reduction). Choices for the

regularization parameter α were 81 values from 10^{-20} to 10^{20}.

Model evaluation

We evaluated our models using the cross-validated coefficient of determination

(R^2). R^2 denotes the percent of variance in general intelligence that was accounted for

(VAF) by prediction models. The formula is

$$R^2 = 1 - \frac{\sum_i (y_i - \hat{y}_i)^2}{\sum_i (y_i - \bar{y}_{i,train})^2}$$

where y_i is the measured score for subject i, $\hat{y}_i$ is the model predicted score for

subject i, and $\bar{y}_{i,\,train}$ is the prediction by the null model. The prediction of the null

model is simply the average score of all training data, and thus it doesn't use any

information from the features (fine- or coarse-grained functional connectivity in this

case) at all. R^2 maximizes at 100%, which means perfect prediction; 0 means model performance is only the same as the null model. In rare cases, cross-validated R^2 can also be negative, which suggests the model performance is even worse than the null model.

To assess model performance against chance, we used permutation testing to create a null distribution of R^2. The HCP dataset has subjects that are from the same family, and they are more likely to have similar general intelligence scores compared with non-related subjects (Plomin and Deary, 2015). Therefore, the subject labels are not fully exchangeable, and we used multi-level block permutation (Winkler et al., 2015) to resolve the issue. With this hierarchical permutation approach, the data exchangeability is properly modeled, providing more accurate estimates of false positive rates.

For each of the 2160 conditions (360 brain regions × 3 connectivity profile types × 2 fMRI data types), we ran a permutation test by training and evaluating prediction models 100 times based on shuffled subject labels. Across conditions (Supplementary Figure S4) the maximum R^2 of all 100 permutations was less than the value obtained with the prediction model (i.e., $p < 0.01$) for all models based on hyperaligned fine-grained connectivity or on MSM-aligned fine-grained task connectivity and for all models based on coarse-scale connectivity or on MSM-aligned fine-grained resting connectivity that had a R^2 over 1.3%.

Estimating confidence intervals

We used bootstrap tests to estimate confidence intervals (CIs) for contrasts between VAF by different prediction models. In each of 1,000,000 repetitions, we randomly sampled a group of 876 individuals used for model evaluation by sampling with replacement from the 876 original individuals. In other words, in each bootstrapped sample, a participant might be selected once, multiple times, or not selected at all. For each bootstrapped sample, we computed VAF differences and VAF ratios. The 95% CI of a difference or ratio is estimated as the 2.5th and 97.5th percentiles of the difference or ratio from the bootstrapped samples (i.e., the sampling distribution of the difference or ratio estimated by bootstrapping participants).

Pearson correlation

We used the Pearson correlation coefficient to assess the relationship between regional topographic idiosyncrasy and the difference in prediction performance based on hyperaligned and MSM-aligned data (Figure 5, panels C and D), and the relationship between the square root of a region's size and the average transformation matrix dissimilarity. In both cases, n (the number of regions) is always 360, and the degrees of freedom is always 358.

Dice coefficient

We used the Dice similarity coefficient (Dice, 1945) to quantify the amount of overlap between the 30 most predictive regions based on task fMRI data and those based on resting fMRI data. The formula is

$$DSC = \frac{2|A \cap B|}{|A| + |B|}$$

where A is the set of vertices covered by the 30 most predictive regions based on task fMRI data, and B is that based on resting fMRI data. $|\cdot|$ denotes set cardinality. *DSC* is short for Dice similarity coefficient.

Overlap with cortical systems

The cerebral cortex can be divided into 7 cortical systems based on functional connectivity (Yeo et al., 2011). For each of the 360 regions, we computed the percentage of vertices belonging to each of the 7 systems as the number of vertices belonging to the system divided by the total number of vertices in the region. For the 30 most predictive regions, we computed the percentage of vertices across all 30 regions that belonged to each system (Figures 3E and 4E). In the scatter plots (Figures 3C and 4C), each region was assigned to one of the cortical systems, which is the system that had the largest amount of vertices in the region.

Software used

We implemented our analysis using Python and Python packages including NumPy (https://numpy.org/), SciPy (https://www.scipy.org/), and NiBabel (https://nipy.org/nibabel/). The code for performing hyperalignment and nuisance regression was adapted from PyMVPA (http://www.pymvpa.org/) (Hanke et al., 2009).

Supplemental material

Comparison of predictions based on task fMRI and resting fMRI data

Supplemental Figure S1. Scatterplots comparing VAF by regional prediction models using task fMRI and resting fMRI connectivity. A. Hyperaligned, fine-grained connectivity. B. Coarse-grained connectivity. C. MSM-aligned fine-grained connectivity. Each circle represents one region. The color of each circle corresponds to the cortical system that each region is part of (based on a plurality of vertices), using the same color scheme as in Figures 3D and 4D.

Results showed that task fMRI data produced better predictions of general intelligence than did resting fMRI for hyperaligned residual fine-grained, coarse-grained, and MSM-aligned residual fine-grained connectivity.

Comparison of alignments and predictions based on single task connectivity

Supplemental Figure S2. Histograms of VAF by predictions of general intelligence using different fMRI connectivity datasets and different alignment methods. A. Prediction based on residual fine-grained connectivity. B. Predictions based on coarse-grained connectivity. C. Predictions based on full fine-grained connectivity, which includes information in both fine-grained and coarse-grained patterns. CHA is short for connectivity hyperalignment.

Connectivity hyperalignment based on task fMRI data produced stronger predictions of general intelligence based on task connectivity than did connectivity hyperalignment based on resting fMRI data. Predictions based on resting connectivity were equivalent for connectivity hyperalignment based on task fMRI and resting fMRI. Prediction based on hyperaligned residual fine-grained connectivity and on hyperaligned full fine-grained connectivity profiles (A and C) were essentially identical.

Hyperalignment transformations remix the time series for cortical vertices, which alters the mean of correlations between the vertices of two regions - namely, the coarse-scale functional connectivity between these regions (B). Analyses of hyperaligned fine-grained connectivity profiles all used the coarse-grained connectivity profiles calculated on the same hyperaligned data for comparison. In practice the effect of calculating coarse-grained connectivity profiles on task hyperaligned task fMRI, hyperaligned resting fMRI, and MSM-aligned fMRI is small and does not affect the results of these analyses (Supplemental Figure S2).

Predicting intelligence based on connectivity during single tasks

Supplemental Figure S3. Histograms of VAF by regional models prediction models based on connectivity calculated from fMRI during single tasks. For every single fMRI task (4.2 to 9.7 min) fine-scale hyperaligned connectivity data produced better predictions of general intelligence than did coarse-scale connectivity. The strongest predictions from single task fMRI were obtained from data during performance of the working memory (WM), language, and social cognition tasks.

Null distribution of model performance based on permutation testing

Supplemental Figure S4. Permutation testing. For each of the 2160 conditions (360 brain regions × 3 connectivity profile types × 2 fMRI data types), we ran a permutation test by training and evaluating prediction models 100 times based on shuffled subject labels. For 2148 out of 2160 conditions (99.4%), the actual R^2 was larger than all 100 permuted R^2's. For the remaining 12 conditions, the actual R^2 was close to 0 (all < 1.3%). In other words, for any model that had a R^2 of at least 1.3%, it's also larger than the maximum R^2 of all 100 permutations (i.e., $p < 0.01$).

Distribution of model parameter choices based on nested cross-validation

Supplemental Figure S5. Distribution of regularization parameters α and number of PCs for prediction models. For each kind of fMRI data (Panel A: task fMRI; Panel B: resting fMRI) and each kind of connectivity profiles (hyperaligned fine-grained, MSM-aligned fine-grained, coarse-grained), we summarize the distribution of model parameters across all cross-validation folds (411 families × 360 regions = 147,960). Models trained on fine-grained connectivity profiles (left and middle columns) tend to use less regularization (smaller alphas) and more PCs compared with models trained on coarse-grained connectivity profiles (right column), especially models trained on hyperaligned fine-grained connectivity profiles. More PCs used by the model suggests that there are more dimensions in the connectivity profiles that are related to general intelligence, and less regularization suggests these PCs contain more signal relative to noise.

Predicting alternative measures of intelligence

Supplemental Figure S6. Predicting alternative measures of intelligence based on connectivity profiles. Our prediction models and connectivity profiles can also be trained to predict other measures of intelligence, such as fluid intelligence measured with the Penn Matrices (Panel A, variable "PMAT24_A_CR" in the dataset) and general intelligence measured as the Cognitive Function Composite score of the NIH Toolbox (Panel B, "CogTotalComp_AgeAdj"). Similar to the results of the main paper (shown here as Panel C for comparisons), predictions based on fine-grained hyperaligned connectivity profiles account for approximately 2 times more variance in intelligence compared with coarse-grained connectivity profiles for task fMRI data, and 3 times more for resting fMRI data.

Fluid intelligence as Penn Matrices score

General intelligence as NIH Toolbox Cognitive Function Composite score

Supplementary Figure S7. Predicting alternative intelligence measures based on regional hyperaligned fine-grained task fMRI connectivity profiles. Regional connectivity profiles that were more predictive of factor analysis based general intelligence score were more likely to be more predictive of matrix reasoning based fluid intelligence score (top row, r = 0.92) and NIH Toolbox based general intelligence score (bottom row, r = 0.96). This suggests our results were robust over intelligence measure choices.

References

Addis DR, Wong AT, Schacter DL. 2007. Remembering the past and imagining the future: common and distinct neural substrates during event construction and elaboration. *Neuropsychologia* **45**:1363–1377. doi:10.1016/j.neuropsychologia.2006.10.016

Andrews-Hanna JR, Reidler JS, Sepulcre J, Poulin R, Buckner RL. 2010. Functional-anatomic fractionation of the brain's default network. *Neuron* **65**:550–562. doi:10.1016/j.neuron.2010.02.005

Andrews-Hanna JR, Smallwood J, Spreng RN. 2014. The default network and self-generated thought: component processes, dynamic control, and clinical relevance. *Ann N Y Acad Sci* **1316**:29–52. doi:10.1111/nyas.12360

Barch DM, Burgess GC, Harms MP, Petersen SE, Schlaggar BL, Corbetta M, Glasser MF, Curtiss S, Dixit S, Feldt C, Nolan D, Bryant E, Hartley T, Footer O, Bjork JM, Poldrack R, Smith S, Johansen-Berg H, Snyder AZ, Van Essen DC, WU-Minn HCP Consortium. 2013. Function in the human connectome: task-fMRI and individual differences in behavior. *Neuroimage* **80**:169–189. doi:10.1016/j.neuroimage.2013.05.033

Behzadi Y, Restom K, Liau J, Liu TT. 2007. A Component Based Noise Correction Method (CompCor) for BOLD and Perfusion Based fMRI. *Neuroimage* **37**:90–101. doi:10.1016/j.neuroimage.2007.04.042

Bilker WB, Hansen JA, Brensinger CM, Richard J, Gur RE, Gur RC. 2012. Development of abbreviated nine-item forms of the Raven's standard progressive matrices test. *Assessment* **19**:354–369. doi:10.1177/1073191112446655

Buckner RL, Andrews-Hanna JR, Schacter DL. 2008. The brain's default network: anatomy, function, and relevance to disease. *Ann N Y Acad Sci* **1124**:1–38. doi:10.1196/annals.1440.011

Connolly AC, Sha L, Guntupalli JS, Oosterhof N, Halchenko YO, Nastase SA, Castello MV di O, Abdi H, Jobst BC, Gobbini MI, Haxby JV. 2016. How the Human Brain Represents Perceived Dangerousness or "Predacity" of Animals. *J Neurosci* **36**:5373–5384. doi:10.1523/JNEUROSCI.3395-15.2016

Cox SR, Ritchie SJ, Fawns-Ritchie C, Tucker-Drob EM, Deary IJ. 2019. Structural brain imaging correlates of general intelligence in UK Biobank. *Intelligence* **76**:101376. doi:10.1016/j.intell.2019.101376

Dice LR. 1945. Measures of the Amount of Ecologic Association Between Species. *Ecology* **26**:297–302. doi:10.2307/1932409

Dixon ML, Vega ADL, Mills C, Andrews-Hanna J, Spreng RN, Cole MW, Christoff K. 2018. Heterogeneity within the frontoparietal control network and its relationship to the default and dorsal attention networks. *PNAS* **115**:E1598–E1607. doi:10.1073/pnas.1715766115

Dubois J, Galdi P, Paul LK, Adolphs R. 2018. A distributed brain network predicts general intelligence from resting-state human neuroimaging data. *Philosophical Transactions of the Royal Society B: Biological Sciences* **373**:20170284. doi:10.1098/rstb.2017.0284

Feilong M, Nastase SA, Guntupalli JS, Haxby JV. 2018. Reliable individual differences in fine-grained cortical functional architecture. *Neuroimage* **183**:375–386. doi:10.1016/j.neuroimage.2018.08.029

Finn ES, Shen X, Scheinost D, Rosenberg MD, Huang J, Chun MM, Papademetris X, Constable RT. 2015. Functional connectome fingerprinting: identifying individuals using patterns of brain connectivity. *Nat Neurosci* **18**:1664–1671. doi:10.1038/nn.4135

Frith CD, Frith U. 1999. Interacting minds--a biological basis. *Science* **286**:1692–1695.

doi:10.1126/science.286.5445.1692

Glasser MF, Coalson TS, Robinson EC, Hacker CD, Harwell J, Yacoub E, Ugurbil K, Andersson J, Beckmann CF, Jenkinson M, Smith SM, Van Essen DC. 2016. A multi-modal parcellation of human cerebral cortex. *Nature* **536**:171–178. doi:10.1038/nature18933

Glasser MF, Sotiropoulos SN, Wilson JA, Coalson TS, Fischl B, Andersson JL, Xu J, Jbabdi S, Webster M, Polimeni JR, Van Essen DC, Jenkinson M, WU-Minn HCP Consortium. 2013. The minimal preprocessing pipelines for the Human Connectome Project. *Neuroimage* **80**:105–124. doi:10.1016/j.neuroimage.2013.04.127

Gobbini MI, Haxby JV. 2007. Neural systems for recognition of familiar faces. *Neuropsychologia* **45**:32–41. doi:10.1016/j.neuropsychologia.2006.04.015

Gobbini MI, Koralek AC, Bryan RE, Montgomery KJ, Haxby JV. 2007. Two takes on the social brain: a comparison of theory of mind tasks. *J Cogn Neurosci* **19**:1803–1814. doi:10.1162/jocn.2007.19.11.1803

Golland Y, Bentin S, Gelbard H, Benjamini Y, Heller R, Nir Y, Hasson U, Malach R. 2007. Extrinsic and intrinsic systems in the posterior cortex of the human brain revealed during natural sensory stimulation. *Cereb Cortex* **17**:766–777. doi:10.1093/cercor/bhk030

Greene AS, Gao S, Scheinost D, Constable RT. 2018. Task-induced brain state manipulation improves prediction of individual traits. *Nature Communications* **9**:1–13. doi:10.1038/s41467-018-04920-3

Guntupalli JS, Feilong M, Haxby JV. 2018. A computational model of shared fine-scale structure in the human connectome. *PLOS Computational Biology* **14**:e1006120. doi:10.1371/journal.pcbi.1006120

Guntupalli JS, Hanke M, Halchenko YO, Connolly AC, Ramadge PJ, Haxby JV. 2016. A Model of Representational Spaces in Human Cortex. *Cereb Cortex* **26**:2919–2934. doi:10.1093/cercor/bhw068

Guntupalli JS, Wheeler KG, Gobbini MI. 2017. Disentangling the Representation of Identity from Head View Along the Human Face Processing Pathway. *Cereb Cortex* **27**:46–53. doi:10.1093/cercor/bhw344

Gur RC, Richard J, Hughett P, Calkins ME, Macy L, Bilker WB, Brensinger C, Gur RE. 2010. A cognitive neuroscience-based computerized battery for efficient measurement of individual differences: standardization and initial construct validation. *J Neurosci Methods* **187**:254–262. doi:10.1016/j.jneumeth.2009.11.017

Hanke M, Halchenko YO, Sederberg PB, Hanson SJ, Haxby JV, Pollmann S. 2009. PyMVPA: A python toolbox for multivariate pattern analysis of fMRI data. *Neuroinformatics* **7**:37–53. doi:10.1007/s12021-008-9041-y

Haxby JV, Connolly AC, Guntupalli JS. 2014. Decoding neural representational spaces using multivariate pattern analysis. *Annu Rev Neurosci* **37**:435–456. doi:10.1146/annurev-neuro-062012-170325

Haxby JV, Gobbini MI, Furey ML, Ishai A, Schouten JL, Pietrini P. 2001. Distributed and overlapping representations of faces and objects in ventral temporal cortex. *Science* **293**:2425–2430. doi:10.1126/science.1063736

Haxby JV, Guntupalli JS, Connolly AC, Halchenko YO, Conroy BR, Gobbini MI, Hanke M, Ramadge PJ. 2011. A common, high-dimensional model of the representational space in human ventral temporal cortex. *Neuron* **72**:404–416. doi:10.1016/j.neuron.2011.08.026

Haxby JV, Guntupalli JS, Nastase SA, Feilong M. 2020. Hyperalignment: Modeling shared information encoded in idiosyncratic cortical topographies. *eLife* **9**:e56601. doi:10.7554/eLife.56601

Jiang R, Zuo N, Ford JM, Qi S, Zhi D, Zhuo C, Xu Y, Fu Z, Bustillo J, Turner JA, Calhoun VD,

Sui J. 2020. Task-induced brain connectivity promotes the detection of individual differences in brain-behavior relationships. *NeuroImage* **207**:116370. doi:10.1016/j.neuroimage.2019.116370

Johnson W, Bouchard TJ, Krueger RF, McGue M, Gottesman II. 2004. Just one g: Consistent results from three test batteries. *Intelligence* **32**:95–107. doi:10.1016/S0160-2896(03)00062-X

Johnson W, Nijenhuis J te, Bouchard TJ. 2008. Still just 1 g: Consistent results from five test batteries. *Intelligence* **36**:81–95. doi:10.1016/j.intell.2007.06.001

Kong R, Li J, Orban C, Sabuncu MR, Liu H, Schaefer A, Sun N, Zuo X-N, Holmes AJ, Eickhoff SB, Yeo BTT. 2019. Spatial Topography of Individual-Specific Cortical Networks Predicts Human Cognition, Personality, and Emotion. *Cereb Cortex* **29**:2533–2551. doi:10.1093/cercor/bhy123

Kriegeskorte N, Mur M, Bandettini P. 2008. Representational similarity analysis - connecting the branches of systems neuroscience. *Front Syst Neurosci* **2**:4. doi:10.3389/neuro.06.004.2008

Luders E, Narr KL, Bilder RM, Thompson PM, Szeszko PR, Hamilton L, Toga AW. 2007. Positive correlations between corpus callosum thickness and intelligence. *Neuroimage* **37**:1457–1464. doi:10.1016/j.neuroimage.2007.06.028

Nastase SA, Liu Y-F, Hillman H, Norman KA, Hasson U. 2020. Leveraging shared connectivity to aggregate heterogeneous datasets into a common response space. *Neuroimage* 116865. doi:10.1016/j.neuroimage.2020.116865

Park SH, Russ BE, McMahon DBT, Koyano KW, Berman RA, Leopold DA. 2017. Functional Subpopulations of Neurons in a Macaque Face Patch Revealed by Single-Unit fMRI Mapping. *Neuron* **95**:971-981.e5. doi:10.1016/j.neuron.2017.07.014

Plomin R, Deary IJ. 2015. Genetics and intelligence differences: five special findings. *Molecular Psychiatry* **20**:98–108. doi:10.1038/mp.2014.105

Raichle ME. 2006. The Brain's Dark Energy. *Science* **314**:1249–1250. doi:10.1126/science.1134405

Raichle ME, MacLeod AM, Snyder AZ, Powers WJ, Gusnard DA, Shulman GL. 2001. A default mode of brain function. *Proc Natl Acad Sci U S A* **98**:676–682.

Robinson EC, Jbabdi S, Glasser MF, Andersson J, Burgess GC, Harms MP, Smith SM, Van Essen DC, Jenkinson M. 2014. MSM: a new flexible framework for Multimodal Surface Matching. *Neuroimage* **100**:414–426. doi:10.1016/j.neuroimage.2014.05.069

Saxe R, Kanwisher N. 2003. People thinking about thinking people. The role of the temporo-parietal junction in "theory of mind." *Neuroimage* **19**:1835–1842. doi:10.1016/s1053-8119(03)00230-1

Schmitt JE, Neale MC, Clasen LS, Liu S, Seidlitz J, Pritikin JN, Chu A, Wallace GL, Lee NR, Giedd JN, Raznahan A. 2019. A Comprehensive Quantitative Genetic Analysis of Cerebral Surface Area in Youth. *J Neurosci* **39**:3028–3040. doi:10.1523/JNEUROSCI.2248-18.2019

Shen X, Finn ES, Scheinost D, Rosenberg MD, Chun MM, Papademetris X, Constable RT. 2017. Using connectome-based predictive modeling to predict individual behavior from brain connectivity. *Nat Protoc* **12**:506–518. doi:10.1038/nprot.2016.178

Spearman C. 1904. "General Intelligence," Objectively Determined and Measured. *The American Journal of Psychology* **15**:201–292. doi:10.2307/1412107

Uğurbil K, Xu J, Auerbach EJ, Moeller S, Vu A, Duarte-Carvajalino JM, Lenglet C, Wu X, Schmitter S, Van de Moortele PF, Strupp J, Sapiro G, De Martino F, Wang D, Harel N, Garwood M, Chen L, Feinberg DA, Smith SM, Miller KL, Sotiropoulos SN, Jbabdi S,

Andersson JL, Behrens TE, Glasser MF, Van Essen D, Yacoub E. 2013. Pushing spatial and temporal resolution for functional and diffusion MRI in the Human Connectome Project. *Neuroimage* **80**:80–104. doi:10.1016/j.neuroimage.2013.05.012

Van Essen DC, Smith SM, Barch DM, Behrens TEJ, Yacoub E, Ugurbil K, WU-Minn HCP Consortium. 2013. The WU-Minn Human Connectome Project: an overview. *Neuroimage* **80**:62–79. doi:10.1016/j.neuroimage.2013.05.041

Winkler AM, Webster MA, Vidaurre D, Nichols TE, Smith SM. 2015. Multi-level block permutation. *NeuroImage* **123**:253–268. doi:10.1016/j.neuroimage.2015.05.092

Yeo BTT, Krienen FM, Sepulcre J, Sabuncu MR, Lashkari D, Hollinshead M, Roffman JL, Smoller JW, Zöllei L, Polimeni JR, Fischl B, Liu H, Buckner RL. 2011. The organization of the human cerebral cortex estimated by intrinsic functional connectivity. *J Neurophysiol* **106**:1125–1165. doi:10.1152/jn.00338.2011