A consensus-based ensemble approach to improve transcriptome assembly

Adam Voshall[1,2,3], Sairam Behera[2], Xiangjun Li[4,5], Xiao-Hong Yu[6], Kushagra Kapil[2], Jitender S. Deogun[2], John Shanklin[7], Edgar B. Cahoon[4,5], & Etsuko N. Moriyama[1,4]*

[1]School of Biological Sciences, University of Nebraska-Lincoln, Lincoln, NE 68588, USA

[2]Department of Computer Science and Engineering, University of Nebraska-Lincoln, Lincoln, NE 68588, USA

[3]Boston Children's Hospital/Harvard Medical School, Boston, MA, USA

[4]Center for Plant Science Innovation, University of Nebraska-Lincoln, Lincoln, NE 68588, USA

[5]Department of Biochemistry, University of Nebraska-Lincoln, Lincoln, NE 68588, USA

[6]Department of Biochemistry and Cell Biology, Stony Brook University, Stony Brook, NY 11794, USA

[7]Biology Department, Brookhaven National Laboratory, Upton, NY 11973, USA

*Correspondence: emoriyama2@unl.edu

Abstract

Background: Systems-level analyses, such as differential gene expression analysis, co-expression analysis, and metabolic pathway reconstruction, depend on the accuracy of the transcriptome. Multiple tools exist to perform transcriptome assembly from RNAseq data. However, assembling high quality transcriptomes is still not a trivial problem. This is especially the case for non-model organisms where adequate reference genomes are often not available. Different methods produce different transcriptome models and there is no easy way to determine which are more accurate. Furthermore, having alternative-splicing events could exacerbate such difficult assembly problems. While benchmarking transcriptome assemblies is critical, this is also not trivial due to the general lack of true reference transcriptomes.

Results: In this study, we first provide a pipeline to generate a set of the benchmark transcriptome and corresponding RNAseq data. Using the simulated benchmarking datasets, we compared the performance of various transcriptome assembly approaches including genome-guided, *de novo*, and ensemble methods. The results showed that the assembly performance deteriorates significantly when the reference is not available from the same genome (for genome-guided methods) or when alternative transcripts (isoforms) exist. Leveraging the overlapping predictions between four assemblers, we present ConSemble, a consensus-based ensemble transcriptome assembly pipeline.

Conclusions: Without using a reference genome, ConSemble using four *de novo* assemblers achieved an accuracy up to twice as high as any *de novo* assemblers we compared. It matched or exceeded the best performing genome-guided assemblers even when the transcriptomes included isoforms. When a reference genome is available, ConSemble using four genome-

guided assemblies removes many incorrectly assembled contigs with minimal impact on

correctly assembled contigs, achieving higher precision and accuracy than individual genome-

guided methods. We thus demonstrated that the consensus strategies both for *de novo* and

genome-guided assemblers can improve transcriptome assembly. The RNAseq simulation

pipeline, the benchmark transcriptome datasets, and the ConSemble pipeline are all freely

available from: http://bioinfolab.unl.edu/emlab/consemble/.

Keywords: RNAseq, Illumina, transcriptome assembly, *de novo* assembly, genome-guided

assembly, ensemble assembly, simulation, benchmarking

Background

A high quality and comprehensive transcriptome is required in many bioinformatics workflows [1-3]. Many methods have been developed for transcriptome assembly (*e.g.*, reviewed in [4]). However, assembled transcriptomes are often incomplete, especially for non-model organisms or highly divergent strains and further improvements are needed in assembler performance [5].

Transcriptome assembly methods can be classified into two general categories: *de novo* assemblers that generate the assembly based solely on the RNAseq data (read sets) and genome-guided assemblers that use a reference genome or transcriptome. Most of the current *de novo* assemblers, such as Trinity [6], rely on kmer decomposition of the reads, where kmers are substrings of length k, and de Bruijn graph construction [7]. However, with this approach, there are tradeoffs with the choice of the kmer length. For example, while shorter kmers are more likely to fully cover the transcript sequences that need to be assembled, they are also more likely to cause ambiguity in assembly graphs when repetitive sequences exist among transcripts. Due to such tradeoffs, each transcript has an optimal kmer length that facilitates the accurate reconstruction of the full-length sequence. Consequently, using different methods or even using the same method with different kmer lengths will generate different sets of contigs. Isoforms, polyploidy, multigene families, and varying levels of gene expression, all contribute to complexity in transcriptome assembly. Therefore, to obtain the complete transcriptome assembly, multiple assemblers are often needed to be used with a broad parameter space [8-13].

Genome-guided assemblers, such as Cufflinks [14], avoid the ambiguity in kmer assembly graphs by mapping the RNAseq data to the reference genome and clustering the reads based on genomic location [1]. However reads mapping to multiple locations within a genome can cause ambiguity [15]. When the reference genome used has any sequence divergence from the target

genome, with more divergence, fewer reads can be mapped to the reference without gaps or

mismatches. Each combination of read mapper and assembly algorithm handles these issues

differently.

While a core set of transcripts is more likely to be assembled correctly by multiple

assemblers, many other transcripts may be missed depending on which specific algorithm and

kmer length (for a *de novo* method) or mapper (for a genome-guided method) are used. Through

combining the results of multiple assemblers, ensemble assemblers such as EvidentialGene [16]

and the method developed by Cerveau and Jackson [17] (we call their method "Concatenation")

attempt to address the limitations of individual assemblers, retaining contigs that are more likely

to be correctly assembled and discarding the rest. Both of these ensemble methods filter the

contigs generated by multiple assemblers (usually *de novo*) by clustering the contigs and

determining the representative contig based on both the entire nucleotide and predicted protein

sequences. For Concatenation, contigs that contain only portions of longer contigs (without

allowing any nucleotide change) are clustered and removed. EvidentialGene clusters contigs by

nucleotide similarity (98% identity by default) based on the predicted coding sequences (CDS's)

and classifies them into gene loci. From each cluster, it selects contigs including the longest CDS

for the main set and those with distinct shorter CDS's for the alternative set. Similar to

Concatenation, contigs that are fragments of other contigs are removed (D. Gilbert, personal

communication). Both approaches greatly reduce the number of assembled contigs by removing

redundant sequences. However, there is no guarantee that the correct sequence is retained as the

representative for a given cluster or that each cluster represents a unique gene. Recently a new

ensemble assembler, TransBorrow, has been released [18]. After extracting reliable subpaths

supported by paired-end reads from a splice graph, it merges transcripts assembled by multiple

genome-guided methods and extracts reliable assembly subpaths based on the number of

assemblers that detect each subpath (transcript). While the study showed superior performance of

TransBorrow compared to individual genome-guided assemblers, how the performance among

ensemble assemblers differs has not been examined.

To evaluate the quality of transcriptome assemblies, several methods are available, such as

DETONATE [19], TransRate [15], and BUSCO [20]. The former two methods evaluate the

assembly quality based on how well the assemblies are explained by the RNAseq data used.

BUSCO evaluates the completeness of transcriptome assemblies by focusing on searching the

universal single-copy gene sets. These methods, however, cannot measure directly the accuracy

of each contig sequence. Moreover, without a benchmark transcriptome, transcripts that are not

assembled (missed) cannot be quantified and the impact of false positives tends to be

underestimated. In a recent study, a "real time" transcriptome was generated using the PacBio

long-read sequencing technology and used as a benchmark to evaluate *de novo* assemblies

generated from short-read RNAseq data obtained from the same biological samples [21].

However, obtaining good quality datasets that have been sequenced by both short- and long-read

technologies, especially from many different organisms with various conditions, is not easy nor

practical.

An alternative approach is to simulate the short-read sequencing based on a reference

genome and generate a benchmark dataset including the reference transcriptome and the RNAseq

reads. We previously used a simple simulation protocol and generated a benchmark

transcriptome based on a human genome [4]. It allowed us to compare transcriptome assembly

performance among different approaches. Our preliminary result showed that *de novo*

transcriptome assembly can be improved by taking the consensus among multiple *de novo*

assemblers.

In our present study, we generated several sets of benchmark transcriptomes with different

conditions. Using these simulated benchmark datasets as well as the real RNAseq data, and using

also various accuracy metrics, we performed a thorough assessment of currently available

methods based on various assembly conditions. We showed that the two currently available

ensemble methods that focus on thoroughness of assemblies (higher recall) retain significantly

high numbers of incorrectly assembled contigs. To demonstrate the value of a consensus

approach for transcriptome assembly, we present ConSemble, a consensus-based ensemble

assembly pipeline. It can combine the results from any types of four assemblers including both

de novo and genome-guided methods. Furthermore, for *de novo* assemblers, assemblies

generated using multiple kmer lengths are included. ConSemble successfully improves the

accuracy of transcriptome assembly over individual tools (both *de novo* and genome-guided).

Compared to other ensemble methods, ConSemble also shows consistent improvements with

fewer incorrectly assembled transcripts.

Results

Generation of simulated benchmark RNAseq data

To understand the exact performance of different transcriptome assembly methods, we first

generated simulated benchmark transcriptomes and corresponding RNAseq read sets as

illustrated in the Pipeline 1 in Additional file 1. Three benchmark datasets were generated. "No0-

NoAlt" and "Col0-Alt" are based on the *Arabidopsis thaliana* accessions Columbia (Col-0) and

Nossen (No-0). As the simplest benchmark dataset, no alternatively spliced transcripts (isoforms)

were included in "No0-NoAlt". Another benchmark dataset was generated from the human

reference genome (HG38). Table S1 in Additional file 3 shows the number and distribution of

transcripts included in each dataset.

Performance comparison of transcriptome assemblers using simulated

benchmark RNAseq data

For the performance analysis, we chose four genome-guided (Cufflinks [14], Bayesembler [22],

Scallop [23], and StringTie2 [24, 25]) and four *de novo* (Trinity [6], SOAPdenovo-Trans [26],

IDBA-Tran [27], and rnaSPAdes [28]) transcriptome assemblers. The experimental design we

used (see Table S2 in Additional file 3) allowed us to evaluate whether or not the transcriptome

assembly performance is affected by having isoforms, and for genome-guided methods, how

important the choice of the reference genome is. The assembly benchmarking process is

summarized in the Pipeline 2 in Additional file 1 (see **Materials and Methods** for further

details).

Genome-guided assemblers

The simplest experiment was to assemble the transcriptome where no alternative splicing

happened (the No0-NoAlt dataset) using the same No-0 genome as a reference (Test 1 in Table

S2 in Additional file 3). The genome-guided assemblers performed surprisingly poorly for this

dataset (Table S3 in Additional file 3). For all assemblies, only 71~75% of the assembled contigs

were correct (shown as Precision). StringTie2 recovered the most benchmark transcripts

(Recall=0.80) and Bayesembler the least (Recall=0.59).

The complexity of dealing with alternative splice forms is evident from the decreased

performance of all four assemblers even when using the same genome as the reference (Tests 3

and 5 in Table S3 in Additional file 3). While Bayesembler consistently produced the fewest

unique contigs, those assembled contigs were most accurate as shown by the consistently highest

values of Precision. Scallop and StringTie2, on the other hand, produced larger numbers of

unique contigs recovering more benchmark transcripts as shown by the larger Recall values.

The performance of all these assemblers was considerably worse when a divergent reference

genome was used as the reference (Tests 2, 4, and 6). While the total numbers of contigs

produced were similar to the corresponding test results with the same reference genomes (Tests

1, 3, and 5), the correctness of the contigs was greatly diminished (*e.g.*, F<0.34) where, on

average, only 32% of the assembled contigs were correct and only 33% of the benchmark

transcripts were recovered.

The results were similar when STAR [29] was used as the aligner (Table S4 in Additional

file 3). STAR with default parameters was shown to more accurately assign reads to the proper

genomic location than Tophat2 [30]. However, we found that the assembly results based on

STAR mapping were comparable to those based on Tophat2 showing no clear advantage in using

one aligner over the other. Since Tophat2 remains the most widely used read mapper for

genome-guided assemblies and is required for Bayesembler, only the results based on Tophat2

alignments are presented for further analyses.

The isoform assembly performance is compared further in Table S5 in Additional file 3.

When more than one isoform existed for a gene (Categories 3-7), Bayesembler and Scallop

recovered more isoforms (higher numbers in Categories 5-7). These two assemblers could

identify all isoforms for 50% or more of the genes that have isoforms (Category 6) or for about

one third of the genes that have three or more isoforms (Category 7). Among the four genome-

guided assemblers, only Bayesembler identified up to seven isoforms correctly, although the

success rates were not very high (Fig. S1 left panel, in Additional file 2). None of the assemblers

could identify all isoforms when there were more than six isoforms.

Contigs assembled by the four genome-guided assemblers are compared in Figs. 1 and 2.

While the 4-way intersection set always included the largest numbers of correctly assembled

contigs, which combination of assemblers shared more correctly assembled contigs depended on

the dataset and the reference genome used (Fig. 1). Some contigs were correctly assembled only

by one of the assemblers, while the majority of such contigs were false positives (incorrectly

assembled, shown in Fig. 2), illustrating the difficulty in choosing a single genome-guided

assembler for any transcriptome assembly problem.

De novo *assemblers*

All four *de novo* assemblers we tested overestimated the number of assembled contigs ranging

from 119% by IDBA-Tran for Test 9 to 203% by rnaSPAdes for Test 8 (Table S6 in Additional

file 3). The numbers of correctly assembled contigs were low for all four methods. Trinity

produced the most accurate assembly for all datasets (*e.g.,* C/I=1.05, F=0.57, and FDR=0.49 for

Test 7). All four assemblers performed worse when isoforms were included in the dataset (Tests

8 and 9). When more than one isoform existed for a gene (Categories 3-7 in Table S5 in

Additional file 3), often none (Category 3) or only one isoform (Category 4) could be correctly

assembled by the *de novo* assemblers. Trinity was most successful among the four *de novo*

assemblers in identifying multiple isoforms (higher numbers in Categories 5-7). It was the only

de novo assembler that identified four or more isoforms (Fig. S1 right panel in Additional file 2).

Of note is that all the *de novo* assemblies had higher accuracy compared to the genome-

guided assemblies generated with the reference differing from the strain sequenced. Trinity, for

example, assembled 41~51% of the contigs correctly (Precision) and recovered 50~64% of

benchmark transcripts (Recall), while all the genome-guided assemblers showed lower than 38%

for these statistics.

Similar to what we observed with genome-guided assemblers, the 4-way intersection set

included a large portion of correct contigs (40 ~ 45%) (Fig. 3A-C). Furthermore, while the large

portion of the contigs that were assembled only by a single method were incorrect, the 4-way

intersection set included only a small number of incorrect contigs (0.6~2%) (Fig. 3D-F). It

illustrates a risk of choosing a single *de novo* assembler.

Pooling the results of *de novo* assemblers with multiple kmer lengths

As described before, different sets of transcripts can be assembled optimally with different kmer

lengths. To explore if we can increase the number of correctly assembled contigs (TP) with *de*

novo assemblers, for each *de novo* assembler, we pooled the assemblies by combining the

contigs produced using multiple different kmer lengths. The range and number of kmer lengths

used for each method is as follows: IDBA-Tran with five kmers (20-60), SOAPdenovo-Trans

with 16 kmers (15-75), rnaSPAdes with 14 kmers (19-71), and Trinity with four kmers (19-31).

As expected, this approach increased TP for all assemblers (Table S7 in Additional file 3;

Recall>0.67 for Test 7, >0.60 for Test 8, and >0.52 for Test 9). However, it also accumulated a

disproportionately large number of incorrectly assembled contigs (*e.g.*, 226,697 more FP with

rnaSPAdes for Test 7). When we merged all these assemblies (taking the union set of assemblies

generated by all methods with multiple kmer lengths; "Merged" in Table S7 in Additional file 3),

the number of correctly assembled contigs (TP) increased further, although again at the cost of

accumulating disproportionately more incorrectly assembled contigs (FP). For example, for the

No0-NoAlt dataset (Test 7), merging all the *de novo* assemblies produced 14,770 correctly

assembled contigs (TP) from the 18,875 benchmark transcripts (Recall=0.78), but also had

549,859 incorrectly assembled contigs (FP). We also note that this merged assembly included

396 correctly assembled contigs that were produced only by the *de novo* assemblers (Fig. 4A).

More contigs were identified uniquely by the *de novo* methods for other datasets (554 for Col0-

Alt and 1,836 for Human, Fig. 4B and C) despite the reduced performance of the *de novo*

assemblers on these datasets.

Similar to what we observed before, the 4-way intersection set included the largest number of

correct contigs (70 ~ 83% of all correctly assembled contigs) (Fig. 5A-C). These numbers were

larger than those (TP) observed with genome-guided assemblers with different references (Tests

2, 4, and 6 in Table S3 in Additional file 3) and close to those with genome-guided assemblers

with the same references (Tests 1, 3, and 5 in Table S3 in Additional file 3). Notably, by taking

the 4-way intersection, the number of incorrect contigs was reduced significantly (Fig. 5D-F).

Furthermore, the vast majority of the contigs that were assembled only by a single method were

incorrect.

When all assemblies were merged including both genome-guided and *de novo* across

multiple kmers (shown as "All" in Table S5 in Additional file 3), many more isoforms were

recovered indicating different sets of isoforms were included in different assemblies.

Performance of the three ensemble assemblers

We next examined the performance of the three existing ensemble assemblers, TransBorrow

[18], EvidentialGene [16], and Concatenation [17]. For TransBorrow, the four genome-guided

assemblers, Cufflinks, Bayesembler, Scallop, and StringTie2, were used. For EvidentialGene, the

four *de novo* assemblers, IDBA-Tran, SOAPdenovo-Trans, rnaSPAdes, and Trinity, using the

same sets of multiple kmers for each assembler (39 assemblies in total) described in the previous

sections were used. For Concatenation, the three *de novo* assemblers, Trinity, IDBA-Tran, and

rnaSPAdes, were used. How exactly each of these methods was run is described in **Materials**

and Methods.

As shown in Table S8 in Additional file 3, compared to genome-guided based TransBorrow,

de novo ensemble methods, especially EvidentialGene, were not effective in filtering incorrectly

assembled contigs (FP). When isoforms were not included (the No0-NoAlt dataset),

EvidentialGene overestimated the number of transcripts significantly (417%). While

EvidentialGene recovered more benchmark transcripts (Recall=0.66) than Trinity (Recall=0.64),

the best of the *de novo* assemblers, many contigs were incorrectly assembled (Precision=0.16

compared to 0.51 for Trinity) leading to very low performance (F=0.26). While Concatenation

produced a lower number of incorrectly assembled contigs (Precision=0.47) compared to Trinity,

it did not achieve the accuracy level shown by Trinity (F=0.52 compared to F=0.57 by Trinity).

When isoforms were included in the dataset (the Col0-Alt and Human datasets), the poor

performance of the four *de novo* assemblers limited the potential for these *de novo* ensemble

assembly methods. EvidentialGene again had far more contigs than the benchmark transcriptome

(283% and 335% for the Col0-Alt and Human datasets, respectively) resulting in very low

performance (F=0.24 and 0.16, respectively). While Concatenation showed much higher

Precision with lower numbers of incorrectly assembled contigs than EvidentialGene, the overall

performance levels (F=0.51 and 0.38, respectively) did not exceed those obtained by Trinity

(F=0.53 and 0.45, respectively).

The genome-guided ensemble method, TransBorrow, showed significantly higher accuracy

especially when the dataset did not include isoforms (No0-NoAlt) with large TP and small FP

and FN achieving ~70% Precision and 83% Recall. For more complex transcriptome datasets,

however, the performance decreased significantly. Although it still performed better than

Concatenation for the Human dataset (~50% for both Precision and Recall), for this dataset,

TransBorrow did not show significantly different assembly performance compared to any

individual genome-guided assemblers. Moreover, TransBorrow could assemble a surprisingly

small number of contigs (<12%) from the Col0-Alt dataset. The authors mentioned about the

possible issues associated to the complexity in building colored graphs depending on the

assembly included [18]. The Col0-Alt dataset may have presented one such challenge.

ConSemble, a new consensus-based ensemble assembly pipeline

As described before, the two *de novo* ensemble methods (EvidentialGene and Concatenation)

cluster the contigs and choose the representatives for the final assemblies. These approaches did

not significantly improve the overall transcriptome assembly performance compared to the best

individual *de novo* assembler. However, as we observed, the "Merged" *de novo* assembly

correctly assembled up to 78% of the transcripts in the benchmark (Table S7 in Additional file

3). Furthermore, as shown in Fig. 5, as the number of *de novo* assemblers sharing a unique contig

sequence increases, the likelihood that the contig is correctly assembled also increases. A large

majority of contigs produced by all four of the *de novo* assemblers, especially for the No0-NoAlt

dataset, were correctly assembled (12,268 out of 13,858 or 89% as shown in Fig. 5A and D),

while the majority of those produced by only one or two assemblers were incorrectly assembled

(Fig. 5D-F). By utilizing such consensus information, it is possible to increase the number of

correctly assembled contigs and at the same time reduce the number of incorrectly assembled

contigs, improving the overall assembly performance. To demonstrate this approach, we present

a new consensus-based ensemble transcriptome assembly pipeline, ConSemble, in which contigs

shared by at least three of the four assemblers are retained for the final assembly.

The Pipeline 3 in Additional file 1 summarizes the process of the ConSemble transcriptome

assembly. Four transcriptome assembly methods, either *de novo* or genome-guided, are used to

generate four "contig libraries". For the *de novo* based pipeline (A), each *de novo* assembler is

used with a given set of multiple kmer lengths, producing a total of 39 assemblies across the four

methods. The assembly sets from each method are pooled to produce four contig sets. In these

pooled contig sets, unique contigs are identified based on the coded protein sequences, producing

four "pooled unique" contig sets. Each of the four pooled unique contig sets is used as the

"contig library" from each method. For the genome-guided based pipeline (B), the assembled

contig set from each method is used as the "contig library". Contigs that share coded protein

sequences in at least three of the four contig libraries are selected for the final assembly output.

Based on the tradeoff between FN and FP (described below), we decided to take two intersection

sets of contigs: the intersection of at least three or the intersection of the four contig libraries.

These assemblies are called ConSemble3+ and ConSemble4, respectively.

The 5' and 3' boundaries of the transcripts are handled differently depending on the

assembler. This affects the overall contig length and potentially the sequence of the untranslated

regions, although it does not affect the predicted open reading frame (ORF) and the coded

protein sequence. Therefore, to minimize the impact of such differing behaviors between

assemblers, we concentrated only on the longest ORFs produced by ORFfinder [31] to compare

assembled contigs. When contigs with differing nucleotide sequences code entirely identical

protein sequences, the one with the shortest nucleotide sequence is chosen and included in the

final assembly. This is done to minimize the risk of including any chimera or over-assembled

sequences. Although all redundant contigs and those with no predicted protein product are

excluded from the final assembly, these contigs are saved in separate files and available for

additional analyses. ConSemble is implemented in Perl. Source codes and test data are freely

available at: http://bioinfolab.unl.edu/emlab/consemble/

The transcriptome assembly performance using ConSemble was compared against the four

genome-guided, the four *de novo*, and the three ensemble methods (Fig. 6 and Table S9 in

Additional file 3). The genome-guided ConSemble showed significant reduction in miss-

assembly (FP) without sacrificing correct assembly (TP). For the No0-NoAlt dataset, it achieved

very high correct-to-incorrect contig ratios (C/I) especially with ConSemble3+g and

ConSemble4g (C/I>9.5, Precision>0.90). For all benchmark datasets, ConSemble3+g assembly

showed balanced and high accuracy (F=0.82 for No0-NoAlt, F=0.67 for Col0-Alt, and F=0.52

for HG38), which was consistently better than TransBorrow as well as individual genome-guided

methods.

The *de novo* based ConSemble also effectively filtered out the incorrectly assembled contigs.

For the No0-NoAlt dataset, 13,352 of 20,263 contigs produced by ConSemble3+d (107% of the

reference) were correctly assembled (Precision=0.66, Recall=0.71), achieving the highest C/I

(1.93) and F (0.68) among any *de novo* (including both individual and ensemble) approach.

Although ConSemble3+d slightly overestimated the number of sequences present in the Col0-Alt

and Human benchmark datasets (109~112%), it again successfully reduced the numbers of

incorrectly assembled contigs outperforming all other *de novo* methods (Precision=0.53 and

0.47, Recall=0.59 and 0.52, and F=0.56 and 0.49, respectively).

The limited ability of the most *de novo* assemblers to reconstruct multiple isoforms limited

ConSemble's ability to accurately recover all of the isoforms present in the merged assembly.

However, although ConSemble3+d recovered fewer isoforms especially for genes with five or

more isoforms than Trinity, ConSemble3+d performed significantly better than other *de novo*

assemblers in terms of isoform identification (Figs. S1 right panel and S2 in Additional file 2).

More isoforms were identified by genome-guided based ConSemble3+g (Fig. S2 in Additional

file 2). However, because many isoforms were identified in only a limited number of genome-

guided assemblies (Fig. S1 left panel in Additional file 2), it also limits the ability of

ConSemble3+g to identify multiple isoforms especially for genes with five or more isoforms.

ConSemble assembly can be performed based on a smaller or larger number of the assembly

overlap. When only two or more assembly overlap was required (ConSemble2+g and

ConSemble2+d in Table S9 in Additional file 3), more correctly assembled contigs (TP) were

recovered but at the cost of disproportionally more FP leading to higher Recall but lower

Precision than ConSemble3+ (*e.g.,* Recall=0.84 and 0.74 and Precistion=0.79 and 0.27,

respectively, for No0-NoAlt). When the 4-way consensus was used (ConSemble4g and

ConSemble4d), while fewer correctly assembled contigs were recovered than ConSemble3+

(*e.g.*, Recall=0.50 and 0.65 for No0-NoAlt, respectively), it reduced FP significantly with only

marginally increased FN. This led to significantly higher Precision *(e.g.*, 0.95 and 0.89 for No0-

Alt, respectively) compared to ConSemble3+. Based on these results, we chose ConSemble3+ as

the main output of the ConSemble pipeline. The ConSemble4 assembly is also useful as part of

post-processing of the ConSemble assembly to obtain a contig set with the highest confidence.

Comparison of nucleotide- and protein-level performance

In addition to the protein-level performance described above, the quality of assembled contigs at

the nucleotide sequence level was examined using DETONATE [19]. DETONATE provides a

reference-free model-based RSEM-EVAL score as well as reference-based scores (F_1 and KC).

The RSEM-EVAL metric given by DETONATE evaluates the transcriptome assembly

performance by comparing the assembled nucleotide sequences to the original reads [19].

Because genome-guided assembly returns the sequence of the reference genome rather than the

RNAseq data, using RSEM-EVAL on assemblies where the RNAseq data did not originate from

the reference genome used can lead to poor results. Therefore, for genome-guided assemblies,

only those produced using the same reference genome as the simulated RNAseq library (Tests 1,

3, and 5) were examined.

Many of the trends seen in the protein-level performance were also reflected in the nucleotide

assembly quality (Table S10 in Additional file 3). In general, the assemblies with higher F at the

protein level (Tables S3, S6, S8, and S9 in Additional file 3) also had relatively high

DETONATE scores (RSEM-EVAL and KC). Among the ensemble assemblers, most often

TransBorrow (except for Col0-Alt) and ConSemble3+g had the best scores in F and/or

DETONATE scores. While EvidentialGene consistently showed the lowest F at the protein level

as well as F_1 both at the nucleotide and contig levels, it was found to perform somewhat better

when the RSEM-EVAL scores were considered. As even a single nucleotide indel can have

major impacts on the predicted protein sequences, it is important to evaluate performance

statistics at both nucleotide and protein levels [32].

RSEM-EVAL and KC tend to provide higher scores for assemblies with longer sequences

that account for, *e.g.*, more of the kmers in the RNAseq data or the reference over the precision

of the contig sequence. To illustrate this issue, using the same ConSemble *de novo* assembly

pipeline, we generated two other collections of contig sets. In one set (ConSemble3+dLong),

instead of the shortest nucleotide sequences for the default ConSemble3+d, the longest

sequences were chosen as the representative contigs from those coding identical protein

sequences. In another set (ConSemble3+dHigh), contig sequences with the highest RSEM-

EVAL scores were chosen instead. Although these three ConSemble3+d assemblies have the

same protein-level accuracy scores (for the same set of protein sequences), DETONATE scores

were significantly different (Table S10 in Additional file 3). By choosing the shortest nucleotide

sequences, ConSemble assemblies tend to truncate the untranslated regions (UTRs) of the

transcripts. ConSemble3+dLong and ConSemble3+dHigh showed similar and much higher

DETONATE scores indicating longer contigs are scored higher.

Impact of using lower percent identity thresholds

The results presented so far are based on the numbers of correctly assembled contigs where the

assembled sequences need to be fully 100% identical to the reference protein sequences. In

practice, this is more strict than necessary for many downstream analyses. We therefore

examined the impact of using lower identity thresholds on the assembly metrics.

The number of correctly assembled contigs identified at varied thresholds are shown in Fig.

S3 in Additional file 2. The increase in the performance metrics was most significant when the

threshold was reduced from 100% to 98%. The increase was generally proportional across all

methods with the exceptions of the genome-guided assemblies using different reference genomes

and EvidentialGene. With the 100% threshold, the performance of the genome-guided methods

was significantly lower than *de novo* methods when different reference genomes were used.

However, with less strict thresholds (<100%), their performance quickly recovered and became

better than that of some of the *de novo* assemblers, although it remained lower than genome-

guided assemblers using the same reference genome down to the lowest threshold (90%) used.

For the No0-NoAlt dataset, EvidentialGene recovered more TP with relaxed thresholds and

resulted in Recall scores higher than other *de novo* methods (including both ensemble and

individual methods) (Table S11 in Additional file 3). However, since EvidentialGene retained a

large number of FP, the C/I was the lowest and the accuracy level was kept very low (F<0.31).

ConSemble3+d remained the best performing non-genome guided method for all three datasets.

Regardless of the threshold, ConSemble3+g maintained the highest accuracy among all methods.

Assembling the real plant transcriptomes

Assembly performance was further tested using the real RNAseq data from three plant species.

We included a strain of a model dicot *A. thaliana* where a high-quality genome and

transcriptome information is available, another dicot *Momordica charantia* (bitter melon, a

diploid), as well as the hexaploidal cotton (*Gossypium hirsutum*). This selection represents a

range of ploidies, which challenges transcriptome assembly methods. In contrast to testing using

simulated benchmark data, when the real RNAseq data are used, we do not know the actual true

positives and hence, we cannot evaluate the assembly performance using the same set of

statistics. We instead used the number of genes identified from the "Eudicotyledons" dataset of

Benchmarking Universal Single-Copy Orthologs (BUSCO) [20] to evaluate the thoroughness of

each assembly. For *A. thaliana* Col-0, the number of contigs matching with those in the

Araport11 reference transcriptome at the protein level was counted. For the nucleotide level, the

reference-free model-based RSEM-EVAL scores were also included. The results are summarized

in Table 1.

For *A. thaliana* Col-0, all ensemble assemblers except TransBorrow produced more contigs

that matched Araport sequences and BUSCOs and had slightly better RSEM-EVAL scores than

the *de novo* assemblers. The very low performance by TransBorrow was consistent to what we

observed with the Col0-Alt benchmark dataset. All ensemble assemblers had better or

comparable performance compared to the genome-guided assemblers. While ConSemble3+g

found slightly fewer BUSCOs compared to SOAPdenovo-Trans, it had the second best RSEM-

EVAL following StringTie2. Among the ensemble methods (excluding TransBorrow),

EvidentialGene assembled the most BUSCOs but the fewest Araport-matching contigs and had

the lowest RSEM-EVAL score.

For *M. charantia*, all ensemble methods including TransBorrow recovered more BUSCOs

than *de novo* assemblers. EvidentialGene, Concatenation, and TransBorrow also recovered more

BUSCOs than the highest performing genome-guided method, StringTie2. Although

EvidentialGene recovered the most BUSCOs, it produced a significantly more contigs (324% of

the reference) indicating a high FP rate. While ConSemble3+d did not find as many BUSCOs as

StringTie2 did, it had the best RSEM-EVAL score among all assemblers. Concatenation

produced the fewest contigs, which was even fewer than those produced by Scallop, the best

genome-guided assembler. Among the genome-guided assemblers, Scallop and StringTie2 had

similar numbers of BUSCOs as well as RSEM-EVAL scores, while the number of contigs

produced by StringTie2 was close to the number reported for the reference transcriptome.

For the hexaploidal cotton (*G. hirsutum*), all methods produced significantly more contigs

than the 70,478 transcripts reported (except TransBorrow where the assembly largely failed). All

genome-guided methods showed high numbers of BUSCOs with StringTie2 producing the most.

Among the *de novo* assemblers, only Trinity produced a comparable number of BUSCOs. The

remaining *de novo* assemblers produced far fewer BUSCOs despite the high numbers of contigs

assembled, suggesting high FP rates. Both EvidentialGene and Concatenation produced large

numbers of BUSCOs. However, EvidentialGene produced more than ten times the number of

sequences in the reference transcriptome and had a lower RSEM-EVAL score. ConSemble3+d

showed a significantly smaller number of BUSCOs and one of the worst RSEM-EVAL scores.

This may be due to the impact of a high ploidy [33]. It is discussed further below.

Discussion

Despite the number of transcriptome assemblers available, there is still no single assembler or

assembly strategy that performs best in all situations. Our simulation study clearly showed that

every assembler correctly assembled a set of contigs while missing sequences correctly

assembled by other methods. When the reference genome was available from the same strain, the

genome-guided assemblers outperformed *de novo* and most ensemble assemblers. However, if

such reference sequences were not available, the performance of genome-guided assemblers

dropped below that of *de novo* assemblers. Ensemble assembly approaches can overcome some

of the limitations of individual assemblers. Our analysis showed that without requiring a

reference genome, ensemble *de novo* methods achieved the assembly performance comparable to

or higher than that of individual genome-guided methods.

Both EvidentialGene and Concatenation generally kept more of the correctly assembled

contigs produced by the individual *de novo* assemblers indicated by high Recall and BUSCO

scores. However, our simulation study showed that they also had many incorrectly assembled

contigs that decreased the overall assembly accuracy. Instead of simply choosing representative

contigs, ConSemble, used consensus-based information to filter more reliable contigs. By

pooling multiple assemblies, especially also pooling those generated using multiple kmer lengths

for *de novo* methods, ConSemble increases the completeness of the assembled transcriptome. By

taking the consensus contig set from four contig libraries, both ConSemble3+g and

ConSemble3+d reduce the incorrectly assembled contigs (FPs) significantly. This was observed

in much lower numbers of incorrectly assembled contigs than those obtained by the other

ensemble methods as well as all individual methods. Furthermore, the ConSemble4d and

ConSemble4g assemblies provide the contig sets with even higher confidence. For the three

benchmark datasets, ConSemble3+d showed comparable accuracies to the genome-guided

assemblers with ideal reference genomes and outperformed all individual *de novo* assemblers

and the individual genome-guided assemblers without good reference genomes.

Any ensemble method will necessarily be limited by the quality of the individual assemblies

it is based on. If no individual method can correctly assemble a contig, no ensemble assembly

can recover it. ConSemble uses the overlap of any three of the four individual assemblies

(ConSemble3+). Therefore, any contigs that are correctly assembled by only one or two

assemblers are omitted from the final contig set. For the three benchmark transcriptome

assemblies, 10~20% of correctly assembled contigs (1,418 of 14,770, 1,988 of 11,179, and 2,139

of 11,267 in the No0-NoAlt, Col0-Alt, and Human datasets, respectively) were discarded in this

manner in ConSemble3+d. In Fig. S4 in Additional file 2, we examined how the assembly

performance is affected by expression levels of transcripts. It shows that assembly performance

are affected by the expression levels regardless of the datasets, and the *de novo* methods are

affected much more significantly than the genome-guided methods. Furthermore, the ConSemble

assembly (both ConSemble3+g and ConSemble3+d) performance was affected more for

transcripts whose expression levels are low (*e.g.,* bin # 1-3 in Fig. S4 in Additional file 2). As we

described before, especially when genes have many isoforms (*e.g.*, five or more) both

ConSemble3+d and ConSemble3+g missed many of such isoforms (Fig. S2 in Additional file 2).

However, as shown in "All Assemblies" in Fig. S1 (Additional file 2), many of these isoforms in

fact existed in at least one of the assemblies that were used as the contig libraries for ConSemble

assembly. These isoforms must have been unique to a single contig library or shared only by two

contig libraries, and subsequently filtered out during the process of consensus assembly. Since

the expression levels of isoforms from a gene are known to vary significantly, it is possible that

the isoforms that were missed by ConSemble3+ assembly were those with low expression. This

may also explain lower than expected levels of performance observed with all assemblers

especially when isoforms were included in the test datasets. To recover such low expression

transcripts, more refined assembly strategies beyond the current simple consensus approach need

to be considered.

A similar effect is found when performance among the assemblers included in ConSemble

varies widely. In the hexaploid cotton assembly, the quality of the ConSemble assembly

deteriorated noticeably. This result suggests that the increased ploidy may decrease the

likelihood that the true sequences are reconstructed by multiple *de novo* methods, consistent with

the reduced overlap between *de novo* assemblers in simulated polyploidy benchmarks [33]. Since

other ensemble approaches showed much larger BUSCOs for the cotton, it would be interesting

to consider an integrated approach. Further benchmarking studies incorporating varied ploidies

are necessary to determine the extent and impact of this issue.

ConSemble for *de novo* methods requires multiple different assemblers to run multiple times

over a range of kmer lengths. Therefore, the availability of computational resources could

become a limiting factor for deciding the number of assemblies ConSemble can utilize.

However, as each assembly process is independent, these jobs can be run in parallel depending

on the availability of the resources. This makes the overall assembly time roughly equivalent to

the time needed for the longest individual assembly reducing the necessary computational time

significantly.

In summary, we presented ConSemble, a consensus-based ensemble transcriptome assembly

pipeline. It can be used with either *de novo* or genome-guided methods. Using the ConSemble

pipeline with *de novo* methods, a transcriptome assembly produced showed the quality rivals that

of genome-guided assembly without requiring a reference genome and outperforms *de novo* and

other ensemble strategies. It achieves high performance by retaining the majority of the contigs

correctly assembled by individual assemblers and removing a significant number of

misassembled contigs. Further work is needed for identifying more correctly assembled contigs

especially when multiple, especially lowly expressed, isoforms exist or in the case of

polyploidies. Improvements are needed to retain more of the contigs that are correctly assembled

only by a small number of assemblers without accumulating incorrectly assembled contigs. We

also showed the importance of developing realistic simulated RNAseq benchmark datasets that

allow evaluating the performance of transcriptome assemblers under various conditions. It

provides the only means of assessing the accuracy of the transcripts assembled directly and

quantitatively.

Materials and Methods

Genomes and transcriptomes used

RNAseq simulations and genome-guided assemblies of the *A. thaliana* accession Columbia (Col-

0) were based on the TAIR reference genome (version 9) [34] and the atRTD transcriptome

dataset (version 3) [35]. The atRTD dataset was chosen over the TAIR transcriptome (version

10) due to the higher prevalence of isoforms in the atRTD dataset, allowing better testing of each

assembler's ability to reconstruct alternative transcripts. RNAseq simulation and genome-guided

assemblies of the *A. thaliana* accession Nossen (No-0) were based on the assembly by Gan *et al.*

[36] downloaded from the 1001 genomes project [37; accession CS6805]. The Human RNAseq

simulations were based on the HG38 reference genome and transcriptome [38;

GCF_000001405.39]. To evaluate the impact of using a different reference for this RNAseq

library, the reads were also mapped to the HuaXia1 (HX1) reference genome (available from

http://hx1.wglab.org).

Three datasets were used for the assembly of real RNAseq data. The *A. thaliana* Col-0

dataset consisting of 116M 76bp read pairs sequenced using Illumina Genome Analyzer II is

from Marquez *et al.* [39], which is available at National Center for Biotechnology Information

(NCBI) (SRA047499). For *M. charantia* (bitter melon), a dataset consisting of 228M 100bp read

pairs was produced by sequencing of RNA samples from leaves, roots, flowers, and seeds using

Illumina HiSeq 2500 (NCBI: SRR3535137, SRR3535138, SRR3535144, and SRR3535149).

The reference genome was from Urasaki *et al.* [40] (NCBI: BDCS01000001–BDCS01001052).

For *G. hirsutum* (upland cotton), an RNAseq dataset consisting of 117M 200bp read pairs was

produced from RNA samples from leaves, roots, flowers, and seeds using Illumina HiSeq 4000

(NCBI: SRR7689126- SRR7689129). The genome assembly used as the reference is the

allotetraploid L. acc. TM-1 [41; http://www.cottongen.org].

Production of simulated benchmark transcriptomes and read sets

Simulated benchmark transcriptomes and corresponding RNAseq read sets were produced from

A. thaliana and humans as follows. A modified Flux Simulator v1.2.1 pipeline [42] illustrated in

the Pipeline 1 in Additional file 1 was used to produce ~250M 76bp read pairs for each dataset.

The No0-NoAlt transcriptome was generated based on the *A. thaliana* No-0 genomic sequence

and no alternative splice events were included. The Col0-Alt transcriptome was generated based

on the *A. thaliana* Col-0 genomic sequence and the version 3 atRTD transcriptome model. The

expressed transcriptome in this dataset contains zero to nine alternative splice events (one to ten

isoforms) per gene where only the isoforms unique at the protein level were included. The

transcriptome for the Human dataset was based on the HG38 reference genome and

transcriptome. It contains zero to 14 alternative splice events (1 to 15 isoforms). Only reference

transcripts with full coverage of RNAseq data (all positions are required to be covered by at least

one read) were included in the benchmark datasets, as transcripts without full coverage cannot be

correctly assembled as a single contig. Table S1 in Additional file 3 shows the number and

distribution of transcripts for each dataset. All benchmark datasets used in this study are

available from: http://bioinfolab.unl.edu/emlab/consemble/

Read processing

The read pairs generated by Flux Simulator were quality filtered using Erne-filter 2.0 [43] using

the 'ultra-sensitive' flag with a minimum average quality of q20 and in paired-end mode. The

remaining reads were normalized using Khmer [44] with a kmer length of 32, an expected

coverage of 50x, and in paired-end mode. As normalization works at the read level, kmer-length

selection for this step has minimal impact on the unique kmers kept, and hence on the

performance of the assembly.

Genome-guided assembly

The normalized reads were first mapped to the reference genomes using Tophat2 2.0.14 with

default settings [45]. Assemblies were performed using Cufflinks 2.2.1 [14], Bayesembler 1.2.0

[22], Scallop 0.10.2 [23], and StringTie2 2.0 [25]. Each assembler was executed on the default

settings. Assembled contig sequences were extracted using the gtf_to_fasta module from

Tophat2. The two *Arabidopsis* RNAseq datasets (No0-NoAlt and Col0-Alt) and the two Human

RNAseq datasets (HG38 and HX1) were assembled using each of the two reference genomes. To

compare the impact of using different read mappers on assembly quality, additional assemblies

were also performed using STAR 2.4.2a [29] for read mapping.

De novo assembly

De novo assembly was performed using Trinity 2.4.0 [6], SOAPdenovo-Trans 1.0.3 [26], IDBA-

Tran 1.1.1 [27], and rnaSPAdes 3.10.0 (using the rnaspades.py script) [46]. Each of the

assemblers was run using default settings as well as using multiple kmer lengths. With the

default setting, IDBA-Tran assembles across multiple kmer lengths and merges the results for the

final assembly. Trinity and SOAPdenovo-Trans use a single default value (25 and 23,

respectively). rnaSPAdes chooses the kmer length depending on the dataset. For this study, a

kmer length of 55 was chosen for both No0-NoAlt and Col0-Alt read sets and a kmer length of

37 was chosen for the Human set. Each method was also run with a range of kmer lengths (k)

with increments (i) as follows: IDBA-Tran with k=20-60 and i=10, SOAPdenovo-Trans with

k=15-75 and i=4, rnaSPAdes with k=19-71 and i=4, and Trinity with k=19-31 and i=4.

The following assemblers were excluded from this study after the preliminary analysis due to

their high computational requirements (both resources and time), issues with program stability,

or both: Velvet 1.2.10 [47] with Oases 0.2.08 [48], and Mira 4.0.2 [49].

Ensemble methods

For EvidentialGene (version 2017.03.09) [9], we chose the "okay" nucleotide contig set (okay.fa

and okalt.fa) produced by the tr2aacds.pl pipeline as the final output for our comparative

analysis. The assembly was performed using the same sets of four *de novo* assemblers and kmer

lengths as described above resulting in 39 assemblies in total. Concatenation originally used

three assemblers, Trinity, IDBA-Tran, and CLC (https://www.qiagenbioinformatics.com/), with

only one kmer length each [17]. For this study, we tested all combinations of three from the four

aforementioned *de novo* assemblers and kmer lengths. CLC was excluded from this study

because it is only available under a commercial license. Based on the numbers of correctly and

incorrectly assembled contigs, we decided to use the following three assemblies as the best

combination for Concatenation: IDBA-Tran with k=50, Trinity with k=31, and rnaSPAdes with

k=55. For TransBorrow (version 1.3) [18], the GTF files for the assemblies with the same

reference genome for each of the four genome-guided assemblers (Cufflinks, Bayesembler,

Scallop, and StringTie2) were manually merged into a single file. The TransBorrow assembly

was performed using default parameters.

Assembly benchmarking

The experimental design we used to evaluate the assembly performance is summarized in Table

S2 in Additional file 3. The assembly benchmarking process is summarized in the Pipeline 2 in

Additional file 1. Each contig assembly was evaluated based on the accuracy of the coded

protein sequences in the ORFs predicted by ORFfinder [31]. This was done to avoid issues with

variation in how the assemblers define the 3' and 5'-ends of the contigs. Contigs with any amino

acid mismatches and gaps compared to the benchmark protein sequences were considered

incorrectly assembled. Only contigs that fully covered the benchmark protein sequences were

considered correctly assembled.

Performance statistics

The overall performance of the assembly is determined as follows:

• **TP** (true positives): number of correctly assembled contigs

• **FP** (false positives): number of incorrectly assembled contigs

• **FN** (false negatives): number of benchmark transcripts that are not assembled (including also

when transcripts are correctly but only partially assembled)

• **C/I** (correct/incorrect ratio) = TP/FP

• **Recall** (or sensitivity) = TP/(TP+FN)

• **Precision** = TP/(TP+FP)

• **F-measure** (F or F_1) = 2(TP)/(2(TP)+FP+FN)

• **CSI (critical success index)** = TP/(TP+FP+FN)

• **FDR** (false discovery rate) = 1 - Precision = FP/(TP+FP)

The higher C/I shows that among the assembled contigs (predicted positives) there are more

correctly assembled contigs than mis-assembled contigs. This is similar to Precision where the

proportion of correctly assembled contigs is shown relative to all assembled contigs. Recall also

shows the proportion of correctly assembled contigs but relative to the number of transcripts in

the reference (actual positives). F-measure is a combined metric, the harmonic mean of Precision

and Recall. It therefore balances the concerns of Recall and Precision. F-measure also does not

require true negatives (TN) to be counted. This is useful because TN is not defined for

transcriptome assembly in this benchmarking. CSI can be also calculated while the regular

accuracy score defined as (TP+TN)/(TP+FP+TN+FN) cannot be calculated. As indicated in the

equations, although CSI is highly correlated to F, when the TP rate is low, CSI increases more

slowly than F. Therefore, the assembler performance difference at low TP rates can be

distinguished more clearly by F.

Isoform detection performance

As described before, only isoforms that produce distinct protein sequences are considered

different. This approach does not account for biologically important alternative splice events in

the UTRs, which can affect protein trafficking or translation without affecting protein sequences.

To simplify the analysis, the performance of the isoform detection was evaluated solely by the

number of correctly assembled isoforms without considering the abundance of each isoform.

Contigs that did not match completely any of the isoforms included in the benchmark dataset

were counted as incorrectly assembled (FP).

Lower identity threshold

To evaluate the effect of using % identity thresholds lower than 100% to identify TPs, identities

between each assembled contig and the benchmark transcript at the translated protein level was

also calculated by dividing the edit distance by the length of the global alignment using the

python library for Edlib (version 1.3.8post2) [50].

Venn diagram generation

The contig overlap between assemblies was evaluated based on the coded protein sequences. The

Venn diagrams were generated using jvenn (version 1.0) [51].

Assembly performance at the nucleotide level

The quality of the nucleotide sequences produced by all of the assembly methods were examined

using DETONATE (version 1.11) [19]. DETONATE provides a reference-free model-based

RSEM-EVAL score as well as reference-based scores including the nucleotide and contig-level

F_1 and KC (kmer compression). RSEM-EVAL scores how well the contigs are supported by the

RNAseq data as well as the compactness of an assembly based on their joint probability. The

thresholds used to identify the contig-level TP to calculate F_1 score (see the formula above) is

99% identity and having ≤1% of insertions and deletions. The KC score is a combination of the

weighted kmer recall and inverse compression rate, the latter of which penalizes large

assemblies.

BUSCO

710 The thoroughness of the assemblies generated from the real plant RNAseq libraries was assessed

711 based on the number of complete genes identified from the Eudicotyledons obd10 dataset of

712 BUSCO (version 3.1.0) [20].

Transcript expression level analysis

715 To determine the impact of expression level on transcript assembly, the benchmark

716 transcriptome was divided into ten equally sized bins by the expression level. The proportion of

717 transcripts in each bin correctly assembled is determined by the number of benchmark transcripts

718 with at least one exact match (full length with no gaps or mismatches) in an assembly divided by

719 the total number of transcripts in the bin.

Declarations

Ethics approval and consent to participate

723 Not applicable.

Consent for publication

726 Not applicable.

Availability of data and materials

The source codes, benchmark datasets, and other datasets used and analyzed in this study are available from: http://bioinfolab.unl.edu/emlab/consemble/ .

Competing interests

The authors declare that they have no competing interests.

Funding

This work has been supported by the National Science Foundation under Grant Nos. 1339385 to JS, EBC, and ENM and 1557417 to EBC and ENM. The funder had no role in study design, data collection and analysis, decision to publish, or preparation of work included in this submission.

Author's contributions

AV and ENM conceived and designed the research. AV wrote and tested the programs. XL, XHY, JS, and EBC generated RNAseq data. AV, SB, KK, and ENM analyzed and interpreted the results. JSD also interpreted the results. AV and ENM wrote the manuscript. All authors read, discussed, revised, and approved the manuscript.

Acknowledgements

747   We would like to thank Dr. Don Gilbert (Indiana University) for his discussions and critical

748   feedback regarding EvidentialGene and its performance.

References

1. Huang X, Chen XG, Armbruster PA. Comparative performance of transcriptome assembly methods for non-model organisms. BMC Genomics. 2016;17:523.

2. Wang S, Gribskov M. Comprehensive evaluation of *de novo* transcriptome assembly programs and their effects on differential gene expression analysis. Bioinformatics. 2017;33:327-333.

3. Conesa A, Madrigal P, Tarazona S, Gomez-Cabrero D, Cervera A, McPherson A *et al*. A survey of best practices for RNA-seq data analysis. Genome Biol. 2016;17:13.

4. Voshall A, Moriyama EN. Next-Generation Transcriptome Assembly: Strategies and Performance Analysis. In: Bioinformatics in the Era of Post Genomics and Big Data. Adburakhmonov IY (editor). Rijeka: IntechOpen; 2018.

5. Simonis M, Atanur SS, Linsen S, Guryev V, Ruzius FP, Game L *et al*. Genetic basis of transcriptome differences between the founder strains of the rat HXB/BXH recombinant inbred panel. Genome Biol. 2012;13:r31.

6. Grabherr MG, Haas BJ, Yassour M, Levin JZ, Thompson DA, Amit I *et al*. Full-length transcriptome assembly from RNA-Seq data without a reference genome. Nature biotechnology. 2011;29:644-652.

7. Martin JA, Wang Z. Next-generation transcriptome assembly. Nat Rev Genet. 2011;12:671-682.

8. Gruenheit N, Deusch O, Esser C, Becker M, Voelckel C, Lockhart P. Cutoffs and k-mers: implications from a transcriptome study in allopolyploid plants. BMC Genomics. 2012;13:92.

9. Gilbert D. Gene-omes built from mRNA seq not genome DNA. In: 7th Annual Arthropod Genomics Symposium: June 13-June 15 2013; Notre Dame, IN.

10. Durai DA, Schulz MH. Informed kmer selection for de novo transcriptome assembly. Bioinformatics. 2016;32:1670-1677.

11. Rana SB, Zadlock FJt, Zhang Z, Murphy WR, Bentivegna CS. Comparison of De Novo

Transcriptome Assemblers and k-mer Strategies Using the Killifish, Fundulus heteroclitus.

PloS one. 2016;11:e0153104.

12. Holding ML, Margres MJ, Mason AJ, Parkinson CL, Rokyta DR. Evaluating the Performance

of De Novo Assembly Methods for Venom-Gland Transcriptomics. Toxins (Basel). 2018;10.

13. Holzer M, Marz M. De novo transcriptome assembly: A comprehensive cross-species

comparison of short-read RNA-Seq assemblers. Gigascience. 2019;8.

14. Trapnell C, Roberts A, Goff L, Pertea G, Kim D, Kelley DR *et al.* Differential gene and transcript

expression analysis of RNA-seq experiments with TopHat and Cufflinks. Nat Protoc.

2012;7:562-578.

15. Smith-Unna R, Boursnell C, Patro R, Hibberd JM, Kelly S. TransRate: reference-free quality

assessment of *de novo* transcriptome assemblies. Genome Res. 2016;26:1134-1144.

16. Gilbert DG. Genes of the pig, *Sus scrofa*, reconstructed with EvidentialGene. PeerJ.

2019;7:e6374.

17. Cerveau N, Jackson DJ. Combining independent de novo assemblies optimizes the coding

transcriptome for nonconventional model eukaryotic organisms. BMC Bioinformatics.

2016;17:525.

18. Yu T, Mu Z, Fang Z, Liu X, Gao X, Liu J. TransBorrow: genome-guided transcriptome

assembly by borrowing assemblies from different assemblers. Genome Res. 2020;30:1181-

1190.

19. Li B, Fillmore N, Bai Y, Collins M, Thomson JA, Stewart R *et al.* Evaluation of *de novo*

transcriptome assemblies from RNA-Seq data. Genome Biol. 2014;15:553.

20. Simao FA, Waterhouse RM, Ioannidis P, Kriventseva EV, Zdobnov EM. BUSCO: assessing

genome assembly and annotation completeness with single-copy orthologs. Bioinformatics.

2015;31:3210-3212.

21. Yang Y, Gribskov M. The evaluation of RNA-Seq *de novo* assembly by PacBio long read

sequencing. bioRxiv. 2019:735621.

22. Maretty L, Sibbesen JA, Krogh A. Bayesian transcriptome assembly. Genome Biol.
2014;15:501.

23. Shao M, Kingsford C. Accurate assembly of transcripts through phase-preserving graph
decomposition. Nature biotechnology. 2017;35:1167-1169.

24. Pertea M, Pertea GM, Antonescu CM, Chang TC, Mendell JT, Salzberg SL. StringTie enables
improved reconstruction of a transcriptome from RNA-seq reads. Nature biotechnology.
2015;33:290-295.

25. Kovaka S, Zimin AV, Pertea GM, Razaghi R, Salzberg SL, Pertea M. Transcriptome assembly
from long-read RNA-seq alignments with StringTie2. Genome Biol. 2019;20:278.

26. Xie Y, Wu G, Tang J, Luo R, Patterson J, Liu S *et al*. SOAPdenovo-Trans: de novo
transcriptome assembly with short RNA-Seq reads. Bioinformatics. 2014;30:1660-1666.

27. Peng Y, Leung HC, Yiu SM, Lv MJ, Zhu XG, Chin FY. IDBA-tran: a more robust de novo de
Bruijn graph assembler for transcriptomes with uneven expression levels. Bioinformatics.
2013;29:i326-334.

28. Bushmanova E, Antipov D, Lapidus A, Prjibelski AD. rnaSPAdes: a de novo transcriptome
assembler and its application to RNA-Seq data. Gigascience. 2019;8.

29. Dobin A, Davis CA, Schlesinger F, Drenkow J, Zaleski C, Jha S *et al*. STAR: ultrafast universal
RNA-seq aligner. Bioinformatics. 2013;29:15-21.

30. Baruzzo G, Hayer KE, Kim EJ, Di Camillo B, FitzGerald GA, Grant GR. Simulation-based
comprehensive benchmarking of RNA-seq aligners. Nat Methods. 2017;14:135-139.

31. Wheeler DL, Church DM, Federhen S, Lash AE, Madden TL, Pontius JU *et al*. Database
resources of the National Center for Biotechnology. Nucleic Acids Res. 2003;31:28-33.

32. Watson M, Warr A. Errors in long-read assemblies can critically affect protein prediction.
Nature biotechnology. 2019;37:124-126.

33. Voshall A, Moriyama EN. Next-generation transcriptome assembly and analysis: Impact of
ploidy. Methods. 2020;176:14-24.

34. Swarbreck D, Wilks C, Lamesch P, Berardini TZ, Garcia-Hernandez M, Foerster H *et al*. The

Arabidopsis Information Resource (TAIR): gene structure and function annotation. Nucleic

Acids Res. 2008;36:D1009-1014.

35. Zhang R, Calixto CP, Tzioutziou NA, James AB, Simpson CG, Guo W *et al*. AtRTD - a

comprehensive reference transcript dataset resource for accurate quantification of transcript-

specific expression in *Arabidopsis thaliana*. New Phytol. 2015;208:96-101.

36. Gan X, Stegle O, Behr J, Steffen JG, Drewe P, Hildebrand KL *et al*. Multiple reference

genomes and transcriptomes for Arabidopsis thaliana. Nature. 2011;477:419-423.

37. 1001 Genomes Consortium. 1,135 genomes reveal the global pattern of polymorphism in

Arabidopsis thaliana. Cell. 2016;166:481-491.

38. Schneider VA, Graves-Lindsay T, Howe K, Bouk N, Chen HC, Kitts PA *et al*. Evaluation of

GRCh38 and *de novo* haploid genome assemblies demonstrates the enduring quality of the

reference assembly. Genome Res. 2017;27:849-864.

39. Marquez Y, Brown JW, Simpson C, Barta A, Kalyna M. Transcriptome survey reveals

increased complexity of the alternative splicing landscape in Arabidopsis. Genome Res.

2012;22:1184-1195.

40. Urasaki N, Takagi H, Natsume S, Uemura A, Taniai N, Miyagi N *et al*. Draft genome sequence

of bitter gourd (*Momordica charantia*), a vegetable and medicinal plant in tropical and

subtropical regions. DNA Res. 2017;24:51-58.

41. Zhang T, Hu Y, Jiang W, Fang L, Guan X, Chen J *et al*. Sequencing of allotetraploid cotton

(*Gossypium hirsutum* L. acc. TM-1) provides a resource for fiber improvement. Nature

Biotechnol. 2015;33:531.

42. Griebel T, Zacher B, Ribeca P, Raineri E, Lacroix V, Guigo R *et al*. Modelling and simulating

generic RNA-Seq experiments with the flux simulator. Nucleic Acids Res. 2012;40:10073-

10083.

43. Del Fabbro C, Scalabrin S, Morgante M, Giorgi FM. An extensive evaluation of read trimming

effects on Illumina NGS data analysis. PloS one. 2013;8:e85024.

44. Crusoe MR, Alameldin HF, Awad S, Boucher E, Caldwell A, Cartwright R *et al*. The khmer
software package: enabling efficient nucleotide sequence analysis. F1000Res. 2015;4:900.

45. Trapnell C, Pachter L, Salzberg SL. TopHat: discovering splice junctions with RNA-Seq.
Bioinformatics. 2009;25:1105-1111.

46. Bankevich A, Nurk S, Antipov D, Gurevich AA, Dvorkin M, Kulikov AS *et al*. SPAdes: a new
genome assembly algorithm and its applications to single-cell sequencing. J Comput Biol.
2012;19:455-477.

47. Zerbino DR, Birney E. Velvet: algorithms for de novo short read assembly using de Bruijn
graphs. Genome Res. 2008;18:821-829.

48. Schulz MH, Zerbino DR, Vingron M, Birney E. Oases: robust de novo RNA-seq assembly
across the dynamic range of expression levels. Bioinformatics. 2012;28:1086-1092.

49. Chevreux B, Pfisterer T, Drescher B, Driesel AJ, Muller WEG, Wetter T *et al*. Using the
miraEST assembler for reliable and automated mRNA transcript assembly and SNP detection
in sequenced ESTs. Genome Res. 2004;14:1147-1159.

50. Sosic M, Sikic M. Edlib: a C/C ++ library for fast, exact sequence alignment using edit distance.
Bioinformatics. 2017;33:1394-1395.

51. Bardou P, Mariette J, Escudie F, Djemiel C, Klopp C. jvenn: an interactive Venn diagram
viewer. BMC Bioinformatics. 2014;15:293.

52. Cheng CY, Krishnakumar V, Chan AP, Thibaud-Nissen F, Schobel S, Town CD. Araport11: a
complete reannotation of the *Arabidopsis thaliana* reference genome. Plant J. 2017;89:789-
804.

Addtional files

Additional file 1

Format: PDF

File content: Pipelines 1-3.

Additional file 2

Format: PDF

File content: Supplementary Figs. S1-S4.

Additional file 3

Format: PDF

File content: Supplementary Tables S1-S13.

Table 1. Performance analysis of real plant transcriptome assembly

Assembler	*A. thaliana* Col-0 (48,359)[a]			*M. charantia* (45,859)[a]			*G. hirsutum* (70,478)[a]		
	# of contigs[b]	BUSCO[c]	EVAL[d]	# of contigs[b]	BUSCO[c]	EVAL[d]	# of contigs[b]	BUSCO[c]	EVAL[d]
[Genome-guided]									
Bayesembler	45,583 (94) [10,611]	1,677	-3.18	44,524 (97)	1,629	-1.99	NA[e]	NA[e]	NA[e]
Cufflinks	34,771 (72) [9,886]	1,593	-2.95	38,655 (84)	1,662	-1.64	98,590 (140)	1,908	-3.44
Scallop	73,172 (151) [13,272]	1,841	-2.82	68,593 (150)	1,855	-1.49	183,625 (261)	1,967	-3.32
StringTie2	37,211 (77) [12,619]	1,819	-2.82	44,149 (90)	1,847	-1.51	108,389 (154)	1,998	-3.24
[*De novo*]									
IDBA-Tran	52,982 (110) [6,871]	1,287	-2.92	106,170 (232)	657	-1.82	215,470 (306)	411	-5.71
rnaSPAdes	101,444 (210) [8,521]	1,475	-2.74	91,791 (200)	1,051	-1.50	211,024 (299)	1,533	-3.66
SOAPdenovo	68,141 (141) [8,973]	1,689	-2.93	115,117 (251)	1,776	-1.47	224,718 (318)	971	-6.22
Trinity	50,023 (103) [7,501]	1,573	-2.89	90,347 (197)	1,779	-1.44	212,852 (302)	1,921	-3.60
[Ensemble]									
EvidentialGene	83,749 (173) [10,892]	1,899	-2.87	148,938 (324)	1,983	-1.60	726,828 (1,031)	2,070	-4.07
Concatenation	70,444 (146) [12,184]	1,855	-2.71	66,613 (145)	1,923	-1.53	97,419 (138)	2,010	-3.76
ConSemble3+d	49,713 (103) [12,659]	1,833	-2.73	90,781 (198)	1,858	-1.42	114,974 (163)	1,312	-5.53
ConSemble3+g	24,355 (50) [11,322]	1,587	-1.18	24,699 (74)	1,718	-2.20	49,530 (54)	1,689	-1.13
TransBorrow	1,521 (3) [734]	29	-2.40	53,191 (116)	1,896	-1.66	6,234 (9)	79	-2.83

[a]Number of protein-coding transcripts reported [34, 40, 41].

[b]Proportion (%) of unique protein sequences in the assembly relative to the number of proteins in the reference transcriptome is shown in parentheses. Number of contigs whose sequences matched those in the Araport11 reference transcriptome [52] is shown in square brackets.

[c]Number of complete BUSCOs identified from the 2,121 orthologs in the Eudicot set.

[d]RSEM-EVAL scores (x10^{-9}) from DETONATE.

[e]Bayesembler was unable to run on this dataset.

Figure legends

Fig. 1 Numbers of correctly assembled contigs shared between the four genome-guided assemblers in the Arabidopsis (No0-NoAlt and Col0-Alt) and Human (HG38) benchmark simulations. All contigs were compared at the protein level.

Fig. 2 Numbers of incorrectly assembled contigs shared between the four genome-guided assemblers in the Arabidopsis (No0-NoAlt and Col0-Alt) and Human (HG38) benchmark simulations. All contigs were compared at the protein level.

Fig. 3 Numbers of assembled contigs shared between the four *de novo* assemblers. The numbers of correctly (A, B, and C) and incorrectly (D, E, and F) assembled contigs are shown. The benchmark datasets used are No0-NoAlt (A and D), Col0-Alt (B and E), and Human HG38 (C and F). The default settings were used for all methods. All contigs were compared at the protein level.

Fig. 4 Numbers of the correctly (A, B, and C) and incorrectly assembled contigs (D, E, and F) shared between merged *de novo* and genome-guided assemblies. The "Merged" assemblies in Table S7 in Additional file 3 were used for the *de novo* assembly datasets. The genome-guided assembly is the union set of the assemblies generated by the four genome-guided methods using the same reference genomes (Tests 1, 3, and 5 in Table S2 in Additional file 3). All contigs were compared at the protein level.

Fig. 5 Numbers of assembled contigs shared between the four pooled *de novo* assemblers. The numbers of correctly (A, B, and C) and incorrectly (D, E, and F) assembled

contigs are shown. The benchmark datasets used are No0-NoAlt (A and D), Col0-Alt (B and E),

and Human HG38 (C and F). For each method, results based on multiple kmer lengths were

pooled. All contigs were compared at the protein level.

Fig. 6 Comparison of assembler performance on simulated benchmark datasets (A: No0-

NoAlt, B: Col0-Alt, and C: Human). For the *de novo* assemblers, results shown were obtained

with their default settings.

A

Genome-guided · *De novo* · Ensemble

B

Genome-guided · *De novo* · Ensemble

C

Genome-guided · *De novo* · Ensemble

■ Correctly assembled   □ Incorrectly assembled   — # of actual transcripts