Representation Learning of Resting State fMRI with Variational Autoencoder

Jung-Hoon Kim[1,3], Yizhen Zhang[2], Kuan Han[2],

Zheyu Wen[2], Minkyu Choi[2], Zhongming Liu[1,2*]

[1]Department of Biomedical Engineering, University of Michigan

[2]Department of Electrical Engineering and Computer Science, University of Michigan

[3]Weldon School of Biomedical Engineering, Purdue University

*Correspondence

Zhongming Liu, PhD

Associate Professor

Department of Biomedical Engineering

Department of Electrical Engineering and Computer Science

University of Michigan, Ann Arbor

Email: zmliu@umich.edu

Abstract

Resting state functional magnetic resonance imaging (rsfMRI) data exhibits complex but structured patterns. However, the underlying origins are unclear and entangled in rsfMRI data. Here we establish a variational auto-encoder, as a generative model trainable with unsupervised learning, to disentangle the unknown sources of rsfMRI activity. After being trained with large data from the Human Connectome Project, the model has learned to represent and generate patterns of cortical activity and connectivity using latent variables. The latent representation and its trajectory represent the spatiotemporal characteristics of rsfMRI activity. The latent variables reflect the principal gradients of the latent trajectory and drive activity changes in cortical networks. Latent representations are clustered by both individuals and brain states. Representational geometry captured as covariance or correlation between latent variables, rather than cortical connectivity, can be used as a more reliable feature to accurately identify subjects from a large group, even if only a short period of data is available per subjects.

INTRODUCTION

The brain is active even at rest, showing complex activity patterns measurable with resting state fMRI (rsfMRI) (Fox and Raichle, 2007). It is widely recognized that rsfMRI activity is shaped by how the brain is wired, or the brain connectome (Sporns et al., 2005). Inter-regional correlations of rsfMRI activity are often used to report functional connectivity (Biswal et al., 1995) and map brain networks for individuals (Finn et al., 2015) or populations in various behavioral (Smith et al., 2009) or disease states (Fox et al., 2014). However, it remains largely unclear where rsfMRI activity comes from (Leopold and Maier, 2012; Lu et al., 2019), whereas understanding its origins is critical to interpretation of any rsfMRI pattern or dynamics (Winder et al., 2017).

Prior findings suggest a multitude of sources (or causes) for rsfMRI activity (Bianciardi et al., 2009), including but not limited to fluctuations in neurophysiology (Mantini et al., 2007), arousal (Chang et al., 2016), unconstrained cognition (Chou et al., 2017), non-neuronal physiology (Birn et al., 2008), head motion (Power et al., 2014) etc. These sources only partially account for rsfMRI activity and may be entangled not only among themselves but also with other sources that are left out simply because they are hard to specify or probe in a task-free state (Leopold and Maier, 2012). An inclusive study would benefit from using a data-driven approach to uncover and disentangle all plausible but hidden sources from rsfMRI data itself, without having to presume the sources to whatever are experimentally observable. To be effective, such an approach should be able to infer sources from rsfMRI data and generate new rsfMRI data from sources, while being able to account for complex and nonlinear relationships between the sources and the data.

These requirements lead us to deep learning, or representation learning with deep

neural networks (LeCun et al., 2015), as a nonlinear method for blind source separation,

in contrast to its linear counterparts, e.g. independent component analysis (Beckmann

and Smith, 2004; Calhoun et al., 2001; Smith et al., 2012). For brain research, deep

learning models has provided testable models of the brain in terms of neural computation

for sensory and language processing (Han et al., 2019; Kell et al., 2018; Khaligh-Razavi

and Kriegeskorte, 2014; Richards et al., 2019; Wen et al., 2018; Yamins and DiCarlo,

2016; Zhang et al., 2020). Deep learning has also been increasingly used as a generic

family of machine learning tools to learn features from fMRI data. See (Khosla et al.,

2019b) for a review. Most applications are in the regime of supervised learning. Typically,

a neural network takes an fMRI-based input data and is trained to generate an output that

optimally matches the ground truth for a task, such as individual identification (Chen and

Hu, 2018; Wang et al., 2019), prediction of gender, age, or intelligence (Fan et al., 2020;

Gadgil et al., 2020; Plis et al., 2014), disease classification (Seo et al., 2019; Suk et al.,

2016; Wang et al., 2020; Yang et al., 2019; Zou et al., 2017). The labels required for

supervised learning are often orders of magnitude smaller in size than the fMRI data itself,

which has a high dimension in both space and time. As a result, the prior studies often

limit the model capacity by using a shallow network and/or limit the input data to activity

at the region of interest (ROI) level (Chen and Hu, 2018; Dvornek et al., 2018; Koppe et

al., 2019; Matsubara et al., 2019; Suk et al., 2016; Wang et al., 2019; Wang et al., 2020)

or reduce it to functional connectivity (D'Souza et al., 2019; Fan et al., 2020; Kawahara

et al., 2017; Kim and Lee, 2016; Riaz et al., 2020; Seo et al., 2019; Venkatesh et al., 2019;

Yang et al., 2019; Zhao et al., 2018). It is also uncertain to what extent representations

learned for a specific task would be generalizable to other tasks. It is further debatable

whether deep neural networks with supervised learning are currently superior to more

conventional and simpler methods (He et al., 2020).

For these considerations, unsupervised learning is more preferable for uncovering

the underlying causes that drive intrinsic brain activity regardless of any task or disease.

We choose to use the Variational Auto-Encoder (VAE) (Higgins et al., 2017; Kingma and

Welling, 2013), for unsupervised learning of the increasing "big data" in rsfMRI without

requiring any label or narrowly focusing on any downstream task. Unlike auto-encoder,

VAE is a generative model capable of synthesizing new data similar to the training data,

and it regularizes the latent space with *a priori* spherical Gaussian distributions. These

properties allow the representation learned to be expressed in terms of latent variables

that encode the disentangled causes of the data. Our emphasis on disentangling latent

representations sets this work apart from several prior work based on the auto-encoder

implemented in various forms of deep neural networks (Cui et al., 2019; Huang et al.,

2017; Liu et al., 2020a; Makkie et al., 2019; Suk et al., 2016; Zhao et al., 2018). Briefly in

this study, we designed and trained a VAE model to represent rsfMRI data in terms of its

latent sources and tested its ability to explain and generate rsfMRI data. We characterized

the time evolving trajectory of latent representation and factorized its gradients by

principal components. We also visualized the representational gradients, clusters, and

geometries within and across individuals, as a way to characterize brain networks and

their dynamic interactions. Lastly, we tested the use of this model for characterizing

individual variations and identifying individuals from their rsfMRI data (Finn et al., 2015),

as a starting example of its applications.

Methods

Data

We used rsfMRI data from 650 healthy subjects randomly chosen from the Q2 release by HCP (Van Essen et al., 2013). For each subject, we used two sessions of rsfMRI data acquired from different days with either the right-to-left or left-to-right phase encoding. Each session included 1,200 time points separated by 0.72s. Following minimal preprocessing (Glasser et al., 2013) and automatic denoising with ICA (or the ICA-FIX) (Griffanti et al., 2014; Salimi-Khorshidi et al., 2014), we applied voxel-wise detrending (regressing out a 3rd-order polynomial function), bandpass filtering (from 0.01 to 0.1 Hz), and normalization (to zero mean and unitary variance). We further separated the data into three sets, including 100, 50, or 500 subjects for training, validating, or testing the VAE model, respectively. The validation dataset was used to determine the hyper-parameters used in the VAE model. The testing data were neither seen nor used by the model during training or validation. This held-out data was used to test the generalizability of the model across different datasets. For an exploratory analysis, we additionally tested the model with rsfMRI data that did not go through denoising with ICA-FIX to evaluate the model performance against presumably noisier rsfMRI data.

Geometric reformatting

We converted the rsfMRI data from 3-D cortical surfaces to 2-D grids in order to structure the rsfMRI pattern as an image to ease the application of convolutional neural networks. As illustrated in Figure 1.a, we inflated each hemisphere to a sphere by using

FreeSurfer (Fischl, 2012). For each location on the spherical surface, we used cart2sph.m

in MATLAB to convert its cartesian coordinates (x, y, z) to spherical coordinates (a, e),

which reported the azimuth and elevation angles in a range from $-\pi$ to π and from $-\frac{\pi}{2}$ to

$\frac{\pi}{2}$, respectively. We defined a 192×192 grid to resample the spherical surface with respect

to azimuth and *sin*(elevation) such that the resampled locations were uniformly distributed

at approximation (Supplementary Figure 1). We used the nearest-neighbor interpolation

to convert data from the 3-D surface to the 2-D grid, and vice versa.

Figure 1. Variational Auto-Encoder (VAE). (a) Geometric reformatting. The cortical distribution of fMRI
activity is converted onto a spherical surface and then to an image by evenly resampling the spherical
surface with respect to sin(e) and a, where e and a are elevation and azimuth, respectively. **(b) Encoder-**
decoder architecture. The encoder and the decoder each contain 5 convolutional layers connected in
series. In the encoder, each layer (numbered from 1 to 5) outputs a feature map with the size of 96x96x64,
48x48x128, 24x24x128, 12x12x256, or 6x6x256, respectively. In layer 1, 32 kernels are applied to 192x192
flattened images of each hemisphere separately, and output feature maps are concatenated along the

kernel dimension, resulting in a feature map with 64 channels. In the decoder, each layer (numbered from
8 to 12) outputs a feature map with a size of 6x6x256, 12x12x256, 24x24x128, 48x48x128, or 96x96x64,
respectively. The operation at each layer is specified as follows. 1: convolution (kernel size=8, stride=2,
padding=3) and rectified nonlinearity; 2-5: convolution (kernel size=4, stride=2, padding=1) and rectified
nonlinearity; 6: fully connected layer and re-parameterization; 7: fully connected layer and rectified
nonlinearity; 8-11: transposed convolution (kernel size=4, stride=2, padding=1) and rectified nonlinearity;
12: transposed convolution (kernel size=8, stride=2, padding=3). The blue and red boundaries highlight the
input and output images for the left and right hemispheres, respectively.
150

Variational autoencoder

We designed a β-VAE model (Higgins et al., 2017), a variation of VAE (Kingma

and Welling, 2013), to learn representations of rsfMRI spatial patterns. This model

included an encoder and a decoder (Figure 1.b). The encoder converted an fMRI map to

a probabilistic distribution of 256 latent variables. Each latent variable was a Gaussian

random variable with a mean and a standard deviation. The decoder sampled the latent

distribution to reconstruct the input fMRI map or generate a new map, which appeared

similar to what would be observable with fMRI. The encoder stacked five convolutional

layers and one fully connected layer. Every convolutional layer applied linear convolution

and rectified its output (Nair and Hinton, 2010). The 1^{st} layer applied 8×8 convolution

separately to the input from each hemisphere and concatenated its output. To the feature

maps concatenated across both hemispheres, the 2^{nd} through 5^{th} layers applied 4×4

convolution. Since a spherical pattern is circularly continuous with respect to the azimuth,

we applied circular padding to the boundaries of azimuth for the flattened 2-D map but

applied zero padding to the boundaries of elevation. Such padding was intended to avoid

artifacts when otherwise applying convolution near those boundaries. The fully connected

layer applied linear weighting and yielded the mean and standard deviation that described

the normal distribution of each latent variable. The decoder used nearly the same

architecture as the encoder but connected the layers in the reverse order for

transformation from the latent space back to the input space. Figure 1.b illustrates the

model architecture.

We trained the VAE model to reconstruct input while constraining the distribution

of every latent variable to be close to an independent and standard normal distribution.

Specifically, using the training data, we optimized the encoding parameters, ϕ, and the

decoding parameters, θ, to minimize the loss function as below.

176                  $$L(x) = \|x - x'\|_2^2 + \beta \cdot D_{KL}[N(\mu_z, \sigma_z) \| N(0, I)] \qquad (1)$$

where x is the input data combined across the left and right hemispheres, x' is the

corresponding output from the model, $N(\mu_z, \sigma_z)$ is the posterior normal distribution of the

latent variables, z, with their mean and standard deviation denoted as μ_z and σ_z, $N(0, I)$

is an independent and standard normal distribution as the prior distribution of the latent

variables, D_{KL} measures the Kullback-Leibler (K-L) divergence between the posterior and

prior distributions, and β is a hyperparameter balancing the two terms in the loss function.

Part of the medial cortical surface that corresponds to corpus callosum (i.e. white matter)

was excluded from training such that the learned model was intended to merely represent

the activity of cortical gray matter. To train the model, we used $\beta = 10$ and stochastic

gradient descent (batch size=128, initial learning rate=10^{-4}, and 100 epochs) and Adam

optimizer (Kingma and Ba, 2014) implemented in PyTorch (v*1.2.0*). The learning rate

decayed by a factor of 10 every 20 epochs.

We determined the hyperparameters by exploring and testing different parameter

settings with the validation dataset. Specifically, we explored four values (1, 5, 10, 15) for

β and chose $\beta = 10$ to balance the reconstruction performance vs. the disentanglement

(or independence) of latent variables (Figure 2) – the two terms in the loss function shown

in Eq. (1). We also explored several options for the number of layers and the learning rate,

and finalized those parameters based on the loss evaluated with the validation dataset

(Supplementary Figure 2 and 3). Note that with the training strategies described above,

only VAE model with 12 layers were able to reduce both reconstruction loss and D_{KL} when

$\beta = 10$.

Figure 2. Validation losses for the VAE models with different values for β in Eq. (1). $\beta = 10$ shows a

reasonable trade-off between the reconstruction loss and the Kullback–Leibler divergence on the validation

dataset.

Synthesizing rsfMRI functional connectivity

We used the trained VAE to synthesize rsfMRI data from random samples of latent

variables. To synthesize a vector in the latent space, we drew a random sample of every

latent variable independently from a standard normal distribution. The synthesized vector

passed through the decoder in VAE, generating a cortical pattern. Repeating this process,

we synthesized 12,000 cortical patterns as data used for seed-based correlation analysis.

As examples, we explored three seed locations within V1, IPS, and PCC and calculated

the functional connectivity to each seed based on the Pearson correlation coefficient. The

MNI coordinates of the seed in V1, IPS, and PCC were (7, -83, 2), (26, -66, 48), and (0,

57, 27), respectively (Jarrett, 2009). In addition, we performed a similar analysis without

limiting to the seed locations. Instead, we calculated the functional connectivity between

each pair of parcels as defined in a 360-parcel atlas of the whole cortex (Glasser et al.,

2016).

For comparison, we similarly calculated seed-based or parcel-to-parcel functional

connectivity with experimental rsfMRI data concatenated across a varying number (1, 5,

10, 50, and 100) of subjects in HCP. We compared the functional connectivity pattern

observed with synthesized and experimental data and repeated the comparison 20 times.

At each time, we generated a different set of synthesized data while using experimental

data from a different subset of subjects. The comparison was thus randomly repeated.

Defining a principal basis set in the latent space

By our design, the VAE model encodes the spatial pattern of fMRI activity and does

not represent the temporal dynamics explicitly. The distribution of every latent variable is

constrained to be close to a standard normal distribution independent of one another, for

the K-L divergence term in the loss function in Eq. (1). This implies that the latent variables

in the VAE model are not unique. An arbitrary rotation of a tentative set of latent variables

would arrive at a new set of latent variables that span the same latent space and satisfy

the same learning objective.

To identify a unique set of latent variables, we exploited the trajectory of the latent

representation. Specifically, for the fMRI data in the testing set (concatenated across 500

subjects), we encoded the fMRI pattern observed at every time into a point (or vector)

embedded in the latent space. As time progressed, this point moved in the latent space

along a trajectory that represented the temporal dynamics of fMRI activity.

In a first-order differential analysis, we evaluated the displacement (or difference)

of the latent representation from every time point to its next. To this time-difference vector

(or the latent gradient), we further applied singular vector decomposition and used the

singular vectors to define a unique basis set of the latent space. As such, each singular

vector was a re-defined latent variable, while the corresponding singular value indicated

its importance in explaining the latent gradient of cortical activity. In other words, the

trajectory was more likely to move along the direction represented by a singular vector

with a larger singular value than that with a smaller singular value.

We further interpreted and visualized the top-10 latent variables defined as the

singular vectors with the largest 10 singular values. For this purpose, we decoded each

of these latent variables onto the cortical surface by using the decoder in the VAE model.

Note that the latent variables were related to cortical patterns through nonlinear functions.

We evenly sampled each latent variable of interest from -5 to 5, while keeping other latent

variables to zero. We mapped the decoded cortical pattern and characterized its variation

due to the variation of a single latent variable. We quantified the variation separately for

each cortical location in terms of the standard deviation multiplied by a sign. The sign of

standard deviation map was determined by measuring the sign of Pearson correlation

coefficient between the decoded values of each cortical location and the samples of the

given latent variable.

Clustering in the latent space

We encoded the rsfMRI spatial pattern at every time point for 500 testing subjects,

yielding 600,000 vectors in the latent space. We used k-means clustering with 1-cosine

distance (based on "kmeans" in Matlab) to group those vectors to 21 clusters. The choice

of k=21 was empirical but made intentionally to be consistent to a prior study with a similar

motivation (Smith et al., 2012). This choice was within a reasonable range for the number

of resting state networks as reported in literature (Smith et al., 2009; Yeo et al., 2011).

Beyond this single choice, we explored other numbers of clusters to ensure that k=21 was

a reasonable choice for the distribution of latent representation. Specifically, we varied k

from 1 to 100. Given each choice, we ran the k-means clustering for the testing data

(n=500 subjects), identified the clusters, calculated the centroid of each cluster, and

summed the distance to the centroid within every cluster. We further plotted the sum of

distance as a function of k and ensured that k=21 was around the "elbow" of the plot, as

a useful, but not strict, rule of thumb.

Given k-means clustering with k=21, we re-ordered individual time points by their

cluster membership and compared the distance between time points within and between

clusters. We also evaluated the relationships among different clusters by calculating the

distance between the centroids of individual clusters and we further grouped clusters into

super-clusters organized in a multi-level hierarchy visualized as a dendrogram (by using

"linkage" in Matlab).

To visualize and interpret each cluster, we further converted the cluster centroid to

a corresponding cortical pattern by using the VAE's decoder. The resulting cortical pattern

was scaled such that its maximal absolute value equaled 1. This pattern was considered

as a functional cortical network. To further evaluated how each cortical network changed

its activity in time, we defined and evaluated the cluster-wise activity as the cosine affinity

between the centroid of each cluster and the latent representation of fMRI activity at every

time. As such, a cluster increased its activity when the latent representation moved toward

the centroid of that cluster or decreased its activity when the representation moved away

from that centroid but towards the centroid of another cluster. After this analysis was done

separately for each session and subject, we averaged the cluster-wise activity across

subjects. Then we compared the group-level activity between sessions and across

clusters, and tested the statistical significance with a non-parametric permutation test

(false discovery rate q<0.01), for which the time points were randomly shuffled for 10,000

trials to yield a null distribution.

Individual variation

To evaluate the individual variation, we compared the latent representations of the

fMRI data from different individuals. In an exploratory analysis, we randomly selected a

small (n=20) subset of subjects. We chose 20 subjects to ease visualization and intuitive

demonstration, before scaling up the analysis to 500 subjects. For each of the 20 subjects,

we converted the fMRI activities, instance by instance, to the representations in the latent

space. To visualize and compare subject-wise representations, we used the t-distributed

Stochastic Neighbor Embedding (t-SNE) method to visualize the 256-dimensional latent

representations (color-coded by subjects) in a two-dimensional space. We calculated the

Silhouette index to measure how similar the latent representation was within the same

subject vs. between different subjects.

Individual identification

After the exploratory analysis above, we evaluated the individual variation across

n=500 subjects. For the distribution of subject-wise latent representation, the first moment

was the mean and the second moment was the covariance, which indicated the location

and geometry of the subject-wise latent representation, respectively. We tested the use

of the first moment (mean) or the second moment (covariance) as the subject-identifying

feature.

In the testing data set, every individual had rsfMRI data acquired for two separate

sessions. From the first session, we extracted the feature from every subject and stored

it as the subject-identifying key in a database that included a population of 500 subjects.

Given this database, we tested the accuracy of retrieving any subject's identity by using

the feature extracted from the second session as a query to match against all keys in the

database. The goodness of match was evaluated as the cosine similarity or the Pearson

correlation coefficient when the query and the key were based on the first moment (mean)

or the second moment (covariance) of the subject-wise representation, respectively. The

accuracy of individual identification was evaluated as the percentage by which the correct

identity was retrieved as one of the best 1, 5, or 10 matches, yielding the namely top-1,

5, or 10 accuracy.

For comparison, we compared the performance of individual identification based

on the above latent-space feature vs. the similar feature evaluated in the cortical space.

The cortical-space features extracted with a similar method as previously reported in

(Finn et al., 2015). Specifically, the FC between brain regions (or connectome) was

calculated as features for individual identification. It is worth noting that the cortical

connectome and covariance of latent representation, although they are nominally different

terms, can both be viewed as the representational geometry of brain activity in the cortical

space (for the connectome) or the latent space (for the covariance of latent

representation). In addition, we may also cast both notions as the functional connectivity

profile in the cortical space or the latent space. Given such conceptual connections, we

evaluated the FC between every pair of 360 cortical parcels defined in an established

atlas (Glasser et al., 2016) and used the FC-based connectome as the feature for

individual identification (Finn et al., 2015). We compared the connectome-based

identification accuracy with that based on the FC profile (or representational geometry) in

the latent space for a varying population size (from n=5 to 500 subjects) or a varying

length of data per subject (from 9 to 180 s). We repeated the above analysis 100 times,

each time with a different subset of the testing data and averaged the identification

accuracy across the repeated tests.

Comparison with linear latent space

The VAE model described herein provided nonlinear mapping from the cortical

space to the latent space (through the encoder) and in reverse (through the decoder).

Such reversible mapping could be conventionally done through linear matrix operations,

such as the principal component analysis (PCA) and independent component analysis

(ICA). Hence, we compared the distribution and geometry of the rsfMRI representation in

the nonlinear latent space obtained with VAE vs. the linear latent space obtained with

PCA or ICA. For such comparison, we used PCA or ICA trained with the training data to

represent rsfMRI data in the testing dataset, while keeping the linear latent space of the

same (256) dimension as its nonlinear counterpart. We compared the performance of

reconstructing fMRI patterns from their latent representations (see results in Fig. 4). In

addition, we also compared PCA or ICA vs. VAE for characterizing individual variation or

performing individual identification by using the representation in the PCA or ICA-derived

linear latent space for the same analyses as used for the representation in the VAE-based

nonlinear latent space (see results in Figs. 8 and 10).

Results

VAE compressed rsfMRI maps

Inspired by its success in artificial intelligence (Higgins et al., 2017; Kingma and

Welling, 2013), we designed a VAE model in order to disentangle the generative factors

underlying rsfMRI activity. The model was trained to represent and reconstruct rsfMRI

data with a set of latent variables that were constrained to be as independent as possible.

The hyper-parameter, β, which expressed the weighting of independence among latent

variables in the overall learning objective, was initially explored for different values (1, 5,

10, 15) before being finalized to $\beta=10$ – a setting that led to a reasonable trade-off of the

model performance vs. constraint as demonstrated with the validation dataset (Fig. 2).

The model used a pair of convolutional and deconvolutional neural networks in an

encoder-decoder architecture (Figure 1.b). The encoder transformed any rsfMRI pattern,

formatted as an image on a regular 2D grid (Figure 1.a), to the probability distributions of

256 latent variables. The decoder used samples of the latent variables to reconstruct or

generate an fMRI map. Using data from HCP (WU-Minn HCP Quarter 2) (Van Essen et

al., 2013), we first trained the model with rsfMRI maps from 100 subjects and then tested

it with rsfMRI data from 500 other subjects.

Figure 3. Image reconstruction using VAE. A series of cortical patterns are reconstructed through the

VAE model. Among them, five original cortical patterns (upper panel) and their corresponding reconstruction

through VAE (bottom panel) are visualized for comparison. For an example region (green circle), the time

series of the original activity (black line) and the reconstructed activity (red line) are plotted for comparison.

After being trained, the model could compress any fMRI map to a low-dimensional latent

space and restore the map from the latent representation separately for every time point

(Figure 3). The compression resulted in spatial blurring comparable to the effect of spatial

smoothing with 4-6 mm full width at half maximum (FWHM) (Figure 4). Given fMRI data

spatially smoothed to a varying extent (FWHM from 1 to 10 mm), VAE showed either

comparable or better performance of reconstruction than its linear counterparts (PCA and

ICA), when VAE, PCA, and ICA all used the same dimension (256) for their latent spaces

(Figure 4.a). The difference in reconstruction performance between VAE and PCA or ICA

was marginal but statistically significant (repeated measures ANOVA followed by post-

hoc paired t-test, false discovery rate $q<0.05$), for all smoothing levels except FWHM=1

mm (Figure 4.b). These results suggest that the latent representation obtained with VAE

preserved the spatial and temporal characteristics of rsfMRI, despite a modest but

acceptable loss in spatial resolution and specificity.

Figure 4. **RsfMRI data compression and reconstruction with VAE vs. PCA and ICA**. (**a**) For illustration,

three example maps of fMRI activity, before (1st row) and after (2nd row) being smoothed (FWHM=6mm),

are shown in comparison with the corresponding maps reconstructed with VAE (3rd row), PCA (4th row), and

ICA (5th row) trained to compress and reconstruct the training data from 100 subjects with 256 variables or
components. (**b**) For quantitative comparison, the reconstruction performance, in terms of the percentage
of variance in the fMRI images as explained by the model reconstruction, is shown for VAE, PCA, and ICA
as a function of FWHM (from 1 to 10 mm) applied to the spatial smoothing of the fMRI images. The error
bar stands for the standard error of mean.
402

VAE synthesized correlated fMRI activity

We asked whether the decoder in the VAE, as a generative model of fMRI activity,

had learned the putative mechanisms by which rsfMRI activity patterns arise from brain

networks. To address this question, we randomly sampled every latent variable from a

standard normal distribution and used the decoder to synthesize 12,000 rsfMRI maps

(equivalent to 10 subjects at 1,200 time points per subject).

We calculated the seed-based correlations by using the VAE-synthesized data and

compared the resulting maps of correlations with those obtained with rsfMRI data

concatenated across a different number of subjects. Figure 5.a shows three examples

with the seed region in the primary visual cortex (V1), intraparietal sulcus (IPS), or

posterior cingulate cortex (PCC). For each of the three seed locations, the synthesized

fMRI data showed a similar correlational map as that based on length-matched rsfMRI

data obtained from 10 subjects (Figure 5.a), and the correlational map was consistent

with the literature (Yeo et al., 2011). The measured FC patterns were more similar to the

synthesized FC patterns, when the measured FC was based on data from increasingly

more subjects, regardless of whether the FC was evaluated and compared with respect

to a specific seed location (Figure 5.b) or across all cortical parcels (Figure 5.c). These

results suggest that the VAE provided a computational account for the generative process

of resting state activity and could synthesize realistic rsfMRI activity patterns and preserve

inter-regional correlations as are experimentally observable at a group or population level.

However, it is worth mentioning that the temporal ordering of the synthesized data is not

meaningful, since the VAE model does not explicitly model the temporal dynamics.

Figure 5. VAE synthesizes correlated fMRI activity. (**a**) Seed-based correlations of VAE-synthesized
fMRI data (top row) vs. experimental fMRI data (bottom row) with the seed location (green circle) at V1 (left),
IPS (middle), or PCC (right). (**b**) Spatial correlations between the seed-based functional connectivity based
on VAE-synthesized data and those based on measured fMRI data concatenated across 1, 5, 10, 50, or
100 subjects. The colors indicate different seed locations (V1: black; IPS: red   ; PCC: blue). Similarly, (**c**)
shows the spatial correlation between the synthesized vs. measured functional connectivity among 360
cortical parcels. The error bar indicates the standard error of the mean averaged across 20 repeated trials.

Latent variables reflected network dynamics

We also examined the time-evolving trajectory of the latent representation and re-

defined the latent variables such that they reflected the dynamic changes of fMRI activity.

We first evaluated the displacement of the latent representation from every time point to

its next. Then we applied singular value decomposition and used the resulting singular

vectors to redefine the latent variables as a new basis set that spanned the latent space.

These redefined latent variables, ranked in a descending order by their singular values,

represented the principal directions in which the instantaneous latent representation

tended to move along its time-evolving trajectory.

We chose the top-10 latent variables for further visualization and interpretation.

For each latent variable, we uniformly sampled its value in a range from -5 to 5 and

visualized each sample by decoding it to a cortical pattern. We found that as the latent

variable increased its value linearly, the decoded cortical pattern changed in a non-linear

way that differed across cortical locations (see illustrative examples in Figure 6.b). To

visualize how each latent variable controlled the activity at each cortical location, we

calculated the standard deviation of the voxel-wise activity change given an increasing

value for the given latent variable and multiplied by a sign (+1 or -1) depending on whether

the activity tended to increase or decrease as the latent variable increased. For example,

the 1^{st} latent variable was visualized as a cortical pattern that resembled the default mode

network (Figure 6.a). Using the same visualization method, we found that the 2^{nd} through

10^{th} latent variables all corresponded to distinct but partially overlapping cortical patterns

(Figure 6.d). However, the top-10 latent variables were found to be inadequate to explain

the dynamics of latent representations. The percentage of the variance explained by each

latent variable was around 1% or less, and the total variance collectively explained by top

10, 20, 50, and 100 latent variables were 9.6, 17.5, 37.6, and 62.3% (Figure 6.c). These

results suggest that the dynamics of rsfMRI is complex and high-dimensional in nature.

Nevertheless, the latent variables derived from the above analysis represent distinctive

factors that drive the dynamic change in resting state activity.

Figure 6. **Latent variables drive the dynamics of latent representation.** The latent variables are defined
as the principal directions for the dynamic change of latent representation across adjacent time points. **(a)**
Visualization of the 1st latent variable as a cortical pattern of the signed standard deviation. (**b**) For each of
the four cortical locations, denoted as i through iv and shown as green circles in (**a**), the activity change is
shown as a function of the 1st latent variable, indicating a varying nonlinear relationship. (**c**) The percentage
of the variance that each latent variable explains the first order dynamics of latent representation. The inset
shows the percentage of the total variance explained by top 10, 20, 50, or 100 latent variables. (**d**) The
visualization of the 2nd through 10th latent variables as cortical patterns.

Clusters in latent space

We further characterized the distribution of latent representation and attempted to identify clusters in the latent space. We used the VAE to encode the rsfMRI pattern observed at every time point from 500 subjects, clustered the time points by applying k-means clustering (k=21) to the latent representations, and decoded the cluster centroids to corresponding cortical maps. The number of clusters (k=21) was close to the "elbow" indicative of a reasonable balance between reducing variation within clusters and avoiding too many clusters (Figure 7.a). The 1-cosine dissimilarity between latent representations reordered by their cluster membership shows not only close affinity within every cluster but also a varying level of affinity between different clusters (Figure 7.b). This motivated us to hierarchically merge clusters into super-clusters (or "clusters of clusters") based on the cosine affinity between cluster centroids (Figure 7.c).

For each of the 21 clusters, we decoded and visualized the cluster centroid as a cortical pattern as shown in Figure 7.d. Among the 21 clusters, 5 clusters (Cluster 4, 6, 11, 12, 18) showed activity increase (positive) at one or multiple regions in the default mode network (Buckner et al., 2008; Greicius et al., 2003; Raichle et al., 2001), alongside activity decrease (negative) at other regions. Similarly, we found 5 clusters with activity increase in the so-called frontoparietal control network (Cluster 8) (Dixon et al., 2018), cingulo-opercular network (Cluster 7 and 9) (Dosenbach et al., 2007), cognitive control network (Cluster 1) (Cole and Schneider, 2007), and dorsal attention networks (Cluster 10) (Fox et al., 2006) – collectively referred to as "the task positive network" (Fox et al., 2005). In addition, cluster 13 and 16 showed activity decrease in the whole brain, thereby a signature of global signal fluctuation (Murphy et al., 2009; Schölvinck et al., 2010; Wen

and Liu, 2016). Cluster 5 and 17 showed widespread synchrony across sensory systems.

Cluster 2 and 21 showed the networks for sensorimotor control of the limbs and of the

mouth, pharynx, and visceral organs, respectively. Whereas most clusters were bilaterally

symmetric, Cluster 15 and 3 were unilateral to the right and left prefrontal cortex,

respectively. A common observation for many clusters was that a cluster could highlight

the positive interactions among a set of well-defined cortical regions alongside their

negative interactions with a different set of regions. Given the above interpretation of

individual clusters, we further interpreted the three super-clusters as sensorimotor, default

mode, and task positive networks (Figure 7.C).

In addition, we evaluated the temporal dynamics of latent representation in terms

of the dynamics of individual clusters or their corresponding cortical networks. Intuitively,

we considered the time-evolving trajectory of the latent representation as the movement

towards or away from each cluster. In this regard, we expressed the cluster-wise activity

as the time series of cosine affinity between the instantaneous latent representation and

the cluster centroid. During a rsfMRI session, different clusters expressed similar activity

levels (Figure 7.e), except in the initial period of the session. In that period of 20 seconds,

clusters presumably related to task positive networks showed a transition from a high

activity level to a lower steady state; the clusters related to sensorimotor networks showed

a transition from a low activity level to a higher steady state; in contrary, clusters related

to the default mode network remained roughly unchanged. These (somewhat incidental)

observations were consistent and reproducible across individuals and sessions. On one

hand, this result suggests that the first 20 seconds in a rsfMRI session are not necessarily

the steady state under a resting condition. On the other hand, this exploratory analysis

shows the feasibility of using the VAE-extracted latent representations to identify brain

networks and reveal their individual dynamics.

Figure 7. Clusters of latent representations. (**a**) The sum of within-cluster distance is shown as a function

of the number of clusters (or K). The choice of k=21 is about where an elbow is observable in the plot. (**b**)

Representational dissimilarity matrix of the 1-cosine distance between instantaneous latent representations

(from 100 subjects with 1,200 time points per subject) reordered by cluster membership. (**c**) Hierarchical

clustering of 21 cluster centroids. The clusters are grouped into three super-clusters, provisionally labeled as sensorimotor (red), default mode (green), and task positive (blue) networks, based on the cortical visualization of individual clusters in (**d**). (**d**) Cortical patterns decoded from every cluster centroid. The number shows the cluster index. The scale of each pattern is normalized by its maximal absolute value. (**e**) The group-averaged cluster-wise activity, described as the cosine affinity of instantaneous representation to the centroid of each cluster. Each thin line corresponds to one cluster; the color indicating the super-cluster (sensorimotor: red; default mode: green; task positive: blue) that each cluster belongs to. The thick lines show the average within super-clusters. The left and right panels show the activity patterns averaged across all subjects for session 1 and session 2, respectively. Colored lines on the top of panel (**e**) highlight the periods in which the sensorimotor (red), default-mode (green) or task positive (blue) super-cluster was statistically significant in the group level (permutation test, false discovery rate q<0.01).

Individual variation of latent representation

Whereas the aforementioned analyses focused on the group-level characteristics of the latent representations, we further asked how the distribution and geometry of latent representation varied across individuals. Only for the sake of demonstration, we randomly selected 20 subjects in the testing dataset and visualized their individual representations in the latent space after reducing its dimension from 256 to 2 by using t-SNE (Figure 8.a). Strikingly, the latent representations were grouped by and separable across individuals. The clustering by individuals was noticeable in the nonlinear latent space obtained with VAE (Figure 8.a), but not in the linear latent space obtained with PCA (Figure 8.b). Such distinctions were quantitatively confirmed (Figure 8.c) by using the Silhouette value to measure the degree of clustering by individuals. The Silhouette value for VAE (mean ± std: $s = 0.044 \pm 0.002$, 50 bootstrapping trials) was significantly higher (p<0.001, two-sample t-test) than that for PCA ($s = -0.020 \pm 0.015$). Using the center of latent

representation as the subject-identifying feature, we found that subject identity could be

retrieved with a reasonably high accuracy when the latent representation was extracted

by VAE, whereas the linear representation by PCA failed the same task nearly entirely

(Figure 8.d). These results suggest the feasibility of using VAE to characterize and reveal

individual variations of resting state activity in a non-linear latent space.

Figure 8. **Individual variation of latent representation obtained with VAE vs. PCA. (a-b)** Subject-wise

latent representations visualized in a 2-D space obtained with t-SNE, when **(a)** VAE or **(b)** PCA is used to

extract representations of rsfMRI activity from 20 subjects. **(c)** The Silhouette value shows how similar a

representation is similar to each other within the same subject as opposed to between different subjects for

VAE (left) or PCA (right). **(d)** The top-1, 5, and 10 accuracy of using the time-averaged representation as

the feature to identify individuals in a large group of (n=500) subjects, for the representations obtained with

VAE (black) or PCA (blue).

Individual identification

From the t-SNE based visualization (Fig. 8.a), it was noticeable that subject-wise

representations exhibited different geometries. Some were more elongated or scattered

than others. This observation motivated us to ask whether the representational geometry

(Kriegeskorte and Kievit, 2013) could be an individual-specific feature (or "fingerprint") to

allow for more accurate individual identification. Specifically, we calculated the covariance

between every pair of latent variables and assembled the pair-wise covariance into a

vector as the feature of the representational geometry and evaluated the similarity in this

feature between two sessions within or between subjects. The representational geometry

evaluated in this way could be interpreted as the functional connectivity (FC) between

latent variables. This interpretation related this approach to a conceptually similar

approach: the "connectome-based fingerprinting" (Finn et al., 2015; Venkatesh et al.,

2020), in which the functional connectivity was evaluated between cortical parcels. So,

we evaluated the use of either the latent-space or cortical-space FC for individual

identification in comparison.

As shown in Figure 9.a, FC between any pair of cortical areas was mostly positive

(mean ± std of z-transformed correlation: $z=0.26\pm0.3$) and highly reproducible not only

within the same subject ($r=0.66$) but also between different subjects ($r=0.45$). On the other

hand, FC between latent variables had both positive and negative values (mean ± std of

covariance: $\sigma^2=0.00\pm0.13$) and its reproducibility was high only within the same subject

(*r*=0.33) but not between different subjects (*r*=0.07). The FC profile was more distinctive

across subjects when it was evaluated between latent variables rather than cortical areas

(Figure 9.b). In the latent space, the FC profile was significantly more consistent within a

subject than between subjects (two-sample t-test, $t(249,998)=254.05$, two-sided $p<0.001$).

The distribution of within-subject correlations was in nearly complete separation from that

of between-subject correlations (Figure 9.b, bottom).

Then we compared the performance of individual identification on the basis of the

FC profile in the latent vs. cortical space. To identify 1 out of 500 subjects, we compared

a target subject's FC profile in the 1st session (as a query) against every subject's FC

profile in the 2nd session (as a key) and chose the best match between the query and the

key in terms of the Pearson correlation coefficient. As such, the choice was correct if the

correlation with the target subject was higher than the largest correlation with any non-

target subject. We found that the FC profile in the cortical space could support 69.3% top-

1 accuracy while identification was often made with marginal confidence relative to the

decision boundary (Figure 9.c). Using the FC in the latent space allowed us to reach 97.8%

top-1 accuracy. The evidence for correct identification was apparent with a large margin

from the decision boundary (Figure 9.d). The use of FC in the latent space supported

reliable and robust performance in top-1 identification given an increasingly larger

population (Figure 9.e) or when the data were limited to a short duration (Figure 9.f), being

notably superior to the use of FC in the cortical space.

Figure 9. Individual identification based on correlations between latent variables or cortical parcels.

(a) Density distributions of z-transformed correlations between every pair of cortical parcels (top) or

covariance between every pair of latent variables (bottom). For each pair, the correlation and covariance in
one session is plotted against the corresponding correlation in the other session for the same subject
(within-subject, left) or different subjects (between-subject, right) given the testing dataset with n=500
subjects. Contour line stands for 20% of the maximal density. **(b)** Within-subject (red) and between-subject
(black) correlations in the FC among cortical parcels (top) or latent variables (bottom) are shown as
histograms with the width of each bin at 0.01. **(c)** In the scatter plot, each dot indicates one subject, plotting
the maximal correlation in the cortical FC profile between that subject and a different subject against the
corresponding correlation within that subject. The red-dashed line indicates y=x, serving as a decision
boundary, across which identification is correct (x>y) or wrong (y>x). The histogram shows the distribution
of y-x (0.05 bin width) with the decision boundary corresponding to 0. Similarly, **(d)** presents the results
obtained with latent-space FC in the same format as (**c**). (**e**) Top-1 identification accuracy evaluated with
an increasing number of subjects (n=5 to 500) given the latent-space (red) or cortical-space (black) FC
profile. The solid line and the shade indicate the mean and the standard deviation of the results with different
testing data. (**f**) Top-1 identification accuracy given rsfMRI data of different lengths (from 9s to 180s). The
line and the error bar indicate the mean and the standard deviation with different testing data.

We further tested to what extent the performance of individual identification relied

on the use of ICA-FIX to preprocess and denoise the rsfMRI data. For this purpose, we

applied ICA-FIX to one or both of the two sessions in every subject and then tested the

individual identification with n=500 subjects. As shown in Table 1, when the FC profile in

the latent space was derived from the (ICA-FIX denoised) clean data for both the keys

and queries, the identification has the highest accuracy (97.5%). When the key and the

query were both based on noisy data (without denoising), the accuracy dropped to 91.3%.

When the key and the query were unpaired as denoising applied to one but not the other,

the accuracy further dropped to about 88%. Nevertheless, this performance obtained with

the latent-space FC was still notably higher than the performance based on the cortical-

space FC. For the latter, the use of unpaired preprocessing for the query and the key

significantly dropped the identification performance from 69.3% to 47.5%. Counter-

intuitively, when the denoising was applied to neither the query nor the key, the

identification accuracy with the cortical-space FC increased to 76.9%, but still significantly

lower than the accuracy of 91.3% obtained with the latent-space FC.

Table 1. Subject identification accuracy across different conditions

| | | | Session 1 | |
			Clean	Noisy
Session 2	Latent Space	Clean	97.8%	87.9%
		Noisy	88.4%	91.3%
	Cortical Space	Clean	69.3%	47.2%
		Noisy	47.5%	76.9%

Lastly, we explored whether the representational geometry (based on the profile of

the covariance between latent variables) would yield a similar level of distinction across

individuals for a linear latent space obtained with PCA or ICA. As shown in Figure. 10,

PCA or ICA was not as effective as VAE. The top-1 accuracy of individual identification

was 61.1% for PCA, 63.6% for ICA, in contrast to 97.8% for VAE. The within-subject vs.

between-subject similarity in the geometry of linear representation obtained with PCA or

ICA exhibited largely overlapping distributions, whereas the corresponding distributions

were separated nearly completely for the nonlinear representations obtained with VAE.

Figure 10. **Individual identification with nonlinear vs. linear representations.** Each plot shows the
histogram of the similarity in the representational geometry between sessions within the same subject (red)
vs. across different subjects (black), for representations in the nonlinear latent space obtained by VAE (top)
or in the linear latent space obtained by PCA (middle) or ICA (bottom). The similarity reported is based on
the inter-session correlation coefficient (or r). The histogram is discretized by bins with a width of 0.02.

Discussion

Here, we present a method for unsupervised representation learning of cortical

rsfMRI activity. Our results suggest that this method is able to disentangle generative

factors underlying spontaneous brain activity, discover overlapping brain networks,

capture individual characteristics or variation, and support accurate individual

identification. We expect this method to be a valuable addition to the existing tools for

investigating the origins of resting state activity, mapping functional brain networks, and

potentially supporting individualized prediction of disease phenotypes and progression.

Next, we discuss our findings from the joint perspective of methodology, neuroscience,

and applications.

VAE is trainable with unsupervised learning (without any label) (Higgins et al., 2017;

Kingma and Welling, 2013), which is appealing for learning representations of rsfMRI data.

Since rsfMRI measures spontaneous brain activity unconstrained by any task, labels as

required for supervised learning are either unavailable or far fewer than the data itself.

Unsupervised learning with VAE can leverage the ever-increasing amount of rsfMRI data

(Van Essen et al., 2013). The latent representations extracted from VAE can serve as the

input to other algorithms to further support more specific goals such as classification of

brain disorders and prediction of their phenotypes (Garrity et al., 2007; Moradi et al., 2015;

Shen et al., 2010; Zhang et al., 2011).

The method herein can be extended in multiple ways. Although it is trained with

rsfMRI data, we hypothesize that the VAE model can encode and decode both rsfMRI

and task-fMRI data but with different latent distributions. If this is true, one may use this

model to classify different perceptual, behavioral, or cognitive states and to reveal the

distinctive network interactions underlying various states (Gonzalez-Castillo et al., 2015).

The fact that the VAE can synthesize new data (Figure 5) is also appealing. It can be used

as a post-processing strategy for data augmentation and interpolation, when data is short

or corrupted, of interest for evaluation of dynamic functional connectivity (Allen et al., 2014;

Chang and Glover, 2010) and correction for head motion (Power et al., 2014). It also

supports the notion that the learned latent space captures the origins of rsfMRI and the

VAE decoder captures the computational account for how rsfMRI arises from its origins.

It is worth mentioning two limitations of the VAE model in its current form. First, the

model focuses on cortical patterns but excludes sub-cortical and white-matter voxels. This

design is not only for the ease of model implementation but also for the predominant role

of the neocortex in brain functions (Rakic, 2009). However, this precludes the model from

accounting for subcortical networks or their interactions with the cortex. Addressing this

limitation awaits future studies to redesign the model as a 3-D neural network that takes

volumetric fMRI data as the input. Second, the VAE model only represents spatial patterns

but ignores temporal dynamics inherent to rsfMRI data. Modeling the temporal dynamics

is desirable but non-trivial, since it is highly irregular, complex and variable. To fill this gap,

we direct future studies to designing a recurrent neural network (Chen and Hu, 2018; Cui

et al., 2019; Shi et al., 2018; Sutskever et al., 2014; Zhao et al., 2019), as an add-on to

VAE, to further learn sequence representation, for example, with a self-supervised

predictive learning strategy (Kashyap and Keilholz, 2020; Khosla et al., 2019a).

Although VAE does not explicitly model the temporal dynamics, the representation

obtained with VAE preserves the temporal dynamics (Figure 3). The trajectory of the latent

representation describes the temporal behavior of brain networks, as opposed to voxels

or regions. This trajectory is amenable to the use of many methods previously described

for voxel-wise or region-wise analysis. To note a few examples explored in this study, the

first-order temporal difference in the latent representation captures the gradient of latent

trajectory that drives the brain to change its activity pattern from one time point to the next.

As the latent gradient is also represented as a vector in the latent space, the length of this

vector measures the displacement in the latent space and presumably the magnitude of

network activity, and the direction of this vector encodes a pattern of network interaction

that drives the instantaneous change of brain activity. The principal components of the

displacement in representation uncover the important hidden factors that drive the

temporal dynamics of brain networks (Figure 6). Similar analysis or notion has also been

explored in two independent studies discussed in two very recent papers published or in

preprint during the peer review of our paper (Brown et al., 2020; Liu et al., 2020b). These

initial analyses are expected to merit and direct future studies upon predictive modeling

of the trajectory of the VAE-derived latent representation, for example, by using

Multivariate Auto-Regressive models (Liégeois et al., 2019; Rogers et al., 2010), Hidden

Markov Models (Eavani et al., 2013; Suk et al., 2016).

VAE provides a new tool for mapping overlapping functional networks in the brain.

A brain region may be involved in multiple networks each supporting a distinctive function

(Liu and Duyn, 2013; Smith et al., 2012). However, existing network analyses still tend to

group brain regions into non-overlapping networks (Yeo et al., 2011). VAE allows us to

discover overlapping networks as clusters in the latent space spanned by independent

latent variables. As such, VAE is conceptually similar to temporal ICA (Smith et al., 2012)

but allows for nonlinear relationships between latent variables and the input data they

represent (Khemakhem et al., 2019). Arguably, finding clusters in the low-dimensional

latent space is more desirable than doing so in the higher-dimensional voxel space (Liu

et al., 2013). Not only is it more computationally efficient, but representations are also

more disentangled in the latent space than in the voxel space to readily reveal the

underlying organization. However, it is not readily straightforward to attribute a cluster in

the latent space to a distinct brain state (Hutchison et al., 2013) or an individual (Xie et

al., 2018). Both are plausible. Our results show that individual variation manifests itself as

the latent representation is in part clustered by subject (Figure 8), suggesting individual

variation is a contributing factor to the clustering of latent representation. Our results also

suggest that cluster-wise activity shows a consistent pattern across all subjects, in

particular for the first 20 seconds of each session (Figure 7). Moreover, the clusters seem

to group themselves hierarchically into presumably functional domains: sensorimotor,

default-mode and task-positive networks (Figure 7). Together These results lead us to

speculate that variation in brain states and individuals both contribute to the clustering of

brain activity in the latent space. It is challenging to fully separate them and awaits future

studies.

Central to this study is the efficacy of using VAE to disentangle what causes resting

state activity. In the VAE model, the sources are the latent variables; the decoder

describes how the sources generate the observed activity; the encoder models the

inverse inference of the sources from the activity. Since the latent variables are data-

driven, it is currently unclear how to interpret them as specific physiological processes,

many of which are not observable. Nevertheless, we expect the latent variables extracted

by VAE to provide the computational basis for further understanding the origins of resting

state activity. We hypothesize that the truly disentangled physiological origins, whether

observable or not, are individually describable as the latent variables up to linear and

sparse projection. This hypothesis awaits confirmation by future studies.

In the latent space, functional connectivity between latent variables describes the

geometry of the latent representation of rsfMRI activity. This is a new perspective different

from the functional connectivity among observable voxels, regions or networks (Biswal et

al., 1995; Yeo et al., 2011). If the VAE model has fully disentangled the sources in a

population level, functional connectivity should be near zero between different latent

variables and thus reflect a spherical geometry. In other words, the model sets a nearly

null population-level baseline, against which individual variation stands out. The latent-

space functional connectivity given data from a single subject becomes a unique feature

of that subject. Supporting this notion, the use of functional connectivity in the latent space

allows for a significantly improved accuracy, robustness, and efficiency in individual

identification, compared to the use of functional connectivity among cortical parcels

(Amico and Goñi, 2018; Byrge and Kennedy, 2019; Finn et al., 2015; Mejia et al., 2018;

Venkatesh et al., 2020).

Note that our main purpose is not to push for a higher identification accuracy but

to understand the distribution and geometry of data representations in the feature space.

Therefore, we opt for minimal preprocessing and the simplest strategy for individual

identification. There is room for methodological development to further improve the

identification accuracy or to extend it for many other tasks, including classification of the

gender or disease states, prediction of behavioral and cognitive performances, to name

a few examples. We expect that such applications would be fruitful and potentially

impactful to cognitive sciences and clinical applications.

Supplementary Figure 1. Grayordinates (# = 29,696) in left hemisphere (left panel) is projected into 2D
space (middle panel) based on their azimuth- and elevation levels. Each color stands for different brain
atlas based on the literature (Glasser et al., 2016). The imbalance in data density along the varying elevation
level (upper in right panel) is alleviated by further applying elevation to Sine function (bottom in right panel).

792   **Supplementary Figure 2. Validation curve of VAE at varying learning rate.**

795   **Supplementary Figure 3. Validation curve of VAE at different layers**

Reference

Allen, E.A., Damaraju, E., Plis, S.M., Erhardt, E.B., Eichele, T., Calhoun, V.D., 2014. Tracking whole-brain connectivity dynamics in the resting state. Cerebral cortex 24, 663-676.

Amico, E., Goñi, J., 2018. The quest for identifiability in human functional connectomes. Scientific reports 8, 1-14.

Beckmann, C.F., Smith, S.M., 2004. Probabilistic independent component analysis for functional magnetic resonance imaging. IEEE transactions on medical imaging 23, 137-152.

Bianciardi, M., Fukunaga, M., van Gelderen, P., Horovitz, S.G., de Zwart, J.A., Shmueli, K., Duyn, J.H., 2009. Sources of functional magnetic resonance imaging signal fluctuations in the human brain at rest: a 7 T study. Magnetic resonance imaging 27, 1019-1029.

Birn, R.M., Smith, M.A., Jones, T.B., Bandettini, P.A., 2008. The respiration response function: the temporal dynamics of fMRI signal fluctuations related to changes in respiration. Neuroimage 40, 644-654.

Biswal, B., Zerrin Yetkin, F., Haughton, V.M., Hyde, J.S., 1995. Functional connectivity in the motor cortex of resting human brain using echo-planar MRI. Magnetic resonance in medicine 34, 537-541.

Brown, J.A., Lee, A.J., Pasquini, L., Seeley, W.W., 2020. Intrinsic brain activity gradients dynamically coordinate functional connectivity states. bioRxiv.

Buckner, R.L., Andrews-Hanna, J.R., Schacter, D.L., 2008. The brain's default network: anatomy, function, and relevance to disease.

Byrge, L., Kennedy, D.P., 2019. High-accuracy individual identification using a "thin slice" of the functional connectome. Network Neuroscience 3, 363-383.

Calhoun, V.D., Adali, T., Pearlson, G., Pekar, J.J., 2001. Spatial and temporal independent component analysis of functional MRI data containing a pair of task-related waveforms. Human brain mapping 13, 43-53.

Chang, C., Glover, G.H., 2010. Time–frequency dynamics of resting-state brain connectivity measured with fMRI. Neuroimage 50, 81-98.

Chang, C., Leopold, D.A., Schölvinck, M.L., Mandelkow, H., Picchioni, D., Liu, X., Frank, Q.Y., Turchi, J.N., Duyn, J.H., 2016. Tracking brain arousal fluctuations with fMRI. Proceedings of the National Academy of Sciences 113, 4518-4523.

Chen, S., Hu, X., 2018. Individual identification using the functional brain fingerprint detected by the recurrent neural network. Brain connectivity 8, 197-204.

Chou, Y.-h., Sundman, M., Whitson, H.E., Gaur, P., Chu, M.-L., Weingarten, C.P., Madden, D.J., Wang, L., Kirste, I., Joliot, M., 2017. Maintenance and representation of mind wandering during Resting-State fMRI. Scientific reports 7, 40722.

Cole, M.W., Schneider, W., 2007. The cognitive control network: integrated cortical regions with dissociable functions. Neuroimage 37, 343-360.

Cui, Y., Zhao, S., Chen, Y., Han, J., Guo, L., Xie, L., Liu, T., 2019. Modeling brain diverse and complex hemodynamic response patterns via deep recurrent autoencoder. IEEE Transactions on Cognitive and Developmental Systems.

D'Souza, N.S., Nebel, M.B., Wymbs, N., Mostofsky, S., Venkataraman, A., 2019. Integrating Neural Networks and Dictionary Learning for Multidimensional Clinical Characterizations from Functional Connectomics Data. International Conference on Medical Image Computing and Computer-Assisted Intervention. Springer, pp. 709-717.

Dixon, M.L., De La Vega, A., Mills, C., Andrews-Hanna, J., Spreng, R.N., Cole, M.W., Christoff,

K., 2018. Heterogeneity within the frontoparietal control network and its relationship to the default
and dorsal attention networks. Proceedings of the National Academy of Sciences 115, E1598-
E1607.
Dosenbach, N.U., Fair, D.A., Miezin, F.M., Cohen, A.L., Wenger, K.K., Dosenbach, R.A., Fox,
M.D., Snyder, A.Z., Vincent, J.L., Raichle, M.E., 2007. Distinct brain networks for adaptive and
stable task control in humans. Proceedings of the National Academy of Sciences 104, 11073-11078.
Dvornek, N.C., Yang, D., Ventola, P., Duncan, J.S., 2018. Learning generalizable recurrent neural
networks from small task-fmri datasets. International Conference on Medical Image Computing
and Computer-Assisted Intervention. Springer, pp. 329-337.
Eavani, H., Satterthwaite, T.D., Gur, R.E., Gur, R.C., Davatzikos, C., 2013. Unsupervised learning
of functional network dynamics in resting state fMRI. International conference on information
processing in medical imaging. Springer, pp. 426-437.
Fan, L., Su, J., Qin, J., Hu, D., Shen, H., 2020. A Deep Network Model on Dynamic Functional
Connectivity With Applications to Gender Classification and Intelligence Prediction. Frontiers in
neuroscience 14, 881.
Finn, E.S., Shen, X., Scheinost, D., Rosenberg, M.D., Huang, J., Chun, M.M., Papademetris, X.,
Constable, R.T., 2015. Functional connectome fingerprinting: identifying individuals using
patterns of brain connectivity. Nature neuroscience 18, 1664.
Fischl, B., 2012. FreeSurfer. Neuroimage 62, 774-781.
Fox, M.D., Buckner, R.L., Liu, H., Chakravarty, M.M., Lozano, A.M., Pascual-Leone, A., 2014.
Resting-state networks link invasive and noninvasive brain stimulation across diverse psychiatric
and neurological diseases. Proceedings of the National Academy of Sciences 111, E4367-E4375.
Fox, M.D., Corbetta, M., Snyder, A.Z., Vincent, J.L., Raichle, M.E., 2006. Spontaneous neuronal
activity distinguishes human dorsal and ventral attention systems. Proceedings of the National
Academy of Sciences 103, 10046-10051.
Fox, M.D., Raichle, M.E., 2007. Spontaneous fluctuations in brain activity observed with
functional magnetic resonance imaging. Nature reviews neuroscience 8, 700-711.
Fox, M.D., Snyder, A.Z., Vincent, J.L., Corbetta, M., Van Essen, D.C., Raichle, M.E., 2005. The
human brain is intrinsically organized into dynamic, anticorrelated functional networks.
Proceedings of the National Academy of Sciences 102, 9673-9678.
Gadgil, S., Zhao, Q., Adeli, E., Pfefferbaum, A., Sullivan, E.V., Pohl, K.M., 2020. Spatio-Temporal
Graph Convolution for Functional MRI Analysis. arXiv preprint arXiv:2003.10613.
Garrity, A.G., Pearlson, G.D., McKiernan, K., Lloyd, D., Kiehl, K.A., Calhoun, V.D., 2007.
Aberrant "default mode" functional connectivity in schizophrenia. American journal of psychiatry
164, 450-457.
Glasser, M.F., Coalson, T.S., Robinson, E.C., Hacker, C.D., Harwell, J., Yacoub, E., Ugurbil, K.,
Andersson, J., Beckmann, C.F., Jenkinson, M., 2016. A multi-modal parcellation of human
cerebral cortex. nature 536, 171-178.
Glasser, M.F., Sotiropoulos, S.N., Wilson, J.A., Coalson, T.S., Fischl, B., Andersson, J.L., Xu, J.,
Jbabdi, S., Webster, M., Polimeni, J.R., 2013. The minimal preprocessing pipelines for the Human
Connectome Project. Neuroimage 80, 105-124.
Gonzalez-Castillo, J., Hoy, C.W., Handwerker, D.A., Robinson, M.E., Buchanan, L.C., Saad, Z.S.,
Bandettini, P.A., 2015. Tracking ongoing cognition in individuals using brief, whole-brain
functional connectivity patterns. Proceedings of the National Academy of Sciences 112, 8762-
8767.
Greicius, M.D., Krasnow, B., Reiss, A.L., Menon, V., 2003. Functional connectivity in the resting

brain: a network analysis of the default mode hypothesis. Proceedings of the National Academy of Sciences 100, 253-258.

Griffanti, L., Salimi-Khorshidi, G., Beckmann, C.F., Auerbach, E.J., Douaud, G., Sexton, C.E., Zsoldos, E., Ebmeier, K.P., Filippini, N., Mackay, C.E., 2014. ICA-based artefact removal and accelerated fMRI acquisition for improved resting state network imaging. Neuroimage 95, 232-247.

Han, K., Wen, H., Shi, J., Lu, K.-H., Zhang, Y., Fu, D., Liu, Z., 2019. Variational autoencoder: An unsupervised model for encoding and decoding fMRI activity in visual cortex. Neuroimage 198, 125-136.

He, T., Kong, R., Holmes, A.J., Nguyen, M., Sabuncu, M.R., Eickhoff, S.B., Bzdok, D., Feng, J., Yeo, B.T., 2020. Deep neural networks and kernel regression achieve comparable accuracies for functional connectivity prediction of behavior and demographics. Neuroimage 206, 116276.

Higgins, I., Matthey, L., Pal, A., Burgess, C., Glorot, X., Botvinick, M., Mohamed, S., Lerchner, A., 2017. beta-VAE: Learning Basic Visual Concepts with a Constrained Variational Framework. Iclr 2, 6.

Huang, H., Hu, X., Zhao, Y., Makkie, M., Dong, Q., Zhao, S., Guo, L., Liu, T., 2017. Modeling task fMRI data via deep convolutional autoencoder. IEEE transactions on medical imaging 37, 1551-1561.

Hutchison, R.M., Womelsdorf, T., Allen, E.A., Bandettini, P.A., Calhoun, V.D., Corbetta, M., Della Penna, S., Duyn, J.H., Glover, G.H., Gonzalez-Castillo, J., 2013. Dynamic functional connectivity: promise, issues, and interpretations. Neuroimage 80, 360-378.

Jarrett, C., 2009. The restless brain. The Psychologist.

Kashyap, A., Keilholz, S., 2020. Brain network constraints and recurrent neural networks reproduce unique trajectories and state transitions seen over the span of minutes in resting-state fMRI. Network Neuroscience 4, 448-466.

Kawahara, J., Brown, C.J., Miller, S.P., Booth, B.G., Chau, V., Grunau, R.E., Zwicker, J.G., Hamarneh, G., 2017. BrainNetCNN: Convolutional neural networks for brain networks; towards predicting neurodevelopment. Neuroimage 146, 1038-1049.

Kell, A.J., Yamins, D.L., Shook, E.N., Norman-Haignere, S.V., McDermott, J.H., 2018. A task-optimized neural network replicates human auditory behavior, predicts brain responses, and reveals a cortical processing hierarchy. Neuron 98, 630-644. e616.

Khaligh-Razavi, S.-M., Kriegeskorte, N., 2014. Deep supervised, but not unsupervised, models may explain IT cortical representation. PLoS computational biology 10, e1003915.

Khemakhem, I., Kingma, D.P., Hyvärinen, A., 2019. Variational autoencoders and nonlinear ica: A unifying framework. arXiv preprint arXiv:1907.04809.

Khosla, M., Jamison, K., Kuceyeski, A., Sabuncu, M.R., 2019a. Ensemble learning with 3D convolutional neural networks for functional connectome-based prediction. Neuroimage 199, 651-662.

Khosla, M., Jamison, K., Ngo, G.H., Kuceyeski, A., Sabuncu, M.R., 2019b. Machine learning in resting-state fMRI analysis. Magnetic resonance imaging.

Kim, H.-c., Lee, J.-h., 2016. Evaluation of weight sparsity control during autoencoder training of resting-state fMRI using non-zero ratio and Hoyer's sparseness. 2016 International Workshop on Pattern Recognition in Neuroimaging (PRNI). IEEE, pp. 1-4.

Kingma, D.P., Ba, J., 2014. Adam: A method for stochastic optimization. arXiv preprint arXiv:1412.6980.

Kingma, D.P., Welling, M., 2013. Auto-encoding variational bayes. arXiv preprint

arXiv:1312.6114.

Koppe, G., Toutounji, H., Kirsch, P., Lis, S., Durstewitz, D., 2019. Identifying nonlinear dynamical systems via generative recurrent neural networks with applications to fMRI. PLoS computational biology 15, e1007263.

Kriegeskorte, N., Kievit, R.A., 2013. Representational geometry: integrating cognition, computation, and the brain. Trends in cognitive sciences 17, 401-412.

LeCun, Y., Bengio, Y., Hinton, G., 2015. Deep learning. nature 521, 436-444.

Leopold, D.A., Maier, A., 2012. Ongoing physiological processes in the cerebral cortex. Neuroimage 62, 2190-2200.

Liégeois, R., Li, J., Kong, R., Orban, C., Van De Ville, D., Ge, T., Sabuncu, M.R., Yeo, B.T., 2019. Resting brain dynamics at different timescales capture distinct aspects of human behavior. Nature communications 10, 1-9.

Liu, M., Li, F., Yan, H., Wang, K., Ma, Y., Shen, L., Xu, M., Initiative, A.s.D.N., 2020a. A multi-model deep convolutional neural network for automatic hippocampus segmentation and classification in Alzheimer's disease. Neuroimage 208, 116459.

Liu, S., Zhao, L., Wang, X., Xin, Q., Zhao, J., Guttery, D.S., Zhang, Y.-D., 2020b. Deep Spatio-Temporal Representation and Ensemble Classification for Attention deficit/Hyperactivity disorder. IEEE Transactions on Neural Systems and Rehabilitation Engineering.

Liu, X., Chang, C., Duyn, J.H., 2013. Decomposition of spontaneous brain activity into distinct fMRI co-activation patterns. Frontiers in systems neuroscience 7, 101.

Liu, X., Duyn, J.H., 2013. Time-varying functional network information extracted from brief instances of spontaneous brain activity. Proceedings of the National Academy of Sciences 110, 4392-4397.

Lu, H., Jaime, S., Yang, Y., 2019. Origins of the resting-state functional MRI signal: potential limitations of the "neurocentric" model. Frontiers in neuroscience 13.

Makkie, M., Huang, H., Zhao, Y., Vasilakos, A.V., Liu, T., 2019. Fast and scalable distributed deep convolutional autoencoder for fMRI big data analytics. Neurocomputing 325, 20-30.

Mantini, D., Perrucci, M.G., Del Gratta, C., Romani, G.L., Corbetta, M., 2007. Electrophysiological signatures of resting state networks in the human brain. Proceedings of the National Academy of Sciences 104, 13170-13175.

Matsubara, T., Tashiro, T., Uehara, K., 2019. Deep neural generative model of functional MRI images for psychiatric disorder diagnosis. IEEE Transactions on Biomedical Engineering 66, 2768-2779.

Mejia, A.F., Nebel, M.B., Barber, A.D., Choe, A.S., Pekar, J.J., Caffo, B.S., Lindquist, M.A., 2018. Improved estimation of subject-level functional connectivity using full and partial correlation with empirical Bayes shrinkage. Neuroimage 172, 478-491.

Moradi, E., Pepe, A., Gaser, C., Huttunen, H., Tohka, J., Initiative, A.s.D.N., 2015. Machine learning framework for early MRI-based Alzheimer's conversion prediction in MCI subjects. Neuroimage 104, 398-412.

Murphy, K., Birn, R.M., Handwerker, D.A., Jones, T.B., Bandettini, P.A., 2009. The impact of global signal regression on resting state correlations: are anti-correlated networks introduced? Neuroimage 44, 893-905.

Nair, V., Hinton, G.E., 2010. Rectified linear units improve restricted boltzmann machines. Proceedings of the 27th international conference on machine learning (ICML-10), pp. 807-814.

Plis, S.M., Hjelm, D.R., Salakhutdinov, R., Allen, E.A., Bockholt, H.J., Long, J.D., Johnson, H.J., Paulsen, J.S., Turner, J.A., Calhoun, V.D., 2014. Deep learning for neuroimaging: a validation

study. Frontiers in neuroscience 8, 229.

Power, J.D., Mitra, A., Laumann, T.O., Snyder, A.Z., Schlaggar, B.L., Petersen, S.E., 2014.
Methods to detect, characterize, and remove motion artifact in resting state fMRI. Neuroimage 84,
320-341.

Raichle, M.E., MacLeod, A.M., Snyder, A.Z., Powers, W.J., Gusnard, D.A., Shulman, G.L., 2001.
A default mode of brain function. Proceedings of the National Academy of Sciences 98, 676-682.

Rakic, P., 2009. Evolution of the neocortex: a perspective from developmental biology. Nature
reviews neuroscience 10, 724-735.

Riaz, A., Asad, M., Alonso, E., Slabaugh, G., 2020. DeepFMRI: End-to-end deep learning for
functional connectivity and classification of ADHD using fMRI. Journal of Neuroscience Methods
335, 108506.

Richards, B.A., Lillicrap, T.P., Beaudoin, P., Bengio, Y., Bogacz, R., Christensen, A., Clopath, C.,
Costa, R.P., de Berker, A., Ganguli, S., 2019. A deep learning framework for neuroscience. Nature
neuroscience 22, 1761-1770.

Rogers, B.P., Katwal, S.B., Morgan, V.L., Asplund, C.L., Gore, J.C., 2010. Functional MRI and
multivariate autoregressive models. Magnetic resonance imaging 28, 1058-1065.

Salimi-Khorshidi, G., Douaud, G., Beckmann, C.F., Glasser, M.F., Griffanti, L., Smith, S.M., 2014.
Automatic denoising of functional MRI data: combining independent component analysis and
hierarchical fusion of classifiers. Neuroimage 90, 449-468.

Schölvinck, M.L., Maier, A., Frank, Q.Y., Duyn, J.H., Leopold, D.A., 2010. Neural basis of global
resting-state fMRI activity. Proceedings of the National Academy of Sciences 107, 10238-10243.

Seo, Y., Morante, M., Kopsinis, Y., Theodoridis, S., 2019. Unsupervised Pre-training of the Brain
Connectivity Dynamic Using Residual D-Net. International Conference on Neural Information
Processing. Springer, pp. 608-620.

Shen, H., Wang, L., Liu, Y., Hu, D., 2010. Discriminative analysis of resting-state functional
connectivity patterns of schizophrenia using low dimensional embedding of fMRI. Neuroimage
49, 3110-3121.

Shi, J., Wen, H., Zhang, Y., Han, K., Liu, Z., 2018. Deep recurrent neural network reveals a
hierarchy of process memory during dynamic natural vision. Human brain mapping 39, 2269-2282.

Smith, S.M., Fox, P.T., Miller, K.L., Glahn, D.C., Fox, P.M., Mackay, C.E., Filippini, N., Watkins,
K.E., Toro, R., Laird, A.R., 2009. Correspondence of the brain's functional architecture during
activation and rest. Proceedings of the National Academy of Sciences 106, 13040-13045.

Smith, S.M., Miller, K.L., Moeller, S., Xu, J., Auerbach, E.J., Woolrich, M.W., Beckmann, C.F.,
Jenkinson, M., Andersson, J., Glasser, M.F., 2012. Temporally-independent functional modes of
spontaneous brain activity. Proceedings of the National Academy of Sciences 109, 3131-3136.

Sporns, O., Tononi, G., Kötter, R., 2005. The human connectome: a structural description of the
human brain. PLoS computational biology 1.

Suk, H.-I., Wee, C.-Y., Lee, S.-W., Shen, D., 2016. State-space model with deep learning for
functional dynamics estimation in resting-state fMRI. Neuroimage 129, 292-307.

Sutskever, I., Vinyals, O., Le, Q.V., 2014. Sequence to sequence learning with neural networks.
Advances in neural information processing systems, pp. 3104-3112.

Van Essen, D.C., Smith, S.M., Barch, D.M., Behrens, T.E., Yacoub, E., Ugurbil, K., Consortium,
W.-M.H., 2013. The WU-Minn human connectome project: an overview. Neuroimage 80, 62-79.

Venkatesh, M., Jaja, J., Pessoa, L., 2019. Brain dynamics and temporal trajectories during task and
naturalistic processing. Neuroimage 186, 410-423.

Venkatesh, M., Jaja, J., Pessoa, L., 2020. Comparing functional connectivity matrices: A geometry-

aware approach applied to participant identification. Neuroimage 207, 116398.

Wang, L., Li, K., Chen, X., Hu, X.P., 2019. Application of convolutional recurrent neural network
for individual recognition based on resting state fmri data. Frontiers in neuroscience 13, 434.

Wang, X., Liang, X., Jiang, Z., Nguchu, B.A., Zhou, Y., Wang, Y., Wang, H., Li, Y., Zhu, Y., Wu,
F., 2020. Decoding and mapping task states of the human brain via deep learning. Human brain
mapping 41, 1505-1519.

Wen, H., Liu, Z., 2016. Broadband electrophysiological dynamics contribute to global resting-state
fMRI signal. Journal of Neuroscience 36, 6030-6040.

Wen, H., Shi, J., Chen, W., Liu, Z., 2018. Deep residual network predicts cortical representation
and organization of visual features for rapid categorization. Scientific reports 8, 1-17.

Winder, A.T., Echagarruga, C., Zhang, Q., Drew, P.J., 2017. Weak correlations between
hemodynamic signals and ongoing neural activity during the resting state. Nature neuroscience 20,
1761-1769.

Xie, H., Calhoun, V.D., Gonzalez-Castillo, J., Damaraju, E., Miller, R., Bandettini, P.A., Mitra, S.,
2018. Whole-brain connectivity dynamics reflect both task-specific and individual-specific
modulation: A multitask study. Neuroimage 180, 495-504.

Yamins, D.L., DiCarlo, J.J., 2016. Using goal-driven deep learning models to understand sensory
cortex. Nature neuroscience 19, 356-365.

Yang, P., Zhou, F., Ni, D., Xu, Y., Chen, S., Wang, T., Lei, B., 2019. Fused sparse network learning
for longitudinal analysis of mild cognitive impairment. IEEE transactions on cybernetics.

Yeo, B.T., Krienen, F.M., Sepulcre, J., Sabuncu, M.R., Lashkari, D., Hollinshead, M., Roffman,
J.L., Smoller, J.W., Zöllei, L., Polimeni, J.R., 2011. The organization of the human cerebral cortex
estimated by intrinsic functional connectivity. Journal of neurophysiology.

Zhang, D., Wang, Y., Zhou, L., Yuan, H., Shen, D., Initiative, A.s.D.N., 2011. Multimodal
classification of Alzheimer's disease and mild cognitive impairment. Neuroimage 55, 856-867.

Zhang, Y., Han, K., Worth, R., Liu, Z., 2020. Connecting concepts in the brain by mapping cortical
representations of semantic relations. Nature communications 11, 1-13.

Zhao, Q., Honnorat, N., Adeli, E., Pfefferbaum, A., Sullivan, E.V., Pohl, K.M., 2019. Variational
autoencoder with truncated mixture of gaussians for functional connectivity analysis. International
Conference on Information Processing in Medical Imaging. Springer, pp. 867-879.

Zhao, Y., Li, X., Zhang, W., Zhao, S., Makkie, M., Zhang, M., Li, Q., Liu, T., 2018. Modeling 4d
fmri data via spatio-temporal convolutional neural networks (st-cnn). International Conference on
Medical Image Computing and Computer-Assisted Intervention. Springer, pp. 181-189.

Zou, L., Zheng, J., Miao, C., Mckeown, M.J., Wang, Z.J., 2017. 3D CNN based automatic
diagnosis of attention deficit hyperactivity disorder using functional and structural MRI. IEEE
Access 5, 23626-23636.

1062

1063

a

Sin(e)

a

b

Input

Variational Autoencoder

Output

x

Encoder

Latent Variables

z

Decoder

x'

L   R

1   2   3   4   5   6   7   8   9   10   11   12

a

Original

Smoothing (6 mm)

VAE

PCA

ICA

-2 ⟶ 2
z

b

Reconstruction performance

FWHM (mm)

Explained Variance (%)

— VAE
— PCA
— ICA

a Total within-cluster sums of distances — Cluster Number

b Representational dissimilarity — Latent representation ID / Latent representation ID — 1-Cosine 0.8 / 1.1

c Cluster ID — Cosine 0.3 / 0.8 — Sensorimotor / Default mode / Task positive

d 1–21

e Affinity to cluster centroids (Cosine) — Session1 / Session2 — Time (seconds)

a VAE

Axis 2

Axis 1

b PCA

Subject ID
20
1

c VAE PCA

Subject ID

0   0.1   0.2   -0.3   0   0.3
Silhouette Value

d

Subject identification accuracy (%)

VAE

PCA

Top-1   Top-5   Top-10

a Reproducibility of pair-wise FC

within-subject
between-subject

Cortical space
FC in Session 2

max
min

r = 0.66
r = 0.45

Latent space
FC in Session 2

r = 0.33
r = 0.07

FC in Session 1
FC in Session 1

b Correlation of FC in cortical vs. latent space

Cortical space
Probability

Latent space
Probability

between-subject
within-subject

Correlation in the FC profile

c Identification with FC in cortical space

Probability
within-subject vs. between-subject

wrong
correct

max between-subject
within-subject

30.7%
69.3%

d Identification with FC in latent space

Probability
within-subject vs. between-subject

wrong
correct

max between-subject
within-subject

2.2%
97.8%

e Identification for more subjects

Top-1 accuracy

Cortical space
Latent space

log (# of subjects)

f Identification with fewer data

Cortical space
Latent space

data length (seconds)

Table 1. Subject Identification Accuracy across different conditions

			Session 1	
			Clean	Noisy
Session 2	Latent Space	Clean	97.8%	87.9%
		Noisy	88.4%	91.3%
	Cortical Space	Clean	69.3%	47.2%
		Noisy	47.5%	76.9%

3D

2D

Density

Elevation

Sin(elevation)

Azimuth