Optimizing spectral quality with quantum dots to enhance crop yield in controlled environments

Charles H. Parrish II,[1] Damon Hebert,[2] Aaron Jackson,[2] Karthik Ramasamy,[2] Hunter McDaniel,[2] Gene A. Giacomelli,[1] & Matthew R. Bergren[2]*

1. Controlled Environment Agriculture Center, University of Arizona, Tucson, Arizona 85719, USA

2. UbiQD, Inc., Los Alamos, New Mexico 87544, USA

AUTHOR INFORMATION

Corresponding Authors

Email: matt@ubiqd.com, Tel: +1-505-310-6766

Email: giacomel@ag.arizona.edu, Tel: +1-520-621-1094

Abstract

Bioregenerative life-support systems (BLSS) involving plants will be required to realize self-sustaining human settlements beyond Earth. To improve the plant photosynthetic efficiency of BLSS, the quality of the solar spectrum can be modified by low-weight, luminescent films. $CuInS_2/ZnS$ quantum dot (QD) films with peak emissions of 600 and 660 nm were used to redshift ultraviolet and blue photons to increase biomass accumulation in red romaine lettuce. All plant growth parameters except spectral quality were held constant between three equivalent plant environments. Compared with the control film, lettuce grown under the 600 and 660 nm-emitting QD films increased edible dry mass (13% and 9%), edible fresh mass (11% each), and total leaf area (8% and 13%), respectively. The spectral modifications by the QD films improved photosynthetic efficiency in lettuce and could be used to enhance crop productivity in greenhouses on Earth or on crewed space missions.

As anthropogenic climate change exacerbates the severity and frequency of extreme weather events,[1] arable farmland is decreasing due to overpopulation and to drought.[2] To protect against these threats, producers of vegetable crops have turned to controlled environment agriculture (CEA) as a solution. CEA affords crop production with the highest resource use efficiency (RUE), and exceeds the annual per-area yield of field agriculture ten-fold.[3] This greater productivity results from optimized environmental controls, year-round production and reduced pests and diseases. Furthermore, recirculating hydroponic plant nutrient delivery systems recycle water for greatest RUE.[4]

CEA food production is particularly advantageous in extreme environments, like outer space, where regular access to fresh vegetables is impractical. NASA and other space agencies are developing CEA systems for crewed space applications, which range from growth chambers with LED lighting to drive photosynthesis,[5] to deployable greenhouses that could utilize sunlight for photosynthesis, like the Prototype Mars-Lunar Greenhouse (MLGH).[6]

Until recently, no viable options were available for controlling the quality of light for greenhouse crop production except for expensive and energy-intensive electrical lighting.[7] Furthermore, supplemental lighting requires heavy electrical equipment to deploy, operate, and maintain, which limits applications for extended space missions. Therefore, technologies that improve light quality, without increasing energy demand, excessive physical mass, deployment challenges, or expense, would be beneficial for terrestrial horticulture and required for space applications where these constraints are even greater.

A new technology that uses luminescent $CuInS_2/ZnS$ (CIS/ZnS) quantum dots (QD) embedded in flexible films to passively modify the solar spectrum is presented which can improve light quality and thereby enhances the photosynthetic efficiency of plants grown in CEA.

Spectral Quality on Plant Growth

The 400 nm to 700 nm waveband of the electromagnetic spectrum primarily powering photosynthesis is referred to as photosynthetically active radiation (PAR). The amount of PAR photons a plant receives is

quantified by the photosynthetic photon flux density (PPFD, $\mu mol\ m^{-2}\ s^{-1}$), which is the number of photosynthetically active photons per unit area per second. The PPFD a plant receives in a 24-hour day is directly proportional to the rate of plant growth, determined as biomass accumulation which is measured by the daily light integral (DLI, $mol\ m^{-2}\ d^{-1}$). While PPFD and DLI are important plant growth parameters for characterizing plant development, they ignore spectral quality differences of radiation received by the plant.

Spectral quality is an important growth parameter since the efficiency of photosynthesis is dependent on the wavelength of the photon absorbed by the plant. The wavelength-dependent photosynthetic efficiency can be determined by the photosynthetic quantum yield (QY), a measure of the production of oxygen or consumption of carbon dioxide, for various crops.[8,9] The photosynthetic action spectrum (Figure 1a, lettuce), compares the relative photosynthetic QY per wavelength, and indicates that wavelengths between 575 nm and 675 nm are ~30% more efficient for photosynthesis than photons in the blue waveband (400-500nm).

Several recent studies about light spectra effects on plant growth have determined that both light quantity and quality affected plant morphology.[10-13] Using a broad-spectrum light source to grow plants outperformed monochromatic light treatments, but modifying the relative percentages of different wavelengths did produce varied and improved results. For example, the sensitivity of seven plant species to blue and green light with a daylight-equivalent 500 $\mu mol\ m^{-2}\ s^{-1}$ PPFD, reduced dry mass in tomatoes cucumbers, and peppers when blue light was increased between 11% and 28% of the total spectrum.[13] At 200 $\mu mol\ m^{-2}\ s^{-1}$ PPFD, tomato continued to be negatively affected, where dry mass was reduced by 41%, while no difference was observed in pepper or cucumber. These results illustrated the importance of spectral quality for influencing plant response, particularly in high light intensity environments, and suggest that there are optimal spectra for different plant species.

Figure 1. (a) The emission spectra of the two QD films with peak PL emissions of 600 nm (orange, solid line) and 660 nm (red, dashed line) overlapped on the photosynthetic response curve for lettuce (green, squares) measured by McCree.[8] (b) Photograph of the PGTC for lettuce plant trials. Three light treatment areas were used to compare different light spectra created by QD films (left and right) to a Control film (middle) under similar light intensity. The spectra of QD films with peak emission of (c) 660 nm and (d) 600 nm were normalized to have an area of 1 and then integrated over PAR wavelengths (400-700 nm) to determine the portion of the emission that was outside of PAR.

Spectral control with CIS/ZnS QD films

QDs have been utilized for a variety of applied technologies, including remote phosphors for displays,[14,15] solid-state lighting,[16,17] solar harvesting electricity generation,[18,19] cancer detection,[20-22] and even for studying pollination habits of bees.[23,24] Here we introduce a new application, incorporating QDs into luminescent agriculture films to improve crop production in greenhouses. Luminescent QD films enable passive modification of the solar spectrum to improve light quality. In this study, CIS/ZnS QDs are incorporated into a film to down-convert UV and blue photons to orange and red photons. Compared with

other QD compositions, CIS/ZnS QDs have unique optical properties: a size-tunable PL emission, a very high PL quantum yield (QY), and a broad spectrum emission.[25] For QDs in general, a broad emission is generally associated with a dispersion of QD sizes or compositions in an ensemble and typically result in lower conversion efficiencies due to an unoptimized synthesis procedure, but for CIS/ZnS this is a result of a defect-mediated emission.[26] Additionally, CIS/ZnS QDs exhibit a large Stokes shift, allowing for absorption in the UV and blue (see Supplemental Information) while emitting in the red or orange, which minimizes PAR absorption and shift the spectrum to more photosynthetically efficient wavelengths.

Two different QD films were manufactured, with peak emissions centered at 600 nm (Orange, O-QD) and 660 nm (Red, R-QD). These wavelengths were chosen due to the strong overlap between their emission spectra and the wavelength range associated with the highest relative photosynthetic QY for lettuce (Figure 1a).

To evaluate how the modified spectra from the QD films affect plant growth, indoor plant trials were conducted with red romaine lettuce (*Lactuca sativa* L. cv. 'Outredgeous') in a custom-built, plant growth test chamber (PGTC). The PGTC was designed to maintain a uniform environment across all plant growing areas, two of which were under O-QD and R-QD films and the third was under a Control (C) polyethylene film, without QDs (Figure 1b).

Commercially available horticultural luminaires and metal-halide (MH) lamps were installed above the three horizontally suspended films (see Methods). The light passing through the films to the plant canopies below provided spatially uniform illumination of approximately 380 $\mu mol\ m^{-2}\ s^{-1}$ PPFD and had a spectrum that was similar to the solar spectrum (see Supplemental Information). Other plant growth parameters, such as the air and root temperatures, atmospheric CO_2 concentration, PPFD, pH, and electrical conductivity (EC) were monitored and remained equivalent for all three treatment areas in each plant trial (see Supplemental Information). This ensured that only the quality of the light spectrum was varied between each treatment area.

The spectra under the O-QD and R-QD films were measured with a spectroradiometer (Apogee Instruments, PS-300) and compared with the spectra under the C film. The total PPFD and the spectral distribution within each light treatment zone is shown in Table 1, The ultraviolet (UV) and blue (B) wavelengths were clearly reduced under both of the QD films compared to the control, while the intensities of O, R, and far-red (FR) were increased, compared with the control.

Table 1. Spectral distribution under QD and control films and light treatment provided to the plants.

Film	PPFD (μmol m^{-2} s^{-1})	UV (<400 nm)	B (400-500 nm)	G (500-600 nm)	R (600-700 nm)	FR (700-800 nm)
Control	382	2.1%	31.3%	35.8%	20.6%	10.2%
Orange	395	1.4%	23.3%	36.4%	26.7%	12.1%
Red	338	0.9%	20.5%	32.3%	29.1%	17.2%

To ensure differences in production were solely resulting from spectral differences, the light intensity for each treatment area were equal. While the difference between PPFD values measured under the C and O-QD films were within 3%, PPFD under the R-QD film the PPFD was 12% lower than the control film. This lower value was attributed to a portion of the R-QD emission extending beyond 700 nm, which is outside the PAR range, and therefore was not measured by the PAR sensor. This is illustrated in Figure 1c and 1d, where normalized emission spectra of the R-QD and O-QD films, respectively indicated only 4.6% of the emission spectrum from O-QD film was outside of PAR (>700 nm), but 28.3% from the R-QD film did not contribute to PPFD. Therefore, even if the total number of incident photons was held constant for the three treatment areas, the measured PPFD would always be lower for the R-QD film compared to the other light treatments. The concentration of QDs in the O-QD and the R-QD films were similar and designed to ensure similar overall absorption of the MH light source. Since both films had similar absorption and had equivalent PL QYs of ~85%, equivalent quantities of photons were converted by each film.

With a spectroradiometer the spectral quality from 300 to 850 nm was also measured to evaluate changes in film performance throughout the experiment. No spectral differences were observed over the three experiments (Figure 2a and 2b).

Figure 2. Spectral differences (ΔPPFD) between each QD-film and control film were recorded before each experiment. Using a spectroradiometer the spectrum measured under the O QD-film (a) and R QD-film (b) were subtracted from the spectrum measured under the C film before each experiment.

Spectral effects on red romaine lettuce production

The plant study consisted of three, 28-day experiments consisting of 36 lettuce plants (N = 36) divided equally among three experimental treatments (n = 12). Plants were harvested 28 days after sowing (DAS). Post-harvest measurements included total leaf area (TLA, cm^2), edible fresh mass (FM, g), and edible dry mass (DM, g) and are shown in Figure 3). TLA was calculated with image recognition software, and manual corrections were performed as needed (see Supplemental Information). The edible portions of the plant include the leaf and shoot mass, but not the root mass. A Student's t-test ANOVA was performed on the model that included two factors, each at three levels which tested all pairwise comparisons of the effect least squares mean. The levels included O-QD, R-QD, and Control (C) film treatments, while the second

Figure 3. Experimental results of measured edible dry mass, edible fresh mass, and total leaf area for three replicate lettuce experiments under three different light spectra (n = 12 per group in each treatment; N = 36 per experiment. Error bars show one standard deviation. Effect sizes for each metric were statistically significant with a confidence level of 95%.

factor included replicate experiment numbers 1, 2, and 3. In cases where the constant variance assumption of the Student's t-test was violated, logarithmic transformation of the data was conducted to analyze the data. Cohen's d effect sizes were calculated to determine the percentage differences in edible DM, edible FM, and TLA between each QD film and C. The effect size gauged the contribution of only one factor among multiple factors (film treatment and experiment number), and as such showed the significance of the contribution from the film treatment only, despite noise in the variation from combining both factors. The results from the three film treatments across all three repeated experiments are summarized in Table 2.

Table 2. Percentage differences and significance of effect sizes, and calculated lighting-use efficiency (LUE) of O-QD and R-QD Films compared with Control (C). Statistically significant increases were observed in dry mass (DM), fresh mass (FM), and total leaf area (TLA) at confidence level $\alpha = 0.05$.

	O-QD Film (600 nm)			R-QD Film (660 nm)		
	DM	FM	TLA	DM	FM	TLA
Increase v. C (%)	+13%	+11%	+8.0%	+8.7%	+11%	+13%
p-value ($\alpha = 0.05$)	0.003	0.004	0.02	0.05	0.005	0.0003
LUE v. C (g mol^{-1})	+5.6%	+3.9%	-	+17.6%	+17.2%	-

These results provided statistically significant data that the QD films improved overall crop yield. The photosynthetic efficiency of the plants was improved because of light quality from the QD films, as more biomass was produced for DLI values compared to the control film. In general, when DLI is reduced, the biomass accumulation is reduced in direct proportion a 1% reduction in DLI correlates with a 1% reduction in biomass production for most plants.[27]

In these plant experiments, the opposite was observed for the R-QD treatment. Even with a reduction in DLI of 12% under the R-QD film, statistically significant increases were observed in edible DM, FM, and TLA. Thus, the light use efficiency (LUE, g mol^{-1}) was greater under the R-QD film, which directly correlates with the photosynthetic efficiency of the plant. The LUE was calculated by dividing the grams of fresh or dry mass produced per day by the DLI (see Supplemental Information). Table 2 illustrates how the R-QD film and O-QD films exhibited an improved LUE compared with the control.

Conclusions

This study introduced and demonstrated the benefits of a novel luminescent film technology enabled by CIS/ZnS QDs to improve spectral quality for plant growth with 95% confidence. The edible DM under the O-QD and R-QD films was increased by +13% and +9%, respectively, and the edible FM was increased by +10% under both films. The TLA was also improved under the O-QD and R-QD films by +8% and +13%, respectively. These results clearly indicated that lettuce grown under the QD films, exhibited more efficient

growth than the Control even with a reduction of 12% DLI under the R-QD film. This is supported by LUE, where the DM was 18% greater under the R-QD film and 6% greater under the O-QD film. The plant production improvements from these QD films would potentially increase crop yields in CEA cultivation and due to their light weight and a small form factor, would be applicable for space missions.

Methods

Plant growth test chamber design and operation

Lettuce plant responses to the modified spectrum of light provided by the QD films were determined within a custom-built plant growth test chamber (PGTC). The PGTC framework (1.8 x 1.0 m x 2.2 m, L x W x H) consisted of three platforms (from top to bottom): a lamp mounting platform located 61 cm above the test films support platform, which was 91 cm above the plant growth platform.

A nutrient storage tank was located below the plant growth platform at the base of the PGTC. The lamp platform had four P.L. Light Systems luminaires fitted with metal-halide (MH) lamps (Solistek, 400-W 10k Finisher) to provide uniform radiation distribution above the test film support frame (1.8 m x 1 m), that held three horizontally mounted and adjacent test films. The plant growth platform was comprised of a 1.8 m x 1 m root zone nutrient solution tray, shared by plants grown within each of three separate zones (60 cm x 86 cm x 91 cm, L x W x H). The zones were delineated with a white-on-black plastic film (California Grow Films ORCA Grow Film, 98% reflection and 99% diffusion of the visible spectrum) that was installed to maximize light intensity, ensure light uniformity, and separate each light treatment by eliminating cross-contamination of light between zones.

The air and root zone temperatures, atmospheric CO_2 concentration, and nutrient solution pH and EC were continuously monitored and remained equivalent for the plants within each of the three zones, thereby having only the light quality based on the light spectrum distribution as modified by the test film as a variable (see Supplemental Information for characteristics of environmental uniformity). A ventilation fan was installed in each test zone to exchange cool, dry air from the room with the warm, moist air of the test zone and to maintain ambient CO_2 concentration, while providing air movement among the plant leaves.

The plants were secured and spaced 12 cm x 12 cm (55 plants m^{-2}) within a rigid, high-density polyethylene (HDPE) board (61 cm x 100 cm x 2.5 cm, L x W x H) covered with ORCA Grow Film and set on top of a water-tight basin. A modified Hoagland hydroponic plant nutrient solution (see Supplemental Information

for formulation) was continually distributed and recirculated to the common root zone environment of all of the plants. The nutrient solution was maintained at a constant depth of 2.5 cm in the root zone tray by sub-irrigation from the nutrient solution storage tank (83 L), providing one volume change of solution every five minutes.

A data acquisition and control system (Campbell Scientific 21X Micrologger® datalogger) monitored and recorded 15-minute averages of plant microclimate conditions of the PGTC measured at 5-second intervals. The datalogger also activated the lamps to control the photoperiod (12:00-02:00, 14 h), and it controlled the nutrient solution pH (6.1-6.2; Weiss Research PHS-0201-3B). Quantum sensors (400-700 nm; Apogee Instruments SQ-500-SS; error $\pm$ 0.8%) and radiation-shielded thermistors (Campbell Scientific 107 BetaTherm 100K6A1IA, error $\pm$ 0.5 °C) were installed in each test zone of the PGTC to measure PPFD (μmol m^{-2} s^{-1}) and air temperature (°C), respectively. Average photoperiod/scotoperiod air temperatures were 24/20 °C, respectively, and average air temperature differences between each test zone remained within $\pm$ 0.5 °C throughout the experiments (see Supplemental Information for environmental data). The atmospheric CO_2 concentration (ppm; Vaisala GMT222, error $\pm$ 1.5%) was monitored in the room adjacent to the PGTC but not controlled and ranged from 361-376 ppm for each experiment.

The recirculating, deep-water culture hydroponic nutrient delivery system consisted of a pump, four emitters, one drain, and two cylindrical storage reservoirs connected with each other at both ends. The shared nutrient solution temperature (°C, Type T copper-constantan thermocouple, error $\pm$ 1.0 °C) and electrical conductivity (EC, mS cm^{-1}; Hanna Instruments HI-3001) were measured and recorded. The acidity of the nutrient solution was controlled to maintain setpoint (pH 6.1-6.2) by the addition of dilute nitric acid into the nutrient storage reservoir by a peristaltic pump. The nutrient storage tank was monitored and manually refreshed daily to maintain EC setpoint (1.8-1.9 mS cm^{-1}) by addition of pre-mixed nutrient solution. Nutrient solution and/or tap H_2O was manually added to the storage reservoirs on a daily basis to ensure the EC remained on target. The nutrient solution was pumped up from the reservoirs to the back wall of the PGTC, where the manifold of four equidistant emitters constantly output nutrient solution to the

lettuce plants in the shared basin. The nutrient solution drained from a single drain at the opposite end of the basin, where it returned to the nutrient storage reservoirs for recirculation.

Plant studies in the PGTC

In each plant experiment, lettuce plants were established by double-seeding 150, 3.8-cm rockwool starter cubes (Grodan AO 36/40) with red romaine lettuce (*Lactuca sativa* L. cv. 'Outredgeous'; Johnny's Seeds, organic variety). They were placed in the three plant zones in the PGTC for 48-72 h without light till seed germination was observed. Germination was marked by root radicle emergence from the seed, after which a 14-h photoperiod (14 h of light per 24-hour period) was initiated to provide a target average daily light integral (DLI) of 17 mol m^{-2} d^{-1} (see Supplemental Information for DLI values). At 7 DAS, the first true leaves emerged, and thinning was performed to leave one healthy seedling in each rockwool cube. Extra rockwool cubes were removed from the floating raft within each of the three treatment zones to achieve a final planting density of 55 plants m^{-2}. The experimental treatments continued to harvest at 28 DAS.

The rockwool cubes were irrigated continuously with pH 6.2 tap H_2O until germination, and between germination and thinning they were irrigated with half-strength modified Hoagland's nutrient solution (see Supplemental Information for formulation). After thinning, full-strength solution was used in the recirculating hydroponic basin which continuously pumped stored nutrient solution to plants in all three zones for the duration of the experiment at a system turnover rate of 5 min.

Harvest occurred at 28 DAS when the edible fresh mass (g) was measured for each data plant (n=12 per treatment, N=36 total). Leaves were then flattened and photographed for measurement of total leaf area (TLA, cm^2) with image analysis software (see Supplemental Information for software description). After photographing, each plant sample was individually bagged and labeled, dried in a drying oven at 40 °C for 72 h to ensure thoroughly uniform drying (see Supplemental Information for percentage dry mass values), and weighed to determine dry mass (g).

QD film manufacture and optical properties

The CuInS$_2$ (CIS)/ZnS QDs used in this study were manufactured using methods similar to those described in reference 28 with slight modifications to optimize peak wavelength emission and QY. Size of the orange (590 nm PL emission) and red (630 nm PL emission) QDs are 4.8 ± 0.7 nm and 5.1 ± 0.9 nm, respectively, and have typical size distribution of ~15-19%. The CIS QDs were incorporated into agriculture films 60 cm x 91 cm in size by dispersing the nanoparticles into an acrylic resin (described in reference 29), which was then coated between two sheets of polyethylene terephthalate (PET) barrier film (manufactured by I-Components, Co.) using a drawdown method. The water vapor transmission rate for the PET barrier films was 0.09 (g/m^2/day). The laminate film was then exposed to 405-nm emitting LEDs to cure the nanocomposite interlayer. The total thickness of the films was 350 µm with an interlayer thickness of 150 µm. After curing the QD resin between the two PET layers, the optical properties of both films were characterized. The PL QY was measured with a commercial PL spectrometer (Horiba Fluoromax 4) equipped with an integrating sphere and using an excitation wavelength of 440 nm. The QY of each film was measured to be $85\% \pm 5\%$, with a peak emission for the O-QD film at 600 nm (120 nm FWHM) and at 660 nm (120 nm FWHM) for the R-QD film. The haze of both QD films and the bi-layer, 6 mil polyethylene (PE) C film was measured using a custom-built setup consisting of a collimated 640-nm LED light source, a 30.5-cm diameter integrating sphere, and a fiber optic spectrometer (Avantes AvaSpec Dual Channel). The haze for all three films was measured to be $2\% \pm 0.5\%$.

Acknowledgements

This work was funded under a Small Business Technology Transfer contract by the National Aeronautics and Space Administration under Award No. 80NSSC18P2144 and the University of Arizona ALVSCE Bridge Funding Program 2019. The authors acknowledge KC Shasteen for developing and implementing the total leaf area analysis program and also acknowledge Lingling An, PhD, for consulting on statistical methods.

Competing financial interests

Authors CHP, DH, AJ, KR, HM, and MRB are employed by UbiQD, Inc. and also have equity in the company. Author GG declares no competing interests.

References

[1] Williams, A. P., Cook, E. R., Smerdon, J. E., Cook, B. I., Abatzoglou, J. T., Bolles, K., Baek, S. H., Badger, A. M., & Livneh, B. Large contribution from anthropogenic warming to an emerging North American megadrought. *Science* **368**(6488), 314-318 (2020).

[2] Fedoroff, N.V. "Food in a Future of 10 Billion." *Agriculture & Food Security* **4**, 11 (2015).

[3] Vox, G., Teitel, M., Pardossi, A., Minuto, A., Tinivella, F., & Schettini, E. Sustainable Greenhouse Systems. In A. Salazar & I. Rios (Eds.), *Sustainable Agriculture: Technology, Planning and Management* (pp. 1-80). Nova Science Publishers. (2010).

[4] Sabeh, N.C., Giacomelli, G.A., Kubota, C. Water use by greenhouse evaporative cooling systems in a semi-arid climate. *ASAE Annual Meeting* 074013 (2017).

[5] Morrow, R., & Remiker, R. A Deployable Salad Crop Production System for Lunar Habitats. *SAE Technical Paper* 2009-01-2382, (2009).

[6] Giacomelli, G. A., Furfaro, R., Kacira, M., Patterson, L., Story, D., Boscheri, G., Lobascio, C., Sadler, P., Pirolli, M., Remiddi, R., Thangavelu, M., & Catalina, M. Bio-regenerative life support system development for Lunar/Mars habitats. *42nd International Conference on Environmental Systems*, July 15-19, 2019, San Diego, California (2012).

[7] Nelson, J. A., & Bugbee, B. Economic Analysis of Greenhouse Lighting: Light Emitting Diodes vs. High Intensity Discharge Fixtures. *PLoS ONE* **9**(6) (2014). https://doi.org/10.1371/journal.pone.0099010

[8] McCree, K. J. The action spectrum, absorptance and quantum yield of photosynthesis in crop plants. *Agricultural and Forest Meteorology* **9**,191-216 (1972). https://doi.org/10.1016/0002-1571(71)90022-7

[9] McCree, K. J. Test of current definitions of photosynthetically active radiation against leaf photosynthesis data. *Agricultural and Forest Meteorology* **10**, 443-453 (1972). https://doi.org/10.1016/0002-1571(72)90045-3

[10] Mickens, M.A., Skoog, E.J., Reese, L.E., Barnwell, P.L., Spencer, L.E., Massa, G.D., & Wheeler, R.M. A strategic approach for investigating light recipes for 'Outredgeous' red romaine lettuce using white and monochromatic LEDs. *Life Sciences in Space Research* **19**, 53-62 (2018). https://doi.org/10.1016/j.lssr.2018.09.003

[11] Snowden, M. C., Cope, K. R., & Bugbee, B. Sensitivity of Seven Diverse Species to Blue and Green Light: Interactions with Photon Flux. *PLoS ONE* **11**(10) (2016).

[12] Cope, K. R., & Bugbee, B. Spectral Effects of Three Types of White Light-emitting Diodes on Plant Growth and Development: Absolute versus Relative Amounts of Blue Light. *HortScience* **48**(4), 504-509 (2013).

[13] Cope, K. R., Snowden, M. C., & Bugbee, B. Photobiological interactions of blue light and photosynthetic photon flux: effects of monochromatic and broad-spectrum light sources. *Photochemical Photobiology* **90**(3) (2014).

[14] Cho, K.-S., Lee, E. K., Joo, W.-J., Jang, E., Kim, T.-H., Lee, S. J., Kwon, S.J., Han, J. Y., Kim, B.-K., Choi, B. L., & Kim, J. M. High-performance crosslinked colloidal quantum-dot light-emitting diodes. *Nature Photon*ics **3**, 341–345 (2009).

[15] Kim, T.-H., Cho, K.-S., Lee, E. K., Lee, S. K., Chae, J., Kim, J. W., Kim, D. H., Kwon, J.-Y., Amaratunga, G., Lee, S. Y., *et al*. Full-colour quantum dot displays fabricated by transfer printing. *Nature Photon* 5, 176-182 (2011).

[16] Yang, X., Zhao, D., Leck, K. S., Tan, S.T., Tang, Y.X., Zhao, J., Demir, H. V., & Sun, X. W. Full visible range covering InP/ZnS nanocrystals with high photometric performance and their application to white quantum dot light-emitting diodes. *Advanced Materials*, **24**, 30 (2012).

[17] Caruge, J. M., Halpert, J. E., Wood, V., Bulović, V., & Bawendi, M. G. Colloidal quantum-dot light-emitting diodes with metal-oxide charge transport layers. Nature Photon **2**, 247-250 (2008).

[18] Meinardi, F., McDaniel, H., Carulli, F., Colombo, A., Velizhanin, K. A., Makarov, N. S., Simonutti, R., Klimov, V. I., & Brovelli, S. Highly efficient large-area colourless luminescent solar concentrators using heavy-metal-free colloidal quantum dots. *Nature Nanotechnology* **10**, 878-885 (2015).

[19] Semonin, O. E., Luther, J. M., Choi, S., Chen, H. Y., Gao, J., Nozik, A. J., & Beard, M. C. Peak external photocurrent quantum efficiency exceeding 100% via MEG in a quantum dot solar cell. *Science*, **334**(6062), 1530-1533 (2011).

[20] Gao, X., Cui, Y., Levenson, R. M., Chung, L. W. K., & Nie, S. *In vivo* cancer targeting and imaging with semiconductor quantum dots. *Nature Biotechnology* **22,** 969-976 (2004).

[21] McHugh, K. J., Jing, L., Behrens, A. M., Jayawardena, S., Tang, W., Gao, M., Langer, R., & Jaklenec, A. Biocompatible semiconductor quantum dots as cancer imaging agents. *Advanced Materials* **30**, 18, 1706356 (2018).

[22] Makarov, N.S., Ramasamy, K., Jackson, A., Velarde, A., Castaneda, C., Archuleta, N., Hebert, D., Bergren, M.R., & McDaniel, H. Fiber-coupled luminescent concentrators for medical diagnostics, agriculture, and telecommunications. *ACS Nano* **13**, 8, 9112-9121 (2019).

[23] Minnaar, C., Anderson, B. Using quantum dots as pollen labels to track the fates of individual pollen grains. *Methods in Ecology and Evolution* **10**, 5, 604-614 (2019).

[24] Minnaar, C., de Jager, M.L., Anderson, B. Intraspecific divergence in floral-tube length promotes asymmetric pollen movement and reproductive isolation. *New Phytologist* **224**, 3, 1160-1170 (2019).

[25] Makarov, N. S., Ramasamy, K., Jackson, A., Velarde, A., Castaneda, C., Archuleta, N., Hebert, D., Bergren, M. R., & McDaniel, H. Fiber-Coupled Luminescent Concentrators for Medical Diagnostics, Agriculture, and Telecommunications. *ACS Nano* **13**(8), 9112-9121 (2019).

[26] Zang, H.; Li, Hongbo; Makarov, N.S.; Velizhanin, K.A; Wu, K.; Park, Y.S.; Klimov, V.I. Thick-shell CuInS2/ZnS Quantum Dots with Suppressed "Blinking" and Narrow Single-Particle Emission Line Widths. *Nano Letters* **17**, 1787-1795 (2017)

[27] Marcelis, L. F. M., Broekhuijsen, A. G. M., Meinen, E., Nijs, E. M. F. M., & Raaphorst, M. G. M. Quantification of the growth response to light quantity of greenhouse grown crops. *Acta Horticulturae* **711**, 97-104 (2006).

[28] McDaniel, H., Koposov, A. Y., Draguta, S., Makarov, N. S., Pietryga, J. M., & Klimov, V. I. Simple yet Versatile Synthesis of CuInSexS2-x Quantum Dots for Sunlight Harvesting. *J. Phys. Chem. C* 118, 16987-16994 (2014).

[29] Bergren, M. R., Makarov, N. S., Ramasamy, K., Jackson, A., Guglielmetti, R., & McDaniel, H. High-Performance CuInS2 Quantum Dot Laminated Glass Luminescent Solar Concentrators for Windows. *ACS Energy Letters* **3**, 520−525 (2018).