GenNet framework: interpretable neural networks for phenotype prediction

Arno van Hilten[1], Steven A. Kushner[2], Manfred Kayser[3], M. Arfan Ikram[4], Hieab H.H.

Adams[1,5], Caroline C.W. Klaver[4,6], Wiro J. Niessen*[1,7] and Gennady V. Roshchupkin*[1,4]

[1] Department of Radiology and Nuclear Medicine, Erasmus MC, Medical Center, Rotterdam, the Netherlands.
[2] Department of Psychiatry, Erasmus MC, Medical Center, Rotterdam, the Netherlands.
[3] Department of Genetic Identification, Erasmus MC, Medical Center, Rotterdam, the Netherlands.
[4] Department of Epidemiology, Erasmus MC, Medical Center, Rotterdam, the Netherlands.
[5] Department of Clinical Genetics, Erasmus MC, Medical Center, Rotterdam, the Netherlands.
[6] Department of Ophthalmology, Erasmus MC, Medical Center, Rotterdam, the Netherlands.
[7] Faculty of Applied Sciences, TU Delft, Delft, the Netherlands.

*Jointly supervised this project

Deep learning is rarely used in population genomics because of the computational burden and challenges in interpreting neural networks. Here, we propose GenNet, a novel open-source deep learning framework for predicting phenotypes from genetic variants. In this framework, interpretable and memory-efficient neural network architectures are constructed by embedding biological knowledge from public databases, resulting in neural networks that contain only biological plausible connections.

We applied the framework to seventeen phenotypes from a case-control study, a population-based study and the UK Biobank. Interpreting the networks revealed well-replicated genes such as _HERC2_ and _OCA2_ for hair and eye color and novel genes such as _ZNF773_ and _PCNT_ for schizophrenia. Additionally, the framework obtained an AUC of 0.74 in the held-out test set and identified ubiquitin mediated proteolysis, endocrine system and viral infectious diseases as most predictive biological pathways for schizophrenia.

GenNet is a freely available, end-to-end deep learning framework that allows researchers to develop and use interpretable neural networks to obtain novel insights into the genetic architecture of complex traits and diseases.

Introduction

While genome-wide association studies (GWAS) have identified numerous genomic loci associated with complex traits and diseases, the biological interpretation of the underlying mechanisms often remain unclear. Recent GWAS studies with increasingly large sample sizes are resulting greater numbers of significant associations, at an increasing number of independent loci. To illustrate, the latest GWAS for body height based on 700,000 individuals identified more than 3000 near-independent significantly associated single nucleotide polymorphisms (SNPs)[1]. Uncovering a clear biological interpretation from all this information is a challenging task, in which causal variants, genes and pathways need to be identified. In response, many methods such as MAGMA[2], ALIGATOR[3] and INRICH[4], have been developed to obtain a biological interpretation from GWAS summary statistics, providing insights into relevant genes and pathways for defined phenotypes of interest. These methods explore GWAS summary statics and utilize knowledge from annotated biological databases such as NCBI RefSeq[5], KEGG[6], Reactome[7] and GTEx[8], that have proven to contain crucial information for understanding the underlying biological mechanisms of the human genome.[9]

Given the increasing amount of data available via biobanks and new developments to integrate data, it is now feasible to analyze raw data with more advanced methods. Deep learning is the state of the art in many domains such as medical image analysis[10] and natural language

processing[11] because of its flexibility and modeling capabilities. In many cases, deep learning

yields better performance than traditional approaches, since it scales very well with data size and

can model highly non-linear relationships. However, a limitation to deep learning is that these

algorithms are often uninterpretable because of their complexity[12,13]. Additionally, genetic data

does not lend itself well to the convolution operation, the main driver of the success of deep

learning in the imaging domain. Classical fully connected neural networks are not feasible

because of the millions of input variants, a fully connected layer would require an infeasible

amount of computational time and memory.

To overcome these limitations, we propose GenNet, a novel framework for predicting phenotype

from genotype. Within the GenNet framework, biological information from annotated biological

sources such as NCBI RefSeq, KEGG and single RNA gene expression datasets, is used to

define biologically plausible connections. As a result, neural networks based on this framework

are memory efficient, interpretable and yield biological interpretations for their predictions.

GenNet is an end-to-end deep learning framework available as a command line tool

(https://github.com/ArnovanHilten/GenNet/).

Figure 1. Overview of the GenNet Framework. Neural networks are created by using prior

biological knowledge to define connections between layers (i.e., SNPs are connected to their

corresponding genes by using gene annotations and genes are connected to their corresponding

pathway by using pathway annotations). Prior knowledge is thus used to define each connection,

creating interpretable networks.

Methods

The main concept of the GenNet framework is summarized graphically in Figure 1. In this

framework, prior knowledge is used to create groups of connected nodes to reduce the number of

learnable parameters in comparison to a fully connected neural network. For example, in the first

layer, biological knowledge in the form of gene annotations, is used to group millions of SNPs

and to connect those SNPs to their corresponding genes. The resulting layer retains only

meaningful connections, significantly reducing the total number of parameters compared to a

classical fully connected layer. Because of this memory-efficient approach networks in the

GenNet framework are able to handle millions of inputs for genotype-to-phenotype prediction.

Biological knowledge is thus used to define only meaningful connections, shaping the

architecture of the neural network. Interpretability is inherent to the neural network's

architecture; each node is uniquely defined by its connections and represent a biological entity

(e.g., gene, pathway). For example, a network that connects SNPs-to-genes and genes-to-output.

The learned weights of the connections between layers represent the effect of the SNP on the

gene or the effect of the gene on the output. In the network, all neurons represent biological

entities and weights model the effects between these entities, together forming a biologically

interpretable neural network.

Many types of layers can be created using this principle. Apart from gene annotations, our

framework provides layers built from exon annotations, pathway annotations, chromosome

annotations, and cell and tissue type expressions. All these layers can be used like building

blocks to form new neural network architectures.

Results

We built proof of concept simulations as shown in Figure 2A and described in Supplementary

Material 1. These simulations demonstrate that the proposed network architecture is

interpretable, the strongest weights are assigned to causal variants and genes. Next, we designed

experiments to test the network architecture's performance under a variety of conditions.

Performance is dependent on phenotype, neural network architecture and dataset size. To

disentangle this, we created simulated data with varying levels of heritability, number of training

samples and polygenicity (Supplementary Materials 1). Figures 2B and 2C demonstrate the

major trends observed in the simulations. As expected, the network performs best for traits with

high heritability, high number of training samples, and low polygenicity.

*Figure 2. **A)** A simple, non-linear proof of concept. In this simulation, each gene in the causal*

region has two causal SNPs that cause the simulated disease. The magnitude of the learned

weight is represented by the line thickness (contributing causal connections in red, non-

contributing control connections in grey). **B)** *A secondary set of simulations show the*

performance of GenNet, expressed as area under the curve, for increasing levels of heritability

and training set size **(C)**. *The black curve presents the theoretical maximum of the AUC versus*

heritability.   **D)** *Manhattan plot showing genes and their relative importance according to the*

network, here we have shown the results for distinguishing between schizophrenia cases and

controls in the Sweden exome study. **E)** *This Manhattan plot is a cross section between the gene*

layer (21,390 nodes) and the outcome of a trained network with 1,288,701 input variants.

Motivated by the proof-of-concept and outcomes of the simulations, we applied the framework

to data from multiple sources, including population-based data from the UK Biobank study[14] ,

the Rotterdam study[15], and the Swedish Schizophrenia Exome Sequencing study[16]. Phenotypes

vary from traits that can be predicted well from only a dozen variants (eye color) to disorders in

which thousands of variants explain only a small portion of the variance (schizophrenia and

bipolar disorder)[17,18]. The datasets also vary in size and type of data. We used 113,241 exonic

variants from imputed microarray-based GWAS data from the Rotterdam study for predicting

eye color while we predict fourteen phenotypes in the UK Biobank using 6,986,636 input

variants from whole exome sequencing (WES) data. Finally, we used 1,288,701 WES input

variants for predicting schizophrenia in the Swedish study. An overview of the main results for

networks embedded with gene and pathway information can be found in Table 1. The results for

all the experiments, including expression-based networks, can be found in Supplementary 2.

Dataset (type)	Trait	Subjects & phenotype		AUC gene test (val)	Top three predictive genes	AUC pathway test (val)	Top predictive pathway		
		Class I	Class II				Global level	Middle level	Local level
Rotterdam Study (genotype array)	Eye color	4041 Blue	2250 Other	**0.75 (0.74)**	*HERC2, OCA2, LAMC1*	0.50 (0.52)	Organismal Systems (78.4%)	Digestive system (72.6%),	Pancreatic secretion (59.1%)
UK Biobank (exome)	Hair color	1734 Red	1727 Other	**0.93 (0.94)**	*MC1R*, SHOC2, DCTN3*	0.77 (0.77)	Genetic Information Processing (87.4%)	Replication and repair (83.4%),	Fanconi anemia pathway (79.7%)
		3762 Black	3753 Other	0.80 (0.82)	*OCA2, RPL23AP8, MC1R**	0.76 (0.78)	Organismal Systems (46.9%)	Endocrine system (18.6%)	Axon guidance (5.0%)
		4501 Blond	4518 Other	**0.66 (0.65)**	*OCA2, TC2N, SLC45A2*	0.58 (0.57)	Organismal Systems (70.2%)	Endocrine system (30.1%),	Adrenergic signaling in cardiomyocytes (4.1%)
	Bipolar disorder	343 Cases	347 Controls	**0.60 (0.56)**	*LINC00266-1, CSMD1, TCERG1L*	0.47 (0.55)	Organismal Systems (76.9%)	Endocrine system (46.5%)	Melanogenesis (32.9%)
	Atrial fibrillation	192 Cases	194 Controls	**0.56 (0.59)**	***BRINP1, SORBS3, ELM0D3*	0.57 (0.63)	Organismal Systems (39.6%)	Signal transduction (11.2%)	Cytokine-cytokine receptor interaction (4.4%)
	Coronary Artery Disease	1563 Cases	1600 Controls	**0.56 (0.58)**	***STARD7-AS1, VWC2L, NSD2*	0.54 (0.56)	Environmental Information Processing (29.5%),	Signal transduction (27.7%)	PI3K-Akt signaling pathway (4.6%)
	Dementia	139 Cases	142 Controls	**0.60 (0.65)**	*RPL23AP87, CTNNA3, LINC01003*	0.55 (0.58)	Human Diseases (39.8%)	Signal transduction (22.2%)	Pathways in cancer (5.6%)
	Male balding pattern	3454 Balding pattern 1	3454 Balding pattern 4	**0.56 (0.57)**	*NGEF, NKRD18B, SYNJ2*	0.54 (0.55)	Organismal Systems (34.6%)	Nervous system (9.7%)	Metabolic pathways (8.7%)
	Asthma	4229 Cases	4214 Controls	**0.55 (0.57)**	*HLA-DQB1, HCG9, LINC00266-1*	0.51 (0.54)	Genetic Information Processing (52.3%)	Folding, sorting and degradation (41.5%)	Ubiquitin mediated proteolysis (22.0%)
	Diabetes	2557 Cases	2555 Controls	**0.54 (0.57)**	***DNAH10, SNAR-I, PSMD13*	0.54 (0.54)	Environmental Information Processing (43.5%),	Signal transduction (40.5%),	Ras signaling pathway (7.9%)
	Breast cancer	1070 Cases	1082 Controls	**0.51 (0.56)**	*RPL23AP87, LINC00266-1, HPSE*	0.51 (0.56)	Human Diseases (57.1%)	Infectious diseases: Viral (16.6%)	Pathways in cancer (6.5%)
Sweden (exome)	Schizophrenia	4969 Cases	6245 Controls	**0.74 (0.73)**	*ZNF773, PCNT, DYSF*	0.68 (0.67)	Human Diseases (30.8%)	Infectious diseases: Viral (27.3%)	Human papillomavirus infection (11.7%)

Table 1. Overview of the main results of the experiments. The performance in AUC for the

network with gene-annotations is bold if the network outperformed or matched LASSO

regression. Manhattan plots for the genes can be found in Supplementary Materials 3, 4 and 5.

*MC1R was not annotated but was identified by linkage disequilibrium. **Many genes

contributed to the prediction without clear separation between genes (see Supplementary

Materials 4).

Phenotypes with more training samples and that require less variants to obtain high predictive

performance, such as eye and hair color, yielded the best performance. Nonetheless, we

achieved a good predictive performance for schizophrenia, a highly polygenic disorder, with an

area under the curve (AUC) of 0.74 in the held-out test set. All models based on gene

annotations outperformed or matched the baseline LASSO logistic regression model with the

exception of the black hair color phenotype.

Inspecting the networks, we found that the *OCA2* gene was the most important gene to predict

blond, dark and light brown hair color. *OCA2* is involved in the transport of tyrosine, a precursor

of melanin.[19] The *OCA2* signal is likely amplified by the nearby gene *HERC2*, previously

identified via functional genetic studies as harboring a strong, long-distance enhancer regulating

OCA2 gene expression underlaying pigmentation variation.[19] According to the network, *OCA2*

and *HERC2* are the two most predictive genes for predicting blue iris color. Both genes were

previously identified through GWAS studies of hair and eye color.[20–22]

In the experiments with schizophrenia as outcome, the network was able to classify cases and

controls with a maximum accuracy of 0.685 (mean of 0.663 ± 0.014 over 10 runs). Based on all

genetic aspects, we estimate the theoretical upper limit for classification accuracy to be roughly

0.72 for schizophrenia (Supplementary Materials 7). The model achieved a maximum area under

the receiver operating curve of 0.738 (mean of 0.715 ± 0.016) in the held-out test set over 10

runs, thereby considerably outperforming the LASSO logistic regression baseline which obtained

a maximum AUC of 0.649 (mean of 0.644 ± 0.003). The genes *ZNF773, PCNT* and *DYSF* were

assigned the highest weights by the neural network and were thus considered to be the most

predictive genes for schizophrenia. However, the polygenic nature of schizophrenia can be seen

when comparing the Manhattan plot of the genes (Figure 2D) to other phenotypes in this study

(Supplementary Materials 3,4 and 5). More genes contributed to the prediction for schizophrenia

than for the other phenotypes examined.

Figure 3. Sunburst plot of the important pathways for predicting schizophrenia. A neural

network with layers based on KEGG pathway information was trained to predict schizophrenia.

The relative importance was calculated for each pathway using the learned weights of this

neural network. The sunburst plot is read from the center, which shows the output node with the

prediction of the neural network. The inner ring represents the last layer with the highest-level

pathways, followed by the mid-level pathways and finally the lowest-level pathways. The gene

and SNP layer are omitted for clarity.

Figure 3 shows the relative importance of the pathways for predicting schizophrenia. The neural

network, embedded with the KEGG pathway information, obtained an AUC of 0.68 in the test

set. Human diseases (30.8%), organismal systems (26.7%) and genetic information processing

(26.5%) were the main contributors to the neural network's prediction of schizophrenia. The

contribution of human diseases was mainly driven by viral infectious diseases (27.3%) which can

be subdivided further into human papillomavirus infection (11.7%), herpes simplex infections

(3.7%), and human cytomegalovirus infection (3.2%), as well as genes and SNPs assigned to

these diseases. The ubiquitin mediated proteolysis pathway, a subset of the genetic information

pathway, had a relative importance of 10.0%.

To investigate if the most predictive genes are concentrated in a single cell or tissue type, we

used three different gene expression datasets processed by Finucane et al. (2018)[23] to create

layers subsequent to the gene-based layer. The relative importance of the trained networks

showed a widespread signal with small contributions by many cell and tissue types. When GTEx

data was embedded in the network, uterine genes had the greatest relative importance (4.2%).

For GTEx brain expression data the frontal cortex (15.1%) had the strongest contribution,

whereas for immune cell types mesenteric lymph nodes (1.23%) contributed most. An overview

of the experiments performed, including GTEx and other expression-based networks for other

phenotypes, can be found in Supplementary Material 2.

Discussion

We presented a novel framework for predicting phenotypes from genotype with interpretable

neural networks. The proposed neural networks have connections defined by prior biological

knowledge only, reducing the number of connections and therefore the number of trainable

parameters. Consequently, the networks can be trained on a single GPU and offer a biological

interpretation for their predictions.

In the first set of experiments, simulations showed the network's performance when varying the

degree of heritability, polygenicity and sample size. In the second set of experiments the

framework was applied to UK Biobank, Rotterdam study and Swedish Schizophrenia Exome

Sequencing Study data. In these experiments, phenotypes with widely different heritability,

sample size and polygenicity were predicted with generally high predictive performance. For

example, we obtained an AUC of 0.96 for red hair color, an AUC of 0.74 for blue eye color and

an AUC of 0.74 for predicting schizophrenia. For schizophrenia, polygenic risk scores from

genome wide association studies obtain similar AUCs, ranging from 0.49 to 0.85, while spanning

the whole genome and using larger sample sizes.[17]

Interpretation of the trained networks revealed well-replicated genes for traits with a known

etiology such as *HERC2* and *OCA2* for eye color and *OCA2* and *TC2N* for hair color.[20–22,24] For

schizophrenia, a disorder with an unclear etiology, the network identified novel genes, including

ZNF773 and *PCNT*. In previous studies, *PCNT* was only nominally associated with

schizophrenia, although it is known to have interactions with *DISC1* (Disrupted in

Schizophrenia-1).[25] There is a strong correlation between (prenatal) viral infections and

increased risk for developing schizophrenia.[26] It is therefore interesting that by using the KEGG

pathway information to create layers, we identified the viral infectious diseases pathway with its

associated pathways, genes and SNPs to be the most important for predicting schizophrenia. The

results of these experiments reveal that with GenNet framework can provide insights across

multiple functional levels, identifying which SNPs, genes, pathways and tissue types are

important for prediction.

In this study, WES data and exonic variants from microarrays have been used, however the

principles in the GenNet framework can be extended to handle diverse types of input, including

genotype, gene expression and methylation data or combinations thereof. Similarly, we explored

only a fraction of the possible layers as building blocks for our networks. Any data that create

unique biological groups can be used in the framework to create new layers. However, the

quality of the resulting network is highly dependent on the quality of the data used. For example,

networks built with biological pathway data performed generally worse than networks using only

gene annotations since many genes are not annotated to pathways. But with new and better data

from projects such as GTEx[8], ENCODE [27] and KEGG[6] the quality of the layers will only

improve. Moreover, given the increasing sample sizes of biobanks in coming years and the

development of algorithms, which allow distributed deep learning between cohorts without

sharing raw data[28], we foresee that our framework can be easily adopted for such settings and

can be widely used for quantitate traits and functional mapping analysis.

In conclusion, we developed a freely-available framework, which can be used to build

interpretable neural networks for genotype data by incorporating prior biological knowledge. In

addition to computationally efficient, the architectures are interpretable, thereby alleviating one

of the most important shortcomings of neural networks. We have demonstrated the effectiveness

of this novel framework across multiple datasets and for multiple phenotypes. Given that each

network node is interpretable, we anticipate this approach to have wide applicability for

uncovering novel insights into the genetic architecture of complex traits and diseases.

Online Methods

Sweden Schizophrenia Exome Sequencing Study

Sweden-Schizophrenia Population-Based Case-Control Exome Sequencing study (dbGaP

phs000473.v2.p2), is a case control study with 4969 cases and 6245 controls.[16] All individuals

aged 18-65, have parents born in Sweden, and provided written informed consent. The following

inclusion criteria were used for cases: at least two times hospitalized with schizophrenia

discharge diagnosis; no hospital register diagnosis consistent with a medical or other psychiatric

disorder that mitigates the schizophrenia diagnosis. Cases were excluded if they had a

relationship closer than 2nd degree relative with any other case. Controls were matched to cases

and controls were never hospitalized with a discharge diagnosis of schizophrenia. Controls were

excluded if they had any relation to either case or control.

The downloaded plink files were converted using HASE[29] to hierarchical data format (HDF), a

format that allows fast and parallel data reading. After conversion, the data was transposed and

SNPs without any variance were removed (1,288,701 SNPs remain). The data was split in a

training, validation and test set (ratio of 60/20/20), while preserving the ratio cases and controls.

UK Biobank

We applied the framework to multiple phenotypes in the UK Biobank using the first release of

the WES data, providing whole exome sequencing for 50,000 UK Biobank participants.[30]

Phenotypes are self-reported using touchscreen questions in the UK Biobank Assessment Centre.

Similar to the Sweden cohort all variants without variance were removed, data was converted to

hierarchical data format, and transposed. For every phenotype an equal number of cases and

controls were sampled. The resulting dataset is split in a train, validation and a test set (ratio of

60/20/20). Related cases, and cases with related controls, (kinship > 0.0625) are all in the

training set. This is done under the assumption that related cases and controls could ease training,

the shared genetic information could steer the network towards the discriminatory features. The

validation and test sets contain only unrelated cases and controls within and between sets.

Unrelated controls are randomly sampled and added to gain an even distribution between cases

and controls in all sets. Misaligned SNPs and sex chromosomes were masked in the first layer

and therefore not included in the study.

Rotterdam Study

The Rotterdam study is a prospective population-based cohort study.[15] We used the first cohort

consisting of 6291 participants, genotyped using the Illumina 550K and 550K duo arrays.

Samples with low call rate (<97.5%), excess autosomal heterozygosity (>0.336) or sex-mismatch

were excluded, as were outliers identified by the identity-by-state clustering analysis (outliers

were defined as being >3 standard deviation (SD) from population mean or having identity-by-

state probabilities >97%). For imputation the Markov Chain Haplotyping (MACH) package

version 1.0 software (Imputed to plus strand of NCBI build 37, 1000 Genomes phase I version 3)

and minimac version 2012.8.6 were used (call rate >98%, MAF >0.001 and Hardy–Weinberg

equilibrium P-value $> 10^{-6}$). From here on, processing steps are identical as described for

Sweden Schizophrenia resulting in a dataset with 113,241 exonic variants for 6291 subjects.

For each subject, both eyes were examined by an ophthalmological medical researcher and eye

(iris) color was categorized into three categories; blue, intermediate and brown using standard

images and based on the predominant color and pigmentation.[31]

Prior knowledge

All SNPs were annotated using Annovar[32]. From these annotations a sparse connectivity matrix

was created, connecting the SNPs to their corresponding genes. Connectivity matrices between

SNPs, exons and genes were made using intron-exon annotations. A mapping between genes and

pathways was made using GeneSCF[33] and the KEGG database[6]. GTEx tissue-expression masks

were made using the fully processed, filtered and normalized gene expression matrices for each

tissue directly obtainable from the GTEx website[8]. All expression based layers in this paper are

created from derived t-score statistics[23] to ensure that nodes are uniquely defined by their

connections and therefore interpretable. There are many possibilities to expand the GenNet

framework, it can create layers from any data that groups data uniquely. For example the

framework contains layers based on single cell expression is created from data released by

FUMA[34].

Neural network architecture

In the GenNet framework, layers are available built from biological knowledge such as; exon

annotations, gene annotations, pathway annotations, cell expression and tissue expression.

Information from these resources is used to define only meaningful connections, shaping an

interpretable and lightweight neural network, allowing evaluation of millions of input variants

together. These networks bear similarities to the first generation of neural networks and recently

interest for these networks has rekindled for biological applications.[35–38]

The GenNet architecture aims to reduce the dimensionality of the network with a minimal loss of

information. By using layers based on prior biological knowledge, the network is reduced in a

biologically sensible way. During training, weights in the network are optimized to predict the

outcome. The network learns the relation between the SNPs, genes and other biological

information used to create the layers. Because the input to each layer is normalized, the

important connections for predicting the phenotype will receive higher absolute weights while

unimportant connections will receive lower absolute weights.

All models were trained on a single GPU with 11 GB memory (Nvidia GeForce GTX 1080 Ti)

and converged within five days. During the experiments, we noticed it is beneficial to add an L1

penalty on the weights in the last dense layer, similar to LASSO logistic regression.

Regularization constraints the search space which leads to better generalization and

interpretation.

Interpretation

Interpretation of the network is straightforward due to the simplicity of the concept, the stronger

the weight is the more it contributes to the final prediction of the network. The simplest network

in the framework, a network built by gene annotations, can be seen as ~20 000 (number of

genes) parallel regressions followed by a single logistic regression. The learned weights in these

regressions are similar to the coefficients in logistic regression. Especially the last node, a single

neuron with a sigmoid activation, $P = Sigmoid(\sum_{i=0}^{n} x_i w_i + B)$ is very similar to logistic

regression $Y = Sigmoid(\sum_{i=0}^{n} x_i \beta_i + B)$.

The inputs in logistic regression are generally normalized to compare coefficients (β). In the

neural network this is achieved by batch normalization (without center and scaling), normalizing

the weights (w) after every activation. The weights can then be compared and used as an

importance measure. Since batch normalization is a batch-wise approximation, the learned

weights can be multiplied with the standard deviation of the activations for a more accurate

estimate. For Manhattan plots, the normalized, absolute weights between the gene layer and the

output is used.

In larger networks, the relative importance is calculated by multiplying the weights for each

possible path from the end node to the input SNPs. At each input we obtain then a value denoting

its contribution. These values are then aggregated (summed) according to the groups of the

subsequent layers to get the importance estimate for each node in the network.

It is important to note that in this work (relative) importance is more similar to effect size or odds

ratio than to statistical significance. The weights represent the direction and effect a gene or

pathway has on the outcome of the network.

Implementation

Technically, the computational performance of the implemented Keras/Tensorfow[39,40] layer

should be on par or an improvement over similar layers. It is implemented using sparse matrix

multiplication, making it faster than the slice-wise locallyconnected1D layer and more memory

efficient than dense matrix multiplication. The layer is friendly to use, with only one extra input

compared to a normal dense layer. This extra input, the sparse connectivity matrix, is made with

prior knowledge and describes how neurons are connected between layers.

The networks behave similar to normal fully connected artificial neural networks but is pruned

by removing irrelevant connection ($Out = Activation(\sum_{i=0}^{n} x_i w_i + b)$) With w as a sparse

matrix with learnable weights, initialized with a sparse connectivity matrix defining connections.

The networks are optimized using the ADAM or Adadelta optimizers, using weighted binary

cross entropy with weights depending on the imbalance of the classes, and are all trained on a

single GPU. For regression tasks, mean squared error is used as a loss function in combination

with ReLu activations (Supplementary Materials 7). The GenNet framework is available as

command line tool and includes functionalities to convert data, to create, train and evaluate

neural networks and to plot the results.

Baseline

As a baseline method, LASSO logistic regression was implemented in Tensorflow by using a

dense layer of a single neuron with a sigmoid activation function and L1 regularization on

weights. Polygenic Risk Scores (PRS) were not used since we used only variants from the

exome.

Upper bound of classification accuracy for predicting phenotypes

In contrast to the application of deep learning for image analysis, where the performance is not

limited, in application for genetic analysis we are limited by the information in DNA relevant for

trait or disease, i.e., by the heritability. Therefore, we cannot expect the performance of the

neural network above certain value.

Population characteristics can be used to calculate the upper bound of performance for a

classifier for any trait. This can be done by creating a confusion matrix. The accuracy between

true and false positives for a perfect classifier, based solely on genetic inputs, is given by the

concordance rate between monozygotic twins. It is impossible to predict better based solely on

genetic code than the rate a trait occurs in people with virtually the same genetic code. The

chance of misclassifying a control should be better than the prevalence, which is often close to

zero for most diseases. Creating a confusion matrix can give insights in the upper bound for

accuracy, sensitivity and specificity in the dataset. An example for schizophrenia in our dataset

can be found in Supplementary Materials 7.

Code availability

GenNet is an open-source framework usable from command line. GenNet and its tutorials,

including how to build new layers and networks from prior knowledge, can be found on:

https://github.com/arnovanhilten/GenNet/

Data availability

Code to run and generate data for the simulations are publicly available on GitHub. The genetic

and phenotypic UK Biobank data are available upon application to the UK Biobank

(https://www.ukbiobank.ac.uk/). Access to the Sweden-Schizophrenia Exome Sequencing study

can be requested on DBGaP (https://www.ncbi.nlm.nih.gov/gap/) (dbGaP phs000473.v2.p2).

References

1. Yengo, L. *et al.* Meta-analysis of genome-wide association studies for height and body

mass index in ~700,000 individuals of European ancestry. *bioRxiv* (2018).

doi:10.1101/274654

2. de Leeuw, C. A., Mooij, J. M., Heskes, T. & Posthuma, D. MAGMA: generalized gene-

set analysis of GWAS data. *PLoS Comput Biol* **11**, e1004219 (2015).

3. Holmans, P. *et al.* Gene ontology analysis of GWA study data sets provides insights into

the biology of bipolar disorder. *Am. J. Hum. Genet.* **85**, 13–24 (2009).

4. Lee, P. H., O'Dushlaine, C., Thomas, B. & Purcell, S. M. INRICH: interval-based

enrichment analysis for genome-wide association studies. *Bioinformatics* **28**, 1797–1799 (2012).

5. Pruitt, K. D., Tatusova, T. & Maglott, D. R. NCBI reference sequences (RefSeq): a curated non-redundant sequence database of genomes, transcripts and proteins. *Nucleic Acids Res.* **35**, D61–D65 (2007).

6. Kanehisa, M. & Goto, S. KEGG: kyoto encyclopedia of genes and genomes. *Nucleic Acids Res.* **28**, 27–30 (2000).

7. Croft, D. *et al.* The Reactome pathway knowledgebase. *Nucleic Acids Res.* **42**, D472–D477 (2014).

8. Lonsdale, J. *et al.* The genotype-tissue expression (GTEx) project. *Nat. Genet.* **45**, 580 (2013).

9. Gallagher, M. D. & Chen-Plotkin, A. S. The post-GWAS era: from association to function. *Am. J. Hum. Genet.* **102**, 717–730 (2018).

10. Litjens, G. *et al.* A survey on deep learning in medical image analysis. *Med. Image Anal.* **42**, 60–88 (2017).

11. Young, T., Hazarika, D., Poria, S. & Cambria, E. Recent trends in deep learning based natural language processing. *ieee Comput. Intell. Mag.* **13**, 55–75 (2018).

12. Edwards, L. & Veale, M. Slave to the algorithm: Why a right to an explanation is probably not the remedy you are looking for. *Duke L. Tech. Rev.* **16**, 18 (2017).

13. Došilović, F. K., Brčić, M. & Hlupić, N. Explainable artificial intelligence: A survey. in *2018 41st International convention on information and communication technology, electronics and microelectronics (MIPRO)* 210–215 (IEEE, 2018).

14. Bycroft, C. *et al.* The UK Biobank resource with deep phenotyping and genomic data.

Nature **562**, 203–209 (2018).

15.   Ikram, M. A. *et al.* Objectives, design and main findings until 2020 from the Rotterdam

Study. *Eur. J. Epidemiol.* 1–35 (2020).

16.   Purcell, S. M. *et al.* A polygenic burden of rare disruptive mutations in schizophrenia.

Nature **506**, 185–190 (2014).

17.   Ripke, S. *et al.* Biological insights from 108 schizophrenia-associated genetic loci. *Nature*

511, 421–427 (2014).

18.   Stahl, E. A. *et al.* Genome-wide association study identifies 30 loci associated with

bipolar disorder. *Nat. Genet.* **51**, 793–803 (2019).

19.   Visser, M., Kayser, M. & Palstra, R.-J. HERC2 rs12913832 modulates human

pigmentation by attenuating chromatin-loop formation between a long-range enhancer and

the OCA2 promoter. *Genome Res.* **22**, 446–455 (2012).

20.   Han, J. *et al.* A genome-wide association study identifies novel alleles associated with hair

color and skin pigmentation. *PLoS Genet.* **4**, (2008).

21.   Hysi, P. G. *et al.* Genome-wide association meta-analysis of individuals of European

ancestry identifies new loci explaining a substantial fraction of hair color variation and

heritability. *Nat. Genet.* **50**, 652–656 (2018).

22.   Liu, F. *et al.* Eye color and the prediction of complex phenotypes from genotypes. *Curr.*

Biol. **19**, R192–R193 (2009).

23.   Finucane, H. K. *et al.* Heritability enrichment of specifically expressed genes identifies

disease-relevant tissues and cell types. *Nat. Genet.* **50**, 621–629 (2018).

24.   Candille, S. I. *et al.* Genome-wide association studies of quantitatively measured skin,

hair, and eye pigmentation in four European populations. *PLoS One* **7**, (2012).

25.   Bradshaw, N. J. & Porteous, D. J. DISC1-binding proteins in neural development,

449   signalling and schizophrenia. *Neuropharmacology* **62**, 1230–1241 (2012).

450   26.   Fatemi, S. H. & Folsom, T. D. The neurodevelopmental hypothesis of Schizophrenia,

451   revisited. *Schizophr. Bull.* **35**, 528–548 (2009).

452   27.   Davis, C. A. *et al.* The Encyclopedia of DNA elements (ENCODE): Data portal update.

453   *Nucleic Acids Res.* **46**, D794–D801 (2018).

454   28.   Li, W. *et al.* Privacy-Preserving Federated Brain Tumour Segmentation. *arXiv Prepr.*

455   *arXiv1910.00962* 133–141 (2019). doi:10.1007/978-3-030-32692-0_16

456   29.   Roshchupkin, G. V *et al.* HASE: Framework for efficient high-dimensional association

457   analyses. *Sci. Rep.* **6**, 36076 (2016).

458   30.   Van Hout, C. V *et al.* Whole exome sequencing and characterization of coding variation

459   in 49,960 individuals in the UK Biobank. *BioRxiv* 572347 (2019).

460   31.   Kayser, M. *et al.* Three genome-wide association studies and a linkage analysis identify

461   HERC2 as a human iris color gene. *Am. J. Hum. Genet.* **82**, 411–423 (2008).

462   32.   Wang, K., Li, M. & Hakonarson, H. ANNOVAR: functional annotation of genetic

463   variants from high-throughput sequencing data. *Nucleic Acids Res.* **38**, e164–e164 (2010).

464   33.   Subhash, S. & Kanduri, C. GeneSCF: a real-time based functional enrichment tool with

465   support for multiple organisms. *BMC Bioinformatics* **17**, 365 (2016).

466   34.   Watanabe, K., Mirkov, M. U., de Leeuw, C. A., van den Heuvel, M. P. & Posthuma, D.

467   Genetic mapping of cell type specificity for complex traits. *Nat. Commun.* **10**, 1–13

468   (2019).

469   35.   Michael, K. Y. *et al.* Visible machine learning for biomedicine. *Cell* **173**, 1562–1565

470   (2018).

471   36.   Ma, J. *et al.* Using deep learning to model the hierarchical structure and function of a cell.

472   *Nat. Methods* **15**, 290–298 (2018).

473   37.   Gazestani, V. H. & Lewis, N. E. From Genotype to Phenotype: Augmenting Deep

474   Learning with Networks and Systems Biology. *Curr. Opin. Syst. Biol.* **15**, 68–73 (2019).

475   38.   Wang, D. *et al.* Comprehensive functional genomic resource and integrative model for the

476   human brain. *Science (80-.).* **362**, (2018).

477   39.   Chollet, F. Keras. *GitHub repository* (2015).

478   40.   Abadi, M. *et al.* Tensorflow: A system for large-scale machine learning. in *12th*

479   *{USENIX} Symposium on Operating Systems Design and Implementation ({OSDI} 16)*

480   265–283 (2016).

Acknowledgements

This work was funded by the Dutch Technology Foundation (STW) through the 2005 Simon

Steven Meester grant 2015 to W.J. Niessen. This research has been conducted using the UK

Biobank Resource under Application Number 23509. This work was carried out on the Dutch

national e-infrastructure with the support of SURF Cooperative (application number 17610). The

Rotterdam study is supported by the Netherlands Organization for Scientific Research (NWO,

91203014, 175.010.2005.011, 91103012).

Author contributions

A.H and G.R conceived and designed the method. A.H performed experiments and implemented

the method. G.R and W.N supervised the work. M.A.I, C.K, H.A, M.K and S.A.K. provided or

gave access to data. A.H, G.R, W.N, M.K., M.A.I., S.A.K, wrote, revised and approved the

manuscript.

Competing interests

W. N. is co-founder and shareholder of Quantib BV. Other authors declare no competing

interests.

Additional Information

Correspondence and requests should be addressed to A.H or G.R.