GenNet framework: interpretable neural networks for phenotype prediction

Arno van Hilten[1], Steven A. Kushner[2], Manfred Kayser[3], M. Arfan Ikram[4], Hieab H.H.

Adams[1,5], Caroline C.W. Klaver[4,6], Wiro J. Niessen*[1,7] and Gennady V. Roshchupkin*[1,4]

[1] Department of Radiology and Nuclear Medicine, Erasmus MC, Medical Center, Rotterdam, the
Netherlands.
[2] Department of Psychiatry, Erasmus MC, Medical Center, Rotterdam, the Netherlands.
[3] Department of Genetic Identification, Erasmus MC, Medical Center, Rotterdam, the
Netherlands.
[4] Department of Epidemiology, Erasmus MC, Medical Center, Rotterdam, the Netherlands.
[5] Department of Clinical Genetics, Erasmus MC, Medical Center, Rotterdam, the Netherlands.
[6] Department of Ophthalmology, Erasmus MC, Medical Center, Rotterdam, the Netherlands.
[7] Faculty of Applied Sciences, TU Delft, Delft, the Netherlands.

*Jointly supervised this project

**Neural networks have been seldomly leveraged in population genomics due to the
computational burden and challenge of interpretability. Here, we propose GenNet, a novel
open-source deep learning framework for predicting phenotype from genotype. In this
framework, public prior biological knowledge is used to construct interpretable and
memory-efficient neural network architectures. These architectures obtain good predictive
performance for multiple traits and complex diseases, opening the door for neural
networks in population genomics.**

Introduction

Genome-wide association studies (GWAS) have identified numerous genomic loci associated

with complex (polygenic) human traits and diseases. Recent GWAS studies with increasingly

larger sample sizes are leading to more significant associations between genotypes and

phenotypes at more and more independent loci. To illustrate, the latest GWAS for body height based on 700,000 individuals identified more than 3000 near-independent significantly associated single nucleotide polymorphisms (SNPs)[1]. This information, used in combination with annotated biological databases such as: NCBI RefSeq, KEGG, Reactome and GTEx has proven to be highly valuable for understanding the underlying biological mechanisms of complex diseases[2-6]. In this paper, we propose a new framework, GenNet, that integrates these biological data sources for discovery and interpretability in an end-to-end deep learning framework for predicting phenotypes.

Deep learning is the state of the art in many domains such as medical image analysis and natural language processing because of its flexibility and modeling capabilities[7,8]. In many cases, deep learning yields better performance compared to traditional approaches, since it can model highly non-linear relations and scales very well with data size. However, this often comes at the cost of interpretability, since there is a trade-off between complexity and interpretability[9,10]. Additionally, when it comes to genotype data, the number of learnable parameters increases dramatically because of the large input size, making it infeasible to use classical neural networks in this domain. To overcome previous limitations, we propose a new framework, GenNet, in which different types of biological information are used to define biologically plausible neural network architectures, avoiding this trade-off and creating interpretable neural networks for

48   predicting complex phenotypes.

Figure 1. Overview of the GenNet Framework. Neural networks are made by combining layers

made of different sources of prior biological knowledge (i.e. a gene layer from gene annotations,

a pathway layer from KEGG pathway annotations). These sources define the connections and

therefore the architecture, creating interpretable networks in the process.

Methods

The main concept of the GenNet framework is summarized graphically in Figure 1. In this

framework, prior knowledge is used to create groups of connected nodes to reduce the number of

learnable parameters in comparison to a fully connected neural network. For example, in the first

layer, where biological knowledge in the form of gene annotations, is used to group millions of

single nucleotide polymorphisms (SNPs) and to connect those SNPs to their corresponding

genes. The resulting layer retains only meaningful connections, significantly reducing the total

number of parameters compared to a classical layer. As a result, these memory-efficient

networks are able to handle the millions of inputs needed for genotype-to-phenotype prediction.

The biological knowledge is thus used to define only meaningful connections, shaping the

architecture of the neural network. Interpretability is inherent to the neural network's

architecture. For example, a network that connects SNPs-to-genes and genes-to-output. The

learned weights of the connections between layers represent the effect of the SNP on the gene or

the effect of the gene on the output. In the network, all neurons represent thus biological entities

and weights model the effects between these entities, together forming a biologically

interpretable neural network. Each connection in the network is thus based on a biological

annotation and the learned weight for this connection represents the importance of this

annotation for the predicted outcome.

Many types of layers can be created using this principle. These layers can be used like building

blocks to form new network architectures. Apart from gene annotations, our framework provides

layers built from exon annotations, pathway annotations, chromosome annotations and cell and

tissue type expressions.

*Figure 2. **A)** Non-linear simulation showing the basic principle of the network, thickness of the*

connections represents the learned weight (causal, contributing connections in red, control

connections in grey). This proof of concept can be run online see https://tinyurl.com/y8hh8rul

*(or see Supplementary 1.1). **B)** A secondary set of simulations show the performance of GenNet,*

expressed in the area under the curve, for increasing levels of heritability and training set size

*(**C**). In black the theoretical maximum of the AUC versus heritability[11]. **D)** Manhattan plot of the*

importance of the genes according to the network for distinguishing between schizophrenia cases

*and controls. **E)** This Manhattan plot is a cross section between the gene layer and the outcome*

of the trained network.

Results

In order to evaluate the network's performance under a variety of conditions, synthetic data was

created with different levels of heritability, number of training samples and polygenicity (see

Supplementary Materials 1 for results and detailed description). Figure 2A shows the proof of

concept demo that can be run online. Figure 2B and 2C show the main trends in the simulations.

As would be expected, the network performs best for traits with high heritability, high number of

training samples and low polygenicity, and the performance decreases with decreasing

heritability, number of training samples or increase of polygenicity.

Motivated by the proof of concept and the outcomes of the simulations, the framework was

applied to real data from multiple sources, including population-based data from the UK Biobank

study and the Rotterdam study, and a case-controls study on schizophrenia from Sweden[12-14].

The analyzed phenotypes vary from traits where high predictive performance can be obtained

from a dozen of variants (eye color) to disorders where thousands of variants only explain a

small portion of the variance (schizophrenia and bipolar disorder)[15,16]. The genotype data

employed included imputed microarray-based GWAS data (eye color in Rotterdam study) as

well as whole exome sequencing (WES) data (hair color, male baldness pattern and bipolar

disorder in UK Biobank; schizophrenia in the Swedish study). An overview of the experiments

and results can be found in table 1.

Trait	Dataset (type)	Number of input variants	Subjects & phenotype		Heritability	AUC LASSO	AUC GenNet	GenNet: top three most important genes
			Class I	Class II				
Eye color	Rotterdam (genotype array)	113,241 (exonic) inputs of 16,628 genes	4041 Blue	2250 Other	0.80-0.98	0.68	0.75	*HERC2, OCA2, LAMC1*
Hair color	UK Biobank (exome)	6,986,636 input variants of 15,827 genes	1648 Blond	1656 Red	0.70-0.97	0.78	0.83	*MC1R*, OCA2, TC2N*
			1672 Dark brown	1664 Red	0.70-0.97	0.79	0.88	*MC1R*, OCA2, ZCCHC4*
			4352 Blond	4343 Dark Brown	0.70-0.97	0.64	0.75	*OCA2, TC2N, EXOC2*
Male baldness	UK Biobank (exome)	6,986,636 Input variants of 15,827 genes.	3454 No balding	3454 Severe balding	0.60-0.70	0.57	0.57	*NGEF, NKRD18B, SYNJ2*
Bipolar	UK Biobank (exome)	6,986,636 Input variants of 15,827 genes	343 Cases	347 Controls	0.73-0.93	0.59	0.60	*LINC00266-1, CSMD1, TCERG1L*
Schizophrenia	Sweden (exome)	1,288,701 input variants of 21,390 genes	4969 Cases	6245 Controls	0.80-0.85	0.65	0.74	*ZNF773, PCNT, DYSF*

Table 1. Summary of the experiments and results in this study for the simplest network in our

framework that contains the input SNPs, the gene layer and the output layer. Manhattan plots for

*gene importance can be found in Supplementary Materials 2,3 & 4. *MC1R was not present in*

gene annotations but was identified by linkage disequilibrium.

In general, the framework's predictive performance is in line with trends seen in simulations and

literature. Phenotypes with more training samples and phenotypes that require less variants to

obtain good predictive performance, such as eye and hair color, performed best. Nonetheless, a

good predictive performance, area under curve (AUC) of 0.74 in the held-out test set, was

obtained for schizophrenia, a highly polygenic disorder. All models outperform or match the

baseline LASSO logistic regression model (see Methods).

Inspecting the networks, we found that the *OCA2* gene was highlighted as the most important

gene to distinguish between brown and blond hair color. *OCA2* is involved in the transport of

tyrosine, a precursor of melanin[17]. The signal is probably amplified by the nearby *HERC2*,

previous identified via functional genetic studies as harboring a strong, long-distance enhancer

regulating *OCA2* gene expression to cause pigmentation variation[17]. *OCA2* and *HERC* are the

two most predictive genes according to the network for predicting blue (iris) eye color. Both

have been earlier identified by hair and eye color GWASes[18-20].

In the experiments with schizophrenia as outcome, the network was able to classify cases and

controls with a maximum accuracy of 68.4% (mean of 66.3 ± 1.37 over 10 runs). We estimate

the theoretical upper limit for classification, including all genetic aspects, to be an accuracy of

72% (supplementary methods 5). The model obtains an area under the receiver operating curve

of 0.74 (ranging 0.72-0.74) in the held-out test set, thereby considerably outperforming the

LASSO logistic regression baseline (AUC of 0.64). The GenNet AUC compares favorably to

polygenic risk scoring for schizophrenia, which have AUC values on the order of 0.70 (ranging

0.49-0.85)[15] . This is noteworthy since in this study the schizophrenia predictions are based on

whole exome sequencing data as opposed to GWAS arrays spanning the whole genome.

Discussion

Here, we present a novel framework to train interpretable neural networks for phenotype

prediction from genotype. The proposed neural networks have connections defined by prior

biological knowledge only, reducing the number of connections and therefore the number of

trainable parameters. Consequently, the networks are interpretable and overcome computational

limitations. All experiments were run on a single GPU (Nvidia GeForce GTX 1080) and

converged within 48 hours. Simulations show the network's performance when varying the

degree of heritability, polygenicity and sample size. The suggested sample size, heritability and

polygenicity are conservative. When applying the framework to UK Biobank, Rotterdam study

and Swedish Schizophrenia WES data, good predictive performance was achieved with smaller

sample sizes and higher number of inputs than suggested by the simulations. In these

experiments, widely different phenotypes are predicted with generally good performance based

exclusively on WES SNPs.

For traits with a known etiology, well-replicated genes such as *HERC2* and *OCA2* for eye color

and *OCA2* and *TCN2* for hair color were found to be important by the network[18-21]. For

schizophrenia, a disorder with an unclear etiology, the network identified previously

unimplicated genes, including *ZNF773* and *PCNT*. However, it is important to note that the

importance captured by the network bears more similarity to effect size rather than statistical

significance.

In general, these experiments indicate that neural networks in our framework can overcome

computational limitations while still obtaining good predictive performance, opening the door for

genetic risk prediction by neural networks. Aside from computational benefits, the architecture

offers interpretability, alleviating one the most important shortcomings of neural networks. In

this study, WES data and exonic variants from microarrays have been used, however the

principles in the GenNet framework can be leveraged to handle diverse types of input, including

genotype, gene expression and methylation data or combinations thereof)

In conclusion, we developed a freely-available framework, which can be used to build

interpretable neural networks for genotype data by incorporating prior biological knowledge. We

have demonstrated the effectiveness of this novel framework across multiple datasets and for

multiple phenotypes. Given that each network node is interpretable, we anticipate this approach

to have wide applicability for uncovering novel insights into the genetic architecture of complex

traits and diseases.

GenNet is an open-source framework, providing code and tutorials

(https://github.com/arnovanhilten/GenNet/). This includes tutorials for applying the networks as

well as creating new layers and networks from prior knowledge.

Online Methods

Sweden Schizophrenia

Sweden-Schizophrenia Population-Based Case-Control Exome Sequencing study (dbGaP phs000473.v2.p2), is a case control study with 4969 cases and 6245 controls[14]. All individuals aged 18-65, have parents born in Sweden and provided written informed consent. Cases were at least 2 times hospitalized with schizophrenia discharge diagnosis and do not have a hospital register diagnosis consistent with a medical or other psychiatric disorder that mitigates the schizophrenia diagnosis. Cases do not have a relationship closer than 2nd degree relative with any other case. Controls do not have any relation to either case or control and all controls have never been hospitalized with a discharge diagnosis of schizophrenia.

The .bim, .bam and .bed files were converted using HASE[22] to .h5 format, a format that allows fast and parallel data reading. After conversion, the data is transposed and SNPs without any variance are removed (~1.2 million SNPs remain). The data is split in a training, validation and test set (ratio of 60/20/20), while preserving the ratio cases and controls. All SNPs with standard deviation greater than zero are used as input to the network after z-score normalization (based on the mean and standard deviation of the training set).

UK Biobank

We applied the framework to multiple phenotypes in the UK Biobank using the first release of the WES data, providing whole exome sequencing for 50,000 UK Biobank participants[23]. Phenotypes are self-reported (touchscreen questions UK Biobank Assessment Centre). Similar to the Sweden cohort all variants without variance were removed, data was converted to hierarchical data format (.h5), and transposed. For every phenotype an equal number of cases

and controls were sampled. The resulting dataset is split in a train, validation and a test set (ratio

of 60/20/20). Related cases, and cases with related controls, (kinship > 0.0625) are all in the

training set. This is done under the assumption that related cases and controls could ease training,

the shared genetic information could steer the network towards the discriminatory features. The

validation and test sets contain only unrelated cases and controls within and between sets.

Unrelated controls are randomly sampled and added to gain an even distribution between cases

and controls in all sets. Misaligned SNPs and sex chromosomes were masked in the first layer

and therefore not included in the study.

Rotterdam Study

The Rotterdam study is a prospective cohort study, in the first cohort 6291 participants were

genotyped using the Illumina 550K and 550K duo arrays. Samples with low call rate (<97.5%),

with excess autosomal heterozygosity (>0.336) or with sex-mismatch were excluded, as were

outliers identified by the identity-by-state clustering analysis (outliers were defined as being >3

standard deviation (SD) from population mean or having identity-by-state probabilities >97%).

For imputation the Markov Chain Haplotyping (MACH) package version 1.0 software (Imputed

to plus strand of NCBI build 37, 1000 Genomes phase I version 3) and minimac version 2012.8.6

were used (call rate >98%, MAF >0.001 and Hardy–Weinberg equilibrium P-value > 10^{-6}).

From here on processing steps are identical as described for Sweden Schizophrenia obtaining

113,241 exonic variants.

Eyes were examined by an ophthalmological medical researcher and eye (iris) color was

categorized into three categories; blue, intermediate and brown using standard images and based

on the predominant color and pigmentation [24].

Prior Knowledge

All SNPs were annotated using Annovar[25]. A sparse connectivity matrix is generated connecting

the SNPs to their corresponding genes. The intron-exon annotations of Annovar were used as a

proxy to create the connectivity matrices between SNPs, exons and genes. The pathway masks

were built by using GeneSCF[26] and the KEGG database[3]. GTEx tissue-expression masks were

made using the fully processed, filtered and normalized gene expression matrices for each tissue

directly obtainable from the GTEx website[5] and from derived t-score statistics[27]. Single cell

expression masks are available made using data from FUMA[28]. Expression masks are continuous

and various thresholds can be used to create connectivity matrices, the threshold should be

chosen with care to ensure unique nodes and thus interpretability.

All available networks in the framework are trait independent but trait specific neural networks

can be created with more specific prior knowledge (e.g. brain cell expression to select genes in

the network for predicting neurological disorders). The GenNet framework is quite flexible, any

information that groups data uniquely can be used to create layers.

Neural Network Architecture

In the GenNet framework, layers are available built from biological knowledge such as; exon

annotations, gene annotations, pathway annotations, cell expression and tissue expression.

Information from these resources are used to define only meaningful connections, shaping an

interpretable and lightweight neural network, allowing evaluation of millions of input variants

together. These networks bear similarities to the first generation of neural networks and recently

interest for these networks has rekindled for biological applications[29-32], In neural networks the

dimensionality of the data is reduced, resulting in a loss of information every layer. Networks

with the GenNet architecture aim to reduce this loss by using prior biological knowledge to

create layers in the network, compressing the network in a biologically sensible way. These

sources are used to define connections between nodes/neurons in the network (see

implementation). The network itself will learn how important the connections are for the

prediction of the outcome. Thus, giving additional information for the sources used to define the

network. For example, in most networks, gene annotations are used to group SNPs. During

training the network will figure out which gene is important and which SNPs in the gene are

important for predicting the outcome.

Interpretation

Interpretation of the network is straightforward due to the simplicity of the concept, the higher

the weight is the more important it is for the network. A network built by gene annotations can

be seen as ~20 000 (number of genes) parallel regressions followed by a single logistic

regression. The learned weights in these regressions are similar to the coefficients in logistic

regression. Especially the last node, a single neuron with a sigmoid activation, $P =$

$Sigmoid(\sum_{i=0}^{n} x_i w_i + B)$ is similar to logistic regression $Y = Sigmoid(\sum_{i=0}^{n} x_i \beta_i + B)$.

To compare coefficients (β) the inputs are normalized in logistic regression. In the neural

network this is achieved by batch normalization (without center and scaling), normalizing the

weights (w) after every activation. Since batch normalization is a batch-wise approximation the

learned weights can be multiplied with the standard deviation of the activations for a more

accurate estimate, resulting in the importance measure. We noticed it might be beneficial to add

an L1 penalty on the weights in the last dense layer, as used in LASSO logistic regression. This

regularizer constraints the search space which might lead to a better generalization and reduced

noise in the signal for easier interpretation.

Implementation

Technically, the computational performance of the implemented Keras/Tensorfow[33,34] layer

should be on par or an improvement over similar layers. It is implemented using sparse matrix

multiplication, making it faster than the slice-wise locallyconnected1D layer and more memory

efficient than dense matrix multiplication. The layer is friendly to use, with only one extra input

compared to a normal dense layer. This extra input, the sparse connectivity matrix, is made with

prior knowledge and describes how neurons are connected between layers.

The networks behave similar to normal fully connected artificial neural networks but is pruned

by removing irrelevant connection ($Out \ = \ Activation(\sum_{i=0}^{n} x_i w_i \ + \ b)$) With *w* as a sparse

matrix with learnable weights, initialized with a sparse connectivity matrix defining connections.

The networks are optimized using the ADAM or Adadelta optimizers [35,36], using weighted binary

cross entropy with weights depending on the imbalance of the classes, and are all trained on a

single GPU.

Baseline

As a baseline method, LASSO logistic regression was implemented in Tensorflow by using a

dense layer of a single neuron with a sigmoid activation function and L1 regularization on

weights.

Upper Bound

Population characteristics can be used to calculate the upper bound of performance for a

classifier for any trait. This can be done by creating a confusion matrix. The accuracy between

true and false positives for a perfect classifier, based solely on genetic inputs, is given by the

concordance rate between monozygotic twins. It is impossible to predict better based solely on

genetic code than the rate a trait occurs in people with virtually the same genetic code. The

chance of misclassifying a control should be better than the prevalence, which is often close to

zero for most diseases. Creating a confusion matrix can give insights in the upper bound for

accuracy, sensitivity and specificity in the dataset. An example for schizophrenia in our dataset

can be found in Supplementary 5.

Code Availability

The code, tutorials and trained networks can be found on github.com/arnovanhilten/GenNet/ in

the form of Jupyter notebooks. The code has been made with an emphasis on easy to use, with

comments and tutorials.

Data Availability

Code to run and generate data for the simulations are publicly available on GitHub. The genetic

and phenotypic UK Biobank data are available upon application to the UK Biobank

(https://www.ukbiobank.ac.uk/). Access to the Sweden-Schizophrenia Exome Sequencing study

can be requested on DBGaP (https://www.ncbi.nlm.nih.gov/gap/) (dbGaP phs000473.v2.p2).

References

1.   Yengo L, Sidorenko J, Kemper KE, et al. Meta-analysis of genome-wide association studies for height and
body mass index in~ 700000 individuals of European ancestry. *Human Molecular Genetics.*
2018;27(20):3641-3649.
2.   Pruitt KD, Tatusova T, Maglott DR. NCBI reference sequences (RefSeq): a curated non-redundant
sequence database of genomes, transcripts and proteins. *Nucleic Acids Research.* 2007;35(suppl_1):D61-
D65.
3.   Kanehisa M, Goto S. KEGG: kyoto encyclopedia of genes and genomes. *Nucleic Acids Research.*
2000;28(1):27-30.
4.   Croft D, Mundo AF, Haw R, et al. The Reactome pathway knowledgebase. *Nucleic Acids Research.*
2014;42(D1):D472-D477.
5.   Lonsdale J, Thomas J, Salvatore M, et al. The genotype-tissue expression (GTEx) project. *Nature Genetics.*
2013;45(6):580.
6.   Gallagher MD, Chen-Plotkin AS. The post-GWAS era: from association to function. *The American Journal of*
Human Genetics. 2018;102(5):717-730.
7.   Litjens G, Kooi T, Bejnordi BE, et al. A survey on deep learning in medical image analysis. *Medical Image*
Analysis. 2017;42:60-88.
8.   Young T, Hazarika D, Poria S, Cambria E. Recent trends in deep learning based natural language
processing. *ieee Computational Intelligence Magazine.* 2018;13(3):55-75.
9.   Edwards L, Veale M. Slave to the algorithm: Why a right to an explanation is probably not the remedy you
are looking for. *Duke L & Tech Rev.* 2017;16:18.
10.   Došilović FK, Brčić M, Hlupić N. Explainable artificial intelligence: A survey. Paper presented at: 2018 41st
International convention on information and communication technology, electronics and microelectronics
(MIPRO)2018.
11.   Wray NR, Yang J, Goddard ME, Visscher PM. The genetic interpretation of area under the ROC curve in
genomic profiling. *PLoS genetics.* 2010;6(2).
12.   Bycroft C, Freeman C, Petkova D, et al. The UK Biobank resource with deep phenotyping and genomic
data. *Nature.* 2018;562(7726):203-209.
13.   Ikram MA, Brusselle G, Ghanbari M, et al. Objectives, design and main findings until 2020 from the
Rotterdam Study. *European Journal of Epidemiology.* 2020:1-35.
14.   Genovese G, Fromer M, Stahl EA, et al. Increased burden of ultra-rare protein-altering variants among
4,877 individuals with schizophrenia. *Nature neuroscience.* 2016;19(11):1433.
15.   Ripke S, Neale BM, Corvin A, et al. Biological insights from 108 schizophrenia-associated genetic loci.
Nature. 2014;511(7510):421-427.
16.   Stahl EA, Breen G, Forstner AJ, et al. Genome-wide association study identifies 30 loci associated with
bipolar disorder. *Nature Genetics.* 2019;51(5):793-803.
17.   Visser M, Kayser M, Palstra R-J. HERC2 rs12913832 modulates human pigmentation by attenuating
chromatin-loop formation between a long-range enhancer and the OCA2 promoter. *Genome Research.*
2012;22(3):446-455.
18.   Han J, Kraft P, Nan H, et al. A genome-wide association study identifies novel alleles associated with hair
color and skin pigmentation. *PLoS genetics.* 2008;4(5).
19.   Hysi PG, Valdes AM, Liu F, et al. Genome-wide association meta-analysis of individuals of European
ancestry identifies new loci explaining a substantial fraction of hair color variation and heritability. *Nature*
Genetics. 2018;50(5):652-656.
20.   Candille SI, Absher DM, Beleza S, et al. Genome-wide association studies of quantitatively measured skin,
hair, and eye pigmentation in four European populations. *PLoS One.* 2012;7(10).
21.   Liu F, van Duijn K, Vingerling JR, et al. Eye color and the prediction of complex phenotypes from genotypes.
Current Biology. 2009;19(5):R192-R193.
22.   Roshchupkin GV, Adams H, Vernooij MW, et al. HASE: Framework for efficient high-dimensional
association analyses. *Scientific Reports.* 2016;6:36076.
23.   Van Hout CV, Tachmazidou I, Backman JD, et al. Whole exome sequencing and characterization of coding
variation in 49,960 individuals in the UK Biobank. *BioRxiv.* 2019:572347.
24.   Kayser M, Liu F, Janssens ACJ, et al. Three genome-wide association studies and a linkage analysis
identify HERC2 as a human iris color gene. *The American Journal of Human Genetics.* 2008;82(2):411-423.
25.   Wang K, Li M, Hakonarson H. ANNOVAR: functional annotation of genetic variants from high-throughput
sequencing data. *Nucleic Acids Research.* 2010;38(16):e164-e164.
26.   Subhash S, Kanduri C. GeneSCF: a real-time based functional enrichment tool with support for multiple
organisms. *BMC Bioinformatics.* 2016;17(1):365.
27.   Finucane HK, Reshef YA, Anttila V, et al. Heritability enrichment of specifically expressed genes identifies
disease-relevant tissues and cell types. *Nature genetics.* 2018;50(4):621-629.
28.   Watanabe K, Mirkov MU, de Leeuw CA, van den Heuvel MP, Posthuma D. Genetic mapping of cell type
specificity for complex traits. *Nature communications.* 2019;10(1):1-13.

29. Gazestani VH, Lewis NE. From genotype to phenotype: Augmenting deep learning with networks and
systems biology. *Current Opinion in Systems Biology.* 2019.
30. Ma J, Yu MK, Fong S, et al. Using deep learning to model the hierarchical structure and function of a cell.
Nature Methods. 2018;15(4):290.
31. Michael KY, Ma J, Fisher J, Kreisberg JF, Raphael BJ, Ideker T. Visible machine learning for biomedicine.
Cell. 2018;173(7):1562-1565.
32. Wang D, Liu S, Warrell J, et al. Comprehensive functional genomic resource and integrative model for the
human brain. *Science.* 2018;362(6420):eaat8464.
33. *Keras* [computer program]. 2015.
34. Abadi M, Barham P, Chen J, et al. Tensorflow: A system for large-scale machine learning. Paper presented
at: 12th {USENIX} Symposium on Operating Systems Design and Implementation ({OSDI} 16)2016.
35. Zeiler MD. Adadelta: an adaptive learning rate method. *arXiv preprint arXiv:12125701.* 2012.
36. Kingma DP, Ba J. Adam: A method for stochastic optimization. *arXiv preprint arXiv:14126980.* 2014.
387

Acknowledgements

This work was funded by the Dutch Technology Foundation (STW) through the 2005 Simon

Steven Meester grant 2015 to W.J. Niessen. This research has been conducted using the UK

Biobank Resource under Application Number 23509. This work was carried out on the Dutch

national e-infrastructure with the support of SURF Cooperative (application number 17610). The

Rotterdam study is supported by the Netherlands Organization for Scientific Research (NWO,

91203014, 175.010.2005.011, 91103012).

Author contributions

A.H and G.R conceived and designed the method. A.H performed experiments and implemented

the method. G.R and W.N supervised the work. M.A.I, C.K, H.A, M.K and S.K. provided or

gave access to data. A.H, G.R, W.N, M.K., M.A.I., S.K, wrote, re-vised and approved the

manuscript.

Competing interests

W. N. is co-founder and shareholder of Quantib BV. Other authors declare no competing

interests.

Additional Information

Supplementary is available for this paper at: https://www.

Correspondence and requests should be addressed to A.H or G.R.