Artificial Neural Networks Accurately Predict Language Processing in the Brain

Martin Schrimpf[1,2,3], Idan Blank[*,1,4], Greta Tuckute[*,1,5], Carina Kauf[*,1], Eghbal A. Hosseini[1],

Nancy Kanwisher[1,2,3], Joshua Tenenbaum[†,1,3], Evelina Fedorenko[†,1,2]

[1] Department of Brain and Cognitive Sciences, MIT, Cambridge, MA, USA
[2] McGovern Institute for Brain Research, MIT, Cambridge, MA, USA
[3] Center for Brains, Minds and Machines, MIT, Cambridge, MA, USA
[4] Psychology Department, UCLA, Los Angeles, CA, USA
[5] Media Lab, MIT, Cambridge, MA, USA

The ability to share ideas through language is our species' signature cognitive skill, but how this feat is achieved by the brain remains unknown. Inspired by the success of artificial neural networks (ANNs) in explaining neural responses in perceptual tasks (Kell et al., 2018; Khaligh-Razavi & Kriegeskorte, 2014; Schrimpf et al., 2018; Yamins et al., 2014; Zhuang et al., 2017), we here investigated whether state-of-the-art ANN language models (e.g. Devlin et al., 2018; Pennington et al., 2014; Radford et al., 2019) capture human brain activity elicited during language comprehension. We tested 43 language models spanning major current model classes on three neural datasets (including neuroimaging and intracranial recordings) and found that the most powerful generative transformer models (Radford et al., 2019) accurately predict neural responses, in some cases achieving near-perfect predictivity relative to the noise ceiling. In contrast, simpler word-based embedding models (e.g. Pennington et al., 2014) only poorly predict neural responses (<10% predictivity). Models' predictivities are consistent across neural datasets, and also correlate with their success on a next-word-prediction task (but not other language tasks) and ability to explain human comprehension difficulty in an independent behavioral dataset. Intriguingly, model architecture alone drives a large portion of brain predictivity, with each model's untrained score predictive of its trained score. These results support the hypothesis that a drive to predict future inputs may shape human language processing, and perhaps the way knowledge of language is learned and organized in the brain. In addition, the finding of strong correspondences between ANNs and human representations opens the door to using the growing suite of tools for neural network interpretation to test hypotheses about the human mind.

As you read these words, your brain is extracting—from simple marks on the page—a complex and structured representation of the meaning of this sentence. This comprehension process causally depends on a left-lateralized fronto-temporal brain network (Bates et al., 2003; Binder et al., 1997; Fedorenko & Thompson-Schill, 2014; Friederici, 2012; Gorno-Tempini et al., 2004; Hagoort, 2019; Price, 2010) (Fig. 1) that responds robustly and selectively to linguistic input (Fedorenko et al., 2011; Monti et al., 2012), whether auditory or visual (Deniz et al., 2019; Regev et al., 2013). Yet the precise computations underlying language processing in the brain remain unknown. Computational models of sentence processing have been used to quantitatively predict behavioral measures such as reading times and eye movements (Dotlačil, 2018; Futrell et al., 2020; Gibson, 1998; Gibson et al., 2013; Hale, 2001; Jurafsky, 1996; Lakretz et al., 2020; Levy, 2008a, 2008b; Lewis et al., 2006; McDonald & Macwhinney, 1998; Smith & Levy, 2013; Spivey-Knowlton, 1996; Steedman, 2000; van Schijndel et al., 2013), and models based on language input statistics and grammatical parsing have had important successes in interpreting and predicting human brain responses to words and sentences (Brennan et al., 2016; Brennan & Pylkkänen, 2017; Ding et al., 2015; Frank et al., 2015; Henderson et al., 2016; Huth et al., 2016; Lopopolo et al., 2017; Lyu et al., 2019; T. M. Mitchell et al., 2008; Nelson et al., 2017; Pallier et al., 2011; Pereira et al., 2018; Rabovsky et al., 2018; Shain et al., 2020; Wehbe et al., 2014; Willems et al., 2016). However, these models do not attempt to solve the full linguistic problem that the brain solves: to form a representation of sentence meaning capable of performing a broad range of real-world language tasks on diverse natural linguistic input. They also leave much of the human neural data unexplained. Recently though, a new cohort of deep artificial neural network models (ANNs) trained with very large language datasets have proven capable of the kind of generic, broad-linguistic-coverage functionality that

Figure 1: **Comparing Artificial Neural Network models of language processing to activity in the brain's language network.** We tested how well different models predict human measurements of neural activity during language comprehension. The candidate models ranged from simple embedding models to more complex recurrent and transformer networks. Stimuli ranged from sentences to passages to stories and were 1) fed into the models, and 2) presented to human participants (visually or auditorily). The resulting internal representations were then 1) captured from the models, and 2) recorded from humans with fMRI or ECoG. To compare model and human representations, we regressed model representations on the corresponding human measurements in response to 80% of the stimuli, and then compared model predictions on the held-out 20% of stimuli against the held-out human data with Pearson correlation (cross-validated 5-fold), yielding a similarity score for each model-data pair.

could be harnessed, in principle, to model the brain's language processing. Trained on generic word prediction tasks—predicting the next word given the previous words (Radford et al., 2019), or predicting missing words given their surrounding context (Devlin et al., 2018)—these ANNs form representations that approximate meaning well enough to answer questions and generate free-form text from prompts (Radford et al., 2019), translate between languages (Lample & Conneau, 2019), and exhibit impressive performance on many other benchmark natural language engineering tasks (Brown et al., 2020). Could these ANNs inform the neural computations that underlie the human ability to understand language? Initial reports (Gauthier & Ivanova, 2018; Gauthier & Levy, 2019; Hu et al., 2020; Jain & Huth, 2018; S. Wang et al., 2020) have tested few models and a single neural dataset each, and left open the critical question of why some models match human data better than others. Testing models broadly is crucial, as even small differences in model architecture or training can lead to large differences in brain predictivity (Kubilius et al., 2019; Schrimpf et al., 2018; Yamins et al., 2014). Further, different models embody qualitatively different hypotheses about the computations underlying language processing, and comprehensively comparing the models' match to human data provides a way to begin testing those hypotheses.

Here, we tested the relationship between 43 diverse state-of-the-art ANN language models (henceforth 'models') and three neural language comprehension datasets (two fMRI, one ECoG) to address four fundamental questions. First, we asked *which models* best capture human neural responses. Second, we tested whether the models that are most brain-like

in their representations perform best on a *next-word prediction task*, as might be expected given the critical role of
predictive processing in human perception and cognition (Clark, 2013; Keller & Mrsic-Flogel, 2018; Tenenbaum et al.,
2011), including language (Altmann & Kamide, 1999; Frank & Bod, 2011; Hale, 2001; Kuperberg & Jaeger, 2016; Levy,
2008b; Shain et al., 2020; Smith & Levy, 2013). Third, we asked whether the models with the highest neural predictivity
also best capture *behavioral signatures* of human language processing in a reading task. Finally, we explored the relative
contributions to brain predictivity of two different aspects of model design: network *architecture* and *training experience*,
to begin to test different hypotheses about the computations performed by the brain's language network and about how it
might have arisen through some combination of evolutionary and learning-based optimization.
81

Results

We evaluated a broad range of state-of-the-art ANN models on the match of their internal representations to three human
neural datasets. The models spanned all major classes of existing language models and included embedding models (e.g.,
GloVe (Pennington et al., 2014)), recurrent neural networks (e.g., LM1B (Jozefowicz et al., 2016)), and variants of attention-
based architectures—transformers (e.g., BERT (Devlin et al., 2018), XLM (Lample & Conneau, 2019), GPT (Radford et al.,
2019), and T5 (Raffel et al., 2019)) (Methods 5, Table S10). The neural datasets consisted of i) fMRI activations while
participants read short passages, presented one sentence at a time (across two experiments) that spanned diverse topics
(*Pereira2018* dataset (Pereira et al., 2018)); ii) ECoG recordings while participants read semantically and syntactically
diverse sentences, presented one word at a time (*Fedorenko2016* dataset (Fedorenko et al., 2016)); and iii) fMRI BOLD
signal time-series elicited while participants listened to few-minutes-long naturalistic stories (*Blank2014* dataset (I. Blank et
al., 2014)) (Methods 1-3). Thus, the datasets varied in the method (fMRI/ECoG), the nature and grain of linguistic units to
which responses were recorded (sentences/words/2s-long story fragments), and modality (reading/listening). We primarily
focused on *Pereira2018* because it includes multiple repetitions per stimulus (sentence) within each participant and
quantitatively exhibits the highest internal reliability (Fig. S1), and then generalized the findings to the other datasets.
Because our research questions concern language processing, we extracted neural responses from language-selective
voxels or electrodes that were functionally identified by an extensively validated independent "localizer" task that
contrasts reading sentences versus nonword sequences (Fedorenko et al., 2010). This localizer robustly identifies the
fronto-temporal language-selective network (Methods 1-3, Fig. 2b, S3).

To compare a given model to a given dataset, we presented the same stimuli to the model that were presented to humans
in neural recording experiments and 'recorded' the model's internal activations (Methods-5-6, Fig. 1). We then tested how
well the model recordings could predict the neural recordings for the same stimuli, using a method originally developed for
studying visual object recognition (Schrimpf et al., 2018; Yamins et al., 2014). Specifically, using a subset of the stimuli, we
fit a linear regression from the model activations to the corresponding human measurements, modeling the response of
each voxel (*Pereira2018*) / electrode (*Fedorenko2016*) / region (*Blank2014*) as a linear weighted sum of responses of
different units from the model. We then computed model predictions by applying the learned regression weights to model
activations for the held-out stimuli, and evaluated how well those predictions matched the corresponding held-out human
measurements by computing Pearson's correlation coefficient. We further normalized these correlations by the
extrapolated reliability of the particular dataset, which places an upper bound ("ceiling") on the correlation between the
neural measurements and any external predictions (Methods 7, Fig. S1). The final measure of a model's performance
('predictivity' or 'score') on a dataset is thus Pearson's correlation between model predictions and neural recordings
divided by the estimated ceiling and averaged across voxels/electrodes/regions and participants. We report the score for
the best-performing layer of each model (Methods 6, Fig. S10).

Figure 2: **Specific models accurately predict neural responses consistently across datasets. (a)** We compared 43 computational models of language processing in their ability to predict human brain data. The neural datasets include: fMRI voxel responses to visually presented sentences (*Pereira2018*), ECoG electrode responses to visually presented (word-by-word) sentences (*Fedorenko2016*), fMRI ROI responses to ~5min-long stories (*Blank2014*). For each model, we plot the normalized predictivity, i.e. the fraction of ceiling (gray line; Methods-7, Fig. S1) the model can predict. Ceiling levels are .32 (*Pereira2018*), .17 (*Fedorenko2016*), and .20 (*Blank2014*). Model classes are grouped by color (Methods-5, Table S10). Error bars (here and elsewhere) represent m.a.d. over subject scores. **(b)** Normalized predictivity of GloVe and GPT2-xl models in the language-responsive voxels in the left hemisphere of two representative participants from *Pereira2018* (also Fig. S3). **(c)** To test how well model scores generalize across datasets, we correlated: two experiments with different stimuli (and some participant overlap) in *Pereira2018* (very strong correlation), and *Pereira2018* model scores with the scores for each of *Fedorenko2016* and *Blank2014* (lower but still highly significant correlations). Scores overall thus tend to generalize across datasets, although differences between datasets exist which warrant the full suite of datasets.

Specific models accurately predict human brain activity. We found (Fig. 2a-b) that specific models predict *Pereira2018* and
Fedorenko2016 datasets with up to 100% predictivity (see Fig. S2 for generalization to another metric) relative to the noise
ceiling (Methods-7, Fig. S1). The *Blank2014* dataset is also reliably predicted, but with lower predictivity. Models vary
substantially in their ability to predict neural data. Generally, embedding models such as GloVe do not perform well on any
dataset. In contrast, recurrent networks such as skip-thoughts, as well as transformers such as BERT, predict large portions
of the data. The model that predicts the human data best across datasets is GPT2-xl, which predicts *Pereira2018* and
Fedorenko2016 at close to 100% and is among the highest-performing models on *Blank2014* with 32% predictivity. These
scores are higher in the language network than other parts of the brain (SI-4).
Model scores are consistent across experiments/datasets. To test the generality of the model representations, we examined the
consistency of model scores across datasets. Indeed, if a model does well on one dataset, it tends to also do well on other
datasets (Fig. 2c), ruling out the possibility that we are picking up on spurious, dataset-idiosyncratic predictivity, and
suggesting that the models' internal representations are general enough to capture brain responses to diverse linguistic
materials presented visually or auditorily, and across three independent sets of participants. Specifically, model scores
across the two experiments in *Pereira2018* (overlapping sets of participants) correlate at *r=*.94 (Pearson here and
elsewhere, *p<<.00001*), scores from *Pereira2018* and *Fedorenko2016* correlate at *r=*.50 (*p<.001*), and from *Pereira2018* and
Blank2014 at *r=*.63 (*p<.0001*).
130
Next-word-prediction task performance predicts neural scores. In vision, ANNs that perform better on the specific task of
visual classification also tend to better predict responses in the primate ventral stream (Schrimpf et al., 2018; Yamins et al.,
2014). Building on work that has established a core role for predictive processing in language (Hale, 2001; Levy, 2008a;
Smith & Levy, 2013) and recent findings that ANNs that perform well on a next-word prediction task (a normative task
known as 'language modeling') better capture human behavioral comprehension measures (Goodkind & Bicknell, 2018; van
Schijndel & Linzen, 2018), we examined the relationship between the models' ability to predict an upcoming word and their
brain predictivity. Words from the Wikitext-2 dataset (Merity et al., 2016) were sequentially fed into the candidate models.
We then fit a linear classifier (over words in the vocabulary; n=50k) from the last layer's feature representation on the
training set to predict the next word, and evaluated performance on the held-out test set (Methods-8).

Figure 3: **Model performance on a next-word-prediction task predicts neural scores**. Next-word-prediction task performance was evaluated as the surprisal between the predicted and true next word in the WikiText-2 dataset of 720 Wikipedia articles, or *perplexity* (x-axis, lower is better). Next-word-prediction task scores strongly predict neural scores for *Pereira2018* and *Blank2014*; the correlation for *Fedorenko2016* is also positive but not significant.

Indeed, next-word-prediction task performance robustly predicts neural scores (Fig. 3; *r*=.45, *p*<.01, averaged across
datasets). The best language model, GPT2-xl, also achieves the highest neural predictivity (see previous section).

This relationship holds for model variants within each model class—embedding models, recurrent networks, and
transformers—suggesting that the power of a model's features to predict the next word of a text is key for matching the
brain's representations.

To test whether next-word prediction is special in this respect, we asked whether model performance on *any* task
correlates with neural predictivity. Focusing on the high-performing, transformer models, we found that performance on
tasks from the GLUE benchmark collection (Cer et al., 2018; Dolan & Brockett, 2005; Levesque et al., 2012; Rajpurkar et al.,
2016; Socher et al., 2013; A. Wang, Singh, et al., 2019; Warstadt et al., 2019; Williams et al., 2018)—including
grammaticality judgments, sentence similarity judgments, and inference—do *not* correlate with neural predictivity, in spite
of eliciting variable performance across models (SI-5). This result, consistent with (Gauthier & Levy, 2019), suggests that
optimizing for predictive representations may be a critical shared objective of biological and artificial neural networks for
language, and perhaps more generally (Singer et al., 2018).

Figure 4: **Behavioral predictivity, neural predictivity, and next-word-prediction task performance are pairwise correlated**. (a) Behavioral predictivity of each model on *Futrell2018* human reading times, notations similar to Fig. 2. Ceiling level is .78. (b) Models' neural predictivity (aggregated across the three neural datasets) correlates with behavioral predictivity (see Fig. S6 for the neural-behavioral predictivity correlations on the three neural datasets individually). (c) Next-word-prediction task performance (Fig. 3) correlates with behavioral predictivity.

Figure 5: **Model architecture alone already yields predictive representations and untrained performance predicts trained performance**. We evaluate untrained models by keeping weights at their initial random values. The remaining representations are driven by architecture alone and are tested on the three neural datasets (a, Fig. 2) and the behavioral dataset (b, Fig. 4). Across all datasets, architecture alone yields representations that predict human brain activity considerably well. For Pereira2018, training typically improves scores by 85% whereas for Fedorenko2016, Blank2014 and Futrell2018 training does not always change and for some models even decreases the similarity with human measurements.

Neural predictivity and next-word-prediction task performance correlate with behavioral predictivity. Beyond internal neural representations, we tested the models' ability to predict external behavioral outputs because, ultimately, we strive for a computationally precise account of language processing that can explain both neural response patterns and observable linguistic behaviors. We chose a large corpus (n=180 participants) of self-paced reading times for naturalistic story materials (*Futrell2018* dataset (Futrell et al., 2018)). Per-word reading times provide a theory-neutral measure of incremental comprehension difficulty, which has long been a cornerstone of psycholinguistic research in testing theories of sentence comprehension (Demberg & Keller, 2008; Gibson, 1998; Just & Carpenter, 1980; D. C. Mitchell, 1984; Rayner, 1978; Smith & Levy, 2013).

Specific models accurately predict human reading times. We regressed each model's last layer's feature representation against reading times and evaluated predictivity on held-out words. As with the neural datasets, we observed a spread of model ability to capture human behavioral data, with models such as GPT2-xl, skip-thoughts, and AlBERT-xxlarge predicting these data close to or at ceiling (Fig. 4a; also Merkx & Frank, 2020; Wilcox et al., 2020).

Neural predictivity correlates with behavioral predictivity. To test whether models with the highest neural scores also predict reading times best, we compared models' neural predictivity (across datasets) with those same models' behavioral predictivity. Indeed, we observed a strong correlation (Fig. 4b; r=.49, *p<.001*), which also holds for the individual neural datasets (Fig. S6). These results are in line with earlier studies (Goodkind & Bicknell, 2018; van Schijndel & Linzen, 2018) and suggest that further improving models' neural predictivity will simultaneously improve their behavioral predictivity. An intriguing outlier in this analysis is the skip-thoughts model, which predicts neural activity only moderately, but predicts reading times at ceiling.

Next-word-prediction task performance correlates with behavioral predictivity. Next-word-prediction task performance is predictive of reading times (Fig. 4c; r=.37, *p<.05).* Note that this relationship, similar to the brain-to-behavior one, is not as strong as the one between next-word-prediction task performance and neural predictivity. This difference could point to additional mechanisms, on top of predictive language processing, that were recruited for the reading task.

Model architecture alone yields predictive representations. All models come with intrinsic architectural properties, like size, the presence of recurrence, and the directionality and length of context used to perform the target task (Methods 5, Table S9). These differences strongly affect model performance on normative tasks like next-word prediction after training, and define the representational space that the model can learn (Arora et al., 2018; Fukushima, 1988). To test whether model architecture alone—without training—already yields representational spaces that are similar to those implemented by the language network in the brain, we evaluated models with their initial (random) weights. Strikingly, even with no training, several model architectures reliably predicted brain activity (Fig. 5). For example, on *Pereira2018*, untrained GPT2-xl

Figure 6: **Summary of the key results**. Normalized neural and behavioral predictivities are shown in circles. For the neural datasets (averaged and individual, top row), and for the behavioral dataset (bottom right), we report i) the value for the model achieving the highest predictivity (GPT2-xl is the model with the highest average score across the four human datasets), and ii) the correlation between the untrained and trained scores. As discussed in <u>Results</u>, architecture alone yields reasonable scores which are also predictive of model scores after training. The next-word prediction task (bottom left) predicts neural and behavioral scores; and neural scores predict behavioral scores.

achieves predictivity of *~80%*, only *~20%* lower than the trained network. (Importantly, a random context-independent
embedding with equal dimensionality but no architectural priors predicts only 27% of this dataset (Fig. S7), suggesting that a
large feature space alone, without architectural priors, is not sufficient.) A similar trend is observed across models: training
generally improves neural predictivity, on average by .3 (85% relative improvement). Across models, the untrained scores
are strongly predictive of the trained scores (*r=.71, p<<.00001*), indicating that models that predict human neural data
poorly with random weights also perform poorly after training, but models that already predict neural data well with
random weights improve further with training.

Although untrained scores are also predictive of the trained scores for *Fedorenko2016* and *Blank2014*, some training
objectives seem to make model representations less brain-like. AlBERT models, for instance, drop from an untrained score
of ≈ *87%* on *Fedorenko2016* to a trained score of ≈ *57%*. The best model in our analyses, GPT2-xl, also predicts *Blank2014*
better without training: its performance decreases from 64% with random weights to 32% after training.

Discussion

Our results, summarized in Fig. 6, show that specific ANN language models can predict human neural and behavioral
responses to linguistic input with high accuracy: the best models achieve, on some datasets, perfect predictivity relative to
the noise ceiling. Neural predictivity correlates across datasets spanning recording modalities (fMRI, ECoG, reading times)
and diverse materials presented visually and auditorily, establishing the robustness and generality of these findings. Both
neural and behavioral predictivity correlate with model performance on the normative next-word prediction task, but not
other language tasks (SI-5). Finally, model architectures alone, with random weights, produce representations that capture
neural and behavioral linguistic responses and closely 'track' the representations with learned weights across datasets.

Underlying this and related work is the idea that large-scale neural networks can serve as possible mechanistic hypotheses
of brain processing. The first goal, we would argue, is to identify models that are highly predictive of brain activity. The most
predictive models can then be dissected to uncover the features critical for achieving high brain scores, and can serve as the
basis for the next generation of mechanistic models of human language comprehension. We found a number of models
with perfect/near-perfect predictivity of neural and behavioral language responses, and took the first steps to interpret
these models. First, we found that the models' neural predictivity strongly relates to their performance on a normative
'language modeling' task (next-word prediction) but not other tasks (SI-5; also (Gauthier & Levy, 2019)). Language modeling
is the task of choice in the natural language processing (NLP) community: it is simple, unsupervised, scalable, and appears to
produce the most generally useful, successful language representations. This is likely because language modeling
encourages a neural network to build a joint probability model of the linguistic signal, which implicitly requires sensitivity to
diverse kinds of regularities in the signal. However, at a deeper conceptual level, predictive processing has advanced to the
forefront of theorizing in cognitive science (Clark, 2013; Tenenbaum et al., 2011) and neuroscience (Keller & Mrsic-Flogel,

2018), including in the domain of language (Kuperberg & Jaeger, 2016; Levy, 2008a). The rich sources of information that
comprehenders combine to interpret language—including lexical and syntactic information, pragmatic reasoning, and world
knowledge (Garnsey et al., 1997; MacDonald et al., 1994; Tanenhaus et al., 1995; Trueswell et al., 1993, 1994)—can be used
to make informed guesses about how the linguistic signal may unfold, and much behavioral and neural evidence now
suggests that readers and listeners indeed engage in such predictive behavior (Altmann & Kamide, 1999; Frank & Bod, 2011;
Kuperberg & Jaeger, 2016; Shain et al., 2020; Smith & Levy, 2013). Some accounts, rooted in the rich tradition of the
analysis-by-synthesis approach to cognition (Neisser, 1967), construe prediction as forward-simulation carried out by the
language production system that draws on the generative language model (Dell & Chang, 2014; Pickering & Garrod, 2013).
An intriguing possibility is therefore that both the human language system and the ANN models of language are optimized
to predict upcoming words in the service of efficient meaning extraction.

We also demonstrated that architecture alone, with random weights, can yield representations that match human brain
data well. If we construe model training as analogous to learning in human development, then human cortex might already
provide a sufficiently rich structure that allows for the rapid acquisition of language (Rodriguez & Granger, 2016). Perhaps
most of development is then a combination of the system wiring up (Saygin et al., 2016; Zador, 2019) and learning the right
decoders on top of largely structurally defined features. In that analogy, community development of new architectures
could be akin to evolution (Hasson et al., 2020), or perhaps, more accurately, selective breeding with genetic modification:
structural changes are tested and the best-performing ones are incorporated into the next generation of models.
Importantly, this process implicitly still optimizes for certain tasks (like language modeling), only on a different timescale.

These discoveries pave the way for many exciting future directions. The most brain-like language models can now be
investigated in richer detail, ideally leading to intuitive theories around their inner workings. Such research is much easier to
perform on models than on biological systems since all their structure and weights are easily accessible and manipulable
(Cheney et al., 2017; Lindsey et al., 2019). Controlled comparisons of minimally different architectural variants and training
objectives could define the necessary and sufficient conditions for human-like language processing (Samek et al., 2017),
synergizing with parallel ongoing efforts in NLP to probe ANNs' linguistic representations (Hewitt & Manning, 2019; Linzen
et al., 2016; Tenney et al., 2020). Here, we worked with off-the-shelf models, and compared their match to neural data
based on their performance on the next-word-prediction task vs. other tasks (also, Gauthier & Levy, 2019). Re-training many
models on many tasks from scratch might determine which features are most important for brain predictivity, but is
currently prohibitively expensive due to the insurmountable space of hyper-parameters. Further, the fact that language
modeling is inherently built into the evolution of language models by the NLP community, as noted above, may make it
impossible to fully eliminate its influences on the architecture even for models trained from scratch on other tasks.

How can we develop models that are even more brain-like? Despite impressive performance on the datasets and metrics
here, ANN language models are far from human-level performance in the hardest problems of language understanding. An
important open direction is to integrate language models like those used here with models and data resources that attempt
to capture aspects of meaning important for commonsense world knowledge (e.g., Bisk et al., 2020; Bosselut et al., 2020;
Sap et al., 2019, 2020; Yi et al., 2018). Such models might capture not only predictive processing in the brain—what word is
likely to come next—but also semantic parsing, mapping language into conceptual representations that support grounded
language understanding and reasoning (Bisk et al., 2020). The fact that language models lack meaning and focus on local
linguistic coherence (Mahowald et al., 2020; Wilcox et al., 2020) may explain why their representations fall short of ceiling
on *Blank2014*, which uses story materials and may therefore require long-range contexts.

One key missing piece in the mechanistic modeling of human language processing is a more detailed mapping from model
components onto brain anatomy. In particular, aside from the general targeting of the fronto-temporal language network, it
is unclear which parts of a model map onto which components of the brain's language processing mechanisms. In models of
vision, for instance, attempts are made to map ANN layers and neurons onto cortical regions (Kubilius et al., 2019) and sub-
regions (Lee & DiCarlo, 2018). However, whereas function and its mapping onto anatomy is at least coarsely defined in the
case of vision (Felleman & Van Essen, 1991), a similar mapping is not yet established in language beyond the broad
distinction between perceptual processing and higher-level linguistic interpretation (Fedorenko & Thompson-Schill, 2014).
The network that supports higher-level linguistic interpretation—which we focus on here—is extensive and plausibly

contains meaningful functional dissociations, but how the network is precisely subdivided and what respective roles its
different components play remains debated. Uncovering the internal structure of the human language network, for which
intracranial recording approaches with high spatial and temporal resolution may prove critical (Mukamel & Fried, 2012;
Parvizi & Kastner, 2018), would allow us to guide and constrain models of tissue-mapped mechanistic language processing.
More precise brain-to-model mappings would also allow us to test the effects of perturbations on models and compare
them against perturbation effects in humans, as assessed with lesion studies or reversible stimulation. More broadly,
anatomically and functionally precise models are a required software component of any form of brain-machine-interface.
275
Taken together, our findings lay a critical foundation for a promising research program synergizing high-performing
mechanistic models of natural language processing with large-scale neural and behavioral measurements of human
language processing in a virtuous cycle: testing model ability to predict neural and behavioral brain measurements,
dissecting the best-performing models to understand which components are critical for high brain predictivity, developing
better models leveraging this knowledge, and collecting new data to challenge and constrain the future generations of
neurally plausible models of language processing.
282

References

Altmann, G. T. M., & Kamide, Y. (1999). Incremental interpretation at verbs: Restricting the domain of subsequent reference. *Cognition*, *73*(3), 247–264. https://doi.org/10.1016/S0010-0277(99)00059-1

Arora, S., Cohen, N., & Hazan, E. (2018). On the optimization of deep networks: Implicit acceleration by overparameterization. *International Conference on Machine Learning (ICML)*, 372–389. http://arxiv.org/abs/1802.06509

Bates, E., Wilson, S. M., Saygin, A. P., Dick, F., Sereno, M. I., Knight, R. T., & Dronker, N. F. (2003). Voxel-based lesion-symptom mapping. *Nature Neuroscience*, *6*(5), 448–450. https://doi.org/10.1038/nn1050

Bautista, A., & Wilson, S. M. (2016). Neural responses to grammatically and lexically degraded speech. *Language, Cognition and Neuroscience*, *31*(4), 567–574. https://doi.org/10.1080/23273798.2015.1123281

Binder, J. R., Frost, J. A., Hammeke, T. A., Cox, R. W., Rao, S. M., & Prieto, T. (1997). Human brain language areas identified by functional magnetic resonance imaging. *Journal of Neuroscience*, *17*(1), 353–362. https://doi.org/10.1523/JNEUROSCI.17-01-00353.1997

Bisk, Y., Holtzman, A., Thomason, J., Andreas, J., Bengio, Y., Chai, J., Lapata, M., Lazaridou, A., May, J., Nisnevich, A., Pinto, N., & Turian, J. (2020). Experience Grounds Language. *ArXiv Preprint*. http://arxiv.org/abs/2004.10151

Bisk, Y., Zellers, R., Bras, R. Le, Gao, J., & Choi, Y. (2019, November 26). PIQA: Reasoning about Physical Commonsense in Natural Language. *AAAI Conference on Artificial Intelligence*. http://arxiv.org/abs/1911.11641

Blank, I. A., & Fedorenko, E. (2017). Domain-general brain regions do not track linguistic input as closely as language-selective regions. *The Journal of Neuroscience*, *37*(41), 9999–10011. https://doi.org/10.1523/JNEUROSCI.3642-16.2017

Blank, I. A., & Fedorenko, E. (2020). No evidence for differences among language regions in their temporal receptive windows. *NeuroImage*, *219*, 116925. https://doi.org/10.1016/j.neuroimage.2020.116925

Blank, I., Balewski, Z., Mahowald, K., & Fedorenko, E. (2016). Syntactic processing is distributed across the language system. *NeuroImage*, *127*, 307–323. https://doi.org/10.1016/j.neuroimage.2015.11.069

Blank, I., Kanwisher, N., & Fedorenko, E. (2014). A functional dissociation between language and multiple-demand systems revealed in patterns of BOLD signal fluctuations. *Journal of Neurophysiology*, *112*(5), 1105–1118. https://doi.org/10.1152/jn.00884.2013

Bosselut, A., Rashkin, H., Sap, M., Malaviya, C., Celikyilmaz, A., & Choi, Y. (2020). CoMET: Commonsense transformers for automatic knowledge graph construction. *Association for Computational Linguistics (ACL)*, 4762–4779. https://doi.org/10.18653/v1/p19-1470

Brennan, J. R., & Pylkkänen, L. (2017). MEG Evidence for Incremental Sentence Composition in the Anterior Temporal Lobe. *Cognitive Science*, *41*, 1515–1531. https://doi.org/10.1111/cogs.12445

Brennan, J. R., Stabler, E. P., Van Wagenen, S. E., Luh, W. M., & Hale, J. T. (2016). Abstract linguistic structure correlates with temporal activity during naturalistic comprehension. *Brain and Language*, *157–158*, 81–94. https://doi.org/10.1016/j.bandl.2016.04.008

Brown, T. B., Mann, B., Ryder, N., Subbiah, M., Kaplan, J., Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., Agarwal, S., Herbert-Voss, A., Krueger, G., Henighan, T., Child, R., Ramesh, A., Ziegler, D. M., Wu, J., Winter, C., … Amodei, D. (2020). Language Models are Few-Shot Learners. *ArXiv Preprint*. http://arxiv.org/abs/2005.14165

Buzsáki, G., Anastassiou, C. A., & Koch, C. (2012). The origin of extracellular fields and currents-EEG, ECoG, LFP and spikes. *Nature Reviews Neuroscience*, *13*(6), 407–420. https://doi.org/10.1038/nrn3241

Cer, D., Diab, M., Agirre, E., Lopez-Gazpio, I., & Specia, L. (2018). SemEval-2017 Task 1: Semantic Textual Similarity Multilingual and Crosslingual Focused Evaluation. *International Workshop on Semantic Evaluation*, 1–14. https://doi.org/10.18653/v1/s17-2001

Chelba, C., Mikolov, T., Schuster, M., Ge, Q., Brants, T., Koehn, P., & Robinson, T. (2014). One billion word benchmark for measuring progress in statistical language modeling. *Annual Conference of the International Speech Communication Association*, 2635–2639. http://arxiv.org/abs/1312.3005

Cheney, N., Schrimpf, M., & Kreiman, G. (2017). On the Robustness of Convolutional Neural Networks to Internal Architecture and Weight Perturbations. *ArXiv Preprint*. http://arxiv.org/abs/1703.08245

Clark, A. (2013). Whatever next? Predictive brains, situated agents, and the future of cognitive science. *Behavioral and Brain Sciences*, *36*(3), 181–204. https://doi.org/10.1017/S0140525X12000477

Conneau, A., Khandelwal, K., Goyal, N., Chaudhary, V., Wenzek, G., Guzmán, F., Grave, E., Ott, M., Zettlemoyer, L., & Stoyanov, V. (2019). Unsupervised Cross-lingual Representation Learning at Scale. *ArXiv Preprint*.

http://arxiv.org/abs/1911.02116

Dai, Z., Yang, Z., Yang, Y., Carbonell, J., Le, Q. V., & Salakhutdinov, R. (2020). Transformer-XL: Attentive language models beyond a fixed-length context. *Association for Computational Linguistics (ACL)*, 2978–2988. https://doi.org/10.18653/v1/p19-1285

Dell, G. S., & Chang, F. (2014). The p-chain: Relating sentence production and its disorders to comprehension and acquisition. In *Philosophical Transactions of the Royal Society B: Biological Sciences* (Vol. 369, Issue 1634, p. 20120394). The Royal Society. https://doi.org/10.1098/rstb.2012.0394

Demberg, V., & Keller, F. (2008). Data from eye-tracking corpora as evidence for theories of syntactic processing complexity. *Cognition*, *109*(2), 193–210. https://doi.org/10.1016/j.cognition.2008.07.008

Deniz, F., Nunez-Elizalde, A. O., Huth, A. G., & Gallant, J. L. (2019). The Representation of Semantic Information Across Human Cerebral Cortex During Listening Versus Reading Is Invariant to Stimulus Modality. *Journal of Neuroscience*, *39*(39), 7722–7736. https://doi.org/10.1523/JNEUROSCI.0675-19.2019

Devlin, J., Chang, M.-W., Lee, K., & Toutanova, K. (2018). BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. *ArXiv Preprint*. https://arxiv.org/abs/1810.04805

Diachek, E., Blank, I., Siegelman, M., Affourtit, J., & Fedorenko, E. (2020). The domain-general multiple demand (MD) network does not support core aspects of language comprehension: A large-scale fMRI investigation. *Journal of Neuroscience*, *40*(23), 4536–4550. https://doi.org/10.1523/JNEUROSCI.2036-19.2020

Dieng, A. B., Ruiz, F. J. R., & Blei, D. M. (2019). Topic Modeling in Embedding Spaces. *ArXiv Preprint*. http://arxiv.org/abs/1907.04907

Ding, N., Melloni, L., Zhang, H., Tian, X., & Poeppel, D. (2015). Cortical tracking of hierarchical linguistic structures in connected speech. *Nature Neuroscience*, *19*(1), 158–164. https://doi.org/10.1038/nn.4186

Dolan, W. B., & Brockett, C. (2005). Automatically Constructing a Corpus of Sentential Paraphrases. *International Workshop on Paraphrasing (IWP)*, 9–16. http://www.cogsci.princeton.edu/~wn/

Dotlačil, J. (2018). Building an ACT-R Reader for Eye-Tracking Corpus Data. *Topics in Cognitive Science*, *10*(1), 144–160. https://doi.org/10.1111/tops.12315

Fedorenko, E., Behr, M. K., & Kanwisher, N. (2011). Functional specificity for high-level linguistic processing in the human brain. *Proceedings of the National Academy of Sciences (PNAS)*, *108*(39), 16428–16433. https://doi.org/10.1073/pnas.1112937108

Fedorenko, E., Blank, I., Siegelman, M., & Mineroff, Z. (2020). Lack of selectivity for syntax relative to word meanings throughout the language network. *BioRxiv Preprint*. https://doi.org/10.1101/477851

Fedorenko, E., Hsieh, P. J., Nieto-Castañón, A., Whitfield-Gabrieli, S., & Kanwisher, N. (2010). New method for fMRI investigations of language: Defining ROIs functionally in individual subjects. *Journal of Neurophysiology*, *104*(2), 1177–1194. https://doi.org/10.1152/jn.00032.2010

Fedorenko, E., Nieto-Castañon, A., & Kanwisher, N. (2012). Lexical and syntactic representations in the brain: An fMRI investigation with multi-voxel pattern analyses. *Neuropsychologia*, *50*(4), 499–513. https://doi.org/10.1016/j.neuropsychologia.2011.09.014

Fedorenko, E., Scott, T. L., Brunner, P., Coon, W. G., Pritchett, B., Schalk, G., & Kanwisher, N. (2016). Neural correlate of the construction of sentence meaning. *Proceedings of the National Academy of Sciences of the United States of America (PNAS)*, *113*(41), E6256–E6262. https://doi.org/10.1073/pnas.1612132113

Fedorenko, E., & Thompson-Schill, S. L. (2014). Reworking the language network. *Trends in Cognitive Sciences*, *18*(3), 120–126. https://doi.org/10.1016/j.tics.2013.12.006

Felleman, D. J., & Van Essen, D. C. (1991). Distributed hierachical processing in the primate cerebral cortex. *Cerebral Cortex*, *1*(1), 1–47. https://doi.org/10.1093/cercor/1.1.1

Frank, S. L., & Bod, R. (2011). Insensitivity of the human sentence-processing system to hierarchical structure. *Psychological Science*, *22*(6), 829–834. https://doi.org/10.1177/0956797611409589

Frank, S. L., Otten, L. J., Galli, G., & Vigliocco, G. (2015). The ERP response to the amount of information conveyed by words in sentences. *Brain and Language*, *140*. https://doi.org/10.1016/j.bandl.2014.10.006

Friederici, A. D. (2012). The cortical language circuit: From auditory perception to sentence comprehension. *Trends in Cognitive Sciences*, *16*(5), 262–268. https://doi.org/10.1016/j.tics.2012.04.001

Fukushima, K. (1988). Neocognitron: A hierarchical neural network capable of visual pattern recognition. *Neural Networks*, *1*(2), 119–130. https://doi.org/10.1016/0893-6080(88)90014-7

Futrell, R., Gibson, E., & Levy, R. P. (2020). Lossy-Context Surprisal: An Information-Theoretic Model of Memory Effects in Sentence Processing. *Cognitive Science*, *44*(3). https://doi.org/10.1111/cogs.12814

Futrell, R., Gibson, E., Tily, H. J., Blank, I., Vishnevetsky, A., Piantadosi, S. T., & Fedorenko, E. (2018). The natural stories corpus. *International Conference on Language Resources and Evaluation (LREC)*, 76–82. http://arxiv.org/abs/1708.05763

Garnsey, S. M., Pearlmutter, N. J., Myers, E., & Lotocky, M. A. (1997). The contributions of verb bias and plausibility to the comprehension of temporarily ambiguous sentences. *Journal of Memory and Language*, *37*(1), 58–93. https://doi.org/10.1006/jmla.1997.2512

Gauthier, J., & Ivanova, A. (2018). *Does the brain represent words? An evaluation of brain decoding studies of language understanding*. http://arxiv.org/abs/1806.00591

Gauthier, J., & Levy, R. (2019). Linking artificial and human neural representations of language. *Empirical Methods for Natural Language Processing (EMNLP)*, 529–539. https://doi.org/10.18653/v1/d19-1050

Gibson, E. (1998). Linguistic complexity: Locality of syntactic dependencies. *Cognition*, *68*(1). https://doi.org/10.1016/S0010-0277(98)00034-1

Gibson, E., Bergen, L., & Piantadosi, S. T. (2013). Rational integration of noisy evidence and prior semantic expectations in sentence interpretation. *Proceedings of the National Academy of Sciences of the United States of America (PNAS)*, *110*(20), 8051–8056. https://doi.org/10.1073/pnas.1216438110

Goodkind, A., & Bicknell, K. (2018). Predictive power of word surprisal for reading times is a linear function of language model quality. *Cognitive Modeling and Computational Linguistics (CMCL)*, 10–18. https://doi.org/10.18653/v1/w18-0102

Gorno-Tempini, M. L., Dronkers, N. F., Rankin, K. P., Ogar, J. M., Phengrasamy, L., Rosen, H. J., Johnson, J. K., Weiner, M. W., & Miller, B. L. (2004). Cognition and Amatomy in Three Variants of Primany Progressive Aphasia. *Annals of Neurology*, *55*(3), 335–346. https://doi.org/10.1002/ana.10825

Hagoort, P. (2019). The neurobiology of language beyond single-word processing. *Science*, *366*(6461), 55–58. https://doi.org/10.1126/science.aax0289

Hale, J. (2001). A probabilistic earley parser as a psycholinguistic model. *North American Chapter of the Association for Computational Linguistics (NAACL)*, 1–8. https://doi.org/10.3115/1073336.1073357

Hasson, U., Nastase, S. A., & Goldstein, A. (2020). Direct Fit to Nature: An Evolutionary Perspective on Biological and Artificial Neural Networks. *Neuron*, *105*(3), 416–434. https://doi.org/10.1016/j.neuron.2019.12.002

Henderson, J. M., Choi, W., Lowder, M. W., & Ferreira, F. (2016). Language structure in the brain: A fixation-related fMRI study of syntactic surprisal in reading. *NeuroImage*, *132*, 293–300. https://doi.org/10.1016/j.neuroimage.2016.02.050

Hewitt, J., & Manning, C. D. (2019). A structural probe for finding syntax in word representations. *North American Chapter of the Association for Computational Linguistics (NAACL)*, *1*, 4129–4138.

Hu, J., Gauthier, J., Qian, P., Wilcox, E., & Levy, R. P. (2020). *A Systematic Assessment of Syntactic Generalization in Neural Language Models*. http://arxiv.org/abs/2005.03692

Huth, A. G., de Heer, W. A., Griffiths, T. L., Theunissen, F. E., & Gallant, J. L. (2016). Natural speech reveals the semantic maps that tile human cerebral cortex. *Nature*, *532*(7600), 453–458. https://doi.org/10.1038/nature17637

Jain, S., & Huth, A. (2018, May 21). Incorporating Context into Language Encoding Models for fMRI. *Neural Information Processing Systems (NeurIPS)*. https://doi.org/10.1101/327601

Jozefowicz, R., Vinyals, O., Schuster, M., Shazeer, N., & Wu, Y. (2016). *Exploring the Limits of Language Modeling*. http://arxiv.org/abs/1602.02410

Jurafsky, D. (1996). A Probabilistic Model of Lexical and Syntactic Access and Disambiguation. *Cognitive Science*, *20*(2), 137–194. https://doi.org/10.1207/s15516709cog2002_1

Just, M. A., & Carpenter, P. A. (1980). A theory of reading: From eye fixations to comprehension. *Psychological Review*, *87*(4), 329–354. https://doi.org/10.1037/0033-295X.87.4.329

Just, M. A., Carpenter, P. A., & Woolley, J. D. (1982). Paradigms and processes in reading comprehension. *Journal of Experimental Psychology: General*, *111*(2), 228–238. https://doi.org/10.1037/0096-3445.111.2.228

Kell, A. J. E., Yamins, D. L. K., Shook, E. N., Norman-Haignere, S. V., & McDermott, J. H. (2018). A Task-Optimized Neural Network Replicates Human Auditory Behavior, Predicts Brain Responses, and Reveals a Cortical Processing Hierarchy. *Neuron*, *98*(3), 630–644. https://doi.org/10.1016/j.neuron.2018.03.044

Keller, G. B., & Mrsic-Flogel, T. D. (2018). Predictive Processing: A Canonical Cortical Computation. *Neuron*, *100*(2), 424–435. https://doi.org/10.1016/j.neuron.2018.10.003

Keskar, N. S., McCann, B., Varshney, L. R., Xiong, C., & Socher, R. (2019). CTRL: A Conditional Transformer Language Model for Controllable Generation. *ArXiv Preprint*. http://arxiv.org/abs/1909.05858

Khaligh-Razavi, S. M., & Kriegeskorte, N. (2014). Deep Supervised, but Not Unsupervised, Models May Explain IT Cortical

442   Representation. *PLoS Computational Biology*, *10*(11). https://doi.org/10.1371/journal.pcbi.1003915

443 Kiros, R., Zhu, Y., Salakhutdinov, R. R., Zemel, R., Urtasun, R., Torralba, A., & Fidler, S. (2015). Skip-Thought Vectors. *Neural*
444   *Information Processing Systems (NIPS)*, 3294–3302. http://papers.nips.cc/paper/5950-skip-thought-vectors

445 Kriegeskorte, N. (2008). Representational similarity analysis – connecting the branches of systems neuroscience. *Frontiers in*
446   *Systems Neuroscience*, *2*. https://doi.org/10.3389/neuro.06.004.2008

447 Kubilius, J., Schrimpf, M., Hong, H., Majaj, N. J., Rajalingham, R., Issa, E. B., Kar, K., Bashivan, P., Prescott-Roy, J., Schmidt, K.,
448   Nayebi, A., Bear, D., Yamins, D. L. K., & DiCarlo, J. J. (2019). Brain-Like Object Recognition with High-Performing
449   Shallow Recurrent ANNs. In H. Wallach, H. Larochelle, A. Beygelzimer, F. D'Alché-Buc, E. Fox, & R. Garnett (Eds.),
450   *Neural Information Processing Systems (NeurIPS)* (pp. 12785--12796). Curran Associates, Inc.
451   http://arxiv.org/abs/1909.06161

452 Kuperberg, G. R., & Jaeger, T. F. (2016). What do we mean by prediction in language comprehension? *Language, Cognition*
453   *and Neuroscience*, *31*(1), 32–59. https://doi.org/10.1080/23273798.2015.1102299

454 Lakretz, Y., Dehaene, S., & King, J. R. (2020). What limits our capacity to process nested long-range dependencies in
455   sentence comprehension? *Entropy*, *22*(4), 446. https://doi.org/10.3390/E22040446

456 Lample, G., & Conneau, A. (2019). Cross-lingual Language Model Pretraining. *Neural Information Processing Systems*
457   *(NeurIPS)*, 7059–7069. http://arxiv.org/abs/1901.07291

458 Lan, Z., Chen, M., Goodman, S., Gimpel, K., Sharma, P., & Soricut, R. (2019). ALBERT: A Lite BERT for Self-supervised Learning
459   of Language Representations. *ArXiv Preprint*. http://arxiv.org/abs/1909.11942

460 Lawrence Marple, S. (1999). Computing the discrete-time analytic signal via fft. *IEEE Transactions on Signal Processing*,
461   *47*(9), 2600–2603. https://doi.org/10.1109/78.782222

462 Lee, H., & DiCarlo, J. (2018, September 21). Topographic Deep Artificial Neural Networks (TDANNs) predict face selectivity
463   topography in primate inferior temporal (IT) cortex. *Cognitive Computational Neuroscience (CCN)*.
464   https://doi.org/10.32470/ccn.2018.1085-0

465 Levesque, H. J., Davis, E., & Morgenstern, L. (2012). The winograd schema challenge. *International Workshop on Temporal*
466   *Representation and Reasoning*, 552–561. www.aaai.org

467 Levy, R. (2008a). Expectation-based syntactic comprehension. *Cognition*, *106*(3), 1126–1177.
468   https://doi.org/10.1016/j.cognition.2007.05.006

469 Levy, R. (2008b). A noisy-channel model of rational human sentence comprehension under uncertain input. *Empirical*
470   *Methods in Natural Language Processing (EMNLP)*, 234–243. https://doi.org/10.3115/1613715.1613749

471 Lewis, R. L., Vasishth, S., & Van Dyke, J. A. (2006). Computational principles of working memory in sentence comprehension.
472   *Trends in Cognitive Sciences*, *10*(10), 447–454. https://doi.org/10.1016/j.tics.2006.08.007

473 Lindsey, J., Ocko, S. A., Ganguli, S., & Deny, S. (2019, January 3). A unified theory of early visual representations from retina
474   to cortex through anatomically constrained deep cnNs. *International Conference on Learning Representations (ICLR)*.
475   http://arxiv.org/abs/1901.00945

476 Linzen, T., Dupoux, E., & Goldberg, Y. (2016). Assessing the Ability of LSTMs to Learn Syntax-Sensitive Dependencies.
477   *Transactions of the Association for Computational Linguistics*, *4*, 521–535. https://doi.org/10.1162/tacl_a_00115

478 Liu, Y., Ott, M., Goyal, N., Du, J., Joshi, M., Chen, D., Levy, O., Lewis, M., Zettlemoyer, L., & Stoyanov, V. (2019). RoBERTa: A
479   Robustly Optimized BERT Pretraining Approach. *ArXiv Preprint*. http://arxiv.org/abs/1907.11692

480 Lopopolo, A., Frank, S. L., Van Den Bosch, A., & Willems, R. M. (2017). Using stochastic language models (SLM) to map
481   lexical, syntactic, and phonological information processing in the brain. *PLoS ONE*, *12*(5).
482   https://doi.org/10.1371/journal.pone.0177794

483 Lyu, B., Choi, H. S., Marslen-Wilson, W. D., Clarke, A., Randall, B., & Tyler, L. K. (2019). Neural dynamics of semantic
484   composition. *Proceedings of the National Academy of Sciences (PNAS)*, *116*(42), 21318–21327.
485   https://doi.org/10.1073/pnas.1903402116

486 MacDonald, M. C., Pearlmutter, N. J., & Seidenberg, M. S. (1994). The lexical nature of syntactic ambiguity resolution.
487   *Psychological Review*, *101*(4), 676–703. https://doi.org/10.1037/0033-295x.101.4.676

488 Mahowald, K., Kachergis, G., & Frank, M. C. (2020). What counts as an exemplar model, anyway? A commentary on
489   Ambridge (2020). *First Language*. https://doi.org/10.1177/0142723720905920

490 McDonald, J., & Macwhinney, B. (1998). Maximum Likelihood Models for Sentence Processing. In *The Crosslinguistic Study*
491   *of Sentence Processing*.
492   https://www.researchgate.net/publication/230876309_Maximum_Likelihood_Models_for_Sentence_Processing

493 Merity, S., Xiong, C., Bradbury, J., & Socher, R. (2016). Pointer Sentinel Mixture Models. *ArXiv Preprint*.
494   http://arxiv.org/abs/1609.07843

Merkx, D., & Frank, S. L. (2020). Comparing Transformers and RNNs on predicting human sentence processing data. *ArXiv Preprint*. http://arxiv.org/abs/2005.09471

Mikolov, T., Sutskever, I., Chen, K., Corrado, G., & Dean, J. (2013, October 16). Distributed representations ofwords and phrases and their compositionality. *Neural Information Processing Systems (NIPS)*. http://arxiv.org/abs/1310.4546

Mitchell, D. C. (1984). Computational psycholinguistics View project Psycholinguistics View project. *New Methods in Reading Comprehension Research*. https://www.researchgate.net/publication/286455549

Mitchell, T. M., Shinkareva, S. V., Carlson, A., Chang, K. M., Malave, V. L., Mason, R. A., & Just, M. A. (2008). Predicting human brain activity associated with the meanings of nouns. *Science*, *320*(5880), 1191–1195. https://doi.org/10.1126/science.1152876

Monti, M. M., Parsons, L. M., & Osherson, D. N. (2012). Thought Beyond Language: Neural Dissociation of Algebra and Natural Language. *Psychological Science*, *23*(8), 914–922. https://doi.org/10.1177/0956797612437427

Mukamel, R., & Fried, I. (2012). Human Intracranial Recordings and Cognitive Neuroscience. *Annual Review of Psychology*, *63*(1), 511–537. https://doi.org/10.1146/annurev-psych-120709-145401

Neisser, U. (1967). Cognitive psychology. *American Psychological Association*. https://psycnet.apa.org/record/1967-35031-000

Nelson, M. J., El Karoui, I., Giber, K., Yang, X., Cohen, L., Koopman, H., Cash, S. S., Naccache, L., Hale, J. T., Pallier, C., & Dehaene, S. (2017). Neurophysiological dynamics of phrase-structure building during sentence processing. *Proceedings of the National Academy of Sciences of the United States of America (PNAS)*, *114*(18), E3669–E3678. https://doi.org/10.1073/pnas.1701590114

Pallier, C., Devauchellea, A. D., & Dehaenea, S. (2011). Cortical representation of the constituent structure of sentences. *Proceedings of the National Academy of Sciences of the United States of America (PNAS)*, *108*(6), 2522–2527. https://doi.org/10.1073/pnas.1018711108

Parvizi, J., & Kastner, S. (2018). Promises and limitations of human intracranial electroencephalography. *Nature Neuroscience*, *21*(4), 474–483. https://doi.org/10.1038/s41593-018-0108-2

Pennington, J., Socher, R., & Manning, C. D. (2014). Glove: Global Vectors for Word Representation. *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 1532–1543. https://doi.org/10.3115/v1/D14-1162

Pereira, F., Lou, B., Pritchett, B., Ritter, S., Gershman, S. J., Kanwisher, N., Botvinick, M., & Fedorenko, E. (2018). Toward a universal decoder of linguistic meaning from brain activation. *Nature Communications*, *9*. https://doi.org/10.1038/s41467-018-03068-4

Pickering, M. J., & Garrod, S. (2013). An integrated theory of language production and comprehension. *Behavioral and Brain Sciences*, *36*(4), 329–347. https://doi.org/10.1017/S0140525X12001495

Price, C. J. (2010). The anatomy of language: A review of 100 fMRI studies published in 2009. In *Annals of the New York Academy of Sciences* (Vol. 1191, pp. 62–88). https://doi.org/10.1111/j.1749-6632.2010.05444.x

Rabovsky, M., Hansen, S. S., & McClelland, J. L. (2018). Modelling the N400 brain potential as change in a probabilistic representation of meaning. *Nature Human Behaviour*, *2*(9), 693–705. https://doi.org/10.1038/s41562-018-0406-4

Radford, A., Narasimhan, K., Salimans, T., & Sutskever, I. (2018). *Improving Language Understanding by Generative Pre-Training*. https://gluebenchmark.com/leaderboard

Radford, A., Wu, J., Child, R., Luan, D., Amodei, D., & Sutskever, I. (2019). Language Models are Unsupervised Multitask Learners. *ArXiv Preprint*. https://github.com/codelucas/newspaper

Raffel, C., Shazeer, N., Roberts, A., Lee, K., Narang, S., Matena, M., Zhou, Y., Li, W., & Liu, P. J. (2019). Exploring the Limits of Transfer Learning with a Unified Text-to-Text Transformer. *ArXiv Preprint*. http://arxiv.org/abs/1910.10683

Rajpurkar, P., Zhang, J., Lopyrev, K., & Liang, P. (2016). SQuad: 100,000+ questions for machine comprehension of text. *Empirical Methods in Natural Language Processing (EMNLP)*, 2383–2392. http://arxiv.org/abs/1606.05250

Rashkin, H., Sap, M., Allaway, E., Smith, N. A., & Choi, Y. (2018). Event2Mind: Commonsense inference on events, intents, and reactions. *Association for Computational Linguistics (ACL)*, 463–473. https://doi.org/10.18653/v1/p18-1043

Rayner, K. (1978). Eye movements in reading and information processing. *Psychological Bulletin*, *85*(3), 618–660. https://doi.org/10.1037/0033-2909.85.3.618

Regev, M., Honey, C. J., Simony, E., & Hasson, U. (2013). Selective and invariant neural responses to spoken and written narratives. *Journal of Neuroscience*, *33*(40), 15978–15988. https://doi.org/10.1523/JNEUROSCI.1580-13.2013

Rodriguez, A., & Granger, R. (2016). The grammar of mammalian brain capacity. *Theoretical Computer Science*, *633*, 100–111. https://doi.org/10.1016/j.tcs.2016.03.021

Samek, W., Wiegand, T., & Müller, K.-R. (2017). Explainable Artificial Intelligence: Understanding, Visualizing and

548    Interpreting Deep Learning Models. *ArXiv Preprint*. http://arxiv.org/abs/1708.08296

549 Sanh, V., Debut, L., Chaumond, J., & Wolf, T. (2019). DistilBERT, a distilled version of BERT: smaller, faster, cheaper and
550    lighter. *ArXiv Preprint*. http://arxiv.org/abs/1910.01108

551 Sap, M., Le Bras, R., Allaway, E., Bhagavatula, C., Lourie, N., Rashkin, H., Roof, B., Smith, N. A., & Choi, Y. (2019). ATOMIC: An
552    Atlas of Machine Commonsense for If-Then Reasoning. *AAAI Conference on Artificial Intelligence*, *33*, 3027–3035.
553    https://doi.org/10.1609/aaai.v33i01.33013027

554 Sap, M., Rashkin, H., Chen, D., Le Bras, R., & Choi, Y. (2020). Social IQA: Commonsense reasoning about social interactions.
555    *Empirical Methods in Natural Language Processing (EMNLP)*, 4463–4473. https://doi.org/10.18653/v1/d19-1454

556 Saygin, Z. M., Osher, D. E., Norton, E. S., Youssoufian, D. A., Beach, S. D., Feather, J., Gaab, N., Gabrieli, J. D. E., & Kanwisher,
557    N. (2016). Connectivity precedes function in the development of the visual word form area. *Nature Neuroscience*,
558    *19*(9), 1250–1255. https://doi.org/10.1038/nn.4354

559 Schrimpf, M., Kubilius, J., Hong, H., Majaj, N. J., Rajalingham, R., Issa, E. B., Kar, K., Bashivan, P., Prescott-Roy, J., Schmidt, K.,
560    Yamins, D. L. K., & DiCarlo, J. J. (2018). Brain-Score: Which Artificial Neural Network for Object Recognition is most
561    Brain-Like? *BioRxiv*. https://doi.org/10.1101/407007

562 Shain, C., Blank, I. A., van Schijndel, M., Schuler, W., & Fedorenko, E. (2020). fMRI reveals language-specific predictive
563    coding during naturalistic sentence comprehension. *Neuropsychologia*, *138*.
564    https://doi.org/10.1016/j.neuropsychologia.2019.107307

565 Singer, Y., Teramoto, Y., Willmore, B. D. B., King, A. J., Schnupp, J. W. H., & Harper, N. S. (2018). Sensory cortex is optimised
566    for prediction of future input. *ELife*, *7*. https://doi.org/10.7554/eLife.31557

567 Smith, N. J., & Levy, R. (2013). The effect of word predictability on reading time is logarithmic. *Cognition*, *128*(3), 302–319.
568    https://doi.org/10.1016/j.cognition.2013.02.013

569 Socher, R., Perelygin, A., Wu, J. Y., Chuang, J., Manning, C. D., Ng, A. Y., & Potts, C. (2013). Recursive deep models for
570    semantic compositionality over a sentiment treebank. *Empirical Methods in Natural Language Processing (EMNLP)*,
571    1631–1642. http://nlp.stanford.edu/

572 Spivey-Knowlton, M. J. (1996). *Integration of visual and linguistic information: Human data and model simulations*.
573    University of Rochester.

574 Steedman, M. (2000). *The Syntactic Process*. MIT Press. https://mitpress.mit.edu/books/syntactic-process

575 Tanenhaus, M. K., Spivey-Knowlton, M. J., Eberhard, K. M., & Sedivy, J. C. (1995). Integration of visual and linguistic
576    information in spoken language comprehension. *Science*, *268*(5217), 1632–1634.
577    https://doi.org/10.1126/science.7777863

578 Tenenbaum, J. B., Kemp, C., Griffiths, T. L., & Goodman, N. D. (2011). How to Grow a Mind: Statistics, Structure, and
579    Abstraction. *Science*, *331*(6022), 1279–1285. https://doi.org/10.1126/science.1192788

580 Tenney, I., Das, D., & Pavlick, E. (2020). BERT rediscovers the classical NLP pipeline. *Association for Computational Linguistics*
581    *(ACL)*, 4593–4601. https://doi.org/10.18653/v1/p19-1452

582 Trueswell, J. C., Tanenhaus, M. K., & Garnsey, S. M. (1994). Semantic Influences On Parsing: Use of Thematic Role
583    Information in Syntactic Ambiguity Resolution. *Journal of Memory and Language*, *33*(3), 285–318.
584    https://doi.org/10.1006/jmla.1994.1014

585 Trueswell, J. C., Tanenhaus, M. K., & Kello, C. (1993). Verb-Specific Constraints in Sentence Processing: Separating Effects of
586    Lexical Preference From Garden-Paths. *Journal of Experimental Psychology: Learning, Memory, and Cognition*, *19*(3),
587    528–553. https://doi.org/10.1037/0278-7393.19.3.528

588 van Schijndel, M., Exley, A., & Schuler, W. (2013). A Model of Language Processing as Hierarchic Sequential Prediction.
589    *Topics in Cognitive Science*, *5*(3), 522–540. https://doi.org/10.1111/tops.12034

590 van Schijndel, M., & Linzen, T. (2018). A neural model of adaptation in reading. *Empirical Methods in Natural Language*
591    *Processing (EMNLP)*, 4704–4710. http://arxiv.org/abs/1808.09930

592 Wang, A., Pruksachatkun, Y., Nangia, N., Singh, A., Michael, J., Hill, F., Levy, O., & Bowman, S. R. (2019). SuperGLUE: A
593    Stickier Benchmark for General-Purpose Language Understanding Systems. *Neural Information Processing Systems*
594    *(NeurIPS)*, 3266–3280. http://arxiv.org/abs/1905.00537

595 Wang, A., Singh, A., Michael, J., Hill, F., Levy, O., & Bowman, S. R. (2019, September 27). Glue: A multi-task benchmark and
596    analysis platform for natural language understanding. *International Conference on Learning Representations (ICLR)*.

597 Wang, S., Zhang, J., Wang, H., Lin, N., & Zong, C. (2020). Fine-grained neural decoding with distributed word
598    representations. *Information Sciences*, *507*, 256–272. https://doi.org/10.1016/j.ins.2019.08.043

599 Warstadt, A., Singh, A., & Bowman, S. R. (2019). Neural Network Acceptability Judgments. *Transactions of the Association*
600    *for Computational Linguistics*, *7*, 625–641. https://doi.org/10.1162/tacl_a_00290

Wehbe, L., Blank, I. A., Shain, C., Futrell, R., Levy, R., Malsburg, T. von der, Smith, N., Gibson, E., & Fedorenko, E. (2020). Incremental language comprehension difficulty predicts activity in the language network but not the multiple demand network. *BioRxiv Preprint*. https://doi.org/10.1101/2020.04.15.043844

Wehbe, L., Vaswani, A., Knight, K., & Mitchell, T. (2014). Aligning context-based statistical models of language with brain activity during reading. *Empirical Methods in Natural Language Processing (EMNLP)*, 233–243. http://www.aclweb.org/anthology/D14-1030

Wilcox, E. G., Gauthier, J., Hu, J., Qian, P., & Levy, R. (2020). On the Predictive Power of Neural Language Models for Human Real-Time Comprehension Behavior. *ArXiv Preprint*. http://arxiv.org/abs/2006.01912

Willems, R. M., Frank, S. L., Nijhof, A. D., Hagoort, P., & Van Den Bosch, A. (2016). Prediction during Natural Language Comprehension. *Cerebral Cortex*, *26*(6), 2506–2516. https://doi.org/10.1093/cercor/bhv075

Williams, A., Nangia, N., & Bowman, S. R. (2018). A broad-coverage challenge corpus for sentence understanding through inference. *North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL HLT)*, *1*, 1112–1122. https://doi.org/10.18653/v1/n18-1101

Wolf, T., Debut, L., Sanh, V., Chaumond, J., Delangue, C., Moi, A., Cistac, P., Rault, T., Louf, R., Funtowicz, M., & Brew, J. (2019). HuggingFace's Transformers: State-of-the-art Natural Language Processing. *ArXiv Preprint*. http://arxiv.org/abs/1910.03771

Yamins, D. L. K., Hong, H., Cadieu, C. F., Solomon, E. A., Seibert, D., & DiCarlo, J. J. (2014). Performance-optimized hierarchical models predict neural responses in higher visual cortex. *Proceedings of the National Academy of Sciences (PNAS)*, *111*(23), 8619–8624. https://doi.org/10.1073/pnas.1403112111

Yang, Z., Dai, Z., Yang, Y., Carbonell, J., Salakhutdinov, R., & Le, Q. V. (2019). XLNet: Generalized Autoregressive Pretraining for Language Understanding. *ArXiv Preprint*. http://arxiv.org/abs/1906.08237

Yi, K., Torralba, A., Wu, J., Kohli, P., Gan, C., & Tenenbaum, J. B. (2018). Neural-symbolic VQA: Disentangling reasoning from vision and language understanding. *Neural Information Processing Systems (NeurIPS)*, *2018-Decem*, 1031–1042. http://nsvqa.csail.mit.edu

Zador, A. (2019). A Critique of Pure Learning: What Artificial Neural Networks can Learn from Animal Brains. *BioRxiv Preprint*. https://doi.org/10.1101/582643

Zellers, R., Bisk, Y., Schwartz, R., & Choi, Y. (2020). SWAG: A large-scale adversarial dataset for grounded commonsense inference. *Empirical Methods in Natural Language Processing (EMNLP)*, 93–104. https://doi.org/10.18653/v1/d18-1009

Zhuang, C., Kubilius, J., Hartmann, M. J., & Yamins, D. L. (2017). Toward Goal-Driven Neural Network Models for the Rodent Whisker-Trigeminal System. *Neural Information Processing Systems (NIPS)*, 2555–2565. http://papers.nips.cc/paper/6849-toward-goal-driven-neural-network-models-for-the-rodent-whisker-trigeminal-system

Methods

1. Neural dataset 1: fMRI (*Pereira2018*). We used the data from Pereira et al.'s (2018) Experiments 2 (n=9) and 3 (n=6) (10 unique participants). (The set of participants is not identical to Pereira et al., 2018: i) one participant (tested at Princeton) was excluded from both experiments here to keep the fMRI scanner the same across participants; and ii) two participants who were excluded from Experiment 2 in Pereira et al., 2018, based on the decoding results in Experiment 1 of that study were included here, to err on the conservative side.) Stimuli for Experiment 2 consisted of 384 sentences (96 text passages, four sentences each), and stimuli for Experiment 3 consisted of 243 sentences (72 text passages, 3 or 4 sentences each). The two sets of materials were constructed independently, and each spanned a broad range of content areas. Sentences were 7-18 words long in Experiment 2, and 5-20 words long in Experiment 3. The sentences were presented on the screen one at a time for 4s (followed by 4s of fixation, with additional 4s of fixation at the end of each passage), and each participant read each sentence three times, across independent scanning sessions (see Pereira et al., 2018 for details of experimental procedure and data acquisition).

Preprocessing and response estimation: Data preprocessing was carried out with SPM5 (using default parameters, unless specified otherwise) and supporting, custom MATLAB scripts. (Note that SPM was only used for preprocessing and basic modeling—aspects that have not changed much in later versions; for several datasets, we have directly compared the outputs of data preprocessed and modeled in SPM5 vs. SPM12, and the outputs were nearly identical.) Preprocessing included motion correction (realignment to the mean image of the first functional run using 2nd-degree b-spline interpolation), normalization (estimated for the mean image using trilinear interpolation), resampling into 2mm isotropic voxels, smoothing with a 4mm FWHM Gaussian filter and high-pass filtering at 200s. A standard mass univariate analysis was performed in SPM5 whereby a general linear model (GLM) estimated the response to each sentence in each run. These effects were modeled with a boxcar function convolved with the canonical Hemodynamic Response Function (HRF). The model also included first-order temporal derivatives of these effects (which were not used in the analyses), as well as nuisance regressors representing entire experimental runs and offline-estimated motion parameters.

Functional localization: Data analyses were performed on fMRI BOLD signals extracted from the bilateral fronto-temporal language network. This network was defined functionally in each participant using a well-validated language localizer task (Fedorenko et al., 2010), where participants read sentences vs. lists of nonwords. This contrast targets brain areas that support 'high-level' linguistic processing, past the perceptual (auditory/visual) analysis. Brain regions that this localizer identifies are robust to modality of presentation (e.g., Fedorenko et al., 2010; Scott et al., 2017), as well as materials and task (Diachek et al., 2020). Further, these regions have been shown to exhibit strong sensitivity to both lexico-semantic processing (understanding individual word meanings) and combinatorial, syntactic/semantic processing (putting words together into phrases and sentences) (Bautista & Wilson, 2016; I. Blank et al., 2016; I. A. Blank & Fedorenko, 2020; Fedorenko et al., 2010, 2012, 2016, 2020). Following prior work, we used group-constrained, participant-specific functional localization (Fedorenko et al., 2010). Namely, individual activation maps for the target contrast (here, sentences>nonwords) were combined with "constraints" in the form of spatial 'masks'—corresponding to data-driven, large areas within which most participants in a large, independent sample show activation for the same contrast. The masks (available from https://evlab.mit.edu/funcloc/ and used in many prior studies e.g., Jouravlev et al., 2019; Diachek et al., 2020; Shain et al., 2020) included six regions in each hemisphere: three in the frontal cortex (two in the inferior frontal gyrus, including its orbital portion: IFGorb, IFG; and one in the middle frontal gryus: MFG), two in the anterior and posterior temporal cortex (AntTemp and PostTemp), and one in the angular gyrus (AngG). Within each mask, we selected 10% of most localizer-responsive voxels (voxels with the highest *t*-value for the localizer contrast) following the standard approach in prior work. This approach allows to pool data from the same functional regions across participants even when these regions do not align well spatially. Functional localization has been shown to be more sensitive and to have higher functional resolution (Nieto-Castanon & Fedorenko, 2012) than the traditional group-averaging approach (Holmes & Friston, 1998), which assumes voxel-wise correspondence across participants. This is to be expected given the well-established inter-individual differences in the mapping of function to anatomy, especially pronounced in the association cortex (e.g., Frost & Goebel, 2012; Tahmasebi et al., 2012; Vazquez-Rodriguez et al., 2019).

We constructed a stimulus-response matrix for each of the two experiments by i) averaging the BOLD responses to each sentence in each experiment across the three repetitions, resulting in 1 data point per sentence per language-responsive voxel of each participant, selected as described above (13,553 voxels total across the 10 participants; 1,355 average, ±6 std.

dev.), and ii) concatenating all sentences (384 in Experiment 2 and 243 in Experiment 3), yielding a 384x12,195 matrix for
Experiment 2, and a 243x8,121 matrix for Experiment 3.

To examine differences in neural predictivity between the language network and other parts of the brain, we additionally
extracted fMRI BOLD signals from two other networks: the multiple demand (MD) network (Duncan, 2010; Fedorenko et al.,
2013) and the default mode network (DMN) (Buckner et al., 2008; Buckner & DiNicola, 2019). These networks were also
defined functionally using well-validated localizer contrasts (Fedorenko et al., 2013; Mineroff et al., 2018) using a similar
procedure as the one used for defining the language network: combining a set of 'masks' with individual activation maps,
and selecting top 10% of most localizer-responsive voxels within each mask. Both networks were defined using a spatial
working memory task (Fedorenko et al., 2011, 2013). For the MD network, we used the hard>easy contrast, and for the
DMN network, we used the fixation>hard contrast. As for the language network, the MD and DMN masks were derived
from large sets of participants for those contrasts, and are also available at https://evlab.mit.edu/funcloc/. The MD network
and the DMN included 29,936 (2,994±230) and 10,978 (1,098±7) voxels, respectively.

2. Neural dataset 2: ECoG (*Fedorenko2016*). We used the data from Fedorenko et al.'s (2016) study (n=5). (The set of
participants includes one participant, S2, who was excluded from the main analyses in Fedorenko et al., 2016 due to a small
number of electrodes of interest; because we here used only language-responsiveness as the criterion for electrode
selection, this participant had enough electrodes to be included.) Stimuli consisted of 80 hand-constructed 8-word long
semantically and syntactically diverse sentences and 80 lists of nonwords (as well as some other stimuli not used in the
current study). For the critical analyses, we selected a set of 52 sentences that were presented to all participants. The
materials were presented visually one word at a time (for 450 or 700 ms), and participants performed a memory probe task
after each stimulus (see Fedorenko et al., 2016 for details of the experimental procedure and data acquisition).

Preprocessing and response estimation: We here provide only a brief summary, highlighting points of deviation from
Fedorenko et al. (2016). The total numbers of implanted electrodes were 120, 128, 112, 134, and 98 for the five
participants, respectively. Signals were digitized at 1200 Hz. Similar to Fedorenko et al. (2016), i) the recordings were high-
pass filtered with a cut off frequency of 0.5 Hz; ii) reference, ground, and electrodes with high noise levels were removed,
leaving 117, 118, 92, 130, and 88 electrodes (for these analyses, we were more permissive with respect to noise levels
compared to Fedorenko et al., 2016, to include as many electrodes in the analyses as possible; hence the numbers of
analyzed electrodes are higher here than in the original study for 4 of the 5 participants); iii) spatially distributed noise
common to all electrodes was removed using a common average reference spatial filter between electrodes with line noise
smaller than a predefined threshold (electrodes connected to the same amplifier); and iv) a set of notch filters were used to
remove the 60 Hz line noise and its harmonics. To extract the high gamma band activity—which has been shown to
correspond to spiking neural activity in the vicinity of the electrodes (Buzsáki et al., 2012)—we used a gaussian filter bank
with centers at 73, 79.5, 87.8, 96.9, 107, 118.1, 130.4, and 144 Hz, and standard deviations of 4.68, 4.92, 5.17, 5.43, 5.7,
5.99, 6.3, and 6.62 Hz, respectively. This approach differs from Fedorenko et al. (2016), where an IIR band-pass filter was
used to select frequencies in the range of 70-170 Hz, and is likely more sensitive (Dichter et al. 2018). Finally, as in
Fedorenko et al. (2016), the Hilbert transform was used to extract the analytic signal (Lawrence Marple, 1999) (except here,
the average of the Hilbert signal across the eight filters was used as high-gamma signal), z-scored for each electrode with
respect to the activity throughout the experiment, and the signal envelopes were downsampled to 300 Hz for further
analysis (we did not additionally low-pass filter at 100 Hz, as in Fedorenko et al., 2016).

Functional localization: Mirroring the fMRI approach, where we focused on language-responsive voxels, data analyses were
performed on signals extracted from language-responsive electrodes. These electrodes were defined in each participant
using the same localizer contrast as in the fMRI datasets. In particular, we examined electrodes in which the envelope of the
high gamma signal was significantly higher (at p<.01) for trials of the sentence condition than the nonword-list condition
(for details, see Fedorenko et al., 2016).

We constructed a stimulus-response matrix by i) averaging the *z*-scored high-gamma signal over the full presentation
window of each word in each sentence, resulting in 8 data points per sentence per language-responsive electrode (97

electrodes total across the 5 participants; 47, 8, 9, 15, and 18 for participants S1 through S5, respectively), and ii)
concatenating all words in all sentences (416 words across the 52 sentences), yielding a 416x97 matrix.

To examine differences in neural predictivity between language-responsive and other electrodes, we additionally extracted
high gamma signals from a set of 'stimulus-responsive' electrodes. Stimulus-responsive electrodes were defined as
electrodes in which the envelope of the high gamma signal for the sentence condition was significantly different (at p<0.05
by a paired-samples *t*-test) from the activity during the inter-trial fixation interval preceding the trial. This selection
procedure resulted in 67, 35, 20, 29, and 26 electrodes. As expected, this set of electrodes included many of the language-
responsive electrodes; for the analysis in SI-4, we exclude the language-responsive electrodes leaving 105 stimulus- (but not
language-) responsive electrodes.

3. Neural dataset 3: fMRI (*Blank2014*). We used the data from Blank et al. (2014) (n=5). (The set of participants includes 5 of
the 10 participants in Blank et al., 2014, because we wanted each participant to have been exposed to the same materials
and as many stories as possible; the 5 participants included here all heard eight stories.) Stimuli consisted of stories from
the publicly available Natural Stories Corpus (Futrell et al., 2018). These stories, adapted from existing texts (fairy tales and
short stories) were designed to be "deceptively naturalistic": they contained an over-representation of rare words and
syntactic constructions embedded in otherwise natural linguistic context. The stories were presented auditorily (each was
~5 min in duration), and following each story, participants answered 6 comprehension questions (see Blank et al., 2014 for
details of the experimental procedure, data acquisition, and preprocessing).

Functional localization: As in the Pereira2018 dataset, data analyses were performed on fMRI BOLD signals extracted from
the language network. From each language-responsive voxel of each participant, the BOLD time-series for each story was
extracted. Across the eight stories, the BOLD time-series included 1,317 time-points (TRs, time of repetition; TR=2s and
corresponds to the time it takes to acquire the full set of slices through the brain). To align the neuroimaging data with the
story text, we first split the text into consecutive 2-second intervals (corresponding to the fMRI TRs) based on the auditory
recording; if a word straddled boundaries of intervals, it was assigned to the 2s interval in which that spoken word ended.
Each of the resulting intervals thus included a story "fragment", which could be a full short sentence, part of a longer
sentence, or a transition between the end of one sentence and the beginning of another. Due to the temporal resolution of
the HRF, whose peak's latency is 4-6 seconds, we assumed that each time-point in the BOLD signal represented activity
elicited by the text fragment that occurred 4s (i.e., 2 TRs) earlier.

We constructed a stimulus-response matrix by i) averaging the BOLD signals corresponding to each TR in each story across
the voxels within each ROI of each participant (averaging across the voxels within ROIs was done to increase the signal-to-
noise ratio), resulting in 1 data point per TR per language-responsive ROI of each participant (60 ROIs total across the 5
participants), and ii) concatenating all story fragments (1,317 'stimuli'), yielding a 1,317x60 matrix.
762

4. Behavioral dataset: Self-paced reading (*Futrell2018*). We used the data from Futrell et al. (2018) (n=179). (The set of
participants excludes 1 participant for whom data exclusions—see below—left only 6 data points or fewer.) Stimuli
consisted of ten stories from the Natural Stories Corpus (same materials as those used in *Blank2014*, plus two additional
stories), and any given participant read between 5 and all 10 stories. The stories were presented online (on Amazon's
Mechanical Turk platform) visually in a dashed moving window display—a standard approach in behavioral psycholinguistic
research (Just et al., 1982). In this approach, participants press a button to reveal each consecutive word of the sentence or
story; as they press the button again, the word they just saw gets converted to dashes again, and the next word is
uncovered. The time between button presses provides an estimate of overall language comprehension difficulty, and has
been shown to be robustly sensitive to both lexical and syntactic features of the stimuli (Grodner & Gibson, 2005; Smith &
Levy, 2013, inter alia) (see Futrell et al., 2018 for details of the experimental procedure and data acquisition.) We followed
data exclusion criteria in Futrell et al. (2018): for any given participant, we only included data for stories where they
answered 5 or all 6 comprehension questions correctly, and we excluded reading times (RTs) that were shorter than 100 ms
or longer than 3000 ms.
776

We constructed a stimulus-response matrix by i) obtaining the RTs for each word in each story for each participant (848,762
RTs total across the 179 participants; 338 average, ±173 std. dev.), and ii) concatenating all words in all sentences (10,256
words across 485 sentences), yielding a 10,256x179 matrix.

5. Computational models. We tested 43 language models that were selected to sample a broad range of computational
designs across three major types of architecture: embeddings, recurrent architectures, and attention-based 'transformer'
architectures. Here we provide a brief overview (see Table SI-11 for a summary of key features varying across the models).
GloVe (Pennington et al., 2014) is a word embedding model where embeddings are positioned based on co-occurrence in
the Common Crawl corpus; **ETM** (Dieng et al., 2019, 20ng dataset) combines word embeddings with an embedding of each
word's assigned topic; and **word2vec** (Mikolov et al., 2013)—abbreviated as w2v—provides embeddings which are trained
to guess a word based on its context. **lm_1b** (Jozefowicz et al., 2016) is a 2-layer long short-term memory (LSTM) model
trained to predict the next word in the One Billion Word Benchmark (Chelba et al., 2014); and the **skip-thoughts** model
(Kiros et al., 2015) is trained to reconstruct surrounding sentences in a passage. For all 38 transformer models (pretrained
models from the HuggingFace library (Wolf et al., 2019)), we only evaluate the encoder and not the decoder; the encoders
process long contexts (100s of words) with a deep neural network stack of multiple attention heads that operate in a feed-
forward manner (except the Transformer-XL-wt103 and the two XLNet models, which use recurrent processing), and differ
mostly in the choice of directionality, network architecture, and training corpora (Table SI-11). We highlight key features of
different classes of transformer models (BERT, RoBERTa, XLM, XLM-RoBERTa, Transformer-XL-wt103, XLNet, CTRL, T5,
AlBERT, and GPT) in the order in which they appear in the bar-plots (e.g., Fig. 2a), except for the three 'distilled' models
(Sanh et al., 2019), which we mention in the end. **BERT** transformers (Devlin et al., 2018) (n=4; bert-base-uncased, bert-
base-multilingual-cased, bert-large-uncased, bert-large-uncased-whole-word-masking) are optimized to train bidirectional
representations taking into account context both to the left and right of a masked token. **RoBERTa** transformers (Liu et al.,
2019) (n=2; roberta-base, roberta-large) as a variation of BERT improve training hyper-parameters such as masking tokens
dynamically instead of always masking the same token. **XLM** models (Lample & Conneau, 2019) (n=7; xlm-mlm-enfr-1024,
xlm-clm-enfr-1024, xlm-mlm-xnli15-1024, xlm-mlm-100-1280 , xlm-mlm-en2048) learn cross-lingual models by predicting
the next ("clm") or a masked ("mlm") token in a different language. **XLM-RoBERTa** (Conneau et al., 2019) (n=2; xlm-roberta-
base, xlm-roberta-large) combines RoBERTa masking with cross-lingual training in XLM. **Transformer-XL-wt103** (Dai et al.,
2020) adds a recurrence mechanism to GPT (see below) and trains on the smaller WikiText-103 corpus. **XLNet** transformers
(Yang et al., 2019) (n=2; xlnet-base-cased, xlnet-large-cased) permute tokens in a sentence to predict the next token. **CTRL**
(Keskar et al., 2019) adds control codes to GPT (see below) which influence text generation in a specific style. **T5**
transformers (Raffel et al., 2019) (n=5; t5-small, t5-base, t5-large, t5-3b, t5-11b) train the same model across a range of
tasks including the prediction of multiple corrupted tokens, GLUE (A. Wang, Singh, et al., 2019), and SuperGLUE (A. Wang,
Pruksachatkun, et al., 2019) in a text-to-text manner where the task is provided as a text prefix. **AlBERT** transformers (Lan et
al., 2019) (n=8; albert-base-v1, albert-large-v1, albert-xlarge-v1, albert-xxlarge-v1, albert-base-v2, albert-large-v2, albert-
xlarge-v2, albert-xxlarge-v2) use parameter-sharing and model inter-sentence coherence. **GPT** transformers (n=5) are
trained to predict the next token in a large dataset emphasizing document quality (openaigpt (Radford et al., 2018) on the
Book Corpus dataset, gpt2, gpt2-medium, gpt2-large, and gpt2-xl (Radford et al., 2019) on WebText). Finally, **distilled**
versions of models (Sanh et al., 2019) (n=3; distilbert-base-uncased, distilgpt2, distilroberta-base) train compressed models
on a larger teacher network.

To retrieve model representations, we treated each model as an experimental participant (Figure 1) and ran the same
experiment on it that was run on humans. Specifically, sentences were fed in sequentially into the model (for Pereira2018,
Blank2014, and Futrell2018, sentences were grouped by passage / story to mimic the procedure with human participants).
For embedding and recurrent models, sentences were fed in word-by-word; for transformers, the context before (but not
after) each word was also fed into the models due to their lack of memory; the length of the context was determined by the
models' architectures. For recurrent models, the memory was reset after each paragraph (*Pereira2018*), each sentence
(*Fedorenko2016*), or each story (*Blank2014* and *Futrell2018*).

After the processing of each word, we retrieved ("recorded") model representations at every computational block (e.g., one
LSTM cell or one Transformer encoder block). (Word-by-word processing increases computational cost but is necessary to
avoid bidirectional models, like the BERT transformers, seeing the future.) When comparing against human recordings

spanning more than one word such as a sentence (*Pereira2018*) or story fragment (*Blank2014*), we aggregated model
representations: for the embedding models, we used the mean of the word representations; for recurrent and transformer
models, we used the representation of the last word since these models already aggregate representations of the preceding
context, up to a maximum context length of 512 tokens.
832

6. Comparison of models to brain measurements. We treated the model representation at each layer separately and
tested how well it could predict human recordings (for *Pereira2018*, we treated the two experiments separately, but
averaged the results across experiments for all plots except Fig. 2c). To generate predictions, we used 80% of the stimuli
(sentences in *Pereira2018*, words in *Fedorenko2016* and *Futrell2018*, and story fragments in *Blank2014*; Fig. 1) to fit a linear
regression from the corresponding 80% of model representations to the corresponding 80% of human recordings. We
applied the regression on model representations of the held-out 20% of stimuli to generate model predictions, which we
then compared against the held-out 20% of human recordings with a Pearson correlation. This process was repeated five
times, leaving out different 20% of stimuli each time, and we computed the per-voxel/electrode/ROI mean predictivity
across those five splits. We aggregated these per-voxel/electrode/ROI scores by taking the median of scores for each
participant's voxels/electrodes/ROIs and then computing the median and median absolute deviation (m.a.d.) across
participants (over per-participant scores). Finally, this score was divided by the estimated ceiling value (see <u>Estimation of</u>
<u>ceiling</u> below) to yield a final score in the range of $[0, 1]$. We report the results for the best-performing layer for each model
(SI-12).

7. Estimation of ceiling. Due to intrinsic noise in biological measurements, we estimated a ceiling value to reflect how well
the best possible model of an average human could perform. To do so, we first subsampled—for each dataset separately—
the data with n recorded participants into all possible combinations of s participants for all $s \in [2, n]$ (e.g. {2, 3, 4, 5} for
Fedorenko2016 with n=5 participants). For each subsample s, we then designated a random participant as the target that
we attempt to predict from the remaining $s - 1$ participants (e.g., predict 1 subject from 1 (other) subject, 1 from 2
subjects, …, 1 from 4, to obtain a mean score for each voxel/electrode/ROI in that subsample. To extrapolate to infinitely
many humans and thus to obtain the highest possible (most conservative) estimate, we fit the equation $v = v_0 \times \Big(1 -$
$e^{-\frac{x}{\tau_0}} \Big)$ where x is each subsample's number of participants, v is each subsample's correlation score and v_0 and τ_0 are the
fitted parameters for asymptote and slope respectively. This fitting was performed for each voxel/electrode/ROI
independently with 100 bootstraps each to estimate the variance where each bootstrap draws x and v with replacement.
The final ceiling value was the median of the per-voxel/electrode/ROI ceilings v_0.
For *Fedorenko2016*, a ceiling was estimated for each electrode in each participant, so each electrode's raw value was
divided by its own ceiling value. Similarly, for *Blank2014*, a ceiling was estimated for each ROI in each participant, so each
ROI's raw value was divided by its own ceiling value. For *Pereira2018*, we treated the two experiments separately, focusing
on the 5 participants that completed both experiments to obtain full overlap in the materials for each participant, and used
10 random sub-samples to keep the computational cost manageable. A ceiling was estimated for all voxels in the 5
participants who participated in both experiments. Each voxel's raw predictivity value was divided by the average ceiling
estimate (across all the voxels for which it was estimated). For *Futrell2018*, given the large number of participants and
because most participants only had measurements for a subset of the stimuli, we did not hold out one participant but
rather tested how well the mean RTs for one half of the participants predicted the RTs for the other half of participants. We
further took 5 random subsamples at every 5 participants, starting from 1, and built 3 random split-halves, again to keep
computational cost manageable. A ceiling was estimated for each participant, and each participant's raw values were
divided by this ceiling. (Note that this approach is even more conservative than the leave-one-out approach, because split-
half correlations tend to be higher than one-vs.-rest, due to a reduction in noise when averaging (for each half).)
870

871   **8. Language Modeling.** To assess the models' performance on the normative next-word-prediction task, we used a dataset
872   of 720 Wikipedia articles, WikiText-2 (Merity et al., 2016), with 2M training, 218k validation, and 246k test tokens (words
873   and word-parts). These tokens were processed by model-specific tokenization with a maximum vocabulary size of 250k,
874   selected based on the tokens' frequency in the model's original training dataset, and split up into blocks of 32 tokens each
875   (both the vocabulary size and the length of blocks were constrained by computational cost limitations). We sequentially

fed the tokens into models as explained in <u>Computational Models</u> and captured representations at each step from each model's final layer. To predict the next word, we fit a linear decoder from those representations to the next token over words in the vocabulary (n=50k), on the training tokens. This decoder is trained with a cross-entropy-loss $L = -\sum_c^C t_c^i \log\left(\frac{e^{s_c^i}}{\sum_d^C e^{s_d^i}}\right)$ where t_c^i is the true label for class c and sample i, and s_c^i is the predicted probability of that class; the linear weights are updated with AdamW and a learning rate of 5e-5 in batches of 4 blocks until convergence as defined on the validation set. Importantly, note that we only trained weights of a readout decoder, *not* the weights of models themselves, in order to maintain the same model representations that we used in model-to-brain and model-to-behavior comparisons. The final language modeling score is reported for each model as the perplexity, i.e. the exponent of the cross-entropy loss, on the held-out test set.

Acknowledgments: We would like to thank Roger Levy, Steve Piantadosi, Cory Shain, and Noga Zaslavsky for comments on the manuscript, Tiago Marques for comments on ceiling estimates and feature analysis, Jon Gauthier for comments on language modeling, Bruce Fischl and Ruopeng Wang for adding a Freeview functionality. MS was supported by the Massachusetts Institute of Technology Shoemaker Fellowship and the SRC Semiconductor Research Corporation. GT was supported by the MIT Media Lab Consortia. CK was funded by the Massachusetts Institute of Technology Presidential Graduate Fellowship. EH was supported by the Friends of the McGovern Institute Fellowship. NK and JT were supported by the Center for Brains, Minds, and Machines (CBMM), funded by NSF STC CCF-1231216. EF was supported by NIH awards R01-DC016607 and R01-DC016950, and by funds from the Brain and Cognitive Sciences Department and the McGovern Institute for Brain Research at MIT.

 # Supplement

Figure S1: **Ceiling estimates for neural and behavioral datasets.** Due to intrinsic noise in biological measurements, we
estimated a ceiling value to reflect how well the best possible model of an average human could perform, based on sub-
samples of the total set of participants (see Methods-7). For each sub-sample, $s - 1$ participants are used to predict a held-
out participant (except in *Futrell2018*, where this is done on split-halves, as described in the text). Each dot represents a
correlation between the average of the $s - 1$ participants and the left-out participant for a random sub-sample of the
number of participants s indicated on the x-axis. We then bootstrapped 100 random combinations of those dots to
extrapolate (gray lines) the highest possible ceiling if we had an infinite number of participants at our disposal. The
parameters of these bootstraps are then aggregated by taking the median to compute an overall estimated ceiling (dashed
gray line with 95% CI in error-bars). We use this estimated ceiling to normalize model scores and here also report the
number of participants at which the estimated ceiling would be met (which show that for *Pereira2018* and *Futrell2018,* the
number of participants we have is at and close to the asymptote value, respectively).

Figure S2: **Scores generalize across metrics.** Model scores on each dataset generalize across different choices of a similarity
metric; here we plot the predictivity metric used in the manuscript on the x-axis against a model-to-brain similarity metric
based on representational dissimilarity matrices (RDMs) between models and neural representations on the y-axis. Like in
the predictivity metric, stimuli along with corresponding model activations and brain recordings were split 5-fold but we
then only compared the respective test splits given that the RDM metric does not employ fitting. Specifically, we followed
(Kriegeskorte, 2008) and computed the RDM for each model's activations, and a separate RDM for each brain recording
dataset, based on 1 minus the Pearson correlation coefficient between pairs of stimuli; then, we measured model-brain
similarity via Spearman correlation across the two RDMs' upper triangles. The RDM score for one model on one human
dataset is then the mean over splits. We ran each model and compared resulting scores with the primarily used scores from
the predictivity metric. Correlations for models' scores between the predictivity and the RDM metrics are: Pereira2018
r=.57, p<0.0001; Fedorenko2016 r=.40, p<.01; Blank2014 r=.38, p<.05.

Figure S3: **Brain surface visualization of model predictivity scores.** Plots show surface projections of volumetric individual language-responsive functional ROIs in the left and right hemispheres (LH and RH) for five representative participants from *Pereira2018.* In each voxel of each fROI, we show a normalized predictivity value for two models that differ substantially in their ability to predict human data: GloVe (first two columns) and GPT2-xl (second two columns; for GPT2-xl, we show predictivity values from the overall best-performing layer, in line with how we report the results in the main text). (Note that the voxel locations are identical between GloVe and GPT2-xl, and are determined by an independent functional language localizer as described in the text; we here illustrate the differences in predictivity values, along with showing sample fROIs used in our analyses). Predictivity values were ceiling-normalized for each participant and each of 12 ROIs separately (a slight deviation from the approach in the main analysis, which was designed to control for between-region differences in reliability). The data were analyzed in the volume space and co-registered using SPM12 to Freesurfer's standard brain CVS35 (combined volumetric and surface-based (CVS)) in the MNI152 space using nearest neighbor interpolation and no smoothing. The ceiled predictivity maps for the language localizer contrast (10% of most language-responsive voxels in each 'mask'; Methods-1) were projected onto the cortical surface using mri_vol2surf in Freesurfer v6.0.0 with a projection fraction of 1. The surface projections were visualized on an inflated brain in the MNI152 space using the developer version of Freeview (assembly March 10th, 2020). The bar plots in the rightmost column show the normalized predictivity values per ROI (median across voxels) in the language network for GPT2-xl. Error bars denote m.a.d. across voxels. The distribution of predictivity values across the language-responsive voxels, and the similar predictivity magnitudes across the ROIs in the bar graphs, both suggest that the results (between-model differences in neural scores) are not driven by one particular region of the language network, but are similar across regions, and between the LH and RH components of the network (see also SI-4).

SI-4 – Language specificity

In the analyses reported in the manuscript, we focused on the language-responsive regions / electrodes. Here, for two
datasets, we investigated the model-brain relationship outside the language network in order to assess the spatial
specificity of our results, i.e., to test whether they obtain only, or more strongly, in the language network compared to
other parts of the brain. For both datasets, we report analyses based on *raw predictivity values*, without normalizing by the
estimated noise ceiling because the brain regions of the language network differ from other parts of the brain in how
strongly their activity is tied to stimulus properties during comprehension (e.g., I. A. Blank & Fedorenko, 2017, 2020;
Diachek et al., 2020; Shain et al., 2020; Wehbe et al., 2020). This variability is important to take into account when
comparing between functionally different brain regions/electrodes because we are interested in how well the models
explain linguistic-stimulus-related neural activity. When we normalize the neural responses of a non-language-responsive
region/electrode using a language comprehension task, we're effectively isolating whatever little *stimulus-related activity*
this region/electrode may exhibit, putting them on ~equal or similar footing with the language-responsive
regions/electrodes. (For completeness and ease of comparison with the main analyses, we also report analyses based on
normalized predictivity values.)

Fedorenko2016: The scores obtained from language-responsive electrodes were compared to those obtained from
stimulus-responsive electrodes, excluding the language-responsive ones (see Methods-2), for all 43 models. The number of
language-responsive electrodes across five participants was 97, and the number of stimulus-, but not language-, responsive
electrodes across the participants was comparable (n=105). The analysis was identical to the main analysis (see Methods),
besides omitting the ceiling normalization for the raw predictivity analyses. As described in Methods, normalization was
performed for each electrode in each participant separately.
For raw predictivity, neural responses in the language-responsive electrodes were predicted 49.21% better on average
across models than the non-language-responsive electrodes (independent-samples two-tailed t-test: t=3.4, p=0.001). (For
normalized predictivity, neural responses in the language-responsive electrodes were predicted 59.26% better on average
across models than the non-language-responsive electrodes (t=2.24, p=0.03).)

Pereira2018: The scores obtained from the language network were compared to those obtained from two control
networks: the multiple demand (MD) network and the default mode network (DMN) (see Methods), for all 43 models. The
number of voxels in the language network across participants was, on average, 1,355 (± 7 SD across participants), and the
average number of voxels in the MD network and the DMN was comparable (MD: 2,994±230); DMN: 1,098±7). The analysis
was identical to the main analysis (see Methods), besides omitting the ceiling normalization for the raw predictivity
analyses. For the normalized predictivity analyses, the network predictivity values were normalized by their respective
network ceiling values.
For raw predictivity, neural responses in the language network ROIs were predicted 16.96% better on average across
models than the MD network ROIs (independent-samples two-tailed t-test: t=2.26, p=0.03) and numerically (14.33%) better
than the DMN ROIs (t=1.78, p=0.08). (For normalized predictivity, neural responses in the language network ROIs were
predicted numerically (6.47%) worse on average than the MD network ROIs (t=-0.92, p=0.36) and also numerically (1.05%)
worse than the DMN ROIs (t=-0.31, p=0.76).)

These results suggest that—when allowing for inter-regional differences in the reliability of language-related responses—
the model-to-brain relationship is stronger in the language-responsive regions/electrodes. However, we leave open the
possibility that language models also explain neural responses outside the boundaries of the language network, perhaps
because these models capture some parts of our general semantic knowledge, which is plausibly stored in a distributed
fashion across the brain. For example, several earlier studies used simple embedding models to decode linguistic meaning
from fMRI data (e.g., Wehbe et al., 2014; Huth et al., 2016; Anderson et al., 2017; Pereira et al., 2018) and reported reliable
decoding not only within the language network, but also across other parts of association cortex. Given that we know that
different large-scale cortical networks differ functionally in important ways (e.g., see Fedorenko & Blank, 2020, for a recent
discussion of the language vs. MD networks), it will be important to investigate in future work the precise mapping between
the language models' representations and neural responses in these different functional networks.

SI-5 – Model performance on diverse language tasks vs. model-to-brain fit

To test whether the next-word prediction task is special in predicting model-to-brain fit, we used the *Pereira2018* dataset to examine the relationship between the models' performance on diverse language processing tasks from the General Language Understanding Evaluation (GLUE) benchmarks (Wang et al., 2018) and neural predictivity. We used a subset of the high-performing, transformer models (n=30 of the 38 where we could find published commitments of which features to use for GLUE). The GLUE benchmark encompasses nine tasks that can be classified into three categories: single-sentence judgment tasks (n=2), sentence-pair semantic similarity judgment tasks (n=3), and sentence-pair inference tasks (n=4). The two single-sentence tasks are both binary classification tasks: models are asked to determine whether a given sentence is grammatical or ungrammatical (Corpus of Linguistic Acceptability, *CoLA* (Warstadt et al., 2018)), or whether the sentiment of a sentence is positive or negative (Stanford Sentiment Treebank, *SST-2* (Socher et al., 2013)). In the semantic similarity tasks, models are asked to assert or deny the semantic equivalence of question pairs (Quora Question Pairs, *QQP* (Chen et al., 2018)) or sentence pairs (Microsoft Research Paraphrase Corpus, *MRPC* (Dolan & Brockett, 2005)), or to judge the degree of semantic similarity between two sentences on a scale of 1-5 (Semantic Textual Similarity Benchmark, *STS-B* (Cer et al., 2017)). Lastly, the benchmark contains four inference tasks, of which we include three (following Devlin et al., 2018), we exclude the Winograd Natual Language Inference, *WNLI*, task; see (12) in https://gluebenchmark.com/faq). In two of these tasks, models are asked to determine the entailment relationship between sentences in a pair using either tertiary classification: entailment, contradiction, neutral (Multi-Genre Natural Language Inference corpus, *MNLI* (Williams et al., 2018)), or binary classification: entailment or no entailment (Recognizing Textual Entailment, *RTE* (Dagan et al., 2006, Bar Haim et al., 2006, Giampiccolo et al., 2007, Bentivogli et al., 2009)). And in the third inference task, the Question Natural Language Inference, *QNLI,* task (Rajpurkar et al., 2016, White et al., 2017, Demszky et al., 2018), models are presented with question-answer pairs and asked to decide whether or not the answer-sentence contains the answer to the question.

In order to evaluate model performance on GLUE benchmark tasks, each GLUE dataset was first converted into a format that is compatible with transformer model input using functionality from the GLUE data processor provided by Huggingface transformers (https://huggingface.co/transformers/). In particular, each set of materials is represented as a matrix that includes the following dimensions: item (and sentence for multi-sentence materials) ID, ID for each individual word (with reference to the vocabulary used by the transformer models), the label (e.g., grammatical vs. ungrammatical), and the 'attention mask' which specifies which part(s) of the sentences the model should pay attention to (e.g., some 'padding' is commonly used to equalize the lengths of sentences/items to the target length of 128 tokens (again constrained by computational cost), and the attention mask is set to include only the actual words in the materials, and not the padding, and in some models to further constain which parts of the input to attend to—e.g., in GPT2 models, the rightward context is ignored). Next, each GLUE dataset was then fed into each model to obtain a sequence of hidden states at the output of the last layer of the model. Following default settings from Huggingface transformers, from these hidden states, we then extracted the token of interest: for bidirectional models such as BERT, this was the first input token—a special token ([cls]) that is appended to each item and designed for sequence classification tasks, and for unidirectional models such as GPT-2, XLNet or CTRL, this token corresponded to the last attended token (e.g., the last word/word-part in the sentence). In order to ensure a fair comparison between the models and to avoid the skewing of representations by individual task pre-training, dense linear pooling projection layers (specific to some transformer) are disregarded. Finally, we fit a linear decoder from the features of the extracted tokens of interest to the task label(s). For tasks with two or more labels, a cross-entropy loss function is used; for the task that uses a rating scale, the decoder is trained with a mean-square error (MSE) loss function. Similar to the next-word prediction task, the linear weights are updated with the AdamW optimizer and a learning rate of 5e-5 in batches of 8 blocks until convergence as defined on the validation set. Importantly, and also similar to the next-word-prediction task, we only trained weights of a readout decoder, *not* the weights of models themselves, in order to maintain the same model representations that we used in model-to-brain and model-to-behavior comparisons. To account for potential bias in the GLUE datasets, multiple metrics within tasks, as well as different metrics across tasks are reported in the GLUE benchmark. Following standards in the field, we report the final task score as accuracy for *SST-2, QQP, MRPC,*

1037 *MNLI*, *RTE,* and *QNLI*, Matthew's Correlation for *CoLA*, and Pearson correlation for *STS-B*. The results are shown in Fig. S5.
1038 None of the tasks significantly predicted neural scores, suggesting that next-word prediction may be special in its ability to
1039 predict brain-like processing.

1040

1041 Figure S5: **Performance on GLUE tasks does not predict model-to-brain fit**. Performance was evaluated as described in SI-5.
1042 None of the correlations were significant.

1043

1044 Figure S6: **Models' neural predictivity for each dataset is correlated with behavioral predictivity.** In Fig. 4b, we showed
1045 that the models' neural predictivity (averaged across the three neural datasets: *Pereira2018*, *Fedorenko2016*, *Blank2014*)
1046 correlates with behavioral predictivity. Here, we show that this relationship also holds for each neural dataset individually:
1047 *Pereira2018*: p<0.0001, *Fedorenko2016*: p<0.01, *Blank2014*: p<0.01.

1048

Figure S7: **Performance of models with random weights depends on architecture.** a) The relationship between model performance with vs. without training on the wikitext-2 next-word-prediction task. Consistent with model performance with vs. without training on neural and behavioral datasets (Fig. 5), untrained models perform reasonably well. Training improves scores by 80% on average, and most prominently for GPT models, in teal (where the quality of the training data is optimized; see Computational models in Methods). b) Neural and behavioral scores of GPT2-xl, the best-performing model, with vs. without training, and of a random embedding of the same size. Embedding size alone is not sufficient: a random embedding matched in size to GPT2-xl scores worse than untrained GPT2-xl in all four datasets (3 neural, and 1 behavioral). These results suggest that model architecture critically contributes to model-to-brain and model-to-behavior fits.

SI-8 – Effects of model architecture and training on neural and behavioral scores

The 43 language models included in the current study span three major types of architecture: embedding models, recurrent models, and attention-based transformer architectures. However, in addition to this coarse distinction, the individual models vary widely in diverse architectural and training features. A rigorous examination of the effects of different model features on model-to-brain/behavior fit would require careful pairwise comparisons of minimally different models, which is not possible for 'off-the-shelf' models without extremely expensive re-training from scratch under many/all possible combinations of architecture, training diet, optimization objective, and other hyper-parameters. However, we here undertook a preliminary exploratory investigation. In particular, for a subset of model features (Table SI-9), we computed a Pearson correlation between the feature values and the averaged model score across all four datasets (3 neural, and 1 behavioral). We included five architectural features. Three features were continuous: i) number of hidden layers, which varied between 1 and 48 (mean 16.02, std. dev. 11.02); ii) number of features (units across considered layers), which varied between 300 and 78,400 (mean 20,971.26, std. dev. 18,362.91); and the size of the embedding layer, which varied between 128 and 48,000 (mean 872.28, std. dev. 744.33). And the remaining two features were binary: iv) uni- vs. bi-directionality (32/43 models were bi-directional), and v) the presence of recurrence (5/43 models had recurrence). And we included two training-related features: i) training data size (in GB), which varied between 0.2 and 336 (mean 351.06 std. dev. 726.81); and ii) vocabulary size, which varied between 30,000 and 3,000,000 (mean 223,096.95 std. dev. 561,737.36). All training data numbers were taken from the original model papers, and if training data was specified in tokens, a conversion rate of 4 bytes per token was used. We further excluded the multilingual XLM and BERT models when examining the effect of training data size, because those numbers could not be confidently verified. For comparison, we also included performance on the next-word-prediction task that we examined in the main text.

The results are shown in Fig. S8. As expected—given the results reported in the main text for the individual datasets (Fig. 3, 4c)—next-word prediction performance robustly predicts model-to-brain/behavior fit (r = 0.49, p < 0.01). These results suggest that optimizing for predictive representations may be a critical shared feature of biological and artificial neural networks for language. How do architectural and training-related features compare to next-word-prediction task performance in their effect on neural/behavioral predictivity? Two architectural size features are most correlated with model performance: number of hidden layers (r = 0.56, p < 0.001), and number of features (r = 0.68, p << 0.0001). This is expected given that the most recent models with the highest performance on linguistic tasks are also the largest ones that researchers are able to run on modern hardware. The two training-related features—training data size and vocabulary

1088   size—are significantly *negatively* correlated with model performance. To rule out the possibility that the negative effect of
1089   training-related features is driven by models with relatively small training datasets and vocabulary size (e.g., ETM; Table S9)
1090   that have low brain/behavior predictivity, we ran an additional analysis considering only transformer models (n=38): even in
1091   these generally highly predictive models, more training data (r = -0.29, p = 0.11 [not plotted]) or larger vocabulary size (r = -
1092   0.21, p = 0.25 [not plotted]) do not appear to be beneficial, although the negative correlations are non-significant.
1093
Does the collection of model designs investigated in this paper inform the hyperparameters that should be optimized for in
any new model to achieve high predictivity? To provide a preliminary answer to this question, we performed an exploratory
analysis in the form of stepwise forward model selection and examined (a) the most parsimonious model that explains the
data, and (b) how much variance the selected features explain cumulatively (Fig. S8b). High overall explained variance
indicates that the combination of features selected by the model is predictive of model performance, whereas low overall
explained variance indicates that crucial predictive hyperparameters are still being neglected. In the forward regression
analysis, we add predictors based on the highest R^2-adjusted value of the new model, as long as variance increases by
adding a new factor. This analysis revealed that adding training dataset size and recurrence does not lead to variance
increase. Significance markers indicate the p-value for significance of adding each term, and for each regression step we
plot the added explained variance (in R^2-adjusted) of the variable chosen by the model. The overall cumulative R^2-adjusted
value of the selected model is 0.822.
1105

Figure S8: **Effects of model architecture vs. training on neural and behavioral scores. a)** We compared the effects on neural
and behavioral scores (the averaged model score across all four datasets) of three kinds of features: (i) architectural
properties, (ii) training-dependent variables, and, for comparison, iii) performance on the next-word-prediction task
examined in the main text (Fig. 3, 4c). **b**) Alternative combination of predictors with stepwise forward regression model.
New predictors are added based on the highest R^2-adjusted value of the new model, as long as variance increases by adding
a new factor (thus excluding training dataset size and recurrence). Significance markers indicate the p-value for significance
of adding model terms. For each regression step, we plot the added explained variance (in R^2-adjusted) of the variable
chosen by the model. The overall cumulative R^2-adjusted value of the selected model is 0.822. As in a), the preferred
explanatory variable is the number of features. Stepwise forward regression based on significance leads to the same model-
choice. Note that, as above, t5-11b is excluded for regression based on next-word-prediction, and multilingual models are
excluded for regression on training size.

1117

1118
1119

	Model identifier	Num. layers	Num. features	Embedding layer size	Vocabulary size	Training data size	Bidirectionality	Recurrence	Tokenization	Training tasks
1	albert-base-v1	12	9984	128	30000	16	1	0	SentencePiece	
2	albert-base-v2	12	9984	128	30000	16	1	0	SentencePiece	
3	albert-large-v1	24	25600	128	30000	16	1	0	SentencePiece	
4	albert-large-v2	24	25600	128	30000	16	1	0	SentencePiece	Masked Language Modeling Sentence-Order Prediction
5	albert-xlarge-v1	24	51200	128	30000	16	1	0	SentencePiece	
6	albert-xlarge-v2	24	51200	128	30000	16	1	0	SentencePiece	
7	albert-xxlarge-v1	12	53248	128	30000	16	1	0	SentencePiece	
8	albert-xxlarge-v2	12	53248	128	30000	16	1	0	SentencePiece	
9	bert-base-multilingual-cased	12	9984	768	119547	n.a.	1	0	WordPiece	
10	bert-base-uncased	12	9984	768	30522	13	1	0	WordPiece	Masked Language Modeling Next-Sentence Prediction
11	bert-large-uncased	24	25600	1024	30522	13	1	0	WordPiece	
12	bert-large-uncased-whole-word-masking	24	25600	1024	30522	13	1	0	WordPiece	
13	ctrl	48	62720	1280	246534	140	1	0	BPE	Causal Language Modeling
14	distilbert-base-uncased	6	5376	768	30522	13	1	0	WordPiece	Masked Language Modeling Next-Sentence Prediction
15	distilgpt2	6	5376	768	50257	40	0	0	bBPE	Causal Language Modeling
16	distilroberta-base	6	5376	768	50265	161	1	0	bBPE	dynamic Masked Language Modeling
17	ETM	1	300	300	52258	0.2	0	0	RegEx word-level tokenizer	Variational inference topic modeling using embedding representations of both words and topics
18	glove	1	300	300	2200000	3360	0	0	Stanford tokenizer	Learning word vectors such that their dot product equals the logarithm of the words' probability of co-occurrence
19	gpt2	12	9984	768	50257	40	0	0	bBPE	
20	gpt2-large	36	47360	1280	50257	40	0	0	bBPE	Causal Language Modeling
21	gpt2-medium	24	25600	1024	50257	40	0	0	bBPE	
22	gpt2-xl	48	78400	1600	50257	40	0	0	bBPE	
23	lm_1b	2	2048	1024	793471	4	0	1	bBPE	Causal Language Modeling
24	openaigpt	12	9984	768	40478	3	0	0	BPE	Causal Language Modeling
25	roberta-base	12	9984	768	50265	161	1	0	bBPE	dynamic Masked Language Modeling
26	roberta-large	24	25600	1024	50265	161	1	0	bBPE	
27	skip-thoughts	1	4800	4800	930911	3	0	1	NLTK tokenizer	Predicting words in neighboring sentences
28	t5-11b	24	25600	1024	32128	862	1	0	SentencePiece	
29	t5-3b	24	25600	1024	32128	862	1	0	SentencePiece	Text-to-text training on a variety of tasks (i.a., prediction of multiple corrupted tokens, and tasks from the GLUE and SuperGLUE benchmark)
30	t5-base	12	9984	768	32128	862	1	0	SentencePiece	
31	t5-large	24	25600	1024	32128	862	1	0	SentencePiece	
32	t5-small	6	3584	512	32128	862	1	0	SentencePiece	
33	transfo-xl-wt103	18	19456	1024	267735	0.4	1	1	Word-level tokenizer	Causal Language Modeling
34	word2vec	1	300	300	3000000	400	0	0	Word-level tokenizer	Predicting a center word from the surrounding context
35	xlm-clm-enfr-1024	6	7168	1024	64139	n.a.	1	0	BPE	multilingual Causal Language Modeling
36	xlm-mlm-100-1280	16	21760	1280	200000	n.a.	1	0	BPE	multilingual Masked Language Modeling
37	xlm-mlm-en-2048	12	26624	2048	30145	16	1	0	BPE	Masked Language Modeling
38	xlm-mlm-enfr-1024	6	7168	1024	64139	n.a.	1	0	BPE	multilingual Masked Language Modeling
39	xlm-mlm-xnli15-1024	12	13312	1024	95000	n.a.	1	0	BPE	multilingual Masked Language Modeling
40	xlm-roberta-base	12	9984	768	250002	2500	1	0	SentencePiece	multilingual Masked Language Modeling
41	xlm-roberta-large	25	25600	1024	250002	2500	1	0	SentencePiece	
42	xlnet-base-cased	12	9984	768	32000	126	1	1	SentencePiece	Permutation Language Modeling
43	xlnet-large-cased	24	25600	1024	32000	126	1	1	SentencePiece	

1120 Table S9: Overview of model designs.

1121

1122

Figure S10: **Distribution of layer preference (best performing layer) per voxel for GPT2-xl for *Pereira2018***. A per-voxel per-
participant raw predictivity value was obtained in the language network by computing the mean over cross-validation splits
and experiments. For each voxel, the layer with the highest predictivity value was estimated as the "preferred" layer
(argmax over layer scores). As in the main analyses, the voxels in the language network were included. Zero on the x-axis
corresponds to the embedding layer of the model. The upper plot is averaged across all participants in *Pereira2018* (n=10).
The lower panel shows the participant-wise layer preference for five representative participants. Across participants, most
voxels show the highest predictivity value for later layers of GPT2-xl. Within participants, the layer preference across voxels
varies but is often clustered around particular layers. Investigations of how predictivity fluctuates across model layers,
and/or between the language network and other parts of the brain, is left for future work.

1132