Segmenting luminance-defined texture boundaries

Abbreviated Title: Luminance texture boundary segmentation

Christopher DiMattina [1,*] & Curtis L. Baker, Jr.[2]

[1]Computational Perception Laboratory, Department of Psychology,
Florida Gulf Coast University, Fort Myers, FL, USA 33965-6565

[2]McGill Vision Research Unit, Department of Ophthalmology,
McGill University, Montreal, QC, Canada H3G1A4

*Corresponding Author:
        Christopher DiMattina
        Whitaker Hall Room 215
        Florida Gulf Coast University
        10501 FGCU Blvd S.
        Fort Myers, FL 33965-6565

        Email: cdimattina@fgcu.edu
        Web: http://itech.fgcu.edu/faculty/cdimattina/
        Tel: (239)-590-1513

Conflict of Interest: The authors declare no competing financial interests.

Acknowledgements: We thank FGCU undergraduates in the Computational Perception Lab for help with data collection.

ABSTRACT

Segmenting the visual scene into distinct surfaces is one of the most basic tasks of visual

perception, and luminance differences between two adjacent surfaces often provide an important

segmentation cue. However, mean luminance differences between two surfaces may exist without

any sharp change in albedo at their boundary, but rather from differences in the proportion of light

and dark areas within each surface, which we refer to as a *luminance texture boundary*. In this

study, we investigate the performance of human observers segmenting luminance texture

boundaries, with the ultimate goal of understanding the underlying visual computations. We

demonstrate that a simple model involving a single stage of filtering is inadequate to explain

observer performance when segmenting luminance texture boundaries, but performance can be

explained when contrast normalization is added to this one-stage model. Performing additional

experiments in which observers segment luminance texture boundaries while ignoring super-

imposed luminance step boundaries, we demonstrate that the one-stage model cannot explain

segmentation performance in this task. We then present a Filter-Rectify-Filter (FRF) model

positing two cascaded stages of filtering, and demonstrate that it neatly fits our data and explains

our ability to segment luminance texture boundary stimuli in the presence of interfering luminance

step boundaries, as well as in the absence of masking stimuli. We propose that such computations

may be useful for boundary segmentation in natural scenes, where shadows often give rise to

luminance step edges which do not correspond to surface boundaries. Finally, we suggest

directions for future work to further investigate possible neural implementation of the

computations suggested by our psychophysical study.

INTRODUCTION

Detecting boundaries separating distinct surfaces is a crucial first step for segmenting the visual

scene into regions. Since different surfaces generally reflect different proportions of the illuminant,

luminance differences provide a highly informative cue for boundary detection in natural images

(Mely, Kim, McGill, Guo, & Serre, 2016; DiMattina, Fox, & Lewicki, 2012; Martin, Fowlkes, &

Malik, 2004; Marr, 1982). Inspired by physiological findings (Hubel & Wiesel, 1962; Parker &

Hawken, 1988), a commonly assumed computational model of luminance boundary detection is a

Gabor filter of appropriate spatial scale and orientation (or a multi-scale population of filters)

detecting a localized change in albedo near the boundary (**Fig. 1a, b**) (Elder & Sachs, 2004; Marr,

1982). However, in many natural scenes, two distinct surfaces may visibly differ in their mean

regional luminance without giving rise to any sharp change in albedo at their boundary. This

situation is illustrated in **Fig. 1d**, which shows two juxtaposed textures from the Brodatz database

(Brodatz, 1966). Clearly, a large-scale Gabor filter defined on the scale of the whole image as in

Fig. 1a can certainly provide some information about a difference in average luminance between

the two surfaces. However, it is unknown whether other mechanisms may be better suited to detect

regional luminance differences at such boundaries.

In order to address this question, we propose a basic taxonomy of two different ways that

luminance cues can define region boundaries. *Luminance step boundaries* (LSBs) are defined by

uniform regional differences in luminance, as in **Fig. 1a**. *Luminance texture boundaries* (LTBs)

are defined by differing proportions of dark and light micro-patterns on two surfaces (**Fig. 1c**).

Note that for the artificial LTB shown in **Fig. 1c** that there are no textural cues present other than

the proportions of dark and light dots on each side of the boundary. Given that regional luminance

differences can arise from either LSBs or LTBs, it is of interest to understand whether or not similar

mechanisms are employed when segmenting these boundaries, and how LTBs and LSBs interact

when both are present, as is the case when a cast shadow overlaps with a scene region containing

one or more surface boundaries.

A number of studies have investigated detection of "first-order" luminance step boundaries

(Elder & Sachs, 2004; McIlhagga & May, 2012; McIlhagga, 2018; McIlhagga & Mullen, 2018),

as well as detection and segmentation of "second-order" texture boundaries having no luminance

difference but differences in contrast (Dakin & Mareschal, 2000; DiMattina & Baker, 2019),

density (Zavitz & Baker, 2014; Sun & Baker 2016), regularity (Sun, Kingdom & Baker, 2019),

orientation (Wolfson & Landy, 1995), polarity (Motoyoshi & Kingdom, 2007) and phase (Hansen

& Hess, 2006). However, to the best of our knowledge, no psychophysical studies have

systematically investigated the segmentation of first-order luminance texture boundaries, or

considered the underlying computations.

In this study, we characterize segmentation of LTBs (**Experiment 1**) and demonstrate that

simple regional luminance difference computation cannot readily explain the segmentation of

LTBs (**Experiments 2, 3**). We demonstrate the robustness of LTB segmentation to variations in

stimulus contrast, and demonstrate an excellent fit to our psychophysical data with a psychometric

function incorporating divisive contrast normalization (**Experiment 3**). We show that when both

cues are present, observers can ignore masking LSBs having opposite orientations when

segmenting LTBs using proportion of imbalanced patterns as a segmentation cue (**Experiment 4**).

However, the presence of a masking LTB having a congruent orientation with the LTB can in

some cases enhance or impair performance (depending on relative phase), suggesting some degree

of pre-attentive interaction between cues. Similar results are obtained when segmenting LTBs in

the presence of supra-threshold LSB maskers (**Experiment 5**).

We test the ability of a simple model positing a single stage of filtering which fit the data

well in **Experiments 2, 3** to explain the findings in **Experiment 4.** We find that this model fails

to fully explain the results of **Experiment 4**, suggesting that LTBs and LSBs are segmented by

distinct underlying mechanisms. We define and fit a "filter-rectify-filter" (FRF) model positing

two stages of filtering to data from **Experiment 4**, and show that this model successfully accounts

for observer performance in the task. Many previous studies of second-order vision have fit

psychophysical data with FRF models (DiMattina & Baker, 2019; Zavitz & Baker, 2013, 2014),

but here we show that the FRF model can account for the ability of observers to extract first-order

(luminance) information in the presence of masking LSB stimuli. We propose that such

mechanisms may be useful for performing boundary segmentation in natural vision, where

extraneous stimuli like shadows often give rise to LSB stimuli which do not correspond to surface

boundaries.

METHODS

Stimuli

<u>Luminance texture boundaries</u>

Luminance texture boundary (LTB) stimuli were created by placing different proportions of non-

overlapping black and white micro-patterns on opposite halves of a circular disc, with the boundary

separating the two regions oriented left-oblique (-45 degrees w.r.t. vertical) or right-oblique (+45

deg. w.r.t. vertical), as shown in **Fig. 2a**. Our basic psychophysical task, described in greater detail

below, was an orientation-identification task used in several previous studies (Zavitz & Baker,

2013, 2014; DiMattina & Baker, 2019), in which the observer classifies the boundary orientation

(L/R oblique). The proportions of black and white micro-patterns on each side of the LTB was

parameterized in two equivalent ways. The first parameterization specified the proportion π_l^W of

micro-patterns on the lighter (*l*) side of the disc which were white (W). π_l^W varied from 0.5 to 1,

with $\pi_l^B = 1 - \pi_l^W$ and $\pi_d^B = \pi_l^W$, where π_d^B is the proportion of micro-patterns on the darker (*d*)

side of the disc which are black (B). The second parameterization, which was more convenient for

data analysis, was to specify the proportion π_U of unbalanced micro-patterns on each side of the

disc, which was related to π_l^W by $\pi_U = 2(\pi_l^W - 0.5)$. This second parameterization had the

advantage of having $\pi_U = 0$ correspond to no boundary between the two regions.

For the experiments described here, we employed a 256 x 256 pixel stimulus subtending 4

deg. visual angle (dva). 32 non-overlapping micro-patterns were randomly placed on each side of

the boundary, with each micro-pattern being an 8 pixel Gaussian (σ = 2 pixels). Unless otherwise

specified, the micro-pattern maximum amplitude *A* was set to +/- 0.25 (W/B) dimensionless

luminance units with respect to the gray mid-point (0.5) so that they were clearly visible. The

Michealson contrast $c_M = (L_{max} - L_{min})/(L_{max} + L_{min})$ of the LTB stimuli is related to the

maximum micro-pattern amplitude A by $c_M = 2A$. In some experiments, we set $A = +/-0.1$

(roughly 3-4 times contrast threshold) to create more a difficult task due to reduced visibility of

the micro-patterns. Stimuli were designed to be have zero luminance difference across the diagonal

perpendicular to the region boundary (*anti-diagonal*), so that the only available luminance cue was

that across the boundary defining the stimulus. For each stimulus, the envelope phase ϕ was

randomly set to one of two possible values: $\phi = 0$ degrees (lighter side on left), and $\phi = 180$ degrees

(lighter side on right).

<u>Luminance step boundaries</u>

We also characterized performance on our identification task with luminance step boundary (LSB)

stimuli, like that shown in **Fig. 2b**. LSB stimuli were defined by multiplying a step edge by a

cosine-tapered circular disc. The detectability of this edge was varied by manipulating its

Michealson contrast c_M, and the envelope phase was randomized to either 0 or 180 degrees.

Luminance discs were also 256 x 256 pixels and scaled to subtend 4 dva.

Observers

Two populations of observers were utilized in these experiments. The first population consisted of

N = 3 observers who were highly experienced with the segmentation tasks. One of these observers

was author CJD, and the other two experienced observers (KNB, ERM) were undergraduate

members of the Computational Perception Laboratory (CP Lab) who were naïve to the purpose of

the experiments. The second population was comprised of N = 17 naïve, inexperienced observers

recruited from several undergraduate FGCU Psychology classes (EXP-3202, PSB-4002, PSY-

3025, PSY-2012) offered during the 2019-2020 academic year, as well as N = 1 student from the

CP Lab. All observers gave informed consent, and all experimental procedures were approved by

the FGCU IRB (Protocol number 2014-01), in accordance with the Declaration of Helsinki.

Visual Displays

Stimuli were presented in a dark room on a 1920x1080, 120 Hz gamma-corrected (gamma = 1.0)

Display++ LCD Monitor (Cambridge Research Systems LTD®) with mid-point luminance of 100

cd/m^2 operating in Mono++ mode. This monitor was driven by an NVIDA GeForce® GTX-645

graphics card, and experiments were controlled by a Dell Optiplex® 9020 running custom-

authored software written in MATLAB® making use of Psychtoolbox-3 routines (Brainard, 1997).

Observers were situated 133 cm from the monitor using a HeadSpot® chin-rest, so that the

256x256 stimuli subtended approximately 4 deg. of visual angle.

Experimental Protocols

Experiment 1: Segmentation thresholds for LTBs and LSBs

The larger motivation for this series of experiments was to determine whether or not luminance

texture boundaries (LTB) are segmented using the same mechanisms as boundaries defined by

uniform luminance steps (LSB). The first step in this process was to characterize observer

segmentation thresholds for both kinds of boundaries. Our task was a single-interval classification

task, in which a single stimulus is displayed and then the observer classifies it as belong it one of

two categories (L/R oblique).

To study the effects of the number of unbalanced micro-patterns on segmentation

(**Experiment 1a**), luminance texture boundaries with 32 micro-patterns on each side were

presented at 9 evenly spaced values of π_l^W from 0.5 to 1.0 in steps of 0.0625 (equivalently, π_U was

varied from 0 to 1 in steps of 0.125). Observers performed 250 psychophysical trials starting at the

highest level, with the stimulus level being adjusted using a standard 1-up, 2-down staircase

procedure, focusing trials near stimulus levels yielding 70.71% correct responses (Leek, 2001).

Pilot studies with N = 3 experienced observers (CJD, ERM, KNB) showed similar thresholds for

32 and 64 micro-patterns, and somewhat higher thresholds for 16 micro-patterns (**Supplementary**

Fig. S1), justifying the use of 32 micro-patterns as our default micro-pattern density.

Luminance step boundaries (LSBs) were defined by a luminance step oriented either left-

or right-oblique, multiplied by a circular window with cosine tapering (Zavitz & Baker, 2013).

LSBs were defined by their Michaelson contrast c_M with respect to the luminance midpoint. LSBs

were presented at Michaelson contrasts in 11 logarithmic steps from $c_M = 10^{-2.7}$ to $10^{-1.7}$, using the

same staircase procedure (**Experiment 1b**) for 250 trials.

Naïve and inexperienced observers recruited from classes tested in **Experiment 1** and

Experiment 4 first obtained experience with segmenting both kinds of boundaries over two

training sessions prior to the experiment. During each training session, they ran two full threshold

series for segmenting both LTBs (cue was π_U) and LSBs (cue was c_M). Data from their final (4th)

threshold series was used to estimate stimulus levels leading to JND (75% correct) performance.

Experiment 2: LTBs with constant luminance difference

In order to test the hypothesis that the key variable determining LTB segmentation performance is

luminance difference, we generated a series of LTB stimuli having constant luminance difference

arising from a fixed number (N = 8) of unbalanced (opposite color) micro-patterns on opposite

sides of the boundary. By adding an equal number of luminance-balanced patterns (patterns with

same color) to both sides of the boundary (N = 0, 8, 16, 24, 32), one can decrease the proportion

of unbalanced patterns, making the boundary more difficult to segment, while maintaining

constant luminance difference across the boundary. A series of this kind is illustrated in **Fig. 5a**.

<u>Experiment 3: Segmenting LTBs with varying RMS contrasts</u>

In order to test further whether total luminance difference was a strong predictor of LTB

segmentation performance, we repeated Experiment 1 for a single density (32 patterns) while

varying the maximum luminance A of each micro-pattern with respect to the screen mid-point

luminance (0.5). This was accomplished by setting the maximum amplitude of each micro-pattern

to three different levels with respect to the mid-point. W/B micro-pattern amplitudes were set at A

$= +/- 0.1, +/- 0.25, +/- 0.4$ with respect to the luminance mid-point of 0.5 ($c_M = 2A =$

$0.2, 0.5, 0.8$). This had the effect of creating drastically different luminance differences across the

LTB, for the same pattern density. Examples of such stimuli are shown in **Fig. 6a**.

<u>Experiment 4: Segmenting LTBs using proportion unbalanced while ignoring masking LSBs</u>

Of particular interest for the current study is investigating the relationship between the mechanisms

used to segment LTBs and those used to segment LSBs. If the mechanisms are fully distinct, if

one super-imposes an LTB and LSB of possibly different orientations, and instruct the observer to

segment using only the LTB cue, the presence of the masking LSB masking boundary should have

little, if any, effect on performance. Conversely, identical or highly overlapping mechanisms

would lead to profound impairment of performance.

To investigate this question, we ran an experiment (**Experiment 4**) using author CJD, two

naïve experienced observers (EMR, KNB), and N = 6 naïve inexperienced observers. Observers

were instructed to segment an LTB target using π_U as the segmentation cue, where π_U was

presented at JND (75% correct), determined from **Experiment 1a**. For some trials, a masking LSB

(also presented at JND), which observers were instructed to ignore, was added to the LTB. There

were three kinds of trials in this experiment: 200 *neutral* trials where the LTB was presented in

isolation, 200 *congruent* trials with the LTB target and masking LSB having congruent boundary

orientation (both cues left or right-oblique: see **Fig. 2c**), and 200 incongruent trials with the LTB

target and masking LSB having incongruent orientations (one cue left-oblique, the other right-

oblique: see **Fig. 2d**). For the (200) congruent stimuli, for half of trials (100) the two stimuli were

phase-aligned (**Fig. 2c**, *left*), and for the other half (100) they had opposite phases (**Fig. 2c**, *right*).

Eight of the nine observers in **Experiment 4** also participated in a control experiment

(**Experiment 4-control**) complementary to **Experiment 4** in which they were instructed to

segment a LSB (presented at JND) while ignoring a masking LTB. The conditions and stimuli

were the same as in **Experiment 4**, except in **Experiment 4-control** the neutral trials contained

an LSB presented in isolation.

Experiment 5: Masking LTB stimuli with supra-threshold LSBs

In order to investigate the effects of supra-threshold LSB maskers on LTB segmentation, observers

CJD, ERM and KNB performed the LTB segmentation task identical to **Experiment 1a**, but in

the presence of masking LTB stimuli. Masking LTB stimuli were presented at multiples of

segmentation JND (0, 1, 2, 4, 8), with 0 corresponding to no masker. LTB stimuli were presented

at two different maximum micro-pattern amplitudes (A = 0.1, 0.2).

Data Analysis

Psychometric function fitting

Data was fit using a signal-detection theory (SDT) psychometric model (Kingdom & Prins, 2016),

where the proportion correct responses (P_C) for a single-interval classification (1-AFC) task is

given by

$$P_C = \Phi\left(\frac{d'}{2}\right), \tag{1}$$

$$d' = [gx]^\tau, \tag{2}$$

where d' is the separation of the (unit variance) signal and noise distributions, with stimulus

intensity x, with free parameters of gain g and transducer exponent τ. The SDT model was fit to

psychophysical   data   using   MATLAB®   routines   from   the   Palemedes   Toolbox

(http://www.palamedestoolbox.org/), as described in (Kingdom & Prins, 2016). Data was fit both

with and without lapse rates, and nearly identical threshold estimates were observed in both case,

although sometimes fitting without lapse rates under-estimated the psychometric function (PF)

slope. For the case of the model fitted using lapse rates

$$P_C = \frac{\lambda}{2} + (1 - \lambda)\Phi\left(\frac{d'}{2}\right), \tag{3}$$

where λ denotes the lapse probability, which was constrained to lie in the range $[0, 0.1]$.

Psychometric functions fit to luminance differences

Psychometric functions were also fit using one or two quantities computed from images. Given

stimulus levels x used to generate the stimulus, we computed from the resulting image two

quantities: (1) $L(x)$, which is the absolute value of the difference in luminance across the diagonal

corresponding to the target orientation, and (2)) $C(x)$, which is the global RMS stimulus contrast.

We then fit an alternative SDT PF where

$$d' = \frac{[g_1 L(x)]^{\tau_1}}{1 + [g_2 C(x)]^{\tau_2}} \tag{4}$$

permitting us to model any effects of global stimulus contrast $C(x)$ that might co-vary with

luminance differences $L(x)$ as stimulus level x is varied. This model (4) is only appropriate for

training sets where the global stimulus contrast $C(x)$ varies, since otherwise it is over-

parametrized, and in these cases we set $g_2 = 0$.

Image-computable model with one filtering stage

By design of the stimuli used in **Experiments 1-3**, there is no difference in luminance across the

anti-diagonal (the axis orthogonal to the stimulus orientation). Therefore, there is no need to take

this into account when applying the model (4). However, in the masking experiment (**Experiment**

4), in the case where the masking LSB has an incongruent orientation, there will be a luminance

difference across the anti-diagonal, which can potentially influence the decision. To analyze this

data, we apply a slightly different model. In this model, illustrated schematically in **Fig. 4a**, we

assume that each stimulus x gives rise to a decision variable $u(x)$ which serves as input to a

psychometric function, so that the probability of a "right-oblique" behavioral response ($b = R$) is

given by

$$P(b = R) = \Phi\big(u(x)\big), \tag{5}$$

$$u(x) = \big[g_1 L_R(x)\big]^{\tau_1} - \big[g_1 L_L(x)\big]^{\tau_1}, \tag{6}$$

where $L_R(x)$, $L_L(x)$ are the absolute values of the luminance differences across the right- and left-

diagonals. We also extended the model (6) to include divisive computations by global stimulus

contrast $C(x)$, as in (4).

<u>Image-computable model with two filtering stages</u>

Masking data from **Experiment 4** was modeled using a two-stage model, illustrated in **Fig. 9a**.

This model first convolves the image with on-center and off-center Difference-of-Gaussians

(DOG) filters. The output of this first filtering stage is rectified and then passed to a second stage

of filtering which computes a difference in first-stage activity across the left and right oblique

diagonals. The outputs of these second-stage filters are then subtracted to calculate a decision

variable $u(x)$. In our modeling, we fixed the first-stage DOG filter properties so that the Gaussian

defining the filter center is matched to the radius of the dots, while that defining the surround has

twice the radius of the center. This choice is consistent with previous classification image studies

of Gaussian detection in noise (Eckstein, Shimozaki & Abbey, 2002). The only free variable which

we estimate from data is the ratio ρ_{IE} of the amplitudes of the center and surrounds.

Mathematically, if the rectified luminance differences (with nonlinear exponent τ_1) from the left

and right-oblique filters from the ON-center filters is given by $L_L^{ON}(x)$, $L_R^{ON}(x)$, and from the OFF-

center filters $L_L^{OFF}(x)$, $L_R^{OFF}(x)$, our decision variable is

$$u(x) = [g_2 L_R^{ON}(x)]^{\tau_2} + [g_2 L_R^{OFF}(x)]^{\tau_2} - [g_2 L_L^{ON}(x)]^{\tau_2} - [g_2 L_L^{OFF}(x)]^{\tau_2}, \qquad (7)$$

where g_2, τ_2 are gains and nonlinearities for the second-stage filters. The two-stage model only

contains 4 free parameters which we estimate by fitting to data. To make computations tractable,

we pre-filtered the stimuli with the center-surround DOG filters with IE amplitude ratios given by

$\rho_{IE} = 0, 0.05, 0.1, 0.15, 0.2, 0.25, 0.3, 0.35, 0.4$ and then optimized the remaining parameters for each

value of ρ_{IE}.

Bootstrapping psychometric functions

Bootstrapping was employed to determine the 95% confidence intervals for both the psychometric

function thresholds (**Experiment 1**), as well as the proportion of correct responses predicted as a

function of the stimulus level defined as either π_U or absolute luminance difference (**Experiment**

3). For bootstrapping analyses, N = 100 or N = 200 simulated datasets were created as follows:

For each stimulus level with n_i presentations and c_i experimentally observed correct responses

(success probability $p_i = c_i/n_i$), we sampled from a binomial distribution having n_i trials with

success probability p_i to create a simulated number of correct responses for that stimulus level. We

fit our models to these simulated datasets, and obtained distributions of the PF parameters, as well

as the stimulus levels corresponding to JND (75% correct) performance.

RESULTS

<u>Luminance texture boundary stimuli</u>

In order to quantitatively examine the segmentation of luminance texture boundaries (LTBs), we

defined a set of LTB stimuli which allowed us to vary the luminance across a boundary by varying

the proportion of black and white micro-patterns within in each region. The observer's task was to

determine whether the boundary was oriented left-oblique (-45 deg.) or right-oblique (+45 deg.)

with respect to vertical. Our LTB stimuli are illustrated in **Fig. 2a**. When there are equal numbers

of black (B) and white (W) micro-patterns on each side of the boundary, each micro-pattern is

balanced by another of the same color on the other side. In this case, the luminance difference

between regions is zero. When one side has more W patterns, and the opposite side has more B

patterns, a proportion of the patterns on each side are *imbalanced*, giving rise to a difference in

luminance across the diagonal. Therefore, we can modulate the luminance difference and therefore

the boundary salience by changing the proportion of patterns on each side that are unbalanced

(π_U), as illustrated in **Fig 2a**. A value of $\pi_U = 0$ corresponds to no boundary, whereas $\pi_U = 1$

means that all the patterns on each side are the same.

368   Since both W and B micro-patterns have the same amplitude relative to the gray mid-point,

the stimulus RMS contras remains constant as we vary π_U. Furthermore, when generating these

stimuli we made sure that there was no luminance difference across the orientation orthogonal to

the boundary (the *anti-diagonal*). This ensured that there was no segmentation cue available which

may mislead the observer into incorrectly classify the boundary as being in the opposite category.

Experiment 1: Measuring segmentation thresholds

In **Experiment 1a**, we examined the ability of N = 17 observers (16 naïve, 14/16 inexperienced)

to segment LTBs using the proportion of unbalanced micro-patterns (π_U) as a cue. **Fig. 3a** shows

the psychometric functions of two representative observers (KNB, JJB), and a histogram of JND

thresholds (75% correct) for all observers is shown in **Fig. 3b** (top). Nearly identical threshold

estimates were obtained with and without lapse rates (**Supplementary Fig. S2**). The median

observer could perform the task at with a threshold of $\pi_U = 0.31$, and the best observer could

reliably segment at $\pi_U = 0.16$, suggesting a strong sensitivity to the proportion of unbalanced

micro-patterns on the two surfaces.

In order to compare segmentation of LTB stimuli to LSB stimuli, in **Experiment 1b** we

also determined LSB segmentation thresholds for luminance disc stimuli like that shown in **Fig.**

2b in units of Michaelson contrast for the same N = 17 observers tested in **Experiment 1a**. **Fig 3c**

shows PFs from two representative observers (MXD, MCO) and **Fig. 3d** shows a histogram of

thresholds. Across the population of observers (**Supplementary Fig. S3**), we observed a

significant positive rank-order correlation between LTB and LSB thresholds obtained in

Experiments 1a and **1b** (Spearman's $\rho = 0.56$; $p = 0.019$).

Evaluating a simple model

One simple explanation for LTB segmentation performance is that the visual system is performing

a simple luminance difference computation. As the proportion of unbalanced micro-patterns

increases, so does this luminance difference, making the LTB more visible. We implemented an

image-computable model like that shown in **Fig. 4a** comprised of a single filtering-stage in which

a left-oblique filter and right-oblique filter compute luminance differences across their respective

boundaries, and the rectified outputs of these filters are subtracted to determine the probability the

observer makes a "right-oblique" (R) response. We see in **Fig. 4b** that this simple model predicts

observer performance quite well as function of the luminance difference for LTB stimuli.

Likewise, this model predicts performance well for LSB stimuli (**Supplementary Fig. S4**).

Experiment 2: Holding luminance difference constant

In order to directly test whether a simple luminance difference computation like that shown in **Fig.**

4a is adequate to explain LTB segmentation, in **Experiment 2** we constructed a series of LTB

stimuli having an identical number of unbalanced micropatterns on each side, which provide the

segmentation cue, while increasing the number of balanced patterns on each side, which serve as

distractors. Stimuli from this experiment are illustrated in **Fig. 5a**. We see in **Fig. 5b** that for all

three observers tested, performance decreases as the number of distractors increases, with all

observers showing a significant effect of the number of distractors (Pearson's chi-squared test;

CJD: $\chi^2(4) = 25.32$, $p < 0.001$, ERM: $\chi^2(4) = 34.817$, $p < 0.001$, KNB: $\chi^2(4) = 18.56$, $p = 0.001$).

These results argue against the hypothesis that LTB stimuli are segmented using a simple

luminance difference computation, at least in cases like this where the total number of micro-

patterns co-varies with the proportion of unbalanced patterns.

Experiment 3: Varying contrast while segmenting by proportion unbalanced patterns

As suggested by **Experiment 2**, a simple luminance difference computation is not a plausible

candidate for segmenting LTB stimuli. In **Experiment 3**, we adduce additional evidence against

this simplistic model. In this experiment, three observers (CJD, KNB, ERM) segmented LTB

stimuli using the proportion of unbalanced micro-patterns π_U as a cue, as in **Experiment 1a**. This

was performed for three different levels of the stimulus Michaelson contrast ($c_M = 0.2, 0.5, 0.8$).

This had the effect of creating drastically different regional luminance differences for stimuli in

different series having the same proportion of unbalanced micro-patterns π_U (**Fig. 6a**). As we see

in **Fig. 6b**, π_U (left panels) is a much better predictor of observer performance than the absolute

luminance difference (right panels), suggesting that LTB segmentation performance generalizes

quite well over absolute luminance difference.

<u>Extending the one-stage model: Divisive computations</u>

One can account for observer performance in **Experiments 2** and **3** using a single-stage model

like that in **Fig. 4a** by introducing a contrast normalization operation (**Eq. 4**). Pooling data from

all three series in **Experiment 3**, we fit both the standard SDT model (**Eq. 2**) using simple

luminance difference only, as well as the divisive SDT model (**Eq. 4**) incorporating both

luminance difference and RMS contrast. As we see in **Fig. 7**, the fit of the standard additive SDT

model (red lines) is quite poor compared to the divisive SDT model (blue lines). Since the divisive

model has more parameters, we compare the goodness-of-fit using the Bayes Information Criterion

(BIC), which rewards fit while penalizing model complexity (Schwarz, 1978; Bishop, 2006). The

BIC analysis suggests a strong preference (Kaas & Raferty, 1995) for the divisive model for all

observers (**Table 1**). Similar results were obtained using models with lapse rates estimated as well

(**Supplementary Fig. S5**).

	BIC: Additive		BIC: Divisive		BIC$_D$ - BIC$_A$	
	None	*Lapse*	*None*	*Lapse*	*None*	*Lapse*
CKD	-427.510	-430.820	-419.665	-423.020	7.845	7.800
ERM	-448.073	-451.383	-438.469	-441.779	9.605	9.605
KNB	-424.487	-427.797	-411.348	-414.658	13.139	13.139

Table 1: Bayes information Criterion (BIC) for fits of Additive and Divisive SDT

models to data from Experiment 3, with (*Lapse*) and without (*None*) lapse rates.

Finally, we see that the divisive SDT model (4) is able to do a reasonably good job of predicting

observer performance in **Experiment 2** (**Supplementary Fig. S6,** *red symbols*).

Experiment 4: Segmenting LTBs while ignoring LSBs

The results of Experiments 1-3 suggest that a model implementing a luminance difference

computation (**Fig. 4a**) with contrast normalization can potentially explain LTB segmentation

performance. However, one weakness of a single-stage model (**Fig. 4a**) computing simple

luminance differences is that it may be susceptible to interference from masking LSBs having

opposite orientations. Motivated by these considerations, in **Experiment 4** we investigated the

extent to which segmentation of LTB stimuli is influenced by the presence of masking LSB stimuli

which observers are instructed to ignore. The logic of this paradigm is that if LTBs and LSBs are

processed by entirely different mechanisms, then the presence of a task- irrelevant LSB should

have no effect on segmentation using the LTB cue. If one cue cannot be ignored, it suggests that

there may be some overlap or interaction between the mechanisms. This sort of paradigm was used

in a previous study (Saarela & Landy, 2012) to demonstrate that color and texture cues were not

processed independently.

In **Experiment 4**, N = 8 observers segmented LTB stimuli having supra-threshold

micropattern amplitudes ($A = 0.25, c_M = 0.5$) using proportion of unbalanced micro-patterns as a

cue, with π_U set to the observer's 75% performance threshold, as determined in **Experiment 1a**.

For 200 *neutral* trials, the LTB was presented in isolation, for 200 *congruent* trials a masking LSB

was presented with the same orientation (L/R oblique) as the target (**Fig. 2c**), and for 200

incongruent trials the LSB was presented at the opposite orientation (**Fig. 2d**). For half of the

congruent trials, the LTB and LSB were phase aligned (**Fig. 2c, left**), and for the other half they

were opposite-phase (**Fig. 2c, right**).

As we can see from **Fig. 8a**, performance when segmenting high-contrast LTB stimuli

when using π_U as the cue is quite robust to interference from masking LSB stimuli. Statistical

tests (Pearson's Chi-squared) comparing observer performance across all three conditions did not

find any significant effect of condition (*neutral* (**neu**), *congruent* (**con**), *incongruent* (**inc**)) for any

individual observer (**Supplementary Table S1**). Pooling across all observers, we did however

obtain significantly different ($\chi^2(2) = 15.319$, $p < 0.001$) proportions for each condition (**neu**:

0.8217, **con**: 0.8622, **inc**: 0.8189), due to slightly enhanced performance for congruent masking

LSBs, since there was no impairment for incongruent masking LSBs ($\chi^2(1) = 0.047$, $p = 0.828$).

The enhanced performance for congruent masking LSBs was phase-dependent, as seen in **Fig. 8b**.

For the aligned-phase case (**con-0**), we observe significant improvements over neutral in

performance for 4/9 observers (**Supplementary Table S2**). We fail to find any significant

difference in performance between the neutral and opposite-phase (**con-180**) cases. Pooling across

observers, we find significant differences ($\chi^2(1) = 24.383$, $p < 0.001$) between the proportions

correct for the neutral case and the aligned-phase case (**neu:** 0.8217, **con-0:** 0.8944). However,

we fail to find a significant difference ($\chi^2(1) = 0.288$, $p = 0.592$) between the proportions correct

in the neutral case and the opposite-phase case (**con-180:** 0.8300). In at least some observers (3/9

total, 2/8 naive) we see improved performance for phase-aligned compared to opposite-phase

boundaries in the congruent case (**Fig. 8b**, **Supplementary Table S3**), as well as significant effect

($\chi^2(1) = 15.732$, $p < 0.001$) pooling across all observers (**con-0**: 0.8944, **con-180**: 0.8300).

In **Experiment 4**, observers segmenting LTBs using proportion unbalanced patterns as a

cue were relatively unimpaired by the presence of masking LSBs having an incongruent

orientation, at least at when the LSBs were presented at their segmentation thresholds. We ran a

complementary experiment (**Experiment 4 - control**) with 8 of these same observers in which

they were instructed to segment the LSB while ignoring a masking LTB. Here we observe a

profound masking of the LSB target stimulus by an incongruently oriented LTB (**Supplementary**

Fig. S7), and statistical tests (Pearson's Chi-squared) demonstrated significantly different

performance across conditions for all observers (**Supplementary Table S4**). Additional details

are available in the Supplementary Results. Taken as a whole, we see that when LTB and LSBs

are equated for perceptual discriminability in a segmentation task, there is a profound asymmetry

in the effects of maskers from the opposite category (**Fig. 8**, **Supplementary Fig. S7**). This is

highly suggestive that different mechanisms may be involved in segmenting these two kinds of

boundaries. We now consider a possible alternative model for LTB segmentation which may

explain these results.

<u>Evaluating one-stage and two-stage models</u>

Given our findings in Experiment 4 that LTB segmentation is fairly robust to interference from

masking LSB stimuli, we considered the possibility that LTB segmentation may be better

explained by a two-stage model like that shown in **Fig. 9a.** In contrast to the model in **Fig. 4a**, this

model posits two stages of processing. The first stage is comprised of localized center-surround

filters which are convolved with the input image and whose outputs are passed through a rectifying

nonlinearity. The second stage analyzes the outputs of the first-stage outputs, with two large-scale

filters looking for left-oblique and right-oblique boundaries, respectively. These second-stage filter

outputs are rectified and subtracted to determine the probability of a "R" response. Note that since

the center-surround filters in the first stage are poorly driven by constant light levels, this model

can in principle exhibit robustness to interference from LSBs, while still permitting some degree

of influence, depending on the relative E/I ratio of the center-surround units, which determines the

DC response of the filter.

Fig. 9b. shows the fits of both the one-stage model (**Fig. 4a**) and two stage model (**Fig. 9a**)

to data obtained from **Experiment 4** for three observers (CJD, ERM, KNB). One stage models

were fit both with and without divisive terms, and identical predictions of observer performance

were obtained. We see in **Fig. 9b** that although both one-stage (green squares) and two-stage (red

squares) models fit observer performance (blue) in the neutral (**neu**) and two congruent cases, the

one-stage model drastically fails to account for observer performance in the incongruent case (**inc**),

predicting near chance performance. Plots like those in **Fig. 9b** are shown for all other observers

in **Supplementary Fig. S8**. The lack of robustness of the one-stage model to incongruently

oriented LSBs argues strongly in favor of the two-stage model as a more plausible mechanisms

for LTB segmentation, at least in the presence of interfering LSBs. BIC values for each model are

given in **Table 2** for these three observers. Fitting these two models to all observers in **Experiment**

4 and plotting the preference for the two-stage model ($BIC_2 - BIC_1$, **Fig. 10a**) reveals over the set

of N = 9 observers a significant preference for the two stage model (single sample t-test, mean =

30.22, $t(8) = 4.077$, $p < 0.004$).

As we see in **Fig. 8b**, for the majority of observers, we see better LTB segmentation

performance in the presence of a congruent boundary with aligned phase (**con-0**) than opposite

phase (**con-180**). Interestingly, the two stage model allows for LSB stimuli to potentially influence

LTB segmentation via the DC response of the first-stage filters. That is, if the on-center (off-center)

filters have a small positive (negative) response to constant light levels, this would allow LSB

stimuli to exert an excitatory influence on the second-stage filters, potentially explaining the

slightly improved performance for the phase-aligned versus opposite-phase congruent case in

Experiment 4 (**Fig. 8, 9b**). For the three observers plotted in **Fig. 9b**, we found the first stage on-

center filters all had a positive DC response, and over the population of observers (**Fig. 10b**) the

mean DC response was positive (single-sample t-test, mean = 6.91, $t(8) = 2.92$, $p < 0.019$). A

weakly positive relationship was seen across observers between the DC response and difference

between phase-aligned and opposite-phase performance (**Supplementary Fig. S9**), although this

relationship failed to obtain statistical significance (Pearson's correlation, $r = 0.314$, $p = 0.411$).

Observer	BIC_1: One Stage	BIC_2: Two Stage	BIC_2-BIC_1
CJD	-334.993	-316.863	18.130
ERM	-375.381	-367.651	7.730
KNB	-344.449	-309.400	35.049

545   **Table 2:** Bayes information Criterion (BIC) for fits of one-stage and two-stage

546   models to data from Experiment 4.

Two-stage model can account for LTB segmentation data

Finally, we show that the two-stage model shown in **Fig. 9a** can successfully fit the data in

Experiment 3 (**Figs. 6, 7**) Fits of the two stage model to data from these experiments is shown in

Fig. 11. We see that as with the one-stage model (**Fig. 7**), the best fits (blue lines) are obtained

with a divisive term in the model.

<u>Experiment 5: Segmenting LTBs while ignoring supra-threshold LSBs</u>

In the previous experiments, the LTB stimulus was masked by an LSB which observers were

instructed to ignore, and this masking LSB was presented at segmentation threshold (75% correct).

However, in natural vision one often segments texture-defined boundaries in the presence of surpa-

threshold luminance steps caused by shadows. In order to investigate the effects of supra-threshold

LSB maskers on LTB segmentation, observers CJD, ERM and KNB performed the LTB

segmentation task in the presence of masking LTB stimuli. Results are shown in **Fig. 12a**. LSB

masker levels are shown in units of multiples of JND (0 corresponds to no masker), and target

LTB JNDs for each masker are shown as multiples of unmasked JND. LTBs were tested at two

levels of the micro-pattern maximum amplitude ($A = 0.1, 0.2$). We see in **Fig. 12a** that for

observers KNB and ERM, LTB segmentation was fairly robust to LSB masker level, although at

the highest masker levels (4, 8 JNDs) we do see significant threshold elevation. However, these

changes in threshold do not correspond to highly visible differences in the LTB target. **Fig. 12b**

shows for each observer the stimulus in our series which was closest to the unmasked threshold

(triangle on left) and closest to the most elevated threshold (triangle on right), which was always

for the lower-contrast ($A = 0.1$) target. We see that for KNB and ERM these are fairly similar

visually. Observer CJD was less robust to interference from LSB stimuli, exhibiting significant

threshold elevation even for smaller masker levels (1, 2 JND), with a more clear visual dis-

similarity between the stimulus closest to the unmasked threshold and most elevated threshold

(**Fig. 12b**). Taken as a whole with the results of **Experiment 4**, we see that while there is a good

degree of robustness to LSB maskers when segmenting LTBs, there is some interaction between

the two, with the degree of interference increasing with masker level. Further supporting this

interpretation of interaction between the two stimuli comes from breaking down the LTB

thresholds by the relative orientations and phases of the LTB target and LSB masker

(**Supplementary Fig. S10**). We observe the most masking when the LTB and LSB stimuli have

the same orientation but opposite phases (**con-180**, magenta symbols), and the least masking (if

any) when the two stimuli have the same orientation and phase (**con-0**), with intermediate levels

for incongruent orientations.

DISCUSSION

Summary

Over half a century of research in modern vision science and has investigated visual texture

segmentation using parametric stimuli (Julesz, 1962, 1981; Landy, 2013; Victor, 2017). However,

this psychophysical work has largely focused on manipulating second-order and higher-order

statistical properties which characterize textures, while holding first-order (luminance) cues

constant (e.g., Zavitz & Baker, 2013, 2014). This is a sensible research strategy because it neatly

isolates the problem of understanding how higher-order statistics influence segmentation.

However, it is ultimately incomplete since natural region boundaries typically contain first-order

cues like color and luminance (Johnson & Baker, 2005; Ing, Wilson, & Geisler, 2010; Mely et al.,

2016; Breuil et al., 2019), which are known to combine with higher-order cues for localization and

segmentation (Rivest & Cavanaugh, 1996; McGraw, Whitaker, Badcock, & Skillen, 2003; Ing et

al., 2010; DiMattina et al., 2012). In most studies in which first-order cues are manipulated they

are presented as steps or gratings (e.g., Elder & Sachs, 2004; McIlhagga, 2018), or when they are

measured from natural images, it is as average luminance within in a region (Ing et al., 2010;

DiMattina et al., 2012). However, as we see in **Fig. 1**, differences in mean luminance can also be

caused by differences in the proportion of light and dark pixels in each surface regions, with no

abrupt change in albedo at the boundary. We refer to boundaries of this kind as luminance texture

boundaries (LTBs), to distinguish them from luminance step boundaries (LSBs). Understanding

whether or not these two kinds of luminance cue (LTB, LSB) are processed via the same, different,

or partially overlapping mechanisms is of great utility for understanding how first-order and

higher-order cues combine to enable natural boundary segmentation. The present study provides a

first step in this direction, suggesting that multiple mechanisms may contribute to luminance-based

boundary segmentation in natural vision.

Multiple mechanisms for segmentation using luminance cues

Clearly, whenever there are mean differences in luminance between two regions, a single stage of

linear filtering (**Fig. 4a**) is capable of detecting this difference, for both LTBs (**Fig. 4b**) and LSBs

(**Supplementary Fig. S4**) alike. However, this simplistic model would make the prediction that

for any two boundaries with equal luminance differences, segmentation performance should be

identical. Explicitly testing this idea in **Experiment 2** and **Experiment 3** lead us to reject this

model. Further exploration revealed that we can however explain the LTB segmentation data in

Experiments 2, 3 with a single stage of linear filtering if we incorporate a divisive operation

(Carandini & Heeger, 2012) which normalizes filter outputs by global RMS contrast. Nevertheless,

even with this improvement, any model positing a single stage of filtering computing a luminance

difference is highly susceptible to interference from stimuli which provide extraneous luminance

cues, for instance a shadow edge (LSB) with an orientation conflicting with the LTB orientation.

We test this prediction explicitly in **Experiment 4** and **Experiment 5**, where we investigated the

ability of observers to segment LTB stimuli in the presence of masking LSB stimuli. In these

experiments, we find that LTB segmentation is remarkably robust to interference from masking

LSB stimuli. This robustness to masking argues against the idea that a single stage of filtering is

adequate to fully explain LTB segmentation.

We posit that two sequential stages of filtering on different spatial scales may be required

to explain LTB segmentation, and implement the two-stage model is shown in **Fig. 9a**. It is

comprised of an initial layer of filtering on a local spatial scale which detects the micro-patterns,

followed by a second-stage of filtering which looks for spatial differences in the rectified outputs

of the first-stage filters on a global scale. This model successfully explains the ability of observers

to segment LTB stimuli in the presence of masking LSBs (**Fig. 9b**), and fits LTB segmentation

data obtained in **Experiment 3** (**Fig. 11**). Although the first stage filters in our model are

implemented as center-surround filters, which are known to be present in area V1 (Ringach,

Shapley, & Hawken, 2002; Talebi & Baker, 2012), orientation tuned mechanisms pooled across

different orientations can in principle serve the same function (Motoyoshi & Kingdom, 2004). This

general model architecture is known as the Filter-Rectify-Filter model (Chubb & Landy, 1991),

and has been applied in dozens of studies to model texture segmentation and second-order vision

(Landy, 2013). To our knowledge, the present study is the first time that it has been explicitly

demonstrated that an FRF-style model can describe how observers segment textures defined

entirely by first-order luminance cues.

One important finding from our psychophysical work is that although LTB segmentation

is highly robust to interference from masking LSB stimuli, it is not entirely independent. For

instance, in **Experiment 4** we found that segmentation performance was slightly better when the

LTB an LSB having congruent orientation were phase-aligned compared to opposite phase (**Fig.**

8b). In addition, in **Experiment 5** we found that LTB segmentation thresholds were lower for

phase-aligned rather than opposite phase masking LSBs as well. This interaction could arise in one

of two possible ways. One possibility, suggested by our model fitting, is that the first-stage filters

have a non-zero DC response. In particular, we observed that the on-center filters which best fit

the data from **Experiment 4** had a slightly positive response to a constant uniform stimulus (**Fig.**

10). This nonzero DC response is consistent with previous psychophysical studies (Eckstein et al.,

2002), as well as known neurophysiology of center-surround retinal ganglion cells (Croner &

Kaplan, 1995). However, another possibility is that the final decision arises by integrating the

outputs of a two-stage model like that in **Fig. 10a** with zero DC response with the outputs of a

single-stage model like that in **Fig. 4a**. Such a model would also be consistent with our

observations, and it is of interest for future work to design an experiment which could distinguish

between these two possibilities.

Future directions

Although natural surfaces may have luminance differences which arise due to luminance texture

boundaries, many other textural differences do not involve changes in luminance. Micro-pattern

orientation, density, and contrast and others all provide powerful segmentation cues (Dakin &

Mareschal, 2000; DiMattina & Baker, 2019; Zavitz & Baker, 2013, 2014; Sun & Baker, 2016;

Wolfson & Landy, 1995; Motoyoshi & Kingdom, 2007), which must be combined with luminance

cues to enable segmentation in natural vision. It is of great interest for future research to understand

how luminance textures combine with other cues. In particular, one could define black and white

micro-patterns as oriented bars instead of the dots used here, and simultaneously vary orientation

and luminance cues to see how these cues summate, i.e. via probability summation or additive

summation (Kingdom et al., 2015). Such an experiment would greatly expand the literature on the

interaction of first-order and second-order cues, which has largely been limited to simple detection

experiments in which the first-order cues were presented as gratings (Schofield & Georgeson,

1999; Allard & Faubert, 2007). Another interesting direction of research would be to consider how

luminance steps and luminance textures combine for boundary segmentation. In many cases, two

surfaces may have both kinds of cues defining luminance difference, and therefore combining both

cues will be helpful for segmentation. Although we suggest that the mechanisms are not identical,

they are most likely overlapping and therefore this kind of psychophysical summation experiment

would be very interesting.

The present study strongly suggests the possibility of neural mechanisms tuned to LTBs

which are minimally influenced by overlapping LSBs. We hypothesize that individual neurons

tuned to LTBs will most likely be found in extra-striate areas, for instance V2 and V4, which are

known to contain units sensitive to second-order boundaries (Mareschal & Baker, 1998; Schmid,

Purpura, & Victor, 2014) and units exhibiting texture selectivity (Okazawa, Tajima, & Komatsu,

2017). As suggested by our psychophysical models, neurons at higher areas of the visual pathway

may receive inputs from neurons in V1 or V2 responsive to the micro-patterns or texture elements.

If the afferent presynaptic V1 neurons in one spatial region are optimally driven by light micro-

patterns, and those in an adjacent spatial region prefer dark micro-patterns, the downstream extra-

striate neuron will be sensitive to differences in the proportion in light and dark micro-patterns in

these adjacent regions. It is of great interest for future neurophysiology studies to see if neurons

can be observed which are selectively responsive to LTB stimuli, while being poorly driven, if at

all, by step edges. Such neurons could provide a physiological basis for the ability to segment

surface boundaries in the presence of shadows and distinguish shadow edges from boundaries

(Vilankar, Golden, Chandler, & Field, 2014; Breuil et al., 2019).

Finally, a large body of work has demonstrated that deep neural networks trained on visual

tasks like object recognition develop intermediate-layer representations which are sensitive to

textural features (Kriegeskorte, 2015; Guclu & van Gerven, 2015). An entire sub-field of

computational neuroscience known as "artificial neurophysiology" has developed to analyze the

selectivity properties of units in these deep networks, and to interpret their results in light of known

neurophysiology. It would be of great interest for future investigation to do an artificial

neurophysiology study on deep neural networks resembling the ventral visual stream (Guclu &

van Gerven, 2015) in order to look for neurons which are tuned to luminance texture boundaries

while being relatively unresponsive to luminance steps, and to see if decoding such a population

of units can account for human performance psychophysical in texture segmentation tasks.

REFERENCES

Allard, R., & Faubert, J. (2007). Double dissociation between first-and second-order processing. *Vision Research*, *47*(9), 1129-1141.

Bishop, C. M. (2006). *Pattern recognition and machine learning*. Springer.

Brodatz, P. (1966). *Textures: A photographic album for artists and designers*. Dover Publications.

Brainard, D. H. (1997). The psychophysics toolbox. *Spatial Vision*, *10*(4), 433-436.

Breuil, C., Jennings, B. J., Barthelmé, S., & Guyader, N. (2019). Color improves edge classification in human vision. *PLoS Computational Biology*, *15*(10), e1007398.

Carandini, M., & Heeger, D. J. (2012). Normalization as a canonical neural computation. *Nature Reviews Neuroscience*, *13*(1), 51-62.

Chubb, C., & Landy, M. S. (1991). Orthogonal distribution analysis: A new approach to the study of texture perception. In: Computational Models of Visual Processing (Eds: Landy, M.S. & Movshon, J.A.). MIT Press.

Croner, L. J., & Kaplan, E. (1995). Receptive fields of P and M ganglion cells across the primate retina. *Vision research*, *35*(1), 7-24.

Dakin, S. C., & Mareschal, I. (2000). Sensitivity to contrast modulation depends on carrier spatial frequency and orientation. *Vision Research*, *40*(3), 311-329.

DiMattina, C., & Baker Jr, C. L. (2019). Modeling second-order boundary perception: A machine learning approach. *PLoS Computational Biology*, *15*(3), e1006829.

DiMattina, C., Fox, S. A., & Lewicki, M. S. (2012). Detecting natural occlusion boundaries using local cues. *Journal of vision*, *12*(13), 15-15.

Eckstein, M. P., Shimozaki, S. S., & Abbey, C. K. (2002). The footprints of visual attention in the Posner cueing paradigm revealed by classification images. *Journal of Vision*, *2*(1), 3-3.

Elder, J. H., & Sachs, A. J. (2004). Psychophysical receptive fields of edge detection mechanisms.

Vision Research, *44*(8), 795-813.

Güçlü, U., & van Gerven, M. A. (2015). Deep neural networks reveal a gradient in the

complexity of neural representations across the ventral stream. *Journal of Neuroscience*,

35(27), 10005-10014.

Hansen, B. C., & Hess, R. F. (2006). The role of spatial phase in texture segmentation and

contour integration. *Journal of Vision*, *6*(5), 5-5.

Hubel, D. H., & Wiesel, T. N. (1962). Receptive fields, binocular interaction and functional

architecture in the cat's visual cortex. *The Journal of Physiology*, *160*(1), 106.

Ing, A. D., Wilson, J. A., & Geisler, W. S. (2010). Region grouping in natural foliage scenes:

Image statistics and human performance. *Journal of vision*, *10*(4), 10-10.

Johnson, A. P., & Baker, C. L. (2005). Spatiochromatic statistics of natural scenes: first-and

second-order information and their correlational structure. *JOSA A*, *22*(10), 2050-2059.

Julesz, B. (1962). Visual pattern discrimination. *IRE transactions on Information Theory*, *8*(2),

84-92.

Julesz, B. (1981). Textons, the elements of texture perception, and their interactions. *Nature*,

290(5802),   91-97.

Kass, R. E., & Raftery, A. E. (1995). Bayes factors. *Journal of the american statistical*

association, *90*(430), 773-795.

Kingdom, F.A.A., Baldwin, A. S., & Schmidtmann, G. (2015). Modeling probability and additive

summation for detection across multiple mechanisms under the assumptions of signal

detection theory. *Journal of Vision*, *15*(5), 1-1.

Kingdom, F.A.A., & Prins, N. (2016). *Psychophysics: a practical introduction*. Academic Press.

Kriegeskorte, N. (2015). Deep neural networks: a new framework for modeling biological vision

and brain information processing. *Annual review of vision science*, *1*, 417-446.

Landy, M. S. (2013). Texture analysis and perception. In: *The New Visual Neurosciences* (Eds:

Werner, J. S., & Chalupa, L. M.). MIT Press.

Leek, M. R. (2001). Adaptive procedures in psychophysical research. *Perception &*

Psychophysics, *63*(8), 1279-1292.

Mareschal, I., & Baker, C. L. (1998). A cortical locus for the processing of contrast-defined

contours. *Nature Neuroscience*, *1*(2), 150-154.

Marr, D. (1982). Vision: A computational investigation into the human representation and

processing of visual information. Henry Holt and Co. Inc.*, New York, NY*.

Martin, D. R., Fowlkes, C. C., & Malik, J. (2004). Learning to detect natural image boundaries

using local brightness, color, and texture cues. *IEEE Transactions on Pattern Analysis*

and Machine Intelligence, *26*(5), 530-549.

McGraw, P. V., Whitaker, D., Badcock, D. R., & Skillen, J. (2003). Neither here nor there:

Localizing conflicting visual attributes. *Journal of Vision*, *3*(4), 2-2.

McIlhagga, W. (2018). Estimates of edge detection filters in human vision. *Vision Research*,

153, 30-36.

McIlhagga, W. H., & May, K. A. (2012). Optimal edge filters explain human blur detection.

Journal of Vision, *12*(10), 9-9.

McIlhagga, W., & Mullen, K. T. (2018). Evidence for chromatic edge detectors in human vision

using classification images. *Journal of Vision*, *18*(9), 8-8.

Mély, D. A., Kim, J., McGill, M., Guo, Y., & Serre, T. (2016). A systematic comparison

between visual cues for boundary detection. *Vision research*, *120*, 93-107.

Motoyoshi, I., & Kingdom, F. A. (2007). Differential roles of contrast polarity reveal two streams

815   of second-order visual processing. *Vision Research*, *47*(15), 2047-2054.

816   Okazawa, G., Tajima, S., & Komatsu, H. (2017). Gradual development of visual texture-selective

817   properties between macaque areas V2 and V4. *Cerebral Cortex*, *27*(10), 4867-4880.

818   Parker, A. J., & Hawken, M. J. (1988). Two-dimensional spatial structure of receptive fields in

819   monkey striate cortex. *JOSA A*, *5*(4), 598-605.

820   Ringach, D. L., Shapley, R. M., & Hawken, M. J. (2002). Orientation selectivity in macaque V1:

821   diversity and laminar dependence. *Journal of Neuroscience*, *22*(13), 5639-5651.

822   Rivest, J., & Cabanagh, P. (1996). Localizing contours defined by more than one attribute. *Vision

823   Research*, *36*(1), 53-66.

824   Saarela, T. P., & Landy, M. S. (2012). Combination of texture and color cues in visual

825   segmentation. *Vision Research*, *58*, 59-67.

826   Schmid, A. M., Purpura, K. P., & Victor, J. D. (2014). Responses to orientation discontinuities in

827   V1 and V2: physiological dissociations and functional implications. *Journal of

828   Neuroscience*, *34*(10), 3559-3578.

829   Schofield, A. J., & Georgeson, M. A. (1999). Sensitivity to modulations of luminance and

830   contrast in visual white noise: Separate mechanisms with similar behaviour. *Vision

831   Research*, *39*(16), 2697-2716.

832   Sun, H. C., & Baker, C. L. (2016). Simultaneous density contrast is bidirectional. *Journal of

833   Vision*, *16*(14), 4-4.

834   Sun, H. C., Kingdom, F. A., & Baker, C. L. (2019). Perceived regularity of a texture is influenced

835   by the regularity of a surrounding texture. *Scientific reports*, *9*(1), 1-11.

Schwarz, G. (1978). Estimating the dimension of a model. *The annals of statistics*, *6*(2), 461-464.

Talebi, V., & Baker, C. L. (2012). Natural versus synthetic stimuli for estimating receptive field

models: a comparison of predictive robustness. *Journal of Neuroscience*, *32*(5), 1560-

1576.

Victor, J. D., Conte, M. M., & Chubb, C. F. (2017). Textures as probes of visual processing.

Annual Review of Vision Science, *3*, 275-296.

Vilankar, K. P., Golden, J. R., Chandler, D. M., & Field, D. J. (2014). Local edge statistics provide

information regarding occlusion and nonocclusion edges in natural scenes. *Journal of

Vision*, *14*(9), 13-13.

Wolfson, S. S., & Landy, M. S. (1995). Discrimination of orientation-defined texture edges. *Vision

Research*, *35*(20), 2863-2877.

Zavitz, E., & Baker, C. L. (2013). Texture sparseness, but not local phase structure, impairs

second-order segmentation. *Vision Research*, *91*, 45-55.

Zavitz, E., & Baker, C. L. (2014). Higher order image structure enables boundary segmentation in

the absence of luminance or contrast cues. *Journal of Vision*, *14*(4), 14-14.

FIGURE CAPTIONS

Figure 1: Boundaries without luminance step edges

(**a**) A luminance step boundary (LSB) and a simple detection model in which a linear Gabor filter

computes the regional luminance difference. (**b**) Model similar to that in (a) where the LSB is

analyzed by multiple Gabor filters at varying spatial scales. (**c**) Example of luminance texture

boundary (LTB). The luminance difference is defined by differing proportions of black and white

micro-patterns on each side of the boundary, with no sharp change in albedo at the boundary. (**d**)

Two juxtaposed textures from the Brodatz database. Although there is clearly a regional difference

in luminance, there is no sharp change in albedo at the boundary.

Figure 2: Stimuli used in this experiment

(**a**) Luminance texture boundary (LTB) stimuli similar to those used in this study, shown for

varying densities (16, 32, 64) and proportion unbalanced patterns ($\pi_U = 0.2, 0.4, 0.6, 0.8$). For all

of these stimuli, the boundary is right oblique. (**b**) Luminance step boundary (LSB) stimulus. (**c**)

Sum of LTB and LSB stimuli having the same boundary orientation (*congruent*). *Right:* Phase-

aligned boundaries. *Left:* Opposite-phase boundaries. (**d**) Sum of LTB and LSB stimuli having

opposite boundary orientations (*incongruent*).

Figure 3: Psychometric functions and threshold distributions

(**a**) Fits of SDT psychometric functions (blue curves) for two observers (KNB, JJB) for luminance

texture boundary (LTB) segmentation (**Experiment 1a**) as proportion unbalanced patterns (π_U) is

varied. The size of each solid dot is proportional to the number of trials obtained at each level, and

dashed black lines denote 75% thresholds for the curves. Circles and lines indicate threshold

estimates and 95% confidence intervals obtained from 200 bootstrapped re-samplings of the data.

(**b**) Histogram of segmentation thresholds (π_U) measured from all observers in **Experiment 1a**.

(**c**) Fits of SDT PFs for two observers (MXD, MCO) segmenting luminance step boundary (LSB)

stimuli as Michealson contrast (c_M) is varied (**Experiment 1b**). (**d**) Histogram of segmentation

thresholds (c_M) from **Experiment 1b**.

Figure 4: Image computable model with one filtering stage

(**a**) Model with a single stage of filtering. Luminance differences are computed across the left-

oblique and right-oblique diagonals, passed through a rectifying nonlinearity and subtracted to

determine the probability P(R) of observer classifying the boundary as right-oblique. (**b**) Fits of

the model in (a) to LTB segmentation data from **Experiment 1a**.

Figure 5: Holding luminance difference constant

(**a**) LTB stimuli having an equal number of unbalanced micro-patterns on each side of the

boundary (8), with varying numbers (0, 16, 32) of balanced micro-patterns. In this series, the

luminance difference across the boundary is constant for all stimuli. (**b**) Proportion correct

responses for three observers for differing numbers of balanced micro-patterns. Lines indicate 95%

binomial proportion confidence intervals for each level (N = 50 trials each level). We see that

performance degrades significantly with increasing numbers of unbalanced patterns, despite

constant luminance difference. This suggests that a simple luminance difference computation may

be inadequate to segment LTB stimuli.

Figure 6: Varying micro-pattern amplitude to vary global luminance difference

(**a**) LTBs with different maximum micro-pattern amplitudes 0.1, 0.25, 0.4 (dimensionless units)

(**b**) Bootstrapped SDT psychometric function fits (200 bootstrapped re-samplings) with 90 percent

confidence intervals of observer performance as a function of proportion unbalanced patterns (left

panels) and absolute luminance difference (right panels). We see that the global luminance

difference is a very poor predictor of performance, with identical luminance differences giving rise

to significantly different predictions of observer performance for the three micro-pattern maximum

amplitudes (right panels). By contrast, we find much better agreement between the proportion of

unbalanced micro-patterns and observer performance (left panels).

Figure 7: Comparison of additive and divisive models

Data from **Experiment 3** (black dots) and fits of the additive (red) and divisive (blue) signal

detection theory models to the data. Each observer was tested at three different maximum micro-

pattern amplitudes, which correspond to different stimulus contrasts (0.2, 0.4, 0.8). We see that a

model incorporating a global luminance difference computation followed by contrast

normalization (blue) provides an excellent fit to this data.

Figure 8: Effects of masking luminance step boundaries on LSB segmentation

(**a**) Performance for N = 9 observers segmenting LTB stimuli using proportion unbalanced patterns

(π_U), which was set at 75% JND measured in **Experiment 1a**. We see similar performance for

most observers in the absence of a masker (neutral case, **neu**) as well as with a masker having

congruent (**con**) and incongruent (**inc**) orientation. (**b**) Performance for same observers for

congruent stimuli with are both in-phase (**con-0**) and opposite-phase (**con-180**).

Figure 9: Two-stage model fits Experiment 4 results

(**a**) Model with two cascaded stages of filtering. The first stage of this model analyzes the micro-

patterns on a localized spatial scale. The second stage of this model looks for differences in the

outputs of these first-stage filters on the spatial scale. Such a model can detect differences in the

proportions of black and white micro-patterns on opposite sides of the boundary, while being fairly

robust to interference from luminance steps. (**b**) Fits of one-stage model (green squares) and two-

stage model (red squares) to data from **Experiment 4** (blue dots, lines denote 95% confidence

intervals).

Figure 10: Analysis of Experiment 4

(**a**) Preference for two stage model over the one stage model (BIC_2 - BIC_1), for all N = 9 observers

in Experiment 4. (**b**) DC response for the first-stage filters obtained from each observer.

Figure 11: Fits of two-stage model to Experiment 3

Fits of two-stage model to data from **Experiment 3**. By comparing with Fig. 7, we see that fits are

identical to those obtained from the one-stage model, and fits are much better with divisive

computation. Luminance differences are obtained from the outputs of the on-center and off-center

surround filters.

Figure 12: Results of Experiment 5

(**a**) Thresholds for LTB segmentation as a function of LSB masker level. (**b**) Visual illustration of

stimuli closest to unmasked segmentation thresholds (left arrows) and highest masked

segmentation thresholds (right arrows).

FIGURE 1

968   **FIGURE 2**

976   **FIGURE 3**

991   **FIGURE 4**

1000

1001

1002

1003

1004

1005   **FIGURE 5**

1006

1007

1008

1009

1010

1011

1012

1013

1014

1015

1016

1017

1018

1019

1020

1021

1022

1023   **FIGURE 6**

1024

1025

1026   **FIGURE 7**

1027

1028

1029

1030

1031

1032

1033

1034

1035

1036

1037   **FIGURE 8**

1038

1039

1040

1041

1042

1043

1044

1045

1046

1047

1048

1049

1050

FIGURE 9

1052

1053

1054

a

b

1055

1056

1057

1058

1059

1060

1061

1062

1063   **FIGURE 10**

1064

1065

1066

1067

1068

1069

1070

1071

1072

1073

1074

1075

1076

1077

1078

1079

1080

1081

1082

1083 **FIGURE 11**

1084

1085

1086

1087

1088

1089

1090

1091

1092

1093

1094

1095   **FIGURE 12**

1096

1097