1 Vigilance decrements in the brain: neural signatures can predict behavioural errors before they
2 happen
3
4
Hamid Karimi-Rouzbahani[1], Alexandra Woolgar*[1,2], Anina N. Rich*[1]

[1]Perception in Action Research Centre and Department of Cognitive Science, Faculty of Human
Sciences, Macquarie University, Australia

[2]Medical Research Council Cognition and Brain Sciences Unit, University of Cambridge, UK

* Equally contributing authors

Abstract- There are now many environments in which humans need to monitor moving displays and

only rarely act, such as train control and driving autonomous vehicles; lapses of attention in these

circumstances can have tragic consequences. Problematically, we know that it is difficult to sustain

attention under these monitoring or vigilance conditions and performance drops: when target

events are rare, we tend to miss them, or are slower to respond. This 'rare target' effect becomes

more marked with longer tasks, known as a vigilance decrement. Despite the importance, we still

have limited understanding of how the brain processes information during monitoring, particularly

with dynamic stimuli, and how this processing changes when attention lapses. Here, we designed a

multiple-object monitoring (MOM) paradigm that required sustained attention to dynamic stimuli,

and used multivariate analyses of magnetoencephalography (MEG) data to examine how the neural

representation of the information in the display varied with target frequency and time on the task.

Behavioural performance decreased over time for the rare target (monitoring) condition, but not for

the frequent target (active) condition. This change was mirrored in the neural results: under

monitoring conditions, there was weaker coding of the critical distance between objects during time

periods when vigilance decrements in performance occurred. There was also weaker informational

connectivity between peri-occipital and peri-frontal brain areas in rare versus frequent target

conditions. We developed a new analysis which used the strength of information decoding to predict

whether the participant was going to miss the target on a given trial. We could predict behavioural

errors more than a second before they occurred. This provides a first step in developing methods to

predict and pre-empt behavioural errors due to lapses in attention and provides new insight into

how vigilance decrements are reflected in information coding in the brain.

Introduction

When people monitor displays for rare targets, they are slower to respond and more likely to miss

those targets relative to frequent target conditions (Wolfe et al., 2005; Warm et al., 2008; Rich et al.,

2008). This effect is more pronounced as the time doing the task increases, which is often called a

'vigilance decrement'. Theoretical accounts of vigilance decrements fall into two main categories.

'Cognitive depletion' theories suggest performance drops as cognitive resources are 'used up' by the

difficulty of sustaining attention under vigilance conditions (Helton et al., 2008; Helton et al., 2011;

Warm et al., 2008). In contrast, 'mind wandering' theories suggest that the boredom of the task

tends to result in insufficient involvement of cognitive resources, which in turn leads to performance

decrements (Manly et al., 1999; Smallwood et al., 2006; Young et al., 2002). Either way, there are

many real-life situations where such a decrease in performance over time can lead to tragic

consequences, such as the Paddington railway disaster (UK, 1999), in which a slow response time to

a stop signal resulted in a train moving another 600 meters past the signal into the path of an

oncoming train. With the move towards automated and semi-automated systems in many high-risk

domains (e.g., power-generation and trains), humans now commonly need to monitor systems for

infrequent computer failures or errors. These modern environments challenge our attentional

systems and make it urgent to understand the way in which monitoring conditions change the way

important information about the task is encoded in the human brain.

To date, most vigilance and rare target studies have used simple displays with static stimuli.

Traditional vigilance tasks, inspired by radar operators in WWII (Mackworth, 1948), require

participants to respond to infrequent visual events on otherwise blank screens (Temple et al., 2000).

Contemporary vigilance tasks, like the Sustained Attention to Response Task (SART), require

participants to respond frequently to a rapid stream of static displays and occasionally withhold a

response (Rosvold et al., 1956; Rosenberg et al., 2013). However, modern environments (e.g., rail

and air traffic control) have additional challenges not encapsulated by these measures. This includes

multiple moving objects, potentially appearing at different times, and moving simultaneously in

different directions. When an object moves in the space, its neural representation has to be

continuously updated so we can perceive the object as having the same identity. Tracking moving

objects also requires considerable neural computation: in addition to spatial remapping, for

example, we need to predict direction, speed, and the distance of the object to a particular

destination. These features cannot be studied using static stimuli; they require objects that shift

across space over time. In addition, operators have complex displays requiring selection of some

items while ignoring others. We therefore need new approaches to study vigilance decrements in

situations that more closely resemble the real-life environments in which humans are now

operating. Developing these methods will provide a new perspective on fundamental questions of

how the brain implements sustained attention in moving displays, and the way in which monitoring

compared with active task involvement changes the encoding of task information. These new

methods may also provide avenues to optimise performance in high-risk monitoring environments.

The brain regions involved in maintaining attention over time has been studied using functional

Magnetic Resonance Imaging (fMRI), which measures changes in cerebral blood flow (Adler et al.,

2001; Benedict et al., 2002; Coull et al., 1996; Gilbert et al., 2006; Johannsen et al., 1997; Ortunoe t

al., 2002; Perin et al., 2010; Scnell et al., 2007; Sturm et al., 1999; Tana et al., 2010; Thakral et al.,

2009; Wingen et al., 2008). These studies compared brain activation in task vs. resting baseline or

sensorimotor control (which involved no action) conditions and used univariate analyses to identify

regions with higher activation under task conditions. This has the limitation that there are many

features that differ between the contrasted (subtracted) conditions, not just the matter of sustained

attention. Specifically, this comparison cannot distinguish whether the activation during sustained

attention is caused by the differences in the task, stimuli, responses or a combination of these

factors. As it is challenging to get sufficient data from monitoring (vigilance) tasks in the scanner,

many previous studies used tasks with relatively frequent targets, in which vigilance decrements

usually do not occur. However, despite these challenges, Langner et al. (2013) reviewed vigilance

neuroimaging studies and identified a network of right-lateralized brain regions including

dorsomedial, mid- and ventrolateral prefrontal cortex, anterior insula, parietal and a few subcortical

areas that they argue form the core network subserving vigilant attention in humans. The areas

identified by Langner et al. (2013) show considerable overlap with a network previously identified as

being recruited by many cognitively challenging tasks, the 'multiple demand' (MD) regions, which

include the right inferior frontal gyrus, anterior insula and intra parietal sulcus (Duncan & Owen,

2000; Duncan, 2010; Fedorenko et al., 2013; Woolgar et al., 2011; Woolgar et al., 2015a; Woolgar et

al., 2015b).

Other fMRI studies of vigilance have focused on the default mode network, composed of discrete

areas in the lateral and medial parietal, medial prefrontal, and medial and lateral temporal cortices

such as posterior cingulate cortex (PCC) and ventral anterior cingulate cortex (vACC), which is

thought to be active during 'resting state' and less active during tasks (Greicius et al., 2003; Greicius

et al., 2009; Raichle et al., 2015). Eichele et al., (2008) suggested that lapses in attention can be

predicted by decrease of deactivation of this default mode network. In contrast, Weissman et al.

(2006) identified deactivation in the anterior cingulate and right prefrontal regions in pre-stimulus

time windows when targets were missed. More recently, Sadaghiani et al. (2015) showed that the

functional connectivity between sensory and 'vigilance-related' (Cingulo-Opercular) brain areas

decreased prior to behavioural misses in an auditory task while the connectivity increased between

the same sensory area and the default-mode network. These suggest that modulation of

interactions between sensory and vigilance-related brain areas might be responsible for behavioural

misses in monitoring tasks.

Detecting changes in brain activation that correlate with lapses of attention can be particularly

challenging with fMRI, given that it has poor temporal resolution. Electroencephalography (EEG),

which records electrical activity at the scalp, has much better temporal resolution, and has been the

other major approach for examining changes in brain activity during sustained attention tasks.

Frequency band analyses have shown that low-frequency alpha (8 to 10.9 Hz) oscillations predict

task workload and performance during monitoring of simulated air traffic (static) displays with rare

targets, while frontal theta band (4 to 7.9 Hz) activity predicts task workload only in later stages of

the experiment (Kamzanova et al., 2014). Other studies find that increases in occipital alpha

oscillations can predict upcoming error responses (Mazaheri et al., 2009) and misses (O'Connell et

al., 2009) in go/no-go visual tasks with target frequencies of 11% and 9%, respectively. These

changes in signal power that correlate with the task workload or behavioural outcome of trials are

useful, but provide relatively coarse-level information about what changes in the brain during

vigilance decrements.

Understanding the neural basis of decreases in performance over time under vigilance conditions is

not just theoretically important, it also has potential real-world applications. In particular, if we

could identify a reliable neural signature of attentional lapses, then we could potentially intervene

prior to any overt error. For example, with the development of autonomous vehicles, being able to

detect when a driver is not engaged, combined with information about a potential threat, could

allow emergency braking procedures to be initiated. Previous studies have used physiological

measures such as pupil size (Yoss, et al., 1970), body temperature (Molina et al., 2019), skin

conductance, blood pressure, etc. (Lohani et al., 2019) to indicate the level of human arousal or

alertness, but these lack the fine-grained information necessary to distinguish transient dips from

problematic levels of inattention in which task-related information is lost. In particular, we lack

detail on how information processing changes in the brain during vigilance decrements. This

knowledge is crucial to develop a greater theoretical and practical understanding of how humans

sustain vigilance.

In this study, we developed a new task, multiple object monitoring (MOM), which includes key

features of real-life situations confronting human operators in high-risk environments. These

features include moving objects, varying levels of target frequency, and a requirement to detect and

avoid collisions. We recorded neural data using the highly-sensitive method of

magnetoencephalography (Baillet, 2017) and used multivariate pattern analyses (MVPA) to detect

changes in information encoded in the brain. We used these new approaches to better understand

the way in which changes between active and monitoring tasks affects neural processing, including

functional connectivity. We then examined the potential for using these neural measures to predict

forthcoming behavioural misses based on brain activity.

Methods

Participants:

We tested twenty-one right-handed participants (10 male, 11 female, mean age = 23.4 years (SD =

4.7 years), all Macquarie University students) with normal or corrected to normal vision. The Human

Research Ethics Committee of Macquarie University approved the experimental protocols and the

participants gave informed consent before participating in the experiment. We reimbursed each

participant AU$40 for their time completing the MEG experiment, which lasted for about 2 hours

including setup.

Apparatus:

We recorded neural activity using a whole-head MEG system (KIT, Kanazawa, Japan) with 160 coaxial

first-order gradiometers, at a sampling rate of 1000 Hz. We projected the visual stimuli onto a mirror

at a distance of 113 cm above participants' heads while they were in the MEG. An InFocus IN5108

LCD back projection system (InFocus, Portland, Oregon, USA), located outside the magnetically

shielded room, presented the dynamically moving stimuli, controlled by a desktop computer

(Windows 10; Core i5 CPU; 16 GB RAM; NVIDIA GeForce GTX 1060 6GB Graphics Card) using

MATLAB with Psychtoolbox 3.0 extension (Brainard, 1997; Kleiner et al., 2007). We set the refresh

rate of the projector at 60 Hz and used parallel port triggers and a photodiode to mark the beginning

(dot appearing on the screen) and end (dot disappearing off the screen) of each trial. We recorded

participant's head shape using a pen digitizer (Polhemus Fastrack, Colchester, VT) and placed five

marker coils on the head which allowed the location of the head in the MEG helmet to be monitored

during the recording- we checked head location at the beginning, half way through and the end of

recording. We used a fibre optic response pad (fORP, Current Designs, Philadelphia, PA, USA) to

collect responses and an EyeLink 1000 MEG-compatible remote eye-tracking system (SR Research,

1000 Hz monocular sampling rate) to record eye position. We focused the eye-tracker on the right

eye of the participant and calibrated the eye-tracker immediately before the start of MEG data

recording.

Task and Stimuli:

Task summary: The task was to avoid collisions of relevant moving dots with the central object by pressing the space bar if the dot passed a deflection point in a visible predicted trajectory without changing direction to avoid the central object (see Figure 1A; a demo can be found here https://osf.io/c6hy9/). A text cue at the start of each block indicated which colour of dot was relevant for that block. The participant only needed to respond to targets in this colour; dots in the other colour formed distractors. Pressing the button deflected the dot in one of two possible directions (counterbalanced) to avoid collision.

Stimuli: The stimuli were moving dots in one of two colours that followed visible trajectories and covered a visual area of 3.8 × 5 degrees of visual angle (dva; Figure 1A). We presented the stimuli in blocks of 110 s duration, with at least one dot moving on the screen at all times during the 110s block. The trajectories directed the moving dots from two corners of the screen (top left and bottom right) straight towards a centrally presented static "object" (a white dot of 0.25 dva) and then deflected away (either towards the top right or bottom left of the screen; in pathways orthogonal to their *direction of approach*) from the static object at a set distance (the deflection point).

Target dots deviated from the visible trajectory at the deflection point and continued moving towards the central object. The participant had to push the space bar to prevent a 'collision'. If the response was made before the dot reached the centre of the object, the dot deflected, and this was counted as a 'hit'. If the response came after this point, the dot continued straight, and this was counted as a 'miss', even if they pressed the button before the dot totally passed through central object.

Figure 1. The Multiple Object Monitoring (MOM) task and types of information decoded. (A) At the start of a block, the relevant colour is cued (here, green; distractors in red). Over the on-task period (~30 mins per task condition), multiple dots entered from either direction, each moving along a visible individual trajectory towards the middle object. Only attended dots that failed to deflect along the trajectories at the deflection point required a response (Target: bottom right display). Participants did not need to press the button for the unattended dot (Distractor: top right display) and the dots that kept moving on the trajectories (Event: middle right panel). Each dot took ~1226 ms from appearance to deflection. (B) Direction of approach information (left display: left vs. right as indicated by dashed and solid lines, respectively) and distance information (right display). Note the blue dashed lines and orange arrows were not present in the actual display. A demo of the task can be found here [https://osf.io/c6hv9/].

The time from dot onset in the periphery to the point of deflection was 1226±10 (Mean ± SD)

milliseconds. Target (and distractor event) dots took 410±10 (Mean ± SD) milliseconds to cross from

the deflection point to the collision point. In total, each dot moved across the display for 2005±12

(Mean ± SD) milliseconds before starting to fade away after either deflection or travel through the

object. The time delay between the onsets of different dots (ISI) was 1660±890 (Mean ± SD)

milliseconds. There were 1920 dots presented in the whole experiment (~56 mins). Each 110 second

block contained 64 dots, 32 (50%) in red and 32 (50%) in green, while the central static object and

trajectories were presented in white on a black background.

Conditions: There were two target frequency conditions. In 'Monitoring' blocks, target dots were

~6.2% of cued-colour dots (2 out of 32 dots). In 'Active' blocks, target dots were 50% of cued-colour

dots (16 out of 32 dots). The same proportion of dots in the non-cued colour failed to deflect; these

were distractors (see Figure 1A, top right panel). Participants completed two practice blocks of the

Active condition and then completed 30 blocks in the main experiment (15 Active followed by 15

Monitoring or *vice versa*, counterbalanced across participants).

The time between the appearance of target dots varied unpredictably, with distractors and

correctly-deflecting dots (events) intervening. In Monitoring blocks, there was an average time

between targets of 57.88 (±36.03 SD) seconds. In Active blocks, there was an average time between

targets of 7.20 (±6.36 SD) seconds.

Feedback: On target trials, if the participant pressed the space bar in time, this 'hit' was indicated by

a specific tone and deflection of the target dot. There were three types of potential false alarm, all

indicated by an error tone and no change in the trajectory of the dot. These were if the participant

responded: (1) too early, while the dot was still on the trajectory; (2) when the dot was not a target

and had been deflected automatically ('event' in Figure 1A, middle right); or (3) when the dot was in

the non-cued colour ('distractor' in Figure 1A, top right) in any situation. Participants had only one

chance to respond per dot; any additional responses resulted in 'error' tones. As multiple dots could

be on the screen, we always associated the button press to the dot which was closest to the central

object.

Pre-processing:

MEG data were filtered online using band-pass filters in the range of 0.03 to 200 Hz and notch-

filtered at 50 Hz. We did not perform eye-blink artefact removal because it has been shown that

blink artefacts are successfully ignored by multivariate classifiers as long as they are not

systematically different between decoded conditions (Grootswagers et al., 2017). We then imported

the data into Matlab and epoched them from -100 to 3000 ms relative to the trial onset time. Finally,

we down-sampled the data to 200 Hz for the decoding of our two key measures: *direction of*

approach and *distance to object* (see below).

Multivariate pattern analyses (MVPA):

We measured the information contained in the multivariate (multi-sensor) patterns of MEG data by

training a linear discriminant analysis (LDA) classifier using a set of training trials from two categories

(e.g., for the *direction of approach* measure, this was dots approaching from left vs. right, see

below). We then tested to see whether the classifier could predict the category of an independent

(left-out) set of testing data from the same participant. We used a 10-fold cross-validation approach,

splitting the data into training and testing subsets. Specifically, we trained the LDA classifier on 90%

of the trials and tested it on the left-out 10% of the trials. This procedure was repeated 10 times

each time leaving out a different 10% subset of the data for testing (i.e., 10-fold cross validation).

We decoded two major task features from the neural data: (1) the *direction of approach* (left vs.

right); and (2) the distance of each moving dot from the centrally fixed object (*distance to object*),

which correspond to visual (retinal) information changing over time. Our interest was in the effect of

selective attention (attended vs. unattended) and Target Frequency conditions (Active vs.

Monitoring) on the neural representation of this information, and how the representation of

information changed on trials when participants missed the target.

We decoded left vs. right *directions of approach* (as indicated by yellow arrows in Figure 1B) every 5

ms starting from 100 ms before the appearance of the dot on the screen to 3000 ms later. Please

note that as each moving dot is considered a trial, trial time windows (epochs) overlapped for 62.2%

of trials. In Monitoring blocks, 1.2% of target trials overlapped (two targets were on the screen

simultaneously but lagged relative to one another). In Active blocks, 17.1% of target trials

overlapped.

For the decoding of *distance to object*, we split the trials into the time windows corresponding to 15

equally spaced distances of the moving dot relative to the central object (as indicated by blue lines in

Figure 1B), with distance 1 being closest to the object, and 15 being furthest away (the dot having

just appeared on the screen). Next, we collapsed (concatenated) the MEG signals from identical

distances (splits) across both sides of the screen (left and right), so that every distance included data

from dots approaching from both left and right side of the screen. This concatenation ensures that

distance information decoding is not affected by the *direction of approach*. Finally, we trained and

tested a classifier to distinguish between the MEG signals (a vector comprising data from all MEG

sensors, concatenated over all time points in the relevant time window), pertaining to each pair of

distances (e.g., 1 vs. 2) using a leave-one-out cross-validation procedure. We obtained classification

accuracy for all possible pairs of distances (105 combinations of 15 distances). To obtain a single

decoding value per distance, we averaged the 14 classification values that corresponded to that

distance against other 14 distances. For example, the final decoding accuracy for distance 15 was an

average of 15 vs. 14, 15 vs. 13, 15 vs. 12 and so on until 15 vs. 1. We repeated this procedure for our

main Target Frequency conditions (Active vs. Monitoring), Attention conditions (attended vs.

unattended) and Time on Task (first and last five blocks of each task condition, which are called early

and late blocks here, respectively). This was done separately for *correct* and *miss* trials and for each

participant separately.

Informational connectivity analysis:

To evaluate possible modulations of brain connectivity between the attentional networks of the

frontal brain and the occipital visual areas, we used a simplified version of our recently developed

RSA-based connectivity analysis (Goddard et al., 2016; Karimi-Rouzbahani, 2018; Karimi-Rouzbahani

et al., 2019). Specifically, we evaluated the informational connectivity, which measures the similarity

of distance information between areas, across our main Target Frequency conditions (Active vs.

Monitoring), Attention conditions (attended vs. unattended) and Time on Task (first and last five

blocks of each task condition, which are called early and late blocks here, respectively). This was

separately done for *correct* and *miss* trials, using representational dissimilarity matrices (RDM;

Kriegeskorte et al., 2008). To construct the RDMs, we decoded all possible combinations of distances

from each other yielding a 15 by 15 cross-condition classification matrix, for each condition

separately. We obtained these matrices from peri-occipital and peri-frontal areas to see how the

manipulation of Attention, Target Frequency and Time on Task modulated the correlation of

information (RDMs) between those areas on *correct* and *miss* trials. We quantified connectivity using

Spearman's rank correlation of the matrices obtained from those areas, only including the lower

triangle of the RDMs (105 decoding values). To avoid bias when comparing the connectivity on

correct vs. *miss* trials, the number of trials were equalized by subsampling the *correct* trials to the

number of *miss* trials and repeating the subsampling 100 times before finally averaging them for

comparison with *miss* trials.

Error data analysis:

Next, we asked what information was coded in the brain when participants missed targets. To study information coding in the brain on *miss* trials, where the participants failed to press the button when targets failed to automatically deflect, we used our recently-developed method of error data analysis (Woolgar et al., 2019). Essentially, this analysis asks whether the brain represents the information similarly on *correct* and *miss* trials. For that purpose, we trained a classifier using the neural data from a proportion of *correct* trials (i.e., when the target dot was detected and manually deflected punctually) and tested on both the left-out portion of the *correct* trials (i.e., cross-validation) and on the *miss* trials. If decoding accuracy is equal between the *correct* and *miss* trials, we can conclude that information coding is maintained on *miss* trials as it is on *correct* trials. However, if decoding accuracy is lower on *miss* trials than on *correct* trials, we can infer that information coding differs on *miss* trials, consistent with the change in behaviour. Since *correct* and *miss* trials were visually different after the deflection point, we only used data from before the deflection point.

For these error data analyses, the number of folds for cross-validation were determined based on the proportion of *miss* to *correct* trials (number of folds = number of miss trials/number of correct trials). This allowed us to test the trained classifiers with equal numbers of *miss* and *correct* trials to avoid bias in the comparison.

Predicting behavioural performance from neural data:

We developed a new method to predict, based on the most task-relevant information in the neural signal, whether or not a participant would press the button for a target dot in time to deflect it on a particular trial. This method includes three steps, with the third step being slightly different for the

left-out testing participant vs. the other 20 participants. First, for every participant, we trained 105

classifiers using ~80% of correct trials to discriminate the 15 distances. Second, we tested those

classifiers using half of the left-out portion (~10%) of the correct trials, which we called validation

trials, by simultaneously accumulating (i.e., including in averaging) the accuracies of the classifiers at

each distance and further distances as the validation dot approached the central object. The

validation set allowed us to determine a decision threshold for predicting the outcome of each

testing trial: whether it was a *correct* or *miss* trial. Third, we performed a second-level classification

on testing trials which were the other half (~10%) of the left-out portion of the correct trials and the

miss trials, using each dot's accumulated accuracy calculated as in the previous step. Accordingly, if

the testing dot's accumulated accuracy was ***higher*** than the decision threshold, it was predicted as

correct, otherwise *miss*. For all participants, except for the left-out testing one, the decision

threshold was chosen from a range of ***multiples*** (0.1 to 4 in steps of 0.1) of the standard deviation

below the accumulated accuracy obtained for the validation set on the second step. For determining

the optimal threshold for the testing participant, however, instead of a range of multiples, we used

the average of the best performing multiples (i.e., the one which predicted the behavioural outcome

of the trial more accurately) obtained from the other 20 participants. This avoided circularity in the

analysis.

To give more detail on the second and third steps, when the validation/testing dots were at distance

#15, we averaged the accuracies of the 14 classifiers trained to classify dots at distance #15 from all

other distances. Accordingly, when the dot reached distance #14, we also included and averaged

accuracies from classifiers which were trained to classify distance #14 from all other distances

leading to 27 classifier accuracies. Therefore, by the time the dot reached distance #1, we had 105

classifier accuracies to average and predict the behavioural outcome of the trial. Every classifier's

accuracies were either 1 or 0 corresponding to correct or incorrect classification of dot's distance,

respectively. Note that accumulation of classifiers' accuracies, as compared to using classifier

accuracy on every distance independently, provides a more robust and smoother classification

measure for deciding on the label of the trials. The validation set, which was different from the

testing set, allowed us to set the decision threshold based on the validation data within each subject

and from the 20 participants and finally test our prediction classifiers on a separate testing set from

the 21st individual participant, iteratively. The optimal threshold was 1.54 (± 0.2) times the SD below

the decoding accuracy on the validation set across participants.

Eye-tracking data analysis:

To see if we could use a less complicated physiological measure to obtain information about the

processing of visual information, and to check that the decoding we observed was not just due to

eye movements, we repeated the above decoding analyses using the eye-tracking data. Specifically,

instead of the MEG sensor data, we decoded the information about the *direction of approach* and

distance to object using x-y coordinates of the right eye fixation provided by the eye-tracker. All

other aspects of the analysis were identical to the 'error data analysis' section. If we observe a

similar decoding of information using the eye-tracking data, it would mean that we could use eye-

tracking, which is a less expensive and more feasible approach for prediction of errors, instead of

MEG. If the prediction from the MEG decoding was stronger than that of the eye tracking, it would

mean that there was information in the neural signal over and above any artefact associated with

eye movement.

Statistical analyses:

To determine the evidence for the null and the alternative hypotheses, we used Bayes analyses as

implemented by Krekelberg (https://klabhub.github.io/bayesFactor/) based on Rouder et al. (2012).

We used standard rules for interpreting levels of evidence (Lee and Wagenmakers, 2014; Dienes,

2014): Bayes factors of >10 and <1/10 were interpreted as strong evidence for the alternative and

null hypotheses, respectively, and >3 and <1/3 were interpreted as moderate evidence for the

alternative and null hypotheses, respectively. We interpreted the Bayes factors which fell between 3

and 1/3 as reflecting insufficient evidence either way.

Specifically, for the behavioural data, we asked whether there was a difference between Active and

Monitoring conditions in terms of miss rates and reaction times. Accordingly, we calculated the

Bayes factor as the probability of the data under alternative (i.e., difference) relative to the null (i.e.,

no difference) hypothesis in each block separately. In the decoding, we repeated the same

procedure to evaluate the evidence for the alternative hypothesis of a difference between decoding

accuracies across conditions (e.g. Active vs. Monitoring and Attended vs. Unattended) vs. the null

hypothesis of no difference between them, at every time point/distance. To evaluate evidence for

the alternative of above-chance decoding accuracy vs. the null hypothesis of no difference from

chance, we calculated the Bayes factor between the distribution of actual accuracies obtained and a

set of 1000 random accuracies obtained by randomising the class labels across the same pair of

conditions (null distribution) at every time point/distance.

To evaluate the evidence for the alternative of main effects of different factors (Attention, Target

Frequency and Time on Task) in decoding, we used Bayes factor ANOVA (Rouder et al., 2012). This

analysis evaluates the evidence for the null and alternative hypothesis as the ratio of the Bayes

factor for the full model ANOVA (i.e., including all three factors of Target Frequency, Attention and

the Time on Task) relative to the restricted model (i.e., including the two other factors while

excluding the factor being evaluated). For example, for evaluating the main effect of Time on Task,

the restricted model included Attention and Target Frequency factors but excluded the factor of

Time on Task.

The priors for all Bayes factor analyses were determined based on Jeffrey-Zellner-Siow priors

(Jeffreys, 1961; Zellner and Siow, 1980) which are from the Cauchy distribution based on the effect

size that is initially calculated in the algorithm using a *t*-test (Rouder et al., 2012). The priors are

data-driven and have been shown to be invariant with respect to linear transformations of

measurement units (Rouder et al., 2012), which reduces the chance of being biased towards the null

or alternative hypotheses.

Results

Behavioural data: The MOM task evokes a reliable vigilance decrement

In the first 110 second experimental block of trials (i.e., excluding the two practice blocks),

participants missed 29% of targets in the Active condition and 40% of targets in the Monitoring

condition. However, the number of targets in any single block is necessarily very low for monitoring

conditions (for a single block, there are 16 targets for Active but only 2 targets for Monitoring). The

pattern does become more robust over blocks, and Figure 2A shows the miss rates changed over

time in different directions for the Active vs. Monitoring conditions. For Active blocks, miss rates

decreased over the first five blocks and then plateaued at ~17%. For Monitoring, however, miss

rates increased throughout the experiment: by the final block, these miss rates were up to 76% (but

again, the low number of targets in Monitoring mean that we should use caution in interpreting the

results of any single block alone). There was evidence that miss rates were higher in the Monitoring

than Active conditions from the 4th block onwards (BF > 3; Figure 2A). Participants' reaction times

(RTs) on correct trials also showed evidence of vigilance decrements, increasing over time under

Monitoring but decreasing under Active task conditions (Figure 2B). There was evidence that

reaction times were slower for Monitoring compared with Active from the sixth block onwards (BF >

3, except for Block #11). The characteristic pattern of increasing miss rates and slower RTs over time

in the Monitoring relative to the Active condition validates the MOM task as effectively evoking

vigilance decrements.

Figure 2. Behavioural performance on the MOM task. The percentage of *miss* trials (A), and *correct* reaction times (B), as a function of block. Thick lines show the average across participants (shading 95% confidence intervals) for Active (blue) and Monitoring (red) conditions. Each block lasted for 110 seconds and had either 16 (Active) or 2 (Monitoring) targets out of 32 cued-colour and 32 non-cued colour dots. Bayes Factors are shown in the bottom section of each graph: Filled circles show moderate/strong evidence for either hypothesis and empty circles indicate insufficient evidence when evaluating the contrast between Active and Monitoring conditions.

Neural data: Decoding different aspects of task-related information

With so much going on in the display at one time, we first needed to verify that we can successfully

decode the major aspects of the moving stimuli, relative to chance. The full data figures and details

are presented in Supplementary Materials: We were able to decode both *direction of approach* and

distance to object relative to chance from MEG signals (see Supplementary Figure 1). Thus, we can

turn to our main question about how these representations were affected by the Target Frequency,

Attention and Time on Task.

The neural correlates of the vigilance decrement

As the behavioural results showed (Figure 2), the difference between Active and Monitoring

conditions increased over time, showing the greatest difference during the final blocks of the

experiment. To explore the neural correlates of these vigilance decrements, we evaluated

information processing in the brain during the first five and last five blocks of each task (called early

and late blocks, respectively) and the interactions between the Target Frequency, Attention and the

Time on Task using a 3-way Bayes factor ANOVA as explained in *Methods*.

Effects of Target Frequency on *direction of approach* information

Direction of approach information is a very clear visual signal ('from the left' vs 'from the right') and

therefore is unlikely to be strongly modulated by other factors, except perhaps whether the dot was

in the cued colour (Attended) or the distractor colour (could be ignored: Unattended). There was

strong evidence for a main effect of Attention (Figure 3A; BF > 10, Bayes factor ANOVA, cyan dots)

starting from 265ms and lasting until dots faded. This is consistent with maintenance of information

about the attended dots and attenuation of the information about unattended dots (Supplementary

Figure 1A). The large difference in coding attributable to attention remained for as long as the dots

were visible.

In contrast, there was no sustained main effect of Target Frequency on the same *direction of*

approach coding (0.1 < BF < 0.3; Bayes factor ANOVA, Figure 3A, pink dots). For the majority of the

epoch there was moderate evidence for the null hypothesis (BF < 1/3). The sporadic time points with

a main effect of Target Frequency, observed a few times before the deflection (3 < BF < 10), likely

reflect noise in the data as there is no clustering. Recall that we only focus on timepoints prior to

deflection, as after this point there are visual differences between Active and Monitoring, with more

dots deflecting in the Monitoring condition.

Figure 3. Impact of different conditions and their interactions on information processing on *correct* trials (all trials except those in which a target was missed or there was a false alarm). (A) Decoding of *direction of approach* information (less task-relevant). The horizontal dashed line refers to theoretical chance-level decoding (50%). Upper graph: Attended dot; Lower graph: Unattended ('distractor') dot. (B) Decoding of *distance to object* information (most task-relevant) and their Bayesian evidence for main effects and interactions. Thick lines show the average across participants (shading 95% confidence intervals). Vertical dashed lines indicate critical times in the trial. Bayes Factors are shown in the bottom section of each graph: Filled circles show moderate/strong evidence for either hypothesis and empty circles indicate insufficient evidence. Main effects and interactions of conditions calculated using Bayes factor ANOVA analysis. Cyan, pink, green and red dots indicate the main effects of Attention, Target frequency, Time on Task and the interaction between Target frequency and Time on Task, respectively. The results of Bayes factor analysis (i.e. the main effects of the three conditions and their interactions) are from the same 3-way ANOVA analysis and therefore identical for attended and unattended panels. Early = data from the first 5 blocks (~10 minutes). Late = data from the last 5 blocks (~10 minutes).

There was also no sustained main effect of the Time on Task on information about the *direction of*

approach (0.1 < BF < 0.3; Bayes factor ANOVA, green dots; Figure 3A). There were no sustained 2-

way or 3-way interactions between Attention, Target Frequency and Time on Task (BF < 1; Bayes

factor ANOVA). Note that the number of trials used in the training and testing of the classifiers were

equalized across the 8 conditions and equalled the minimum available number of trials across those

conditions shown in Figure 3. Therefore, the observed effects cannot be attributed to a difference in

the number of trials across conditions.

Effects of Target Frequency on critical *distance to object* information

The same analysis for the representation of the task-relevant *distance to object* information showed

strong evidence for a main effect of Attention (BF > 10; Bayes factor ANOVA) at all 15 distances,

moderate or strong evidence for a main effect of Time on Task (BF > 3; Bayes factor ANOVA) at eight

of the earlier distances, and an interaction between Time on Task and Target Frequency at two of

these distances (Figure 3B). There was more decoding for attended than unattended dots (compare

top and bottom panels of Figure 3B). The main effect of Time on Task reflected decreased decoding

in later blocks (compare dashed lines to solid lines in Figure 3B). Finally, the interaction between

Target Frequency and Time on Task can be seen when comparing the solid to the dashed lines in

blue and red colours, separately, and suggests a bigger decline in decoding in Monitoring compared

to Active conditions. Note that as there was moderate evidence for no interaction between

Attention and Target Frequency or between Attention and Time on Task (0.1 < BF < 0.3, 2-way Bayes

factor ANOVA) or simultaneously between the three factors (BF < 0.1, 3-way Bayes factor ANOVA),

we do not show those statistical results in the figure.

Together, these results suggest that while vigilance conditions had little or no impact on coding of

the *direction of approach*, they did impact the critically task-relevant information about the distance

of the dot from the object. Coding of this information declined as the time on the task increased and

this effect was more pronounced when the target events happened infrequently.

Is brain connectivity modulated by Attention, Target Frequency and the Time on Task?

Using graph-theory-based univariate connectivity analysis, it has been recently shown that the

connectivity between relevant sensory areas and "vigilance-related" cognitive areas changes prior to

lapses in attention (behavioural misses; Sadaghiani et al., 2015). Therefore, we asked whether

vigilance decrements across the time course of our task corresponded to changes in multi-variate

connectivity, which tracks information transfer, between frontal attentional networks and sensory

visual areas. Specifically, we asked whether there were changes in *information exchange* between

these conditions. We used a simplified version of our method of RSA-based informational

connectivity to evaluate the (Spearman's rank) correlation between distance information RDMs

across the peri-frontal and peri-occipital electrodes (see *Methods*; Goddard et al., 2016; Figure 4A).

Results showed strong evidence (Bayes factor ANOVA, BF = $6.3e^{21}$) for higher informational

connectivity for Attended compared to Unattended trials, and moderate evidence for higher

connectivity in Active compared to Monitoring conditions (Bayes factor ANOVA, BF = 3.4; Figure 4B).

There was insufficient evidence to determine whether there was a main effect of Time on Task

(Bayes factor ANOVA, BF = 0.83). There was moderate evidence for no 2-way and 3-way interactions

between the three factors (Bayes factor ANOVA, 2-way Time on Task-Target Frequency: BF = 0.17;

Time on Task-Attention: BF = 0.16; Target Frequency-Attention: BF = 0.15; their 3-way interactions

BF = 0.12). These results suggest that Monitoring conditions and trials in which the dots are in the

distractor (unattended) colour, in which the attentional load is low, result in less informational

connectivity between occipital and frontal brain areas compared to Active conditions and attended

trials, respectively. This is consistent with a previous study (Alnaes et al., 2015), which suggested

that large-scale functional brain connectivity depends on the attentional load, and might underpin or

accompany the decrease in information decoding across the brain in these conditions (Figure 3B).

Figure 4. Relationship between informational connectivity and Attention, Target Frequency, Time on Task and the behavioural outcome of the trial (i.e., correct vs. miss). (A) Calculation of connectivity using Spearman's rank correlation between RDMs obtained from the peri-frontal and peri-occipital sensors as indicated by colored boxes, respectively. RDMs include decoding accuracies obtained from testing the 105 classifiers trained to discriminate different *distance to object* categories. (B) Connectivity values for the eight different conditions of the task and the results of three-way Bayes factor ANOVA with factors Time on Task (early, late), Attention (attended, unattended) and Target Frequency (active, monitoring), using only correct trials. (C) Connectivity values for the Active and Monitoring, Early and Late blocks of each task for *correct* and *miss* trials (attended condition only) and the result of Bayes factor ANOVA with factors Target Frequency (Active, Monitoring), Time on Task (early, late) and behavioural outcome (correct, miss) as inputs. Number of trials are equalized across conditions in B and C separately. Bars show the average across participants (error bars 95% confidence intervals). Bold fonts indicate moderate or strong evidence for either the effect or the null hypothesis.

We also compared the connectivity for the correct vs. miss trials (Figure 4C). This analysis was

performed only for attended condition as there are no miss trials for unattended condition, by

definition. There was strong evidence for less (almost half) connectivity on *miss* compared to *correct*

trials (Bayes factor ANOVA, BF = 3e^{63}). There was insufficient evidence to determine the effects of

the Time on Task or Target Frequency (Bayes factor ANOVA, BF = 0.33 and BF = 0.35, respectively)

and moderate evidence for a lack of 2-way and 3-way interactions between the three factors (Bayes

factor ANOVA, Behaviour-Target Frequency: BF = 0.17; Behaviour-Time on Task: BF = 0.18; Target

Frequency-Time on Task: BF = 0.16; their 3-way interactions BF = 0.11). Weaker connectivity

between occipital and frontal areas could have led to the behavioural misses observed in this study

(Figure 1) as was previously reported in an auditory monitoring task using univariate graph-theoretic

connectivity analyses (Sadaghiani et al., 2015), although, of course, these are correlational data and

so we cannot make any strong causal inferences. These results cannot be explained by the number

of trials as they are equalized across the 8 conditions in each of the analyses separately.

Can we use the neural data to predict behavioural errors before they occur?

Is neural information processing different on *miss* trials?

The results presented in Figure 3, which used only *correct* trials, showed changes due to target

frequency to the representation of task-relevant information when the task was performed

successfully. We next move on to our second question, which is whether these neural

representations change when overt behaviour *is* affected, and therefore, whether we can use the

neural activity as measured by MEG to predict behavioural errors before they occur. We used our

method of error data analysis (Woolgar et al., 2019) to examine whether the patterns of information

coding on miss trials differed from correct trials (see *Methods*). For these analyses we used only

attended dots, as unattended dots do not have behavioural responses, and we matched the total

number of trials in our implementation of correct and miss classification.

First, we evaluated the processing of the less relevant information - the *direction of approach*

measure (Figure 5A). The results for *correct* trials provided information dynamics very similar to the

attended condition in Figure 3A, except for higher overall decoding, which is explained by the

inclusion of the data from the whole experiment (15 blocks) rather than just the five early and late

blocks (note the number of trials is still matched to miss trials).

Figure 5. Decoding of information on *correct* vs. *miss* trials. (A) Decoding of *direction of approach* information (less task-relevant). (B) Decoding of *distance to object* information (most task-relevant). The horizontal dashed lines refer to chance-level decoding. Top panels: Decoding using correct trials; Bottom panels: Decoding using miss trials. In both top and bottom panels, the classifiers were trained on *correct* trials and tested on (left out) *correct* and all *miss* trials, respectively. Thick lines show the average across participants (shading 95% confidence intervals). Vertical dashed lines indicate critical events in the trial. Bayes Factors are shown in the bottom section of each graph: Filled circles show moderate/strong evidence for either hypothesis and empty circles indicate insufficient evidence. They show the results of Bayes factor analysis when evaluating the difference of the decoding values from chance for Active (blue) and Monitoring (red) conditions separately, the comparison of the two conditions (green) and the comparison of correct and miss trials (black). Note that for the comparison of correct and miss trials, Active and Monitoring conditions were averaged separately.

Active and Monitoring conditions did not show any time windows of sustained difference (BF < 0.3).

However, when the classifiers were tested on *miss* trials, from onset to deflection, the pattern of

information dynamics were different, even though we had matched the number of trials.

Specifically, while the level of information was comparable to *correct* trials with spurious instances

(but no sustained time windows) of difference (BF > 3 as indicated by black dots) before 500 ms,

decoding traces were much noisier for *miss* trials with more variation across trials and between

nearby time points (Figure 5A). Note that after the deflection, the visual signal is different for correct

and miss trials, so the difference between their decoding curves (BF > 3) is not meaningful. These

results suggest a noisier processing of *direction of approach* information for the missed dots

compared to correctly deflected dots.

We then repeated the same procedure on the processing of the most task-relevant *distance to*

object information on *correct* vs. *miss* trials (Figure 5B). Although on *correct* trials, the distance

information for both Active and Monitoring conditions was well above chance (77%; BF > 10), for

miss trials, the corresponding distance information was only just above chance (55%; BF > 10 for all

distances except one). The direct comparison revealed that distance information dropped

considerably on *miss* trials compared to *correct* trials (Figure 5; Black dots; BF > 10 across all

distances; Active and Monitoring results were averaged for correct and miss trials separately before

Bayes analyses). This is consistent with less representation of the crucial information about the

distance from the object preceding a behavioural miss.

Can we predict behavioural errors using neuroimaging?

Finally, we asked whether we could use this information to predict the behavioural outcome of each

trial. To do so, we developed a new method that classified trials based on their behavioural

outcomes (correct vs. miss) by asking how well a set of classifiers, pre-trained on correct trials,

would classify the distance of the dot from the target (see *Methods*; Figure 6A). To achieve this, we

used a second-level classifier which labelled a trial as correct or miss based on the average

accumulated accuracies obtained for that dot at every distance from the first-level decoding

classifiers which were trained on *correct* trials (Figure 6A and 6B; see *Methods*). If the accumulated

accuracy for the given dot at the given distance was less than the average accuracy obtained from

testing on the validation set minus a specific threshold (based on standard deviation), the testing dot

(trial) was labelled as *correct*, otherwise *miss*. As Figure 6B shows, there was strong evidence (BF >

10) that decoding accuracy of distances was higher for *correct* than *miss* trials with the inclusion of

more classifier accuracies as the dot approached from the corner of the screen towards the centre

with a multiple of around 1.5 as threshold (Figure 6C). This clear separation of accumulated

accuracies for *correct* vs. *miss* trials allowed us to predict with above-chance accuracy the

behavioural outcome of the ongoing trial (Figure 6D). To find the optimal threshold for each

participant, we evaluated the thresholds used for all other participants except for a single testing

participant for whom we used the average of the best thresholds that led to highest prediction

accuracy for other participants. This was ~1.5 standard deviation below the average accuracy on the

other participants' validation (correct trial) sets (Figure 6C).

The prediction accuracy of behavioural outcome was above chance level (68% vs. 50%; BF > 10) even

when the dot had only been on the screen for 80ms, which corresponds to our furthest distance #15

(1200ms prior to deflection point; Figure 6D). The accuracy increased to 85% as the dot approached

the centre of the screen, with ~80% accuracy with still 800 ms to go before required response.

Importantly, the prediction algorithm showed generalisable results across participants; the threshold

for decision obtained from the other participants could predict the accuracy of an independent

participant's behaviour using only their neural data.

Figure 6. Prediction of behavioural outcome (*correct* vs. *miss*) trial-by-trial using decoding of *distance to object* information. (A) Sample classifiers' accuracies (correct or incorrect classification of current distance as indicated by colors) for a *miss* (left panel; average accuracy ~= 43% when the dot reached the deflection point) and a *correct* trial (right panel; average accuracy ~=67% at the deflection point). The classifiers were trained on the data from *correct* trials and tested on the data from *correct* and *miss* trials. For the *miss* trials, around half the classifiers classified the dot's distance incorrectly by the time it reached the deflection point. (B) Accumulation of classifiers' accuracies over decreasing dot distances/time to deflection. This shows stronger information coding of the crucial *distance to object* information on the *correct* trials over *miss* trials. A variable threshold used in (C) is shown as a blue dashed line. (C) Prediction of behavioural outcome as a function of threshold and distance using a second-level behavioural outcome classification. Results show highest prediction accuracies on the participant set at around the threshold of 1.5 (see *Methods*), increasing at closer distances. (D) Accuracy of predicting behavioural outcome for the left-out participant using the threshold obtained from all the other participants as function of distance/time from the deflection point. Results showed successful (~=70%) prediction of behavioural outcome of the trial as early as 80 ms after stimulus appearance. Thick lines and shading refer to average and one standard deviation around the mean across participants, respectively. Bayes Factors are shown in the bottom section of each graph: Filled circles show moderate/strong evidence for either hypothesis and empty circles indicate insufficient evidence (black dots under B and D).

Please note that the results presented so far were from *correct* and *miss* trials and we excluded

early, late and wrong-colour *false alarms* to be more specific about the error type. However, the

false alarm results (collapsed across all three types of false alarms) were very similar (Supplementary

Figure 2) to those of the missed trials (Figure 5): noisy information about the *direction of approach*

and at-chance information about the *distance to object*. This may suggest that both miss and false

alarm trials are caused by a similar impaired processing of information, or at least captured similarly

by our decoding methods. The average number of miss trials was 58.17 (±21.63 SD) and false alarm

trials was 65.94 (±21.13 SD; out of 1920 trials).

Can we decode direction and distance information from eye-tracking data?

To see whether we could decode information about the dot motion using only the eye-tracking data,

we repeated the same error data analysis as above, but this time using the 2-dimensional signals

(i.e., corresponding to the x-y coordinates of the gaze location) provided by the eye-tracker (Görgen

et al., 2018). The decoding of *direction of approach* from *correct* trials showed above-chance

information (Supplementary Figure 3A) starting from 455 and 460 ms post-stimulus onset for the

Active and Monitoring conditions (BF > 10), respectively. The information on *miss* trials was noisier

but showed a similar pattern. The correct and miss trials only showed moderate evidence (3 < BF <

10) for difference in the span from 310 ms to 490 ms. This suggests that participants moved their

eyes differently for the dots approaching from opposite directions, which is not unexpected (and

observed in the eye-tracking fixation points data). Although the dynamics of this decoding over time

is different to the neural decoding, in line with visually evoked information decoding studies

(VanRullen, 2007; Karimi-Rouzbahani et al., 2017), the eye-movement data do hold enough

information to decode the *direction of approach*.

In contrast, for the crucial *distance to object* measure, although the eye-tracking data showed

above-chance values at a few distances (BF > 10; Supplementary Figure 3B), most were very close to

chance and much lower than those obtained from the neural data (cf. Figure 5B; BF > 10 for the

difference between decoding of neural vs eyetracking data for correct trials; indicated by black dots

in Supplementary Figure 3A). Only for the decoding for *miss* vs. *correct* trials was there any evidence

(moderate) for similarity between neural and eyetracking data (0.1 < BF < 0.3; black dots;

Supplementary Figure 3B). Note that *distance to object* data collapses across identical distances from

the left and right sides of the screen, which avoids the potential confound of eye-movements data

driving the classifier for this crucial distance measure.

Discussion

This study developed new methods to gain insights into how attention, the frequency of target

events, and the time doing a task affect the representation of task information in the brain. Our new

multiple object monitoring (MOM) task evoked reliable vigilance decrements in both accuracy and

reaction time in a situation that more closely resembles real-life modern tasks than classic vigilance

tasks. By using the sensitive analysis method of MVPA, we were able to test information coding

across task conditions to evaluate the neural correlates of vigilance decrements. We also developed

a novel informational brain connectivity method, which allowed evaluation of the correlation

between information coding across peri-occipital and peri-frontal areas in different task conditions,

to investigate the brain connectivity under different levels of attention, target frequency and the

time on the task. Finally, we utilised our recent error data analysis to predict forthcoming

behavioural misses with high accuracy. In the following sections, we explain each of the four

contributions in detail and compare them with relevant literature.

First, the MOM task includes key features of real-world monitoring situations that are not usually

part of other vigilance tasks (e.g., Mackworth, 1948; Temple, 2000; Rosvold et al., 1956; Rosenberg

et al., 2013), and the results show clear evidence of vigilance decrements. Behavioural performance,

measure with both reaction time and accuracy, deteriorated over time in monitoring (infrequent

target) relative to active (frequent target) conditions. These vigilance decrements demonstrate that

the MOM task can be used to explore vigilance in situations more closely resembling modern

environments, namely involving moving stimuli and selection of relevant from irrelevant

information, giving a useful tool for future research.

Second, the high sensitivity of MVPA to extract information from neural signals allowed us to

investigate the temporal variations in processing as the experiment progressed. The manipulation of

attention showed a strong overall effect with enhanced representation of both the less important

direction of approach and the most task-relevant *distance to object* information for cued dots,

regardless of how frequent the targets were (Figure 3). The improved representation of information

under attention extends previous findings from us and others (Woolgar et al., 2015b; Goddard et al.,

2019; Nastase et al., 2017) to moving displays, in which the participants monitor multiple objects

simultaneously.

The manipulation of target frequency showed that when participants only had to respond

infrequently, modelling real-life monitoring situations, the neural coding of crucial information about

the task dropped, correlating with the decrease in behavioural performance (i.e., vigilance effects in

both accuracy and RT; Figure 2). This suggests that when people monitor for rare targets, they

process or encode the relevant information less effectively as the time passes relative to conditions

in which they are actively engaged in completing the task. Several previous studies have examined

the neural correlates of vigilance decrements using univariate analyses (for a review see Langner et

al. (2013)). However, univariate analyses fail to capture widespread but subtle differences of

patterns between conditions across distant brain networks. One recent study utilized the sensitivity

of MVPA to extract task-relevant and task-irrelevant information under sustained attention (Megan

et al., 2015). In this case, however, the aspects of information were similar in identity (i.e. high-level

visual categories of face and scenes) and switched their attentional role (i.e. attended vs.

unattended) across the experiment, which makes it difficult to see whether (if at all) vigilance

decrements would differentially affect encoding of different aspects of information depending on

their relevance to the task. To address this issue, here we not only switched the task-relevance of

information across the experiment to replicate the attentional effect of that study (i.e. cued/un-cued

dots), but we also studied two aspects of the dot motion information that varied in importance for

carrying out the task (i.e., *direction of approach* and *distance to object*) with unchanging roles across

the experiment. While switching between dot colours showed the effect of attention, with greater

representation of the cued dots over uncued dots, the relevance of the *direction of approach* and

the *distance to object* did not vary. The less relevant direction information was unaffected by target

frequency, whereas the coding of the critical task-relevant distance information correlated with the

decrease in behavioural performance over time. This is relevant to theories of vigilance, by

demonstrating that the task-relevance of information might be a major factor in whether vigilance

decrements occur.

It is important to note that previous studies have tried other physiological/behavioural measures to

determine participants' vigilance or alertness, such as pupil size (Yoss et al., 1970), response time

variability (Rosenberg et al., 2013), blood pressure and thermal energy (Lohani et al., 2019) or even

body temperature (Molina et al., 2019). We used highly-sensitive analysis of neuroimaging data so

that we could address two questions that could not be answered using these more general vigilance

measures. Our approach allowed us to test for changes in the way information is processed in the

brain, particularly testing for differences in the impact of monitoring on the relevance of the

information, rather than whether the participants were vigilant and alert in general. Moreover, we

could also investigate how relevant and less relevant information was affected by the target

frequency and time on the task, which could explain the behavioural vigilance decrement observed

in many previous studies (e.g., Dehais et al., 2019; Wolfe et al., 2005; Wolfe et al., 2007; Kamzanova

et al., 2014; Ishibashi et al., 2012). We tested our methods also on the eye-tracking data and found

that the critical task-relevant information change under monitoring conditions could not be

replicated based on eye-movements, demonstrating the benefit of the neural approach.

Third, our information-based brain connectivity method showed weaker connectivity between the

peri-frontal attentional network and the peri-occipital visual areas of the brain in the unattended

and monitoring conditions (Figure 4), where participants encountered fewer targets relative to the

other conditions. We also observed less connectivity between the same areas on *miss* vs. *correct*

trials, which might explain the behavioural outcome of the trials. Most previous neuroimaging

studies have used univariate brain connectivity analyses, which are prone to missing existing

functional connectivity across areas when encountering low-amplitude activity on individual sensors

(Anzellotti & Coutanche, 2018; Basti et al., 2020). The method we used here evaluated the

correlation between representational dissimilarity matrices, which has provided high-dimensional

information about *distance to object*, obtained from multiple sensors across the brain areas. This

makes the analysis more sensitive to capturing subtle connectivity and also aligns with a major

recent shift in literature from univariate to multivariate informational connectivity analyses

(Goddard et al., 2016; Goddard et al., 2019; Karimi-Rouzbahani et al., 2019; Karimi-Rouzbahani,

2017; Anzellotti & Coutanche, 2018; Basti et al., 2020).

Fourth, building upon our recently-developed method of error analysis (Woolgar et al., 2019), we

were able to predict forthcoming behavioural misses before the response was given. This method

only used *correct* trials for training, which makes its implementation plausible for real-world

situations since we usually have plenty of correct trials and only few miss trials (i.e., cases when the

railway controller diverts the trains correctly vs. misses and a collision happens). In our study, the

method showed a large decline in the crucial task-relevant (i.e., *distance to object*) information

decoding on *miss* vs. *correct* trials but less decline in the less task-relevant information (i.e., *direction*

of approach). A complementary analysis allowed the prediction of behaviourally missed trials as

soon as the stimulus appeared on the screen (after ~80 ms), which was ~1200 ms before the time of

response. This method was generalisable across participants, with the decision threshold for trial

classification other participants' data successful in predicting errors for a left-out participant. A

number of previous studies have shown that behavioural performance could be correlated with

aspects of brain activity even before the stimulus onset (Eichele et al., 2008; Weissman et al., 2006;

Sadaghiani et al., 2015). This can be crucial for many high-risk environments, including semi-

autonomous car driving and railway control. Those studies have explained the behavioural errors by

implicit measures such as less deactivation of the default-mode network, reduced stimulus-evoked

sensory activity (Weissman et al., 2006; Eichele et al., 2008) and even the connectivity between

sensory and vigilance-related/default-mode brain areas (Sadaghiani et al., 2015). It would be

informative, however, if they could show how (if at all) the processing of task-relevant information is

disrupted in the brain and how this might lead to behavioural errors. To serve an applied purpose, it

would be ideal if there was a procedure to use those neural signatures to predict behavioural

outcomes. Only two previous studies have approached this goal. Sadaghiani et al. (2015) and Dehais

et al. (2019) reported maximum prediction accuracies of 63% and 72% (with adjusted chance levels

of 55% and 59%, respectively), far lower than what we have obtained here (up to 85% with a chance

level of 50%), suggesting our method accesses more relevant neural signatures of vigilance

decrements, or is more sensitive in discriminating these. The successful prediction of an error from

neural data more than a second in advance of the impending response provides a promising avenue

for detecting lapses of attention before any consequences occur.

Current explanations for vigilance effects generally fall into two categories: mind-wandering and

cognitive overload. In the first, the low cognitive demands of monitoring tasks result in mind-

wandering and then, when a response is required, there are insufficient resources dedicated to the

task (e.g., malleable attention theory (Manly et al., 1999; Smallwood et al., 2006; Young et al.,

2002)). In the second, the demands of sustaining attention depletes cognitive resources over time

leading to insufficient resources and increased errors in later stages of the task (e.g., Helton et al.,

2008; Helton et al., 2011; Warm et al., 2008). There are several previous observations of decreased

functional connectivity during mind wandering (Chou et al., 2017; Kucyi et al., 2018; van Son et al.,

2019), which our informational connectivity results broadly replicate. For example, Chou et al.

(2017) reported a decrease in functional connectivity between visual and sensorimotor and in turn

to frontal brain areas in later stages of a resting-state mind-wandering fMRI study in which

participants were instructed to draw their mind to specific but broad sets of thoughts. In another

study, using EEG-fMRI, von Son et al. (2019) found reduced functional connectivity between the

dorsolateral PFC, dorsal anterior cingulate cortex (ACC), and posterior parietal regions, namely the

"executive control network", when participants counted and reported their number of inhales and

episodes of mind wandering. Our finding of a decrease in higher order cognitive (peri-frontal) and

sensory (peri-occipital) areas in later (compared with early) stages of the experiment is broadly

consistent with these findings, but we are unable to distinguish whether this is due to mind

wandering or the depletion of cognitive resources, as in our task either is a plausible explanation for

the effect.

The overall goal of this study was to understand how neural information processing of dynamic

displays were affected by attention and target frequency, and whether reliable changes in behaviour

over time could be predicted on the basis of neural patterns. We observed that the neural

representation of critically relevant information in the brain decreases over time, especially when

targets are infrequent. This neural representation was particularly poor on trials where participants

missed the target. We used this observation to predict behavioural outcome of individual trials, and

showed that we could accurately predict behavioural outcome more than a second before action

was needed. These results provide new insights about how vigilance decrements impact information

coding in the brain and propose an avenue for predicting behavioural errors using novel

neuroimaging analysis techniques.

Acknowledgments

782 This work was funded by an Australian Research Council (ARC) Discovery Project grant to A.N.R and

783 A.W. (DP170101780). A.W. was supported by an ARC Future Fellowship (FT170100105) and MRC

784 intramural funding SUAG/052/G101400. We thank Denise Moerel, Mark Wiggins, Jeremy Wolfe and

785 William Helton for contributions to an earlier design of the MOM task.

References

Adler, C. M., Sax, K. W., Holland, S. K., Schmithorst, V., Rosenberg, L., & Strakowski, S. M. (2001). Changes
in neuronal activation with increasing attention demand in healthy volunteers: an fMRI study. Synapse, 42(4),
266-272.

Alnaes, D., Kaufmann, T., Richard, G., Duff, E. P., Sneve, M. H., Endestad, T., ... & Westlye, L. T. (2015).
Attentional load modulates large-scale functional brain connectivity beyond the core attention networks.
Neuroimage, 109, 260-272.

Anzellotti, S., & Coutanche, M. N. (2018). Beyond functional connectivity: investigating networks of
multivariate representations. Trends in cognitive sciences, 22(3), 258-269.

Basti, A., Nili, H., Hauk, O., Marzetti, L., & Henson, R. (2020, February 11). Multivariate connectivity: a
conceptual and mathematical review. https://doi.org/10.31219/osf.io/2q9v4

Baillet, S. (2017). Magnetoencephalography for brain electrophysiology and imaging. Nature neuroscience,
20(3), 327-339.

Benedict, R. H., Shucard, D. W., Maria, M. P. S., Shucard, J. L., Abara, J. P., Coad, M. L., ... & Lockwood, A.
(2002). Covert auditory attention generates activation in the rostral/dorsal anterior cingulate cortex. Journal of
Cognitive Neuroscience, 14(4), 637-645.

Brainard, D. H. (1997). The psychophysics toolbox. Spatial vision, 10(4), 433-436.

Chou, Y. H., Sundman, M., Whitson, H. E., Gaur, P., Chu, M. L., Weingarten, C. P., ... & Diaz, M. T. (2017).
Maintenance and representation of mind wandering during Resting-State fMRI. Scientific reports, 7, 40722.

Coull, J. T., Frith, C. D., Frackowiak, R. S. J., & Grasby, P. M. (1996). A fronto-parietal network for rapid
visual information processing: a PET study of sustained attention and working memory. Neuropsychologia,
34(11), 1085-1095.

Dehais, F., Roy, R. N., & Scannella, S. (2019). Inattentional deafness to auditory alarms: Inter-individual
differences, electrophysiological signature and single trial classification. Behavioural brain research, 360, 51-59.

Dienes, Z. (2014). Using Bayes to get the most out of non-significant results. Frontiers in psychology, 5, 781.

Duncan, J. (2010). The multiple-demand (MD) system of the primate brain: mental programs for intelligent
behaviour. Trends in cognitive sciences, 14(4), 172-179.

Duncan, J., & Owen, A. M. (2000). Common regions of the human frontal lobe recruited by diverse cognitive
demands. Trends in neurosciences, 23(10), 475-483.

Eichele, H., Juvodden, H., Ullsperger, M., & Eichele, T. (2010). Mal-adaptation of event-related EEG responses
preceding performance errors. Frontiers in human neuroscience, 4, 65.

Eichele, T., Debener, S., Calhoun, V. D., Specht, K., Engel, A. K., Hugdahl, K., ... & Ullsperger, M. (2008).
Prediction of human errors by maladaptive changes in event-related brain networks. Proceedings of the National
Academy of Sciences, 105(16), 6173-6178.

Fedorenko, E., Duncan, J., & Kanwisher, N. (2013). Broad domain generality in focal regions of frontal and
parietal cortex. Proceedings of the National Academy of Sciences, 110(41), 16616-16621.

Gilbert, S. J., Simons, J. S., Frith, C. D., & Burgess, P. W. (2006). Performance-related activity in medial rostral
prefrontal cortex (area 10) during low-demand tasks. Journal of Experimental Psychology: Human Perception
and Performance, 32(1), 45.

Goddard, E., Carlson, T. A., & Woolgar, A. (2019). Spatial and feature-selective attention have distinct effects
on population-level tuning. bioRxiv, 530352.

Goddard, E., Carlson, T. A., Dermody, N., & Woolgar, A. (2016). Representational dynamics of object
recognition: Feedforward and feedback information flows. Neuroimage, 128, 385-397.

Görgen, K., Hebart, M. N., Allefeld, C., & Haynes, J. D. (2018). The same analysis approach: Practical
protection against the pitfalls of novel neuroimaging analysis methods. Neuroimage, 180, 19-30.

Greicius, M. D., Krasnow, B., Reiss, A. L., & Menon, V. (2003). Functional connectivity in the resting brain: a
network analysis of the default mode hypothesis. Proceedings of the National Academy of Sciences, 100(1),
253-258.

Greicius, M. D., Supekar, K., Menon, V., & Dougherty, R. F. (2009). Resting-state functional connectivity
reflects structural connectivity in the default mode network. Cerebral cortex, 19(1), 72-78.

Grootswagers, T., Wardle, S. G., & Carlson, T. A. (2017). Decoding dynamic brain patterns from evoked
responses: A tutorial on multivariate pattern analysis applied to time series neuroimaging data. Journal of
cognitive neuroscience, 29(4), 677-697

Helton, W. S., & Russell, P. N. (2011). Feature absence–presence and two theories of lapses of sustained
attention. Psychological research, 75(5), 384-392.

Helton, W. S., & Warm, J. S. (2008). Signal salience and the mindlessness theory of vigilance. Acta
psychologica, 129(1), 18-25.

Indovina, I., & Macaluso, E. (2004). Occipital–parietal interactions during shifts of exogenous visuospatial
attention: trial-dependent changes of effective connectivity. Magnetic resonance imaging, 22(10), 1477-1486.

Ishibashi, K., Kita, S., & Wolfe, J. M. (2012). The effects of local prevalence and explicit expectations on
search termination times. Attention, Perception, & Psychophysics, 74(1), 115-123.

Jeffreys, H. (1961). Theory of probability (3rd ed.). New York: Oxford University Press.

Johannsen, P., Jakobsen, J., Bruhn, P., Hansen, S. B., Gee, A., Stødkilde-Jørgensen, H., & Gjedde, A. (1997).
Cortical sites of sustained and divided attention in normal elderly humans. Neuroimage, 6(3), 145-155.

Kamzanova, A. T., Kustubayeva, A. M., & Matthews, G. (2014). Use of EEG workload indices for diagnostic
monitoring of vigilance decrement. Human factors, 56(6), 1136-1149.

Karimi-Rouzbahani, H. (2018). Three-stage processing of category and variation information by entangled
interactive mechanisms of peri-occipital and peri-frontal cortices. Scientific reports, 8(1), 1-22.

Karimi-Rouzbahani, H., Bagheri, N., & Ebrahimpour, R. (2017). Hard-wired feed-forward visual mechanisms
of the brain compensate for affine variations in object recognition. Neuroscience, 349, 48-63.

Karimi-Rouzbahani, H., Vahab, E., Ebrahimpour, R., & Menhaj, M. B. (2019). Spatiotemporal analysis of
category and target-related information processing in the brain during object detection. Behavioural brain
research, 362, 224-239.

Kleiner, M., Brainard, D., & Pelli, D. (2007). What's new in Psychtoolbox-3?

Kriegeskorte, N., Mur, M., & Bandettini, P. A. (2008). Representational similarity analysis-connecting the
branches of systems neuroscience. Frontiers in systems neuroscience, 2, 4.

Kucyi, A. (2018). Just a thought: How mind-wandering is represented in dynamic brain connectivity.
Neuroimage, 180, 505-514.

Langner, R., & Eickhoff, S. B. (2013). Sustaining attention to simple tasks: a meta-analytic review of the neural
mechanisms of vigilant attention. Psychological bulletin, 139(4), 870.

Lee, M., & Wagenmakers, E. J. (2005). Bayesian statistical inference in psychology: comment on Trafimow
(2003). Psychological Review, 112, 662–668.

Lohani, M., Payne, B. R., & Strayer, D. L. (2019). A review of psychophysiological measures to assess
cognitive states in real-world driving. Frontiers in human neuroscience, 13.

Mackworth, N. H. (1948). The breakdown of vigilance during prolonged visual search. Quarterly Journal of
Experimental Psychology, 1(1), 6-21.

Manly, T., Robertson, I. H., Galloway, M., & Hawkins, K. (1999). The absent mind: further investigations of
sustained attention to response. Neuropsychologia, 37(6), 661-670.

Mazaheri, A., Nieuwenhuis, I. L., Van Dijk, H., & Jensen, O. (2009). Prestimulus alpha and mu activity predicts
failure to inhibit motor responses. Human brain mapping, 30(6), 1791-1800.

Megan, T. D., Cohen, J. D., Lee, R. F., Norman, K. A., & Turk-Browne, N. B. (2015). Closed-loop training of
attention with real-time brain imaging. Nature neuroscience, 18(3), 470.

Molina, E., Sanabria, D., Jung, T. P., & Correa, A. (2019). Electroencephalographic and peripheral temperature
dynamics during a prolonged psychomotor vigilance task. Accident Analysis & Prevention, 126, 198-208.

Nastase, S. A., Connolly, A. C., Oosterhof, N. N., Halchenko, Y. O., Guntupalli, J. S., Visconti di Oleggio
Castello, M., ... & Haxby, J. V. (2017). Attention selectively reshapes the geometry of distributed semantic
representation. Cerebral Cortex, 27(8), 4277-4291.

O'Connell, R. G., Dockree, P. M., Robertson, I. H., Bellgrove, M. A., Foxe, J. J., & Kelly, S. P. (2009).
Uncovering the neural signature of lapsing attention: electrophysiological signals predict errors up to 20 s before
they occur. Journal of Neuroscience, 29(26), 8604-8611.

Ortuno, F., Ojeda, N., Arbizu, J., Lopez, P., Martı-Climent, J. M., Penuelas, I., & Cervera, S. (2002). Sustained
attention in a counting task: normal performance and functional neuroanatomy. Neuroimage, 17(1), 411-420.

Périn, B., Godefroy, O., Fall, S., & De Marco, G. (2010). Alertness in young healthy subjects: an fMRI study of
brain region interactivity enhanced by a warning signal. Brain and cognition, 72(2), 271-281.

Raichle, M. E. (2015). The brain's default mode network. Annual review of neuroscience, 38, 433-447.

Rich, A. N., Kunar, M. A., Van Wert, M. J., Hidalgo-Sotelo, B., Horowitz, T. S., & Wolfe, J. M. (2008). Why
do we miss rare targets? Exploring the boundaries of the low prevalence effect. Journal of Vision, 8(15), 15-15.

Rosenberg, M., Noonan, S., DeGutis, J., & Esterman, M. (2013). Sustaining visual attention in the face of
distraction: a novel gradual-onset continuous performance task. Attention, Perception, & Psychophysics, 75(3),
426-439.

Rosvold, H. E., Mirsky, A. F., Sarason, I., Bransome Jr, E. D., & Beck, L. H. (1956). A continuous performance
test of brain damage. Journal of consulting psychology, 20(5), 343.

Rouder, J. N., Morey, R. D., Speckman, P. L., & Province, J. M. (2012). Default Bayes factors for ANOVA
designs. Journal of Mathematical Psychology, 56(5), 356-374.

Sadaghiani, S., Poline, J. B., Kleinschmidt, A., & D'Esposito, M. (2015). Ongoing dynamics in large-scale
functional connectivity predict perception. Proceedings of the National Academy of Sciences, 112(27), 8463-
8468.

Schnell, K., Heekeren, K., Schnitker, R., Daumann, J., Weber, J., Heßelmann, V., ... & Gouzoulis-Mayfrank, E.
(2007). An fMRI approach to particularize the frontoparietal network for visuomotor action monitoring:
detection of incongruence between test subjects' actions and resulting perceptions. Neuroimage, 34(1), 332-341.

Smallwood, J., & Schooler, J. W. (2006). The restless mind. Psychological bulletin, 132(6), 946.

Sturm, W., De Simone, A., Krause, B. J., Specht, K., Hesselmann, V., Radermacher, I., ... & Willmes, K.
(1999). Functional anatomy of intrinsic alertness: evidencefor a fronto-parietal-thalamic-brainstem network in
theright hemisphere. Neuropsychologia, 37(7), 797-805.

Tana, M. G., Montin, E., Cerutti, S., & Bianchi, A. M. (2010). Exploring cortical attentional system by using
fMRI during a Continuous Perfomance Test. Computational intelligence and neuroscience, 2010.

Temple, J. G., Warm, J. S., Dember, W. N., Jones, K. S., LaGrange, C. M., & Matthews, G. (2000). The effects
of signal salience and caffeine on performance, workload, and stress in an abbreviated vigilance task. Human
factors, 42(2), 183-194.

Thakral, P. P., & Slotnick, S. D. (2009). The role of parietal cortex during sustained visual spatial attention.
Brain Research, 1302, 157-166.

van Son, D., de Rover, M., De Blasio, F. M., van der Does, W., Barry, R. J., & Putman, P. (2019).
Electroencephalography theta/beta ratio covaries with mind wandering and functional connectivity in the
executive control network. Annals of the New York Academy of Sciences, 1452(1), 52.

VanRullen, R. (2007). The power of the feed-forward sweep. Advances in Cognitive Psychology, 3(1-2), 167.

Warm, J. S., Parasuraman, R., & Matthews, G. (2008). Vigilance requires hard mental work and is stressful.
Human factors, 50(3), 433-441.

Weissman, D. H., Roberts, K. C., Visscher, K. M., & Woldorff, M. G. (2006). The neural bases of momentary
lapses in attention. Nature neuroscience, 9(7), 971-978.

Wingen, M., Kuypers, K. P., van de Ven, V., Formisano, E., & Ramaekers, J. G. (2008). Sustained attention and
serotonin: a pharmaco-fMRI study. Human Psychopharmacology: Clinical and Experimental, 23(3), 221-230.

Wolfe, J. M., Horowitz, T. S., & Kenner, N. M. (2005). Rare items often missed in visual searches. Nature,
435(7041), 439-440.

Wolfe, J. M., Horowitz, T. S., Van Wert, M. J., Kenner, N. M., Place, S. S., & Kibbi, N. (2007). Low target
prevalence is a stubborn source of errors in visual search tasks. Journal of experimental psychology: General,
136(4), 623.

Woolgar, A., Afshar, S., Williams, M. A., & Rich, A. N. (2015a). Flexible coding of task rules in frontoparietal
cortex: an adaptive system for flexible cognitive control. Journal of cognitive neuroscience, 27(10), 1895-1911.

Woolgar, A., Dermody, N., Afshar, S., Williams, M. A., & Rich, A. N. (2019). Meaningful patterns of
information in the brain revealed through analysis of errors. bioRxiv, 673681.

Woolgar, A., Hampshire, A., Thompson, R., & Duncan, J. (2011). Adaptive coding of task-relevant information
in human frontoparietal cortex. Journal of Neuroscience, 31(41), 14592-14599.

Woolgar, A., Williams, M. A., & Rich, A. N. (2015b). Attention enhances multi-voxel representation of novel
objects in frontal, parietal and visual cortices. Neuroimage, 109, 429-437.

Yoss, R. E., Moyer, N. J., & Hollenhorst, R. W. (1970). Pupil size and spontaneous pupillary waves associated
with alertness, drowsiness, and sleep. Neurology, 20(6), 545-545.

Young, M. S., & Stanton, N. A. (2002). Malleable attentional resources theory: a new explanation for the effects
of mental underload on performance. Human factors, 44(3), 365-375.

Zellner, A., & Siow, A. (1980). Posterior odds ratios for selected regression hypotheses. In J.M. Bernardo, M.H.
DeGroot, D.V. Lindley, A.F.M. Smith (Eds.), Bayesian Statistics: proceedings of the first international meeting
held in Valencia (Spain) (585–603). University of Valencia.

Supplementary Material

Supplementary figure 1 shows the same decoding results as presented in Figure 3 but evaluated against chance-level decoding (50%).

Our first analysis was to verify that our analyses could decode the important aspects of the display, relative to chance, given the overlapping moving stimuli. Here, we give the detailed results of this analysis.

We started with the information about the *direction of approach* (top left or bottom right of screen) which is a strong visual signal but not critical to the task decision. From 95 ms post-stimulus onset onwards, this visual information could be decoded from the MEG signal for all combinations of the factors: Attended and Unattended dots, both Target Frequency conditions (Active, Monitoring), and both our Time on Task durations (Early - first 5 blocks; Late - last 5 blocks; all BF > 10, different from chance).

All conditions were decodable above chance until at least 385 ms post-stimulus onset (BF > 3; Supplementary Figure 1A), which was when the dots came closer to the centre, losing their visual difference. There was a rapid increase in information about the *direction of approach* between 50 ms to 150 ms post-stimulus onset, consistent with an initial forward sweep of visual information processing (VanRullen, 2007; Karimi-Rouzbahani et al., 2017; Karimi-Rouzbahani et al., 2019). For attended dots only (but regardless of the Target Frequency or Time on Task), the information then increased again before the deflection time, and remained different from chance until 1915 ms post-stimulus onset, which is just before the dot faded (Supplementary Figure 1A). The second rise of decoding, which was more pronounced for the attended dots, could reflect the increasing relevance to the task as the dot approached the crucial deflection point, but it could also be due to higher visual acuity in foveal compared to peripheral areas of the visual field. The decoding peak observed

999 after the deflection point for the attended dots, was most probably caused by the large visual

1000 difference between the deflection trajectories for the dots approaching from the left vs. right side of

1001 the screen (see the deflection trajectories in Figure 1A).

1002

The most task-relevant feature of the motion is the distance between the moving dot and the

central object, with the deflection point of the trajectories being the key decision point. We

therefore tested for decoding of distance information (*distance to object,* see *Methods*). There was a

brief increase in decoding of *distance to object* for attended dots across the other factors (Target

Frequency and Time on Task) between the 15^{th} and 10^{th} distances and for the unattended dots

across the other factors between 15^{th} and the 12^{th} distances. This corresponds to the first 400 ms for

the attended dots and the first 240 ms for the unattended dots after the onset (Supplementary

Figure 1B). Distance decoding then dropped somewhat before ascending again as the dot

approached the deflection point. The second rise of decoding, which was more pronounced for the

attended dots, could reflect the increasing relevance to the task as the dot approached the crucial

deflection point, but it could also be due to higher visual acuity in foveal compared to peripheral

areas of the visual field. There was strong evidence that decoding of distance information for all

conditions was greater than chance (50%, BF > 10) across all 15 distance levels (Supplementary

Figure 1B).

Supplementary Figure 1. Impact of different conditions in the *direction of approach* (A) and *distance to object* (B) information coding and their Bayesian evidence for difference from chance. (A) Decoding of *direction of approach* information (less task-relevant). The horizontal dashed line refers to chance-level decoding. Upper graph: Attended colour dot; Lower graph: Unattended ('distractor') colour dot. (B) Decoding of *distance to object* information (most task-relevant). Thick lines show the average across participants (shading 95% confidence intervals). Vertical dashed lines indicate critical times in the trial. Bayes Factors are shown in the bottom section of each graph: Filled circles show moderate/strong evidence for either hypothesis and empty circles indicate insufficient evidence. They show the results of Bayes factor analysis when evaluating the difference of the decoding values from chance as explained in *Methods*. Early = data from the first 5 blocks (~10 minutes). Late = data from the last 5 blocks (~10 minutes).

1018

1019

1020

1021

 Supplementary figure 2 shows the data for false alarm trials.

1023

Supplementary Figure 2. Decoding of information on *correct* vs. *false alarm* trials. (A) Decoding of *direction of approach* information (less task-relevant). (B) Decoding of *distance to object* information (most task-relevant). The horizontal dashed lines refer to chance-level decoding. Top row: Decoding using correct trials; Bottom row: Decoding using false alarm trials. In both top and bottom rows, the classifiers were trained on correct trials and tested on *correct* and *false alarm* trials, respectively. Thick lines show the average across participants (shading 95% confidence intervals). Vertical dashed lines indicate critical events in the trial. Bayes Factors are shown in the bottom section of each graph: Filled circles show moderate/strong evidence for either hypothesis and empty circles indicate insufficient evidence. They show the results of Bayes factor analysis when evaluating the difference of the decoding values from chance for Active (blue) and Monitoring (red) conditions separately, the comparison of the two conditions (green) and the comparison of correct and miss trials (black). Note that for the comparison of correct and miss trials, Active and Monitoring conditions were averaged separately.

1024

1025

1026

Supplementary Figure 3. Decoding of information about the dot motion using the eye-tracking data. (A) Decoding of *direction of approach* information (less task-relevant). (B) Decoding of *distance to object* information (most task-relevant). The horizontal dashed lines refer to chance-level decoding. Top panels: Decoding using correct trials; Bottom panels: Decoding using miss trials. In both top and bottom panels, the classifiers were trained on *correct* trials and tested on (left out) *correct* and all *miss* trials, respectively. Thick lines show the average across participants (shading 95% confidence intervals). Vertical dashed lines indicate critical events in the trial. Bayes Factors are shown in the bottom section of each graph: Filled circles show moderate/strong evidence for either hypothesis and empty circles indicate insufficient evidence. They show the results of Bayes factor analysis when evaluating the difference of the decoding values from chance for Active (blue) and Monitoring (red) conditions separately, the comparison of the two conditions (green) and the comparison of correct and miss trials (black). Note that for the comparison of correct and miss trials, Active and Monitoring conditions were averaged separately.