Different Perspective of Machine Learning Technique to Better Predict Breast Cancer Survival

Kaushal Kumar
Institute of Applied Mathematics
Heidelberg University
Germany, 69117 Heidelberg
Email: kaushal.kumar@stud.uni-heidelberg.de

Vijay Vikram Singh
SCIS, Jawaharlal Nehru University
New Delhi-110067, India
Email: vvsvikramsingh@gmail.com

Ramakrishna Ramaswamy
Department of Chemistry
Indian Institute of Technology Delhi
New Delhi-110016, India
Email: ramaswamy@iitd.ac.in

Abstract—Machine learning plays a key role in the aid of cancer diagnosis and detection. The researcher has implemented different techniques of machine learning for the detection of breast cancer. Some researchers claim that their algorithms are more accurate, faster, and easier than others. My study relies on recently developed machine learning algorithms like genetic algorithms and deep belief nets. I'm interested to construct a system to accurately differentiate between benign and malignant breast tumors. We've optimized the training algorithm. During this unique circumstance, we applied the genetic programming procedure to settle on the main genuine highlights and perfect boundary estimations of the AI classifiers. The examinations rely upon affectability, cross-validation, precision, and ROC curve. Among all the varying kinds of classifiers used in this paper genetic programming is the premier viable model for highlight determination and classifier.

Index Terms—Breast cancer, Deep Learning, Deep belief nets, Genetic Algorithm.

I. INTRODUCTION

The study of cancer research isn't new using Machine learning. Artificial neural networks (ANNs) and decision trees (DTs) are employed in cancer detection and diagnosis for nearly 20 years. Today the job of AI techniques has used in an exceedingly huge choice of uses beginning from identifying and grouping tumors through X-beam and CRT pictures to the arrangement of malignancies from proteomic and genomic (microarray) measures [1]. In line with the foremost recent PubMed statistics, over 1600 papers are published on the subject of machine learning and cancer [2]. These papers have the enthusiasm to recognize, characterize, identify, or recognize tumors and different malignancies utilizing AI strategies. In other words, machine learning plays a key role in aid of cancer diagnosis and detection [3].

Breast cancer could also be a prevalent explanation for death, widespread among women worldwide [4]. Different techniques are developed for early detection and treatment of breast cancer and reduced the number of deaths, and different aided breast cancer diagnosis methods are aware of increase the diagnostic accuracy [5]. Within the previous number of decades, Machine learning techniques which require three main stages: preprocessing, feature extraction, and classification. During this process, singular value decomposition (SVD) or principal component analysis (PCA) is applied to scale back the dimensionality of the feature representation. Many works have attempted to automate the diagnosis of breast cancer supported machine learning algorithms [6].

Nowadays, machine learning is playing a very important role in the medical sciences. Unfortunately, machine learning continues to be a field with high barriers and sometimes requires expert knowledge. Designing an honest machine learning model including the stages of preprocessing, feature selection, and classification processes requires a bunch of skills and expertise. The expert in machine learning chooses the acceptable technique for this problem domain. However, the nonexperts in machine learning spend many some time to optimize their proposed models and to attain the target performance. during this context, the aim of the work is to automate the design of the machine learning models employing dozens of techniques. and Genetic programming is the best combination to optimized the techniques.

There are two challenges to automate the breast cancer diagnosis: (i) to find out which model most closely fits the information and (ii) a way to automatically design machine learning model by adjusting the parameters.

In Section 2,3,4 we have explained material methods and mathematical details of algorithms. Section 5 explains the computational results, whereas the foremost conclusions are discussed in Section 6.

II. MATERIALS AND METHODS

Dataset Used for research: We use the breast cancer, Coimbra, Data Set downloaded from the UCI Machine learning Repository. This dataset [7] employed by Patricio to predict cancerous and noncancerous tumors. A blood sample was all collected at the identical time of the day after overnight fasting. Clinical, demographic, and anthropocentric data were collected for all participants, under similar conditions, always by the identical research physician during consultation. Collected data included age, weight, height, and menopausal status (for each participant, this status expressed whether she was a minimum of 12 months after menopause or reported a bilateral oophorectomize). During this process, clinical features, including age, BMI, Glucose, Insulin, HOMA, Leptin, Adiponectin, Resistin, and MCP-1 were observed or

measured for every one of the 166 patients. There are 10 predictors, all quantitative, and a binary quantity, indicating the presence or absence of breast cancer. The predictors are anthropocentric data and parameters which may somewhat be gathered in routine blood analysis [8].

Background: For analysis purposes, we use several machine learning techniques like decision tree, random forest naive Bayes, Linear SVM, Logistical regression, and KNN [9] to get possible biomarkers.

Feature Selection: In this process, we try to find a minimum number of effective features. Feature selection methods could even be divided into the wrapper, filter, and embedded methods [10]. During this content, we make the intrigued peruser caution to the probabilities of feature selection, giving an essential scientific classification of feature selection strategies, and talking about their utilization, assortment, and, potential during diffusion of both common similarly as upcoming bioinformatics applications [11].

A. Genetic Algorithm

In 1975 Holland developed the Genetic Algorithm [12]. In his book, Adaptation in Natural and Artificial Systems said the Genetic Algorithm could even be a computational optimization paradigm modeled on the concept of biological evolution. The advantage of a random search to the goal of the foremost effective subset. Genetic Algorithm is an optimization procedure that operates in binary search spaces and manipulates a population of potential solutions. It evaluates fitness function by a get above-average performance with high performance. Genetic algorithm system encodes the solution into a numerical form called a chromosome that consists of the smallest genetic component of the gene [13]. Then, randomly selected to form a spread of chromosomes thanks to the initial population. Then there will be selected pairs of chromosomes from the population for crossover and mutation operations, repeated until the result stops within the desired condition that the utmost number of generations is achieved. After that, the fitness values of each chromosome are calculated. the foremost effective possible fitness value of the chromosome is visiting be selected within the gene column for next-generation reproduction [14]. The calculations of this technique could even be portrayed as follows:

Step 1: Generating the beginning population.
Step 2: Evaluate fitness value.
Step 3: Selection process from the underlying populace to lead hybrid operations.
Step 4: Crossover of each pair of chosen parent chromosomes.
Step 5: Mutation on the picked chromosome, and figure the wellness estimation of the chromosome.
Step 6: After the change, assessing the wellness estimation of the recently produced youngster populace. In the event that the wellness estimation of the posterity is higher, at that point, the parent chromosome is supplanted with a substitution posterity chromosome. On the off chance that not, at that point don't go spinning.

Step 7: If its bomb rehashes the progression (3) to (6) until it arrives at the preeminent number of ages.

B. Classification Using Support Vector Machines

In 1998 Vapnik developed the Support Vector Machine (SVM). It constructs a classifier which divides training samples. And also, maximizes the minimum distance or margin [15]. Think about the arrangement of two classes, which can to some degree be portrayed as

$$(t_i, t_j), \qquad i = 1, 2, ..., n. \qquad t \in R^n, x \in \{-1, +1\}$$

where x_i refers to class labels and i denotes the number of data. The basic idea of this method is to construct the hyperplane that separated the two classes of data with the equation

$$x(t) = w^T.t + b$$

where b is that the bias and w is vector perpendicular (n-dimensional) to hyperplane. The maximize of margin is like minimizing the load norm $\| w \|^2$ defined to

$$x_i(w.t + b) \geq 1, \qquad i = 1, 2, ..., n$$

By introducing positive Lagrange multipliers $\alpha_i, i = 1, 2, ..., n$ for the above constraints, formed a primal Lagrange function as follows

$$L_P = \frac{1}{2} \| w \|^2 - \Sigma_{i=1}^n \alpha_i[x_i(w.t + b) - 1]$$

That is a convex quadratic programming problem to resolve the "dual" problem. Its means maximize L_p subject to the ∇L_p with relevancy w and b vanishes. the solution of dual problem's

$$\alpha = argmin \frac{1}{2} \Sigma_{i=1}^n \Sigma_{j=1}^n \alpha_i \alpha_j x_i x_j (t_i, t_j) - \Sigma_{i=1}^n \alpha_i$$

is given by above equation with constraints

$$\alpha_i \geq 0, \qquad i = 1, 2, ..., n$$

$$\Sigma_{i=1}^n \alpha_i x_i = 0$$

Then the solution is these samples with nonzero α_i are called support vectors, which are critical samples for classification [16]. we'll map the training data to higher dimensional space to create a nonlinear decision surface. The separating hyperplane to maximize the margin and hyperplanes is represented to kernel function functions as follows

$$H(t_i, t_j) = \psi(t_i).\psi(t_j)$$

The decision function is defined in formula these kernels as [17]

$$f(t) = sign(\Sigma_{i=1}^n \lambda_i x_i H(t_i.t_j)) + b$$

where λ_i are coefficients of Lagrange multipliers.

III. RESTRICTED BOLTZMANN MACHINE

Restricted Boltzmann Machine (RBM) [18] could be a two-layer undirected graphical model within which the first layer consists of visible input variables $\mathbf{x} \in \{0,1\}^D$, and a second layer consists of hidden variables (units) $\mathbf{h} \in \{0,1\}^M$. We permit just the between layer associations, i.e., there aren't any associations inside layers. Moreover, we add a third layer that represents observable output variable $y \in \{1, 2, ..., K\}$. we use the 1-to-K coding scheme which finally ends up in representing the output as a binary vector of length K denoted by y, specified if the output (or class) is k, then all elements are zero except element y_k which takes the worth 1.

A RBM with M hidden units might be a parametric model of the joint distribution of visible and hidden variables, that takes the form:

$$p(\mathbf{x}, \mathbf{y}, \mathbf{h}|\theta) = \frac{1}{Z(\theta)} e^{-E(\mathbf{x}, \mathbf{y}, \mathbf{h}|\theta)}$$

with parameter $\theta = \{\mathbf{b}, \mathbf{c}, \mathbf{d}, \mathbf{W}^1, \mathbf{W}^2\}$, and where:

$$E(\mathbf{x}, \mathbf{y}, \mathbf{h}|\theta) = -\mathbf{b}^T\mathbf{x} - \mathbf{c}^T\mathbf{h} - \mathbf{d}^T\mathbf{y} - \mathbf{x}^T\mathbf{W}^1\mathbf{h} - \mathbf{h}^T\mathbf{W}^2\mathbf{y}$$

is the energy function, and

$$Z(\theta) = \Sigma_{\mathbf{x}, \mathbf{y}, \mathbf{h}} E(\mathbf{x}, \mathbf{y}, \mathbf{h}|\theta)$$

is a partition function.
This model is termed Restricted Boltzmann Machine (RBM) [19]. The condition probability of a configuration of the visible unit **,** given a configure of the hidden units $\mathbf{h}$, is

$$p(\mathbf{x}|\mathbf{h}) = \Pi_i p(x_1|\mathbf{h})$$

$$p(x_i = 1|\mathbf{h}) = \sigma(b_i + \mathbf{W}_i^1.\mathbf{h})$$

$$p(y|\mathbf{h}) = \frac{e^{d_y} + (\mathbf{W}_{.y}^2)^T\mathbf{h}}{\Sigma_{\bar{y}} e^{d_y} + (\mathbf{W}_{.y}^2)^T\mathbf{h}}$$

$$p(\mathbf{h}|y, \mathbf{x}) = \Pi_j p(h_j|\mathbf{h}$$

$$p(h_j = 1|y, \mathbf{x}) = \Pi_j \sigma(c_j + W_{jy}^2 + (\mathbf{W}_j^1)^T\mathbf{x})$$

where σ is that the logistic sigmoid function, $\mathbf{W}_i^l$ is that the ith row of weight matrix $\mathbf{W}^l$, $\mathbf{W}_j^l$ is that the jth column of weight matrix $\mathbf{W}^l$, W_{ij}^l is that the element of weights matrix $\mathbf{W}^l$.
It is possible to exactly compute the distribution $p(y|\mathbf{x})$ which can be further accustomed choose the foremost probable class label. This conditional distribution takes the following form

$$p(y|\mathbf{x}) = \frac{e^{d_y}\Pi_j(1 + (e^{c_j + (\mathbf{W}_j^1)^T\mathbf{x}})e^{W_{jy}^2})}{\Sigma_{\bar{y}} e^{d_{\bar{y}}}\Pi_j(1 + (e^{c_j + (\mathbf{W}_j^1)^T\mathbf{x}})e^{W_{j\bar{y}}^2})}$$

Pre-computing the terms $c_j + (\mathbf{W}_j^1)^T\mathbf{x}$ allows to chop back the time needed for computing the conditional distribution to $O(MD + MK)$. within the medical context, this chance expresses the probability of occurring ith input for the given other inputs and class labels.

Typically, the parameter θ in RBM are learned from the knowledge using the likelihood function:

$$p(\mathbf{x}, \mathbf{y}, |\theta) = \frac{1}{Z(\theta)} \Sigma_{\mathbf{h}} e^{-E(\mathbf{x}, \mathbf{y}, \mathbf{h}|\theta)}$$

There are diverse inductive standards for learning RBM, e.g., Approximate Maximum Likelihood, Maximum Pseudo-Likelihood, proportion Matching [20]. The generally utilized technique is Contrastive Divergence, which is utilized during this paper.

IV. DEEP BELIEF NETWORKS (DBN)

DBN is adjusted as neural systems, DBN has numerous non-straight shrouded layers, DBN is generatively pre-prepared close to it can go about as non-direct dimensionality decrease for input highlights vector, and in the long run, the arranged instructor is another tangible info [21]. Let the output neurons state y represent the training example y^*. The discrepancy between the expected output y^* and thus the actual output y is using the squared error measure:

$$E = (y^* - y)^2$$

The change in weight, which is added to the old weight, is adequate the merchandise of the training rate and also the gradient of the error function, multiplied by 1:

$$\triangle w_{ij} = -\frac{\partial E}{\partial w_{ij}}$$

where the majority data is unlabeled. However, backpropagation neural network requires a labeled training data [22], [23]. In recent years, attention has shifted to deep learning [24]. Deep learning [25] would be a gaggle of algorithms in AI that endeavors to show significant level deliberations in information by utilizing model structures made out of various non-direct changes [26]. RBM may be a stochastic artificial neural network which learns a probability distribution over its set of inputs, whereas, DBN could be a graphical model composed of multiple layers of latent variables (hidden units), with connections between the layers, but not between units within each layer [27].
From Hintons perspective, the DBN is viewed as a composition of easy learning modules each of which can be a restricted quite RBM that contains a layer of visible units. This layer represents knowledge. Another layer of concealed units speaks to features that catch higher-request connections inside the information. the 2 layers are connected by a matrix of symmetrically weighted connections (W) and there don 't seem to be any connections within a layer [28].
The key idea behind DBN is its weight (w), learned by an RBM define both $p(v|h, w)$ then the prior distribution over hidden vectors $p(h|w)$ [28]. The probability of generating a visual vector is written as

$$p(v) = \Sigma_h(p(h|w)p(v|h, w))$$

As the learning of DBN is also a computationally escalated task, Hinton indicated that RBMs could even be stacked and

prepared in an exceedingly ravenous way to make the DBN [29]. He introduced a quick algorithm for learning DBN [29]. The load update between visible v and hidden h unites simply as

$$\triangle w_{ij} = \varepsilon(\langle v_i, h_j \rangle^0 - \langle v_i, h_i \rangle^1)$$

where 0 and 1 within the above equation designate to the network data and reconstruction state, respectively.

V. Experimental Results

We used Python 3.7.4 and import various libraries for data handling so that it can read datasets, then we've imported other libraries for data illustrate so that we are able to easily understand the data sets and interpret furthermore. We've identified NaN values throughout the row likewise as a column so as that we are able to fill it with various methods sort of a global mean or with the mean of row or column etc [30]. For organization, interpretation, presentation, and an intensive understanding of the information. We've described the knowledge set, so we could know the mean, variance, minimum, maximum limit, and thus, the precise distribution of knowledge set [31]. As we all know that ultimately our data is assessed into a binary classification which we've got illustrated the classification into a bar chart.

Fig.1: Classification labels

Descriptive statistics were calculated for all variables employed in the study using python syntax. we've got identified the assorted arrangement with relation to binary classification, which creates us know the mean, median, mode, and variance of a specific classification. As we respond to through observation, each data carries with it nine entry, and to grasp the distribution of feature in two classes, we've plated two or more plots in one figure so, that we are able to easily visualize each feature.

Fig.2 : Heat Map/Correlation plot

Heat Map: We've got also used another technique to simplify the complex data set .i.e. heat map [32]. A heat map could be a two-dimensional representation of knowledge within which values are represented by color. There are often some ways to display heat maps, but all of them share one thing in common they use color to speak relationships between data values that will be much harder to know if presented numerically in an exceeding spreadsheet.

A. Machine learning algorithms

We have used several supervised and unsupervised machine learning techniques to search out of the possible biomarker for breast cancer. to create a model for implementing the machine learning technique, Firstly we imported the library for the machine learning technique then we segregate data into tests and train to create a model. during this case, we've selected 25% data for testing and rest others for training.
Following Machine Learning techniques we've used with the subsequent accuracy:

Machine Learning Technique	Accuracy
Genetic Alogrithm	0.875000
Logistic Regression	0.862069
Linear SVM	0.827586
Random Forest	0.793103
Deep Belief Network	0.758621
Decision Tree	0.724138
Naive Bayes	0.724138
Radial SVM	0.551724
KNN	0.551724

Table: 1

As we see the above Machine learning technique with their accuracy we found the Fluctuation within the accuracy of models is because of lack of knowledge. we've only 116 individuals data and to organize a decent model we want to data a minimum of in a thousand. The experimental data on cancer is extremely scarce. There are many various methods are available for solving these problems, but lack of knowledge is clearly not an answer. a technique to beat this problem is to either we've to rearrange the important data.

B. K-Fold cross-validation

To overcome the matter with splitting into training and testing data sets, we've got applied K-fold cross-validation [33].To utilize an AI method, we've to indicate what division of information is utilized for training and testing informational collections and it'd be conceivable that some data in training data sets to urge the simplest results and a maximum number of knowledge points tested to urge the simplest validation [17]. Each data we've removed from the training set into the test is lost for training sets. So, we've got to reset this swap. This can be the place cross-validation comes into the picture since this reason augments both of the sets, we have a decent arrangement of data inside the training sets to urge the most effective learning results, and also the maximum number of knowledge point we tested to induce to urge the simplest validation.

The key thought of cross-validation is that segment of the information set into k canister of equivalent size, for instance: on the off chance that we have 300 datums and 10 container size which implies per receptacle have 30 information focuses, in this way, we've 30 information point in each container. So in cross-validation, one among the k subsets, as a testing test and remaining k-1 receptacle, are assembled as training sets at that point train AI calculations, and test the presentation on the testing set. [34]. AI calculations run various times, during this case, multiple times thus the normal the ten diverse testing sets exhibitions for the ten unique sets and normal the test results for those k experiments. this can be the way by which we will use all data sets for training, and everyone data for testing.

Machine Learning Technique	Cross-validation mean
Decision Tree	0.581818
Random Forest	0.562879
Naive Bayes	0.547727
Linear SVM	0.533333
Logistic Regression	0.509091
Radial SVM	0.509091
KNN	0.506818

Table: 2

Fig.3 : Cross Validation accuracies with different classifiers

C. t-SNE Visualization

As we all know that we board a 3-D world in order that we are able to easily visualize the pattern within the 3-D, but what if we've data that is more complex? The visualization of knowledge is crucial steps to grasp the info and to grasp the complex data, dimension reduction is very important to step to require. Nowadays high dimensional data is everywhere and t-SNE [35] may be a popular technique for dimension reduction that we will use via sci-kit learn.

Fig.4 : t-SNE visualization of Cancer data

The complete list of parameters which are important in predicting breast cancer are as follows

Feature	Importance	Normalized	Cumulative
Resistin	33.4	0.213965	0.213965
Age	32.7	0.209481	0.423447
Glucose	31.9	0.204356	0.627803
BMI	16.9	0.108264	0.736067
HOMA	12.9	0.082639	0.818706
Leptin	10.5	0.067265	0.885971
Adiponectin	9.1	0.058296	0.944266
Insulin	4.5	0.028828	0.973094
MCP.1	4.2	0.026906	1.000000

Table: 3

The feature analysis shows that there are not many highlights with the increasingly prescient incentives for the determination. From our investigation from Table:3, a few highlights like Resistin, Age, Glucose, and BMI are biomarkers for bosom malignant growth. Also, Patricio in his paper [7] discussed these features as the best biomarkers for prediction.

D. ROC curve

We have tested a number of models to predict the possible outcomes and to understand what is the simplest model overall without having any quite hypothesis regarding the acceptance of the speed of the model. one all told the foremost credit risk models relies upon sensitivity and specificity [36] which has evaluated by the receiver operating graph i.e. ROC curve [37]. In this, a graph is plotted by plotting the sensitivity against 1-specificity for every cutoff, the plot always starts with the lower-left corner where sensitivity is 0 and specificity is 1, in upper right corner correspond cut-off up to zero where sensitivity is 1 and specificity is 0. In general, speaking the maximum area of the best-left corner cover is healthier i.e. those curve cover maximum area of the best left have the next specificity associated with higher sensitivity [36]. The askew line partitioned the ROC curve into equal parts, a degree over the corner to corner for example upper left space represents good classification results contrariwise. Following formula for verity positive and false negative of ROC curve.

- $Sensitivity = \frac{TruePositive}{TruePositive+FalseNegative}$
- $Specificity = \frac{TrueNegative}{TrueNegative+FalsePositive}$

<div style="text-align:center">ROC curves from the investigated models</div>

Fig.5 : ROC curves from the investigated models

VI. Conclusion

In this exploration, we've executed various strategies of a Machine learning tools for detecting breast cancer like deep belief nets, regression, decision tree, and genetic algorithms.. The overall neural network accuracy is 75.85% for DBN in breast cancer cases. Genetic algorithms give the upper accuracy of 87.50%. From fig3: We can observe that among all the classifiers, Deep Belief Nets and Genetic Algorithms are better classifiers then others. The variability is less in these two classifiers. We believe that the proposed system is very helpful to the physicians for his or her final decisions on their patients. Since the info sets utilized during this work are little if we have an oversized amount of information sets then methods used for prediction may be more accurate. By using such a tool, they'll make very accurate decisions.

Acknowledgment

KK thanks the India Department of Biotechnology (DBT): Joint DBT-Heidelberg University Graduate program on Big Data Research (fund: 2302086, assignment: 7815564) for support and RR is supported by the DST (Govt of India) through the JC Bose fellowship.

References

[1] A. L. D. Brown, J. Martin, "The role of apoptosis in cancer development and treatment response," *Nature Reviews Cancer*, 2005.

[2] S. Agrawal and J. Agrawal, "Neural network techniques for cancer prediction: A survey," *Procedia Computer Science*, vol. 60, pp. 769 – 774, 2015.

[3] K. D. Cole, H.-J. He, and L. Wang, "Breast cancer biomarker measurements and standards," *PROTEOMICS Clinical Applications*, vol. 7, no. 1-2, pp. 17–29, 2013.

[4] M. LLC, "MS Windows NT kernel description," 2018.

[5] M. Bacac and I. Stamenkovic, "Metastatic cancer cell," *Annual Review of Pathology: Mechanisms of Disease*, vol. 3, no. 1, pp. 221–247, 2008. PMID: 18233952.

[6] J. Malek, S. Abderrahim, S. Mabrouk, K. Torki, and R. Tourki, "Automated breast cancer diagnosis based on gvf-snake segmentation, wavelet features extraction and fuzzy classification," *Signal Processing Systems*, vol. 55, pp. 49–66, 04 2009.

[7] M. Patrício, J. Pereira, J. Crisóstomo, P. Matafome, M. Gomes, R. Seiça, and F. Caramelo, "Using resistin, glucose, age and bmi to predict the presence of breast cancer," *BMC Cancer*, vol. 18, p. 29, Jan 2018.

[8] D. S.-S. A. L. G. M. G. M. P. L. L. A. B. S.-R. L. S. . R. S. Joana Crisstomo, Paulo Matafome

[9] C. M. Bishop, *Pattern Recognition and Machine Learning (Information Science and Statistics)*. Berlin, Heidelberg: Springer-Verlag, 2006.

[10] R. O. Duda, P. E. Hart, and D. G. Stork, *Pattern Classification (2Nd Edition)*. New York, NY, USA: Wiley-Interscience, 2000.

[11] M. F. Akay, "Support vector machines combined with feature selection for breast cancer diagnosis," *Expert Systems with Applications*, vol. 36, no. 2, Part 2, pp. 3240 – 3247, 2009.

[12] J. H. Holland, "Genetic algorithms and adaptation," in *Adaptive Control of Ill-Defined Systems*, pp. 317–333, Springer, 1984.

[13] A. M. E. M.-A. E. W. F. N. M. Dhahri, Habib, "Automated breast cancer diagnosis based on machine learning algorithms," *Journal of Healthcare Engineering*, 11 2019.

[14] K. Sastry, D. Goldberg, and G. Kendall, "Genetic algorithms," in *Search methodologies*, pp. 97–125, Springer, 2005.

[15] C. Cortes and V. Vapnik, "Support-vector networks," *Machine learning*, vol. 20, no. 3, pp. 273–297, 1995.

[16] K. Polat and S. Gne, "Breast cancer diagnosis using least square support vector machine," *Digital Signal Processing*, vol. 17, no. 4, pp. 694 – 701, 2007.

[17] T. Hastie, R. Tibshirani, and J. Friedman, *The elements of statistical learning: data mining, inference, and prediction*. Springer Science & Business Media, 2009.

[18] R. Salakhutdinov, A. Mnih, and G. Hinton, "Restricted boltzmann machines for collaborative filtering," in *Proceedings of the 24th international conference on Machine learning*, pp. 791–798, 2007.

[19] R. Salakhutdinov and G. Hinton, "An efficient learning procedure for deep boltzmann machines," *Neural computation*, vol. 24, no. 8, pp. 1967–2006, 2012.

[20] H. Larochelle, M. Mandel, R. Pascanu, and Y. Bengio, "Learning algorithms for the classification restricted boltzmann machine," *The Journal of Machine Learning Research*, vol. 13, no. 1, pp. 643–669, 2012.

[21] D. Erhan, A. Courville, Y. Bengio, and P. Vincent, "Why does unsupervised pre-training help deep learning?," in *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, pp. 201–208, 2010.

[22] B. E. Boser, I. M. Guyon, and V. N. Vapnik, "A training algorithm for optimal margin classifiers," in *Proceedings of the fifth annual workshop on Computational learning theory*, pp. 144–152, 1992.

[23] J. A. Suykens, *Advances in learning theory: methods, models, and applications*, vol. 190. IOS Press, 2003.

[24] A. M. Abdel-Zaher and A. M. Eldeib, "Breast cancer classification using deep belief networks," *Expert Systems with Applications*, vol. 46, pp. 139 – 144, 2016.

[25] S. S. Haykin, *Neural networks and learning machines*. Upper Saddle River, NJ: Pearson Education, third ed., 2009.

[26] J. Dheeba, N. A. Singh, and S. T. Selvi, "Computer-aided detection of breast cancer on mammograms: A swarm intelligence optimized wavelet neural network approach," *Journal of biomedical informatics*, vol. 49, pp. 45–52, 2014.

[27] G. E. Hinton, "Deep belief nets.."

[28] G. E. Hinton, "Deep belief networks," *Scholarpedia*, vol. 4, no. 5, p. 5947, 2009. revision #91189.

[29] G. E. Hinton, S. Osindero, and Y.-W. Teh, "A fast learning algorithm for deep belief nets," *Neural computation*, vol. 18, no. 7, pp. 1527–1554, 2006.

[30] albertbup, "A python implementation of deep belief networks built upon numpy and tensorflow with scikit-learn compatibility," 2017.

[31] "Using machine learning algorithms for breast cancer risk prediction and diagnosis," *Procedia Computer Science*, vol. 83, pp. 1064 – 1069, 2016.

[32] W. Samek, A. Binder, G. Montavon, S. Lapuschkin, and K.-R. Müller, "Evaluating the visualization of what a deep neural network has learned," *IEEE transactions on neural networks and learning systems*, vol. 28, no. 11, pp. 2660–2673, 2016.

[33] R. Kohavi *et al.*, "A study of cross-validation and bootstrap for accuracy estimation and model selection,"

[34] B. Zheng, S. W. Yoon, and S. S. Lam, "Breast cancer diagnosis based on feature extraction using a hybrid of k-means and support vector machine algorithms," *Expert Systems with Applications*, vol. 41, no. 4, Part 1, pp. 1476 – 1482, 2014.

[35] L. v. d. Maaten and G. Hinton, "Visualizing data using t-sne," *Journal of machine learning research*, vol. 9, no. Nov, pp. 2579–2605, 2008.

[36] K. Kourou, T. P. Exarchos, K. P. Exarchos, M. V. Karamouzis, and D. I. Fotiadis, "Machine learning applications in cancer prognosis and prediction," *Computational and Structural Biotechnology Journal*, vol. 13, pp. 8 – 17, 2015.

[37] T. Fawcett, "An introduction to roc analysis," *Pattern recognition letters*, vol. 27, no. 8, pp. 861–874, 2006.