The Unique Advantage of Adolescents in Probabilistic Reversal: Reinforcement Learning and Bayesian Inference Provide Adequate and Complementary Models

Maria K. Eckstein[1*], Sarah L. Master[1†], Ronald E. Dahl[1], Linda Wilbrecht[1], Anne G.E. Collins[1]

*For correspondence:
annecollins@berkeley.edu (AGEC);
maria.eckstein@berkeley.edu (MKE)

Present address: [†]Department of Psychology, New York University, NYC NY, USA

[1]UC Berkeley, CA, USA

Abstract

During adolescence, youth venture out, explore the wider world, and are challenged to learn how to navigate novel and uncertain environments. We investigated whether adolescents are uniquely adapted to this transition, compared to younger children and adults. In a stochastic, volatile reversal learning task with a sample of 291 participants aged 8-30, we found that adolescents 13-15 years old outperformed both younger and older participants. We developed two independent cognitive models, one based on Reinforcement learning (RL) and the other Bayesian inference (BI), and used hierarchical Bayesian model fitting to assess developmental changes in underlying cognitive mechanisms. Choice parameters in both models improved monotonously. By contrast, RL update parameters and BI mental-model parameters peaked closest to optimal values in 13-to-15-year-olds. Combining both models using principal component analysis yielded new insights, revealing that three readily-interpretable components contributed to the early- to mid-adolescent performance peak. This research highlights early- to mid-adolescence as a neurodevelopmental window that may be more optimal for behavioral adjustment in volatile and uncertain environments. It also shows how increasingly detailed insights can be gleaned by invoking different cognitive models.

Keywords: Reinforcement learning, Bayesian inference, computational modeling, development, volatility, adolescence, non-linear changes

Introduction

In mammals and other species with parental care, there is typically an adolescent stage of development in which the young are no longer supported by parental care but are not yet adult. This adolescent period can be identified in many species across the animal kingdom (Natterson-Horowitz and Bowers, 2019) and is increasingly viewed as a critical epoch of development in which organisms explore the world, make critical decisions, and learn about important features of their environment (DePasque and Galván, 2017; Larsen and Luna, 2018; Laube, Lorenz, et al., 2020; Piekarski, Johnson, et al., 2017; Steinberg, 2005). The kind of learning and decision making that occurs during adolescence likely has critical short and long-term impact on survival (Frankenhuis and Walasek,

2020). In humans, the adolescent transition to independence usually involves a rapid expansion of encountered contexts and increasingly frequent transitions between them, as well as increased exposure to stochasticity and uncertainty. Accordingly, it has been argued that adolescent brains and cognition are specifically adapted for contextual volatility and stochasticity (Dahl et al., 2018; Davidow et al., 2016; Johnson and Wilbrecht, 2011; Lourenco and Casey, 2013; Sercombe, 2014). The goal of the current study was to test this prediction in a controlled laboratory environment, using a probabilistic reversal-learning task in a large developmental sample ($n = 291$) with a wide, continuous age range (8-30 years), which offered enough statistical power to observe non-linear effects of age (such as U-shape patterns). We complement behavioral analyses with sophisticated, state-of-the-art computational methods.

Reversal Learning Tasks

Reversal-learning tasks—tasks where the correct choices change unpredictably—have been used in the cognitive neurosciences for decades. Originally associated with response inhibition, reversal tasks are now thought by most to measure cognitive flexibility (Izquierdo et al., 2017). We employed a probabilistic reversal-learning paradigm in the current study in order to combine the two above-mentioned elements of the adolescent transition period: stochasticity of outcomes and volatility of contexts (Fig. 1A). In a probabilistic learning task, a non-rewarding outcome could be due to noise or changes in contingencies. Participants' main challenge therefore lies in discriminating which negative outcomes occurred due to the task's inherent stochasticity, and should not lead to a change in behavior, and which occurred due to task switches, and should lead to a change in behavior.

Abundant previous research in rodents, non-human primates, and humans has shed light on both brain areas (notably orbitofrontal cortex and striatum) and endocrine systems (notably sero­tonin, dopamine, and glutamate) that are involved during reversal-learning tasks (e.g., Tai et al., 2012; for reviews, see Clark et al., 2004; Frank and Claus, 2006; Hamilton and Brigman, 2015; Izquierdo et al., 2017; Izquierdo and Jentsch, 2012; Kehagia et al., 2010; for fMRI meta-analysis, see Yaple and Yu, 2019). Many of these neural systems continue development into late adoles­cence or early adulthood, some with non-linear trajectories (Albert et al., 2013; Casey et al., 2008; Dahl et al., 2018; DePasque and Galván, 2017; Larsen and Luna, 2018; Laube, Lorenz, et al., 2020; Lourenco and Casey, 2013; Piekarski, Johnson, et al., 2017; Somerville and Casey, 2010; Toga et al., 2006). Reversal-learning tasks have also been used in psychopathology in an effort to under­stand the cognitive and neural processes that underlie a range of conditions, in both adults (e.g., Peterson et al., 2009; Swainson et al., 2000; Waltz and Gold, 2007; for review, see Izquierdo and Jentsch, 2012) and developing populations (e.g., Adleman et al., 2011; Dickstein, Finger, Brotman, et al., 2010; Dickstein, Finger, Skup, et al., 2010; Finger et al., 2008; Harms et al., 2018; Hildebrandt et al., 2018). More recently, the focus has shifted to using reversal-learning tasks to understand cognitive development itself, studying differences between adults compared to children and ado­lescents (e.g., Hauser et al., 2015; Javadi et al., 2014; van der Schaaf et al., 2011; for brief coverage in a review, see DePasque and Galván, 2017), and even toddlers (Minto de Sousa et al., 2015). Over­all, in use since the 1950's, the use of reversal-learning paradigms has seen an almost exponential growth over the past two decades (Izquierdo et al., 2017, Fig. 1).

We know of three particular studies that have used reversal tasks to investigate cognitive de­velopment (Hauser et al., 2015; Javadi et al., 2014; van der Schaaf et al., 2011). van der Schaaf et al., 2011 tested four different age groups across adolescence, which allowed to assess non-linear changes, albeit in a deterministic reversal task. In accordance with our prediction, this study re­vealed an adolescent peak in reversal performance—however, this was in a very small sample and using a deterministic task. Two later studies used stochastic reversal tasks in 2-group designs to test for linear developments, but failed to see significant differences (Hauser et al., 2015; Javadi et al., 2014). The details about these three studies are summarized in the supplemental material (suppl. Tables 1 and 2). Taken together, a clear picture of the development of probabilistic reversal

88 learning during adolescence has yet to emerge.

Computational Modeling

In most reversal-learning studies to date, analyses have focused on error types (e.g., reversal er-
rors; Cools et al., 2002) or other ways of comparing task conditions (e.g., switches induced by re-
ward versus punishment; van der Schaaf et al., 2011). Such model-independent analyses have led
to many interesting insights, but have been unable to test hypotheses about specific cognitive pro-
cesses that are at work while subjects perform the task. In an effort to better understand these
processes, more recent studies have started to employ computational modeling, most often in the
RL framework (e.g., Boehme et al., 2017; Chase et al., 2010; Gläscher et al., 2009; Hauser et al.,
2015; Javadi et al., 2014; Metha et al., 2020; Peterson et al., 2009).

Reinforcement Learning (RL)

The basic idea of RL is that agents rely on choice *values* to decide between choices. These values
reflect choices' expected long-term cumulative reward. If values are accurate, agents can maximize
long-term outcomes without having to plan into the future, simply by selecting options according
to their values. The core of RL therefore lies in estimating accurate choice values, and doing this
efficiently, in order to avoid computationally-expensive long-term predictions. RL achieves this
by updating choice values incrementally every time choice outcomes are observed (see section
Reinforcement Learning (RL) Models), a procedure that is guaranteed to converge to optimal values
if certain conditions are met (Sutton and Barto, 2017). The size of each update, determined by
an agent's *learning rate*, captures the integration time scale, i.e., whether the agent emphasizes
more recent or distant outcomes. RL models have been used extensively in cognitive neuroscience,
and a specialized network of brain regions, including the striatum and frontal cortex, has been
consistently identified as executing similar computations to RL algorithms (for reviews, see Frank
and Claus, 2006; D. Lee et al., 2012; Niv, 2009; O'Doherty et al., 2015).

Applied to reversal tasks, RL frames cognitive processes as *learning*: Participants continuously
adjust current choice values based on new information, striving to learn more-and-more accurate
values (Fig. 3A, left). Importantly, the same gradual learning process is employed during stable
task periods and after switches, without an explicit concept of switching. Roughly speaking, behav-
ioral change arises in RL when the previously-rewarding option has resulted in enough negative
outcomes to push its value below the value of the previously-unrewarding option. This can result
in slow switching behavior in basic RL algorithms, in contrast to abrupt switching in humans and
animals (Costa et al., 2015; Izquierdo et al., 2017). Indeed, environmental stability is a condition
for the convergence of choice values in the RL framework (Sutton and Barto, 2017), making basic
RL sub-optimal for volatile environments (Gershman and Uchida, 2019). For this reason, various
augmentations to basic RL have been proposed that enable rapid switching, for example counter-
factual updating (e.g., Hauser et al., 2015). For this study, we implemented an RL model that com-
bines several such augmentations (for details, see section Reinforcement Learning (RL) Models).

Bayesian Inference (BI)

While the striking mapping of RL algorithms onto the neural substrate has contributed to mak-
ing them the standard modeling framework in the reversal-learning literature, many have argued
that a different framework, BI, might actually provide a better model for human and animal be-
havior (Bromberg-Martin et al., 2010; Costa et al., 2015; Fuhs and Touretzky, 2007; Gershman
and Uchida, 2019; Solway and Botvinick, 2012). Indeed, in at least two reversal-learning studies
in healthy adults, BI models have shown better model fit than standard RL models (Hauser et al.,
2014; Schlagenhauf et al., 2014), and a recent study in macaques showed similar results (Bartolo
and Averbeck, 2020). The main theoretical reason for the supposed superiority of BI compared to
RL is its inherent ability for rapid behavioral switches, explained below.

The basic concept of BI is to make inferences by applying Bayes formula. Applied to reversal

tasks, BI frames cognitive processes as *inference*. The goal of a BI agent is to infer the hidden state of its environment, the unobservable features of the environment that determine its underlying mechanics (in this case, which choice is "objectively" correct at a given time). The agent achieves this by making observations in the environment, and engaging a *predictive model* to determine how likely each observation arises from each possible hidden state (in this case, e.g., how likely a negative outcome occurs if the choice is objectively correct). To balance new observations and existing knowledge, the agent combines this state *likelihood* with its *prior belief* about hidden states, which is informed by all previous trials, to obtain an updated *posterior belief* about hidden states. In this way, observed outcomes change beliefs about which choice is correct. This process of combining prior beliefs and likelihoods to obtain posterior beliefs about states is repeated for each observation, using posterior beliefs as the subsequent prior beliefs, to create a continuous cycle of Bayesian inference (Perfors et al., 2011; Sarkka, 2013). BI deals naturally with environmental volatility because agents explicitly represent distinct task periods as distinct hidden states, and discovering a state switch can trigger an immediate behavioral switch.

Summarizing the main conceptual difference between the RL and BI frameworks, whereas in RL, agents adapt to task switches by gradually relearning choice values, in BI, they explicitly infer hidden states and switch behavior after detecting a state switch. Despite the growing evidence in favor of BI models for reversal learning, their use is still rare (Hauser et al., 2014; Schlagenhauf et al., 2014) and less common than RL models. To the best of our knowledge, BI models have never been applied to reversal learning in developmental populations, leaving the question unanswered whether Bayesian mechanisms could shed light on developmental changes.

Goals of The Study

The current study aims to fill this gap in the literature. We aimed to determine whether adolescents outperform younger and older participants in stochastic reversal learning, in accordance with a prior study on deterministic reversal learning (van der Schaaf et al., 2011), and extending prior research on stochastic reversal learning whose 2-group design did not allow detection of non-linear changes (Hauser et al., 2015; Javadi et al., 2014). To adequately assess the hypothesized non-linear trajectory, we tested a large sample of 291 participants across a continuous age range from 8-30 years (section Participants). We specifically aimed to clarify the cognitive mechanisms that underlie the hypothesized non-linear developments by employing computational modeling, building on previous developmental research that either did not employ models (van der Schaaf et al., 2011), or lacked now-standard practices of modeling quality (Hauser et al., 2015; Javadi et al., 2014). Specifically, to ensure state-of-the-art results, we compared an extensive number of competing models (Wilson and Collins, 2019), carefully validated the behavior of winning models against human behavior (Palminteri et al., 2017), and used hierarchical parameter fitting based on sampling to obtain the most accurate parameter estimates (M. D. Lee, 2011; see also Daw, 2011; van den Bos et al., 2017; for details, see section Reinforcement Learning (RL) Models). Concretely, we aimed to distill the insights that have been gained from the rich RL reversal research into a single model by combining several previously-proposed augmentations with relevance for reversal learning, an important step to ensure the generalizability of computational models (Nassar and Frank, 2016). Augmentations included counter-factual updating (e.g., Boehme et al., 2017; Boorman et al., 2011; Gläscher et al., 2009; Hauser et al., 2014; Palminteri et al., 2016), distinct learning rates for positive and negative outcomes (e.g., Cazé and van der Meer, 2013; Christakou et al., 2013; Frank et al., 2004; Harada, 2020; Javadi et al., 2014; Lefebvre et al., 2017; Palminteri et al., 2016; van den Bos et al., 2012; for similar ideas in machine learning, see Dabney et al., 2020), and choice persistence (e.g., Sugawara and Katahira, 2021; for details, see section Reinforcement Learning (RL) Models). With the ability of rapid behavioral switching, this model represents a stronger competitor to the favored BI framework than the more basic models employed in previous studies (Hauser et al., 2014; Schlagenhauf et al., 2014).

To adequately assess the age trajectories of fitted parameters in this model, we employed a

novel fitting technique based on hierarchical Bayesian model fitting (Katahira, 2016; M. D. Lee, 2011). This technique avoids the biases that arise when comparing parameters between participants that have been fitted using maximum-likelihood, the standard in the literature (van den Bos et al., 2017). Our technique tests specific hypotheses about parameter trajectories by explicitly modeling these trajectories within the hierarchical Bayesian fitting framework of model fitting (section Model Fitting and Comparison). Lastly, we aimed to resolve the debate between RL and BI models of reversal learning. We therefore independently created, fitted, and validated both model types, taking a thorough approach to model comparison that integrates qualitative and quantitative criteria of model fit (Bernardo and Smith, 2009; Blohm et al., 2020; Jacobs and Grainger, 1994; Kording et al., 2020; Navarro, 2019; Palminteri et al., 2017; Uttal, 1990; Webb, 2001), extending previous studies that used numerical model fit alone (Hauser et al., 2014; Schlagenhauf et al., 2014) and provided the impression of a false dichotomy between models.

Predictions

Consistent with van der Schaaf et al., 2011, we predicted that adolescents would perform the task best, and employed computational models to understand how. Specifically, we use the BI model to assess how participants' mental models developed with age. We predicted that adolescents' models would be better tuned for volatile and stochastic environments than children's and adults'. Because the BI model employed rational, Bayes-optimal behavior, it allowed us to evaluate whether and how participants deviated from optimality: We hypothesized that adolescents would use the most accurate mental models. We used the RL model to understand the parameters of the learning process, i.e., the learning rates that controlled participants' updating time scales. Due to the asymmetry in information provided by positive compared to negative feedback (see section Experimental Design), we predicted differences in updates based on positive and negative feedback; we also predicted that participants would employ counter-factual reasoning, due to the binary nature of the task. Nevertheless, we did not have strong a priori predictions about how the parameters that guided these learning processes would change with age, because past studies have shown conflicting results (for review, see Nussenbaum and Hartley, 2019), potentially due to seemingly small differences in experimental design (e.g., Davidow et al., 2016; Master et al., 2020; Palminteri et al., 2016; for review, see Eckstein et al., n.d.) . Lastly, both RL and BI models contained parameters that controlled choice: decision noise and persistence. We expected both to decrease monotonously with age, consistent with previous literature (e.g., Master et al., 2020; for review, see Nussenbaum and Hartley, 2019).

In the following, we first present model-agnostic analyses, which revealed that adolescents (13-15 years) outperformed younger and older participants in several measures of task performance. We then present our modeling results. We first show that the winning RL and BI models captured human behavior equally adequately qualitatively, establishing both as useful models of human behavior. We then show the age trajectories of both models' parameters. Independently, both revealed a monotonic decrease in the values of choice parameters (decision noise, persistence), consistent with the previous literature (e.g., Master et al., 2020; for review, see Nussenbaum and Hartley, 2019). The BI model additionally revealed that 13-to-15-year-olds' mental models of the task were more optimal than younger and older participants', reflected in more accurate values of mental model parameters (probability of state switch p_{switch}; likelihood of reward for correct action p_{reward}). The RL model revealed a longer integration time horizon for negative feedback in 13-to-15-year-olds compared to younger and older participants, evident in increased values of learning rate parameter α_-. Finally, we focus on the relationship between both models, assessing parameter correlations, differences in explained variance, and insights gained from combining model parameters using principle component analysis (PCA). This analysis revealed that parameter variance between participants was captured by just four dimensions, three of which showed marked and interpretable developmental changes.

Results

Task Design

The goal of the task was to collect gold coins, which were hidden in one of two locations (Fig. 1A). Which location contained the coin changed unpredictably several times throughout the task (*volatility*), whereby the correct location provided coins only 75% of the time (stochasticity; Fig. 1A). Specifically, participants first completed a child-friendly tutorial (section Experimental Design), and then performed the following task: On each trial, two identical green boxes appeared on the screen. Participants chose one, and either received a reward (gold coin) or not (empty box; Fig. 1A). One box was rewarded in 75% of the trials on which it was chosen, whereas the other was never rewarded—in other words, a positive outcome indicated deterministically that the choice was correct, but a negative outcome was ambiguous, and could either indicate random noise or a switch. After a participant reached a non-deterministic performance criterion (see section Experimental Design), an unsignaled switch occurred, after which the opposite box became rewarding. Several unpredictable switches occurred over 120 trials (Fig. 1B).

Task Behavior

Participants gradually adjusted their behavior after task switches, and on average started selecting the correct action about 2 trials after a switch, reaching asymptotic performance of around 80% correct choices within 3-4 trials after a switch (Fig. 1C). Participants almost always repeated their choice ("stayed") after receiving positive outcomes ("- +" and "+ +"), and often switched actions after receiving two negative outcomes ("- -"). Behavior was most ambivalent after receiving a positive followed by a negative outcome ("+ -"), i.e., on "potential" switch trials (Fig. 1D; for age differences, see suppl. Fig. 10).

Figure 1. (A) Task design. On each trial, participants chose one of two boxes, using the two red buttons of the shown game controller. The chosen box either revealed a gold coin (left) or was empty (right). The probability of coin reward was 75% on the rewarded side, and 0% on the non-rewarded side. (B) The rewarded side changed multiple times, according to unpredictable task switches. (C) Average human performance and standard errors, aligned to true task switches (dotted line; trial 0). Switches only occurred after rewarded trials (section Experimental Design), resulting in performance of 100% on trial -1. The red arrow shows the switch trial, grey bars show trials included as asymptotic performance. (D) Average probability of repeating a previous choice ("stay"), as a function of the two previous outcomes ($t-2, t-1$) for this choice ("+": reward; "-": no reward). Error bars indicate between-participant standard errors. Red arrow highlights potential switch trials, i.e., when a rewarded trial is followed by a non-rewarded one, which—from participants' perspective—is consistent with a task switch.

Age Differences: Performance Peak in Adolescents

There are two main ways of testing developmental changes: continuous analyses (e.g., regressing age against performance; van der Schaaf et al., 2011) and binned analyses (e.g., comparing a group of adolescents to a group of adults; Hauser et al., 2015; Javadi et al., 2014). Because our study included a large participant sample balanced across a wide age range, we were able to use both: We used continuous regression models to characterize the shapes of age trajectories, statistically testing the presence of linear and quadratic age effects (section Behavioral Analyses; Fig. 2). We used binned analyses to identify the age of peak performance because averages over age bins provide the least biased estimate of performance in any age group (suppl. Fig. 8D-F; Fig. 3C-F). Specifically, we used four age bins for 8-to-17-year-olds, which were defined by age quartiles; and two bins for adults, defined by the sample (undergraduate students, community adults; see section Quantile Bins).

Using (logistic) mixed-effects regression (methods in section Behavioral Analyses; results in Table 1), we found positive linear and negative quadratic age contrasts in all three performance measures. This reveals that the shape of age trajectories was dominated by monotonic performance improvements in combination with a performance peak in mid-adolescents (Fig. 2A, C, D; Table 1).

To identify the age of peak performance suggested by the quadratic effect, we assessed the binned data. In accordance with our hypothesis, the peak occurred in the intermediate age range,

such that 13-to-15-year-olds outperformed both younger participants (8-13) and adults (18-30) on several measures of task performance. In terms of overall accuracy, performance peaked in 13-to-15-year-olds and declined steeply for both younger and older participants (Fig. 3C). 13-to-15-year-olds were also most willing to repeat previous actions after a single negative outcome ("stay on (potential) switch trial"), especially compared to younger children (Fig. 3E). This suggests that 13-to-15-year-olds were most persistent in the face of negative feedback. Furthermore, 13-to-15-year-olds performed best during stable task periods, showing the highest accuracy on asymptotic trials, especially compared to younger participants (Fig. 3F; also see suppl. Fig. 8).

Table 1. Statistics of mixed-effects regression models predicting performance measures from sex (male, female), age (years and months; "lin."), and squared age ("qua."). Overall accuracy, stay after potential (pot.) switch, and asymptotic performance were modeled using logistic regression, and z-scores are reported. Log-transformed response times on correct trials were modeled using linear regression, and t-values are reported. * $p < .05$; ** $p < .01$, *** $p < .001$.

Performance measure (Figure)	Predictor	β	z / t	p	sig.
Overall accuracy (2A)	Age (lin.)	0.054	3.1	0.0017	**
	Age (qua.)	-0.0014	-3.0	0.0024	**
	Sex	0.0074	0.2	0.82	
Response times (2B)	Age (lin.)	-0.17	-8.4	< 0.001	***
	Age (qua.)	-0.004	-7.4	< 0.001	***
	Sex	0.19	5.1	< 0.001	***
Stay after (pot.) switch (2C)	Age (lin.)	0.42	3.8	< 0.001	***
	Age (qua.)	-0.010	-3.5	< 0.001	***
	Sex	0.27	1.3	0.19	
Asymptotic performance (2D)	Age (lin.)	0.19	4.2	< 0.001	***
	Age (qua.)	-0.0048	-4.0	< 0.001	***
	Sex	0.025	0.3	0.77	

Figure 2. Task performance across age. Each dot shows one participant, color denotes sex. Curves show best-fitting regression models, including linear and quadratic effects of age. Shaded areas show standard errors of the mean regression line. "Lin.": significant linear contrast (liner change with age); "qua.": significant quadratic contrast (U-shaped or inverse-U-shaped change with age). Stars denote p-values (* p<.05, ** p<.01, *** p<.001). (A) Percentage of correct choices across the entire task (120 trials). (B) Median response times on correct trials. Regression coefficients differed significantly between males and females and are shown separately. (C) Fraction of stay trials after (potential, "pot.") switches (red arrows in Fig. 1C). (D) Accuracy on asymptotic trials (grey bars in Fig. 1C).

Behavioral and Age Effects of Positive versus Negative Outcomes

We next assessed the effects of positive and negative outcomes on behavior. 13-to-15-year-olds adapted their choices more optimally to previous outcomes than younger or older participants. To show this, we used mixed-effects logistic regression to predict actions on trial t from predictors encoding positive or negative outcomes on trials $t - i$, for delays $1 \leq i \leq 8$ (for details, see section Behavioral Analyses). The effects of positive outcomes were several times larger than the effects of negative outcomes (suppl. Table 7; Fig. 8B-F), in accordance with the task structure: Positive outcomes were diagnostic, indicating with certainty that an action was correct, whereas negative outcomes were non-diagnostic, being ambivalent as to whether a switch occurred or not. This justifies the strong effect of positive and the weak effect of negative outcomes on behavior. Crucially, this pattern showed prominent age effects, revealed by interactions between age and previous outcomes in the regression models (suppl. Fig. 8B, C, E, and F; suppl. Table 7). On trials $t - 1$ and $t - 2$, positive outcomes interacted with age and squared age (all $p's < 0.014$; suppl. Table 7), showing that the effect of positive outcomes increased with age and then slowly plateaued (suppl. Fig. 8C, F). For negative outcomes, the signs of the interaction was opposite for trials $t - 1$ versus $t - 2$ (all $p's < 0.046$; suppl. Table 7), showing that the effect of negative outcomes flipped, being weakest in 13-to-15-year-olds for trial $t - 1$ (Fig. 8F), but strongest for trial $t - 2$. In other words, 13-to-15-year-olds were best at ignoring single, ambivalent negative outcomes ($t - 1$), but most likely to integrate long-range negative outcomes ($t - 2$), which potentially indicate task switches.

To summarize our model-agnostic results, 13-to-15-year-olds outperformed younger participants, older adolescents, and adults on a stochastic and volatile task, which was designed to mimic

304 environmental challenges specific to adolescence. We next used computational modeling to test
305 hypotheses about the cognitive processes that might underlie these age differences, employing
306 both RL and BI.

Figure 3. (A) Conceptual depiction of the RL and BI models. In RL (left), actions are selected based on learned values, illustrated by the size of stars ($Q(left)$, $Q(right)$). In BI (right), actions are selected based on a mental model of the task, which differentiates different hidden states ("Left is correct", "Right is correct"), and specifies the transition probability between them ($p(switch)$) as well as the task's stochasticity ($p(reward)$). The sizes of the two boxes illustrate the inferred probability of being in each state. (B) Hierarchical Bayesian model fitting. Left box: RL and BI models had free parameters θ^{RL} and θ^{BI}, respectively. Individual parameters θ_j were based on group-level parameters θ_{sd}, θ_{int}, θ_{lin}, and θ_{qua} in a regression setting (see text on the right). For each model, all parameters were simultaneously fit to the observed (shaded) sequence of actions a_{jt} of all participants j and trials t, using MCMC sampling. Right: We chose uninformative priors for group-level parameters; the shape of each prior was based on the parameter's allowed range. For each participant j, each parameter θ was sampled according to a linear regression model, based on group-wide standard deviation θ_{sd}, intercept θ_{int}, linear change with age θ_{lin}, and quadratic change with age θ_{qua}. Each model (RL or BI) provided a choice likelihood $p(a_{jt})$ for each participant j on each trial t, based on individual parameters θ_j. Action selection followed a Bernoulli distribution (see Model Fitting and Comparison for details). (C)-(F) Human behavior for the measures shown in Fig. 2, binned in age quantiles. (C), (E), and (F) also show simulated model behavior for model validation, verifying that models closely reproduced human behavior and age differences.

Cognitive Modeling

Winning RL Model

The winning RL model had four free parameters: persistence p, inverse decision temperature β,
and learning rates α_+ and α_- for positive and negative outcomes, respectively (section Reinforce-
ment Learning (RL) Models). The model had the ability to learn from counterfactual outcomes, but
model fit was best when counterfactual learning was directly tied to factual learning rather than
controlled by an additional free parameter, such that updates of the same size (but opposite signs)
were applied to both chosen and unchosen actions, according to learning rates α_+ for positive out-
comes and α_- for negative outcomes. Parameters p and β controlled the translation of RL values
into choices: persistence p increased the probability of repeating choices (independently of choice
value) when $p > 0$, and of alternating choices when $p < 0$, while β induced decision noise (increased
probability of exploratory choices) when small, and allowed for reward-maximizing choices when
large.

Winning BI model

In the BI framework, participants cast the task as having distinct hidden states, separated by reversals (e.g., "Left choice is correct" and "Right choice is correct"; Fig. 3A, right). Participants' goal is to infer the current hidden state, by observing the outcomes (e.g., reward, no reward) to their actions (e.g., left, right), engaging a mental model that specifies how likely each outcome arises in response to each action in each hidden state, and how likely each hidden state transitions to each other. Once participants have formed a posterior belief about the current hidden state, combining the state likelihood with their prior state belief, they can select the action with the highest probability of reward in this state.

The winning BI model also had four parameters: choice-parameters p and β as in the RL model, as well as task volatility p_{switch} and reward stochasticity p_{reward}, which characterized participants' internal model of the task (Fig. 3A; section Bayesian Inference (BI) Models). p_{switch} ranged from stable ($p_{switch} = 0$) to volatile ($p_{switch} > 0$), and p_{reward} ranged from deterministic ($p_{reward} = 1$) to stochastic ($p_{reward} < 1$). The actual task was based on $p_{switch} = 0.05$ and $p_{reward} = 0.75$, meaning that the optimal mental model of the task would employ these values.

Hierarchical Bayesian Model Fitting

We first conducted exhaustive model comparison to create a best-possible model of each type (RL and BI), assessing improvements caused by adding various previously-proposed model augmentations (for details, see section Reinforcement Learning (RL) Models). The winning models of both types showed superior numerical model fit in terms of WAIC scores (Watanabe, 2013) when compared to differently parameterized models or the same type (Table 2), and also validated better behaviorally, closely reproducing human behavior (Palminteri et al., 2017; Wilson and Collins, 2019; Fig. 3C, E, F; suppl. Fig. 11). The winning RL model had the overall lowest WAIC score, revealing best quantitative fit, but both models validated equally well qualitatively: Both showed human-like behavior, and reproduced all age differences in detail, including 13-to-15-year-olds' performance peak (Fig. 3C), their peak in the proportion of staying after (potential) switch trials (Fig. 3E), in asymptotic performance on non-switch trials (Fig. 3F), and their most efficient use of previous outcomes to adjust future actions (suppl. Fig. 8 D-F). Other models did not capture all these qualitative patterns (suppl. Fig. 11, 12).

The closeness in WAIC scores (Table 2), and especially the fact that both models were equally able to reproduce all crucial details of human behavior, show that both models captured human behavior adequately, and suggests that both might provide adequate explanations of the underlying cognitive processes. We therefore fitted both models to participant data to estimate individuals' parameter values, using hierarchical Bayesian fitting (Fig. 3B; section Model Fitting and Comparison). We chose the hierarchical Bayesian method because it 1) recovered individual parameters better than classic maximum-likelihood fitting (suppl. Fig. 9); and 2) allowed us to estimate the effects of age on model parameters in a superior, statistically unbiased way (Katahira, 2016; M. D. Lee, 2011; van den Bos et al., 2017).

Table 2. WAIC model fits and standard errors for all models, based on hierarchical Bayesian fitting. Bold numbers highlight the winning model of each class. For the parameter-free BI model, the Akaike Information Criterion (AIC) was calculated precisely. WAIC differences are relative to next-best model of the same class, and include estimated standard errors of the difference as an indicator of meaningful difference. In the RL model, "α" refers to the classic RL formulation in which $\alpha_+ = \alpha_-$. "α_c" refers to the counterfactual learning rate that guides updates of unchosen actions, with $\alpha_{+c} = \alpha_{-c}$ (see section Reinforcement Learning (RL) Models).

	Free parameters (count)		(W)AIC	WAIC Difference
BI	–	(0)	31,959	$2,668 +-0$
	β	(1)	$29,291 +-206$	$868 +-78$
	β, p	(2)	$28,423 +-201$	$4,769 +-132$
	β, p, p_{reward}	(3)	$23,654 +-203$	$51 +-10$
	$\beta, p, p_{reward}, p_{switch}$	(4)	**23,603** $+-$ **200**	0
RL	α, β	(2)	$26,678 +-200$	$438 +-44$
	α, β, α_c	(3)	$26,240 +-201$	$1,429 +-78$
	$\alpha, \beta, \alpha_c, p$	(4)	$24,811 +-190$	$42 +-13$
	$\alpha_+, \beta, \alpha_{+c}, p, \alpha_-$	(5)	$24,769 +-213$	$1,260 +-73$
	$\alpha_+, \beta, \alpha_{+c}, p, \alpha_-, \alpha_{-c}$	(6)	$23,509 +-211$	$17 +-10$
	$\alpha_+ = \alpha_{+c}, \alpha_- = \alpha_{-c}, \beta, p$	(4)	**23,492** $+-$ **201**	0

Age Differences in Model Parameters

Our analyses revealed that several parameters changed with age (Fig. 4; suppl. Tables 10 and 11). In both the RL and BI model, choice parameters p and β increased monotonically with age, growing rapidly at first and plateauing around early adulthood (Fig. 4A, B, E, F). The age-based fitting model (section Model Fitting and Comparison) revealed that both the initial linear increase and later change in slope were significant, showing significant linear and negative quadratic effects of age for both parameters (suppl. Table 10). This shows that in this task, participants' willingness to repeat previous actions independently of previous outcomes (p), and to exploit the best known option (β), steadily increased until adulthood, with steady growth during the teen years. Parameters p and β were thereby almost perfectly correlated between the RL and BI model (parameter p: Spearman $\rho = 0.97$, $p < 0.05$; parameter β: $\rho = 0.94$, $p < 0.05$; Fig. 5B), even though both models were fitted independently. This suggests that choice parameters captured robust, update-independent aspects of decision making.

Other parameters showed non-monotonic age trajectories. α_-, p_{reward}, and p_{switch} declined drastically between ages 8-10 and 13-15, but then reversed their trajectory and increased again, reaching a slightly lower plateau around 15-17 years, which lasted through adulthood (Fig. 4C, G-H). For α_- and p_{reward}, these changes were captured in significant pairwise differences between 8-to-10-year-olds and 13-to-15-year-olds, as well as between 13-to-15-year-olds and adults (25-30; for statistics, see suppl. Table 11), tested using the age-less fitting model (Model Fitting and Comparison). For p_{switch}, age differences were captured in a significant quadratic effect of age in the age-based model (suppl. Table 10).

Because the mental model in the BI model mirrored the true task structure, participants' model parameters can be compared to the task's true underlying parameters ($p_{reward} = 0.75$; $p_{switch} = 0.05$) to determine the optimality of the mental model. In accordance with the behavioral peak, both parameters were most optimal in 13-to-15-year-olds, whereas 8-to-10-year-olds and adults (18-30) fundamentally overestimated task volatility (p_{switch}), while underestimating reward stochasticity (p_{reward}). Even though the RL model does not afford assessment of optimality, lower learning rates from negative feedback α_- are beneficial in this task because they allow to avoid premature switching based on single negative outcomes, while allowing for adaptive switching after multiple negative outcomes. In correspondence with our behavioral findings, α_- was lowest in 13-to-15-year-olds.

Parameter α_+ showed a unique stepped age trajectory, featuring relatively stable values through-out childhood and adolescence (8-17), but a sudden increase in adults (18-30; Fig. 4D). To summarize our modeling results, all 4 computational parameters in each model contributed to the age-related differences in behavior exhibited by participants and reproduced by the models. This shows that the non-linear trajectory of task performance can be explained by an interplay of trajec-tories in the underlying parameters, including monotonic growth (p, β), U-shaped trajectories (α_-, p_{reward}, p_{switch}), and a step function (α_+). Both an explanation in terms of changes in learning, with a crucial distinction between learning from positive and negative outcomes (RL model), and an ex-planation in terms of mental models, with a non-linear trajectory of optimality (BI model), might appropriately explain participants' developmental trajectory in probabilistic switching.

Figure 4. Fitted model parameters for the winning RL (left column) and BI model (right column), plotted over age. Stars indicate significant linear ("lin") and quadratic ("qua") effects of age on model parameters, based on the age-based fitting model, and differences between age groups, based on the age-less fitting model (section Model Fitting and Comparison; suppl. Tables 10 and 11). Dots (means) and error bars (standard errors) show the results of the age-less fitting model, providing an unbiased representation of individual fits. (A)-(D) RL model parameters. (E)-(H) BI model parameters.

Integrating RL and BI Model Findings

This result raises several questions: Why do both models, RL and BI, capture human behavior? Do both capture the same aspects of behavior, or different ones? Do the cognitive processes each in-

vokes differ from each other fundamentally, or do they actually describe similar processes, simply
using different terms? And lastly, can the use of both models lead to insights that could not have
been gained from one model alone? The following section addresses these questions, conducting
a generate-and-recover procedure to determine whether models were identifiable; assessing the
correlations between the parameters of both models; determining how much variance in each pa-
rameter was explained by the parameters of the other model; and evaluating the dimensions of
largest variance that arose in the shared space of both models.

Model Identifiability

For the generate-and-recover model-recovery procedure, we simulated artificial behavior from
each model and assessed how well the opposite model fit these data. We used human-fitted pa-
rameter values for simulation to ensure that simulated behavior occupied a meaningful range
(Heathcote et al., 2015; Wilson and Collins, 2019). This analysis can shed light on whether both
models captured the same or distinct aspects of behavior: If models are identifiable, i.e., the sim-
ulated behavior of each model is better fitted by the corresponding model than the other one,
that means that the models generated and captured different aspects of behavior, making them
distinguishable. For example, in a situation in which the RL model fits the RL data best, and the
BI model fits the BI best, both generated and captured distinguishable behaviors. If models are
not identifiable, on the other hand, i.e., simulated behavior of each model is fitted equally well by
both models, both potentially generated and captured the same variance in behavior; in this case,
it is not possible to draw conclusions from model comparison. We found that both models were
identifiable (Fig. 5A), showing that each captured unique aspects of behavior. Interestingly, the
difference in fits was smaller when fitting the RL model (left column in Fig. 5A), suggesting that the
RL model captured more aspects of BI behavior than the other way around, potentially reflecting
increased versatility of this model.

Relations between Parameters

We next asked whether both models captured similar cognitive mechanisms, despite their differ-
ences in form.

To answer this question, we first determined how closely individual parameters were related
between models, assessing pairwise Spearman correlations. As mentioned before, parameters p
and β were almost perfectly correlated between models, suggesting high similarity of choice pro-
cesses between models (Fig. 5B). Furthermore, parameter p_{reward} (BI) was strongly correlated with
α_- (RL), suggesting that beliefs about task stochasticity and negative learning rates played simi-
lar roles in both models, presumably in the integration of negative outcomes. The other mental-
model parameter, p_{switch} (BI), was strongly negatively correlated with β (RL), suggesting that beliefs
about task volatility in the BI model captured aspects that were explained by decision noise in the
RL model. This is consistent with the notion that an expectation of high task volatility could be
mistaken for increased choice stochasticity. The only parameter that showed no large correlations
with other parameters was α_+ (RL), potentially reflecting a cognitive process unique to the RL model.
Taken together, some parameters likely captured similar cognitive processes in both models, ex-
emplified by large correlations across participants. These similarities arose despite differences in
the functional form of both models. On the other hand, models also showed unique parameters,
potentially reflecting more unique cognitive processes.

The previous analysis showed that both models captured similar processes using different *in-*
dividual parameters, but similar processes might also be captured in the interplay between *several*
parameters. To investigate this possibility, we next used linear regression to evaluate how well we
could predict each parameter based on the parameters and one-way parameter interactions of
the other model. This analysis revealed that 7 of 8 parameters could be predicted almost perfectly
(Fig. 5C), showing that the interplay between parameters in one model captured almost all variance
in almost every parameter in the opposite model. In other words, fitting the RL model on partici-

pants' data allowed us to nearly perfectly predict participants' BI parameters, without fitting the BI model. Parameter α_+ (RL) was again an exception, with only small amounts of variance captured by BI parameters, suggesting that it reflected mechanisms that were unique to the RL model. These mechanisms might increase the versatility of the RL model, and possibly account for the slightly better numerical fit of the RL model to human (Table 2) and simulated data (Fig. 5A). In sum, in addition to significant similarities between individual parameters, the RL and BI models showed even greater similarities in terms of cognitive processes that were captured in the interactions between multiple parameters. This suggests that both models captured very similar cognitive processes, albeit without reaching identity (e.g., parameter α_+).

Figure 5. Relating RL and BI models. (A) Model recovery. WAIC scores were worse (larger; lighter colors) when recovering behavior that was simulated from one model (row) using the other model (column), than when using the same model (diagonal), revealing that the models were discriminable. The difference in fit was smaller for BI simulations (bottom row), suggesting that the RL model captured BI behavior better than the other way around (top row). (B) Spearman pairwise correlations between model parameters. Red (blue) hue indicates negative (positive) correlation, saturation indicates correlation strength. Non-significant correlations are crossed out (Bonferroni-corrected at $p = 0.00089$). Light-blue (teal) letters refer to RL (BI) model parameters. Light-blue / teal-colored triangles show correlations within each model, remaining cells show correlations between models. (C) Variance of each parameter explained by parameters and interactions of the other model ("R^2"), estimated through linear regression. All four BI parameters (green) were predicted almost perfectly by the RL parameters, and all RL parameters except for α_+ (RL) were predicted by the BI parameters. (D)-(E) Results of PCA on model parameters. (D) Cumulative variance explained by all principal components PC1-8. The first four components captured 96.5% of total parameter variance. (E) Age-related differences in PC1-4: PC1 reflected overall behavioral quality and showed rapid development between ages 8-13, which were captured by linear ("lin") and quadratic ("qua") effects in a regression model. PC2 captured a step-like transition from shorter to longer updating time scales at age 15, as revealed by PC-based model simulations (Supplements). PC3 showed no significant age effects. PC4 captured the variance in α_+ and differed between adolescents 15-17 and both 8-13 year olds and adults. PC2 and PC4 were analyzed using t-tests. * $p < .05$; ** $p < .01$, *** $p < .001$.

Distilling Model Parameters Using PCA

Based on the fact that each model captured unique aspects of behavior and employed unique cognitive processes, we lastly aimed to determine what we could deduce from both models combined that we could not deduce from each alone. To this end, we used PCA to unveil lower-dimensional structure embedded in the 8-dimensional parameter space created by both models (section Principal Component Analysis (PCA)). We found that the first four principle components (PCs) of the PCA explained almost all variance (96.5%; Fig. 5D), showing that individual differences in all 8 pa-

rameters could be summarized by differences in just 4 dimensions. Succinctly summarizing both

computational models, these 4 PCs provide a compressed and information-rich representation

of the cognitive process, which has the potential to further illuminate the trajectory of cognitive

development.

Our next goal therefore was to understand these PCs. The standard approach to interpreting

PCs is to investigate which raw features (in our case, model parameters) were combined with which

weights (factor loadings) to produce each PC (section Principal Component Analysis (PCA)). In our

case, this approach was impeded by the fact that some model parameters—specifically RL learning

rates—are inherently difficult to interpret because their roles are influenced by many factors, in-

cluding the underlying task (Eckstein et al., n.d.) and computational model (Sugawara and Katahira,

2021), which makes them less suitable to anchor the meaning of PCs. To resolve this issue, we de-

vised a novel method to understand the PCs in our study: Because PCs were linear combinations

of model parameters, we could directly simulate the effects each PC had on behavior by simulating

datasets with the corresponding model parameters, using our RL and BI models (for details, see

section Principal Component Analysis (PCA)). Specifically, we simulated datasets with particularly

big and particularly small values of each PCs (suppl. Fig. 13A). Assessing the behavior of these

extreme cases provides detailed insight into the specific roles of each PC, and can—in turn—aid

the interpretation of model parameters. More details are provided in section **??**.

Our analysis revealed that PC1, capturing the largest proportion of variance in the dataset, re-

flected a broad measure of behavioral quality. This was evident in the low performance and lack

of distinction between reward histories for the datasets that were simulated based on low values

of PC1, and the high performance and optimal response to reward histories in the datasets based

on high values of PC1 (suppl. Fig. 13A, left and right; suppl. Table 12; suppl. Text). Factor loadings

revealed that low behavioral quality was caused by larger-than-average values of α_- (RL), which

likely led to premature switching, and p_{reward} and p_{switch} (BI), which created overly deterministic and

volatile mental models of the task (suppl. Fig. 13A, center). High behavioral quality, on the other

hand, was caused by larger-than-average values of α_+ (RL), which likely facilitated the quick inte-

gration of positive outcomes; p (RL and BI), which increased choice persistence; and β (RL and BI),

which reduced decision noise.

PC2, which explained the second-most variance after PC1, represented integration time scales.

Simulated behavior based on low values of PC2 exemplified overly-short time scales, reflected in

pronounced win-stay behavior—i.e., immediate switching after negative outcomes and consistent

staying after positive outcomes—, which led to suboptimal performance on asymptotic trials (suppl.

Fig. 13B, left). High values of PC2, on the other hand, led to overly-long time scales, such that every

behavioral change took a long time, leading to suboptimally-slow behavioral switches (suppl. Fig.

13B, right). Overly-short time scales were driven by larger-than-average values of α_+ and α_- (RL),

which led to a reliance of learning on just the most recent outcomes; mental models that are above-

average volatile (p_{switch}) and extremely deterministic (p_{reward}), i.e., the belief that every correct action

is rewarded and hidden states switch permanently; and larger-than-average values of p (RL and BI),

which lead to a prevalence of outcome-independent choice repetitions.

PC3 captured responsiveness to task outcomes. Low responsiveness was characterized by a

lack of differentiation between outcome histories and slow behavioral switching (suppl. Fig. 13C,

right), whereas high responsiveness was characterized by extremely consistent win-stay-lose-shift

behavior (suppl. Fig. 13C, left). Behavior with low responsiveness was caused by larger-than-

average values of p, which favors outcome-independent choices; and p_{switch}, which leads to the

belief that the task is constantly switching. Behavior with high responsiveness was caused by larger-

than-average values of β, which effectively made task experience the only factor that determined

choices; and larger-than-average values of p_{reward}, which institute the belief that every correct action

is rewarded.

PC4 was dedicated to the unique RL parameter α_+, capturing the tension between slow and fast

updates from positive outcomes (suppl. Fig. 13D).

518 Three of these four PCs showed prominent age effects, suggesting that the PCA can provide an
519 additional window into cognitive development in our task. PC1 (behavioral quality) was very low
520 in the youngest age group (8-10 years), but increased drastically until age 13, at which it reached
521 a stable plateau that lasted throughout adulthood (Fig. 5E, top-left). Regression models revealed
522 significant linear and quadratic effects of age (lin.: $\beta = -0.47$, $t = -4.0$, $p < 0.001$; quad.: $\beta = 0.011$,
523 $t = 3.43$, $p < 0.001$), with no effect of sex ($\beta = 0.020$, $t = 0.091$, $p = 0.93$). This shows that one side of the
524 inverse U-shape we observed in overall task performance (Fig. 2; suppl. Fig. 8; Fig. 3C-F) might be
525 caused by age differences in behavioral quality: Thirteen-to-15-year-olds had reached adult levels
526 of behavioral quality, while younger participants showed noisier, less focused, and less consistent
527 behavior, potentially related to relatively less experience with computerized tasks, psychological
528 experiments, and assessments of performance.
529 Nevertheless, PC1 could not explain the other side of the inverse U-shape in overall task perfor-
530 mance, i.e., how 13-to-15-year-olds outperformed older teenagers (15-17) and adults (18-30). The
531 key to this question might lie in PC2 (updating time scales): PC2 showed a step function, such that
532 participants aged 8-15 acted on short times scales, whereas participants aged 15-30 acted on long
533 time scales (Fig. 5E, top-right). A post-hoc t-test revealed that the difference between both groups
534 was significant ($t(266.2) = 3.44$, $p < 0.001$). This pattern is in accordance with the interpretation that
535 shorter time scales, facilitating rapid behavioral switches (suppl. Fig. 13B, left), were more ben-
536 eficial for the current task than longer time scales, which impeded them (suppl. Fig. 13B, right).
537 Times scales might therefore represent the determining factor that allowed 13-to-15-year-olds to
538 outperform older participants.
539 PC4 (positive updates) differentiated the larger group of 13-to-17-year-olds from both younger
540 (8-13) and older (18-30) participants (Fig. 5E, bottom-right), as revealed by significant post-hoc,
541 Bonferroni-corrected, t-tests (8-13 vs 13-17: $t(176.8) = 2.28$, $p = 0.047$; 13-17 vs 18-30: $t(176.6) =$
542 2.49, $p = 0.028$). In other words, after accounting for variance in PCs 1-3, the remaining variance
543 was explained by 13-to-17-year-olds' relatively longer updating timescales for positive outcomes,
544 meaning that positive outcomes had relatively weaker immediate, but stronger long-lasting effects.
545 Even though longer positive time scales might play a role in 13-to-15-year-olds' remarkable task
546 performance, they are unlikely the only explanation because they did not distinguish 13-to-15-
547 year-olds from 15-to-17-year-olds.

Discussion

549 Across species, the adolescent transition from childhood to adulthood brings great challenges for
550 learning and exploration. These challenges may have caused the adolescent brain to evolve be-
551 havioral tendencies that promote adaptive learning in rapidly changing, uncertain environments.
552 To test this idea, we examined the choice behavior of a large sample of participants across a wide
553 age range in a stochastic and volatile task, which we adapted from rodent studies (Tai et al., 2012).

Behavioral Results

555 Indeed, 13-to-15-year-olds performed better than both younger (8-13) and older participants, in-
556 cluding adults (15-30): 13-to-15-year-olds achieved the highest overall accuracy, were most willing
557 to wait out negative feedback, and made the best choices during stable task periods. 13-to-15-
558 year-olds also used negative feedback most optimally to guide future choices, being least affected
559 by proximal, but most sensitive to distal outcomes. This shows an ability to ignore ambivalent
560 information while responding appropriately to meaningful patterns.
561 Whereas the developmental literature has long documented linear developments between
562 childhood and adulthood, a recent focus on the period of adolescence has revealed an abundance
563 of similar U-shaped trajectories, especially in the domain of neuro-cognitive and emotional pro-
564 cessing (for reviews, see Dahl et al., 2018; Giedd et al., 1999; Somerville and Casey, 2010; Sowell
565 et al., 2003; Toga et al., 2006). Increasingly, evidence is accumulating that adolescents outperform
566 adults in various domains, including probabilistic learning (Cauffman et al., 2010; Davidow et al.,

567 2016), deterministic reversals (van der Schaaf et al., 2011), creativity (Kleibeuker et al., 2013), and
568 social learning (Gopnik et al., 2017). Similar prowess in flexibility has also been reported in studies
569 of developing rodents (Guskjolen et al., 2017; Johnson and Wilbrecht, 2011; Simon et al., 2013).

Modeling results

RL Model

To understand which cognitive and neural processes underlay these differences in task behavior,
we created two types of computational models, RL and BI. To reproduce human behavior appro-
priately, the RL model required several augmentations: the ability to learn from counterfactual
outcomes (updating values of non-chosen actions); different learning rates for positive and nega-
tive outcomes (α_+ and α_-); persistence, i.e., the tendency to repeat actions independently of their
previous outcomes (p); and the classic decision temperature β, which allows for the exploration of
non-maximizing actions. One reason that RL models have been used so extensively in the (clinical)
cognitive neurosciences is the abundance of evidence that has linked RL computations to specific
neural mechanisms in a specialized network of brain regions including basal ganglia, cortical, and
limbic regions (for reviews, see Frank and Claus, 2006; D. Lee et al., 2012; Niv, 2009; O'Doherty
et al., 2015; Schultz and Dickinson, 2000). Using RL modeling in developmental population there-
fore holds the promise of shedding light not only on cognitive, but also brain development (e.g.,
Christakou et al., 2013; Davidow et al., 2016; Javadi et al., 2014; Master et al., 2020; for reviews, see
Nussenbaum and Hartley, 2019; van den Bos et al., 2017). In our study, RL models showed that
choice parameters (β, p) grew monotonically throughout childhood and adolescence, maturing in
late adolescence or early adulthood. This is consistent with previous developmental modeling
research (reviewed in Nussenbaum and Hartley, 2019), and with a role of late-developing brain
circuits in choice behavior (Giedd et al., 1999; Gogtay et al., 2004; Nussenbaum and Hartley, 2019;
Sowell et al., 2003; Toga et al., 2006). Nevertheless, our study provided a more detailed picture
of the developmental trajectory than previous studies, showing a striking initial increase in the
youngest participants, followed by an asymptote in late adolescence.

Whereas RL choice parameters have shown relatively consistent age trajectories across studies
in the previous literature, there have been major inconsistencies for learning rate parameters (for
review, see Nussenbaum and Hartley, 2019). In our study, learning rates from negative feedback
(α_-) showed a pronounced U-shape, with the lowest (most beneficial) values in 13-to-15-year-olds.
Learning rates from positive feedback (α_+), on the other hand, were stable throughout childhood
and adolescence, then suddenly increased in adults. This suggests that one of the reasons why
adolescents outperformed younger and older participants in the current task was that they re-
sponded more appropriately to the stochastic negative feedback, paying attention to consistent
patterns and avoiding impulsive switches based on single outcomes.

Accordingly, previous studies have shown unique feedback processing in adolescents com-
pared to younger and older participants (for review, see Lourenco and Casey, 2013). Nevertheless,
whereas some previous studies have shown hypersensitivity to feedback, others have shown hypo-
sensitivity, and some have found effects unique to positive feedback, while others were unique to
negative feedback, or applied to both (e.g., Christakou et al., 2013; Davidow et al., 2016; Palminteri
et al., 2016; van den Bos et al., 2009; for review, see Lourenco and Casey, 2013). These discrep-
ancies make it difficult to link feedback processing to a single neural system across studies, and
indeed, several systems have been suggested to underlie learning, including striatal incremen-
tal learning (Yagishita et al., 2014), hippocampal-based episodic memory (Bornstein and Norman,
2017; Wimmer et al., 2014), and frontal-cortical cognitive control (Badre et al., 2010; Collins and
Frank, 2012; Daw et al., 2011). Evidence is also accumulating that the same model parameters can
reflect different neuro-cognitive systems in different tasks when cognitive demands differ (Eckstein
et al., n.d.; Nussenbaum and Hartley, 2019; but see Gershman, 2017; Gershman and Uchida, 2019;
Starkweather et al., 2018 for a single-system account based on neural modulation). In accordance
with these results, in our study, RL parameter α_- showed similar developmental trajectories as BI

parameters p_{switch} and p_{reward}, suggesting that α_- might have taken on a mental-model-like role in
planning behavioral switches, rather than reflecting the incremental, striatal-based learning many
might expect from an RL learning-rate parameter (Schultz and Dickinson, 2000).

BI Model

Despite the large success and wide application of RL models in the (developmental) cognitive neu-
rosciences (for reviews, see Frank and Claus, 2006; D. Lee et al., 2012; Niv, 2009; Nussenbaum and
Hartley, 2019; O'Doherty et al., 2015; Schultz and Dickinson, 2000; van den Bos et al., 2017), it has
recently been proposed that the BI framework is better suited to model reversal-learning tasks
(Bartolo and Averbeck, 2020; Bromberg-Martin et al., 2010; Costa et al., 2015; Fuhs and Touret-
zky, 2007; Gershman and Uchida, 2019; Hauser et al., 2014; Izquierdo et al., 2017; Schlagenhauf
et al., 2014; Solway and Botvinick, 2012). BI is often used as a model of inductive reasoning, i.e.,
the prediction of future events based on past regularities (Hume, 2008), and has been applied to
a wide range of domains including categorical thinking (Goodman et al., 2008; Medin and Schaf-
fer, 1978), word learning (Xu and Tenenbaum, 2007), causal reasoning (Griffiths and Tenenbaum,
2005), and creativity (Collins and Koechlin, 2012; for reviews, see Friston, 2009; Tenenbaum et al.,
2011; also see special issue Chater et al., 2006). In addition, BI has become an indispensable tool
in understanding cognitive development and learning, and BI models have even been proposed
to reconcile the century-long debate between empiricist and nativist accounts of cognitive devel-
opment (for examples, see special issue Gopnik and Tenenbaum, 2007). Even though they consist
separate literatures, some inductive reasoning tasks have the same structure as stochastic reversal-
learning tasks, presenting participants with observations that are generated from a noisy process,
whose otherwise stable mean sometimes changes unexpectedly (e.g., Nassar et al., 2012; O'Reilly
et al., 2013; Yu and Dayan, 2005). Like in our task, the challenge of these tasks lies in differentiating
noisy observations during stable task periods from actual switches in the hidden state.

Due to their natural framing of volatile, stochastic environments (Chater et al., 2006; Friston,
2009; Gershman and Uchida, 2019; Izquierdo et al., 2017; Tenenbaum et al., 2011), and their huge
promise for developmental research (Gopnik and Tenenbaum, 2007), we decided to fit a BI model
to the current task, and compare it to the more established RL model. The BI model showed al-
most identical age trajectories of parameters β and p as the RL model, confirming that in our task,
choice parameters increased monotonically through the second decade of life. BI mental model
parameters—reward stochasticity p_{reward} and task volatility p_{switch}—, on the other hand, showed pro-
nounced inverse-U trajectories, with most accurate values in 13-to-15-year-olds. This means that
13-to-15-year-olds possessed the most optimal mental model of the task (even though this model
still deviated from Bayes-optimal behavior, being both too volatile and too deterministic). Children
and adults treated the task as even more volatile and more deterministic than adolescents. For
example, 8-to-13-year-olds behaved as if the task rewarded 92% of their correct responses, and
adults as if it rewarded 91%, whereas 13-to-15-year-olds only expected rewards for 89% of their
correct choices; in actuality, 75% of correct responses were rewarded.

Previous research has suggested that model parameters might be more accurately interpreted
as cognitive "adaptation" rather than fixed "settings" (Nussenbaum and Hartley, 2019): Rather
than reflecting a particular, developmentally-fixed state of the neural system (setting), parameters
might instead reflect an ability of participants to adjust to specific task demands (adaptation; for
a similar argument, see Davidow et al., 2016). In this light, our study suggests that adolescents
have a unique ability to adapt to probabilistic (p_{reward}) and volatile environments (p_{switch}), showing
an optimal response to negative feedback (α_-).

PCA on Both Models

663 We next directly compared the RL and BI models to each other, and found that they captured both
664 overlapping and unique behavioral patterns, and invoked both overlapping and unique cognitive
665 processes (for detailed discussion, see section Benefits of Using Multiple Model Types). To combine

the unique insights of both models, while stripping away redundancies, we performed a PCA on the parameters of both. This analysis revealed that general behavioral quality (PC1) improved steeply during childhood and early adolescence, and reached a stable plateau in 13-to-15-year-olds, which lasted through adulthood. Updating time scales (PC2), on the other hand, remained short during childhood and adolescence, including 13-to-15-year-olds, and only transitioned to adult levels thereafter. This suggests that 13-to-15-year-olds outperformed younger participants due to adult-like levels of behavioral quality (PC1), while outperforming adults due to child-like updating time scales (PC2). Reward processing (PC4) showed an inverse-U trajectory with minimum in 13-to-17-year-olds. Though this PC therefore cannot account for differences between 13-to-15-year-olds and 15-to-17-year-olds, it may contribute to differences between 13-to-15-year-olds and both children (8-13) and adults (18-30).

In conclusion, adolescents aged 13-15 likely performed so well on this task because they occupied a developmental "sweet spot" that combined mature levels of behavioral quality (PC1) with youthful times scales (PC2) and unique long-term updating of rewards (PC4). Though this combination would not be optimal in all environments (e.g., short time scales would be less beneficial if contexts switched less frequently), it was beneficial in our task, which supports the idea that the adolescent brain may pass through stages that have evolved to enhance success in stochastic and volatile environments.

Different Models at Different Ages?

Previous studies have shown that participants of different ages sometimes are better fitted by different computational models, suggesting that they might employ entirely different cognitive mechanisms at different ages (e.g., Palminteri et al., 2016). Could the same be the case in our study? For example, children's cognitive processes might resemble a simple incremental RL model, whereas adolescents' might approximate the mental-model-based—and more optimal—BI model. This outcome would be in accordance with the previously reported increase in "model-based" (compared to "model-free") behavior with age (Decker et al., 2016), as well as with a reported increase in the tendency to employ counterfactual updating, which also reflects an improved mental task model (Palminteri et al., 2016). Even though this is a justified question, it is unlikely that different models applied to different age groups in our study, given that both models captured the behavior of all age groups equally well during model validation. Compared to previous studies that showed age differences in model types, the greater flexibility of our models in terms of the number of free parameters and other augmentations might have allowed them to capture more age differences, obliterating the need to change the model itself.

Previous Reversal-Learning Research in Adolescents

Even though reversal learning tasks have frequently been used in developmental samples (e.g., Boehme et al., 2017; Dickstein, Finger, Brotman, et al., 2010; Dickstein, Finger, Skup, et al., 2010; Finger et al., 2008; Harms et al., 2018), the development of reversal learning itself has received relatively little attention so far (Hauser et al., 2015; Javadi et al., 2014; van der Schaaf et al., 2011). One of the previous developmental studies (Javadi et al., 2014), comparing a large sample of 260 14-to-15-year-olds to 29 adults, did not show the same performance differences we found in our study. A likely reason is a crucial difference between task designs: whereas this study rewarded both correct (70%) and incorrect choices (40%), our study only rewarded correct choices (75%), but never incorrect ones (0%), making positive feedback perfectly diagnostic of correct choice (for study details, see suppl. Table 1). The behavioral benefits of adolescents we report here might therefore be contingent on the diagnosticity of positive feedback, a conclusion that is also supported by our PCA results (see section Integrating RL and BI Model Findings).

Another study compared a smaller sample of 19 adolescents across a wider age range (12-16 years) to 17 adults (Hauser et al., 2015), and also found no differences in overall task performance (see suppl. Table 2). This result, however, is in accordance with our study: with a U-shaped trajec-

tory of performance, combining participants across the entire age range of 12-16 years will lead to a similar average as shown by adults. With respect to computational modeling, the study reported larger counterfactual negative learning rates in adolescents compared to adults, whereas we found the inverse. However, the study by Hauser et al. (2015) only provided limited model comparison, and did not validate the winning model against behavioral data, leaving open the possibility that model parameters did not adequately capture the observed behavior (Blohm et al., 2020; Palminteri et al., 2017; Wilson and Collins, 2019). In support of this conclusion, not just counterfactual negative learning, but all other learning parameters showed the same pattern of differences between adolescents and adults (Hauser et al., 2015, Fig. 2), and a similar model was previously found to generally fit adolescents worse than adults (Javadi et al., 2014), suggesting that differences in counterfactual negative learning were an unspecific artifact of other issues related to model fitting.

A third study (van der Schaaf et al., 2011) compared three groups of 15 adolescents each (10-17 years) to 16 adults (suppl. Table 1), thereby providing the only previous study that allowed treating age as a continuous variable, and therefore detecting potential U-shaped developments. Indeed, this study revealed the same inverse U-shape in performance on reversal trials as our study (Table 2; van der Schaaf et al., 2011, Fig. 3C). Despite differences in specific outcomes, both studies were also compatible in terms of adolescents' unique learning patterns: While adolescents showed the most *balanced* reward-to-punishment learning in the Van der Schaaf et al. (2011), where rewards and punishments provided the same amount of information, they showed the most *reduced* learning from negative outcomes in our study, in which negative outcomes provided less information than positive outcomes. In other words, adolescents showed balanced learning in a task with balanced positive-to-negative feedback (van der Schaaf et al., 2011), but biased learning in a task with biased feedback (ours). Applying the lens of "adaptation" (Nussenbaum and Hartley, 2019) highlights the consistency between both studies, and suggests that adolescents were more able to adapt to the specific settings of reversal tasks than children or adults.

Taken together, our study builds on and extends previous findings, showing that some developmental changes occur linearly, with a monotonic trajectory between childhood and adulthood (e.g., choice parameters β and p), whereas other changes are U-shaped, and show prominent peaks during adolescence (e.g., mental model parameters p_{switch} and p_{reward}; response to negative feedback α_-). Previous group-based studies were unable to reveal these pattern in as much detail.

A Role of Puberty?

This study has shown that age makes a crucial difference in how participants make reward-based decisions in a volatile, stochastic environment. Nevertheless, we have not answered the question which biological mechanisms underlie these differences. There is growing evidence that gonadal hormones affect inhibitory neurotransmission, spine pruning, and other variables in the prefrontal cortex of rodents (Delevich et al., 2019; Delevich et al., 2018; Drzewiecki et al., 2016; Juraska and Willing, 2017; Piekarski, Boivin, et al., 2017; Piekarski, Johnson, et al., 2017), and evidence for puberty-related neurobehavioral change is also accumulating in human studies (Blakemore et al., 2010; Braams et al., 2015; Gracia-Tabuenca et al., 2021; Laube, van den Bos, et al., 2020; Op de Macks et al., 2016), suggesting that puberty-related changes in brain chemistry might be a mechanism behind the observed differences. To answer this question, we investigated how performance and model parameters changed with pubertal development—assessed through salivary testosterone levels (Master et al., 2020) and self-reported physical development (Petersen et al., 1988), This analysis revealed qualitatively similar patterns compared to age (suppl. Fig. 2, 3, 4; suppl. Tables 3, 4; for discussion, see suppl. Text). Nevertheless, pubertal measures were highly correlated with age (suppl. Fig. 1), making it difficult to identify puberty-specific effects. To investigate whether pubertal development had a unique effect after controlling for age, we also tested puberty effects within different age bins, but failed to reveal significant differences (suppl. Fig. 5, 6, 7). Nevertheless, some trends that emerged in the pubertal analyses, especially with respect

765 to pre-pubertal participants, deserve a more detailed investigation in future research (section **??**).
766 Thus, pubertal development was unlikely a mechanism that underlay the observed age differences
767 in the current study. A clear limitation of our study is that it was cross-sectional, rather than longitu-
768 dinal. Future research with longitudinal designs might better address the potential role of puberty
769 (Kraemer et al., 2000).

Benefits of Using Multiple Model Types

As mentioned above, it was one of our goals in this study to compare RL models—the standard
in the learning and reversal literature—to BI models—claimed increasingly frequently to provide a
better fit to reversal-learning tasks than RL models. We wanted to know if one model fit the data
strictly better than the other; whether they captured different behavioral patterns; and whether
they invoked different cognitive processes. To answer the two latter questions, we assessed sim-
ulated behavior from each model using the other model, determined whether parameters were
correlated between models, and whether each parameter's variance could be explained by the
other model. All three analyses showed that the two models captured overlapping, but not fully
identical behaviors, using overlapping, but not fully identical cognitive mechanisms. This shows
that each model was unique, and that one could not be replaced by the other.

To answer the first question, we employed a broader approach to model comparison than
most previous studies. Following the standard computational modeling approach, one type of
cognitive model is selected (e.g., RL), and different variants of this type are compared to find the
best-fitting one, which is then interpreted as the cognitive process employed by participants. The
best-fitting model is identified using quantitative criteria of model fit such as Bayes factors (Mulder
and Wagenmakers, 2016), minimum description length (Grünwald, 2007), or other appropriate
measures of model fit that take model complexity into account (e.g. AIC, BIC, or here WAIC; Pitt
and Myung, 2002; Watanabe, 2013). One problem with this approach is that it cannot rule out
whether a model of a different type (e.g., BI) would fit the data better altogether. In the words of
Nassar and Frank (2016), "the question always remains: could the data be better explained through
a different set of mechanisms under a different set of assumptions?" This issue can be mitigated by
verifying that the chosen model reproduces human behavior adequately, and is therefore a valid
reflection of the observed data (Heathcote et al., 2015; Palminteri et al., 2017; Wilson and Collins,
2019), but only a small number of researchers adopt this practice consistently, so that we are often
left wondering whether the "best-fitting" model actually captures the observed behavior.

Another concern with the standard approach, which is more difficult to address, is that differ-
ent types of models frame behavior in terms of different cognitive processes, and one framing can
be more informative, interpretable, appropriate to test the current hypothesis, concise, or in any
other way better, than a different framing, and should therefore be chosen, potentially despite
lower numerical model fit (Kording et al., 2020; Uttal, 1990; Webb, 2001): "The model that best
fits your data may not be the best model" (Blohm et al., 2020). Identifying the "best" model based
on such qualitative criteria is fundamentally difficult, and often based on researchers' (explicitly
stated or implicit) scientific goals (e.g., a preference for explanatory or predictive models; Bernardo
and Smith, 2009; Navarro, 2019) and research philosophy (Blohm et al., 2020). The conclusion of
decades of model building research is therefore that model selection needs to strike a balance be-
tween many aspects of model quality, including qualitative (e.g., generality, explanatory adequacy)
and quantitative criteria (e.g., descriptive adequacy, complexity; Jacobs and Grainger, 1994). In
other words, numerical model fit (e.g., BIC, AIC, WAIC) should never be used as the only criterion to
assess model quality—good modeling practices take several criteria into account when assessing a
model, including its qualitative fit to the data, generality, and explanatory power, amongst others.

Applying this approach, we found that both types of models—properly tuned—captured partic-
ipant behavior in our task equally well. The numerical model fit (WAIC) favored the RL model over
the BI model, but qualitative model validation showed that both models captured human behavior
equally well (Palminteri et al., 2017). Model development and assessment of model quality can be

based on "many potential criteria" (Blohm et al., 2020), which are equally valid, depending on the scientific question (Kording et al., 2020). In our case, the main motivation for the RL model was the continuity and comparability with previous research in the cognitive neurosciences, and specifically on the reversal-learning paradigm. We achieved this goal by creating an RL model that was continuous with previous research, uniting several previously proposed augmentations that had not been combined before, and achieving an overall better fit to the data. The main motivation for the BI model were numerous claims for its superiority compared to RL in our specific task (Gershman and Uchida, 2019; Izquierdo et al., 2017), and its promise in the cognitive (Tenenbaum et al., 2011), brain (Friston, 2009), and developmental sciences (Gopnik and Tenenbaum, 2007). Indeed, the BI model provided an immense advantage in terms of interpretability: BI model parameters directly mapped onto the concepts of interest for our research (stochasticity, volatility), promising a more direct window into their perception by participants. This highlights the important fact that each computational model offers just one of many possible interpretations of the underlying cognitive mechanism, and specifically, that many cognitive processes that have traditionally been explained in terms of RL could also be explained in terms of BI (or the other way around). Based on all these criteria, we concluded that both models, RL and BI, provided accurate, informative, and conclusive insights into our research questions, and that both should be interpreted with equal determination.

Fitting both models provided several benefits in understanding participants' cognitive processes in our task: Both models provided converging as well as additive evidence. Converging results showed surprisingly strong, direct replication ($\beta_{RL} \leftrightarrow \beta_{BI}$, $p_{RL} \leftrightarrow p_{BI}$), and parallelism between different model parameters across models (p_{reward}, p_{switch}, α_-). Independent components led to additive insights (α_+). In addition, each model's conceptual framework and interpretation of the cognitive process became more distinctive in direct comparison with the other. For example, the parallelism between BI mental-model parameters and RL negative learning rate helped clarify the role of this otherwise ambiguous parameter. A final advantage of fitting both models was the possibility to investigate patterns that combined the insights of both models, going beyond any specific one, by using PCA on the shared parameter space. This analysis exposed a different set of factors, which differentiated 13-to-15-year-olds from younger participants (PC1), from older participants (PC2), and from both (PC4).

Conclusion

In conclusion, we used a simple task based on volatility and stochasticity to show that adolescents outperformed adults in a task that represented the kind of learning challenge that may have ecological validity to the transitions and challenges of adolescence. In our community sample, behavior was most optimal at age 13-15. We used two models to examine the underlying cognitive processes, based on RL and BI. The results suggest that adolescents achieved better performance for several reasons: (1) 13-to-15-year-olds lay on the right spot in a monotonic trajectory between childhood and adulthood (p and β). (2) 13-to-15-year-olds were outliers in terms of their ability to accurately assess the volatility and stochasticity of their environment, and in terms of their integration of negative outcomes (U-shapes in p_{reward}, p_{switch}, and α_-). (3) 13-to-15-year-olds combined adult-like (PC1), child-like (PC2), and developmentally unique (PC4) strategies. These data suggest that multiple (neuro)cognitive systems might underlie developmental changes in brain function, at staggered time scales. Pubertal development and steroid hormones may impact a subset of these processes, yet causality is difficult to determine without manipulation or longitudinal designs (Kraemer et al., 2000).

For purposes of translation from the lab to the "real world", our study indicates that how youth learn and decide changes in a nonlinear fashion as they grow. This underscores the importance of youth-serving programs that are developmentally informed and avoid a one-size-fits-all approach. Finally, these data support a positive view of adolescence and the idea that the adolescent brain exhibits remarkable learning capacities that should be celebrated.

865 Methods

866 Participants

All procedures were approved by the Committee for the Protection of Human Subjects at the Uni-
versity of California, Berkeley. We tested 312 participants: 191 children and adolescents (ages 8-17)
and 55 adults (ages 25-30) were recruited from the community and completed a battery of comput-
erized tasks, questionnaires, and saliva samples (Master et al., 2020); 66 university undergraduate
students (aged 18-50) completed the four tasks as well, but not the pubertal-development ques-
tionnaire (PDS; Petersen et al., 1988) or saliva sample. Community participants were prescreened
for the absence of present or past psychological and neurological disorders; the undergraduate
sample indicated the absence of these. Compensation for community participants consisted in 25$
for the 1-2 hour in-lab portion of the experiment and 25$ for completing optional take-home saliva
samples; undergraduate students received course credit for participation in the 1-hour study.

877 Exclusion Criteria

Out of the 191 participants under 18, 184 completed the current task; reasons for not completing
the task included getting tired, running out of time, and technical issues. Five participants (mean
age 10.0 years) were excluded because their mean accuracy was below 58% (chance: 50%), an el-
bow point in accuracy, which suggests that they did not pay attention to the task. This led to a
sample of 179 participants under 18 (male: 96, female: 83). Two participants from the undergrad-
uate sample were excluded because they were older than 30, leading to a sample aged 18-28; 7
were excluded because they failed to indicate their age. This led to a final sample of 57 undergrad-
uate participants (male: 19, female: 38). All 55 adult community participants (male: 26, female: 29)
completed the task and were included in the analyses, leading to a sample size of 179 participants
below 18, and 291 in total (suppl. Fig. 1).

888 Quantile Bins

889 For some analyses, we split participants into quantiles based on age. This way of data binning
890 led to samples of adequate sizes for summary statistics, and balanced group sizes after exclusion.
891 Quantiles were calculated separately within each sex.

892 Testing Procedure

After entering the testing room, participants under 18 years and their guardians provided informed
assent and permission; participants over 18 provided informed consent. Guardians and partici-
pants over 18 filled out a demographic form. Participants were led into a quiet testing room in
view of their guardians, where they used a video game controller to complete four computerized
tasks. At the conclusion of the tasks, participants between 11 and 18 completed the PDS question-
naire themselves and were measured in height and weight. Participants were then compensated
with $25 Amazon gift cards.

900 Experimental Design

The task described in this work was the last of the four tasks. The other tasks will be or have
been reported elsewhere (Master et al., 2020; Xia et al., 2020). The goal of this task was to collect
golden coins, which were hidden in one of two green boxes. On each trial, participants decided
which box to open, and task contingencies switched unpredictably throughout the task (Fig. 1B).
Before the main task, participants completed a 3-step tutorial: A first prompt explained that one
of the two boxes contained a coin (was "magical"), whereas the other one did not. Ten practice
trials followed on which one box revealed a coin when selected, whereas the other was empty
(deterministic tutorial). The second prompt stated that the magical box would sometimes switch
sides. Participants then received eight trials on which the second box contained the coin (but not
the first), followed by eight more trials on which the first box contained the coin (but not the second;

switching tutorial). The third and last prompt explained that even the magical box did not always contain a coin. This prompt directly led into the main task (stochastic switching), with 120 trials.

In the main task, the correct box was rewarded in 75% of trials; the incorrect box was never rewarded. After participants reached a performance criterion (see below), it became possible for contingencies to switch (without notice), such that the previously incorrect box was now the correct one. The performance criterion was to collect 7-15 rewards, whereby the specific number was pre-randomized for each block. Any number of non-rewarded trials was allowed in-between rewarded trials. Due to this design, switches only occurred after rewarded trials. For consistency with the rodent version of the task (Tai et al., 2012), the first correct choice after a switch was always rewarded (while retaining an average of %75 probability of reward for correct choices).

Behavioral Analyses

We assessed the effects of age on behavioral outcomes (Fig. 2), using (logistic) mixed-effects regression models with the package lme4 (Bates et al., 2015) in R (RCoreTeam, 2016). All models included the following set of regressors to predict outcomes of interest (e.g., overall accuracy, response times): Age, to assess the linear effect of age on the outcome; squared age, to assess the quadratic (U-shaped) effect of age; and sex; furthermore all models specified random effects of participants, allowing participants' intercepts and slopes to vary independently. When models included additional predictors, this is noted in the main text.

We assessed the effects of previous outcomes on participants' choices (suppl. Fig. 8B, C, E, F) using a logistic mixed-effects regression model, which predicted actions (left, right) from previous outcomes (details below), while testing for effects of and interactions with sex, z-scored age, and z-scored quadratic age, specifying participants as mixed effects. We included one predictor for positive and one for negative outcomes at each delay i with respect to the predicted action (e.g., $i = 1$ trial ago). Outcome predictors were coded -1 for left and +1 for right choices, and 0 otherwise. Including predictors of trials $1 \leq i \leq 8$ provided the best model fit (suppl. Table 7). To visualize the results of this grand regression model (including all participants), we ran a separate model for each participant with the same structure, and show individual fits in suppl. Fig. 8B, C, E, F.

Computational Models

Reinforcement Learning (RL) Models

In RL, decisions are made based on action values, which are continuously updated based on outcomes (Sutton and Barto, 2017). A simple RL model has two parameters, learning rate α and decision temperature β. On each trial t, the value $Q_t(a)$ of action a is updated based on the observed outcome $o_t \in [0, 1]$ (reward, no reward), in the following way:

$$Q_{t+1}(a) = Q_t(a) + \alpha(o_t - Q_t(a))$$

This means that previous action values are updated in proportion to the difference between the estimated value and the actual reward, scaled by the learning rate α. The difference itself, $o_t - Q_t(a)$, is called "reward prediction error".

Over time, action values approximate the true underlying reward probabilities. Decisions are based on these values by calculating action probabilities using a softmax transform:

$$p_t(a) = \frac{exp(\beta\ Q_t(a))}{exp(\beta\ Q_t(a)) + exp(\beta\ Q_t(a_{ns}))}$$

Here, a is the selected, and a_{ns} the non-selected action.

The best-fit 4-parameter RL model was based on this 2-parameter model, with additional parameters learning rate for negative outcomes α_-, persistence p, as well as counterfactual reasoning (see below). Adding α_- allowed for separate updates of rewarded ($o_t = 1$) and non-rewarded ($o_t = 0$) trials: $Q_t(a) = Q_t(a) + \alpha_+(o_t - Q_t(a))$ iff $o_t = 1$, and $Q_t(a) = Q_t(a) + \alpha_-(o_t - Q_t(a))$ iff $o_t = 0$, with independent α_- and α_+. Choice persistence or "stickiness" p changed the value of the previously-selected

action a_t on the subsequent trial, biasing toward staying ($p > 0$) or switching ($p < 0$): $Q(a_t) = Q(a_t) + p$
iff $a_t = a_{t-1}$.

Counterfactual reasoning was implemented through updates to the values of non-selected ac-
tions, using counterfactual outcomes $1 - o_t$: $Q_{t+1}(a_{ns}) = Q_t(a_{ns}) + \alpha_+((1 - o_t) - Q_t(a_{ns}))$ iff $o = 1$, and
$Q_{t+1}(a_{ns}) = Q_t(a_{ns}) + \alpha_-((1 - o_t) - Q_t(a_{ns}))$ iff $o = 0$. Initially, we used four parameters α_+, α_{+c}, α_-, and α_{-c}
to represent each combination of value-based ("+" versus "-") and counter-factual ("c" versus fac-
tual) updating, but collapsing $\alpha_+ = \alpha_{+c}$ and $\alpha_- = \alpha_{-c}$ improved model fit (Table 2). This suggests that
outcomes triggered equal-sized updates to chosen and unchosen actions. Explained differently,
the final model based decisions on a single value estimate—the value difference between the two
available actions—, rather than on independent value estimates for each. Chosen and unchosen
actions were updated to the same degree and in opposite directions on each trial.

Action values were initialized at 0.5 for all models, reflecting equal initial values for the two
actions.

Bayesian Inference (BI) Models

962 The BI model assumes that participants know that the task has two latent states: "Left action is
correct" ($a_{left} = cor$) and "Right action is correct" ($a_{right} = cor$), where cor stands for correct (inc:
incorrect). Participants assume that on each trial, the latent state switches with probability p_{switch},
and that in each state, the probability of receiving a reward for the correct action is p_{reward} (Fig.
3A). On each trial, participants select an action in two phases, using the Bayesian Filter algorithm
(Sarkka, 2013): (1) In the *estimation phase*, participants infer the hidden state of the previous trial
$t - 1$, based on the outcome o_{t-1} they received for their action a_{t-1}, using Bayes rule:

$$p(a_{t-1} = cor \mid o_{t-1}) = \frac{p(o_{t-1}|a_{t-1} = cor)\ p(a_{t-1} = cor)}{p(o_{t-1}|a_{t-1} = cor)\ p(a_{t-1} = cor) + p(o_{t-1}|a_{t-1} = inc)\ p(a_{t-1} = inc)}$$

$p(a_{t-1} = cor)$ is the prior probability that a_{t-1} was correct (on the first trial, $p(a = cor) = 0.5$ for both
actions), and $p(o_{t-1}|a_{t-1})$ is the likelihood of the observed outcome o_{t-1} given action a_{t-1}. According
to the mental model, likelihoods are (dropping underscripts for clarity): $p(o = 1|a = cor) = p_{reward}$,
$p(o = 0|a = cor) = 1 - p_{reward}$, $p(o = 1|a = inc) = \epsilon$, and $p(o = 0|a = cor) = 1 - \epsilon$, where ϵ is the probability
of receiving a reward for an incorrect action, which was 0 in reality, but we set $\epsilon = 0.0001$ to avoid
model degeneracy.

   (2) In the *prediction phase*, participants integrate the possibility of state switches by propagating
the inferred knowledge about the hidden state at $t - 1$ forward to trial t:

$$p(a_t = cor) = (1 - p_{switch})\ p(a_{t-1} = cor) + p_{switch}\ p(a_{t-1} = inc)$$

We first assessed a parameter-free version of the BI model, truthfully setting $p_{reward} = 0.75$, and
$p_{switch} = 0.05$. Lacking free parameters, this model was unable to capture individual differences
and led to poor qualitative (suppl. Fig. 12A) and quantitative model fit (Table 2). The best-fit BI
model had four free parameters: p_{reward} and p_{switch}, as well as the choice parameters β and p, like
the winning RL model. β and p were introduced by applying a softmax to $p(a_t = cor)$ to calculate
$p(a_t)$, the probability of selecting action a on trial t: $p(a_t) = \frac{1}{(1+exp(\beta(0.5-p-p(a_t=cor))))}$. When both actions
had the same probability $p(a)$ and persistence $p > 0$, then staying was more likely; when $p < 0$, then
switching was more likely.

Model Fitting and Comparison

977 We fitted parameters using hierarchical Bayesian methods (Katahira, 2016; M. D. Lee, 2011; Fig.
3B), and found that the obtained results clearly superseded those of classical maximum-likelihood
fitting in terms of parameter recovery (suppl. Fig. 9). Rather than fitting individual participants,
hierarchical Bayesian model fitting estimates the parameters of an entire population jointly, by
maximizing the posterior probability $p(\theta|data)$ of all parameters θ conditioned on the observed
data, using Bayesian methods:

$$p(\theta|data) \propto p(data|\theta)p(\theta)$$

The unique feature of hierarchical Bayesian model fitting is that individual parameters are embedded in a hierarchical structure of priors, which helps resolve uncertainty at the individual level.

We ran two models to fit parameters: The "age-less" model was used to estimate individuals' parameters in the least biased way and conduct binned analyses on parameter differences; the "age-based" model was used to statistically assess the shapes of parameters' age trajectories. In the age-less model, each individual j's parameters $\theta_j^{RL} = [p, \beta, \alpha_-, \alpha_+]$ or $\theta_j^{BI} = [p, \beta, p_{switch}, p_{reward}]$ were drawn from group-wide prior parameter distributions. Parameter β was drawn from a prior Gamma distribution, p from a prior Normal distribution, and α_+, α_-, p_{reward}, and p_{switch} from prior Beta distributions, in accordance with each parameter's allowed range of values. The hyperpriors of these distributions are shown in suppl. Table 8.

Each individual's parameters θ_j were entered into the RL or BI model, with the goal of determining both the group-level and individual parameters with the largest posterior probability under the behavioral data $p(\theta|data)$. Because $p(\theta|data)$ was analytically intractable, we approximated it using Markov-Chain Monte Carlo sampling, using the no-U-Turn sampler as implemented in the PyMC3 package in python (Salvatier et al., 2016). We ran 2 chains per model with 6,000 samples per chain, discarding the first 1,000 as burn-in. All models converged with small MC errors, sufficient effective sample sizes, and $\hat{R}$ close to 1 (suppl. Table 9). For model comparison, we used the Watanabe-Akaike information criterion (WAIC), which estimates the expected out-of-sample prediction error using a bias-corrected adjustment of within-sample error (Watanabe, 2013).

To obtain each participant's individual fitted parameters, we calculated the means over all posterior samples in the age-less model, as shown in Fig. 4 and suppl. Figures 10, 11, and 12. To test whether a parameter θ differed between two age groups $a1$ and $a2$, we determined the number of MCMC samples in the age-less model in which the parameter was larger in one group than the other, i.e., the expectation $\mathbb{E}(\theta_{a1} < \theta_{a1})$ across MCMC samples. Following statistical convention, $p < 0.05$ was used to determine significance.

The age-less model was necessary to show individual parameters in the least biased way, given that this model did not have access to participants' ages. To statistically assess the continuous effects of age on model parameters, we conducted a separate model in which model parameters were allowed to change depending on participants' ages (Fig. 3B). This model was only used to statistically assess the shapes of parameters' age trajectories, and not to estimate individuals' parameters because individual parameters would be biased by the inclusion of age in the hierarchical structure of the model.

In the age-based model, each parameter θ of each participant j was sampled from a Normal distribution around an age-based regression line (Fig. 3B):

$$\theta_j \sim Normal(\mu = \theta_{int} + age\ \theta_{lin} + age^2\ \theta_{qua},\ \sigma = \theta_{sd})$$

Each parameter's intercept θ_{int}, linear change with age θ_{lin}, quadratic change with age θ_{qua}, and standard deviation around the regression line θ_{sd} were sampled from prior distributions of the form specified in suppl. Table 8.

Comparing RL and BI Models

Generate-and-Recover Procedure (Fig. 5A)

We simulated one dataset per participant from each model (RL and BI), using the model parameters fitted for the participant using the age-free fitting method. We then fitted the simulated data with the RL and BI model, again using the age-free method. We finally calculated WAIC scores and standard errors using PyMC3 (Salvatier et al., 2016).

Correlations between Model Parameters (Fig. 5B)

We used Spearman correlation, the nonparametric version of the Pearson product-moment correlation, because parameters followed different, not necessarily normal, distributions. Employing Pearson correlation led to similar results. p-values were corrected for multiple comparisons using the Bonferroni method.

₁₀₂₄ Predicting Parameters from Parameters of the Other Model (Fig. 5C)

₁₀₂₅ We ran eight different regression models, predicting each parameter from the four parameters of
₁₀₂₆ the opposite models, as well as their one-way interactions, using linear regression in R (RCoreTeam,
₁₀₂₇ 2016). Fig. 5C shows the explained variance (R^2) of each model.

₁₀₂₈ Principal Component Analysis (PCA)

₁₀₂₉ To extract components that covary across parameters, we ran PCA on the fitted parameters data (8
₁₀₃₀ parameters per participant). PCA can be understood as a method that rotates the initial coordinate
₁₀₃₁ system of a dataset (in our case, 8 axes corresponding to the 8 parameters), such that the first axis
₁₀₃₂ is aligned with the dimension of largest variation in the dataset (first principle component; PC), the
₁₀₃₃ second axis with the dimension of second-largest variance (second PC), while being orthogonal
₁₀₃₄ to the first, and so on. In this way, all resulting PCs are orthogonal to each other, and explain
₁₀₃₅ subsequently less variance in the original dataset. We conducted a PCA after centering and scaling
₁₀₃₆ (z-scoring) the data, using the statistical programming language R (RCoreTeam, 2016).

₁₀₃₇ Age Differences in Principle Components (PCs; Fig. 5E)

₁₀₃₈ For each PC, we ran similar regression models as for our behavioral measures of performance,
₁₀₃₉ predicting participants' PCs from age (linear), age (quadratic), and sex. When significant, effects
₁₀₄₀ were noted in Fig. 5E. For PC2 and PC4, we also conducted post-hoc t-tests, correcting for multiple
₁₀₄₁ comparison using the Bonferroni method (Table 3).

Table 3. Results of t-tests on PC2 and PC4. df: Welch-adjusted degrees of freedom.

Comparison	t	df	p	Sig.
PC2 (8-15 vs. 15-30)	3.44	266.2	< 0.001	***
PC4 (8-13 vs. 13-17)	2.28	176.8	0.047	*
PC4 (13-17 vs. 18-30)	2.49	176.6	0.028	*

₁₀₄₂ **Acknowledgments**

₁₀₄₃ Numerous people contributed to this research: Amy Zou, Lance Kriegsfeld, Celia Ford, Jennifer
₁₀₄₄ Pfeifer, Megan Johnson, Gautam Agarwal, Liyu Xia, Vy Pham, Rachel Arsenault, Josephine Christon,
₁₀₄₅ Shoshana Edelman, Lucy Eletel, Neta Gotlieb, Haley Keglovits, Julie Liu, Justin Morillo, Nithya Ra-
₁₀₄₆ jakumar, Nick Spence, Tanya Smith, Benjamin Tang, Talia Welte, and Lucy Whitmore. We are also
₁₀₄₇ grateful to our participants and their families. The work was funded by National Science Founda-
₁₀₄₈ tion SL-CN grant 1640885 to RD, AGEC, and LW.

₁₀₄₉ **References**

₁₀₅₀ Adleman, N., Kayser, R., Dickstein, D., Blair, R., Pine, D., & Leibenluft, E. (2011). Neural Correlates of Rever-
₁₀₅₁ sal Learning in Severe Mood Dysregulation and Pediatric Bipolar Disorder. *Journal of the American*
₁₀₅₂ *Academy of Child and Adolescent Psychiatry*, *50*, 1173–1185.e2. https://doi.org/10.1016/j.jaac.2011.07.011
₁₀₅₃ Albert, D., Chein, J., & Steinberg, L. (2013). The Teenage Brain: Peer Influences on Adolescent Decision Making.
₁₀₅₄ *Current Directions in Psychological Science*, *22*(2), 114–120. https://doi.org/10.1177/0963721412471347
₁₀₅₅ Badre, D., Kayser, A. S., & D'Esposito, M. (2010). Frontal Cortex and the Discovery of Abstract Action Rules.
₁₀₅₆ *Neuron*, *66*(2), 315–326. https://doi.org/10.1016/j.neuron.2010.03.025
₁₀₅₇ Bartolo, R., & Averbeck, B. B. (2020). Prefrontal Cortex Predicts State Switches during Reversal Learning. *Neuron*,
₁₀₅₈ *106*(6), 1044–1054.e4. https://doi.org/10.1016/j.neuron.2020.03.024
₁₀₅₉ Bates, D., Mächler, M., Bolker, B., & Walker, S. (2015). Fitting Linear Mixed-Effects Models Using lme4. *Journal of*
₁₀₆₀ *Statistical Software*, *67*(1), 1–48. https://doi.org/10.18637/jss.v067.i01
₁₀₆₁ Bernardo, J. M., & Smith, A. F. M. (2009). *Bayesian Theory* [Google-Books-ID: 11nSgIcd7xQC]. John Wiley & Sons.
₁₀₆₂ Blakemore, S.-J., Burnett, S., & Dahl, R. E. (2010). The Role of Puberty in the Developing Adolescent Brain. *Human*
₁₀₆₃ *Brain Mapping*, *31*(6), 926–933. https://doi.org/10.1002/hbm.21052
₁₀₆₄ Blohm, G., Kording, K. P., & Schrater, P. R. (2020). A How-to-Model Guide for Neuroscience [Publisher: Society
₁₀₆₅ for Neuroscience Section: Research Article: Methods/New Tools]. *eNeuro*, *7*(1). https://doi.org/10.1523/
₁₀₆₆ ENEURO.0352-19.2019

Boehme, R., Lorenz, R. C., Gleich, T., Romund, L., Pelz, P., Golde, S., Flemming, E., Wold, A., Deserno, L., Behr, J., Raufelder, D., Heinz, A., & Beck, A. (2017). Reversal learning strategy in adolescence is associated with prefrontal cortex activation. *European Journal of Neuroscience*, *45*(1), 129–137. https://doi.org/10.1111/ejn. 13401

Boorman, E. D., Behrens, T. E., & Rushworth, M. F. (2011). Counterfactual Choice and Learning in a Neural Network Centered on Human Lateral Frontopolar Cortex (M. L. Platt, Ed.). *PLoS Biology*, *9*(6), e1001093. https://doi.org/10.1371/journal.pbio.1001093

Bornstein, A. M., & Norman, K. A. (2017). Reinstated episodic context guides sampling-based decisions for reward. *Nature Neuroscience*, *20*(7), 997–1003. https://doi.org/10.1038/nn.4573

Braams, B. R., Duijvenvoorde, A. C. K. v., Peper, J. S., & Crone, E. A. (2015). Longitudinal Changes in Adolescent Risk-Taking: A Comprehensive Study of Neural Responses to Rewards, Pubertal Development, and Risk-Taking Behavior. *Journal of Neuroscience*, *35*(18), 7226–7238. https://doi.org/10.1523/JNEUROSCI. 4764-14.2015

Bromberg-Martin, E. S., Matsumoto, M., Hong, S., & Hikosaka, O. (2010). A Pallidus-Habenula-Dopamine Pathway Signals Inferred Stimulus Values [Publisher: American Physiological Society]. *Journal of Neurophysiology*, *104*(2), 1068–1076. https://doi.org/10.1152/jn.00158.2010

Casey, B. J., Jones, R. M., & Hare, T. A. (2008). The Adolescent Brain. *Annals of the New York Academy of Sciences*, *1124*(1), 111–126. https://doi.org/10.1196/annals.1440.010

Cauffman, E., Shulman, E. P., Steinberg, L., Claus, E., Banich, M. T., Graham, S., & Woolard, J. (2010). Age differences in affective decision making as indexed by performance on the Iowa Gambling Task. [Publisher: US: American Psychological Association]. *Developmental Psychology*, *46*(1), 193. https://doi.org/10.1037/a0016128

Cazé, R. D., & van der Meer, M. A. A. (2013). Adaptive properties of differential learning rates for positive and negative outcomes. *Biological Cybernetics*, *107*(6), 711–719. https://doi.org/10.1007/s00422-013-0571-5

Chase, H. W., Swainson, R., Durham, L., Benham, L., & Cools, R. (2010). Feedback-related Negativity Codes Prediction Error but Not Behavioral Adjustment during Probabilistic Reversal Learning. *Journal of Cognitive Neuroscience*, *23*(4), 936–946. https://doi.org/10.1162/jocn.2010.21456

Chater, N., Tenenbaum, J. B., & Yuille, A. (2006). Probabilistic models of cognition: Conceptual foundations. *Trends in Cognitive Sciences*, *10*(7), 287–291. https://doi.org/10.1016/j.tics.2006.05.007

Christakou, A., Gershman, S. J., Niv, Y., Simmons, A., Brammer, M., & Rubia, K. (2013). Neural and psychological maturation of decision-making in adolescence and young adulthood. *Journal of Cognitive Neuroscience*, *25*(11), 1807–1823. https://doi.org/10.1162/jocn_a_00447

Clark, L., Cools, R., & Robbins, T. W. (2004). The neuropsychology of ventral prefrontal cortex: Decision-making and reversal learning. *Brain and Cognition*, *55*(1), 41–53. https://doi.org/10.1016/S0278-2626(03)00284-7

Collins, A. G. E., & Frank, M. J. (2012). How much of reinforcement learning is working memory, not reinforcement learning? A behavioral, computational, and neurogenetic analysis: Working memory in reinforcement learning. *European Journal of Neuroscience*, *35*(7), 1024–1035. https://doi.org/10.1111/j.1460-9568.2011.07980.x

Collins, A. G. E., & Koechlin, E. (2012). Reasoning, Learning, and Creativity: Frontal Lobe Function and Human Decision-Making. *PLOS Biology*, *10*(3), e1001293. https://doi.org/10.1371/journal.pbio.1001293

Cools, R., Clark, L., Owen, A. M., & Robbins, T. W. (2002). Defining the Neural Mechanisms of Probabilistic Reversal Learning Using Event-Related Functional Magnetic Resonance Imaging. *Journal of Neuroscience*, *22*(11), 4563–4567. https://doi.org/10.1523/JNEUROSCI.22-11-04563.2002

Costa, V. D., Tran, V. L., Turchi, J., & Averbeck, B. B. (2015). Reversal Learning and Dopamine: A Bayesian Perspective. *Journal of Neuroscience*, *35*(6), 2407–2416. https://doi.org/10.1523/JNEUROSCI.1989-14.2015

Dabney, W., Kurth-Nelson, Z., Uchida, N., Starkweather, C. K., Hassabis, D., Munos, R., & Botvinick, M. (2020). A distributional code for value in dopamine-based reinforcement learning. *Nature*, *577*(7792), 671–675. https://doi.org/10.1038/s41586-019-1924-6

Dahl, R. E., Allen, N. B., Wilbrecht, L., & Suleiman, A. B. (2018). Importance of investing in adolescence from a developmental science perspective. *Nature*, *554*(7693), 441–450. https://doi.org/10.1038/nature25770

Davidow, J. Y., Foerde, K., Galvan, A., & Shohamy, D. (2016). An Upside to Reward Sensitivity: The Hippocampus Supports Enhanced Reinforcement Learning in Adolescence. *Neuron*, *92*(1), 93–99. https://doi.org/10.1016/j.neuron.2016.08.031

Daw, N. D. (2011). Trial-by-trial data analysis using computational models. *Decision Making, Affect, and Learning: Attention and Performance XXIII*. https://doi.org/10.1093/acprof:oso/9780199600434.003.0001

Daw, N. D., Gershman, S. J., Seymour, B., Dayan, P., & Dolan, R. J. (2011). Model-Based Influences on Humans' Choices and Striatal Prediction Errors. *Neuron*, *69*(6), 1204–1215. https://doi.org/10.1016/j.neuron.2011.02. 027

Decker, J. H., Otto, A. R., Daw, N. D., & Hartley, C. A. (2016). From Creatures of Habit to Goal-Directed Learners. *Psychological Science*, *27*(6), 848–858. https://doi.org/10.1177/0956797616639301

Delevich, K., Piekarski, D., & Wilbrecht, L. (2019). Neuroscience: Sex Hormones at Work in the Neocortex. *Current Biology*, *29*(4), R122–R125. https://doi.org/10.1016/j.cub.2019.01.013

Delevich, K., Thomas, A. W., & Wilbrecht, L. (2018). Adolescence and "Late Blooming" Synapses of the Prefrontal Cortex. *Cold Spring Harbor Symposia on Quantitative Biology*, *83*, 37–43. https://doi.org/10.1101/sqb.2018.83.037507

DePasque, S., & Galván, A. (2017). Frontostriatal development and probabilistic reinforcement learning during adolescence. *Neurobiology of Learning and Memory*, *143*, 1–7. https://doi.org/10.1016/j.nlm.2017.04.009

Dickstein, D. P., Finger, E. C., Brotman, M. A., Rich, B. A., Pine, D. S., Blair, J. R., & Leibenluft, E. (2010). Impaired probabilistic reversal learning in youths with mood and anxiety disorders. *Psychological Medicine*, *40*(7), 1089–1100. https://doi.org/10.1017/S0033291709991462

Dickstein, D. P., Finger, E. C., Skup, M., Pine, D. S., Blair, J. R., & Leibenluft, E. (2010). Altered neural function in pediatric bipolar disorder during reversal learning. *Bipolar Disorders*, *12*(7), 707–719. https://doi.org/10.1111/j.1399-5618.2010.00863.x

Drzewiecki, C. M., Willing, J., & Juraska, J. M. (2016). Synaptic number changes in the medial prefrontal cortex across adolescence in male and female rats: A role for pubertal onset. *Synapse (New York, N.Y.)*, *70*(9), 361–368. https://doi.org/10.1002/syn.21909

Eckstein, M. K., Master, S. L., Xia, J., Dahl, R. E., Wilbrecht, L., & Collins, A. G. E. (n.d.). Learning Rates Are Not All the Same: Differences Between Tasks Demand Differences in Interpretation.

Finger, E. C., Marsh, A. A., Mitchell, D. G., Reid, M. E., Sims, C., Budhani, S., Kosson, D. S., Chen, G., Towbin, K. E., Leibenluft, E., Pine, D. S., & Blair, J. R. (2008). Abnormal Ventromedial Prefrontal Cortex Function in Children With Psychopathic Traits During Reversal Learning. *Archives of General Psychiatry*, *65*(5), 586–594. https://doi.org/10.1001/archpsyc.65.5.586

Frank, M. J., & Claus, E. D. (2006). Anatomy of a decision: Striato-orbitofrontal interactions in reinforcement learning, decision making, and reversal. *Psychological Review*, *113*(2), 300–326. https://doi.org/10.1037/0033-295X.113.2.300

Frank, M. J., Seeberger, L. C., & O'Reilly, R. C. (2004). By Carrot or by Stick: Cognitive Reinforcement Learning in Parkinsonism. *Science*, *306*(5703), 1940–1943. https://doi.org/10.1126/science.1102941

Frankenhuis, W. E., & Walasek, N. (2020). Modeling the evolution of sensitive periods. *Developmental Cognitive Neuroscience*, *41*, 100715. https://doi.org/10.1016/j.dcn.2019.100715

Friston, K. (2009). The free-energy principle: A rough guide to the brain? *Trends in Cognitive Sciences*, *13*(7), 293–301. https://doi.org/10.1016/j.tics.2009.04.005

Fuhs, M. C., & Touretzky, D. S. (2007). Context Learning in the Rodent Hippocampus. *Neural Computation*, *19*(12), 3173–3215. https://doi.org/10.1162/neco.2007.19.12.3173

Gershman, S. J. (2017). Dopamine, Inference, and Uncertainty. *Neural Computation*, *29*(12), 3311–3326. https://doi.org/10.1162/neco_a_01023

Gershman, S. J., & Uchida, N. (2019). Believing in dopamine [Number: 11 Publisher: Nature Publishing Group]. *Nature Reviews Neuroscience*, *20*(11), 703–714. https://doi.org/10.1038/s41583-019-0220-7

Giedd, J. N., Blumenthal, J., Jeffries, N. O., Castellanos, F. X., Liu, H., Zijdenbos, A., Paus, T., Evans, A. C., & Rapoport, J. L. (1999). Brain development during childhood and adolescence: A longitudinal MRI study. *Nature Neuroscience*, *2*(10), 861–863. https://doi.org/10.1038/13158

Gläscher, J., Hampton, A. N., & O'Doherty, J. P. (2009). Determining a role for ventromedial prefrontal cortex in encoding action-based value signals during reward-related decision making. *Cerebral Cortex (New York, N.Y.: 1991)*, *19*(2), 483–495. https://doi.org/10.1093/cercor/bhn098

Gogtay, N., Giedd, J. N., Lusk, L., Hayashi, K. M., Greenstein, D., Vaituzis, A. C., Nugent, T. F., Herman, D. H., Clasen, L. S., Toga, A. W., Rapoport, J. L., & Thompson, P. M. (2004). Dynamic mapping of human cortical development during childhood through early adulthood. *Proceedings of the National Academy of Sciences*, *101*(21), 8174–8179. https://doi.org/10.1073/pnas.0402680101

Goodman, N. D., Tenenbaum, J. B., Feldman, J., & Griffiths, T. L. (2008). A rational analysis of rule-based concept learning. *Cognitive Science*, *32*(1), 108–154. https://doi.org/10.1080/03640210701802071

Gopnik, A., O'Grady, S., Lucas, C. G., Griffiths, T. L., Wente, A., Bridgers, S., Aboody, R., Fung, H., & Dahl, R. E. (2017). Changes in cognitive flexibility and hypothesis search across human life history from childhood to adolescence to adulthood. *Proceedings of the National Academy of Sciences*, *114*(30), 7892–7899. https://doi.org/10.1073/pnas.1700811114

Gopnik, A., & Tenenbaum, J. B. (2007). Bayesian networks, Bayesian learning and cognitive development. *Developmental Science*, *10*(3), 281–287. https://doi.org/10.1111/j.1467-7687.2007.00584.x

Gracia-Tabuenca, Z., Moreno, M. B., Barrios, F. A., & Alcauter, S. (2021). Development of the brain functional connectome follows puberty-dependent nonlinear trajectories. *NeuroImage*, *229*, 117769. https://doi.org/10.1016/j.neuroimage.2021.117769

Griffiths, T. L., & Tenenbaum, J. B. (2005). Structure and strength in causal induction. *Cognitive Psychology*, *51*(4), 334–384. https://doi.org/10.1016/j.cogpsych.2005.05.004

Grünwald, P. (2007). *The Minimum Description Length Principle*. https://doi.org/10.7551/mitpress/4643.001.0001

Guskjolen, A., Josselyn, S. A., & Frankland, P. W. (2017). Age-dependent changes in spatial memory retention and flexibility in mice. *Neurobiology of Learning and Memory*, *143*, 59–66. https://doi.org/10.1016/j.nlm.2016.12.006

Hamilton, D. A., & Brigman, J. L. (2015). Behavioral flexibility in rats and mice: Contributions of distinct fronto-cortical regions. *Genes, brain, and behavior*, *14*(1), 4–21. https://doi.org/10.1111/gbb.12191

Harada, T. (2020). Learning From Success or Failure? – Positivity Biases Revisited. *Frontiers in Psychology*, *11*. https://doi.org/10.3389/fpsyg.2020.01627

Harms, M. B., Bowen, K. E. S., Hanson, J. L., & Pollak, S. D. (2018). Instrumental learning and cognitive flexibility processes are impaired in children exposed to early life stress. *Developmental Science*, *21*(4), e12596. https://doi.org/10.1111/desc.12596

Hauser, T. U., Iannaccone, R., Ball, J., Mathys, C., Brandeis, D., Walitza, S., & Brem, S. (2014). Role of the Medial Prefrontal Cortex in Impaired Decision Making in Juvenile Attention-Deficit/Hyperactivity Disorder. *JAMA Psychiatry*, *71*(10), 1165. https://doi.org/10.1001/jamapsychiatry.2014.1093

Hauser, T. U., Iannaccone, R., Walitza, S., Brandeis, D., & Brem, S. (2015). Cognitive flexibility in adolescence: Neural and behavioral mechanisms of reward prediction error processing in adaptive decision making during development. *NeuroImage*, *104*, 347–354. https://doi.org/10.1016/j.neuroimage.2014.09.018

Heathcote, A., Brown, S. D., & Wagenmakers, E.-J. (2015). An Introduction to Good Practices in Cognitive Modeling (B. U. Forstmann & E.-J. Wagenmakers, Eds.). In B. U. Forstmann & E.-J. Wagenmakers (Eds.), *An Introduction to Model-Based Cognitive Neuroscience*. New York, NY, Springer. https://doi.org/10.1007/978-1-4939-2236-9_2

Hildebrandt, T., Schulz, K., Schiller, D., Heywood, A., Goodman, W., & Sysko, R. (2018). Evidence of prefrontal hyperactivation to food-cue reversal learning in adolescents with anorexia nervosa. *Behaviour Research and Therapy*, *111*, 36–43. https://doi.org/10.1016/j.brat.2018.08.006

Hume, D. (2008). *An Enquiry concerning Human Understanding* (P. Millican, Ed.; 1 edition). Oxford, Oxford University Press.

Izquierdo, A., Brigman, J. L., Radke, A. K., Rudebeck, P. H., & Holmes, A. (2017). The neural basis of reversal learning: An updated perspective. *Neuroscience*, *345*, 12–26. https://doi.org/10.1016/j.neuroscience.2016.03.021

Izquierdo, A., & Jentsch, J. D. (2012). Reversal learning as a measure of impulsive and compulsive behavior in addictions. *Psychopharmacology*, *219*(2), 607–620. https://doi.org/10.1007/s00213-011-2579-7

Jacobs, A. M., & Grainger, J. (1994). Models of visual word recognition: Sampling the state of the art [Place: US Publisher: American Psychological Association]. *Journal of Experimental Psychology: Human Perception and Performance*, *20*(6), 1311–1334. https://doi.org/10.1037/0096-1523.20.6.1311

Javadi, A. H., Schmidt, D. H. K., & Smolka, M. N. (2014). Adolescents adapt more slowly than adults to varying reward contingencies. *Journal of Cognitive Neuroscience*, *26*(12), 2670–2681. https://doi.org/10.1162/jocn_a_00677

Johnson, C., & Wilbrecht, L. (2011). Juvenile mice show greater flexibility in multiple choice reversal learning than adults. *Developmental Cognitive Neuroscience*, *1*(4), 540–551. https://doi.org/10.1016/j.dcn.2011.05.008

Juraska, J. M., & Willing, J. (2017). Pubertal onset as a critical transition for neural development and cognition. *Brain Research*, *1654*(Pt B), 87–94. https://doi.org/10.1016/j.brainres.2016.04.012

Katahira, K. (2016). How hierarchical models improve point estimates of model parameters at the individual level. *Journal of Mathematical Psychology*, *73*, 37–58. https://doi.org/10.1016/j.jmp.2016.03.007

Kehagia, A. A., Murray, G. K., & Robbins, T. W. (2010). Learning and cognitive flexibility: Frontostriatal function and monoaminergic modulation. *Current Opinion in Neurobiology*, *20*(2), 199–204. https://doi.org/10.1016/j.conb.2010.01.007

Kleibeuker, S. W., Dreu, C. K. W. D., & Crone, E. A. (2013). The development of creative cognition across adolescence: Distinct trajectories for insight and divergent thinking. *Developmental Science*, *16*(1), 2–12. https://doi.org/10.1111/j.1467-7687.2012.01176.x

Kording, K. P., Blohm, G., Schrater, P., & Kay, K. (2020). Appreciating the variety of goals in computational neuroscience [arXiv: 2002.03211]. *arXiv:2002.03211 [q-bio]*. Retrieved January 28, 2021, from http://arxiv.org/abs/2002.03211

Kraemer, H. C., Yesavage, J. A., Taylor, J. L., & Kupfer, D. (2000). How can we learn about developmental processes from cross-sectional studies, or can we? *The American Journal of Psychiatry*, *157*(2), 163–171. https://doi.org/10.1176/appi.ajp.157.2.163

Larsen, B., & Luna, B. (2018). Adolescence as a neurobiological critical period for the development of higher-order cognition. *Neuroscience & Biobehavioral Reviews*, *94*, 179–195. https://doi.org/10.1016/j.neubiorev.2018.09.005

Laube, C., Lorenz, R., & van den Bos, W. (2020). Pubertal testosterone correlates with adolescent impatience and dorsal striatal activity. *Developmental Cognitive Neuroscience*, *42*, 100749. https://doi.org/10.1016/j.dcn.2019.100749

Laube, C., van den Bos, W., & Fandakova, Y. (2020). The relationship between pubertal hormones and brain plasticity: Implications for cognitive training in adolescence. *Developmental Cognitive Neuroscience*, 100753. https://doi.org/10.1016/j.dcn.2020.100753

Lee, D., Seo, H., & Jung, M. W. (2012). Neural Basis of Reinforcement Learning and Decision Making. *Annual review of neuroscience*, *35*, 287–308. https://doi.org/10.1146/annurev-neuro-062111-150512

Lee, M. D. (2011). How cognitive modeling can benefit from hierarchical Bayesian models. *Journal of Mathematical Psychology*, *55*(1), 1–7. https://doi.org/10.1016/j.jmp.2010.08.013

Lefebvre, G., Lebreton, M., Meyniel, F., Bourgeois-Gironde, S., & Palminteri, S. (2017). Behavioural and neural characterization of optimistic reinforcement learning. *Nature Human Behaviour*, *1*(4), 0067. https://doi.org/10.1038/s41562-017-0067

Lourenco, F., & Casey, B. (2013). Adjusting behavior to changing environmental demands with development. *Neuroscience & Biobehavioral Reviews*, *37*(9), 2233–2242. https://doi.org/10.1016/j.neubiorev.2013.03.003

Master, S. L., Eckstein, M. K., Gotlieb, N., Dahl, R., Wilbrecht, L., & Collins, A. G. E. (2020). Disentangling the systems contributing to changes in learning during adolescence. *Developmental Cognitive Neuroscience*, *41*, 100732. https://doi.org/10.1016/j.dcn.2019.100732

Medin, D. L., & Schaffer, M. M. (1978). Context theory of classification learning. *Psychological Review*, *85*(3), 207–238. https://doi.org/10.1037/0033-295X.85.3.207

Metha, J. A., Brian, M. L., Oberrauch, S., Barnes, S. A., Featherby, T. J., Bossaerts, P., Murawski, C., Hoyer, D., & Jacobson, L. H. (2020). Separating Probability and Reversal Learning in a Novel Probabilistic Reversal Learning Task for Mice [Publisher: Frontiers]. *Frontiers in Behavioral Neuroscience*, *13*. https://doi.org/10.3389/fnbeh.2019.00270

Minto de Sousa, N., Gil, M. S. C. d. A., & McIlvane, W. J. (2015). Discrimination and Reversal Learning by Toddlers Aged 15-23 Months. *The Psychological Record*, *65*(1), 41–47. https://doi.org/10.1007/s40732-014-0084-1

Mulder, J., & Wagenmakers, E.-J. (2016). Editors' introduction to the special issue "Bayes factors for testing hypotheses in psychological research: Practical relevance and new developments". *Journal of Mathematical Psychology*, *72*, 1–5. https://doi.org/10.1016/j.jmp.2016.01.002

Nassar, M. R., & Frank, M. J. (2016). Taming the beast: Extracting generalizable knowledge from computational models of cognition. *Current Opinion in Behavioral Sciences*, *11*, 49–54. https://doi.org/10.1016/j.cobeha.2016.04.003

Nassar, M. R., Rumsey, K. M., Wilson, R. C., Parikh, K., Heasly, B., & Gold, J. I. (2012). Rational regulation of learning dynamics by pupil-linked arousal systems [Number: 7 Publisher: Nature Publishing Group]. *Nature Neuroscience*, *15*(7), 1040–1046. https://doi.org/10.1038/nn.3130

Natterson-Horowitz, D. B., & Bowers, K. (2019). *Wildhood: The Astounding Connections between Human and Animal Adolescents*. New York, Scribner.

Navarro, D. J. (2019). Between the Devil and the Deep Blue Sea: Tensions Between Scientific Judgement and Statistical Model Selection. *Computational Brain & Behavior*, *2*(1), 28–34. https://doi.org/10.1007/s42113-018-0019-z

Niv, Y. (2009). Reinforcement learning in the brain. *Journal of Mathematical Psychology*, *53*(3), 139–154.

Nussenbaum, K., & Hartley, C. A. (2019). Reinforcement learning across development: What insights can we draw from a decade of research? *Developmental Cognitive Neuroscience*, *40*, 100733. https://doi.org/10.1016/j.dcn.2019.100733

O'Doherty, J. P., Lee, S. W., & McNamee, D. (2015). The structure of reinforcement-learning mechanisms in the human brain. *Current Opinion in Behavioral Sciences*, *1*, 94–100. https://doi.org/10.1016/j.cobeha.2014.10.004

Op de Macks, Z. A., Bunge, S. A., Bell, O. N., Wilbrecht, L., Kriegsfeld, L. J., Kayser, A. S., & Dahl, R. E. (2016). Risky decision-making in adolescent girls: The role of pubertal hormones and reward circuitry. *Psychoneuroendocrinology*, *74*, 77–91. https://doi.org/10.1016/j.psyneuen.2016.08.013

O'Reilly, J. X., Schüffelgen, U., Cuell, S. F., Behrens, T. E. J., Mars, R. B., & Rushworth, M. F. S. (2013). Dissociable effects of surprise and model update in parietal and anterior cingulate cortex. *Proceedings of the National Academy of Sciences of the United States of America*, *110*(38), E3660–3669. https://doi.org/10.1073/pnas.1305373110

Palminteri, S., Kilford, E. J., Coricelli, G., & Blakemore, S.-J. (2016). The Computational Development of Reinforcement Learning during Adolescence. *PLoS Computational Biology*, *12*(6). https://doi.org/10.1371/journal.pcbi.1004953

Palminteri, S., Wyart, V., & Koechlin, E. (2017). The Importance of Falsification in Computational Cognitive Modeling. *Trends in Cognitive Sciences*, *21*(6), 425–433. https://doi.org/10.1016/j.tics.2017.03.011

Perfors, A., Tenenbaum, J. B., Griffiths, T. L., & Xu, F. (2011). A tutorial introduction to Bayesian models of cognitive development, 61.

Petersen, A. C., Crockett, L., Richards, M., & Boxer, A. (1988). A self-report measure of pubertal status: Reliability, validity, and initial norms. *Journal of Youth and Adolescence*, *17*(2), 117–133. https://doi.org/10.1007/BF01537962

Peterson, D. A., Elliott, C., Song, D. D., Makeig, S., Sejnowski, T. J., & Poizner, H. (2009). Probabilistic reversal learning is impaired in Parkinson's disease. *Neuroscience*, *163*(4), 1092–1101. https://doi.org/10.1016/j.neuroscience.2009.07.033

Piekarski, D. J., Boivin, J. R., & Wilbrecht, L. (2017). Ovarian Hormones Organize the Maturation of Inhibitory Neurotransmission in the Frontal Cortex at Puberty Onset in Female Mice. *Current biology: CB*, *27*(12), 1735–1745.e3. https://doi.org/10.1016/j.cub.2017.05.027

Piekarski, D. J., Johnson, C. M., Boivin, J. R., Thomas, A. W., Lin, W. C., Delevich, K., M Galarce, E., & Wilbrecht, L. (2017). Does puberty mark a transition in sensitive periods for plasticity in the associative neocortex? *Brain Research*, *1654*(Pt B), 123–144. https://doi.org/10.1016/j.brainres.2016.08.042

Pitt, M. A., & Myung, I. J. (2002). When a good fit can be bad. *Trends in Cognitive Sciences*, *6*(10), 421–425. https://doi.org/10.1016/S1364-6613(02)01964-2

RCoreTeam. (2016). *R: A Language and Environment for Statistical Computing*. Vienna, Austria, R Foundation for Statistical Computing.

Salvatier, J., Wiecki, T. V., & Fonnesbeck, C. (2016). Probabilistic programming in Python using PyMC3. *PeerJ Computer Science*, *2*, e55. https://doi.org/10.7717/peerj-cs.55

Sarkka, S. (2013). *Bayesian Filtering and Smoothing*. Cambridge, Cambridge University Press. https://doi.org/10.1017/CBO9781139344203

Schlagenhauf, F., Huys, Q. J., Deserno, L., Rapp, M. A., Beck, A., Heinze, H.-J., Dolan, R., & Heinz, A. (2014). Striatal dysfunction during reversal learning in unmedicated schizophrenia patients. *Neuroimage*, *89*(100), 171–180. https://doi.org/10.1016/j.neuroimage.2013.11.034

Schultz, W., & Dickinson, A. (2000). Neuronal Coding of Prediction Errors. *Annual Review of Neuroscience*, *23*(1), 473–500. https://doi.org/10.1146/annurev.neuro.23.1.473

Sercombe, H. (2014). Risk, adaptation and the functional teenage brain. *Brain and Cognition*, *89*, 61–69. https://doi.org/10.1016/j.bandc.2014.01.001

Simon, N. W., Gregory, T. A., Wood, J., & Moghaddam, B. (2013). Differences in response initiation and behavioral flexibility between adolescent and adult rats. *Behavioral Neuroscience*, *127*(1), 23–32. https://doi.org/10.1037/a0031328

Solway, A., & Botvinick, M. (2012). Goal-directed decision making as probabilistic inference: A computational framework and potential neural correlates. *Psychological Review*, *119*(1), 120–154. https://doi.org/10.1037/a0026435

Somerville, L. H., & Casey, B. (2010). Developmental neurobiology of cognitive control and motivational systems. *Current Opinion in Neurobiology*, *20*(2), 236–241. https://doi.org/10.1016/j.conb.2010.01.006

Sowell, E. R., Peterson, B. S., Thompson, P. M., Welcome, S. E., Henkenius, A. L., & Toga, A. W. (2003). Mapping cortical change across the human life span. *Nature Neuroscience*, *6*(3), 309–315. https://doi.org/10.1038/nn1008

Starkweather, C. K., Gershman, S. J., & Uchida, N. (2018). The Medial Prefrontal Cortex Shapes Dopamine Reward Prediction Errors under State Uncertainty. *Neuron*, *98*(3), 616–629.e6. https://doi.org/10.1016/j.neuron.2018.03.036

Steinberg, L. (2005). Cognitive and affective development in adolescence. *Trends in Cognitive Sciences*, *9*(2), 69–74. https://doi.org/10.1016/j.tics.2004.12.005

Sugawara, M., & Katahira, K. (2021). Dissociation between asymmetric value updating and perseverance in human reinforcement learning [Number: 1 Publisher: Nature Publishing Group]. *Scientific Reports*, *11*(1), 3574. https://doi.org/10.1038/s41598-020-80593-7

Sutton, R. S., & Barto, A. G. (2017). *Reinforcement Learning: An Introduction* (2nd ed.). Cambridge, MA; London, England, MIT Press.

Swainson, R., Rogers, R. D., Sahakian, B. J., Summers, B. A., Polkey, C. E., & Robbins, T. W. (2000). Probabilistic learning and reversal deficits in patients with Parkinson's disease or frontal or temporal lobe lesions: Possible adverse effects of dopaminergic medication. *Neuropsychologia*, *38*(5), 596–612. https://doi.org/10.1016/S0028-3932(99)00103-7

Tai, L.-H., Lee, A. M., Benavidez, N., Bonci, A., & Wilbrecht, L. (2012). Transient stimulation of distinct subpopulations of striatal neurons mimics changes in action value. *Nature Neuroscience*, *15*(9), 1281–1289. https://doi.org/10.1038/nn.3188

Tenenbaum, J. B., Kemp, C., Griffiths, T. L., & Goodman, N. D. (2011). How to Grow a Mind: Statistics, Structure, and Abstraction. *Science*, *331*(6022), 1279–1285. https://doi.org/10.1126/science.1192788

Toga, A. W., Thompson, P. M., & Sowell, E. R. (2006). Mapping brain maturation. *Trends in neurosciences*, *29*(3), 148–159. https://doi.org/10.1016/j.tins.2006.01.007

Uttal, W. R. (1990). On some two-way barriers between models and mechanisms. *Perception & Psychophysics*, *48*(2), 188–203. https://doi.org/10.3758/BF03207086

van den Bos, W., Bruckner, R., Nassar, M. R., Mata, R., & Eppinger, B. (2017). Computational neuroscience across the lifespan: Promises and pitfalls. *Developmental Cognitive Neuroscience*. https://doi.org/10.1016/j.dcn.2017.09.008

van den Bos, W., Cohen, M. X., Kahnt, T., & Crone, E. A. (2012). Striatum–Medial Prefrontal Cortex Connectivity Predicts Developmental Changes in Reinforcement Learning. *Cerebral Cortex*, *22*(6), 1247–1255. https://doi.org/10.1093/cercor/bhr198

van den Bos, W., Guroglu, B., van den Bulk, B. G., Rombouts, S. A., & Crone, E. A. (2009). Better than Expected or as Bad as You Thought? The Neurocognitive Development of Probabilistic Feedback Processing. *Frontiers in Human Neuroscience*, *3*. https://doi.org/10.3389/neuro.09.052.2009

van der Schaaf, M. E., Warmerdam, E., Crone, E. A., & Cools, R. (2011). Distinct linear and non-linear trajectories of reward and punishment reversal learning during development: Relevance for dopamine's role in adolescent decision making. *Developmental Cognitive Neuroscience*, *1*(4), 578–590. https://doi.org/10.1016/j.dcn.2011.06.007

Waltz, J. A., & Gold, J. M. (2007). Probabilistic reversal learning impairments in schizophrenia: Further evidence of orbitofrontal dysfunction. *Schizophrenia Research*, *93*(1), 296–303. https://doi.org/10.1016/j.schres.2007.03.010

Watanabe, S. (2013). A Widely Applicable Bayesian Information Criterion. *Journal of Machine Learning Research*, *14*(Mar), 867–897. Retrieved October 30, 2019, from http://www.jmlr.org/papers/v14/watanabe13a.html

Webb, B. (2001). Can robots make good models of biological behaviour? [Publisher: Cambridge University Press]. *Behavioral and Brain Sciences*, *24*(6), 1033–1050. https://doi.org/10.1017/S0140525X01000127

Wilson, R. C., & Collins, A. G. E. (2019). Ten simple rules for the computational modeling of behavioral data. *arxiv*. https://doi.org/10.31234/osf.io/46mbn

Wimmer, G. E., Braun, E. K., Daw, N. D., & Shohamy, D. (2014). Episodic memory encoding interferes with reward learning and decreases striatal prediction errors. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*, *34*(45), 14901–14912. https://doi.org/10.1523/JNEUROSCI.0204-14.2014

Xia, L., Master, S., Eckstein, M., Wilbrecht, L., & Collins, A. G. E. (2020). Learning under uncertainty changes during adolescence, In *Proceedings of the Cognitive Science Society*.

Xu, F., & Tenenbaum, J. B. (2007). Sensitivity to sampling in Bayesian word learning. *Developmental Science*, *10*(3), 288–297. https://doi.org/10.1111/j.1467-7687.2007.00590.x

Yagishita, S., Hayashi-Takagi, A., Ellis-Davies, G. C. R., Urakubo, H., Ishii, S., & Kasai, H. (2014). A critical time window for dopamine actions on the structural plasticity of dendritic spines. *Science (New York, N.Y.)*, *345*(6204), 1616–1620. https://doi.org/10.1126/science.1255514

Yaple, Z. A., & Yu, R. (2019). Fractionating adaptive learning: A meta-analysis of the reversal learning paradigm. *Neuroscience & Biobehavioral Reviews*, *102*, 85–94. https://doi.org/10.1016/j.neubiorev.2019.04.006

Yu, A. J., & Dayan, P. (2005). Uncertainty, Neuromodulation, and Attention. *Neuron*, *46*(4), 681–692. https://doi.org/10.1016/j.neuron.2005.04.026