1 **Title**

2 MAVE-NN: learning genotype-phenotype maps from multiplex assays of variant effect

3 **Authors**

Ammar Tareen[1], Mahdi Kooshkbaghi[1], Anna Posfai[1], William T. Ireland[2,3], David M.

McCandlish[1], Justin B. Kinney[1,*]

[1] Simons Center for Quantitative Biology, Cold Spring Harbor Laboratory, Cold Spring Harbor, NY, 11724

[2] Department of Physics, California Institute of Technology, Pasadena, CA, 91125

[3] Present address: Department of Applied Physics, Harvard University, Cambridge, MA, 02134

[*] To whom correspondence should be addressed: jkinney@cshl.edu

<u>Abstract</u>

Multiplex assays of variant effect (MAVEs) are a family of methods that includes deep

mutational scanning (DMS) experiments on proteins and massively parallel reporter assays

(MPRAs) on gene regulatory sequences. However, a general strategy for inferring quantitative

models of genotype-phenotype (G-P) maps from MAVE data is lacking. Here we introduce

MAVE-NN, a neural-network-based Python package that implements a broadly applicable

information-theoretic framework for learning G-P maps—including biophysically interpretable

models—from MAVE datasets. We demonstrate MAVE-NN in multiple biological contexts, and

highlight the ability of our approach to deconvolve mutational effects from otherwise

confounding experimental nonlinearities and noise.

Main Text

Introduction

Over the last decade, the ability to quantitatively study genotype-phenotype (G-P) maps

has been revolutionized by the development of multiplex assays of variant effect (MAVEs),

which can measure molecular phenotypes for thousands to millions of genotypic variants in

parallel.[1,2] MAVE is an umbrella term that describes a diverse set of experimental methods,

three examples of which are illustrated in **Fig. 1**. Deep mutational scanning (DMS) experiments[3]

are a type of MAVE commonly used to study protein sequence-function relationships. These

assays work by linking variant proteins to their coding sequences, either directly or indirectly,

then using deep sequencing to assay which variants survive a process of activity-dependent

selection (e.g., **Fig. 1a**). Massively parallel reporter assays (MPRAs) are another major class of

MAVE, and are commonly used to study DNA or RNA sequences that regulate gene expression

at a variety of steps, including transcription, mRNA splicing, cleavage and polyadenylation,

translation, and mRNA decay.[4–7] MPRAs typically rely on either an RNA-seq readout of barcode

abundances (**Fig. 1c**) or the sorting of cells expressing a fluorescent reporter gene (**Fig. 1e**).

Most computational methods for analyzing MAVE data have focused on accurately

quantifying the activity of individual assayed sequences.[8–14] However, MAVE measurements like

enrichment ratios or cellular fluorescence levels usually cannot be interpreted as providing

direct quantification of biologically meaningful activities, due to the presence of experiment-

specific nonlinearities and noise. Moreover, MAVE data is usually incomplete, as one often

wishes to understand G-P maps over vastly larger regions of sequence space than can be

exhaustively assayed. The explicit quantitative modeling of G-P maps can address both the

indirectness and incompleteness of MAVE measurements.[1,15] The goal here is to determine a

mathematical function that, given a sequence as input, will return a quantitative value for that

sequence's molecular phenotype. Such quantitative modeling has been of great interest since

the earliest MAVE methods were developed,[16–18] but no general-use software has yet been

described for inferring G-P maps of arbitrary functional form from MAVE data.

Here we introduce a unified conceptual framework for the quantitative modeling of

MAVE data. This framework is based on the use of latent phenotype models, which assume that

each assayed sequence has a well-defined latent phenotype (specified by the G-P map), of

which the MAVE experiment provides an indirect readout (described by the measurement

process). The quantitative forms of both the G-P map and the measurement process are then

inferred from MAVE data simultaneously. We further introduce an information-theoretic

approach for separately assessing the performance of the G-P map and the measurement

process components of latent phenotype models. This strategy is implemented in an easy-to-

use open-source Python package called MAVE-NN, which represents latent phenotype models

as neural networks and infers the parameters of these models from MAVE data using a

TensorFlow 2 backend.[19]

In what follows, we expand on this unified MAVE modeling strategy and apply it to a

diverse array of DMS and MPRA datasets. Doing so, we find that MAVE-NN provides

substantial advantages over other MAVE modeling approaches. Our results also highlight the

substantial benefits of including sequence variants with multiple mutations in assayed sequence

libraries, as doing so allows MAVE-NN to deconvolve the features of the G-P map from

potentially confounding effects of experimental nonlinearities and noise. Importantly, we find that

including just a modest number of multiple-mutation variants in a MAVE experiment can be

beneficial even when one is primarily interested in the effects of single mutations. Finally, we

illustrate how the ability of MAVE-NN to train custom G-P maps can shed light on the

biophysical mechanisms of gene regulation.

Results

Latent phenotype modeling strategy

MAVE-NN supports the analysis of MAVE data on DNA, RNA, and protein sequences,

and can accommodate either continuous or discrete measurement values. Given a set of

sequence-measurement pairs, MAVE-NN aims to infer a probabilistic mapping from sequence

to measurement. Our primary enabling assumption, which is encoded in the structure of the

latent phenotype model (**Fig. 2a**), is that this mapping occurs in two stages. Each sequence is

first mapped to a latent phenotype by a deterministic G-P map, then this latent phenotype is

mapped to possible measurement values via a stochastic measurement process. During

training, the G-P map and measurement process are simultaneously learned by maximizing a

regularized form of likelihood.

MAVE-NN includes four types of built-in G-P maps: additive, neighbor, pairwise, and

black box. Additive G-P maps assume that each character at each position within a sequence

contributes independently to the latent phenotype. Neighbor G-P maps incorporate interactions

between adjacent (i.e., nearest-neighbor) characters in a sequence, while pairwise G-P maps

include interactions between all pairs of characters in a sequence regardless of the distance

separating the characters in each pair. Black box G-P maps have the form of a densely

connected multilayer perceptron, the specific architecture of which can be controlled by the

user. MAVE-NN also supports custom G-P maps that can be used, e.g., to represent specific

biophysical hypotheses about the mechanisms of sequence function.

To handle both discrete and continuous measurement values, two different strategies for

modeling measurement processes are provided. Measurement process agnostic (MPA)

regression uses techniques from the biophysics literature[15,16,20,21] to analyze MAVE datasets

that report discrete measurements. Here the measurement process is represented by an

overparameterized neural network that takes the latent phenotype value as input and outputs

the probability of each possible measurement value (**Fig. 2b**). Global epistasis (GE) regression

(**Fig. 2c**), by contrast, leverages ideas previously developed in the evolution literature for

analyzing datasets that contain continuous measurements,[22–25] and is becoming an increasingly

popular strategy for modeling DMS data.[26–28] Here, the latent phenotype is nonlinearly mapped

to a prediction that represents the most probable measurement value. A noise model is then

used to describe the distribution of likely deviations from this prediction. MAVE-NN supports

both homoscedastic and heteroscedastic noise models based on three different classes of

probability distribution: Gaussian, Cauchy, and skewed-t. We note that the skewed-t distribution,

introduced by Jones and Faddy,[29] reduces to Gaussian and Cauchy distributions in certain limits

while also accommodating asymmetric experimental noise. **Fig. 2d** shows an example of a GE

measurement process with a heteroscedastic skewed-t noise model.

Readers should note that the current implementation of MAVE-NN places certain

constraints on input data and model architecture. Input sequences must be the same length,

and when analyzing continuous data, only scalar measurements (as opposed to vectors of

multiple measurements) can be used to train models. In addition, because our method for

learning the form of experimental nonlinearities depends on observing how multiple mutations

combine, MAVE-NN's functionality is more limited when analyzing MAVE libraries that comprise

only single-mutation variants. More information on these constraints and the reasons behind

them can be found below in the section "Constraints on datasets and models".

Information-theoretic measures of model performance

We further propose three distinct quantities for assessing the performance of latent

phenotype models: intrinsic information, predictive information, and variational information (**Fig.**

2e). These quantities come from information theory and are motivated by thinking of G-P maps

in terms of information compression. In information theory, a quantity called mutual information

quantifies the amount of information that the value of one variable communicates about the

value of another.[30,31] Mutual information is symmetric, nonnegative, is measured in units of

"bits", and is equal to 0 bits only if the two variables are independent. Alternatively, if knowing

the value of one variable allows you to narrow down the value of the other variable to one of two

possibilities that would otherwise be equally likely, the mutual information between these two

variables will be 1.0 bits. If the value is narrowed down to one of four otherwise equally likely

possibilities, the mutual information will be 2.0 bits. Narrowing down to one of with eight

possibilities will yield 3.0 bits, and so on. But importantly, mutual information does not require

that the relationship between two variables in question be so clean cut, and mutual information

can in fact be computed between any two types of variables—discrete, continuous, multi-

dimensional, etc.. This property makes the information-based quantities we propose applicable

to all MAVE datasets, regardless of the specific type of experimental readout used. By contrast,

many of the standard model performance metrics have restricted domains of applicability:

accuracy can only be applied to data with discrete labels, R^2 can only be applied to data with

univariate continuous labels, and so on. We note, however, that estimating mutual information

and related quantities from finite data is nontrivial and that MAVE-NN uses a variety of

approaches to do this.

Intrinsic information, I_{int}, is the mutual information between the sequences and

measurements contained within a MAVE dataset. This quantity provides a benchmark against

which to compare the performance of inferred G-P maps. Predictive information, I_{pre}, is the

mutual information between MAVE measurements and the latent phenotype values predicted by

a G-P map of interest. This quantifies how well the G-P map preserves sequence-encoded

information that is determinative of experimental measurements. When evaluated on test data,

I_{pre} is bounded above by I_{int}, and equality is realized only when the latent phenotype losslessly

encodes relevant sequence-encoded information. Variational information, I_{var}, is a linear

transformation of log likelihood that provides a variational lower bound on I_{pre}.[32–34] The

difference between I_{pre} and I_{var} quantifies how accurately the inferred measurement process

matches the observed distribution of measurements and latent phenotypes (see **Supplemental**

Information).

MAVE-NN infers model parameters by maximizing a (lightly) regularized form of

likelihood. These computations are performed using the standard backpropagation-based

training algorithms provided within the TensorFlow 2 backend. With certain caveats noted (see

Methods), this optimization procedure maximizes I_{pre} while avoiding the costly estimates of

mutual information at each iteration that have hindered the adoption of previous mutual-

information-based modeling strategies.[16]

Application: deep mutational scanning assays

We now demonstrate the capabilities of MAVE-NN on three DMS datasets, starting with

the study of Olson et al.[35] on pairwise epistasis in protein G. Here the authors measured the

effects of all single and nearly all double mutations to residues 2-56 of the IgG binding domain.

This domain, called GB1, has long served as a model system for studying protein sequence-

function relationships. To assay the binding of GB1 variants to IgG, the authors combined

mRNA display with ultra-high-throughput DNA sequencing (**Fig. 1a**). The resulting dataset

reports log enrichment values for all 1,045 single- and 530,737 double-mutant GB1 variants

(**Fig. 1b**).

Inspired by the work of Otwinowski et al.,[25] we used MAVE-NN to infer a latent

phenotype model comprising an additive G-P map and a GE measurement process. This

inference procedure required only about 5 minutes on a single node of a computer cluster

(**Supplemental Fig. S1**). **Fig. 3a** illustrates the inferred additive G-P map via the effects that

every possible single-residue mutation has on the latent phenotype. From this heatmap of

additive effects, we can immediately identify all of the critical GB1 residues, including the IgG

interacting residues at 27, 31, and 43.[35] We also observe that missense mutations to proline

throughout the GB1 domain tend to negatively impact IgG binding, as expected due to this

amino acid's exceptional conformational rigidity. **Fig. 3b** illustrates the corresponding GE

measurement process, revealing a sigmoidal relationship between log enrichment

measurements and the latent phenotype values predicted by the G-P map. Nonlinearities like

this are ubiquitous in DMS data due to the presence of background and saturation effects.

Unless they are explicitly accounted for in one's quantitative modeling efforts, as they are here,

these nonlinearities can greatly distort the parameters of inferred G-P maps. **Fig. 3c** shows that

accounting for this nonlinearity yields predictions that correlate quite well with measurement

values. Moreover, every latent phenotype model inferred by MAVE-NN can be used as a MAVE

dataset simulator (see **Methods**). By analyzing simulated data generated by our inferred model

for this GB1 experiment, we further observed that MAVE-NN can accurately and robustly

recover the GE nonlinearity and ground-truth G-P map parameters (**Supplementary Fig. S1**).

Fig. 3d summarizes the values of our information-theoretic metrics for model

performance. On held-out test data, we find that $I_{var} = 2.178 \pm 0.027$ bits and $I_{pre} = 2.225 \pm$

0.017 bits. The similarity of these two values suggests that the inferred GE measurement

process, which includes a heteroscedastic skewed-t noise model, has nearly sufficient accuracy

to fully describe the distribution of residuals. We further find that 2.741 ± 0.013 bits $\leq I_{int} \leq$

3.215 ± 0.007 bits (see **Methods**), meaning that the inferred G-P map accounts for 69%-81% of

the total sequence-dependent information in the dataset. While this performance is impressive,

the additive G-P map evidently misses some relevant sequence features. This observation

motivates the more complex biophysical model for GB1 discussed later in **Results**.

The ability of MAVE-NN to deconvolve experimental nonlinearities from additive G-P

maps requires that some of the assayed sequences contain multiple mutations. This is because

such nonlinearities are inferred by reconciling the effects of single mutations with the effects

observed for combinations of two or more mutations. To investigate how many multiple-mutation

variants are required, we performed GE inference on subsets of the GB1 dataset containing all

1,045 single-mutation sequences and either 50,000, 5,000, or 500 double-mutation sequences

(see **Methods**). The shapes of the resulting GE nonlinearities are illustrated in **Figs. 3e-g**.

Remarkably, MAVE-NN is able to recover the underlying nonlinearity using only about 500

randomly selected double mutants, which represent only ~0.1% of all possible double mutants.

The analysis of simulated data also supports the ability to accurately recover ground-truth model

predictions using highly reduced datasets (**Supplemental Fig. S1**). These findings have

important implications for the design of DMS experiments: even if one only wants to determine

an additive G-P map, including a modest number of multiple-mutation sequences in the assayed

library is often advisable because it may allow the removal of artifactual nonlinearities.

To test the capabilities of MAVE-NN on less complete DMS datasets, we analyzed

recent experiments on amyloid beta (Aβ)[36] and TDP-43,[37] both of which exhibit aggregation

behavior in the context of neurodegenerative diseases. In these experiments, protein

functionality was assayed using selective growth in genetically modified *Saccaromyces*

cerevisiae: Seuma et al.[36] performed a selection against Aβ toxicity, whereas Bolognesi et al.[37]

positively selected for TDP-43 aggregation. Like with GB1, the variant libraries used in these

two experiments included a substantial number of multiple-mutation sequences: 499 single- and

15,567 double-mutation sequences for Aβ; 1,266 single- and 56,730 double-mutation

sequences for TDP-43. But unlike with GB1, these datasets are highly incomplete due to the

use of mutagenic PCR (for Aβ) or doped oligo synthesis (TDP-43) for variant library

construction.

We used MAVE-NN to infer additive G-P maps from these two datasets, adopting the

same type of latent phenotype model used for GB1. **Fig. 4a** illustrates the additive G-P map

inferred from aggregation measurements of Aβ variants. In agreement with the original study,

we see that most amino acid mutations between positions 30-40 have a negative effect on

nucleation, suggesting that this region plays a major role in nucleation behavior. **Fig. 4b** shows

the corresponding measurement process (see also **Supplemental Information Fig. S2**). Even

though these data are much sparser than the GB1 data, the inferred model performs well on

held-out test data ($I_{\mathrm{var}} = 1.142 \pm 0.065$ bits, $I_{\mathrm{pre}} = 1.187 \pm 0.050$ bits, $R^2 = 0.763 \pm 0.024$).

Similarly, **Figs. 4c-d** show the G-P map parameters and GE measurement process inferred

from toxicity measurements of TDP-43 variants, revealing among other things the toxicity-

determining hot-spot observed by Bolognesi et al.[37] at positions 310-340. The resulting latent

phenotype model performs well on held-out test data ($I_{\mathrm{var}} = 1.834 \pm 0.035$ bits, $I_{\mathrm{pre}} = 1.994 \pm$

0.023 bits, $R^2 = 0.914 \pm 0.007$).

Application: a massively parallel splicing assay

Exon/intron boundaries are defined by 5′ splice sites (5′ss), which bind the U1 snRNP

during the initial stages of spliceosome assembly. To investigate how 5′ss sequence

quantitatively controls alternative mRNA splicing, Wong et al.[38] used a massively parallel

splicing assay (MPSA) to measure percent-spliced-in (PSI) values for nearly all 32,768 possible

5′ss of the form NNN/GYNNNN in three different genetic contexts (**Fig. 1c,d**). Applying MAVE-

NN to data from the BRCA2 exon 17 context, we inferred four different types of G-P maps:

additive, neighbor, pairwise, and black box. As with GB1, these G-P maps were each inferred

using GE regression with a heteroscedastic skewed-t noise model. For comparison, we also

inferred an additive G-P map using the epistasis package of Sailer and Harms.[24]

Fig. 5a compares the performance of these G-P map models on held-out test data, while

Figs. 5b-d illustrate the corresponding inferred measurement processes. We observe that the

additive G-P map inferred using the epistasis package[24] exhibits less predictive information

($I_{pre} = 0.180 \pm 0.011$ bits) than the additive G-P map found using MAVE-NN ($P = 3.8 \times 10^{-6}$,

two-sided z-test). This is likely because the epistasis package estimates the parameters of the

additive G-P map prior to estimating the GE nonlinearity. We also note that, while the epistasis

package provides a variety of options for modeling the GE nonlinearity, none of these options

appear to work as well as our mixture-of-sigmoids approach (compare **Figs. 5b,c**). This finding

again demonstrates that the accurate inference of G-P maps requires the explicit and

simultaneous modeling of experimental nonlinearities.

We also observe that increasingly complex G-P maps exhibit increased accuracy. For

example, the additive G-P map gives $I_{pre} = 0.257 \pm 0.013$ bits, whereas the pairwise G-P map

(**Figs. 5e,f**) attains $I_{pre} = 0.374 \pm 0.014$ bits. Using MAVE-NN's built-in parametric bootstrap

approach for quantifying parameter uncertainty, we find that both the additive and pairwise G-P

map parameters are very precisely determined (see **Supplemental Information Fig. S3**). The

black box G-P map, which is comprised of 5 densely connected hidden layers of 10 nodes each,

performed the best of all four G-P maps, achieving $I_{pre} = 0.458 \pm 0.015$ bits. Remarkably, this

last predictive information value exceeds the lower bound of $I_{int} \geq 0.462 \pm 0.009$ bits, which was

estimated from replicate experiments (see **Methods**). We thus conclude that pairwise

interaction models are not flexible enough to fully account for how 5´ss sequences control

splicing. More generally, these results underscore the need for software that is capable of

inferring and assessing a variety of different G-P maps through a uniform interface.

Application: biophysically interpretable G-P maps

Biophysical models, unlike the phenomenological models considered thus far, have

mathematical structures that reflect specific hypotheses about how sequence-dependent

interactions between macromolecules mechanistically define G-P maps. Thermodynamic

models, which rely on a quasi-equilibrium assumption, are the most commonly used type of

biophysical model.[39–41] Previous studies have shown that precise thermodynamic models can

be inferred from MAVE datasets,[16] but no software intended for use by the broader MAVE

community has yet been developed for doing this. MAVE-NN meets this need by enabling the

inference of custom G-P maps. We now demonstrate this biophysical modeling capability in the

contexts of protein-ligand binding (using DMS data; **Fig. 1a**) and bacterial transcriptional

regulation (using sort-seq MPRA data; **Fig. 1e**). An expanded discussion of how these models

are mathematically formulated and specified within MAVE-NN is provided in the "Biophysical

modeling" section of **Supplemental Information**.

Otwinowski[42] showed that a three-state thermodynamic G-P map (**Fig. 6a**), one that

accounts for GB1 folding energy in addition to GB1-IgG binding energy,[43] can explain the DMS

data of Olson et al.[35] better than a simple additive G-P map does. This biophysical model

subsequently received impressive confirmation in the work of Nisthal et al.,[44] who measured the

thermostability of 812 single-mutation GB1 variants. We tested the ability of MAVE-NN to

recover the same type of thermodynamic model that Otwinowski had inferred using custom

analysis scripts. Our analysis yielded a G-P map with significantly improved performance on the

data of Olson et al. ($I_{\mathrm{var}} = 2.303 \pm 0.013$ bits, $I_{\mathrm{pre}} = 2.357 \pm 0.007$ bits, $R^2 = 0.947 \pm 0.001$)

relative to the additive G-P map of **Fig. 3**. **Fig. 6b** shows the two inferred energy matrices that

respectively describe the effects of every possible single-residue mutation on the Gibbs free

energies of protein folding and protein-ligand binding. The folding energy predictions of our

model also correlate as well with the data of Nisthal et al. ($R^2 = 0.570 \pm 0.049$) as the

predictions of Otwinowski's model does ($R^2 = 0.515 \pm 0.056$). This demonstrates that MAVE-NN

can infer accurate and interpretable quantitative models of protein biophysics.

To test MAVE-NN's ability to infer thermodynamic models of transcriptional regulation,

we re-analyzed the MPRA data of Kinney et al.,[16] in which random mutations to a 75 bp region

of the *Escherichia coli lac* promoter were assayed. This promoter region binds two regulatory

proteins, σ^{70} RNA polymerase (RNAP) and the transcription factor CRP. As in Kinney et al.,[16]

we proposed a four-state thermodynamic model that quantitatively explains how promoter

sequences control transcription rate (**Fig. 6c**). The parameters of this G-P map include the

Gibbs free energy of interaction between CRP and RNAP (ΔG_I), as well as energy matrices that

describe the CRP-DNA and RNAP-DNA interaction energies. Because the sort-seq MPRA of

Kinney et al. yielded discrete measurement values (**Figs. 1e,f**), we used an MPA measurement

process in our latent phenotype model (**Fig. 6d**). The biophysical parameter values we thus

inferred (**Fig. 6e**), including a CRP-RNAP interaction energy of $\Delta G_\mathrm{I} = -2.598 \pm 0.018 \, \mathrm{kcal/mol}$,

largely match those of Kinney et al., but were obtained far more rapidly (in ~10 min versus

multiple days) thanks to the use of stochastic gradient descent rather than Metropolis Monte

Carlo.

Constraints on datasets and models

As stated above, MAVE-NN places certain limitations on both input datasets and latent

phenotype models. Some of these constraints have been adopted to simplify the initial release

of MAVE-NN and can potentially be relaxed in future updates. Others reflect fundamental

mathematical properties of latent phenotype models. Here we summarize the primary

constraints users should be aware of.

MAVE-NN currently requires that all input sequences be the same length. This constraint

has been adopted because a large fraction of MAVE datasets have this form, and all of the built-

in G-P maps operate only on fixed-length sequences. Users who wish to analyze variable length

sequences can still do so by padding the ends of sequences with dummy characters.

Alternatively, users can provide a multiple-sequence alignment as input and include the gap

character as one of the characters to consider when training models.

314   As stated above, MAVE-NN can analyze MAVE datasets that have either continuous or

315   discrete measurements. At present, both types of measurements must be one-dimensional, i.e.,

316   users cannot fit a single model to vectors of multiple measurements (e.g., joint measurements of

317   protein binding affinity and protein stability, as in Ref. [27]). This constraint has been adopted only

318   to simplify the user interface of the initial release. It is not a fundamental limitation of latent

319   phenotype models and is scheduled to be relaxed in upcoming versions of MAVE-NN.

320   The current implementation of MAVE-NN also supports only one-dimensional latent

phenotypes (though the latent phenotype of custom G-P maps can depend on multiple

precursor phenotypes, e.g., binding energy or folding energy). This restriction was made

because accurately interpreting multi-dimensional latent phenotypes is substantially more

fraught than interpreting one-dimensional latent phenotypes, and we believe that additional

computational tools need to be developed to facilitate such interpretation. That being said, the

mathematical form of latent phenotype models is fully compatible with multi-dimensional latent

phenotypes. Indeed, this modeling strategy has been used in other work,[20,27,28,45] and we plan to

enable this functionality in future updates to MAVE-NN.

329   More fundamental constraints come into play when analyzing MAVE data that contains

only single-mutation variants. In such experiments, the underlying effects of individual mutations

are hopelessly confounded by the biophysical, physiological, and experimental nonlinearities

that may be present. By contrast, when the same mutation is observed in multiple genetic

backgrounds, MAVE-NN can use systematic differences in the mutational effects observed

between stronger and weaker backgrounds to remove these confounding influences. Thus, for

datasets that comprise only single-mutant effects, we limit MAVE-NN to inferring only additive

G-P maps using GE regression, and while the noise model in the GE measurement process is

allowed to be heteroscedastic, the nonlinearity is constrained to be linear.

We emphasize that, in practice, only a modest number of multiple-mutant variants are

required for MAVE-NN to learn the form of a non-linear measurement process (see Fig. 3e-g).

In this way, including a small fraction of the possible double-mutation variants in MAVE libraries

can be beneficial even just for determining the effects of single mutations. Adding such non-

comprehensive sets of double mutants to MAVE libraries is experimentally straight-forward, and

our numerical experiments suggest that assaying roughly the same number of double-mutation

variants as single-mutation variants should often suffice. We therefore recommend that

experimentalists—even those primarily interested in the effects of single mutations—consider

augmenting their MAVE libraries with a small subset of double-mutation variants.

Discussion

In this work we have presented a unified strategy for inferring quantitative models of G-P

maps from diverse MAVE datasets. At the core of our approach is the conceptualization of G-P

maps as a form of information compression, i.e., the G-P map first compresses an input

sequence into a latent phenotype value, which the MAVE then reads out indirectly via a noisy

nonlinear measurement process. By explicitly modeling this measurement process, one can

remove potentially confounding effects from the G-P map, as well as accommodate diverse

experimental designs. We have also introduced three information-theoretic metrics for

assessing the performance of the resulting models. These capabilities have been implemented

within an easy-to-use Python package called MAVE-NN.

We have demonstrated the capabilities of MAVE-NN in diverse biological contexts,

including in the analysis of both DMS and MPRA data. We have also demonstrated the superior

performance of MAVE-NN relative to the epistasis package of Sailer and Harms.[24] Along the

way, we observed that MAVE-NN can deconvolve experimental nonlinearities from additive G-P

maps when a relatively small number of sequences containing multiple mutations are included

in the assayed libraries. This capability provides a compelling reason for experimentalists to

include such sequences in their MAVE libraries, even if they are primarily interested in the

effects of single mutations. Finally, we showed how MAVE-NN can learn biophysically

interpretable G-P maps from both DMS and MPRA data.

MAVE-NN thus fills a critical need in the MAVE community, providing user-friendly

software capable of learning quantitative models of G-P maps from diverse MAVE datasets.

MAVE-NN has a streamlined user interface and is readily installed from PyPI by executing "pip

install mavenn" at the command line. Comprehensive documentation and step-by-step tutorials

are available at http://mavenn.readthedocs.io.

Acknowledgements. This work was supported by NIH grant 1R35GM133777 (awarded to

JBK), NIH Grant 1R35GM133613 (awarded to DMM), an Alfred P. Sloan Research Fellowship

(awarded to DMM), a grant from the CSHL/Northwell Health partnership, and funding from the

Simons Center for Quantitative Biology at Cold Spring Harbor Laboratory.

Author Contributions. AT, WTI, DMM, and JBK conceived the project. AT and JBK wrote the

software with assistance from AP and MK. WTI and JBK wrote a preliminary version of the

software. AT, MK, and JBK performed the data analysis. AT, DMM, and JBK wrote the

manuscript with contributions from MK and AP.

Availability of Data and Materials. MAVE-NN can be installed from PyPI by executing "pip

install mavenn" at the POSIX command line. Comprehensive documentation, including step-by-

step tutorials, is available at http://mavenn.readthedocs.io. Source code, the data sets analyzed

in this paper, and the scripts used for training the models and making the figures presented

herein, are available under an MIT open-source license at https://github.com/jbkinney/mavenn.

MAVE-NN version 1.0.0 was used for all of the analysis described in this manuscript and is

archived on Zenodo at https://doi.org/10.5281/zenodo.5812439.

Conflicts of Interest. The authors declare that they have no known conflicts of interest.

Figure 1. Examples illustrating the diversity of MAVEs. (**a**) DMS assays using either affinity purification or selective growth. **(i)** The DMS assay of Olson et al.[35] used a library of variant GB1 proteins covalently linked to their coding mRNAs via mRNA display. Functional GB1 proteins were then enriched using IgG beads. **(ii)** The DMS studies of Seuma et al.[36] and Bolognesi et al.[37] used selective growth in genetically modified *Saccharomyces cerevisiae* cells to respectively assay the functionality of variant Aβ and TDP-43 proteins. In all three experiments, deep sequencing was used to determine an enrichment ratio for each protein variant. (**b**) The resulting DMS dataset consists of variant protein sequences and their corresponding log enrichment values. (**c**) The MPSA of Wong et al..[38] A library of 3-exon minigenes was constructed from exons 16, 17, and 18 of *BRCA2*, with each minigene having a variant 5´ss at exon 17 and a random 20 nt barcode in the 3' UTR. This library was transfected into HeLa cells, and deep sequencing was used to quantify mRNA isoform abundance. (**d**) The resulting MPSA dataset comprises variant 5´ss with (noisy) PSI

values. (**e**) The sort-seq MPRA of Kinney et al..[16] A plasmid library was generated in which randomly mutagenized

versions of the *Escherichia coli lac* promoter drove the expression of GFP. Cells carrying these plasmids were sorted

using FACS, and the variant promoters in each bin of sorted cells as well as the initial library were sequenced. (**f**) The

resulting dataset comprises a list of variant promoter sequences, as well as a matrix of counts for each variant in

each FACS bin. MAVE: multiplex assay of variant effect; DMS: deep mutational scanning; MPSA: massively parallel

splicing assay; 5′ss: 5′ splice site(s); PSI: percent spliced in; GFP: green fluorescent protein; FACS: fluorescence-

activated cell sorting.

Figure 2. MAVE-NN quantitative modeling strategy. (**a**) Structure of latent phenotype models. A G-P map $f(x)$ maps

each sequence x to a latent phenotype ϕ, after which a measurement process $p(y|\phi)$ determines the measurement

y. (**b**) Example of an MPA measurement process inferred from the sort-seq MPRA data of Kinney et al..[16] MPA

measurement processes are used when y values are discrete. (**c**) Structure of a GE regression model, which is used

when y is continuous. A GE measurement process assumes that the mode of $p(y|\phi)$, called the prediction $\hat{y}$, is given

by a nonlinear function $g(\phi)$, and the scatter about this mode is described by a noise model $p(y|\hat{y})$. (**d**) Example of a

GE measurement process inferred from the DMS data of Olson et al..[35] Shown are the nonlinearity, the 68% CI, and

the 95% CI. (**e**) Information-theoretic quantities used to assess model performance. Intrinsic information, I_{int}, is the

mutual information between sequences x and measurements y. Predictive information, I_{pre}, is the mutual information

between measurements y and the latent phenotype values ϕ assigned by a model. Variational information, I_{var} , is a

linear transformation of log likelihood. The inequality $I_{\mathrm{int}} \geq I_{\mathrm{pre}} \geq I_{\mathrm{var}}$ always holds on test data (modulo finite data

uncertainties), with $I_{\mathrm{int}} = I_{\mathrm{pre}}$ when the G-P map is correct, and $I_{\mathrm{pre}} = I_{\mathrm{var}}$ when the measurement process correctly

describes the distribution of y conditioned on ϕ. G-P: genotype-phenotype; MPA: measurement process agnostic;

GE: global epistasis; CI: confidence interval.

Figure 3. Analysis of DMS data for protein GB1. MAVE-NN was used to infer a latent phenotype model, consisting of

an additive G-P map and a GE measurement process having a heteroskedastic skewed-t noise model, from the DMS

data of Olson et al..[35] All 530,737 pairwise variants reported for positions 2 to 56 of the GB1 domain were analyzed.

Data were split 90:5:5 into training, validation, and test sets. (**a**) The G-P map parameters inferred from all pairwise

variants. Gray dots indicate wildtype residues. Amino acids are ordered as in Olson et al..[35] (**b**) GE plot showing

measurements versus predicted latent phenotype values for 5,000 randomly selected test-set sequences (blue dots),

alongside the inferred nonlinearity (solid orange line) and the 95% CI (dashed lines) of the noise model. Gray line

indicates the latent phenotype value of the wildtype sequence. (**c**) Measurements plotted against $\hat{y}$ predictions for

these same sequences. Dashed lines indicate the 95% CI of the noise model. Gray line indicates the wildtype

sequence $\hat{y}$. (**d**) Corresponding information metrics computed during model training (using training data) or for the

final model (using test data); uncertainties in these estimates are roughly the width of the plotted lines. Gray shaded

area indicates allowed values for intrinsic information based on upper and lower bounds estimated as described in

Methods. (**e-g**) Test set predictions (blue dots) and GE nonlinearities (orange lines) for models trained using subsets

of the GB1 data containing all single mutants and 50,000 (**e**), 5,000 (**f**), or 500 (**g**) double mutants. The GE

nonlinearity from panel **b** is shown for reference (yellow-green lines). Uncertainties reflect standard errors. GE: global

epistasis; G-P: genotype-phenotype; CI: confidence interval.

Figure 4. Analysis of DMS data for Aβ and TDP-43. (**a,b**) Seuma et al.[36] measured nucleation scores for 499 single mutants and 15,567 double mutants of Aβ. These data were used to train a latent phenotype model comprising (**a**) an additive G-P map and (**b**) a GE measurement process with a heteroskedastic skewed-t noise model. (**c,d**) Bolognesi et al.[37] measured toxicity scores for 1,266 single mutants and 56,730 double mutants of TDP-43. The resulting data were used to train (**c**) an additive G-P map and (**d**) a GE measurement process of the same form as in panel **b**. In both cases, data were split 90:5:5 into training, validation, and test sets. In (**a,c**), gray dots indicate the wildtype sequence, amino acids are ordered as in the original publications, and * indicates a stop codon. White squares [355/882 (40.2%) for Aβ; 433/1764 (24.5%) for TDP-43] indicate residues that were not observed in the training set and thus could not be assigned values for their additive effects. In (**b,d**), blue dots indicate latent phenotype values versus measurements for held-out test data, gray line indicates the latent phenotype value of the wildtype sequence, solid orange line indicates the GE nonlinearity, and dashed orange lines indicate a corresponding 95% CI for the inferred noise model. Values for I_{var}, I_{pre}, and R^2 (between y and $\hat{y}$) are also shown. Uncertainties reflect standard errors. **Supplemental Fig. S2** shows measurements plotted against the $\hat{y}$ predictions of these models. Aβ: amyloid beta; TDP-43: TAR DNA-binding protein 43; G-P: genotype-phenotype; GE: global epistasis; CI: confidence interval.

Figure 5. Analysis of MPSA data from Wong et al..[38] This dataset reports PSI values, measured in the *BRCA2* exon 17 context, for nearly all 32,768 variant 5´ss of the form NNN/GYNNNN. Data were split 60:20:20 into training, validation, and test sets. Latent phenotype models with one of four types of G-P map (additive, neighbor, pairwise, or black box), as well as a GE measurement process with a heteroscedastic skewed-t noise model, were inferred. The epistasis package of Sailer and Harms[24] was also used to infer an additive G-P map and GE nonlinearity. (**a**)

Performance of trained models as quantified by I_var and I_pre, computed on test data. The lower bound on I_int was

estimated from experimental replicates (see **Methods**). p-value reflects a two-sided z-test. I_var was not computed for

the additive (epistasis package) model because that package does not infer an explicit noise model. (**b-d**)

Measurement values versus latent phenotype values, computed on test data, using the additive (epistasis package)

model (**b**), the additive model (**c**), and the pairwise model (**d**). The corresponding GE measurement processes are

also shown. (**e**) Sequence logo[46] illustrating the additive effects component of the pairwise G-P map. Dashed line

indicates the exon/intron boundary. G at +1 serves as a placeholder because no other bases were assayed at this

position. Only values for U and C at +2 were inferred. (**f**) Heatmap showing the pairwise effects component of the

pairwise G-P map. White diagonals correspond to unobserved bases. Error bars indicate standard errors.

Supplemental Information Fig. S3 shows the uncertainties in these parameters. MPSA: massively parallel splicing

assay; PSI: percent spliced in; G-P: genotype-phenotype; GE: global epistasis.

Figure 6. Biophysical models inferred from DMS and MPRA data. (**a**) Thermodynamic model for IgG binding by GB1. This model comprises three GB1 microstates (unfolded, folded-unbound, and folded-bound). The Gibbs free energies of folding (ΔG_F) and binding (ΔG_B) are computed from sequence using additive models called energy matrices. The latent phenotype is given by the fraction of time GB1 is in the folded-bound state. (**b**) The $\Delta\Delta G$ parameters of the energy matrices for folding and binding, inferred from the data of Olson et al.[35] using GE regression. **Supplemental Fig. S5** plots folding energy predictions against the measurements of Nisthal et al..[44] (**c**) A four-state thermodynamic model for transcriptional activation at the *E. coli lac* promoter. The Gibbs free energies of RNAP-DNA binding (ΔG_R) and CRP-DNA binding (ΔG_C) are computed using energy matrices, whereas the CRP-RNAP interaction energy ΔG_I is a scalar. The latent phenotype is the fraction of time a promoter is bound by RNAP. (**d,e**) The latent phenotype model inferred from the sort-seq MPRA of Kinney et al.,[16] including both the MPA measurement process (**d**) and the parameters of the thermodynamic G-P map (**e**). Supplemental **Fig. S4** provides detailed definitions of the thermodynamic models in panels **a** and **c**. Sequence logos in panel **e** were generated using Logomaker,[46] and standard errors for the protein-protein interaction energy were determined using the built-in parametric bootstrapping

approach described in Methods. GE: global epistasis. RNAP: RNA polymerase. MPA: measurement-process

agnostic. G-P: genotype-phenotype.

Online Methods

Notation

We represent each MAVE dataset as a set of N observations, $\{(x_n, y_n)\}_{n=0}^{N-1}$, where each

observation consists of a sequence x_n and a measurement y_n. Here, y_n can be either a

continuous real-valued number, or a nonnegative integer representing the "bin" in which the nth

sequence was found. Note that, in this representation the same sequence x can be observed

multiple times, potentially with different values for y due to experimental noise.

G-P maps

We assume that all sequences have the same length L, and that at each of the L

positions in each sequence there is one of C possible characters. MAVE-NN represents

sequences using a vector of one-hot encoded features of the form

503
$$x_{l:c} \quad = \quad \begin{cases} 1 & \text{if character } c \text{ occurs at position } l \\ 0 & \text{otherwise} \end{cases} , \tag{1}$$

where $l = 0,1,\dots,L-1$ indexes positions within the sequence, and c indexes the C distinct

characters. MAVE-NN supports built-in alphabets for DNA, RNA and protein (with or without

stop codons), as well as user-defined sequence alphabets.

We assume that the latent phenotype is given by a linear function $\phi(x; \theta)$ that depends

on a set of G-P map parameters θ. As mentioned in the main text, MAVE-NN supports four

types of G-P map models, all of which can be inferred using either GE regression or MPA

regression. The additive model is given by,

511
$$\phi_{\text{additive}}(x; \theta) \quad = \quad \theta_0 + \sum_{l=0}^{L-1} \sum_{c} \theta_{l:c}\, x_{l:c} , \tag{2}$$

512   and thus each position in x contributes independently to the latent phenotype. The neighbor

513   model is given by,

$$\phi_{\text{neighbor}}(x;\theta) = \theta_0 + \sum_{l=0}^{L-1}\sum_{c}\theta_{l:c}\,x_{l:c} + \sum_{l=0}^{L-2}\sum_{c,c'}\theta_{l:c,l+1:c'}\,x_{l:c}x_{l+1:c'}\,, \tag{3}$$

515   and further accounts for potential epistatic interactions between neighboring positions. The

516   pairwise model is given by,

$$\phi_{\text{pairwise}}(x;\theta) = \theta_0 + \sum_{l=0}^{L-1}\sum_{c}\theta_{l:c}\,x_{l:c} + \sum_{l=0}^{L-2}\sum_{l'=l+1}^{L-1}\sum_{c,c'}\theta_{l:c,l':c'}\,x_{l:c}x_{l':c'}\,, \tag{4}$$

and includes interactions between all pairs of positions. Note our convention of requiring $l' > l$ in

the pairwise parameters $\theta_{l:c,l':c'}$.

Unlike these three parametric models, the black box G-P map does not have a fixed

functional form. Rather, it is given by a multilayer perceptron that takes a vector of sequence

features (additive, neighbor, or pairwise) as input, contains multiple fully-connected hidden

layers with nonlinear activations, and has a single node output with a linear activation. Users are

able to specify the number of hidden layers, the number of nodes in each hidden layer, and the

activation function used by these nodes.

MAVE-NN further supports custom G-P maps that users can define by subclassing the G-

P map base class. These G-P maps can have arbitrary functional form, e.g., representing specific

biophysical hypotheses of sequence function. This feature of MAVE-NN is showcased in the

analyses of **Fig. 6**.

Gauge modes and diffeomorphic modes

G-P maps typically have non-identifiable degrees of freedom that must be fixed, i.e.,

pinned down, before the values of individual parameters can be meaningfully interpreted or

compared between models. These degrees of freedom come in two flavors: gauge modes and

diffeomorphic modes. Gauge modes are changes to θ that do not alter the values of the latent

phenotype ϕ. Diffeomorphic modes[15,20] are changes to θ that do alter ϕ, but do so in ways that

can be undone by transformations of the measurement process $p(y|\phi)$. As shown by Kinney

and Atwal,[15,20] the diffeomorphic modes of linear G-P maps like those considered here will in

general correspond to affine transformations of ϕ, although additional unconstrained modes can

occur in special situations.

MAVE-NN fixes both gauge modes and diffeomorphic modes of inferred models (except

when using custom G-P maps). The diffeomorphic modes of G-P maps are fixed by

transforming θ via

$$\theta_0 \rightarrow \theta_0 - a, \tag{5}$$

544   and then

$$\theta \rightarrow \frac{\theta}{b}, \tag{6}$$

546   where $a = \mathrm{mean}(\{\phi_n\})$ and $b = \mathrm{std}(\{\phi_n\})$ are the mean and standard deviation of ϕ values

547   computed on the training data. This produces a corresponding change in latent phenotype

548   values $\phi \rightarrow (\phi - a)/b$. To avoid altering likelihood values, MAVE-NN makes a corresponding

549   transformation to the measurement process $p(y|\phi)$. In GE regression this is done by adjusting

550   the GE nonlinearity via

$$g(\phi) \rightarrow g(a + b\phi), \tag{7}$$

552   while keeping the noise model $p(y|\hat{y})$ fixed. In MPA regression MAVE-NN transforms the full

553   measurement process via

554
$$p(y|\phi) \to p(y|a + b\phi).$$
(8)

For the three parametric G-P maps, gauge modes are fixed using what we call the

"hierarchical gauge." Here, the parameters θ are adjusted so that the lower-order terms in

$\phi(x; \theta)$ account for the highest possible fraction of variance in ϕ. This procedure requires a

probability distribution on sequence space with respect to which these variances are computed.

MAVE-NN assumes that such distributions factorize by position, and can thus be represented

by a probability matrix with elements $p_{l:c}$, denoting the probability of character c at position l.

MAVE-NN provides three built-in choices for this distribution: uniform, empirical, or wildtype.

The corresponding values of $p_{l:c}$ are given by

563
$$p_{l:c} \;=\; \begin{cases} 1/C & \text{for uniform} \\ n_{l:c}/N & \text{for empirical} \\ x_{l:c}^{\text{wt}} & \text{for wildtype} \end{cases},$$
(9)

where $n_{l:c}$ denotes the number of sequences (out of N total) that have character c at position l,

and $x_{l:c}^{\text{wt}}$ is the one-hot encoding of a user-specified wildtype sequence. In particular, the

wildtype gauge was used for illustrating the additive G-P maps in **Fig. 3** and **Fig. 4**, while the

uniform gauge was used for illustrating the pairwise G-P map in **Fig. 5** and the energy matrices

in **Fig. 6**. After a sequence distribution is chosen, MAVE-NN fixes the gauge of the pairwise G-P

map by transforming

570
$$\begin{aligned} \theta_0 \;\to\; & \theta_0 \\ & + \sum_l \sum_{c'} \theta_{l:c'} \, p_{l:c'} \\ & + \sum_l \sum_{l'>l} \sum_{c,c'} \theta_{l:c,l':c'} \, p_{l:c} \, p_{l':c'} , \end{aligned}$$
(10)

$$
\begin{aligned}
\theta_{l:c} \quad \rightarrow \quad & \theta_{l:c} \\
& - \sum_{c'} \theta_{l:c'} \, p_{l:c'} \\
& + \sum_{l'>l} \sum_{c'} \theta_{l:c,l':c'} \, p_{l':c'} \\
& + \sum_{l'<l} \sum_{c'} \theta_{l':c',l:c} \, p_{l':c'} \\
& - \sum_{l'>l} \sum_{c',c''} \theta_{l:c',l':c''} \, p_{l:c'} \, p_{l':c''} \\
& - \sum_{l'<l} \sum_{c',c''} \theta_{l':c'',l':c'} \, p_{l:c'} \, p_{l':c''} ,
\end{aligned}
\tag{11}
$$

572 and

$$
\begin{aligned}
\theta_{l:c,l':c'} \quad \rightarrow \quad & \theta_{l:c,l':c'} \\
& - \sum_{c''} \theta_{l:c'',l':c'} \, p_{l:c''} \\
& - \sum_{c''} \theta_{l:c,l':c''} \, p_{l':c''} \\
& + \sum_{c'',c'''} \theta_{l:c'',l':c'''} \, p_{l:c''} \, p_{l':c'''} .
\end{aligned}
\tag{12}
$$

This transformation is also used for the additive and neighbor G-P maps, but with $\theta_{l:c,l':c'} = 0$ for

all l, l' (additive) or whenever $l' \neq l + 1$ (neighbor).

GE nonlinearities

GE models assume that each measurement y is a nonlinear function of the latent

phenotype $g(\phi)$ plus some noise. In MAVE-NN, this nonlinearity is represented as a sum of

tanh sigmoids:

$$
g(\phi; \alpha) = a + \sum_{k=0}^{K-1} b_k \tanh(c_k \phi + d_k) .
\tag{13}
$$

Here, K specifies the number of hidden nodes contributing to the sum, and $\alpha = \{a, b_k, c_k, d_k\}$ are

trainable parameters. We note that this mathematical form is an example of the bottleneck

architecture previously used by[23,45] for modeling GE nonlinearities. By default, MAVE-NN

constrains $g(\phi; \alpha)$ to be monotonic in ϕ by requiring all $b_k \geq 0$ and $c_k \geq 0$, but this constraint

can be relaxed.

GE noise models

MAVE-NN supports three types of GE noise model: Gaussian, Cauchy, and skew-t.

These all support the analytic computation of quantiles and confidence intervals, as well as the

rapid sampling of simulated measurement values. The Gaussian noise model is given by

590
$$p_{\text{gauss}}(y|\hat{y}; s) = \frac{1}{\sqrt{2\pi s^2}} \exp\left[-\frac{(y - \hat{y})^2}{2s^2}\right],$$
(14)

591   where s denotes the standard deviation. Importantly, MAVE-NN allows this noise model to be

592   heteroskedastic by representing s as an exponentiated polynomial in $\hat{y}$, i.e.,

593
$$s(\hat{y}) = \exp\left[\sum_{k=0}^{K} a_k \hat{y}^k\right],$$
(15)

594   where K is the order of the polynomial and $\{a_k\}$ are trainable parameters. The user has the

595   option to set K, and setting $K = 0$ renders this noise model homoscedastic. Quantiles are

596   computed using $y_q = \hat{y} + s\sqrt{2}\,\text{erf}^{-1}(2q - 1)$ for user-specified values of $q \in [0,1]$. Similarly, the

597   Cauchy noise model is given by

598
$$p_{\text{cauchy}}(y|\hat{y}; s) = \left[\pi s\left(1 + \frac{(y - \hat{y})^2}{s^2}\right)\right]^{-1},$$
(16)

599   where the scale parameter s is an exponentiated K'th order polynomial in $\hat{y}$, and quantiles are

600   computed using $y_q = \hat{y} + s\tan\left[\pi(q - \frac{1}{2})\right].$

601   The skew-t noise model is of the form described by Jones and Faddy,[29] and is given by

602
$$p_{\text{skewt}}(y|\hat{y}; s, a, b) = s^{-1} f(t; a, b),$$
(17)

603   where

604
$$t = t^* + \frac{y - \hat{y}}{s}, \quad t^* = \frac{(a - b)\sqrt{a + b}}{\sqrt{2a + 1}\sqrt{2b + 1}},$$
(18)

605   and

606
$$f(t; a, b) = \frac{2^{1-a-b}}{\sqrt{a + b}} \frac{\Gamma(a + b)}{\Gamma(a)\Gamma(b)} \left[1 + \frac{t}{\sqrt{a + b + t^2}}\right]^{a+\frac{1}{2}}$$
$$\times \left[1 - \frac{t}{\sqrt{a + b + t^2}}\right]^{b+\frac{1}{2}}.$$
(19)

607   Note that the t statistic here is an affine function of y chosen so that the distribution's mode

608   (corresponding to t^*) is positioned at $\hat{y}$. The three parameters of this noise model, $\{s, a, b\}$, are

609   each represented using K-th order exponentiated polynomials with trainable coefficients.

610   Quantiles are computed using

611
$$y_q = \hat{y} + (t_q - t^*)s,$$
(20)

612   where

613
$$t_q = \frac{(2x_q - 1)\sqrt{a + b}}{\sqrt{1 - (2x_q - 1)^2}}, \quad x_q = I_q^{-1}(a, b),$$
(21)

and I^{-1} denotes the inverse of the regularized incomplete Beta function $I_x(a, b)$.

Empirical noise models

MAVE-NN further supports the inference of GE regression models that account for user-

specified measurement noise. In such cases, the user provides a set of measurement-specific

uncertainties $\{s_n\}_{n=0}^{N-1}$ along with the corresponding sequences and measurements. These uncertainties

can, for example, be estimated by using a software package like Enrich2[11] or DiMSum[14]. MAVE-NN then

trains the parameters of latent phenotype models by assuming a Gaussian noise model of the form

621
$$p_{\text{empirical}}(y_n|\hat{y}_n, s_n) = \frac{1}{\sqrt{2\pi s_n^2}} \exp\left[-\frac{(y_n - \hat{y}_n)^2}{2s_n^2}\right],$$
(14)

where $\hat{y}_n = g(f(x_n; \theta); \alpha)$ is the expected measurement for sequence x_n, θ denotes G-P map

parameters, and α denotes the parameters of the GE nonlinearity. This noise model thus has

the advantage of having no free parameters, but it may be problematically mis-specified if the

true error distribution is heavy-tailed or skewed.

MPA measurement process

In MPA regression, MAVE-NN directly models the measurement process $p(y|\phi)$. At

present, MAVE-NN only supports MPA regression for discrete values of y indexed using

nonnegative integers. MAVE-NN supports two alternative forms of input for MPA regression.

One is a set of sequence-measurement pairs $\{(x_n, y_n)\}_{n=0}^{N-1}$, where N is the total number of

reads, $\{x_n\}$ is a set of (typically) non-unique sequences, each $y_n \in \{0,1,\dots,Y-1\}$ is a bin

number, and Y is the total number of bins. The other is a set of sequence-count-vector pairs

$\{(x_m, c_m)\}_{m=0}^{M-1}$, where M is the total number of unique sequences and $c_m = (c_{m0}, c_{m1}, \dots, c_{m(Y-1)})$

is a vector that lists the number of times c_{my} that the sequence x_m was observed in each bin y.

MPA measurement processes are represented as multilayer perceptron with one hidden layer

(having tanh activations) and a softmax output layer. Specifically,

637
$$p(y|\phi) = \frac{w_y(\phi)}{\sum_{y'} w_{y'}(\phi)},$$
(22)

638   where

639
$$w_y(\phi) = \exp\left[a_y + \sum_{k=0}^{K-1} b_{yk} \tanh(c_{yk}\phi + d_{yk})\right]$$
(23)

and K is the number of hidden nodes per value of y. The trainable parameters of this

measurement process are $\eta = \{a_y, b_{yk}, c_{yk}, d_{yk}\}$.

Loss function

Let θ denote the G-P map parameters, and η denote the parameters of the

measurement process. MAVE-NN optimizes these parameters using stochastic gradient

descent on a loss function given by

646
$$\mathcal{L} = \mathcal{L}_{\text{like}} + \mathcal{L}_{\text{reg}} , \tag{24}$$

647   where $\mathcal{L}_{\text{like}}$ is the negative log likelihood of the model, given by

648
$$\mathcal{L}_{\text{like}}[\theta, \eta] = -\sum_{n=0}^{N-1} \log\left[p(y_n|\phi_n; \eta)\right] \tag{25}$$

where $\phi_n = \phi(x_n; \theta)$, and $\mathcal{L}_{\text{reg}}$ provides for regularization of the model parameters.

In the context of GE regression, we can write $\eta = (\alpha, \beta)$ where α represents the

parameters of the GE nonlinearity $g(\phi; \alpha)$, and β denotes the parameters of the noise model

$p(y|\hat{y}; \beta)$. The likelihood contribution from each observation n then becomes $p(y_n|\phi_n; \eta) =$

$p(y_n|\hat{y}_n; \beta)$ where $\hat{y}_n = g(\phi_n; \alpha)$. In the context of MPA regression with a dataset of the form

$\{(x_m, c_m)\}_{m=0}^{M-1}$, the loss function simplifies to

655
$$\mathcal{L}_{\text{like}}[\theta, \eta] = -\sum_{m=0}^{M-1}\sum_{y=0}^{Y-1} c_{my} \log[p(y|\phi_m; \eta)] \tag{26}$$

656   where $\phi_m = \phi(x_m; \theta)$. For the regularization term, MAVE-NN uses an L_2 penalty of the form

657
$$\mathcal{L}_{\text{reg}}[\theta, \eta] = \lambda_\theta |\theta|^2 + \lambda_\eta |\eta|^2 , \tag{27}$$

where the user-adjusted parameters λ_θ and λ_η respectively control the strength of regularization

for the G-P map and measurement process parameters.

Predictive information

In what follows, we use $p_{\mathrm{model}}(y|\phi)$ to denote a measurement process inferred by

MAVE-NN, whereas $p_{\mathrm{true}}(y|\phi)$ denotes the empirical conditional distribution of y and ϕ values

that would be observed in the limit of infinite test data.

Predictive information $I_{\mathrm{pre}} = I[y; \phi]$, where $I[\cdot; \cdot]$ represents mutual information computed

on data not used for training (i.e., a held-out test set or data from a different experiment), I_{pre}

provides a measure of how strongly a G-P map predicts experimental measurements.

Importantly, this quantity does not depend on the corresponding measurement process

$p_{\mathrm{model}}(y|\phi)$. To estimate I_{pre}, we use k'th nearest neighbor (kNN) estimators of entropy and

mutual information adapted from the NPEET Python package.[47] Here, the user has the option of

adjusting k, which controls a variance/bias tradeoff. When y is discrete (MPA regression), I_{pre} is

computed using the classic kNN entropy estimator[48,49] via the decomposition $I[y; \phi] = H[\phi] -$

$\sum_y p(y) H_y[\phi]$, where $H_y[\phi]$ denotes the entropy of $p_{\mathrm{true}}(\phi|y)$. When y is continuous (GE

regression), $I[y; \phi]$ is estimated using the kNN-based Kraskov Stögbauer Grassberger (KSG)

algorithm.[49] This approach optionally supports the local nonuniformity correction of Gao et al.,

which is important when y and ϕ exhibit strong dependencies, but which also requires

substantially more time to compute.

Variational information

We define variational information as an affine transformation of $\mathcal{L}_{\mathrm{like}}$,

679
$$I_{\mathrm{var}} = H[y] - \frac{\log_2(e)}{N} \mathcal{L}_{\mathrm{like}} . \tag{28}$$

680   Here, $H[y]$ is the entropy of the data $\{y_n\}$, which is estimated using the k'th nearest neighbor

681   (kNN) estimator from the NPEET package.[47] Noting that this quantity can also be written as

682     $I_{\text{var}} = H[y] - \text{mean}(\{Q_n\})$, where $Q_n = -\log_2 p(y_n|\phi_n)$, we estimate the associated uncertainty

683   using

$$\delta I_{\text{var}}[y; \phi] = \sqrt{\delta H[y]^2 + \frac{\text{var}(\{Q_n\})}{N}} \ . \tag{29}$$

685   The inference strategy used by MAVE-NN is based on the fact that I_{var} provides a tight

686   variational lower bound on I_{pre}. Indeed, in the large data limit,

$$I_{\text{pre}} = I_{\text{var}} + D_{\text{KL}}(p_{\text{true}}||p_{\text{model}}) \, , \tag{30}$$

where $D_{\text{KL}}(\cdot) \geq 0$ is the Kullback-Leibler divergence, and thus quantifies the accuracy of the

inferred measurement process. From **Eq. 30** one can see that, with appropriate caveats,

maximizing I_{var} (or equivalently, $\mathcal{L}_{\text{like}}$) will also maximize I_{pre}.[20] But unlike I_{pre}, I_{var} is readily

compatible with backpropagation and stochastic gradient descent. See Supplemental

Information for a derivation of **Eq. 30** and an expanded discussion of this key point. Note:

Sharpee et al.[50] cleverly showed that I_{pre} can, in fact, be optimized using stochastic gradient

descent. Computing gradients of I_{pre}, however, requires a time-consuming density estimation

step. Optimizing I_{var}, on the other hand, can be done using standard per-datum

backpropagation.

Intrinsic information

Intrinsic information, $I_{\text{int}} = I[x; y]$, is the mutual information between the sequences x

and measurements y in a dataset. This quantity is somewhat tricky to estimate due to the high-

dimensional nature of sequence space. We instead used three different methods to obtain the

upper and lower bounds on I_{int} shown in **Fig. 3d** and **Fig. 5a**. More generally, we believe the

development of both computational and experimental methods for estimating I_{int} is be an

important avenue for future research.

To compute the upper bound on I_{int} for GB1 data (in **Fig. 3d**), we used the fact that

$$I[x; y] = H[y] - \langle H_x[y] \rangle_x, \tag{31}$$

706   where $H[y]$ is the entropy of all measurements y, $H_x[y]$ is the entropy of $p(y|x)$ for a specific

707   choice of sequence x, and $\langle \cdot \rangle_x$ indicates averaging over all sequences x. In this dataset, the

708   measurement values were computed using

$$y = \log_2 \left[\frac{c_s + 1}{c_i + 1} \right], \tag{32}$$

710   where c_i is the input read count and c_s is the selected read count. $H[y]$ was estimated using the

711   KNN estimator.[48] We estimated the uncertainty in y by propagating errors expected due to

712   Poisson fluctuations in read counts, which gives

$$\delta y = \log_2(e) \sqrt{\frac{1}{c_s + 1} + \frac{1}{c_i + 1}}. \tag{33}$$

714   Then, assuming $p(y|x)$ to be approximately Gaussian, we find the corresponding conditional

715   entropy to be

$$H_x[y] = \frac{1}{2} \log_2(2\pi e \, \delta y^2). \tag{34}$$

These $H[y]$ and $H_x[y]$ values were then used in **Eq. 31** to estimate I_{int}. This should provide an

upper bound on the true value of I_{int} because uncertainty in y must be at least that expected

under Poisson sampling of reads. We note, however, that the use of linear error propagation

and the assumption that $p(y|x)$ is approximately Gaussian complicate this conclusion. Also,

when applied to MPSA data, this method yielded an upper bound of 0.96 bits. We believe this

value is likely to be far higher than the true value of I_{int}, and that this mismatch probably

resulted from read counts in the MPSA data being over-dispersed.

To compute the lower bound on I_{int} for GB1 data (**Fig. 3d**) we used the predictive

information I_{pre} (on test data) of a GE regression model having a blackbox G-P map. This

provides a lower bound because $I_{int} \geq I_{pre}$ for any model (when evaluated on test data) due to

the Data Processing Inequality and the Markov Chain nature of the dependencies $y \leftarrow x \rightarrow \phi$ in

Fig. 2e.[20,31]

To compute a lower bound on I_{int} for MPSA data (**Fig. 5c**), we leveraged the availability

of replicate data in Wong et al..[38] Let y and y' represent the original and replicate

measurements obtained for a sequence x. Because $y \leftarrow x \rightarrow y'$ forms a Markov chain, $I[x; y] \geq$

$I[y; y']$.[31] We therefore used an estimate of $I[y; y']$, computed using the KSG method,[47,49] as the

lower bound for I_{int}.

Uncertainties in kNN estimates of mutual information

MAVE-NN quantifies uncertainties in $H[y]$ and $I[y; \phi]$ using multiple random samples of

half the data. Let $\mathcal{D}_{100\%}$ denote a full dataset, and let $\mathcal{D}_{50\%,r}$ denote a 50% subsample (indexed

by r) of this dataset. Given an estimator $E(\cdot)$ of either entropy or mutual information, as well as

the number of subsamples R to use, the uncertainty in $E(\mathcal{D}_{100\%})$ is estimated as

739
$$\delta E(\mathcal{D}_{100\%}) = \frac{1}{\sqrt{2}} \text{std}\left[\left\{E\left(\mathcal{D}_{50\%,r}\right)\right\}_{r=0}^{R-1}\right].\tag{35}$$

MAVE-NN uses $R = 25$ by default. We note that computing such uncertainty estimates

substantially increases computation time, as $E(\cdot)$ needs to be evaluated $R + 1$ times instead of

just once. We also note that bootstrap resampling[51,52] is often inadvisable in this context, as it

systematically underestimates $H[y]$ and overestimates $I[y; z]$.

Uncertainties in G-P map parameters

Given a trained latent phenotype model, having G-P map parameters θ^* and

measurement process parameters η^*, MAVE-NN can optionally assess model uncertainty using

the following parametric bootstrap approach. Using the trained model with parameters (θ^*, η^*)

as "ground truth", MAVE-NN simulates R (chosen by the user) different MAVE datasets $\mathcal{D}_r =$

$\left\{(x_n, y_n^{(r)})\right\}_{n=0}^{N-1}$, where $r = 0, 1, \ldots, R-1$ indexes the different simulations. Note that the

sequences in these simulated datasets are the same as the original training sequence, but the

measurements are different. For each simulated dataset $\mathcal{D}_r$, MAVE-NN then trains a new

model, by default using the same hyperparameters as were used for the ground truth model.

This procedure yields a set $\left\{\left(\tilde{\theta}^{(r)}, \eta^{(r)}\right)\right\}_{r=0}^{R-1}$ of simulation-inferred G-P map parameters and

corresponding measurement process parameters. Users can then use this sampling of G-P map

parameters to estimate uncertainties, e.g., by reporting $\delta\theta_k = \text{std}\left[\left\{\theta_k^{(r)}\right\}_{r=0}^{R-1}\right]$.

An important detail when assessing parameter uncertainty is to ensure that both the

gauge modes and the diffeomorphic modes of each model are fixed. This is necessary so that

differences in the parameters that cannot result in changes to model predictions do not inflate

the uncertainty estimates. For additive, neighbor, and pairwise G-P maps, MAVE-NN

automatically implements the procedure described in the "Gauge modes and diffeomorphic

modes" section above, thereby removing these extra degrees of freedom. However, for more

complex models such as those implemented by MAVE-NN's custom G-P map functionality (e.g.,

representing biophysical models) different gauge freedoms and diffeomorphic modes may arise

depending on the details of the model, and users must take care to determine and fix these

prior to assessing parameter uncertainty. We also note that no meaningful computation of

individual parameter uncertainties is likely to be possible for highly over-parameterized models,

such as the "black box" deep neural network models supported by MAVE-NN.

Datasets

For the GB1 DMS dataset of Olson et al.,[35] measurements were computed using

770
$$y_n = \log_2 \frac{(c_n^{\text{out}}+1)/(c_{\text{WT}}^{\text{out}}+1)}{(c_n^{\text{in}}+1)/(c_{\text{WT}}^{\text{in}}+1)},$$

where c_n^{in} and c_n^{out} respectively represent the number of reads from the input and output

samples (i.e., pre-selection and post-selection libraries), and $n = \text{WT}$ represents the 55 aa

wildtype sequence, corresponding to positions 2-56 of the GB1 domain. To infer the model in

Fig. 3b and to compute the information metrics in **Fig. 3c**, only double-mutant sequences with

$c_n^{\text{in}} \geq 10$ were used; these represent 530,737 out of the 536,085 possible double mutants. For

the models in **Figs. 3d-f**, y_n values for the 1045 single-mutant were also used in the inference

procedure.

For the Aβ DMS data of Seuma et al.[36] and TDP-43 DMS data of Bolognesi et al.,[37] y_n

values respectively represent nucleation scores and toxicity scores reported by the authors.

For the MPSA data of Wong et al.,[38] we used the data of library 1 replicate 1 obtained

for the *BRCA2* minigene data. Measurements were computed as

782
$$y_n = \log_{10}\left[100 \times \frac{(c_n^{\text{inc}}+1)/(c_{\text{CONS}}^{\text{inc}}+1)}{(c_n^{\text{tot}}+1)/(c_{\text{CONS}}^{\text{tot}}+1)}\right],$$

where c_n^{inc} and c_n^{tot} respectively represent the number of barcode reads obtained from exon

inclusion isoforms and from total mRNA, and $n = \text{CONS}$ corresponds to the consensus 5´ss

sequence CAG/GUAAGU. Corresponding PSI values were computed as $\text{PSI}_n = 10^{y_n}$. Only

sequences with $c_n^{\text{tot}} \geq 10$ were used, representing 30,483 of the 32,768 possible sequences of

the form NNN/GYNNNN.

For the lac promoter sort-seq MPRA data of Kinney et al.,[16] we used data from the "full-

wt" experiment (available at https://github.com/jbkinney/09_sortseq).

References

1. Kinney, J. B. & McCandlish, D. M. Massively parallel assays and quantitative sequence-function relationships. *Annu Rev Genom Hum G* **20**, 99-127 (2019).

2. Starita, L. M. *et al.* Variant interpretation: functional assays to the rescue. *Am J Hum Genetics* **101**, 315-325 (2017).

3. Fowler, D. M. & Fields, S. Deep mutational scanning: a new style of protein science. *Nat Methods* **11**, 801-807 (2014).

4. Levo, M. & Segal, E. In pursuit of design principles of regulatory sequences. *Nat Rev Genet* **15**, 453-468 (2014).

5. White, M. A. Understanding how cis-regulatory function is encoded in DNA sequence using massively parallel reporter assays and designed sequences. *Genomics* **106**, 165-170 (2015).

6. Inoue, F. & Ahituv, N. Decoding enhancers using massively parallel reporter assays. *Genomics* **106**, 159-164 (2015).

7. Peterman, N. & Levine, E. Sort-seq under the hood: implications of design choices on large-scale characterization of sequence-function relations. *BMC Genomics* **17**, 206 (2016).

8. Fowler, D. M., Araya, C. L., Gerard, W. & Fields, S. Enrich: software for analysis of protein function by enrichment and depletion of variants. *Bioinformatics* **27**, 3430-3431 (2011).

9. Alam, K. K., Chang, J. L. & Burke, D. H. FASTAptamer: A bioinformatic toolkit for high-throughput sequence analysis of combinatorial selections. *Mol Ther-Nucleic Acids* **4**, e230 (2015).

10. Bloom, J. D. Software for the analysis and visualization of deep mutational scanning data. *BMC Bioinformatics* **16**, 168 (2015).

11. Rubin, A. F. *et al.* A statistical framework for analyzing deep mutational scanning data. *Genome Biol* **18**, 1-15 (2017).

12. Ashuach, T. *et al.* MPRAnalyze: statistical framework for massively parallel reporter assays. *Genome Biol* **20**, 183 (2019).

13. Niroula, A., Ajore, R. & Nilsson, B. MPRAscore: robust and non-parametric analysis of massively parallel reporter assays. *Bioinformatics* **35**, 5351-5353 (2019).

14. Faure, A. J., Schmiedel, J. M., Baeza-Centurion, P. & Lehner, B. DiMSum: an error model and pipeline for analyzing deep mutational scanning data and diagnosing common experimental pathologies. *Genome Biol* **21**, 207 (2020).

15. Atwal, G. S. & Kinney, J. B. Learning quantitative sequence-function relationships from
massively parallel experiments. *J Stat Phys* **162**, 1203-1243 (2016).

16. Kinney, J. B., Murugan, A., Callan, C. G. & Cox, E. C. Using deep sequencing to
characterize the biophysical mechanism of a transcriptional regulatory sequence. *Proc Natl*
Acad Sci USA **107**, 9158-9163 (2010).

17. Melnikov, A. *et al.* Systematic dissection and optimization of inducible enhancers in human
cells using a massively parallel reporter assay. *Nat Biotechnol* **30**, 271-277 (2012).

18. Mogno, I., Kwasnieski, J. C. & Cohen, B. A. Massively parallel synthetic promoter assays
reveal the in vivo effects of binding site variants. *Genome Res* **23**, 1908-1915 (2013).

19. Abadi, M. *et al.* TensorFlow: A Systems for Large-Scale Machine Learning. in *Proceedings*
of the 12th USENIX Symposium on Operating Systems Design and Implementation (OSDI '16)
(2016).

20. Kinney, J. B. & Atwal, G. S. Parametric inference in the large data limit using maximally
informative models. *Neural Comput* **26**, 637-653 (2014).

21. Kinney, J. B., Tkačik, G. & Callan, C. G. Precise physical models of protein-DNA interaction
from high-throughput data. *Proc Natl Acad Sci USA* **104**, 501-506 (2007).

22. Otwinowski, J. & Nemenman, I. Genotype to phenotype mapping and the fitness landscape
of the E. coli lac promoter. *PLoS ONE* **8**, e61570 (2013).

23. Sarkisyan, K. S. *et al.* Local fitness landscape of the green fluorescent protein. *Nature* **533**,
397-401 (2016).

24. Sailer, Z. R. & Harms, M. J. Detecting high-order epistasis in nonlinear genotype-phenotype
maps. *Genetics* **205**, 1079-1088 (2017).

25. Otwinowski, J., McCandlish, D. M. & Plotkin, J. B. Inferring the shape of global epistasis.
Proc Natl Acad Sci USA **115**, E7550-E7558 (2018).

26. Gelman, S., Fahlberg, S. A., Heinzelman, P., Romero, P. A. & Gitter, A. Neural networks to
learn protein sequence-function relationships from deep mutational scanning data. *Proc Natl*
Acad Sci USA **118**, e2104878118 (2021).

27. Faure, A. J. *et al.* Global mapping of the energetic and allosteric landscapes of protein
binding domains. *bioRxiv* doi:10.1101/2021.09.14.460249 (2021)

28. Tonner, P. D., Pressman, A. & Ross, D. Interpretable modeling of genotype-phenotype
landscapes with state-of-the-art predictive power. *bioRxiv* doi:10.1101/2021.06.11.448129
(2021).

29. Jones, M. C. & Faddy, M. J. A skew extension of the t-distribution, with applications. *J Roy*
Stat Soc B **65**, 159-174 (2003).

30. Kinney, J. B. & Atwal, G. S. Equitability, mutual information, and the maximal information
coefficient. *Proc Natl Acad Sci USA* **111**, 3354-3359 (2014).

31. Cover, T. M. & Thomas, J. A. *Elements of information theory*. (Wiley, 2006).

32. Barber, D. & Agakov, F. The IM algorithm: a variational approach to information
maximization. *Advances in neural information processing systems 16.* (2004).

33. Alemi, A. A., Fischer, I., Dillon, J. V. & Murphy, K. Deep variational information bottleneck.
arXiv:1612.00410 (2016).

34. Chalk, M., Marre, O. & Tkačik, G. Relevant sparse codes with variational information
bottleneck. *arXiv:1605.07332* (2016).

35. Olson, C. A., Wu, N. C. & Sun, R. A comprehensive biophysical description of pairwise
epistasis throughout an entire protein domain. *Curr Biol* **24**, 2643-2651 (2014).

36. Seuma, M., Faure, A., Badia, M., Lehner, B. & Bolognesi, B. The genetic landscape for
amyloid beta fibril nucleation accurately discriminates familial Alzheimer's disease mutations.
eLife **10**, e63364 (2021).

37. Bolognesi, B. *et al.* The mutational landscape of a prion-like domain. *Nat Commun* **10**, 4162
(2019).

38. Wong, M. S., Kinney, J. B. & Krainer, A. R. Quantitative activity profile and context
dependence of all human 5´ splice sites. *Mol Cell* **71**, 1012-1026.e3 (2018).

39. Bintu, L. *et al.* Transcriptional regulation by the numbers: models. *Curr Opin Genet Dev* **15**,
116-124 (2005).

40. Sherman, M. S. & Cohen, B. A. Thermodynamic state ensemble models of cis-regulation.
PLoS Comput Biol **8**, e1002407 (2012).

41. Wong, F. & Gunawardena, J. Gene Regulation in and out of equilibrium. *Annu Rev Biophys*
49, 199-226 (2020).

42. Otwinowski, J. Biophysical inference of epistasis and the effects of mutations on protein
stability and function. *Mol Biol Evol* **35**, 2345-2354 (2018).

43. Manhart, M. & Morozov, A. V. Protein folding and binding can emerge as evolutionary
spandrels through structural coupling. *Proc Natl Acad Sci USA* **112**, 1797-1802 (2015).

44. Nisthal, A., Wang, C. Y., Ary, M. L. & Mayo, S. L. Protein stability engineering insights
revealed by domain-wide comprehensive mutagenesis. *Proc Natl Acad Sci USA* **116**, 16367-
16377 (2019).

45. Pokusaeva, V. O. *et al.* An experimental assay of the interactions of amino acids from
orthologous sequences shaping a complex fitness landscape. *PLoS Genet* **15**, e1008079
(2019).

46. Tareen, A. & Kinney, J. B. Logomaker: beautiful sequence logos in Python. *Bioinformatics*
36, 2272-2274 (2020).

47. Steeg, G. V. Non-Parametric Entropy Estimation Toolbox (NPEET).
https://www.isi.edu/~gregv/npeet.html (2014).

48. Vasicek, O. A test for normality based on sample entropy. *J Roy Stat Soc B* **38**, 54-59
(1976).

49. Kraskov, A., Stögbauer, H. & Grassberger, P. Estimating mutual information. *Phys Rev E*
69, 066138 (2004).

50. Sharpee, T., Rust, N. C. & Bialek, W. Analyzing neural responses to natural signals:
maximally informative dimensions. *Neural Comput* **16**, 223-250 (2004).

51. Efron, B. Bootstrap methods: another look at the jackknife. *Ann Stat* **7**, 1-26 (1979)..

52. Efron, B. & Tibshirani, R. Bootstrap methods for standard errors, confidence intervals, and
other measures of statistical accuracy. *Stat Sci* **1**, 54-75 (1986).