Title

MAVE-NN: learning genotype-phenotype maps from multiplex assays of variant effect

Authors

Ammar Tareen[1], Mahdi Kooshkbaghi[1], Anna Posfai[1], William T. Ireland[2,3], David M.

McCandlish[1], Justin B. Kinney[1,*]

[1] Simons Center for Quantitative Biology, Cold Spring Harbor Laboratory, Cold Spring Harbor, NY, 11724

[2] Department of Physics, California Institute of Technology, Pasadena, CA, 91125

[3] Present address: Department of Applied Physics, Harvard University, Cambridge, MA, 02134

[*] To whom correspondence should be addressed: jkinney@cshl.edu

11 **<u>Abstract</u>**

Multiplex assays of variant effect (MAVEs) are diverse techniques that include deep mutational

scanning (DMS) experiments on proteins and massively parallel reporter assays (MPRAs) on

cis-regulatory sequences. MAVEs are being rapidly adopted in many areas of biology, but a

general strategy for inferring quantitative models of genotype-phenotype (G-P) maps from

MAVE data is lacking. Here we introduce a conceptually unified approach for learning G-P maps

from MAVE datasets. Our strategy is grounded in concepts from information theory, and is

based on the view of G-P maps as a form of information compression. We also introduce

MAVE-NN, an easy-to-use Python package that implements this approach using a neural

network backend. The ability of MAVE-NN to infer diverse G-P maps—including biophysically

interpretable models—is demonstrated on DMS and MPRA data in a variety of biological

contexts. MAVE-NN thus provides a unified solution to a major outstanding need in the MAVE

community.

Main Text

Introduction

Over the last decade, the ability to quantitatively study genotype-phenotype (G-P) maps

has been revolutionized by the development of multiplex assays of variant effect (MAVEs),

which can measure molecular phenotypes for thousands to millions of genotypic variants in

parallel.[1,2] MAVE is an umbrella term that describes a diverse set of experimental methods,

three examples of which are illustrated in **Fig. 1**. Deep mutational scanning (DMS) experiments[3]

are a type of MAVE commonly used to study protein sequence-function relationships. These

assays work by linking variant proteins to their coding sequences, either directly or indirectly,

then using deep sequencing to assay which variants survive a process of activity-dependent

selection (e.g., **Fig. 1a**). Massively parallel reporter assays (MPRAs) are another major class of

MAVE, and are commonly used to study DNA or RNA sequences that regulate gene expression

at a variety of steps, including transcription, mRNA splicing, cleavage and polyadenylation,

translation, and mRNA decay.[4–7] MPRAs typically rely on either an RNA-seq readout of barcode

abundances (**Fig. 1c**) or the sorting of cells expressing a fluorescent reporter gene (**Fig. 1e**).

Most computational methods for analyzing MAVE data have focused on accurately

quantifying the activity of individual assayed sequences.[8–14] However, MAVE measurements like

enrichment ratios or cellular fluorescence levels usually cannot be interpreted as providing

direct quantification of biologically meaningful activities, due to the presence of experiment-

specific nonlinearities and noise. Moreover, MAVE data is usually incomplete, as one often

wishes to understand G-P maps over vastly larger regions of sequence space than can be

exhaustively assayed. The explicit quantitative modeling of G-P maps can address both the

indirectness and incompleteness of MAVE measurements.[1,15] The goal here is to determine a

mathematical function that, given a sequence as input, will return a quantitative value for that

sequence's molecular phenotype. Such quantitative modeling has been of great interest since

the earliest MAVE methods were developed,[16–18] but no general-use software has yet been

described for inferring G-P maps of arbitrary functional form from MAVE data.

Here we introduce a unified conceptual framework for the quantitative modeling of

MAVE data. This framework is based on the use of latent phenotype models, which assume that

each assayed sequence has a well-defined latent phenotype (specified by the G-P map), of

which the MAVE experiment provides an indirect readout (described by the measurement

process). The quantitative forms of both the G-P map and the measurement process are then

inferred from MAVE data simultaneously. We further introduce an information-theoretic

approach for separately assessing the performance of the G-P map and the measurement

process components of latent phenotype models. This strategy is implemented in an easy-to-

use open-source Python package called MAVE-NN, which is built on a TensorFlow 2 backend.[19]

In what follows, we expand on this unified MAVE modeling strategy and apply it to a diverse

array of DMS and MPRA datasets. Along the way we note the substantial advantages that

MAVE-NN provides over other MAVE modeling methods, illustrate how the capabilities of

MAVE-NN can inform experimental design going forward, and highlight new biological insights

that our quantitative modeling of MAVE data reveals.

Results

Latent phenotype modeling strategy

MAVE-NN supports the analysis of MAVE data on DNA, RNA, and protein sequences,

and can accommodate either continuous or discrete measurement values. Given a set of

sequence-measurement pairs, MAVE-NN aims to infer a probabilistic mapping from sequence

to measurement. Our primary enabling assumption, which is encoded in the structure of the

latent phenotype model (**Fig. 2a**), is that this mapping occurs in two stages. Each sequence is

first mapped to a latent phenotype by a deterministic G-P map, then this latent phenotype is

mapped to possible measurement values via a stochastic measurement process. During

training, the G-P map and measurement process are simultaneously learned by maximizing a

regularized form of likelihood. Our initial implementation of MAVE-NN assumes that latent

phenotypes are one-dimensional quantities, but multidimensional latent phenotypes are fully

compatible within this conceptual framework.[20,21]

MAVE-NN includes four types of built-in G-P maps: additive, neighbor, pairwise, and

black box. Additive G-P maps assume that each character at each position within a sequence

contributes independently to the latent phenotype. Neighbor G-P maps incorporate interactions

between nearest-neighbor characters, while pairwise G-P maps include interactions between all

pairs of characters regardless of their position. Black box G-P maps have the form of a densely

connected multilayer perceptron, the specific architecture of which can be controlled by the

user. MAVE-NN also supports custom G-P maps that can be used, e.g., to represent specific

biophysical hypotheses about the mechanisms of sequence function.

To handle both discrete and continuous measurement values, two different strategies for

modeling measurement processes are provided. Measurement process agnostic (MPA)

regression uses techniques from the biophysics literature[15,16,20,22] to analyze MAVE datasets

that report discrete measurements. Here the measurement process is represented by an

overparameterized neural network that takes the latent phenotype value as input and outputs

the probability of each possible measurement value (**Fig. 2b**). Global epistasis (GE) regression,

by contrast, leverages ideas previously developed in the evolution literature[23–26] for analyzing

datasets that contain continuous measurements (**Fig. 2c**). Here, the latent phenotype is

nonlinearly mapped to a prediction that represents the most probable measurement value. A

noise model is then used to describe the distribution of likely deviations from this prediction.

MAVE-NN supports both homoscedastic and heteroscedastic noise models based on three

different classes of probability distribution: Gaussian, Cauchy, and skewed-t. We note that the

skewed-t distribution, introduced by Jones and Faddy,[27] reduces to Gaussian and Cauchy

distributions in certain limits while also accommodating asymmetric experimental noise. **Fig. 2d**

shows an example of a GE measurement process with a heteroscedastic skewed-t noise model.

Information-theoretic measures of model performance

We further propose three distinct quantities for assessing the performance of latent

phenotype models (**Fig. 2e**). These quantities are motivated by thinking of G-P maps in terms of

information compression. In information theory, a quantity called mutual information quantifies

the amount of information that one variable encodes about another.[28,29] Unlike standard metrics

of model performance, like accuracy or R^2, mutual information can be computed between any

two types of variables (discrete, continuous, multi-dimensional, etc.). This property makes the

information-based quantities we propose below applicable to all MAVE datasets, regardless of

the specific type of experimental readout used. We note, however, that accurately estimating

mutual information and related quantities from finite data is nontrivial and that MAVE-NN uses a

variety of approaches to do this.

Intrinsic information, I_{int}, is the mutual information between the sequences and

measurements contained within a MAVE dataset. This quantity provides a benchmark against

which to compare the performance of inferred G-P maps. Predictive information, I_{pre}, is the

mutual information between MAVE measurements and the latent phenotype values predicted by

a G-P map of interest. This quantifies how well the G-P map preserves sequence-encoded

information that is determinative of experimental measurements. When evaluated on test data,

I_{pre} is bounded above by I_{int}, and equality obtains only when the latent phenotype losslessly

encodes relevant sequence-encoded information. Variational information, I_{var}, is a linear

transformation of log likelihood that provides a variational lower bound on I_{pre}.[30–32] The

difference between I_pre and I_var quantifies how accurately the inferred measurement process

matches the observed distribution of measurements and latent phenotypes (see **Supplemental**

Information).

MAVE-NN infers model parameters by maximizing a (lightly) regularized form of

likelihood. These computations are performed using the standard backpropagation-based

training algorithms provided within the TensorFlow 2 backend. With certain caveats noted (see

Methods), this optimization procedure maximizes I_pre while avoiding the costly estimates of

mutual information at each iteration that have hindered the adoption of previous mutual-

information-based modeling strategies.[16]

Application: deep mutational scanning assays

We now demonstrate the capabilities of MAVE-NN on three DMS datasets, starting with

the study of Olson et al.[33] on pairwise epistasis in protein G. Here the authors measured the

effects of all single and nearly all double mutations to residues 2-56 of the IgG binding domain.

This domain, called GB1, has long served as a model system for studying protein sequence-

function relationships. To assay the binding of GB1 variants to IgG, the authors combined

mRNA display with ultra-high-throughput DNA sequencing (**Fig. 1a**). The resulting dataset

reports log enrichment values for all 1,045 single- and 530,737 double-mutant GB1 variants

(**Fig. 1b**).

Inspired in by the work of Otwinowski et al.,[26] we used MAVE-NN to infer a latent

phenotype model comprising an additive G-P map and a GE measurement process. This

inference procedure required only about 3 minutes on a standard laptop computer

(**Supplemental Fig. S1**). **Fig. 3a** illustrates the inferred additive G-P map via the effects that

every possible single-residue mutation has on the latent phenotype. From this heatmap of

additive effects, we can immediately identify all of the critical GB1 residues, including residues

27, 31, 41, 43, and 52. We also observe that missense mutations to proline throughout the GB1

domain tend to negatively impact IgG binding, as expected due to this amino acid's exceptional

conformational rigidity. **Fig. 3b** illustrates the corresponding GE measurement process,

revealing a sigmoidal relationship between log enrichment measurements and the latent

phenotype values predicted by the G-P map. Nonlinearities like this are ubiquitous in DMS data

due to the presence of background and saturation effects. Unless they are explicitly accounted

for in one's quantitative modeling efforts, as they are here, these nonlinearities can greatly

distort the parameters of inferred G-P maps. **Fig. 3c** shows that accounting for this nonlinearity

yields predictions that correlate quite well with measurement values. Moreover, every latent

phenotype model inferred by MAVE-NN can be used as a MAVE dataset simulator (see

Methods). By analyzing simulated data generated by our inferred model for this GB1

experiment, we further observed that MAVE-NN can accurately and robustly recover the GE

nonlinearity and ground-truth G-P map parameters (**Supplementary Fig. S1**).

Fig. 3d summarizes the values of our information-theoretic metrics for model

performance. On held-out test data, we find that $I_{var} = 2.194 \pm 0.020$ bits and $I_{pre} = 2.220 \pm$

0.008 bits and. The similarity of these two values suggests that the inferred GE measurement

process, which includes a heteroscedastic skewed-t noise model, has nearly sufficient accuracy

to fully describe the distribution of residuals. We further find that 2.680 ± 0.008 bits $\leq I_{int} \leq$

3.213 ± 0.033 bits (see **Methods**), meaning that the inferred G-P map accounts for 70%-84% of

the total sequence-dependent information in the dataset. While this performance is impressive,

the additive G-P map evidently misses some relevant sequence features. This observation

motivates the more complex biophysical model for GB1 discussed later in **Results**.

The ability of MAVE-NN to deconvolve experimental nonlinearities from additive G-P

maps requires that some of the assayed sequences contain multiple mutations. This is because

such nonlinearities are inferred by reconciling the effects of single mutations with the effects

observed for combinations of two or more mutations. To investigate how many multiple-mutation

variants are required, we performed GE inference on subsets of the GB1 dataset containing all

1,045 single-mutation sequences and either 50,000, 5,000, or 500 double-mutation sequences

(see **Methods**). The shapes of the resulting GE nonlinearities are illustrated in **Figs. 3e-g**.

Remarkably, MAVE-NN is able to recover the underlying nonlinearity using only about 500

randomly selected double mutants, which represent only ~0.1% of all possible double mutants.

The analysis of simulated data also supports the ability to accurately recover ground-truth model

predictions using highly reduced datasets (**Supplemental Fig. S1**). These findings have

important implications for the design of DMS experiments: even if one only wants to determine

an additive G-P map, including a modest number of multiple-mutation sequences in the assayed

library is often advisable because it may allow the removal of artifactual nonlinearities.

To test the capabilities of MAVE-NN on less complete DMS datasets, we analyzed

recent experiments on amyloid beta (Aβ)[34] and TDP-43,[35] both of which exhibit aggregation

behavior in the context of neurodegenerative diseases. Like with GB1, the variant libraries used

in both experiments included a substantial number of multiple-mutation sequences: 499 single-

and 15,567 double-mutation sequences for Aβ; 1,266 single- and 56,730 double-mutation

sequences for TDP-43. But unlike with GB1, these datasets are highly incomplete due to the

use of mutagenic PCR for variant library creation.

We used MAVE-NN to infer additive G-P maps from these two datasets, adopting the

same type of latent phenotype model used for GB1. **Fig. 4a** illustrates the additive G-P map

inferred from aggregation measurements of Aβ variants. In agreement with the original study,

we see that most amino acid mutations between positions 30-40 have a negative effect on

nucleation, suggesting that this region plays a major role in nucleation behavior. **Fig. 4b** shows

the corresponding measurement process. Even though these data are much sparser than the

GB1 data, the inferred model performs well on held-out test data ($I_{\mathrm{var}} = 1.147 \pm 0.043$ bits,

$I_{\mathrm{pre}} = 1.254 \pm 0.024$ bits, $R^2 = 0.793 \pm 0.071$). Similarly, **Figs. 4c-d** show the G-P map

parameters and GE measurement process inferred from toxicity measurements of TDP-43

variants, revealing among other things the toxicity-determining hot-spot observed by Bolognesi

et al.[35] at positions 310-340. The resulting latent phenotype model performs well on held-out

test data ($I_{\mathrm{var}} = 1.806 \pm 0.018$ bits, $I_{\mathrm{pre}} = 2.011 \pm 0.019$ bits, $R^2 = 0.912 \pm 0.052$).

Application: a massively parallel splicing assay

Exon/intron boundaries are defined by 5´ splice sites (5´ss), which bind the U1 snRNP

during the initial stages of spliceosome assembly. To investigate how 5´ss sequence

quantitatively controls alternative mRNA splicing, Wong et al.[36] used a massively parallel

splicing assay (MPSA) to measure percent-spliced-in (PSI) values for nearly all 32,768 possible

5´ss of the form NNN/GYNNNN in three different genetic contexts (**Fig. 1c,d**). Applying MAVE-

NN to data from the BRCA2 exon 17 context, we inferred four different types of G-P maps:

additive, neighbor, pairwise, and black box. As with GB1, these G-P maps were each inferred

using GE regression with a heteroscedastic skewed-t noise model. For comparison, we also

inferred an additive G-P map using the epistasis package of Sailer and Harms.[25]

Fig. 5a compares the performance of these G-P map models on held-out test data, while

Figs. 5b-d illustrate the corresponding inferred measurement processes. We observe that the

additive G-P map inferred using the epistasis package[25] exhibits less predictive information

($I_{\mathrm{pre}} = 0.220 \pm 0.012$ bits) than the additive G-P map found using MAVE-NN ($P = 0.007$, two-

sided z-test). This is likely because the epistasis package estimates the parameters of the

additive G-P map prior to estimating the GE nonlinearity. We also note that, while the epistasis

package provides a variety of options for modeling the GE nonlinearity, none of these options

appear to work as well as our mixture-of-sigmoids approach (compare **Figs. 5b,c**). This finding

again demonstrates that the accurate inference of G-P maps requires the explicit and

simultaneous modeling of experimental nonlinearities.

We also observe that increasingly complex G-P maps exhibit increased accuracy. For

example, the additive G-P map gives $I_{\mathrm{pre}} = 0.262 \pm 0.011$ bits, whereas the pairwise G-P map

(**Figs. 5e,f**) attains $I_{\mathrm{pre}} = 0.367 \pm 0.015$ bits. We note that the parameters of the pairwise G-P

map appear to be very precisely determined, as MAVE-NN was able to accurately recover

ground-truth parameters from simulated datasets of the same size (**Supplemental Fig. S2**).

The black box G-P map, which is comprised of 5 densely connected hidden layers of 10 nodes

each, performed the best of all four G-P maps, achieving $I_{\mathrm{pre}} = 0.489 \pm 0.012$ bits. Remarkably,

this last predictive information value exceeds the lower bound of $I_{\mathrm{int}} \geq 0.461 \pm 0.007$ bits, which

was estimated from replicate experiments (see **Methods**). We thus conclude that pairwise

interaction models are not flexible enough to fully account for how 5´ss sequences control

splicing. More generally, these results underscore the need for software that is capable of

inferring and assessing a variety of different G-P maps through a uniform interface.

Application: biophysically interpretable G-P maps

Biophysical models, unlike the phenomenological models considered thus far, have

mathematical structures that reflect specific hypotheses about how sequence-dependent

interactions between macromolecules mechanistically define G-P maps. Thermodynamic

models, which rely on a quasi-equilibrium assumption, are the most commonly used type of

biophysical model.[37–39] Previous studies have shown that precise thermodynamic models can

be inferred from MAVE datasets,[16] but no software intended use by the broader MAVE

community has yet been developed for doing this. MAVE-NN meets this need by enabling the

inference of custom G-P maps. We now demonstrate this biophysical modeling capability in the

contexts of protein-ligand binding (using DMS data; **Fig. 1a**) and bacterial transcriptional

regulation (using sort-seq MPRA data; **Fig. 1e**).

Otwinowski[40] showed that a three-state thermodynamic G-P map (**Fig. 6a**), one that

accounts for GB1 folding energy in addition to GB1-IgG binding energy,[41] can explain the DMS

data of Olson et al.[33] better than a simple additive G-P map does. This biophysical model

subsequently received impressive confirmation in the work of Nisthal et al.,[42] who measured the

thermostability of 812 single-mutation GB1 variants. We tested the ability of MAVE-NN to

recover the same type of thermodynamic model that Otwinowski had inferred using custom

analysis scripts. Our analysis yielded a G-P map with significantly improved performance on the

data of Olson et al. ($I_{\mathrm{var}} = 2.353 \pm 0.012$ bits, $I_{\mathrm{pre}} = 2.373 \pm 0.009$ bits, $R^2 = 0.948 \pm 0.002$)

relative to the additive G-P map of **Fig. 3**. **Fig. 6b** shows the two inferred energy matrices that

respectively describe the effects of every possible single-residue mutation on the Gibbs free

energies of protein folding and protein-ligand binding. The folding energy predictions our model

also correlate as well with the data of Nisthal et al. ($R^2 = 0.548 \pm 0.050$) as the predictions of

Otwinowski's model does ($R^2 = 0.517 \pm 0.058$). This demonstrates that MAVE-NN can infer

accurate and interpretable quantitative models of protein biophysics.

To test MAVE-NN's ability to infer thermodynamic models of transcriptional regulation,

we first re-analyzed the MPRA data of Kinney et al.,[16] in which random mutations to a 75 bp

region of the *Escherichia coli lac* promoter were assayed. This promoter region binds two

regulatory proteins, σ^{70} RNA polymerase (RNAP) and the transcription factor CRP. As in Kinney

et al.,[16] we proposed a four-state thermodynamic model that quantitatively explains how

promoter sequences control transcription rate (**Fig. 6c**). The parameters of this G-P map include

the Gibbs free energy of interaction between CRP and RNAP, as well as energy matrices that

describe the CRP-DNA and RNAP-DNA interaction energies. Because the sort-seq MPRA of

Kinney et al. yielded discrete measurement values (**Figs. 1e,f**), we used an MPA measurement

process in our latent phenotype model (**Fig. 6d**). The biophysical parameter values we thus

inferred (**Fig. 6e**) largely match those of Kinney et al., but were obtained far more rapidly (in ~10

min versus multiple days) thanks to the use of stochastic gradient descent rather than

Metropolis Monte Carlo.

Next we analyzed sort-seq MPRA data obtained by Belliveau et al.[43] for the *xylE*

promoter, which had no regulatory annotation prior to that study and for which no biophysical

model had yet been developed. Based on their MPRA data, as well as follow-up mass

spectrometry experiments, Belliveau et al. proposed that *xylE* is regulated by RNAP, CRP, and

the locus-specific regulator XylR. These findings motivated us to propose and train an eight-

state thermodynamic model describing how interactions between these three regulatory proteins

might control *xylE* expression (**Fig. 6f**). The resulting quantitative model includes energy matrix

descriptions for RNAP, CRP, and XylR binding to DNA, as well as Gibbs free energy values for

the CRP-XylR and XylR-RNAP interactions (**Fig. 6g)**. From this model we see that XylR

activates RNAP through what appears to be a class II activation mechanism,[44] as energetic

contributions from the -35 region of the RNAP binding site are markedly reduced in the *xylE*

context relative to the *lac* context (**Fig. 6e**). We also see that CRP—a homodimer with dyadic

symmetry—binds its site with remarkable asymmetry (again, compare to **Fig. 6e**). The

biophysical factors that determine whether symmetric transcription factors like CRP interact with

DNA in symmetric or asymmetric poses are poorly understood, and represent just one avenue

of investigation opened up by the capabilities of MAVE-NN. More generally, these results

provide a proof-of-principle demonstration of how MAVE-NN can be used, together with MPRA

experiments, to establish biophysical models for previously uncharacterized gene regulatory

sequences.

Discussion

In this work we have presented a unified strategy for inferring quantitative models of G-P

maps from diverse MAVE datasets. At the core of our approach is the conceptualization of G-P

maps as a form of information compression, i.e., that the G-P map first compresses an input

sequence into a latent phenotype value, which the MAVE then reads out indirectly via a noisy

nonlinear measurement process. By explicitly modeling this measurement process, one can

remove potentially confounding effects from the G-P map, as well as accommodate diverse

experimental designs. We have also introduced three information-theoretic metrics for

assessing the performance of the resulting models. These capabilities have been implemented

within an easy-to-use Python package called MAVE-NN.

We have demonstrated the capabilities of MAVE-NN in diverse biological contexts,

including in the analysis of both DMS and MPRA data. We have also demonstrated the superior

performance of MAVE-NN relative to the epistasis package of Sailer and Harms.[25] Along the

way, we observed that MAVE-NN can deconvolve experimental nonlinearities from additive G-P

maps when a relatively small number of sequences containing multiple mutations are included

in the assayed libraries. This capability provides a compelling reason for experimentalists to

include such sequences in their MAVE libraries, even if they are primarily interested in the

effects of single mutations. Finally, we showed how MAVE-NN can learn biophysically

interpretable G-P maps from both DMS and MPRA data.

Applying MAVE-NN to the MPSA data of Wong et al.,[36] we discovered that pairwise

interaction models are not sufficient to describe how 5´ss sequences govern alternative mRNA

splicing, and that higher-order epistatic interactions are needed to describe this critical aspect of

eukaryotic biology. We also inferred the first biophysical model for transcriptional regulation by

the *xylE* promoter. This biophysical model reveals that the well-studied transcription factor CRP

binds its target site with surprising asymmetry *in vivo*, an intriguing phenomenon about which

much remains to be learned.

316   MAVE-NN thus fills a critical need in the MAVE community, providing user-friendly

317 software capable of learning quantitative models of G-P maps from diverse MAVE datasets.

318 MAVE-NN has a streamlined user interface, is thoroughly tested, and is readily installed from

319 PyPI by executing "pip install mavenn" at the command line. Comprehensive documentation,

320 worked examples, and step-by-step tutorials are available at http://mavenn.readthedocs.io.

321 **Acknowledgements**. This work was supported by NIH grant 1R35GM133777 (awarded to

322 JBK), NIH Grant 1R35GM133613 (awarded to DMM), an Alfred P. Sloan Research Fellowship

323 (awarded to DMM), a grant from the CSHL/Northwell Health partnership, and funding from the

324 Simons Center for Quantitative Biology at Cold Spring Harbor Laboratory.

325 **Author contributions**. AT, WTI, DMM, and JBK conceived the project. AT and JBK wrote the

326 software with assistance from AP and MK. WTI and JBK wrote a preliminary version of the

327 software. AT, MK, and JBK performed the data analysis. AT, DMM, and JBK wrote the

328 manuscript with contributions from MK and AP.

329 **Conflicts of interest**. The authors declare that they have no known conflicts of interest.

Figure 1. Three example MAVEs. (**a**) The DMS assay of Olson et al..[33] A library of variant GB1 proteins were covalently linked to their coding mRNAs using mRNA display. Functional GB1 proteins were then enriched using IgG beads, and deep sequencing was used to determine an enrichment ratio for each GB1 variant. (**b**) The resulting DMS dataset consists of variant protein sequences and their corresponding log enrichment values. (**c**) The MPSA of Wong et al..[36] A library of 3-exon minigenes was constructed from exons 16, 17, and 18 of *BRCA2*, with each minigene having a variant 5´ss at exon 17 and a random 20 nt barcode in the 3' UTR. This library was transfected into HeLa cells, and deep sequencing was used to quantify mRNA isoform abundance. (**d**) The resulting MPSA dataset comprises variant 5´ss with (noisy) PSI values. (**e**) The sort-seq MPRA of Kinney et al..[16] A plasmid library was generated in which randomly mutagenized versions of the *Escherichia coli lac* promoter drove the expression of GFP. Cells carrying these plasmids were sorted using FACS, and the variant promoters in each bin of sorted cells as well as the initial library were sequenced. (**f**) The resulting dataset comprises a list of variant promoter sequences, as well as a matrix of counts for each variant in each FACS bin. MAVE: multiplex assay of variant effect; DMS: deep

345   mutational scanning; MPSA: massively parallel splicing assay; 5´ss: 5´ splice site(s); PSI: percent spliced in; GFP:

346   green fluorescent protein; FACS: fluorescence-activated cell sorting.

Figure 2. MAVE-NN quantitative modeling strategy. (**a**) Structure of latent phenotype models. A G-P map $f(x)$ maps each sequence x to a latent phenotype ϕ, after which a measurement process $p(y|\phi)$ determines the measurement y. (**b**) Example of an MPA measurement process inferred from the sort-seq MPRA data of Kinney et al..[16] MPA measurement processes are used when y values are discrete. (**c**) Structure of a GE regression model, which is used when y is continuous. A GE measurement process assumes that the mode of $p(y|\phi)$, called the prediction $\hat{y}$, is given by a nonlinear function $g(\phi)$, and the scatter about this mode is described by a noise model $p(y|\hat{y})$. (**d**) Example of a GE measurement process inferred from the DMS data of Olson et al..[33] Shown is the nonlinearity, the 68% CI, and the 95% CI. (**e**) Information-theoretic quantities used to assess model performance. Intrinsic information, I_{int}, is the mutual information between sequences x and measurements y. Predictive information, I_{pre}, is the mutual information between measurements y and the latent phenotype values ϕ assigned by a model. Variational information, I_{var}, is a linear transformation of log likelihood. The inequality $I_{\text{int}} \geq I_{\text{pre}} \geq I_{\text{var}}$ always holds on test data (modulo finite data uncertainties), with $I_{\text{int}} = I_{\text{pre}}$ when the G-P map is correct, and $I_{\text{pre}} = I_{\text{var}}$ when the measurement process correctly describes the distribution of y conditioned on ϕ. G-P: genotype-phenotype; MPA: measurement process agnostic; GE: global epistasis; CI: confidence interval.

Figure 3. Analysis of DMS data for protein GB1. MAVE-NN was used to infer a latent phenotype model, consisting of

an additive G-P map and a GE measurement process having a heteroskedastic skewed-t noise model, from the DMS

data of Olson et al..[33] All 1,045 single variants and 530,737 pairwise variants reported for positions 2 to 56 of the GB1

domain were analyzed. Data were split 80:10:10 into training, validation, and test sets. (**a**) The G-P map parameters

inferred from all pairwise variants. Gray dots indicate wildtype residues. Amino acids are ordered as in Olson et al..[33]

(**b**) GE plot showing measurements versus predicted latent phenotype values for 5,000 randomly selected test-set

sequences (blue dots), alongside the inferred nonlinearity (solid orange line) and the 95% CI (dashed lines) of the

noise model. Gray line indicates the latent phenotype value of the wildtype sequence. (**c**) Measurements plotted

against $\hat{y}$ predictions for these same sequences. Dashed lines indicate the 95% CI of the noise model. Gray line

indicates the wildtype sequence $\hat{y}$. (**d**) Corresponding information metrics computed during model training (using

training data) or for the final model (using test data); uncertainties in these estimates are roughly the width of the

plotted lines. Gray shaded area indicates allowed values for intrinsic information based on upper and lower bounds

estimated as described in **Methods**. (**e-g**) Test set predictions (blue dots) and GE nonlinearities (orange lines) for

models trained using subsets of the GB1 data containing all single mutants and 50,000 (**e**), 5,000 (**f**), or 500 (**g**)

double mutants. The GE nonlinearity from panel **b** is shown for reference (yellow-green lines). Uncertainties reflect

standard errors. GE: global epistasis; G-P: genotype-phenotype; CI: confidence interval.

Figure 4. Analysis of DMS data for Aβ and TDP-43. (**a,b**) Seuma et al.[34] measured nucleation scores for 499 single mutants and 15,567 double mutants of Aβ. These data were used to train a latent phenotype model comprising (**a**) an additive G-P map and (**b**) a GE measurement process with a heteroskedastic skewed-t noise model. (**c,d**) Bolognesi et al.[35] measured toxicity scores for 1,266 single mutants and 56,730 double mutants of TDP-43. The resulting data were used to train (**c**) an additive G-P map and (**d**) a GE measurement process of the same form as in panel **b**. In both cases, data were split 90:5:5 into training, validation, and test sets. In (**a,c**), gray dots indicate the wildtype sequence, amino acids are ordered as in the original publications, and * indicates a stop codon. In (**b,d**), blue dots indicate latent phenotype values versus measurements for held-out test data, gray line indicates the latent phenotype value of the wildtype sequence, solid orange line indicates the GE nonlinearity, and dashed orange lines indicate a corresponding 95% CI for the inferred noise model. Values for I_{var}, I_{pre}, and R^2 (between y and $\hat{y}$) are also shown. Uncertainties reflect standard errors. **Supplemental Fig. S3** shows measurements plotted against the $\hat{y}$ predictions of these models. Aβ: amyloid beta; TDP-43: TAR DNA-binding protein 43; G-P: genotype-phenotype; GE: global epistasis; CI: confidence interval.

Figure 5. Analysis of MPSA data from Wong et al..[36] This dataset reports PSI values, measured in the *BRCA2* exon

17 context, for nearly all 32,768 variants 5´ss of the form NNN/GYNNNN. Data were split 60:20:20 into training,

validation, and test sets. Latent phenotype models with one of four types of G-P map (additive, neighbor, pairwise, or

black box), as well as a GE measurement process with a heteroscedastic skewed-t noise model, were inferred. The

epistasis package of Sailer and Harms[25] was also used to infer an additive G-P map and GE nonlinearity. (**a**)

Performance of trained models as quantified by I_var and I_pre, computed on test data. The lower bound on I_int was

estimated from experimental replicates (see **Methods**). p-value reflects a two-sided z-test. I_var was not computed for

the additive (epistasis package) model because that package does not infer an explicit noise model. (**b-d**)

Measurement values versus latent phenotype values, computed on test data, using the additive (epistasis package)

model (**b**), the additive model (**c**), and the pairwise model (**d**). The corresponding GE measurement processes are

also shown. (**e**) Sequence logo[45] illustrating the additive effects component of the pairwise G-P map. Dashed line

indicates the exon/intron boundary. G at +1 serves as a placeholder because no other bases were assayed at this

position. Only values for U and C at +2 were inferred. (**f**) Heatmap showing the pairwise effects component of the

pairwise G-P map. White diagonals correspond to unobserved bases. Error bars indicate standard errors. MPSA:

massively parallel splicing assay; PSI: percent spliced in; G-P: genotype-phenotype; GE: global epistasis.

Figure 6. Biophysical models inferred from DMS and MPRA data. (**a**) Thermodynamic model for IgG binding by GB1.

This model comprises three GB1 microstates (unfolded, folded-unbound, and folded-bound). The Gibbs free energies

of folding (ΔG_F) and binding (ΔG_B) are computed from sequence using additive models called energy matrices. The

latent phenotype is given by the fraction of time GB1 is in the folded-bound state. (**b**) The $\Delta\Delta G$ parameters of the

energy matrices for folding and binding, inferred from the data of Olson et al.[33] using GE regression. **Supplemental**

Fig. S5 plots folding energy predictions against the measurements of Nisthal et al..[42] (**c**) A four-state thermodynamic

model for transcriptional activation at the *E. coli lac* promoter. The Gibbs free energies of RNAP-DNA binding (ΔG_R)

and CRP-DNA binding (ΔG_C) are computed using energy matrices, whereas the CRP-RNAP interaction energy ΔG_I is

a scalar. The latent phenotype is the fraction of time a promoter is bound by RNAP. (**d,e**) The latent phenotype model

inferred from the sort-seq MPRA of Kinney et al.,[16] including both the MPA measurement process (**d**) and the

parameters of the thermodynamic G-P map (**e**). (**f**) An eight-state thermodynamic model for transcriptional activity at

the *xylE* promoter. (**g**) Corresponding G-P map parameters inferred from the sort-seq MPRA data of Belliveau et al..[43]

These parameters include energy matrices describing the CRP-DNA, RNAP-DNA, and XylR-DNA interactions, as

well as scalar values for the CRP-XylR and XylR-RNAP interaction free energies. Supplemental **Fig. S4** provides

detailed definitions of the thermodynamic models in panels **a,c,f**. In panels **e,g**, sequence logos were generated

using Logomaker,[45] and standard errors for protein-protein interactions energies were determined by analyzing

simulated data. GE: global epistasis. RNAP: RNA polymerase. MPA: measurement-process agnostic. G-P: genotype-

phenotype.

Online Methods

Notation

We represent each MAVE dataset as a set of N observations, $\{(x_n, y_n)\}_{n=0}^{N-1}$, where each

observation consists of a sequence x_n and a measurement y_n. Here, y_n can be either a

continuous real-valued number, or a nonnegative integer representing the "bin" in which the nth

sequence was found. Note that, in this representation the same sequence x can be observed

multiple times, potentially with different values for y due to experimental noise.

G-P maps

We assume that all sequences have the same length L, and that at each of the L

positions in each sequence there is one of C possible characters. MAVE-NN represents

sequences using a vector of one-hot encoded features of the form

446
$$x_{l:c} = \begin{cases} 1 & \text{if character } c \text{ occurs at position } l \\ 0 & \text{otherwise} \end{cases}, \tag{1}$$

where $l = 0, 1, \ldots, L-1$ indexes positions within the sequence, and c indexes the C distinct

characters. MAVE-NN supports built-in alphabets for DNA, RNA and protein (with or without

stop codons), as well as user-defined sequence alphabets.

We assume that the latent phenotype is given by a linear function $\phi(x; \theta)$ that depends

on a set of G-P map parameters θ. As mentioned in the main text, MAVE-NN supports four

types of G-P map models, all of which can be inferred using either GE regression or MPA

regression. The additive model is given by,

454
$$\phi_{\text{additive}}(x; \theta) = \theta_0 + \sum_{l=0}^{L-1} \sum_c \theta_{l:c} \, x_{l:c}, \tag{2}$$

455 and thus each position in x contributes independently to the latent phenotype. The neighbor

456 model is given by,

$$\phi_{\text{neighbor}}(x;\theta) = \theta_0 + \sum_{l=0}^{L-1}\sum_{c}\theta_{l:c}\, x_{l:c} + \sum_{l=0}^{L-2}\sum_{c,c'}\theta_{l:c,l+1:c'}\, x_{l:c}x_{l+1:c'}\,, \qquad (3)$$

458 and further accounts for potential epistatic interactions between neighboring positions. The

459 pairwise model is given by,

$$\phi_{\text{pairwise}}(x;\theta) = \theta_0 + \sum_{l=0}^{L-1}\sum_{c}\theta_{l:c}\, x_{l:c} + \sum_{l=0}^{L-2}\sum_{l'=l+1}^{L-1}\sum_{c,c'}\theta_{l:c,l':c'}\, x_{l:c}x_{l':c'}\,, \qquad (4)$$

and includes interactions between all pairs of positions. Note our convention of requiring $l' > l$ in

the pairwise parameters $\theta_{l:c,l':c'}$.

Unlike these three parametric models, the black box G-P map does not have a fixed

functional form. Rather, it is given by a multilayer perceptron that takes a vector of sequence

features (additive, neighbor, or pairwise) as input, contains multiple fully-connected hidden

layers with nonlinear activations, and has a single node output with a linear activation. Users are

able to specify the number of hidden layers, the number of nodes in each hidden layer, and the

activation function used by these nodes.

MAVE-NN further supports custom G-P maps that users can define by subclassing the G-

P map base class. These G-P maps can have arbitrary functional form, e.g., representing specific

biophysical hypotheses of sequence function. This feature of MAVE-NN is showcased in the

analyses of **Fig. 6**.

Gauge modes and diffeomorphic modes

G-P maps typically have non-identifiable degrees of freedom that must be fixed, i.e.,

pinned down, before the values of individual parameters can be meaningfully interpreted or

compared between models. These degrees of freedom come in two flavors: gauge modes and

diffeomorphic modes. Gauge modes are changes to θ that do not alter the values of the latent

phenotype ϕ. Diffeomorphic modes[15,20] are changes to θ that do alter ϕ, but do so in ways that

can be undone by transformations of the measurement process $p(y|\phi)$. As shown by Kinney

and Atwal,[15,20] the diffeomorphic modes of linear G-P maps like those considered here will in

general correspond to affine transformations of ϕ, although additional unconstrained modes can

occur in special situations.

MAVE-NN fixes both gauge modes and diffeomorphic modes of inferred models (except

when using custom G-P maps). The diffeomorphic modes of G-P maps are fixed by

transforming θ via

$$\theta_0 \to \theta_0 - a \,, \tag{5}$$

and then

$$\theta \to \frac{\theta}{b}, \tag{6}$$

where $a = \mathrm{mean}(\{\phi_n\})$ and $b = \mathrm{std}(\{\phi_n\})$ are the mean and standard deviation of ϕ values

computed on the training data. This produces a corresponding change in latent phenotype

values $\phi \to (\phi - a)/b$. To avoid altering likelihood values, MAVE-NN makes a corresponding

transformation to the measurement process $p(y|\phi)$. In GE regression this is done by adjusting

the GE nonlinearity via

$$g(\phi) \to g(a + b\phi) \,, \tag{7}$$

while keeping the noise model $p(y|\hat{y})$ fixed. In MPA regression MAVE-NN transforms the full

measurement process via

497
$$p(y|\phi) \rightarrow p(y|a + b\phi) \, . \tag{8}$$

For the three parametric G-P maps, gauge modes are fixed using what we call the

"hierarchical gauge." Here, the parameters θ are adjusted so that the lower-order terms in

$\phi(x; \theta)$ account for the highest possible fraction of variance in ϕ. This procedure requires a

probability distribution on sequence space with respect to which these variances are computed.

MAVE-NN assumes that such distributions factorize by position, and can thus be represented

by a probability matrix with elements $p_{l:c}$, denoting the probability of character c at position l.

MAVE-NN provides three built-in choices for this distribution: uniform, empirical, or wildtype.

The corresponding values of $p_{l:c}$ are given by

506
$$p_{l:c} = \begin{cases} 1/C & \text{for uniform} \\ n_{l:c}/N & \text{for empirical} \\ x^{\text{wt}}_{l:c} & \text{for wildtype} \end{cases} , \tag{9}$$

where $n_{l:c}$ denotes the number of sequences (out of N total) that have character c at position l,

and $x^{\text{wt}}_{l:c}$ is the one-hot encoding of a user-specified wildtype sequence. In particular, the

wildtype gauge was used for illustrating the additive G-P maps in **Fig. 3** and **Fig. 4**, while the

uniform gauge was used for illustrating the pairwise G-P map in **Fig. 5** and the energy matrices

in **Fig. 6**. After a sequence distribution is chosen, MAVE-NN fixes the gauge of the pairwise G-P

map by transforming

513
$$\begin{aligned} \theta_0 \quad \rightarrow \quad & \theta_0 \\ & + \sum_l \sum_{c'} \theta_{l:c'} \, p_{l:c'} \\ & + \sum_l \sum_{l'>l} \sum_{c,c'} \theta_{l:c,l':c'} \, p_{l:c} \, p_{l':c'} \, , \end{aligned} \tag{10}$$

$$
\begin{aligned}
\theta_{l:c} \quad \rightarrow \quad & \theta_{l:c} \\
& - \sum_{c'} \theta_{l:c'} \, p_{l:c'} \\
& + \sum_{l'>l} \sum_{c'} \theta_{l:c,l':c'} \, p_{l':c'} \\
& + \sum_{l'<l} \sum_{c'} \theta_{l':c',l:c} \, p_{l':c'} \\
& - \sum_{l'>l} \sum_{c',c''} \theta_{l:c',l':c''} \, p_{l:c'} \, p_{l':c''} \\
& - \sum_{l'<l} \sum_{c',c''} \theta_{l':c'',l':c'} \, p_{l:c'} \, p_{l':c''} \, ,
\end{aligned}
\tag{11}
$$

515 and

$$
\begin{aligned}
\theta_{l:c,l':c'} \quad \rightarrow \quad & \theta_{l:c,l':c'} \\
& - \sum_{c''} \theta_{l:c'',l':c'} \, p_{l:c''} \\
& - \sum_{c''} \theta_{l:c,l':c''} \, p_{l':c''} \\
& + \sum_{c'',c'''} \theta_{l:c'',l':c'''} \, p_{l:c''} \, p_{l':c'''} \, .
\end{aligned}
\tag{12}
$$

This transformation is also used for the additive and neighbor G-P maps, but with $\theta_{l:c,l':c'} = 0$ for

all l, l' (additive) or whenever $l' \neq l + 1$ (neighbor).

GE nonlinearities

GE models assume that each measurement y is a nonlinear function of the latent

phenotype $g(\phi)$ plus some noise. In MAVE-NN, this nonlinearity is represented as a sum of

tanh sigmoids:

523
$$
g(\phi; \alpha) = a + \sum_{k=0}^{K-1} b_k \tanh(c_k \phi + d_k) .
\tag{13}
$$

Here, K specifies the number of hidden nodes contributing to the sum, and $\alpha = \{a, b_k, c_k, d_k\}$ are

trainable parameters. We note that this mathematical form is an example of the bottleneck

architecture previously used by[21,24] for modeling GE nonlinearities. By default, MAVE-NN

constrains $g(\phi; \alpha)$ to be monotonic in ϕ by requiring all $b_k \geq 0$ and $c_k \geq 0$, but this constraint

can be relaxed.

GE noise models

MAVE-NN supports three types of GE noise model: Gaussian, Cauchy, and skew-t.

These all support the analytic computation of quantiles and confidence intervals, as well as the

rapid sampling of simulated measurement values. The Gaussian noise model is given by

533
$$p_{\text{gauss}}(y|\hat{y}; s) = \frac{1}{\sqrt{2\pi s^2}} \exp\left[-\frac{(y - \hat{y})^2}{2s^2}\right], \tag{14}$$

534 where s denotes the standard deviation. Importantly, MAVE-NN allows this noise model to be

535 heteroskedastic by representing s as an exponentiated polynomial in $\hat{y}$, i.e.,

536
$$s(\hat{y}) = \exp\left[\sum_{k=0}^{K} a_k\, \hat{y}^k\right], \tag{15}$$

537 where K is the order of the polynomial and $\{a_k\}$ are trainable parameters. The user has the

538 option to set K, and setting $K = 0$ renders this noise model homoscedastic. Quantiles are

539 computed using $y_q = \hat{y} + s\sqrt{2}\,\text{erf}^{-1}(2q - 1)$ for user-specified values of $q \in [0,1]$. Similarly, the

540 Cauchy noise model is given by

541
$$p_{\text{cauchy}}(y|\hat{y}; s) = \left[\pi s\left(1 + \frac{(y - \hat{y})^2}{s^2}\right)\right]^{-1}, \tag{16}$$

542 where the scale parameter s is an exponentiated K'th order polynomial in $\hat{y}$, and quantiles are

543 computed using $y_q = \hat{y} + s\tan\left[\pi(q - \frac{1}{2})\right]$.

544   The skew-t noise model is of the form described by Jones and Faddy,[27] and is given by

545
$$p_{\text{skewt}}(y|\hat{y}; s, a, b) = s^{-1} f(t; a, b) ,$$
(17)

546   where

547
$$t = t^* + \frac{y - \hat{y}}{s}, \quad t^* = \frac{(a - b)\sqrt{a + b}}{\sqrt{2a + 1}\sqrt{2b + 1}} ,$$
(18)

548   and

549
$$f(t; a, b) = \frac{2^{1-a-b}}{\sqrt{a + b}} \frac{\Gamma(a + b)}{\Gamma(a)\Gamma(b)} \left[1 + \frac{t}{\sqrt{a + b + t^2}}\right]^{a+\frac{1}{2}}$$
$$\times \left[1 - \frac{t}{\sqrt{a + b + t^2}}\right]^{b+\frac{1}{2}} .$$
(19)

550   Note that the t statistic here is an affine function of y chosen so that the distribution's mode

551   (corresponding to t^*) is positioned at $\hat{y}$. The three parameters of this noise model, $\{s, a, b\}$, are

552   each represented using K-th order exponentiated polynomials with trainable coefficients.

553   Quantiles are computed using

554
$$y_q = \hat{y} + (t_q - t^*)s ,$$
(20)

555   where

556
$$t_q = \frac{(2x_q - 1)\sqrt{a + b}}{\sqrt{1 - (2x_q - 1)^2}}, \quad x_q = I_q^{-1}(a, b) ,$$
(21)

and I^{-1} denotes the inverse of the regularized incomplete Beta function $I_x(a, b)$.

MPA measurement process

In MPA regression, MAVE-NN directly models the measurement process $p(y|\phi)$. At

present, MAVE-NN only supports MPA regression for discrete values of y indexed using

nonnegative integers. MAVE-NN supports two alternative forms of input for MPA regression.

One is a set of sequence-measurement pairs $\{(x_n, y_n)\}_{n=0}^{N-1}$, where N is the total number of

reads, $\{x_n\}$ is a set of (typically) non-unique sequences, each $y_n \in \{0, 1, ..., Y-1\}$ is a bin

number, and Y is the total number of bins. The other is a set of sequence-count-vector pairs

$\{(x_m, c_m)\}_{m=0}^{M-1}$, where M is the total number of unique sequences and $c_m = (c_{m0}, c_{m1}, ..., c_{m(Y-1)})$

is a vector that lists the number of times c_{my} that the sequence x_m was observed in each bin y.

MPA measurement processes are represented as multilayer perceptron with one hidden layer

(having tanh activations) and a softmax output layer. Specifically,

569
$$p(y|\phi) = \frac{w_y(\phi)}{\sum_{y'} w_{y'}(\phi)} , \tag{22}$$

570   where

571
$$w_y(\phi) = \exp\left[a_y + \sum_{k=0}^{K-1} b_{yk} \tanh(c_{yk}\phi + d_{yk})\right] \tag{23}$$

and K is the number of hidden nodes per value of y. The trainable parameters of this

measurement process are $\eta = \{a_y, b_{yk}, c_{yk}, d_{yk}\}$.

Loss function

Let θ denote the G-P map parameters, and η denote the parameters of the

measurement process. MAVE-NN optimizes these parameters using stochastic gradient

descent on a loss function given by

578
$$\mathcal{L} = \mathcal{L}_{\text{like}} + \mathcal{L}_{\text{reg}} , \tag{24}$$

579   where $\mathcal{L}_{\text{like}}$ is the negative log likelihood of the model, given by

580
$$\mathcal{L}_{\text{like}}[\theta, \eta] = -\sum_{n=0}^{N-1} \log\left[p(y_n|\phi_n; \eta)\right] \tag{25}$$

where $\phi_n = \phi(x_n; \theta)$, and $\mathcal{L}_{\text{reg}}$ provides for regularization of the model parameters.

In the context of GE regression, we can write $\eta = (\alpha, \beta)$ where α represents the

parameters of the GE nonlinearity $g(\phi; \alpha)$, and β denotes the parameters of the noise model

$p(y|\hat{y}; \beta)$. The likelihood contribution from each observation n then becomes $p(y_n|\phi_n; \eta) =$

$p(y_n|\hat{y}_n; \beta)$ where $\hat{y}_n = g(\phi_n; \alpha)$. In the context of MPA regression with a dataset of the form

$\{(x_m, c_m)\}_{m=0}^{M-1}$, the loss function simplifies to

$$\mathcal{L}_{\text{like}}[\theta, \eta] \;=\; -\sum_{m=0}^{M-1}\sum_{y=0}^{Y-1} c_{my}\log[p(y|\phi_m; \eta)] \tag{26}$$

588   where $\phi_m = \phi(x_m; \theta)$. For the regularization term, MAVE-NN uses an L_2 penalty of the form

$$\mathcal{L}_{\text{reg}}[\theta, \eta] = \lambda_\theta |\theta|^2 + \lambda_\eta |\eta|^2 , \tag{27}$$

where the user-adjusted parameters λ_θ and λ_η respectively control the strength of regularization

for the G-P map and measurement process parameters.

Predictive information

In what follows, we use $p_{\text{model}}(y|\phi)$ to denote a measurement process inferred by

MAVE-NN, whereas $p_{\text{true}}(y|\phi)$ denotes the empirical conditional distribution of y and ϕ values

that would be observed in the limit of infinite test data.

Predictive information $I_{\text{pre}} = I[y; \phi]$, where $I[\cdot; \cdot]$ represents mutual information computed

on data not used for training (i.e., a held-out test set or data from a different experiment), I_{pre}

provides a measure of how strongly a G-P map predicts experimental measurements.

Importantly, this quantity does not depend on the corresponding measurement process

$p_{\text{model}}(y|\phi)$. To estimate I_{pre}, we use k'th nearest neighbor (kNN) estimators of entropy and

mutual information adapted from the NPEET Python package.[46] Here, the user has the option of

adjusting k, which controls a variance/bias tradeoff. When y is discrete (MPA regression), I_{pre} is

computed using the classic kNN entropy estimator[47,48] via the decomposition $I[y; \phi] = H[\phi] -$

$\sum_y p(y) H_y[\phi]$, where $H_y[\phi]$ denotes the entropy of $p_{\mathrm{true}}(\phi|y)$. When y is continuous (GE

regression), $I[y; \phi]$ is estimated using the kNN-based Kraskov Stögbauer Grassberger (KSG)

algorithm.[48] This approach optionally supports the local nonuniformity correction of Gao et al.,[49]

which is important when y and ϕ exhibit strong dependencies, but which also requires

substantially more time to compute.

Variational information

We define variational information as an affine transformation of $\mathcal{L}_{\mathrm{like}}$,

611
$$I_{\mathrm{var}} = H[y] - \frac{\log_2(e)}{N} \mathcal{L}_{\mathrm{like}} \ . \tag{28}$$

612   Here, $H[y]$ is the entropy of the data $\{y_n\}$, which is estimated using the k'th nearest neighbor

613   (kNN) estimator from the NPEET package.[46] Noting that this quantity can also be written as

614     $I_{\mathrm{var}} = H[y] - \mathrm{mean}(\{Q_n\})$, where $Q_n = -\log_2 p(y_n|\phi_n)$, we estimate the associated uncertainty

615   using

616
$$\delta I_{\mathrm{var}}[y; \phi] = \sqrt{\delta H[y]^2 + \frac{\mathrm{var}(\{Q_n\})}{N}} \ . \tag{29}$$

617   The inference strategy used by MAVE-NN is based on the fact that I_{var} provides a tight

618   variational lower bound on I_{pre}.[30] Indeed, in the large data limit,

619
$$I_{\mathrm{pre}} = I_{\mathrm{var}} + D_{\mathrm{KL}}(p_{\mathrm{true}}||p_{\mathrm{model}}) \ , \tag{30}$$

where $D_{\mathrm{KL}}(\cdot) \geq 0$ is the Kullback-Leibler divergence, and thus quantifies the accuracy of the

inferred measurement process. From **Eq. 30** one can see that, with appropriate caveats,

maximizing I_{var} (or equivalently, $\mathcal{L}_{\mathrm{like}}$) will also maximize I_{pre}.[20] But unlike I_{pre}, I_{var} is readily

compatible with backpropagation and stochastic gradient descent. See Supplemental

Information for a derivation of **Eq. 30** and an expanded discussion of this key point. Note:

Sharpee et al.[50] cleverly showed that I_{pre} can, in fact, be optimized using stochastic gradient

descent. Computing gradients of I_{pre}, however, requires a time-consuming density estimation

step. Optimizing I_{var}, on the other hand, can be done using standard per-datum

backpropagation.

Intrinsic information

Intrinsic information, $I_{\text{int}} = I[x; y]$, is the mutual information between the sequences x

and measurements y in a dataset. This quantity is somewhat tricky to estimate due to the high-

dimensional nature of sequence space. We instead used three different methods to obtain the

upper and lower bounds on I_{int} shown in **Fig. 3d** and **Fig. 5a**. More generally, we believe the

development of both computational and experimental methods for estimating I_{int} is be an

important avenue for future research.

To compute the upper bound on I_{int} for GB1 data (in **Fig. 3d**), we used the fact that

637
$$I[x; y] = H[y] - \langle H_x[y] \rangle_x \,, \tag{31}$$

638 where $H[y]$ is the entropy of all measurements y, $H_x[y]$ is the entropy of $p(y|x)$ for a specific

639 choice of sequence x, and $\langle \cdot \rangle_x$ indicates averaging over all sequences x. In this dataset, the

640 measurement values were computed using

641
$$y = \log_2 \left[\frac{c_s + 1}{c_i + 1} \right] \,, \tag{32}$$

642 where c_i is the input read count and c_s is the selected read count. $H[y]$ was estimated using the

643 KNN estimator.[47] We estimated the uncertainty in y by propagating errors expected due to

644 Poisson fluctuations in read counts, which gives

$$645 \qquad\qquad \delta y = \log_2(e)\sqrt{\frac{1}{c_s+1}+\frac{1}{c_i+1}} \, . \qquad\qquad (33)$$

646   Then, assuming $p(y|x)$ to be approximately Gaussian, we find the corresponding conditional

647   entropy to be

$$648 \qquad\qquad H_x[y] = \frac{1}{2}\log_2(2\pi e \, \delta y^2) \, . \qquad\qquad (34)$$

These $H[y]$ and $H_x[y]$ values were then used in **Eq. 31** to estimate I_{int}. This should provide an

upper bound on the true value of I_{int} because uncertainty in y must be at least that expected

under Poisson sampling of reads. We note, however, that the use of linear error propagation

and the assumption that $p(y|x)$ is approximately Gaussian complicate this conclusion. Also,

when applied to MPSA data, this method yielded an upper bound of 0.96 bits. We believe this

value is likely to be far higher than the true value of I_{int}, and that this mismatch probably

resulted from read counts in the MPSA data being over-dispersed.

To compute the lower bound on I_{int} for GB1 data (**Fig. 3d**) we used the predictive

information I_{pre} (on test data) of a GE regression model having a blackbox G-P map. This

provides a lower bound because $I_{\text{int}} \geq I_{\text{pre}}$ for any model (when evaluated on test data) due to

the Data Processing Inequality and the Markov Chain nature of the dependencies $y \leftarrow x \rightarrow \phi$ in

Fig. 2e.[20,29]

To compute a lower bound on I_{int} for MPSA data (**Fig. 5c**), we leveraged the availability

of replicate data in Wong et al..[36] Let y and y' represent the original and replicate

measurements obtained for a sequence x. Because $y \leftarrow x \rightarrow y'$ forms a Markov chain, $I[x;y] \geq$

$I[y;y'].$[29] We therefore used an estimate of $I[y;y']$, computed using the KSG method,[46,48] as the

lower bound for I_{int}.

Uncertainties in kNN estimates

MAVE-NN quantifies uncertainties in $H[y]$ and $I[y; \phi]$ using multiple random samples of

half the data. Let $\mathcal{D}_{100\%}$ denote a full dataset, and let $\mathcal{D}_{50\%,r}$ denote a 50% subsample (indexed

by r) of this dataset. Given an estimator $E(\cdot)$ of either entropy or mutual information, as well as

the number of subsamples R to use, the uncertainty in $E(\mathcal{D}_{100\%})$ is estimated as

671
$$\delta E(\mathcal{D}_{100\%}) = \frac{1}{\sqrt{2}} \text{std} \left[\{E(\mathcal{D}_{50\%,r})\}_{r=0}^{R-1} \right] . \tag{35}$$

MAVE-NN uses $R = 25$ by default. We note that computing such uncertainty estimates

substantially increases computation time, as $E(\cdot)$ needs to be evaluated $R + 1$ times instead of

just once. We also note that bootstrap resampling[51,52] is often inadvisable in this context, as it

systematically underestimates $H[y]$ and overestimates $I[y; z]$.

Datasets

For the GB1 DMS dataset of Olson et al.,[33] measurements were computed using

678
$$y_n = \log_2 \frac{(c_n^{\text{out}}+1)/(c_{\text{WT}}^{\text{out}}+1)}{(c_n^{\text{in}}+1)/(c_{\text{WT}}^{\text{in}}+1)} ,$$

where c_n^{in} and c_n^{out} respectively represent the number of reads from the input and output

samples (i.e., pre-selection and post-selection libraries), and $n = \text{WT}$ represents the 55 aa

wildtype sequence, corresponding to positions 2-56 of the GB1 domain. To infer the model in

Fig. 3b and to compute the information metrics in **Fig. 3c**, only double-mutant sequences with

$c_n^{\text{in}} \geq 10$ were used; these represent 530,737 out of the 536,085 possible double mutants. For

the models in **Figs. 3d-f**, y_n values for the 1045 single-mutant were also used in the inference

procedure.

For the Aβ DMS data of Seuma et al.[34] and TDP-43 DMS data of Bolognesi et al.,[35] y_n

values respectively represent nucleation scores and toxicity scores reported by the authors.

For the MPSA data of Wong et al.,[36] we used the data of library 1 replicate 1 obtained

for the *BRCA2* minigene data. Measurements were computed as

690
$$y_n = \log_{10}\left[100 \times \frac{(c_n^{\text{inc}}+1)/(c_{\text{CONS}}^{\text{inc}}+1)}{(c_n^{\text{tot}}+1)/(c_{\text{CONS}}^{\text{tot}}+1)}\right],$$

where c_n^{inc} and c_n^{tot} respectively represent the number of barcode reads obtained from exon

inclusion isoforms and from total mRNA, and $n = \text{CONS}$ corresponds to the consensus 5′ss

sequence CAG/GUAAGU. Corresponding PSI values were computed as $\text{PSI}_n = 10^{y_n}$. Only

sequences with $c_n^{\text{tot}} \geq 10$ were used, representing 30,483 of the 32,768 possible sequences of

the form NNN/GYNNNN.

For the *lac* promoter sort-seq MPRA data of Kinney et al.,[16] we used data from the "full-

wt" experiment (available at https://github.com/jbkinney/09_sortseq). For the *xylE* promoter

sort-seq MPRA data of Bellilveau et al.,[43] we used data kindly provided by the authors.

<u>References</u>

1. Kinney, J. B. & McCandlish, D. M. Massively parallel assays and quantitative sequence-
function relationships. *Annu Rev Genom Hum G* **20**, 99-127 (2019).

2. Starita, L. M. *et al.* Variant interpretation: functional assays to the rescue. *Am J Hum Genetics*
101, 315-325 (2017).

3. Fowler, D. M. & Fields, S. Deep mutational scanning: a new style of protein science. *Nat*
Methods **11**, 801-807 (2014).

4. Levo, M. & Segal, E. In pursuit of design principles of regulatory sequences. *Nat Rev Genet*
15, 453-468 (2014).

5. White, M. A. Understanding how cis-regulatory function is encoded in DNA sequence using
massively parallel reporter assays and designed sequences. *Genomics* **106**, 165-170 (2015).

6. Inoue, F. & Ahituv, N. Decoding enhancers using massively parallel reporter assays.
Genomics **106**, 159-164 (2015).

7. Peterman, N. & Levine, E. Sort-seq under the hood: implications of design choices on large-
scale characterization of sequence-function relations. *BMC Genomics* **17**, 206 (2016).

8. Fowler, D. M., Araya, C. L., Gerard, W. & Fields, S. Enrich: software for analysis of protein
function by enrichment and depletion of variants. *Bioinformatics* **27**, 3430-3431 (2011).

9. Alam, K. K., Chang, J. L. & Burke, D. H. FASTAptamer: A bioinformatic toolkit for high-
throughput sequence analysis of combinatorial selections. *Mol Ther-Nucleic Acids* **4**, e230
(2015).

10. Bloom, J. D. Software for the analysis and visualization of deep mutational scanning data.
BMC Bioinformatics **16**, 168 (2015).

11. Rubin, A. F. *et al.* A statistical framework for analyzing deep mutational scanning data.
Genome Biol **18**, 1-15 (2017).

12. Ashuach, T. *et al.* MPRAnalyze: statistical framework for massively parallel reporter assays.
Genome Biol **20**, 183 (2019).

13. Niroula, A., Ajore, R. & Nilsson, B. MPRAscore: robust and non-parametric analysis of
massively parallel reporter assays. *Bioinformatics* **35**, 5351-5353 (2019).

14. Faure, A. J., Schmiedel, J. M., Baeza-Centurion, P. & Lehner, B. DiMSum: an error model
and pipeline for analyzing deep mutational scanning data and diagnosing common experimental
pathologies. *Genome Biol* **21**, 207 (2020).

15. Atwal, G. S. & Kinney, J. B. Learning quantitative sequence-function relationships from
massively parallel experiments. *J Stat Phys* **162**, 1203-1243 (2016).

16. Kinney, J. B., Murugan, A., Callan, C. G. & Cox, E. C. Using deep sequencing to
characterize the biophysical mechanism of a transcriptional regulatory sequence. *Proc Natl*
Acad Sci USA **107**, 9158-9163 (2010).

17. Melnikov, A. *et al.* Systematic dissection and optimization of inducible enhancers in human
cells using a massively parallel reporter assay. *Nat Biotechnol* **30**, 271-277 (2012).

18. Mogno, I., Kwasnieski, J. C. & Cohen, B. A. Massively parallel synthetic promoter assays
reveal the in vivo effects of binding site variants. *Genome Res* **23**, 1908-1915 (2013).

19. Abadi, M. *et al.* TensorFlow: A Systems for Large-Scale Machine Learning. in *Proceedings*
of the 12th USENIX Symposium on Operating Systems Design and Implementation (OSDI '16)
(2016).

20. Kinney, J. B. & Atwal, G. S. Parametric inference in the large data limit using maximally
informative models. *Neural Comput* **26**, 637-653 (2014).

21. Pokusaeva, V. O. *et al.* An experimental assay of the interactions of amino acids from
orthologous sequences shaping a complex fitness landscape. *PLoS Genet* **15**, e1008079
(2019).

22. Kinney, J. B., Tkačik, G. & Callan, C. G. Precise physical models of protein-DNA interaction
from high-throughput data. *Proc Natl Acad Sci USA* **104**, 501-506 (2007).

23. Otwinowski, J. & Nemenman, I. Genotype to phenotype mapping and the fitness landscape
of the *E. coli lac* promoter. *PLoS ONE* **8**, e61570 (2013).

24. Sarkisyan, K. S. *et al.* Local fitness landscape of the green fluorescent protein. *Nature* **533**,
397-401 (2016).

25. Sailer, Z. R. & Harms, M. J. Detecting high-order epistasis in nonlinear genotype-phenotype
maps. *Genetics* **205**, 1079-1088 (2017).

26. Otwinowski, J., McCandlish, D. M. & Plotkin, J. B. Inferring the shape of global epistasis.
Proc Natl Acad Sci USA **115**, E7550-E7558 (2018).

27. Jones, M. C. & Faddy, M. J. A skew extension of the t-distribution, with applications. *J Roy*
Stat Soc B **65**, 159-174 (2003).

28. Kinney, J. B. & Atwal, G. S. Equitability, mutual information, and the maximal information
coefficient. *Proc Natl Acad Sci USA* **111**, 3354-3359 (2014).

29. Cover, T. M. & Thomas, J. A. *Elements of information theory*. (Wiley, 2006).

30. Barber, D. & Agakov, F. The IM algorithm: a variational approach to information
maximization. *Advances in neural information processing systems 16.* (2004).

31. Alemi, A. A., Fischer, I., Dillon, J. V. & Murphy, K. Deep variational information bottleneck.
arXiv:1612.00410 (2016).

32. Chalk, M., Marre, O. & Tkacik, G. Relevant sparse codes with variational information
bottleneck. *arXiv:1605.07332* (2016).

33. Olson, C. A., Wu, N. C. & Sun, R. A comprehensive biophysical description of pairwise
epistasis throughout an entire protein domain. *Curr Biol* **24**, 2643-2651 (2014).

34. Seuma, M., Faure, A., Badia, M., Lehner, B. & Bolognesi, B. The genetic landscape for
amyloid beta fibril nucleation accurately discriminates familial Alzheimer's disease mutations.
eLife **10**, e63364 (2021).

35. Bolognesi, B. *et al.* The mutational landscape of a prion-like domain. *Nat Commun* **10**, 4162
(2019).

36. Wong, M. S., Kinney, J. B. & Krainer, A. R. Quantitative activity profile and context
dependence of all human 5´ splice sites. *Mol Cell* **71**, 1012-1026.e3 (2018).

37. Bintu, L. *et al.* Transcriptional regulation by the numbers: models. *Curr Opin Genet Dev* **15**,
116-124 (2005).

38. Sherman, M. S. & Cohen, B. A. Thermodynamic state ensemble models of cis-regulation.
Plos Comput Biol **8**, e1002407 (2012).

39. Wong, F. & Gunawardena, J. Gene Regulation in and out of equilibrium. *Annu Rev Biophys*
49, 199-226 (2020).

40. Otwinowski, J. Biophysical inference of epistasis and the effects of mutations on protein
stability and function. *Mol Biol Evol* **35**, 2345-2354 (2018).

41. Manhart, M. & Morozov, A. V. Protein folding and binding can emerge as evolutionary
spandrels through structural coupling. *Proc Natl Acad Sci USA* **112**, 1797-1802 (2015).

42. Nisthal, A., Wang, C. Y., Ary, M. L. & Mayo, S. L. Protein stability engineering insights
revealed by domain-wide comprehensive mutagenesis. *Proc Natl Acad Sci USA* **116**, 16367-
16377 (2019).

43. Belliveau, N. M. *et al.* Systematic approach for dissecting the molecular mechanisms of
transcriptional regulation in bacteria. *Proc Natl Acad Sci USA* **115**, 201722055 (2018).

44. Browning, D. F. & Busby, S. J. W. Local and global regulation of transcription initiation in
bacteria. *Nat Rev Microbiol* **14**, 638-650 (2016).

45. Tareen, A. & Kinney, J. B. Logomaker: beautiful sequence logos in Python. *Bioinformatics*
36, 2272-2274 (2020).

46. Steeg, G. V. Non-Parametric Entropy Estimation Toolbox (NPEET).
https://www.isi.edu/~gregv/npeet.html (2014).

47. Vasicek, O. A test for normality based on sample entropy. *J Roy Stat Soc B* **38**, 54-59
(1976).

48. Kraskov, A., Stögbauer, H. & Grassberger, P. Estimating mutual information. *Phys Rev E*
69, 066138 (2004).

49. Gao, S., Steeg, G. V. & Galstyan, A. Efficient estimation of mutual information for strongly
dependent variables. *In Artificial intelligence and statistics (pp. 277-286). PMLR.*

50. Sharpee, T., Rust, N. C. & Bialek, W. Analyzing neural responses to natural signals:
maximally informative dimensions. *Neural Comput* **16**, 223-250 (2004).

51. Efron, B. Bootstrap methods: another look at the jackknife. *Ann Stat* **7**, 1-26 (1979).

52. Efron, B. & Tibshirani, R. Bootstrap methods for standard errors, confidence intervals, and
other measures of statistical accuracy. *Stat Sci* **1**, 54-75 (1986).