ACDC: Automated Cell Detection and Counting for Time-lapse Fluorescence Microscopy

Leonardo Rundo [1,2,†], **Andrea Tangherloni** [3,4,5,†], **Darren R. Tyson** [6,†], **Riccardo Betta** [7], **Carmelo Militello** [8], **Simone Spolaor** [7], **Marco S. Nobile** [9,10], **Daniela Besozzi** [7], **Alexander L. R. Lubbock** [6], **Vito Quaranta** [6], **Giancarlo Mauri** [7,10], **Carlos F. Lopez** [6,‡] and **Paolo Cazzaniga** [10,11,‡*]

[1] Department of Radiology, University of Cambridge, CB2 0QQ Cambridge, United Kingdom

[2] Cancer Research UK Cambridge Centre, University of Cambridge, CB2 0RE Cambridge, United Kingdom

[3] Department of Haematology, University of Cambridge, CB2 0XY Cambridge, United Kingdom

[4] Wellcome Trust Sanger Institute, Wellcome Trust Genome Campus, CB10 1HH Hinxton, United Kingdom

[5] Wellcome Trust – Medical Research Council Cambridge, Stem Cell Institute, CB2 0AW Cambridge, United Kingdom

[6] Department of Biochemistry, Vanderbilt University School of Medicine, Nashville, TN 37232, United States of America

[7] Department of Informatics, Systems and Communication, University of Milano-Bicocca, 20126 Milan, Italy

[8] Institute of Molecular Bioimaging and Physiology, Italian National Research Council, 90015 Cefalù (PA), Italy

[9] Department of Industrial Engineering & Innovation Sciences, Eindhoven University of Technology, The Netherlands

[10] SYSBIO/ISBE.IT Centre for Systems Biology, 20126 Milan, Italy

[11] Department of Human and Social Sciences, University of Bergamo, 24129 Bergamo, Italy

* Correspondence: paolo.cazzaniga@unibg.it, c.lopez@vanderbilt.edu

† These authors contributed equally to this work.

‡ Co-corresponding authors.

Version July 14, 2020 submitted to Appl. Sci.

Featured Application: Novel method for Automated Cell Detection and Counting (ACDC) in
time-lapse fluorescence microscopy.

Abstract: Advances in microscopy imaging technologies have enabled the visualization of live-cell
dynamic processes using time-lapse microscopy imaging. However, modern methods exhibit several
limitations related to the training phases and to time constraints, hindering their application in the
laboratory practice. In this work, we present a novel method, named Automated Cell Detection and
Counting (ACDC), designed for activity detection of fluorescent labeled cell nuclei in time-lapse
microscopy. ACDC overcomes the limitations of the literature methods, by first applying bilateral
filtering on the original image to smooth the input cell images while preserving edge sharpness, and
then by exploiting the watershed transform and morphological filtering. Moreover, ACDC represents
a feasible solution for the laboratory practice, as it can leverage multi-core architectures in computer
clusters to efficiently handle large-scale imaging datasets. ACDC was tested on two distinct cell
imaging datasets to assess its accuracy and effectiveness on images with different characteristics,
allowing us to achieve an accurate cell-count and nuclei segmentation, without relying on large-scale
annotated datasets.

Keywords: Bioimage informatics; Time-lapse microscopy; Fluorescence imaging; Cell counting;
Nuclei segmentation

1. Introduction

Advances in microscopy imaging technologies have enabled the visualization of dynamic live-cell processes using time-lapse microscopy methodologies [1–3]. Therefore, collections of microscopy images have become a primary source of data to unravel the complex mechanisms and functions of living cells [4]. The vast quantity and complexity of the data generated by modern visualization techniques preclude visual or manual analysis, therefore requiring computational methods to infer biological knowledge from large datasets [5,6]. In particular, the objects of interest in cellular images are characterized by high variations of morphology and intensity from image to image [6], which make features such as cell boundaries and intracellular features difficult to accurately identify. For this reason, cell segmentation analysis has gained increasing attention over the last decade [7].

The most commonly used free and open-source software tools for microscopy applications in the laboratory are ImageJ [8] or Fiji [9], and CellProfiler [10]. Although these tools offer customization capabilities, they do not provide suitable functionalities for fast and efficient high-throughput cell image analysis on large-scale datasets. In addition, CellProfiler Analyst [11] allows the user to explore and visualize image-based data and to classify complex biological phenotypes with classic supervised Machine Learning (e.g., Random Forests, Support Vector Machines). Taken together, these tools provide accurate performance for image quantification on high-quality annotated datasets but generally lack capabilities to work in the laboratory practice, because training and model setup phases are required; in addition, the user is often forced to transfer data from one tool to another for achieving the desired analysis outcome. Therefore, this hinders these tools to match the time constraints imposed by time-lapse microscopy studies.

Various mathematical morphology methodologies have been extensively used in cell imaging to tackle the problem of cell segmentation [7]. Wählby *et al.* [12] presented a region-based segmentation approach in which both foreground and background seeds are used as starting points for the watershed segmentation of the gradient magnitude image. Since more than one seed could be assigned to a single object, initial over-segmentation might occur. In [13], the authors developed an automated approach based on the Voronoi tessellation [14] built from the centers of mass of the cell nuclei, to estimate morphological features of epithelial cells. Similarly to the approach presented in this paper, the authors leveraged the watershed algorithm to correctly segment cell nuclei. It is worth noting that we do not exploit Voronoi tessellation since our objective disregards the morphological properties of adjacent cells in a tissue. Kostrykin *et al.* [15] introduced an approach based on globally optimal models for cell nuclei segmentation, which exploits both shape and intensity information of fluorescence microscopy images. This globally optimal model-based approach relies on convex level set energies and parameterized elliptical shape priors. Differently, no detection with ellipse fitting was exploited in [16], as this shape prior is not always suitable for representing the shape of the cell nuclei because of the highly variable appearance. In particular, a two-stage method combining the split-and-merge and watershed algorithms was proposed. In the first splitting stage, the method identifies the clusters by using inherent characteristics of the cell (such as size and convexity) and separates them by watershed. The second merging stage aims at detecting the over-segmented regions according to the area and eccentricity of the segmented regions. These sub-divisions are eliminated by morphological closing.

Machine Learning techniques have been applied to bioimage analysis [17,18]. For instance, CellCognition aims at annotating complex cellular dynamics in live-cell microscopic movies [19] by combining Support Vector Machines with hidden Markov models to evaluate the progression by using morphologically distinct biological states. More recently, it has been shown that methods based on Deep Convolutional Neural Networks (DCNNs) [20,21] can successfully address detection and segmentation problems otherwise difficult to solve by exploiting traditional image processing methods [22]. Further, an ensemble of DCNNs defined to segment cell images was presented in [23], where a gating network automatically divides the input image into several sub-problems and assigns them to specialized networks, allowing for a more efficient learning with respect to a single DCNN.

Traditional image segmentation approaches often require experiment-specific parameter tuning, while DCNNs require large amounts of high-quality annotated samples or ground truth. The ground truth, representing the extent to which an object is actually present, is usually delineated by a domain expert, *via* a tedious, cumbersome and time-consuming visual and manual approach. The annotated samples for one dataset may not be useful for another dataset, so new ground truth generation may be needed for a new dataset, thus limiting the effectiveness of DCNNs. The authors of [22] proposed an approach for automatically creating high-quality experiment-specific ground truth for segmentation of bright-field images of cultured cells based on end-point fluorescent staining, then exploited to train a DCNN [24]. In general, applying DCNNs to microscopy images is still challenging due to the lack of large datasets labeled at the single cell level [24]; moreover, Gamarra *at al.* [16] showed that watershed-based methods can achieve performance comparable to DCNN-based approaches. Thus, unsupervised techniques that do not require a training phase (i.e., data fitting or modeling) represent valuable solutions in this practical context [19,25].

In this work, we present a novel method named Automated Cell Detection and Counting (ACDC), designed for time-lapse microscopy activity detection of fluorescent-labeled cell nuclei. ACDC is capable of overcoming the practical limitations of the literature approaches, mainly related to the training phases or time constraints, making it a feasible solution for the laboratory practice. Specifically, ACDC uses bilateral filtering [26] applied on the original image to smooth the input cell image while preserving edge sharpness. This is followed by watershed transform [27,28] and morphological filtering [29,30], applied in a fully automatic manner. Thus, ACDC efficiently yields reliable results by only requiring the settings of a few parameters, which may be conveniently adjusted by the user. Therefore, unlike sophisticated solutions that do not provide any interactive control, ACDC makes the end-user sufficiently aware of the underlying automated analysis, thanks to the resulting interpretability of the segmentation model. We demonstrate applications of ACDC on two different cell imaging datasets in order to show its reliability in different experimental conditions.

The manuscript is structured as follows: Section 2 presents the results achieved with ACDC, and Section 3 provides discussions and final remarks. Finally, the analyzed fluorescence imaging datasets as well as the proposed method are described in Section 4.

2. Results

In this section we present the results obtained with ACDC on the Vanderbilt University (VU) dataset and the 2018 Data Science Bowl (DSB) training dataset [31]. Figure 1 shows an example of results obtained on VU and DSB datasets, where the detected cells are displayed with different colors to highlight the separation among overlapping and merging cells. We note that the analyzed images are characterized by a considerable variability in terms of cell density.

The assessment of cell count was quantified by means of the Pearson coefficient to measure the linear correlation between the automated and manual cell counts. The accuracy of the achieved segmentation results was evaluated by using the Dice Similarity Coefficient (DSC) and the Intersection over Union (IoU) metrics. Table 1 reports the results for both the analyzed datasets, which are supported by the scatter plots in Figure 2.

Table 1. Evaluation metrics on cell counting and segmentation achieved by ACDC on the analyzed time-lapse microscopy datasets. The results for the DSC and IoU metrics, as well as the execution time measurements, are expressed as mean value $\pm$ standard deviation.

Dataset	Pearson coeff. (p-value)	DSC (%)	IoU (%)	Exec. time (s)
Vanderbilt University	$\rho = 0.99974$ $(p = 6.6 \times 10^{-74})$	76.84 ± 6.71	62.84 ± 8.58	7.49 ± 0.30
2018 Data Science Bowl	$\rho = 0.96121$ $(p = 2.6 \times 10^{-169})$	88.64 ± 7.41	80.37 ± 10.58	0.12 ± 0.09

The achieved high ρ coefficient values confirm the effectiveness of the proposed approach, according to a validation performed against the manual cell counting, which is considered as the gold standard.

Figure 1. Examples of cell nuclei segmented by ACDC considering the images in Figures 4a and 4b **(a)-(b)**, and the images in Figures 5a and 5b **(c)-(d)**.

A strong positive correlation between the cell counts computed automatically by ACDC and the manual measurements was observed for both datasets analyzed in this study. In particular, in the case of the VU dataset, the automated cell counting is strongly consistent with the corresponding manual measurements, by denoting also a unity slope, as shown in Figure 2a. In the case of the DSB dataset (Figure 2b), the identity straight-line reveals a negative offset in the ACDC measurements. This finding means that the cell counts achieved by ACDC slightly under-estimated the gold standard in approximately 55% of cases. Besides the high variability of the fluorescence images included in the DSB dataset, this systematic error often depends on the gold standard binary masks that consider also partial connected-components of cell nuclei smaller than 40 pixels located at the cropped image borders. Notice that no ACDC's setting was modified, so some very small partial cell components were removed according to the morphological refinements based on the connected-component size.

The agreement between ACDC and the manual cell counting measurements can be graphically represented also by using a Bland–Altman plot [32], as reported in Figure 3 for both datasets. The Bland–Altman analysis allows for a better data visualization by showing the pairwise difference between the measurements obtained with the two methods, against their mean value. In this way, we can assess any possible relationship between the estimation errors and easily detect any outlier (i.e., observations outside the 95% limits of agreement). Figure 3 reveals that ACDC achieved reproducible results also by considering the whole range of the cell counts concerning the analyzed cell microscopy images; only about the 4% and 6% of outliers are observed in the ACDC results achieved on the VU

Figure 2. Scatter plots depicting ACDC results compared to the gold standard in terms of cell nuclei counting in the case of: **(a)** time-lapse fluorescence images from the VU dataset; **(b)** selection of fluorescence images from the DSB dataset. The equality line through the origin is drawn as a dashed line.

Figure 3. Bland–Altman plots of the cell counting measurements achieved by ACDC versus the gold standard for the **(a)** VU and **(b)** DSB datasets. Solid horizontal and dashed lines denote the mean and ± 1.96 standard deviation values, respectively.

and DSB datasets, respectively. This confirms the observations on the scatter plots in Figure 2; neither
systematic discrepancy between the measurements nor bias can be observed in the VU dataset, while a
negative bias is visible in the case of the DSB dataset.

The analysis of the DSC and IoU mean values reported in Table 1, calculated on the VU images,
reveals a good agreement between the segmentation results achieved by ACDC and the gold standard.
The standard deviation values confirm the high variability encountered in the input datasets. In
particular, in the case of the VU images, this evidence strongly depends on the density of the cells
represented in the input image. As a matter of fact, the DSC and IoU metrics is highly affected by
the size of the foreground regions with respect to the background. This behavior is confirmed by the
results achieved on the DSB dataset, where the IoU values are considerably higher than those achieved
on the VU images, even though the Pearson coefficient is slightly lower in this case. Accordingly, the

high standard deviation for the DSB dataset is due to the intrinsic variety of the images—in terms of
image size, zoom factor, and specimen type—included in this dataset (see Section 4.1.2).
The mean execution times concerning the segmentation tests are shown in Table 1. These
experiments were run on a personal computer equipped with a quad-core Intel Core 7700HQ (clock
frequency 3.80 GHz), 16 GB RAM, and Ubuntu 16.04 LTS operating system. The computational
efficiency of ACDC is confirmed in both cases, as cell detection and counting tasks can be completed
in respect of the time constraints imposed by the high-throughput laboratory routine. As expected, the
execution times are dependent on the image size. This trend is mainly due to the bilateral filtering
operation.
To conclude, considering the two experimental datasets, ACDC achieved accurate results in terms
of cell counting as well as segmentation accuracy. Therefore, ACDC proved to be a reliable and efficient
solution even when dealing with multiple datasets characterized by significant variations, in terms of
acquisition devices, specimens, experimental conditions, and imaging characteristics.

3. Discussion

The fully automatic pipeline for cell detection and counting proposed in this paper exploits
watershed transform [27,28] and morphological filtering operations [29,30], and also benefits from the
edge-preserving smoothing achieved by the bilateral filtering [26]. The capabilities of ACDC were
tested on two different cell imaging datasets characterized by significantly different acquisition and
experimental conditions. ACDC was shown to be accurate and reliable in terms of cell counting and
segmentation accuracy, thus representing a laboratory feasible solution also thanks to its computational
efficiency. As a matter of fact, the Pearson coefficient achieved both in the case of the VU and DSB
datasets was higher than 0.96, demonstrating an excellent agreement between automated cell count
achieved with ACDC and the manual gold standard. Finally, with the current ACDC implementation,
it is also possible to distribute the computation on multi-core architectures and computer clusters,
to further reduce the running time required to analyze large single image stacks. To this end, an
asynchronous job queue, based on a distributed message passing paradigm was developed exploiting
Celery and RabbitMQ.
The time-lapse microscopy image samples analyzed in this study are considerably different
from to the publicly available microscopy images of cell nuclei, such as in [33,34] and [35]. Indeed,
these datasets were captured under highly different microscope configurations compared to the VU
experiments; with particular interest to magnification, a $40\times/0.9$ numerical aperture and a $20\times/0.8$
objective lens were used in [33,34] and [35], respectively. These acquisition characteristics, summarized
in Table 2, produce substantially different images, compared to the datasets analyzed in this work,
as in the case of the average coverage (i.e., the percentage of pixels covered by cell nuclei), which is
remarkably different. As a future development, we plan to improve ACDC, to achieve accurate cell
nuclei detection and analysis for different cell imaging scenarios, independently from the acquisition
methods.

Table 2. Main characteristics of fluorescence microscopy datasets.

	U2OS [33]	NIH3T3 [34]	VU	DSB [31]
# images	48	49	46	301
Image size	1349×1030	1344×1024	2160×2160	various
Magnification	$40\times$	$40\times$	$10\times$	various
Total #cells	1831	2178	14045	7931
Min. #cells	24	29	22	1
Max. #cells	63	70	1763	124
Avg. %coverage	23%	18%	2.07%	5.41%

176   We also aim at exploiting the most recent Machine Learning techniques [36] to accurately refine
177 the segmentation results. The improvements may be achieved by classifying the geometrical and
178 textural features extracted from the detected cells [37]. This advanced computational analysis can allow

us to gain biological insights into complex cellular processes [17]. Finally, as a biological application, in the near future we plan to focus on the Fluorescent, Ubiquitination-based Cell-Cycle Indicator (FUCCI) reporter system for investigating cell-cycle states [38], by combining accurate nuclei segmentation results with live-cell imaging of cell cycle and division.

4. Materials and Methods

In this section we first present the fluorescence imaging datasets analyzed in this work, then we describe the pipeline at the basis of ACDC.

4.1. Fluorescence Microscopy Imaging Data

4.1.1. Vanderbilt University Dataset

This dataset collects time-lapse microscopy images from two experiments performed at the Department of Biochemistry of the Vanderbilt University School of Medicine, Nashville, TN, USA. All images were acquired by using Molecular Devices (San Jose, CA, USA) from ImageXpress Micro XL with a $10\times$ objective in the red channel (Cy3); some images were acquired in the green channel (FITC) for the same well and location (overlapping information) with a PCO.SDK Camera (Kelheim, Germany). The imaged region is 2160×2160 pixels and the pixel intensity from the camera has a range of 12 bits stored in a 16-bit format. The PC-9 human lung adenocarinoma cell line used in these studies had previously been engineered to express histone 2B conjugated to monomeric red fluorescent protein and geminin 1–110 fused to monomeric azami green [38–40]. The total number of the analyzed images with the corresponding manual cell segmentation (performed by a biologist) was 46, related to two distinct experiments. Two examples of input images are shown in Figure 4.

(a)　　　　　　　　　　　　　　　　(b)

Figure 4. Examples of the analyzed microscopy fluorescence images provided by the Department of Biochemistry of the VU. The images were displayed by automatically adjusting the brightness and contrast according to an histogram-based procedure.

4.1.2. 2018 Data Science Bowl

With the goal of validating ACDC on imaging data coming from different sources, we considered a selection of the training set of the DSB dataset [31], which was a competition organized by Kaggle (San Francisco, CA, USA). We used only the human-annotated training set because the gold standard for the test set is not publicly provided by the organizers. The goal of the DSB regarded the detection of the nuclei of the cells to identify each individual cell in a sample, a mandatory operation to understand

(a) (b) (c)

Figure 5. Examples of the analyzed microscopy fluorescence from the DSB dataset.

Figure 6. Boxplots depicting the distribution for both the analyzed datasets in terms of: **(a)** total number of cells, and **(b)** coverage of the cell nuclei regions.

the underlying biological processes. This dataset includes a large number of labelled nuclei images acquired under a variety of conditions, magnification, and imaging modality (i.e., bright-field and fluorescence microscopy). Image size varies among 256×256, 256×320, 260×347, 360×360, 512×640, 520×696, 603×1272, and 1040×1388 pixels.

The DSB dataset aimed at evaluating the generalization capabilities of computational methods when dealing with significantly different data. Therefore, to run tests with ACDC, we first extracted the fluorescence microscopy images from the training set; then, we selected images where the maximum size of the region cells segmented in the ground truth was equal or less than 1000 pixels to obtain a magnification factor roughly comparable to the VU dataset, for a total of 301 images. Three examples of input images with highly different characteristics are shown in Figure 5.

Finally, Figure 6 shows the boxplots the reveal the high variability of the analyzed microscopy imaging datasets, in terms of the number of cells and cell coverage, to support the validity of the experiments carried out in this study.

4.2. ACDC: a Method for the Automatic Cell Detection and Counting

Advances in optics and imaging systems have enabled biologists to visualize live-cell dynamic processes by time-lapse microscopy images. However, the imaging data recorded during even a

Figure 7. Flow diagram of the ACDC pipeline. The gray, black and light-blue data blocks denote gray-scale images, binary masks and information extracted from the images, respectively. The three macro-blocks represent the three main processing phases, namely: pre-processing, seed selection, and watershed-based segmentation.

single experiment may consist of hundreds of objects over thousands of images, which makes manual inspection a tedious, time-consuming and inaccurate option. Traditional segmentation techniques proposed in the literature generally exhibit low performance on live unstained cell images. These limitations are mainly due to low contrast, intensity-variant, and non-uniform illuminated images [1]. Therefore, novel automated computational tools tailored to quantitative system-level biology are required.

ACDC is a method designed for time-lapse microscopy that aims at overcoming the main limitations of the literature methods [10,19,41], especially in terms of efficiency and execution time, by means of a fully automatic strategy that allows for reproducible measurements [42]. The processing pipeline of ACDC exploits classic image processing techniques in a smart fashion, enabling feasible analyses in real laboratory environments. Figure 7 outlines the overall flow diagram of the ACDC segmentation pipeline, as described hereafter. It is worth noting that the number of parameters that need to be set in the underlying image processing operations involves only the kernel size of spatial filters and the structuring element sizes in morphological operations, providing a robust yet simple solution. Nevertheless, these parameters allow the user to have control over the achieved cell segmentation results. Unlike DCNN-based black- or opaque-boxes, ACDC offers an interpretable model for biologists that may conveniently adjust the parameters values according to the cell lines under investigations. Differently from supervised Machine Learning approaches [11,18,22], ACDC does not require any training phase, thus representing a reliable and practical solution even without the availability of large-scale annotated datasets.

4.2.1. Pre-processing

The input microscopy image is pre-processed to yield a convenient input to the downstream watershed-based segmentation by means of the following steps:

1. Application of bilateral filtering that allows for denoising the image $\mathcal{I}$ while preserving the edges by means of a non-linear combination of nearby image values [26]. This noise-reducing smoothing filter combines gray levels (colors) according to both a geometric closeness function c and a radiometric (photometric) similarity function s. This combination is used to strengthen near values with respect to distant values in both spatial and intensity domains. More specifically, the intensity of each pixel is replaced with a weighted average of intensity values from neighboring pixels. The weights depend not only on the Euclidean distance between pixels, but also on the radiometric differences (i.e., range differences). This dependence on pixel intensity helps preserve the edge sharpness. The image I_{bf} smoothed through the bilateral filter can be denoted by Eq. (1):

$$\mathcal{I}_{\text{bf}}(\mathbf{p}) = \frac{1}{\eta} \sum_{\mathbf{q} \in \Omega} \mathcal{I}(\mathbf{q}) \cdot c(\mathbf{p}, \mathbf{q}) \cdot s(\mathcal{I}(\mathbf{p}), \mathcal{I}(\mathbf{q}))), \tag{1}$$

where the normalization term $\eta = \sum_{\mathbf{q} \in \Omega} c(\mathbf{p}, \mathbf{q}) \cdot s(\mathcal{I}(\mathbf{p}), \mathcal{I}(\mathbf{q}))$ constrains the sum of weights to 1 and preserves the local mean [43]. The squared window Ω, centered on the current pixel $\mathbf{p}$ for filtering, is characterized by: $\text{size}(\Omega) = \max\{5, 2 \cdot \lceil 3 \cdot \sigma_s \rceil + 1\} = 7$ pixels. This simple yet effective strategy allows for contrast enhancement [44]. Bilateral filter has been shown to work properly in fluorescence imaging even preserving the directional information, such as in the case of the F-actin filaments [45]. This denoising technique was effectively applied to biological electron microscopy [46], as well as to cell detection [47], revealing better performance—compared to low-pass filtering—in noise reduction without removing the structural features conveyed by strong edges. The most commonly used version of bilateral filtering is the shift-invariant Gaussian filtering, wherein both the closeness function c and the similarity function s are Gaussian functions of the Euclidean distance between their arguments [26]. With more details, c is radially symmetric: $c(\mathbf{p}, \mathbf{q}) = e^{-\frac{1}{2}\left(\frac{\|\mathbf{p}-\mathbf{q}\|}{\sigma_s}\right)^2}$. Consistently, the similarity function s can be defined as: $s(\mathbf{p}, \mathbf{q}) = e^{-\frac{1}{2}\left(\frac{\|I(\mathbf{p})-I(\mathbf{q})\|}{\sigma_r}\right)^2}$. In ACDC we set $\sigma_c = 1$ and $\sigma_s = \sigma_{\text{global}}$ (where σ_{global} is the the standard deviation of the input image $\mathcal{I}$) for the standard deviation of the Gaussian functions c and s, respectively. This smart denoising approach allows us to keep the edge sharpness while reducing the noise of the processed image, so avoiding cell region under-estimation.

2. Application of top-hat transform for background correction with a binary circular structuring element (radius: 21 pixels) on the smoothed image. This operation accounts for non-uniform illumination artifacts, by extracting the nuclei from the background. The white top-hat transform is the difference between the input image I and the opening of $\mathcal{I}$ with a gray-scale structuring element b: $\mathcal{T}_{\text{w}} = \mathcal{I} - \mathcal{I} \circ b$ [48].

The results of the pre-processing images applied to Figures 4a and 5a are shown in Figures 8a and 8b, respectively.

4.2.2. Nucleus Seed Selection

The following steps are executed to obtain a reliable seed selection, so that the cells nuclei can be accurately extracted from the pre-processed images:

1. A thresholding technique has to be first applied to detect the cell regions. Both global and local thresholding techniques aim at separating foreground objects of interest from the background in an image, considering differences in pixel intensities [49]. Global thresholding determines a single threshold for all pixels and works well if the histogram of the input image contains

Figure 8. Result of the application of the pre-processing steps on the images shown in Figure 4a **(a)** and Figure 5a **(b)**.

well-separated peaks corresponding to the desired foreground objects and background [50]. Local adaptive thresholding techniques estimate the threshold locally over sub-regions of the entire image, by considering only a user-defined window with a specific size and exploiting local image properties to calculate a variable threshold [48,49]. These algorithms find the threshold by locally examining the intensity values of the neighborhood of each pixel according to image intensity statistics. To avoid unwanted pixels in the thresholded image, mainly due to small noisy hyper-intense regions caused by non-uniform illumination, we apply the Otsu global thresholding method [50] instead of local adaptive thresholding based on the mean value in a neighborhood [51]. Moreover, global adaptive threshold techniques are significantly faster than local adaptive strategies.

2. Hole filling is applied to remove possible holes in the detected nuclei due to small hypo-intense regions included in the nuclei regions.

3. Morphological opening (using a 1-pixel disk as a structuring element) is used to remove loosely connected components, such as in the case of almost overlapping cells.

4. Unwanted areas are removed according to the connected-components size. In particular, the detected candidate regions with areas smaller than 40 pixels are removed to refine the achieved segmentation results by robustly avoiding false positives.

5. Morphological closing (using a 2-pixel radius circular structuring element) is applied to smooth the boundaries of the detected nuclei and avoid the under-estimation of the detected nuclei regions.

6. The approximate Euclidean distance transform (EDT) from the binary mask, achieved by applying the Otsu algorithm and refined by using the previous 3 steps, is used to obtain the matrix of distances of each pixel to the background by exploiting the ℓ_2 Euclidean distance [52] (with a 5×5 pixel mask for a more accurate distance estimation). This algorithm calculates the distance to the closest background pixel for each pixel of the source image. Let $\mathcal{G}$ be a regular grid and $f : \mathcal{G} \to \mathbb{R}$ an arbitrary function on the grid, called a sampled function [53]. We define the distance transform $\mathcal{D}_f : \mathcal{G} \to \mathbb{R}$ of f as:

$$\mathcal{D}_f(\mathbf{p}) = \min_{\mathbf{q} \in \mathcal{G}} (d(\mathbf{p}, \mathbf{q}) + f(\mathbf{q})), \qquad (2)$$

where $d(\mathbf{p}, \mathbf{q})$ is a measure of the distance between the pixels $\mathbf{p}$ and $\mathbf{q}$. Owing to the fact that cells have a pseudo-circular shape, we used the Euclidean distance, achieving the EDT of f. In

the case of binary images, with a set of points $\mathcal{P} \subseteq \mathcal{G}$, the distance transform $\mathcal{D}_{\mathcal{P}}$ is a real-valued image of the same size:

$$\mathcal{D}_{\mathcal{P}} = \min_{\mathbf{q} \in \mathcal{P}} \left(d(\mathbf{p}, \mathbf{q}) + \mathbb{1}(\mathbf{q}) \right), \tag{3}$$

where:

$$\mathbb{1}(\mathbf{q}) = \begin{cases} 0, & \text{if } \mathbf{q} \in \mathcal{P} \\ \infty, & \text{otherwise} \end{cases}$$

is an indicator function for the membership in $\mathcal{P}$ [53]. The computed distance map is normalized by applying contrast linear stretching to the full 8-bit dynamic range.

7. Regional maxima computation allows for estimating foreground peaks on the normalized distance map. Regional maxima are connected-components of pixels with a constant intensity value, whose external boundary pixels have all a lower intensity value [30]. The resulting binary mask contains pixels that are set to 1 for identifying regional maxima, while all other pixels are set to 0. A 5×5 pixel square was employed as structuring element.

8. Morphological dilation (using a 3-pixel radius circular structuring element) is applied to the foreground peaks previously detected for better defining the foreground regions and merging neighboring local minima into a single seed point. The segmentation results on Figures 8a and 8b are shown in Figures 9a and 9b, respectively. The detail in Figure 8a shows that ACDC is highly specific to cell nuclei detection, discarding non-cell regions related to acquisition artifacts.

(a)   (b)

Figure 9. Segmented images obtained after the refinement steps applied to the image shown in Figure 8a **(a)**, and to the image shown in Figure 8b **(b)**.

4.2.3. Cell Nuclei Segmentation Using the Watershed Transform

The watershed transform [27] is one of the most used approaches in cell image segmentation [7], while it was originally proposed in the field of mathematical morphology [30].

The intuitive description of this transform is straightforward: assuming an image as a topographic relief, where the height of each point is directly related to its gray level, and considering rain gradually falling on the terrain, then the watersheds are the lines that separate the resulting catchment basins [28]. This technique is valuable because the watershed lines generally correspond to the most significant edges among the markers [29] and are useful to separate overlapping objects. Even when no strong edges between the markers exist, the watershed method is able to detect a contour in the area. This contour is detected on the pixels with higher contrast [27]. As a matter of fact, edge-based segmentation techniques—which strongly rely on local discontinuities in gray levels—often do not yield unbroken edge curves, thus heavily limiting their performance in cell segmentation [12]. Unfortunately, it is also

well-known that the watershed transform may be affected by over-segmentation issues, thus requiring further processing [54].

From a computational perspective, the watershed algorithm analyzes a gray-scale image by means of a flooding-based procedure. Since the flooding process is performed on either a gradient image or edge map, the basins should emerge along the edges. As a matter of fact, during the watershed process, the edge information allows for a better discrimination of the boundary pixels with respect to the original image. Finally, only the markers of the resulting foreground cells are selected. ACDC uses an efficient version of the watershed algorithm that exploits a priority queue to store the pixels according to the pixel value (i.e., the height in the gray-scale image landscape) and the entry order into the queue (giving precedence to the closest marker). More specifically, during the flooding procedure, this process sorts the pixels in increasing order of their intensity value by relying on a breadth-first scan of the plateaus based on a first-in-first-out data structure [28].

Although the watershed transform can detect also weak edges, it may not accurately detect the edge of interest in the case of blurred boundaries [54]. This sensitivity to noise could be worsened by the use of high pass filters to estimate the gradient and the edges, which amplify the noise. We address this issue by formerly applying the bilateral filter that reduces the halo effects [26]. Accordingly, we implemented the following steps:

1. Connected-component labeling [55] of the foreground region binary mask for encoding the markers employed in the following watershed algorithm.
2. Laplacian operator for producing the edge image [48] to feed the edge map as input to the watershed transform.
3. Watershed segmentation on the edge image according to the previously defined markers [56,57].

4.2.4. Implementation Details

The sequential version of ACDC has been entirely developed using the Python programming language (version 2.7.12), exploiting the following libraries and packages: NumPy, SciPy, OpenCV, scikit-image [58], and Mahotas [59]. The resulting processing pipeline makes use of classic image processing techniques in a smart fashion [60], thus enabling an efficient and feasible solution in time-lapse microscopy environments.

For laboratory feasibility purposes, an asynchronous job queue, based on a distributed message passing paradigm—namely Advanced Message Queuing Protocol (AMQP)—was developed using Celery [61] (implementing workers that execute tasks in parallel) and RabbitMQ [62] (exploited as a message broker to handle communications among workers) for leveraging modern multi-core processors and computer clusters.

4.3. Segmentation Evaluation Metrics

The accuracy of the achieved segmentation results $\mathcal{S}$ was quantitatively evaluated with respect to the real measurement—i.e., the ground truth $\mathcal{T}$ obtained manually by an experienced biologist—by using the Dice Similarity Coefficient (DSC):

$$\text{DSC} = \frac{2 \times |\mathcal{S} \cap \mathcal{T}|}{|\mathcal{S}| + |\mathcal{T}|} \times 100 \, (\%), \tag{4}$$

as well as the Intersection over Union (IoU) metrics, also known as Jaccard coefficient:

$$\text{IoU} = \frac{|\mathcal{S} \cap \mathcal{T}|}{|\mathcal{S} \cup \mathcal{T}|} \times 100 \, (\%) = \frac{|\mathcal{S} \cap \mathcal{T}|}{|\mathcal{S}| + |\mathcal{T}| - |\mathcal{S} \cap \mathcal{T}|} \times 100 \, (\%) = \frac{\text{DSC}}{2 - \text{DSC}}. \tag{5}$$

Author Contributions: Conceptualization, L.R., A.T., D.R.T., C.F.L., and P.C.; Investigation, L.R., A.T., D.R.T., D.B., V.Q., C.F.L., and P.C.; Methodology, L.R., A.T., D.R.T., C.F.L., and P.C.; Software, L.R., A.T., D.R.T., and A.L.R.L.; Validation, L.R., A.T., D.R.T., R.B., C.M., C.F.L., and P.C.; Writing – original draft, L.R., A.T., D.R.T., A.L.R.L., C.F.L.,

and P.C.; Writing – review & editing, R.B., C.M., S.S., M.S.N., D.B., A.L.R.L., V.Q., and G.M.; Visualization, L.R., A.T., D.R.T., C.F.L., and P.C.; Supervision, D.R.T., G.M., C.F.L., and P.C.. All authors read and approved the final manuscript.

Funding: This research received no external funding

Conflicts of Interest: The authors declare no conflict of interest.

References

1. Kanade, T.; Yin, Z.; Bise, R.; Huh, S.; Eom, S.; Sandbothe, M.F.; Chen, M. Cell image analysis: Algorithms, system and applications. Proceedings of the IEEE Workshop on Applications of Computer Vision (WACV). IEEE, 2011, pp. 374–381. doi:10.1109/WACV.2011.5711528.

2. Orth, J.D.; Kohler, R.H.; Foijer, F.; Sorger, P.K.; Weissleder, R.; Mitchison, T.J. Analysis of mitosis and antimitotic drug responses in tumors by in vivo microscopy and single-cell pharmacodynamics. *Cancer Res.* **2011**, *71*, 4608–4616. doi:10.1158/0008-5472.CAN-11-0412.

3. Manandhar, S.; Bouthemy, P.; Welf, E.; Danuser, G.; Roudot, P.; Kervrann, C. 3D flow field estimation and assessment for live cell fluorescence microscopy. *Bioinformatics* **2020**, *36*, 1317–1325. doi:10.1093/bioinformatics/btz780.

4. Peng, H. Bioimage informatics: a new area of engineering biology. *Bioinformatics* **2008**, *24*, 1827–1836. doi:10.1093/bioinformatics/btn346.

5. Meijering, E.; Carpenter, A.E.; Peng, H.; Hamprecht, F.A.; Olivo-Marin, J.C. Imagining the future of bioimage analysis. *Nat. Biotechnol.* **2016**, *34*, 1250. doi:10.1038/nbt.3722.

6. Peng, H.; Bateman, A.; Valencia, A.; Wren, J.D. Bioimage informatics: a new category in Bioinformatics. *Bioinformatics* **2012**, *28*, 1057–1057. doi:10.1093/bioinformatics/bts111.

7. Meijering, E. Cell segmentation: 50 years down the road [life sciences]. *IEEE Signal Process. Mag.* **2012**, *29*, 140–145. doi:10.1109/MSP.2012.2204190.

8. Schneider, C.A.; Rasband, W.S.; Eliceiri, K.W. NIH Image to ImageJ: 25 years of image analysis. *Nat. Methods* **2012**, *9*, 671. doi:10.1038/nmeth.2089.

9. Schindelin, J.; Arganda-Carreras, I.; Frise, E.; Kaynig, V.; Longair, M.; Pietzsch, T.; Preibisch, S.; Rueden, C.; Saalfeld, S.; Schmid, B.; others. Fiji: an open-source platform for biological-image analysis. *Nat. Methods* **2012**, *9*, 676. doi:10.1038/nmeth.2019.

10. Carpenter, A.E.; Jones, T.R.; Lamprecht, M.R.; Clarke, C.; Kang, I.H.; Friman, O.; others. CellProfiler: image analysis software for identifying and quantifying cell phenotypes. *Genome Biol.* **2006**, *7*, R100. doi:10.1186/gb-2006-7-10-r100.

11. Dao, D.; Fraser, A.N.; Hung, J.; Ljosa, V.; Singh, S.; Carpenter, A.E. CellProfiler Analyst: interactive data exploration, analysis and classification of large biological image sets. *Bioinformatics* **2016**, *32*, 3210–3212. doi:10.1093/bioinformatics/btw390.

12. Wählby, C.; Sintorn, I.M.; Erlandsson, F.; Borgefors, G.; Bengtsson, E. Combining intensity, edge and shape information for 2D and 3D segmentation of cell nuclei in tissue sections. *J. Microsc.* **2004**, *215*, 67–76. doi:10.1111/j.0022-2720.2004.01338.x.

13. Kaliman, S.; Jayachandran, C.; Rehfeldt, F.; Smith, A.S. Limits of Applicability of the Voronoi Tessellation Determined by Centers of Cell Nuclei to Epithelium Morphology. *Front. Physiol.* **2016**, *7*, 551. doi:10.3389/fphys.2016.00551.

14. Honda, H. Description of cellular patterns by Dirichlet domains: the two-dimensional case. *J. Theor. Biol.* **1978**, *72*, 523–543. doi:10.1016/0022-5193(78)90315-6.

15. Kostrykin, L.; Schnörr, C.; Rohr, K. Globally optimal segmentation of cell nuclei in fluorescence microscopy images using shape and intensity information. *Med. Image Anal.* **2019**, *58*, 101536. doi:10.1016/j.media.2019.101536.

16. Gamarra, M.; Zurek, E.; Escalante, H.J.; Hurtado, L.; San-Juan-Vergara, H. Split and merge watershed: a two-step method for cell segmentation in fluorescence microscopy images. *Biomed. Signal Process. Control* **2019**, *53*, 101575. doi:10.1016/j.bspc.2019.101575.

17. Angermueller, C.; Pärnamaa, T.; Parts, L.; Stegle, O. Deep learning for computational biology. *Mol. Syst. Biol.* **2016**, *12*, 878. doi:10.15252/msb.20156651.

18. Berg, S.; Kutra, D.; Kroeger, T.; Straehle, C.N.; Kausler, B.X.; Haubold, C.; others. ilastik: interactive machine learning for (bio) image analysis. *Nat. Methods* **2019**, *16*, 1226–1232. doi:10.1038/s41592-019-0582-9.

19. Held, M.; Schmitz, M.H.; Fischer, B.; Walter, T.; Neumann, B.; Olma, M.H.; Peter, M.; Ellenberg, J.; Gerlich, D.W. CellCognition: time-resolved phenotype annotation in high-throughput live cell imaging. *Nat. Methods* **2010**, *7*, 747. doi:10.1038/nmeth.1486.

20. Ciresan, D.; Giusti, A.; Gambardella, L.M.; Schmidhuber, J. Deep neural networks segment neuronal membranes in electron microscopy images. Advances in Neural Information Processing Systems (NIPS), 2012, pp. 2843–2851.

21. Rosati, R.; Romeo, L.; Silvestri, S.; Marcheggiani, F.; Tiano, L.; Frontoni, E. Faster R-CNN approach for detection and quantification of DNA damage in comet assay images. *Comput. Biol. Med.* **2020**, p. 103912. doi:10.1016/j.compbiomed.2020.103912.

22. Sadanandan, S.K.; Ranefall, P.; Le Guyader, S.; Wählby, C. Automated Training of Deep Convolutional Neural Networks for Cell Segmentation. *Sci. Rep.* **2017**, *7*, 7860. doi:10.1038/s41598-017-07599-6.

23. Hiramatsu, Y.; Hotta, K.; Imanishi, A.; Matsuda, M.; Terai, K.; Liu, D.; Zhang, D.; Song, Y.; Zhang, C.; Huang, H.; others. Cell Image Segmentation by Integrating Multiple CNNs. Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR) Workshops, 2018, pp. 2205–2211.

24. Kraus, O.Z.; Ba, J.L.; Frey, B.J. Classifying and segmenting microscopy images with deep multiple instance learning. *Bioinformatics* **2016**, *32*, i52–i59. doi:10.1093/bioinformatics/btw252.

25. Militello, C.; Rundo, L.; Minafra, L.; Cammarata, F.P.; Calvaruso, M.; Conti, V.; Russo, G. MF2C3: Multi-Feature Fuzzy Clustering to Enhance Cell Colony Detection in Automated Clonogenic Assay Evaluation. *Symmetry* **2020**, *12*, 773. doi:10.3390/sym12050773.

26. Tomasi, C.; Manduchi, R. Bilateral filtering for gray and color images. Proceedings of the Sixth International Conference on Computer Vision (ICCV). IEEE, 1998, pp. 839–846. doi:10.1109/ICCV.1998.710815.

27. Soille, P.J.; Ansoult, M.M. Automated basin delineation from digital elevation models using mathematical morphology. *Signal Process.* **1990**, *20*, 171–182. doi:10.1016/0165-1684(90)90127-K.

28. Vincent, L.; Soille, P. Watersheds in digital spaces: an efficient algorithm based on immersion simulations. *IEEE Trans. Pattern Anal. Mach. Intell.* **1991**, *13*, 583–598. doi:10.1109/34.87344.

29. Beucher, S.; Meyer, F. The morphological approach to segmentation: the watershed transformation. In *Mathematical Morphology in Image Processing*; Marcel Dekker Inc.: New York. NY, USA, 1993; Vol. 34, pp. 433–481.

30. Soille, P. *Morphological Image Analysis: Principles and Applications*, 2 ed.; Springer Science & Business Media: Secaucus, NJ, USA, 2004. doi:10.1007/978-3-662-05088-0.

31. Kaggle. 2018 Data Science Bowl. https://www.kaggle.com/c/data-science-bowl-2018, 2018. Online; accessed 14 December 2019.

32. Bland, J.M.; Altman, D.G. Measuring agreement in method comparison studies. *Stat. Methods Med. Res.* **1999**, *8*, 135–160. doi:10.1177/096228029900800204.

33. Coelho, L.P.; Shariff, A.; Murphy, R.F. Nuclear segmentation in microscope cell images: a hand-segmented dataset and comparison of algorithms. Proceedings of the IEEE International Symposium on Biomedical Imaging (ISBI): From Nano to Macro. IEEE, 2009, pp. 518–521. doi:10.1109/ISBI.2009.5193098.

34. Osuna, E.G.; Hua, J.; Bateman, N.W.; Zhao, T.; Berget, P.B.; Murphy, R.F. Large-scale automated analysis of location patterns in randomly tagged 3T3 cells. *Ann. Biomed. Eng.* **2007**, *35*, 1081–1087. doi:10.1007/s10439-007-9254-5.

35. Wiliem, A.; Wong, Y.; Sanderson, C.; Hobson, P.; Chen, S.; Lovell, B.C. Classification of human epithelial type 2 cell indirect immunofluoresence images via codebook based descriptors. Proceedings of the IEEE Workshop on Applications of Computer Vision (WACV). IEEE, 2013, pp. 95–102. doi:10.1109/WACV.2013.6475005.

36. Kraus, O.Z.; Grys, B.T.; Ba, J.; Chong, Y.; Frey, B.J.; Boone, C.; Andrews, B.J. Automated analysis of high-content microscopy data with deep learning. *Mol. Syst. Biol.* **2017**, *13*, 924. doi:10.15252/msb.20177551.

37. Win, K.; Choomchuay, S.; Hamamoto, K.; Raveesunthornkiat, M. Detection and Classification of Overlapping Cell Nuclei in Cytology Effusion Images Using a Double-Strategy Random Forest. *Appl. Sci.* **2018**, *8*, 1608. doi:10.3390/app8091608.

38. Sakaue-Sawano, A.; Kurokawa, H.; Morimura, T.; Hanyu, A.; Hama, H.; Osawa, H.; Kashiwagi, S.; Fukami, K.; Miyata, T.; Miyoshi, H.; others. Visualizing spatiotemporal dynamics of multicellular cell-cycle progression. *Cell* **2008**, *132*, 487–498. doi:10.1016/j.cell.2007.12.033.

39. Tyson, D.R.; Garbett, S.P.; Frick, P.L.; Quaranta, V. Fractional proliferation: a method to deconvolve cell population dynamics from single-cell data. *Nat. Methods* **2012**, *9*, 923. doi:10.1038/nmeth.2138.

40. Harris, Leonard A.; Frick, Peter L.; Garbett, Shawn P.; Hardeman, Keisha N.; Paudel, B Bishal.; Lopez, Carlos F.; Quaranta, Vito.; Tyson, Darren R. An unbiased metric of antiproliferative drug effect in vitro. *Nat. Methods* **2016**, *13*, 497–500. doi:10.1038/nmeth.3852.

41. Georgescu, W.; Wikswo, J.P.; Quaranta, V. CellAnimation: an open source MATLAB framework for microscopy assays. *Bioinformatics* **2011**, *28*, 138–139. doi:10.1093/bioinformatics/btr633.

42. Sansone, M.; Zeni, O.; Esposito, G. Automated segmentation of comet assay images using Gaussian filtering and fuzzy clustering. *Med. Biol. Eng. Comput.* **2012**, *50*, 523–532. doi:10.1007/s11517-012-0882-z.

43. Chaudhury, K.N.; Sage, D.; Unser, M. Fast $O(1)$ bilateral filtering using trigonometric range kernels. *IEEE Trans. Image Process.* **2011**, *20*, 3376–3382. doi:10.1109/TIP.2011.2159234.

44. Schettini, R.; Gasparini, F.; Corchs, S.; Marini, F.; Capra, A.; Castorina, A. Contrast image correction method. *J. Electron. Imaging* **2010**, *19*, 023005. doi:10.1117/1.3386681.

45. Venkatesh, M.; Mohan, K.; Seelamantula, C.S. Directional bilateral filters for smoothing fluorescence microscopy images. *AIP Advances* **2015**, *5*, 084805. doi:10.1063/1.4930029.

46. Jiang, W.; Baker, M.L.; Wu, Q.; Bajaj, C.; Chiu, W. Applications of a bilateral denoising filter in biological electron microscopy. *J. Struct. Biol.* **2003**, *144*, 114–122. doi:10.1016/j.jsb.2003.09.028.

47. Li, K.; Miller, E.D.; Chen, M.; Kanade, T.; Weiss, L.E.; Campbell, P.G. Computer vision tracking of stemness. Proceedings of the 5th IEEE International Symposium on Biomedical Imaging: From Nano to Macro (ISBI). IEEE, 2008, pp. 847–850. doi:10.1109/ISBI.2008.4541129.

48. Gonzalez, R.; Woods, R. *Digital Image Processing*, 3 ed.; Prentice Hall Press: Upper Saddle River, NJ, USA, 2002.

49. Jain, A.K. *Fundamentals of Digital Image Processing*, 1 ed.; Prentice Hall Press: Upper Saddle River, NJ, USA, 2002.

50. Otsu, N. A threshold selection method from gray-level histograms. *IEEE Trans. Syst. Man Cybern.* **1975**, *11*, 23–27. doi:10.1109/TSMC.1979.4310076.

51. Militello, C.; Rundo, L.; Conti, V.; Minafra, L.; Cammarata, F.P.; Mauri, G.; Gilardi, M.C.; Porcino, N. Area-based cell colony surviving fraction evaluation: A novel fully automatic approach using general-purpose acquisition hardware. *Comput. Biol. Med.* **2017**, *89*, 454–465. doi:10.1016/j.compbiomed.2017.08.005.

52. Borgefors, G. Distance transformations in digital images. *Comput. Vis. Graph. Image Process.* **1986**, *34*, 344–371. doi:10.1016/S0734-189X(86)80047-0.

53. Felzenszwalb, P.F.; Huttenlocher, D.P. Distance transforms of sampled functions. *Theory Comput.* **2012**, *8*, 415–428. doi:10.4086/toc.2012.v008a019.

54. Grau, V.; Mewes, A.; Alcaniz, M.; Kikinis, R.; Warfield, S.K. Improved watershed transform for medical image segmentation using prior information. *IEEE Trans. Med. Imaging* **2004**, *23*, 447–458. doi:10.1109/TMI.2004.824224.

55. Suzuki, K.; Horiba, I.; Sugie, N. Linear-time connected-component labeling based on sequential local operations. *Comput. Vis. Image Underst.* **2003**, *89*, 1–23. doi:10.1016/S1077-3142(02)00030-9.

56. Meyer, F. Topographic distance and watershed lines. *Signal Process.* **1994**, *38*, 113–125. doi:10.1016/0165-1684(94)90060-4.

57. Najman, L.; Couprie, M.; Bertrand, G. Watersheds, mosaics, and the emergence paradigm. *Discrete Appl. Math.* **2005**, *147*, 301–324. doi:10.1016/j.dam.2004.09.017.

58. van der Walt, S.; Schönberger, J.L.; Nunez-Iglesias, J.; Boulogne, F.; Warner, J.D.; Yager, N.; Gouillart, E.; Yu, T.; the scikit-image contributors. scikit-image: image processing in Python. *PeerJ* **2014**, *2*, e453. doi:10.7717/peerj.453.

59. Coelho, L.P. Mahotas: Open source software for scriptable computer vision. *J. Open Res. Softw.* **2013**, *1*, e3. doi:10.5334/jors.ac.

60. Rundo, L.; Militello, C.; Vitabile, S.; Casarino, C.; Russo, G.; Midiri, M.; Gilardi, M.C. Combining
split-and-merge and multi-seed region growing algorithms for uterine fibroid segmentation in MRgFUS
treatments. *Med. Biol. Eng. Comput.* **2016**, *54*, 1071–1084. doi:10.1007/s11517-015-1404-6.
61. Celery Project.. Celery Distributed Task Queue. http://www.celeryproject.org/, 2018. Online; accessed 14
December 2019.
62. Pivotal Software, Inc.. RabbitMQ. http://www.rabbitmq.com/, 2018. Online; accessed 14 December 2019.