1
2
3
Neural representation of abstract task structure during generalization
5
6
7

8 **Authors**: Avinash R. Vaidya [1], Henry M. Jones [1,2], Johanny Castillo [1,3], & David Badre [1,4]
9
10
11 [1] Department of Cognitive, Linguistic, and Psychological Sciences, Brown University
12 [2] Department of Psychology, Stanford University
13 [3] Department of Psychology and Brain Sciences, University of Massachusetts Amherst
14 [4] Carney Institute for Brain Science, Brown University
15
Address correspondence to:
Avinash R. Vaidya
Brown University
Providence, RI 02912-1978
tel. 401-863-3634
email: avinash_vaidya (at) brown.edu

22
23
24

Abstract

Cognitive models in psychology and neuroscience widely assume that the human brain maintains an abstract representation of tasks. This assumption is fundamental to theories explaining how we learn quickly, think creatively, and act flexibly. However, neural evidence for a verifiably generative abstract task representation has been lacking. Here, we report an experimental paradigm that requires forming such a representation to act adaptively in novel conditions without feedback. Using functional magnetic resonance imaging, we observed that abstract task structure was represented within left mid-lateral prefrontal cortex, bilateral precuneus and inferior parietal cortex. These results provide support for the neural instantiation of the long-supposed abstract task representation in a setting where we can verify its influence. Such a representation can afford massive expansions of behavioral flexibility without additional experience, a vital characteristic of human cognition.

Introduction

Many complex tasks we perform daily, though different in their details, share an

abstract structure. For example, riding a bike and driving a car differ in many details,

including the actions they require, but they share an abstract similarity as modes of

transportation. It has long been proposed that humans can learn this abstract structure and

leverage it to think creatively, make novel inferences and rapidly generalize knowledge to

unique problems we have never encountered before (Gick and Holyoak, 1980; Harlow, 1949;

Tenenbaum et al., 2011; Tolman, 1948) — e.g. applying rules learned about when to break

on a bicycle to an automobile. Reproducing this generativity continues to vex even the most

impressive artificial intelligences (Lake et al., 2017; Russin et al., 2020), and is arguably one

of the most defining features of human cognition (Penn et al., 2008).

In reinforcement learning, the structure of a task is described by its decomposition

into 'states' — variables that specify the condition of the environment (Sutton and Barto,

2018). The definition of states is critical to determining how learning takes place, such as

whether new information is restricted to a specific set of circumstances or is shared between

conditions with overlapping features. States that cannot be resolved from sensory

information alone are said to be 'hidden' or 'latent' —in such cases, the organization of these

states must inferred from the distribution of rewards, or other outcomes, throughout the

task. In practice, latent states have been defined as distributions over the spatio-temporal

occurrence of rewards or punishments (Gershman et al., 2013; Nassar et al., 2019), task

stimuli or stimulus features (Collins and Frank, 2013; Gershman and Niv, 2013; Tomov et al.,

2018), or conditionalization of action-values based on recent task history (Schuck et al.,

2016; Zhou et al., 2019). From this distribution over task features, an agent can infer which

conditions might belong to the same latent states and which do not. This information can

then be used to segregate or lump together observations, making learning more efficient,

and enabling generalization of learning between settings that share the same latent states

(Gershman and Niv, 2010; Niv, 2019).

Recent work has provided evidence that the orbitofrontal cortex (OFC) and

hippocampus (HPC) maintain structured, abstract representations of tasks during planning

and navigation in conceptual spaces, including latent task states (Liu et al., 2019; McKenzie

et al., 2014; Schuck et al., 2016; Tavares et al., 2015; Wilson et al., 2014; Zhou et al., 2019) .

Likewise, other studies have investigated the neural processes supporting fast acquisition of

stimulus-response rules based on latent task knowledge (Badre et al., 2010; Collins et al.,

2014; Eichenbaum et al., 2020; Frank and Badre, 2012). However, an essential feature of an

abstract representation is that it can be used to generalize behaviors to new settings, in

absence of feedback, through a process of inference. To date, no study has investigated the

neural systems that maintain an abstract task representation that is observed to satisfy this

criterion. As a consequence, it remains unknown how the brain carries out this essential

function. To address this gap, we used fMRI to test the hypothesis that latent, generalizable

task representations used to control our behavior during a task are instantiated in neural

activity, particularly in OFC and HPC.

Participants completed a task where they gathered rewards in an environment where

a latent, generalizable structure was available. Throughout the experiment, images of trial-

unique items from three categories appeared beneath a context, denoted by a scene **(Figure

1a**). Participants decided whether to "sell" each item or pass. If they sold, they would receive

or lose reward probabilistically, as determined by the combination of item category and

context. Participants saw each of these combinations in short batches of trials termed mini-

blocks. Importantly, the contexts could be clustered based on the expected values associated

with each item category. This structure provided an opportunity to link these contexts

together using an abstract, latent state representation based on the distribution of category-

value associations over contexts. We hypothesized that participants would form, and later

use, this representation to generalize adaptive behaviors to new conditions without any

need for reinforcing feedback.

This hypothesis was tested across three phases (**Figure 1 –figure supplement 1**).

During phase one, participants learned about the abstract latent states using three item

categories (hands, foods and leaves) across nine contexts (**Figure 1b**). In the next phase,

participants learned the values of three new item categories (faces, animals, and objects) in

three of the nine contexts; one drawn from each latent state (**Figure 1c**). Then, in a final

generalization phase, they were tested on the remaining six contexts using the three new

image categories, without feedback. Optimal performance depended on generalizing the new

category values learned during the second phase to the held-out contexts (**Figure 1d**). We

expected that this inference would depend on those contexts being linked to a latent state

representation within a generalizable task representation based on the expected values of

categories encountered during the first phase.

Figure 1. Schematic of the experimental task, and its design and logic. **a.** In each trial of the training and generalization phases, participants were asked to make a decision to sell or pass on an image, the value of which depended on contexts shown above the image. Throughout the two training phases, participants received feedback on every trial, but not during generalization. Participants saw three categories of images in the same context over small batches of trials for each unique combination (termed a mini-block) before switching to a new context. **b-d**. The left tables show the reward structure for example context-category pairs across the three phases of the experiment in a single session. Cells show the probabilities of reward for each pair. The right schematics illustrate clustering of contexts by category-values into latent states (blue and orange arrows) and inference of values via structured knowledge (red arrows). Only two latent states are shown for visualization. Latent State (LS) Hands (H), Foods (F), Objects (O) and Animals (A). **b.** In the initial training phase, participants were presented with trial-unique images from three categories of images. These contexts could be grouped together through an abstract latent state representation based on the similarity of their category-value associations. **c.** Participants were later trained on three new categories in a subset of the previous contexts. Greyed out columns indicate contexts that were left out of this phase. Thus, the values of new categories were trained in only one context. in each LS cluster **d.** In the generalization phase, participants were asked to make decisions about the left out, novel context-category combinations without feedback. Participants had to use their knowledge of the latent states linking contexts together learned in the initial training. See **Figure 1 - figure supplement 1** for a table laying out the full experimental design over three experimental sessions.

Results

Participants were tested in three sessions. In session 1, participants completed a behavioral version of the task where performance in the generalization phase determined their inclusion in the fMRI experiment in sessions 2 and 3. 48% of participants passed a criterion of ≥70% accuracy in all 18 generalization conditions and so were recruited for two fMRI sessions. Participants who failed to meet this criterion performed the same task in two additional behavioral sessions rather than in the scanner. Of these participants, 50% ultimately passed the accuracy criterion by the third session. Thus, the majority of participants (75%) could carry out this generalization task given sufficient experience (**Figure 2 –figure supplement 1**).

In session 2, all participants carried out the same task, but with new context stimuli — requiring them to learn which contexts linked to which latent states anew. This session also included additional blocks of the generalization phase with conditions pseudo-randomized (rather than organized in mini-blocks). fMRI participants completed these additional blocks in the scanner and the rest of the experiment behaviorally. In session 3, all participants completed a shortened version of the training as a reminder of the task, and were presented with new pseudo-randomized generalization blocks (in the scanner for fMRI participants).

Abstract task structure affords inference of novel behaviors without feedback

Analysis of learning curves within mini-blocks of trials demonstrates that participants immediately made use of the abstract task structure in the first segment of the generalization phase. Through the first few trials of each mini-block of the initial and new category training, fMRI participants' accuracy steadily improved. In contrast, in the

generalization phase, accuracy was near ceiling from the first trial (mean P(correct) = 0.96,

SD = 0.06; **Figure 2a**). The rate of this learning curve in the generalization phase was

significantly lower than either of the other phases (**Figure 2b**), consistent with participants

inferring an adaptive behavior without need for additional experience or feedback

(Wilcoxon signed rank tests: Z's ≥ 3.21, P's ≤ 0.004, Bonferroni-corrected for multiple

comparisons). Similar results were observed in participants in participants who completed

the behavioral version of the task in session 2 and passed the generalization accuracy

criterion (**Figure 2 – figure supplement 2a**), with a significantly lower rate of change in the

accuracy learning curve in the generalization phase compared to the initial training or new

category training phases (Wilcoxon signed rank tests: W's = 45, P's = 0.01, Bonferroni-

corrected for multiple-comparisons).

Notably, high accuracy during generalization was accompanied by elevated reaction

times (RT; mean = 4.04 s, SD = 1.7 s) on the first trial, with a sharp drop-off subsequently

(mean=1.15 s, SD = 0.08 s; **Figure 2c**). The rate of speeding was significantly steeper in the

generalization phase compared to the initial or new category training phases averaged

across the first three contexts in each phase (Wilcoxon signed rank tests: Z ≥ 3.46, P ≤ 0.002,

Bonferroni corrected for multiple comparisons; **Figure 2d**). The same pattern in the rate of

speeding was observed in participants from the behavioral group who passed the

generalization criterion in session 2 (generalization versus initial training RT rates: W = 36,

P = 0.047, Bonferroni-corrected for multiple-comparisons; **Figure 2 – figure supplement

2d**). Thus, rather than immediately apply a structure learned incidentally during training,

participants took additional time to infer values during the first generalization trials —

indicative of a concerted, deliberative process.

Figure 2. Learning curves and repetition effects from training and generalization phases for fMRI participants in session 2. **a**. Mean accuracy across participants for first six trials of the first nine mini-blocks of initial and new category training, as well as blocked generalization phase. Dashed line indicates chance-level performance. **b**. Estimated exponential rate of change in mean accuracy in the first six trials for all mini-blocks in each phase. **c.** Mean reaction times (RT) for each trial in each of the first nine mini-blocks for each of these phases. Shaded area represents standard error of the mean (SEM). Mean and standard error were calculated from the log-transformed RTs. **d.** Estimated exponential rate of change in RT for first six trials within each phase for the first mini-blocks within the first three contexts in presentation order. For panels **b** and **d**, each dot represents a single participant, horizontal and vertical bars represent the mean and SEM, respectively. * P < 0.05, ** P < 0.01, Wilcoxon signed rank test, corrected for multiple comparisons. **e.** RTs for trials from the pseudo-randomized generalization phase from sessions 2 and 3 during fMRI scanning where latent states remained the same or switched from the previous trial, while the context switched or stayed the same. RTs have been log-transformed and z-scored within session for each participant. Each line represents a participant, black dashed line indicates mean and error bars indicate SEM. †P < 0.05, †††P < 0.0001, repeated-measures t-test. See **Figure 2 - figure supplement 1** for the mean accuracies for the fMRI and behavioral groups for each phase and session of the experiment. See **Figure 2 – figure supplement 2** for data from behavioral group participants who passed the generalization accuracy criterion in session 2.

As each latent state was repeated twice via two contexts during generalization, we

could test how previously encountering a latent state impacted RTs during a repetition.

Participants were faster for the second presentation of contexts from the same latent state

during generalization compared to contexts from different latent states (repeated measures

t-tests: (15) ≥ 2.13, P's < 0.05, d's ≥ 0.53), indicating that additional inferences were made

more quickly when a latent state had been accessed previously (**Figure 3a**). Comparison of

the rate of exponential curves fit to these RT data in each participant demonstrated that

these curves were steeper in the first context compared to the second context averaged

across latent states (Wilcoxon signed rank test: $Z = 3.36$, $P = 0.0007$), but there were no

differences in the rate of these curves according to the sequential order of latent states

(Wilcoxon signed rank test: $Z \leq 1.13$, $P \geq 0.2$, uncorrected; **Figure 3b**). A numerically similar

pattern of results was observed for the rate of change for learning curves in the behavioral

group who passed the generalization criterion, but did not reach statistical significance

(**Figure 3 – figure supplement 1**). These data argue that participants were faster in

completing the transfer of new category values to contexts if a context belonging to the same

latent state representation had already been activated, but did not necessarily use

information about other latent states they had encountered in narrowing this inference

problem.

Figure 3. Reaction times (RT) for fMRI participants in mini-blocks during generalization in session 2, organized by the presentation of latent states (LS 1, 2, 3) and contexts (1st and 2nd). Participants were significantly slower on the first trial of mini-blocks when encountering the first context in a latent state compared to the second context in the same latent state), but not in subsequent trials **a**. RT curves for mini-blocks organized by the order of latent states and contexts encountered. Lines indicate means, shaded area indicates the SEM. **b.** Rates of exponential functions fit to these RT curves. Each dot represents a single participant. †† *P*<0.001, Wilcoxon signed-rank test, **P* < 0.05, Bonferroni-corrected for multiple comparisons, ^*P* < 0.05, uncorrected. See **Figure 3- figure supplement 1** for data from the behavioral group participants who passed the generalization criterion in session 2.

Latent task states continue to influence behavior after initial inference

After an initial inference, participants may have formed rules for responding to the

new context-category combinations and no longer used the latent state representation

throughout the scanned generalization task. We reasoned that if participants are continuing

to utilize the latent abstract task structure, this would be evident in switch costs when the

active latent state changed between-trials (Collins and Frank, 2013). To avoid conflating

latent state and context switches, we isolated this analysis to only trials where the context

changed between trials. We found a significant switch cost in RT for trials when the latent

state changed versus stayed the same between trials (repeated-measures t-test: $t(15) = 2.33$,

$P = 0.03$, $d = 0.58$; **Figure 2e**), which did not differ between scanner sessions ($P = 0.8$). The

same effect was independently observed in participants in the behavioral group who passed

the generalization criterion (Figure 2 – figure supplement 2; $t(8) = 3.45$, $P = 0.009$, $d = 1.15$).

These data indicate that participants used these latent state representations throughout the

scanned task. Participants were also faster when both the context and latent state remained

the same ($t(15) = 5.29$, $P < 0.0001$, $d = 1.32$).

Generalization behavior is best explained by a hierarchical latent state representation

Notably, generalization in this task might not only be achieved through the use of a

latent state representation to bridge contexts. For example, an associative retrieval process

could also explain these results if newly trained category values could be transferred through

mediated retrieval of contexts held-out of the generalization phase via shared category-value

associations learned in the initial training (Kumaran and McClelland, 2012; Schapiro et al.,

2017).

To test this possibility, we compared four alternative computational models that

generated predictions for participants' RTs based on different memory network

configurations where contexts, category-values and latent states were represented as nodes

with different levels of activation.

First, the conjunctive associative retrieval model represented each condition as a

combination of category and context features, and linked these conjunctive representations

to each other based on shared features, but had no representation of latent state (**Figure 4a**).

The independent associative retrieval model similarly did without a latent state

representation, but rather than only representing contexts and categories as conjunctions,

maintained independent representations of each and linked contexts to each other based on

shared category-value associations (**Figure 4b**).

In contrast to these associative retrieval models, we included two latent state models.

A simple latent state model connected category-values to three latent states, but forewent

any representation of context (**Figure 4c**). A hierarchical latent state model connected

category-values to contexts, and further clustered these contexts around latent states, so that

activation of each context and category was inherited from the latent state representation

(**Figure 4d**).

Each of these models relied on the basic assumption that RTs depend on the degree

of activation in the network nodes currently activated. On each trial, activation within the

network would increase at different rates depending on the relation of nodes to those that

were activated during retrieval. Three rate parameters determined this increase for nodes

that were directly activated on a trial (α_1), nodes directly connected to those activated (α_2),

and the rest of the network which might be searched but was not directly relevant to the

current trial (α_3). To establish that these models differed substantially in their predictions,

we tested each model on data simulated using the best fit model parameters from itself and

the two alternatives. This cross-model comparison clearly demonstrated that the predictions

of these four models were dissimilar and each model provided a much better fit to itself than

its alternative counterparts (**Figure 4 -figure supplement 1a**).

Figure 4. Computational modeling of reaction times (RT) during generalization phase for fMRI participants in session 2. Each panel shows simplified schematics for spreading activation in four alternative model networks for a trial involving a decision about an image of an object in context A1 (i.e. A1-O-): **a.** Conjunctive associative retrieval (CAR) model where each node represents a context-category conjunction with a particular value, **b.** Independent associative retrieval (IAR) model where contexts and category-values are represented separately, **c.** Latent state (LS) model where category-values are linked to a latent state node, without any representation of context, **d.** Hierarchical latent state (LS) model with contexts clustered around latent states, and category-values linked to each context. Border and arrow colors signify mode of retrieval. Below each schematic are scatterplots for z-scored reaction times for all participants in all correct trials of the generalization phase and simulated reaction times from each model, color-coded by trial type. See **Figure 4 – figure supplement 1** for further details on fit of each model to the data. H, Hands; A, Animals; F, Faces; O, Objects. Values: +, positive expected value; -, negative expected value.

The hierarchical latent state model provided the best fit to participants' RT data in

the fMRI group in sessions 1 and 2, and the nine participants in the behavioral group who

passed the generalization accuracy criterion in session 2 (**Table 1**; **Figure 4 – figure**

supplement 1a). Comparison of the three rate parameters of this model showed an ordering

consistent with the expectation that the degree of activation of items should fall off at a

distance from the items presented on the current trial (**Figure 4 – figure supplement 1b**),

where values for α_1 were significantly greater than α_2 and α_3 (Wilcoxon signed rank test: Z's

=3.51, P's = 0.001, Bonferroni corrected), and values for α_2 were significantly greater than

α_3 (Z =2.68, P = 0.02, Bonferroni corrected).

To understand why the hierarchical latent state model better accounted for

participants' data, we compared RTs simulated from the best fit model parameters for each

participant with each of the four models, focusing on data from session 2 for the fMRI group,

as it was more pertinent to the neuroimaging results (**Figure 4a-d**). We organized these data

by the order of presentation of each context associated with each latent state (as in **Figure**

3), switches of category mini-block, and all other trials within a mini-block and then

compared the root-mean squared deviation (RMSD) of each model for each trial type. We

found that the both latent state models provided a better fit on category switch trials

compared to the conjunctive associative retrieval model (repeated-measures t-test, $t(15) \geq$

4.76, P's $\leq$ 0.002, $d \geq$ 1.19, Bonferroni-corrected for multiple comparisons). Numerically, the

hierarchical latent state model also provided a better fit to these trials than the independent

associative retrieval model, though this difference was not statistically significant ($t(15) =$

2.02, P = 0.06, d = 0.50, uncorrected). The two associative retrieval models tended to

systematically overestimate RTs on these category switch trials, likely because category-

values associated with the trained context in the new category training phase were only

activated by mediated retrieval, whereas in the latent state models these category-values

benefited from inherited direct retrieval of the higher-order latent state representation. The

hierarchical latent state model also had lower RMSD for the first presentation of the second

context compared to the latent state model ($t(15)$ = 4.76, P = 0.001, d = 1.19, Bonferroni-

corrected for multiple comparisons). As the latent state model had no separate

representation of context, any activation related to a prior latent state would be fully

transferred to its second presentation through another context, resulting in an

underestimation of RTs. Instead, the results were more consistent with separate context

representations that inherit activation from a higher-order latent states, i.e., the use of a

hierarchical latent state structure.

Representation of an abstract task representation in multi-voxel activity patterns

Having verified that participants form and use an abstract task representation to

control behavior, we sought to test the neural systems that support this representation. We

carried out a representational similarity searchlight analysis (RSA) using multiple linear

regression to compare empirical representational dissimilarity matrices (RDMs) from

pattern activity to hypothesis RDMs quantifying the predicted distances between conditions

based on latent states, contexts, item categories, expected value, interactions between these

factors and control regressors (**Figure 5 – figure supplement 5**).

Figure 5. Whole-brain representational similarity searchlight analysis for main effects of interest. Each upper panel shows hypothesis representational dissimilarity matrix (RDM) for task factors. Lower panels show t-statistic map from a searchlight analysis testing these predictions in pattern activity projected onto inflated cortical surfaces. All maps are defined with a cluster forming threshold of $P < 0.001$ and corrected for multiple comparisons with permutation tests for defining a cluster extent threshold at $P < 0.05$. These maps include representations of **a.** latent states **b.** contexts, and **c.** value. Cluster extent threshold for each contrast is given by the value of k. A, B, C refer to distinct latent states. A1-C1 and A2-C2 refer to distinct contexts that belong to each of those latent states. F, Faces; A, Animals; O, Objects. +, positive value; -, negative value. See **Figure 5 - figure supplement 1** for comparison of latent state map to 17 network parcellation by Yeo et al. (2011), **Figure 5 - figure supplement 2** for the statistical map for the item category regressor, and **Figure 5 - figure supplement 4** for interaction terms. See **Figure 5 - figure supplement 3** for comparison of main effects of interest within each session, and **Figure 5 – figure supplement 5** for a view of all regressors included in the multiple linear regression model.

We found evidence for a latent state representation in bilateral dorsal- and

ventrolateral prefrontal cortex (PFC) with a rostral distribution, as well as the bilateral

precuneus, left middle temporal gyrus and bilateral inferior parietal lobules (**Figure 5a**;

Supplementary Table 1). Comparing this statistical map with resting-state functional

networks from Yeo et al., (2011), revealed that this latent state representation overlapped

most with a frontoparietal network centered on the inferior frontal and intraparietal sulci

(**Figure 5 – figure supplement 1**).

In contrast, context was associated with activity in the bilateral fusiform gyri (**Figure**

5b). Expected value was associated with activity in OFC, as well as left superior frontal and

angular gyri (**Figure 5c**). Item category was robustly represented throughout visual areas

and PFC (caudally on the left and broadly on the right; **Figure 5 – figure supplement 2**).

To test whether these results were consistent across fMRI sessions, we carried out

separate whole-brain searchlight RSAs within each session. The resultant statistical maps

for the main effects of interest were similar in both sessions (**Figure 5– figure supplement**

3). Contrasts between statistical maps for all terms in the multiple regression model only

revealed a stronger effect for value in the left middle temporal gyrus in session 2 compared

to session 3 (MNI coordinates: -48, -22, 0), and no other significant differences in either

direction.

As a secondary question, we were also interested in whether higher-order

representations of latent task states and expected value influenced each other, or perceptual-

semantic representations of item category. To test this, we included regressors for

hypothesis RDMs that captured interactions between latent states, value and item category,

as well as control regressors for interactions of these factors with context. Interactions

between item category with value and latent state were not significant, though items with

same value in the same latent state were represented more similarly in ventral temporal

cortex (VTC) (**Figure 5 –figure supplement 5**), observations recapitulated in ROI-based

analyses of activity within the VTC (**Figure 6b**).

Figure 6. Representational similarity analysis results from all voxels included in regions of interest (ROIs). Plots show distribution of beta coefficients across participants from multiple linear regression analyses comparing hypothesis representational dissimilarity matrices (RDMs) with empirical RDMs estimated for each ROI. Each dot represents a single participant. Horizontal lines indicate means and vertical lines the SEM. **a.** Orbitofrontal cortex (OFC), **b.** Ventral temporal cortex (VTC) and **c.** Hippocampus (HPC). *$P < 0.05$, **$P < 0.01$, ***$P < 0.0001$ one-sample t-tests against zero. See **Figure 6 - figure supplement 1** for results of second-level tests on value and latent state terms restricted to the OFC ROI.

We also conducted ROI-based RSAs focused on HPC and OFC, given *a priori*

expectation that these regions are involved in representing latent task structure during task

performance. RSAs within these ROIs were null for latent state representations **(Figure 6a,**

c). To test these effects at a finer grain, we conducted second-level tests of the whole-brain

searchlight analysis masked by these ROIs. Here, we found signals consistent with latent

state and expected value representations in central OFC, but not HPC (**Figure 6 – figure**

supplement 1; Supplementary Table 2). There were significant effects for category

representations in both of these ROIs, in line with broad discrimination between

semantically and perceptually distinct categories of stimuli in these regions (Chikazoe et al.,

2014; Kuhl et al., 2012; McNamee et al., 2013; Pegors et al., 2015).

Univariate contrast of accuracy

Lastly, we tested a univariate contrast of correct and error responses. Although less

functionally specific than the above analyses, we expected this contrast to reveal regions

broadly involved in engaging with this generalization task. This contrast revealed greater

activation in the HPC and OFC on correct responses (**Figure 7**; **Supplementary Table 3**).

Figure 7. Univariate whole-brain contrast of correct and erroneous responses projected onto inflated cortical surfaces and on a single axial slice showing orbitofrontal cortex and hippocampus. This statistical map was defined with a cluster forming threshold of $P < 0.001$ and corrected for multiple comparisons with permutation tests for defining a cluster extent threshold at $P < 0.05$. Cluster extent threshold for each contrast is given by the value of k.

Discussion

Here, we observed that a latent state representation capable of supporting

generalization of knowledge to new settings is instantiated most strongly within activity in

mid-lateral PFC and parietal cortex. This pattern overlaps with a network previously

implicated in contextual modulation of behavior in hierarchical reinforcement learning and

cognitive control tasks (Badre et al., 2010; Choi et al., 2018; Collins et al., 2014). Like

hierarchical task structure in those experiments, latent task states enable faster learning,

reduced memory load and greater behavioral flexibility (Frank and Badre, 2012; Koechlin

and Summerfield, 2007). Recent work has similarly implicated mid-lateral and inferior

parietal cortex in inferring latent causes within tasks (Tomov et al., 2018), and discovering

hierarchical rules (Collins et al., 2014; Eichenbaum et al., 2020). Our findings extend these

observations to indicate that this network is not just involved in discovering and maintaining

task structure, but more generally represents tasks in an abstract format that facilitates

novel behaviors, even in absence of reinforcement. Once formed, such a fully abstract task

representation could potentially be used not only for on-line, stable task control in the face

of changing circumstances, but also as the generative mechanism for rapidly generalizing

diverse knowledge between settings, affording great behavioral flexibility with minimal

training.

Our behavioral results offer insights into the timing and nature of processes that form

this abstract task representation. While some accounts of generalization argue that

integration of related items occurs during encoding (Shohamy and Wagner, 2008; D

Zeithamova et al., 2012), others have suggested that this can happen online during retrieval

through statistical inference (Kumaran and McClelland, 2012). In this task, participants

could build their task representation at any point prior to the generalization phase, including

during the initial training phase. The lengthy RTs during the first trials of generalization

suggest that this inference required additional online processing, and this abstract task

structure may not have been fully constructed until it was probed. These data are consistent

with accounts arguing that generalization during acquired equivalence can also occur at

retrieval (De Araujo Sanchez and Zeithamova, 2020), and depends on the demand to make

new inferences. It is likely that linking of contexts to a latent state occurs at both encoding

and retrieval, with the timecourse of this process varying across individuals.

Modeling of RTs during the first mini-blocked section of the generalization phase has

also provided some insight into the process of how generalization of task information takes

place. An associative retrieval model without any latent state representation underestimated

RTs on category switch trials, as this model did not separate category-values by context or

latent state. However, a fully integrative representation of latent states was also insufficient,

as this alternative collapsed related contexts into the same latent state, and underestimated

the time needed to make additional inferences about contexts that had not been presented

earlier. Instead, our data were most consistent with an intermediate solution where related

contexts were bridged by a latent state, and category-values were separated by contexts.

Thus, our data were consistent with participants accomplishing generalization via an

integrated task representation on the basis of shared features (Schlichting and Preston,

2015; Shohamy and Wagner, 2008; Dagmar Zeithamova et al., 2012), while still retaining

independent representations of each context.

Our task design may have shaped this representation: the instructions strongly

encouraged participants to link contexts to an unseen latent variable (see methods), and the

mini-block trial structure likely encouraged learning the values of each category within each

context. Thus, ours is evidence that we can form such latent state representations, use them

for generalization, and represent them in fronto-parietal network while performing a task

based on them. We do not rule out that people cannot also use associative retrieval or that

they may do so instead of using a latent state in other task contexts. Nonetheless, evidence

that we can, and do, form latent states under certain circumstances is an important

observation that confirms a long held hypothesis in the field.

Behavioral evidence also indicated that this latent state representation was

maintained throughout the scanned generalization task. Analysis of RTs showed switch costs

for latent task states that exceeded those for changes of context alone. In principle, this

representation was not necessary for this portion of the task, as participants could have

instead consulted the inferred values of the 18 context-category combinations, or simply

memorized which six conditions were associated with negative expected values. Instead,

participants appeared to continue referencing this more abstract, and compact,

representation of the three latent task states to aid decision-making. Maintaining such a

representation would be particularly helpful as a means of compressing task information in

memory, and in could be useful in case of further need to update information about these

latent task states and propagate this information to linked task conditions (e.g. in a reversal

of the expected values for a particular context-category combination). Characterizing if, and

how, the neural representation of latent task states described here comes to influence

decision-making and learning in such settings remains an important outstanding question.

In this experiment, we were able to cross two factors previously associated with OFC

function within the same experiment: latent task states and expected value (Stalnaker et al.,

2015). We found limited evidence for OFC representing latent task states, though expected

value was robustly represented in this ROI. These data are consistent with rodent

electrophysiological data indicating that expected value signals contribute more to the

variance of activity within this region than representations of task space (Farovik et al., 2015;

Zhou et al., 2019). However, both OFC and HPC were activated for correct responses

compared to errors, possibly consistent with their role in retrieving relevant task

knowledge, if not in actively representing latent task structure in this experiment.

Prior observations may be reconciled with our results if distinct neural circuits are

involved in representing latent task states under different cognitive demands. Much recent

work has focused on the involvement of the medial PFC, OFC and hippocampus in learning

and representing structured knowledge, from the relations of paired associates to complex

schemas (Baldassano et al., 2018; Chen et al., 2017; Garvert et al., 2017; Ghosh et al., 2014;

van Kesteren et al., 2013). However, the network identified here as representing latent task

states shares greater similarity with regions in lateral PFC and inferior parietal cortex

identified by past studies focused on abstract representations of a task in cognitive control

settings (Loose et al., 2017; Woolgar et al., 2011). While these regions belong to mostly

distinct functional networks (Choi et al., 2018; Thomas Yeo et al., 2011), information may be

shared via strong connections between mid-lateral PFC with medial PFC, OFC and

hippocampus (Averbeck and Seo, 2008; Petrides, 2005), and regions that straddle these

networks, such as the angular and superior frontal gyri (Margulies et al., 2009). Information

passed through these select pathways might allow structured knowledge about abstract task

elements to inform a control representation in mid-lateral PFC (Badre and Nee, 2018).

Frontoparietal systems may be more involved in representing this kind of abstract

task structure when it is necessary for actively controlling behavior contingent on changing

contexts, as in this experiment. Other work that has examined analogous abstract task

representations in the context of conditional action selection and selecting between causal

models have found evidence for the involvement of frontoparietal cortex (Collins et al., 2014;

Eichenbaum et al., 2020; Tomov et al., 2018), similar to our results. In contrast, OFC and HPC

could be engaged more by resolving uncertainty about the prevailing latent task state (Chan

et al., 2016; Saez et al., 2015), or planning within a cognitive map of latent task states (Schuck

et al., 2016; Zhou et al., 2019). Other related work indicates that these regions are involved

in, and necessary for, constructing abstract representations (Kumaran et al., 2009; Schuck

and Niv, 2019; Spalding et al., 2018; D Zeithamova et al., 2012), and so may be particularly

engaged by the process of bridging contexts and forming a representation of latent task

states. Thus, while OFC and HPC may work together to form an understanding of the latent

task structure, mid-lateral PFC and parietal cortex are perhaps more involved in

implementing this representation for the purposes of controlling behavior. Indeed, such a

division of labor, would be consistent with the long-standing observation of a knowledge-

action dissociation from the study of patients with frontal lobe disorders (Milner, 1964). As

we did not scan participants during training, or the first mini-blocked section of the

generalization phase, we cannot yet speak to the neural circuits engaged in initially forming

this abstract task representation.

In sum, we have discovered evidence of a neural instantiation of a long-supposed

construct of cognitive models: an abstract task representation that enables generalization to

new tasks in absence of reinforcement. Future studies could evaluate how and when this

representation is formed, when and if this neural representation is necessary for

generalization behavior, and why some participants take longer to leverage this abstract task

structure. This study thus opens new ground in understanding the neural systems

supporting some of the key cognitive processes and behavioral features that distinguish

species like humans in their behavioral flexibility and capacity for rapid leaning (Lake et al.,

2017; Penn et al., 2008).

Materials and methods

Experimental procedure

The study design and analyses were pre-registered on the Open Sciences Framework

prior to collecting the data (https://osf.io/x6fmb). Participants completed an acquired

equivalence task where they learned that nine contexts belonged to three different latent

states (three per state) on the basis of their shared value associations for three object

categories. They then used this knowledge to complete a generalization task where they

inferred values for a new set of categories in contexts with which they had not been

previously paired. A schematic overview of the structure of this experiment is provided in

Figure 1 and **Figure 1 – supplementary figure 1**.

To aid in building a structured representation of the task, participants were told they

were playing the role of a photographer selling photos of different item categories in three

goblin kingdoms with distinct preferences for these categories. In each trial, participants had

to make a bet on whether to sell an image or to pass. This decision was a risky choice where

selling could be paid off with a reward in fictitious gold or punished with a loss of gold. After

a decision to sell, feedback was provided in terms of the gold won or lost. Passing would lead

to no change in gold, but feedback was provided in terms of the outcome had the participant

chosen to sell. Thus, in all phases of the experiment except for generalization (see below),

fully informative feedback was provided independent of participants' choices. Participants

were incentivized with a monetary bonus proportional to the amount of gold they earned in

the task. All photos were trial-unique so that participants never learned the values of specific

images, but of general image categories.

This experiment took place over three sessions. Each experimental session was

comprised of three main phases. First, in the beginning of the initial training phase,

participants were tasked with selling photos of hands, foods and leaves in three contexts,

represented by a natural scene image above the photo they were selling (A1, B1, C1).

Participants were told that the contexts each came from a different "kingdom", equivalent to

the generative latent states (LS A, LS B, LS C), and that each of these kingdoms preferred one

category of items strongly over the other two categories. Within each context one item

category was associated with a 90% probability of reward and 10% probability of

punishment for a decision to sell, while the other two categories were associated with a 10%

chance of reward and 90% chance of punishment. In each trial in this initial training phase,

participants could gain 50 gold or lose 25 gold for choosing to sell a photo. Thus, the expected

value of selling, without knowledge of the probability of reward for each category, was zero.

After two blocks of this training, participants then encountered 'roadwork' after

which they would learn about a new context in each kingdom represented by novel natural

scenes (A2, B2, C2). This roadwork repeated a second time after another two blocks so that

participants learned about three contexts in each of the three kingdoms. Importantly, all

contexts associated with a given latent state had the same reward probability structure

across item categories. Participants were not directly informed of which contexts

corresponded to which kingdoms, but had to make these inferences based on their shared

category values. The scene images for each context were randomly selected from a set of nine

for each participant, so there was no systematic visual relationship between the contexts of

each kingdom. Further, as contexts belonging to each "kingdom" were encountered after

each episode of roadwork, this event bound was not a cue to task structure and no aspect of

temporal adjacency could link contexts to a latent state.

These initial training blocks consisted of 54 trials with six trials per condition. This

initial training phase was organized in batches consisting of a series of trials for each context-

category combination (i.e. a 'mini-block'). These mini-blocks were nested by context, so that

participants saw each category in the same context one after another (e.g. A1-hands, A1-

leaves, A1-foods), before switching to a new context and looping once again through each

combination of context-category pairs (e.g. B1-leaves, etc.). The order of presentation for

these categories within each context was randomized, as was the order of these contexts.

Following these six initial training blocks, participants completed a final reminder training

block with the three categories presented in all nine contexts in mini-blocks of eight trials

(216 trials total).

In the second phase, participants completed training on new image categories (faces,

animals and man-made objects) within a subset of the previous contexts (e.g. A3, B3, C3).

Which set of contexts was presented in this phase (i.e. A1, B1, C1 versus A2, B2, C2 or A3, B3,

C3) was randomized across participants. Participants completed 90 trials in the course of a

single block, consisting of 10 trial mini-blocks for each combination of the three contexts and

three categories.

In the new category training phase, two categories of items were now associated with

a 90% chance of reward and 10% chance of punishment in each context, while these values

were reversed in one context. The categories that were rewarded and punished in each

context were randomized with respect to the categories in the initial training across

participants. For example, there was no rule in the experiment that faces have high value in

contexts where hands have low value. The punishment associated with selling a photo was

increased to 100 gold in this block so that the expected value of selling a photo without

knowing the probability of reward in a specific category-context combination was still zero.

Finally, in the third phase, participants carried out a generalization test where they

were presented with photos from these new categories in conjunction with the six contexts

held out of the prior new category training (e.g. A1, B1, C1 and A2, B2, C2, if A3, B3, C3 were

trained with the new categories). Critically, participants did not receive feedback throughout

this phase and could thus not learn the values of these new categories from experience.

Instead, they would have to rely on their knowledge about which contexts belonged to which

kingdoms (i.e. latent states) based on the shared category value associations learned in the

initial training phase. This generalization test included 10 trial mini-blocks for each of the 18

conditions (each context-category combination, with three categories and six contexts),

resulting in 180 trials total. Participants were informed that the value in gold earned and

lost on each trial had been doubled from the new category training phase to further

incentivize performance.

It is important to emphasize that generalization during this phase was only possible

based on a representation of the shared latent states among contexts. The particular pairings

of items and contexts during generalization had never been encountered previously. And, as

no feedback was provided during this phase, mappings could not be learned through

reinforcement. Further, as the item categories themselves were different from the initial

training phase, nothing about the objects or values could link the contexts encountered

during generalization to what was learned during phases 1 or 2 except for an abstract latent

state. That latent state already clustered the contexts encountered during generalization

with that encountered during new category learning because they had shared a value

structure during initial learning, albeit a different value structure on different object

categories. Thus, performing accurately during the generalization phase of this task provides

unambiguous evidence for reliance on an abstract latent state representation.

For all blocks of the training and mini-blocked generalization phases, there was no

response deadline. The inter-trial interval (ITI) was generated from a lognormal distribution

with a mean of 1 s, maximum time of 4 s and minimum of 0.5 s. Participants' choice was

underlined and the stimuli remained on screen for a 0.5 s inter-stimulus interval. In all

blocks, except the generalization test, feedback was displayed for 1.5 s, after which the trial

would end. Participants also briefly saw the total gold they had earned within the block after

it had ended. However, as there was no way for participants to link these earnings back to

the specific trials within the generalization phase, they could not learn the structure of the

task from this kind of feedback once they had reached this section of the experiment.

As already noted, this experiment took place over three sessions. The first session

was entirely behavioral and served to test how well participants could complete the

generalization phase. Prior behavioral pilot experiments had found that approximately 50%

of participants did not successfully infer all new context-category values during

generalization based on only one experience with training, and so failed to completely learn

the latent task structure. As our pre-registered analysis plan depended on participants

understanding this structure, we planned, *a priori*, to exclude from fMRI any participants

who did not meet a performance criterion of ≥70% accuracy in all 18 conditions of the

generalization test in this first session. Instead these participants were asked to return and

complete the rest of the experiment in two additional behavioral sessions. This allowed us

test whether these participants could generalize in this task, given sufficient experience (see

main text). That observation helps limit any concerns about generalizability raised by our

selection procedures.

In the second and third session, after completing the blocked generalization test,

participants completed three functional runs of the generalization task but without the

nested trial structure (i.e. mini-blocks nested by contexts). These blocks also had a three

second response deadline for each trial. In each run, ten trials from each of the 18 conditions

were presented in a pseudo-random sequence optimized for efficiency using Optseq2 with

ITIs ranging from 1 to 9 s (180 trials total) (Greve, 2002). This also ensured that the rate of

transitions between trials that shared features was effectively at chance (i.e. 33% for latent

states, 16.7% for contexts). After each response, the chosen option ('sell' or 'pass') was

underlined and the stimulus would remain on-screen until the end of the response deadline.

A random subset of six of these 12 optimized sequences was selected for the six functional

runs for each participant. Thus, each participant completed 1080 trials of this generalization

task over the course of two sessions in the scanner (60 trials per 18 conditions), or

behaviorally for those participants who did not pass the generalization criterion in the first

session. This dense sampling per participant provided more statistical power for our study

by reducing within-subject measurement error. Before completing this task, participants

also completed a short practice task with the same mixed trial structure with just one trial

from each condition.

Participants were given ample information about the structure of the task in

instructions that preceded each new phase of the experiment, but not specific information

that about which categories were rewarding in which contexts, and which contexts were part

of the same kingdoms (i.e. latent states). Specifically, participants were informed that the

outcomes were stable but probabilistic (without being explicitly informed of this

probability), and were told how many categories of photos each kingdom preferred in each

phase of the task. Participants were also instructed that they would later complete a test

phase without feedback, so they should strive to commit the values of photo categories in

each context to memory. They were also informed of the latent task structure in a general

sense, namely that contexts represented locations within distinct kingdoms, and that the

relation of contexts to different kingdoms could be uncovered by their shared values for the

item categories, but were never explicitly told which contexts were associated with which

kingdoms. Participants were also informed that the contexts within each kingdom could

appear to be visually very different from each other to discourage them from using such a

strategy to link contexts together. To facilitate forming such an abstract task representation,

the instructions specifically suggested that participants use a semantic elaboration strategy

that tied together the distinct contexts within each kingdom, and the values of the categories

within these contexts. These instructions and the cover story about the goblin kingdoms

were included to help encourage participants to learn the abstract structure of the task

rather than try and individually commit the values of all 54 context-category conjunctions to

memory.

At the end of the third session, outside of the scanner, participants completed a

similarity judgment task for the context natural scene images that were shown in their

specific generalization test. Participants were shown these images on a black background in

random starting positions and asked to use the mouse to drag and drop these images on-

screen so that their distances reflected the similarity. Participants were specifically

instructed not to use any information about to which kingdoms the contexts belonged, but

only the visual content of the image. The Euclidean distances between these images was then

used to estimate a subjective, participant-specific estimate of the visual similarity of these

images used as a nuisance regressor for RSA analyses.

Participants

Fifty participants were recruited for this study. Four participants were found to not

meet eligibility requirements for the study after session 1 (e.g. they had piercings or implants

that were not compatible with MRI), and their data was not analyzed. Twenty-four did not

reach criterion performance in the generalization phase (see above) in session 1, and were

invited to complete the second and third sessions in behavioral testing settings rather than

in the scanner. Six of these participants dropped out of the study before completing both

remaining sessions and two did not have complete data due to computer errors. Twenty-two

participants passed the generalization criterion and were asked to complete the remaining

two sessions in the scanner. Of these participants, two had low accuracy in the generalization

phase in the fMRI sessions, indicating a failure to learn the task structure, and their data was

not analyzed. Two further participants were excluded because of excessive movement (more

than 1 voxel) in more than one run. One participant had excessive movement only in the last

run of the last session and this single run was discarded from analysis. One participant could

not complete the experiment due to problems with the scanner on the day of testing, and one

participant dropped out of the study before finishing both scanned sessions. In total, 16

participants (10 female, mean age 21.3 years, SD = 3.3 years) passed the generalization

criterion on the first day, completed both days of the fMRI experiment and were included in

analyses, while 16 participants (11 female, mean age 22.3 years, SD = 2.5 years) did not pass

this criterion on the first day and completed the remaining two days of testing in behavioral

sessions. All participants gave their written informed consent to participate in this study, as

approved by the Human Research Protections Office at Brown University, and were

compensated for their participation.

The sample size for this study was determined by the target sample size for the fMRI

experiment. Data collection was ceased once 16 participants had completed both fMRI

scanning sessions while meeting eligibility for inclusion in our analysis (i.e. very little

movement and high accuracy during the generalization phase of the experiment). The target

sample size was based on a related experiment that successfully used RSA within an OFC ROI

(Chan et al., 2016). This target sample was halved, as the current experiment involved two

sessions of fMRI scanning and we expected within-subject measurement error to be reduced

by this dense sampling approach.

Materials

Eighteen images of natural scenes from Konkle et al., (2010) were used to represent

contexts within kingdoms (nine for session 1 and nine for sessions 2 and 3). These scenes

were chosen to be distinct from each other in content and did not include any visible animals,

people or man-made objects (i.e. the image categories included in the fMRI task). Over the

course of the experiment, participants saw 360 images in the initial category training for

each image category (randomly sampled from a larger set of 468 images). Hand images were

taken from the 11k Hands Database (Afifi, 2019), leaf images from the Leafsnap database

(Kumar et al., 2012), and food images from the Bank of Standardized Stimuli (BOSS)

(Brodeur et al., 2014), as well as the Foodpics database (Blechert et al., 2014). In the new

category training and generalization phases, 546 images were used from each stimulus

category. These included faces from the Chicago Face Database (Ma et al., 2015), animals

from the BOSS and CARE databases (Russo et al., 2018), and man-made objects, also from

the BOSS database. All category images were cropped or padded with white pixels to fit

within a square image with a white background.

Exponential curve fitting

To test the rate of change in RTs and accuracy, we fit an exponential function to these

data in the form of:

$$y = ab^x$$

Where y indicates the predicted trial RT or mean accuracy, b indicates the trial number, and

a and x are free parameters that determine the scale and rate of the function respectively.

The MATLAB function *fminunc* (Mathworks, Natick, MA) was used to find values for a and x

that produced a function that best fit individual participants' data using a least squares cost

function. This model-fitting process was run 10 times for each parameter fit for each subject,

each time with a different random starting point drawn from a standard normal distribution.

We chose the parameters that resulted in the lowest sum of squares from these 10 iterations

to avoid fits that had converged to local minima.

Computational modeling of reaction times

We developed a set of simple learning models to compare and contrast different

explanations for how participants carried out the transfer of option values during the initial

generalization phase. The models express retrieval and generalization in terms of spreading

activation among a set of nodes that represent the various task elements. In each model, we

structured the memory network differently according to the hypothesis tested. However,

these models relied on the same basic assumptions and parameters: 1. RTs are a function of

the activation strength of the nodes containing retrieved items (Anderson, 1983). 2. The

activation strength for each item is initialized at zero and increases according to a Rescorla-

Wagner learning rule (Rescorla and Wagner, 1972), controlled by a single rate parameter

bounded by 0 to 1 (α_1), each time an option is retrieved, until it reaches an asymptotic value

of one. 3. Activation spreads to contexts and categories linked with retrieved items,

controlled by a 'mediated retrieval' parameter (α_2). 4. Memory search increases activation

in all other task-related items in each trial according to an 'incidental retrieval' parameter

(α_3). 5. Increases in activation that are inherited from connected nodes falls off according to

a power law where the rates of successive steps are multiplied together.

We tested four model variants that each differed in how they represented this

memory network, and how activation of task elements propagates during generalization.

Importantly, these models are not meant simulate any particular neural system, but only

describe how the format of these representations in memory might differentially affect the

retrieval process and, by extension, RTs:

1. <u>Conjunctive associative retrieval</u> – This model implements generalization through

associative retrieval by assuming that the memory system stores conjunctions of

task-relevant features which can be retrieved if any one of these features is later

encountered. This memory network was represented as a matrix of contexts-by-

category conjunctions. On each generalization trial, the presented context (e.g. A1)

would activate related context-category-value conjunctions from the initial training

based on the rate parameter α_1 (e.g. A1-leaves- (negative value), A1-food-, A1-hands+

(positive value)). This would lead to the mediated activation of context-category

conjunctions with the same value associations from initial training with the rate

parameter α_2 (e.g. A3-hands+, A2-hands+, etc.), which would in turn lead to activation

of conjunctions of new categories associated with the context that appeared in the

second training phase (e.g. A3-objects-, A3-Faces+ etc.), as determined by the rate of

α_2^2. At the same time, the category presented on the current trial (e.g. objects) would

activate conjunctions with that category from the new category training phase (e.g.

A3-objects-, B3-objects+) at a rate determined by α_1 The conjunction shown on the

current trial (e.g. A1-objects-) would inherit activation from the related conjunction

from the new category training phase (e.g. A3-objects-) and increase in activation at

a rate determined by $\alpha_1^{2*}\alpha_2^2$. Similarly, the same category conjunction with the held

out related context (e.g. A2-objects-) would receive a mediated increase in activation

at a rate of $\alpha_1^{2*}\alpha_2^3$. All other nodes not activated by the current trial would also

increase their activation as a rate of α_3.

2. <u>Independent associative retrieval</u> – This model also implements generalization

through associative retrieval, but rather than relying on episodic conjunctions of

context and category, it stores each individual task element independently and links

them together based on experience. The memory network was represented as two

vectors of contexts and category-value conjunctions (i.e. separate nodes for faces+

faces-, etc.). Each context was linked to their associated category-values from the

initial training phase, and only the held-out contexts were directly linked to category-

values from the new category training. In each trial (e.g. A1-objects-), activation in the

current context (e.g. A1) would increase with the rate parameter α_1. This activation

would result in direct retrieval of category-values from initial training at a rate of $\alpha_1{}^2$,

and direct retrieval of the context from the new category training phase with the same

category-value associations (e.g. A3) at the rate $\alpha_1{}^3$. Retrieval of this context then led

to activation of the relevant category-value node for the current trial (e.g. objects-)

from the new training phase at a rate of $\alpha_1{}^4$, allowing generalization, as well as

mediated retrieval of other category-values (e.g. faces+, animals+) at a rate of $\alpha_1{}^3*\alpha_2$.

Activation of category values from the initial training would also lead to mediated

retrieval of the other related context (e.g. A2) at a rate of $\alpha_1{}^2*\alpha_2$. All other nodes

would increase their activation with a rate set by α_3.

3. <u>Latent state</u> – This model implements generalization through the formation of a latent

state that replaces separate representations of individual contexts. Here the memory

network was represented as a vector of latent states and a matrix of latent states-by-

categories, so category-values were separately nested in each latent state. In this case,

there was no separate representation of a context, so any increase in activation from

a trial involving context A1 immediately carried over to context A2. On each trial,

activation in the current latent state (e.g. latent state A) would increase according to

the rate parameter α_1, and in the current category-value node according to $\alpha_1{}^2$. All

other categories nodes linked to the active latent state increase in activation

according to α_2, and all other latent states increase activation according to α_3, and

their nested categories according to α_3^2.

4. <u>Hierarchical latent states</u> – This model also implements generalization through a

latent state, but builds on the basic latent state model to hierarchically cluster

contexts within latent states. Thus, this model builds on the latent state model but

includes a distinct vector for contexts, as well as a matrix of contexts-by-categories.

These contexts and context-category nodes are hierarchically nested within each

latent state (e.g. contexts A1 and A2 are nested within latent state A). Thus, activation

for each of these contexts and category nodes is inherited from activation of the latent

states and latent state-category nodes. On each trial, activation in the current context

increases at a rate of α_1^2, and in the current context-category at α_1^3. Contexts linked

to the current latent state also increase in activation according to $\alpha_1*\alpha_2$, as these

contexts inherit mediated activation from the latent state. Categories nested in these

contexts increase activation according to the rate $\alpha_1*\alpha_2^2$. Activation in all other latent

states increases at a rate of α_3, contexts not linked to the current latent state increase

at a rate of α_3^2, and their nested categories according to α_3^3.

For each model, predicted RTs were calculated simply as the sum of the activation

level in the current context (or latent state in case of the third model) and category,

subtracted from the maximum asymptotic activation level for both combined. These values

were then z-scored and compared to participants' z-scored RTs so that both model

predictions and behavioral data were on the same scale. The fit of each of these models was

calculated as the negative log-likelihood for a simple linear function. Only correct

responses were included in this analysis, as the model assumes correct recovery of option

values from memory on each trial. Across all 16 participants in the fMRI group, only 17

trials were errors in session 2, and thus accounted for a very small fraction of the data

(0.6%). Parameters were optimized using the MATLAB function *fmincon*, with each model

fit for each participant 30 times with random starting points in order to avoid convergence

on local minima.

To test whether these models made substantially different RT predictions, we carried

out a cross-model comparison using simulated data. We simulated data using the optimized

parameters from each participant for each model. We then fit each model on these simulated

data, in the same way as with participants' behavioral data and calculated the negative log-

likelihood of this fit to test if the generative model provided a better explanation of the

simulated data than the three alternatives.

fMRI acquisition procedures

Whole-brain imaging was acquired using a Siemens 3T Magnetom Prisma system

with a 64-channel head coil. In each fMRI session, a high resolution T1 weighted MPRAGE

image was acquired for visualization (repetition time (TR), 1900 ms; echo time (TE), 3.02

ms; flip angle, 9°; 160 sagittal slices; 1 x 1 x 1 mm voxels). Functional volumes were acquired

using a gradient-echo echo planar sequence (TR, 2000 ms; TE, 25 ms; flip angle 90°; 40

interleaved axial slices tilted approximately 30° from the AC-PC plane; 3 x 3 x 3 mm voxels).

Functional data were acquired over three runs. Each run lasted 15.1 min on average (452

acquisitions). After the functional runs, a brief in-plane anatomical T1 image was collected,

which was used to define a brain mask that respected the contours of the brain and the space

of the functional runs (TR, 350 ms; TE 2.5 ms; flip angle 70°; 40 axial slices; 1.5 x 1.5 x 3 mm

voxels). The sequence of scans was identical on both sessions. Soft padding was used to

restrict head motion throughout the experiment. Stimuli were presented on a 32-inch

monitor at the back of the bore of the magnet, and participants viewed the screen through a

mirror attached to the head coil. Participants used a five-button fiber optic response pad to

interact with the experiment (Current Designs, Philadelphia, PA).

fMRI preprocessing and analysis

Functional data were preprocessed using SPM12. Quality assurance for the functional

data of each participant was first assessed through visual inspection and TSdiffAna

(https://sourceforge.net/projects/spmtools/)　　　　　　and　　　　　　ArtRepair

(http://cibsr.stanford.edu/tools/human-brain-project/artrepair-software.html).　Outlier

volumes (defined by standard deviations from the global average signal) were interpolated

when possible. If interpolation was not possible, a nuisance regressor was added to the run

with a stick function at the time points for these volumes. Slice timing correction was carried

out by resampling slices to match the first slice. Next, motion during functional runs and days

was corrected by registering volumes to the first volume in the first session using rigid-body

transformation.

A deformation matrix for spatial normalization to Montreal Neurological Institute

(MNI) stereotaxic space using 4^{th} order B-spline interpolation was calculated for the motion

corrected functional volumes. The in-plane T1 anatomical image was used to create a brain

mask　for　functional　analysis　using　the　Brain　Extraction　Tool　in　FSL

(https://fsl.fmrib.ox.ac.uk/fsl/fslwiki/). This mask was then normalized to MNI space using

the inverse deformation matrix from the normalization of the functional data.

Functional data were analyzed under the assumptions of the GLM using SPM12.

Separate regressors were included for correct, erroneous and missed responses for each

condition with the duration of each response set to participants trial-wise RT (or the

duration of the stimulus display for missed responses). Nuisance regressors for participant

motion (six translational and rotational components) were also included, as was an

additional regressor for scan session. Regressors and parametric modulators were

convolved with the SPM canonical hemodynamic response function (HRF). Functional data

were pre-whitened and high-pass filtered at 0.008 Hz.

Representational similarity analysis

Whole-brain searchlight and ROI-based RSA were carried out in a two-step process.

First, in participant-level analyses, an empirical RDM was estimated from the cross-

validated Mahalanobis distances of the regressors for the 18 conditions (6 contexts x 3

categories) averaged over six runs within the generalization phase from a designated subset

of voxels in each participant (either defined by an ROI or a spherical searchlight) using the

RSAtoolbox v.2.0 (Nili et al., 2014; Walther et al., 2016). The lower triangle of this empirical

RDM was extracted giving the distances for the 153 condition pairs in this multivoxel space.

Hypothesis RDMs were constructed based on the similarities/dissimilarities that

would be expected for a pure representation of a given type. These included five main effects

(latent state, context, value, image category and subjective visual similarity of contexts), as

well as five interactions (latent state X category, latent state X value, value X category, context

X category, context X value).

In the case of latent state, value and context RDMs, the hypothesized distances were

simply set so that conditions that were the same on these factors would have smaller

expected distances, and larger distances where these conditions were not the same. For the

category RDM, hypothesized distances were based on asymmetric distances related to the

perceptual-semantic distances of animate and inanimate stimuli observed in many other

studies (Chikazoe et al., 2014; Thorat et al., 2019). Namely, that animate categories (faces

and animals) were expected to be more similar to each other than inanimate objects, but

inanimate objects were expected to be more similar to animals than to faces. Distances for

these hypothesis RDMs were set as ordinal integer numbers to reflect predicted distances

(e.g. for the category RDM, the expected distance between two conditions with faces would

be 1, the distance between faces and animals would be 2 and between faces and objects

would be 4). The RDM for the subjective visual similarity of contexts was specific to each

participant and derived from the Euclidean distances of these natural scene images in the

similarity judgment task completed at the end of the third session of the experiment.

Interaction RDMs were created by extracting main effect RDMs below the diagonal (i.e. the

lower triangle of the RDM matrix) as a vector, z-scoring these values and multiplying them

together. These interaction regressors allowed us to test where pattern-similarity reflected

the modulation of one task component another (e.g. where items belonging to different

categories were represented more similarly because of shared value associations).

Second, these hypothesis RDMs were related to the empirical RDM through multiple

linear regression analysis, where a coefficient was estimated relating each hypothesis RDM

to empirical RDMs allowing us to parcel out variance in representational distances due to

multiple factors in the same model (e.g. Nassar et al., 2019). Main effects and interaction

terms within this model were allowed to compete for variance simultaneously. The lower-

triangle of all hypothesis RDMs were extracted as vectors, z-scored, and included as

predictors, along with an intercept term, in a multiple linear regression analysis to calculate

beta coefficients relating each hypothesis RDM to the empirical RDM.

Searchlight analyses

Whole-brain analyses were carried out by passing a spherical searchlight with a

radius of 9 mm over each voxel within participants' brain mask in native space. For each

participant, beta coefficients for hypothesis RDMs were calculated at each step and averaged

over searchlight passes for all voxels included in the searchlight to compute fixed-effects in

a first-level analysis. This approach is similar to a common approach of assigning coefficients

to a the central voxel of each searchlight and then smoothing these maps before second-level

tests (e.g. (Devereux et al., 2013)), but requires one less experimenter degree of freedom in

defining the full-width half-maximum (FWHM) of the smoothing kernel. Group level analyses

were conducted by normalizing participants' beta coefficient maps to MNI space using the

deformation field from the normalization of participants' functional data and computing a

one-sample t-test against zero. These volumes were kept in a 1.5 x 1.5 x 1.5 mm space and

not resampled. Whole brain t-statistic maps were thresholded at a cluster defining threshold

of $P < 0.001$ uncorrected. Non-parametric permutation tests (10,000 permutations) were

used to derive a cluster extent threshold (k) for each test by randomly flipping the sign for

half of participants' contrasts and generating a null distribution based on the suprathreshold

maximum cluster statistics. The cluster extent threshold in each contrast was defined as the

95[th] percentile of this null distribution in order to test for statistical significance at $P < 0.05$,

corrected for multiple comparisons. (Nichols and Holmes, 2002).

Region of interest analyses

We defined three *a priori* anatomical ROIs in this study based on prior work using the

Automated Anatomical Labelling (AAL2) atlas (Rolls et al., 2015). First, the OFC ROI was

given the same definition used by a study examining latent state representations in this

region (Schuck et al., 2016), which followed that of Kahnt et al. (2012) (Kahnt et al., 2012).

This definition included the bilateral combination of the following regions: the superior

orbital gyri, middle orbital gyri, inferior orbital gyri medial orbital gyri, and rectal gyri. The

ventral temporal cortex (VTC) ROI was given the same definition used by a study that

showed that pattern activity in this region differentiated between visual images based on

animacy (Chikazoe et al., 2014), excepting the bilateral parahippocampal gyri. This definition

included the bilateral lingual gyri, fusiform gyri and inferior temporal cortices. The HPC ROI

was defined as the bilateral hippocampi. These masks were warped into participants' native

brain space using the inverse deformation matrix for all ROI-based analyses. We first

conducted an RSA analysis using all voxels within these ROIs by calculating empirical RDMs

for the cross-validated Mahalanobis distances from voxels within these ROIs in the same way

as in the searchlight analyses, and then using the same multiple linear regression model to

relate hypothesis RDMs to these empirical RDMs. These beta-coefficients were then

subjected to a second-level, one-sample t-test against zero to estimate statistical significance.

These ROIs were also used as an explicit mask in searchlight analyses to test for

effects that were below threshold at a whole-brain cluster-corrected level within HPC and

OFC. For these analyses, statistical significance was evaluated as in the whole-brain

searchlight analysis with cluster-based permutation tests to compute a cluster extent

threshold within these smaller volumes for each contrast, controlling for multiple

comparisons at $P < 0.05$.

Univariate analyses

Functional volumes were normalized to a 1.5 x 1.5 x 1.5 mm MNI space and smoothed

with an 8 mm FWHM Gaussian isotropic kernel. Beta coefficients for single subject effects

were estimated using a fixed-effects model in a first-level analysis. For whole-brain

contrasts, these estimates were then included in a second-level analysis using a one-sample

t-test against zero at each voxel. As with whole-brain RSA analyses, t-statistical maps were

thresholded at a cluster forming threshold of $P < 0.001$ and cluster-based permutation tests

were used to compute a cluster extent threshold controlling for multiple comparisons at $P <$

0.05.

Comparison with functional networks

The results of the whole-brain latent state RSA searchlight was compared with a

cortical parcellation based on resting state functional connectivity data from 1000

individuals by Yeo et al. (Thomas Yeo et al., 2011). To find the degree of overlap within each

of these functional networks, we calculated the proportion of voxels in the cluster-corrected

latent state statistical map that fell within these 17 networks projected to MNI152 space and

defined with liberal boundaries around the cortex.

Comparison across sessions

To assess the stability of task-relevant representations across scanning sessions, we

carried out two separate searchlight RSA analyses using data from within each session, as

above. The resultant coefficient maps from the multiple linear regression analysis were then

contrasted between sessions in both directions using paired t-tests. These contrasts were

then assessed with the same cluster-forming threshold and cluster-based permutation tests

to control for multiple comparisons, as in univariate and multivariate analyses.

Acknowledgements

This work was supported by a Multidisciplinary University Research Initiative award

from the Office of Naval Research (N00014-16-1-2832), a Postbaccalaureate Research

Education Program grant from the National Institute of General Medical Sciences

(R25GM125500), and a Ruth L. Kirschstein National Research Service Award to A.V. from the

National Institute of Mental Health (F32MH116592). We thank Apoorva Bhandari and other

members of the Badre Lab for constructive discussion and consultation on task design and

fMRI analysis, as well as Linda Q. Yu for comments on this manuscript. We also thank Emily

Chicklis for assistance with data collection.

References

Afifi M. 2019. 11K Hands: Gender recognition and biometric identification using a large

dataset of hand images. *Multimed Tools Appl*. doi:10.1007/s11042-019-7424-8

Anderson JR. 1983. A spreading activation theory of memory. *J Verbal Learning Verbal*

Behav. doi:10.1016/S0022-5371(83)90201-3

Averbeck BB, Seo M. 2008. The statistical neuroanatomy of frontal networks in the

macaque. *PLoS Comput Biol*. doi:10.1371/journal.pcbi.1000050

Badre D, Kayser AS, D'Esposito M. 2010. Frontal cortex and the discovery of abstract action

rules. *Neuron*. doi:10.1016/j.neuron.2010.03.025

Badre D, Nee DE. 2018. Frontal Cortex and the Hierarchical Control of Behavior. *Trends*

Cogn Sci. doi:10.1016/j.tics.2017.11.005

Baldassano C, Hasson U, Norman KA. 2018. Representation of real-world event schemas

during narrative perception. *J Neurosci*. doi:10.1523/JNEUROSCI.0251-18.2018

Blechert J, Meule A, Busch NA, Ohla K. 2014. Food-pics: an image database for experimental

research on eating and appetite. *Front Psychol* **5**:617. doi:10.3389/fpsyg.2014.00617

Brodeur MB, Guérard K, Bouras M. 2014. Bank of Standardized Stimuli (BOSS) phase ii: 930

new normative photos. *PLoS One*. doi:10.1371/journal.pone.0106953

Chan SCY, Niv Y, Norman KA. 2016. A Probability Distribution over Latent Causes, in the

Orbitofrontal Cortex. *J Neurosci* **36**:7817–7828. doi:10.1523/JNEUROSCI.0659-

16.2016

Chen J, Leong YC, Honey CJ, Yong CH, Norman KA, Hasson U. 2017. Shared memories reveal

shared structure in neural activity across individuals. *Nat Neurosci*.

doi:10.1038/nn.4450

Chikazoe J, Lee DH, Kriegeskorte N, Anderson AK. 2014. Population coding of affect across

stimuli, modalities and individuals. *Nat Neurosci* **17**:1114–1122. doi:10.1038/nn.3749

Choi EY, Drayna GK, Badre D. 2018. Evidence for a functional hierarchy of association

networks. *J Cogn Neurosci*. doi:10.1162/jocn_a_01229

Collins AGE, Cavanagh JF, Frank MJ. 2014. Human EEG uncovers latent generalizable rule

structure during learning. *J Neurosci*. doi:10.1523/JNEUROSCI.3900-13.2014

Collins AGE, Frank MJ. 2013. Cognitive control over learning: Creating, clustering, and

generalizing task-set structure. *Psychol Rev*. doi:10.1037/a0030852

De Araujo Sanchez MA, Zeithamova D. 2020. Generalization and source memory in

acquired equivalence. *PsyArXiv*.

Devereux BJ, Clarke A, Marouchos A, Tyler LK. 2013. Representational similarity analysis

reveals commonalities and differences in the semantic processing of words and

objects. *J Neurosci*. doi:10.1523/JNEUROSCI.3809-13.2013

Eichenbaum A, Scimeca JM, D'Esposito M. 2020. Dissociable Neural Systems Support the

Learning and Transfer of Hierarchical Control Structure. *J Neurosci*.

doi:10.1523/jneurosci.0847-20.2020

Farovik A, Place RJ, McKenzie S, Porter B, Munro CE, Eichenbaum H. 2015. Orbitofrontal

cortex encodes memories within value-based schemas and represents contexts that

guide memory retrieval. *J Neurosci* **35**:8333–8344. doi:10.1523/JNEUROSCI.0134-

15.2015

Frank MJ, Badre D. 2012. Mechanisms of hierarchical reinforcement learning in

corticostriatal circuits 1: computational analysis. *Cereb Cortex* **22**:509–526.

doi:10.1093/cercor/bhr114

Garvert MM, Dolan RJ, Behrens TEJ. 2017. A map of abstract relational knowledge in the

human hippocampal–entorhinal cortex. *Elife*. doi:10.7554/eLife.17086

Gershman SJ, Jones CE, Norman KA, Monfils MH, Niv Y. 2013. Gradual extinction prevents

the return of fear: Implications for the discovery of state. *Front Behav Neurosci*.

doi:10.3389/fnbeh.2013.00164

Gershman SJ, Niv Y. 2013. Perceptual estimation obeys Occam's razor. *Front Psychol*.

doi:10.3389/fpsyg.2013.00623

Gershman SJ, Niv Y. 2010. Learning latent structure: Carving nature at its joints. *Curr Opin*

Neurobiol. doi:10.1016/j.conb.2010.02.008

Ghosh VE, Moscovitch M, Melo Colella B, Gilboa A. 2014. Schema representation in patients

with ventromedial PFC lesions. *J Neurosci* **34**:12057–12070.

doi:10.1523/JNEUROSCI.0740-14.2014

Gick ML, Holyoak KJ. 1980. Analogical problem solving. *Cogn Psychol*. doi:10.1016/0010-

0285(80)90013-4

Greve DN. 2002. optseq2. *Optseq Home Page*.

Harlow HF. 1949. The formation of learning sets. *Psychol Rev*. doi:10.1037/h0062474

Kahnt T, Chang LJ, Park SQ, Heinzle J, Haynes JD. 2012. Connectivity-based parcellation of

the human orbitofrontal cortex. *J Neurosci*. doi:10.1523/JNEUROSCI.0257-12.2012

Koechlin E, Summerfield C. 2007. An information theoretical approach to prefrontal

executive function. *Trends Cogn Sci*. doi:10.1016/j.tics.2007.04.005

Konkle T, Brady TF, Alvarez GA, Oliva A. 2010. Scene memory is more detailed than you

think: The role of categories in visual long-term memory. *Psychol Sci*.

doi:10.1177/0956797610385359

Kuhl BA, Rissman J, Wagner AD. 2012. Multi-voxel patterns of visual category

representation during episodic encoding are predictive of subsequent memory.

Neuropsychologia. doi:10.1016/j.neuropsychologia.2011.09.002

Kumar N, Belhumeur PN, Biswas A, Jacobs DW, Kress WJ, Lopez IC, Soares JVB. 2012.

Leafsnap: A computer vision system for automatic plant species identificationLecture

Notes in Computer Science (Including Subseries Lecture Notes in Artificial Intelligence

and Lecture Notes in Bioinformatics). doi:10.1007/978-3-642-33709-3_36

Kumaran D, McClelland JL. 2012. Generalization through the recurrent interaction of

episodic memories: A model of the hippocampal system. *Psychol Rev*.

doi:10.1037/a0028681

Kumaran D, Summerfield JJ, Hassabis D, Maguire EA. 2009. Tracking the emergence of

conceptual knowledge during human decision making. *Neuron* **63**:889–901.

doi:10.1016/j.neuron.2009.07.030

Lake BM, Ullman TD, Tenenbaum JB, Gershman SJ. 2017. Building machines that learn and

think like people. *Behav Brain Sci*. doi:10.1017/S0140525X16001837

Liu Y, Dolan RJ, Kurth-Nelson Z, Behrens TEJ. 2019. Human Replay Spontaneously

Reorganizes Experience. *Cell*. doi:10.1016/j.cell.2019.06.012

Loose LS, Wisniewski D, Rusconi M, Goschke T, Haynes JD. 2017. Switch-independent task

representations in frontal and parietal cortex. *J Neurosci*.

doi:10.1523/JNEUROSCI.3656-16.2017

Ma DS, Correll J, Wittenbrink B. 2015. The Chicago face database: A free stimulus set of

faces and norming data. *Behav Res Methods*. doi:10.3758/s13428-014-0532-5

Margulies DS, Vincent JL, Kelly C, Lohmann G, Uddin LQ, Biswal BB, Villringer A, Castellanos

FX, Milham MP, Petrides M. 2009. Precuneus shares intrinsic functional architecture in

humans and monkeys. *Proc Natl Acad Sci U S A*. doi:10.1073/pnas.0905314106

McKenzie S, Frank AJ, Kinsky NR, Porter B, Riviere PD, Eichenbaum H. 2014. Hippocampal

representation of related and opposing memories develop within distinct,

hierarchically organized neural schemas. *Neuron* **83**:202–215.

doi:10.1016/j.neuron.2014.05.019

McNamee D, Rangel A, O'Doherty JP. 2013. Category-dependent and category-independent

goal-value codes in human ventromedial prefrontal cortex. *Nat Neurosci* **16**:479–485.

doi:10.1038/nn.3337

Milner B. 1964. Some effects of frontal lobectomy in manThe Frontal Granular Cortex and

Behavior.

Nassar MR, McGuire JT, Ritz H, Kable JW. 2019. Dissociable forms of uncertainty-driven

representational change across the human brain. *J Neurosci*.

doi:10.1523/JNEUROSCI.1713-18.2018

Nichols TE, Holmes AP. 2002. Nonparametric permutation tests for functional

neuroimaging: a primer with examples. *Hum Brain Mapp* **15**:1–25.

Nili H, Wingfield C, Walther A, Su L, Marslen-Wilson W, Kriegeskorte N. 2014. A toolbox for

representational similarity analysis. *PLoS Comput Biol* **10**:e1003553.

doi:10.1371/journal.pcbi.1003553

Niv Y. 2019. Learning task-state representations. *Nat Neurosci*. doi:10.1038/s41593-019-

0470-8

Pegors TK, Kable JW, Chatterjee A, Epstein RA. 2015. Common and unique representations

in pFC for face and place attractiveness. *J Cogn Neurosci* **27**:959–973.

doi:10.1162/jocn_a_00777

Penn DC, Holyoak KJ, Povinelli DJ. 2008. Darwin's mistake: Explaining the discontinuity

between human and nonhuman minds. *Behav Brain Sci*.

doi:10.1017/S0140525X08003543

Petrides M. 2005. Lateral prefrontal cortex: architectonic and functional organization.

Philos Trans R Soc L B Biol Sci **360**:781–795. doi:10.1098/rstb.2005.1631

Rescorla RA, Wagner AR. 1972. A theory of Pavlovian conditioning: Variations in the

effective- ness of reinforcement and non-reinforcement In: Black AH, Prokasy WF,

editors. Classical Conditioning. II. Current Research and Theory. New York: Appleton-

Century-Crofts. pp. 64–99.

Rolls ET, Joliot M, Tzourio-Mazoyer N. 2015. Implementation of a new parcellation of the

orbitofrontal cortex in the automated anatomical labeling atlas. *Neuroimage*.

doi:10.1016/j.neuroimage.2015.07.075

Russin J, O'Reilly RC, Bengio Y. 2020. Deep Learning Needs a Prefrontal Cortex. *Work*

"Bridging AI Cogn Sci (ICLR 2020).

Russo N, Hagmann CE, Andrews R, Black C, Silberman M, Shea N. 2018. Validation of the

C.A.R.E. stimulus set of 640 animal pictures: Name agreement and quality ratings. *PLoS*

One. doi:10.1371/journal.pone.0192906

Saez A, Rigotti M, Ostojic S, Fusi S, Salzman CD. 2015. Abstract Context Representations in

Primate Amygdala and Prefrontal Cortex. *Neuron* **87**:869–881.

doi:10.1016/j.neuron.2015.07.024

Schapiro AC, Turk-Browne NB, Botvinick MM, Norman KA. 2017. Complementary learning

systems within the hippocampus: A neural network modelling approach to reconciling

episodic memory with statistical learning. *Philos Trans R Soc B Biol Sci.*

doi:10.1098/rstb.2016.0049

Schlichting ML, Preston AR. 2015. Memory integration: Neural mechanisms and

implications for behavior. *Curr Opin Behav Sci.* doi:10.1016/j.cobeha.2014.07.005

Schuck NW, Cai MB, Wilson RC, Niv Y. 2016. Human Orbitofrontal Cortex Represents a

Cognitive Map of State Space. *Neuron* **91**:1402–1412.

doi:10.1016/j.neuron.2016.08.019

Schuck NW, Niv Y. 2019. Sequential replay of nonspatial task states in the human

hippocampus. *Science (80-)*. doi:10.1126/science.aaw5181

Shohamy D, Wagner AD. 2008. Integrating Memories in the Human Brain: Hippocampal-

Midbrain Encoding of Overlapping Events. *Neuron*. doi:10.1016/j.neuron.2008.09.023

Spalding KN, Schlichting ML, Zeithamova D, Preston AR, Tranel D, Duff MC, Warren DE.

2018. Ventromedial Prefrontal Cortex Is Necessary for Normal Associative Inference

and Memory Integration. *J Neurosci* **38**:3767–3775. doi:10.1523/JNEUROSCI.2501-

17.2018

Stalnaker TA, Cooch NK, Schoenbaum G. 2015. What the orbitofrontal cortex does not do.

Nat Neurosci **18**:620–627. doi:10.1038/nn.3982

Sutton R, Barto A. 2018. Reinforcment Learning. *MIT Press*.

Tavares RM, Mendelsohn A, Grossman Y, Williams CH, Shapiro M, Trope Y, Schiller D. 2015.

A Map for Social Navigation in the Human Brain. *Neuron*.

doi:10.1016/j.neuron.2015.06.011

Tenenbaum JB, Kemp C, Griffiths TL, Goodman ND. 2011. How to grow a mind: Statistics,

structure, and abstraction. *Science (80-)*. doi:10.1126/science.1192788

Thomas Yeo BT, Krienen FM, Sepulcre J, Sabuncu MR, Lashkari D, Hollinshead M, Roffman

JL, Smoller JW, Zöllei L, Polimeni JR, Fisch B, Liu H, Buckner RL. 2011. The organization

of the human cerebral cortex estimated by intrinsic functional connectivity. *J*

Neurophysiol. doi:10.1152/jn.00338.2011

Thorat S, Proklova D, Peelen M V. 2019. The nature of the animacy organization in human

ventral temporal cortex. *Elife*. doi:10.7554/eLife.47142

Tolman EC. 1948. Cognitive Maps in Rats and Men. *Psychol Rev* **55**:189–208. doi:Doi

10.1037/H0061626

Tomov MS, Dorfman HM, Gershman SJ. 2018. Neural computations underlying causal

structure learning. *J Neurosci*. doi:10.1523/JNEUROSCI.3336-17.2018

van Kesteren MT, Beul SF, Takashima A, Henson RN, Ruiter DJ, Fernandez G. 2013.

Differential roles for medial prefrontal and medial temporal cortices in schema-

dependent encoding: from congruent to incongruent. *Neuropsychologia* **51**:2352–

2359. doi:10.1016/j.neuropsychologia.2013.05.027

Walther A, Nili H, Ejaz N, Alink A, Kriegeskorte N, Diedrichsen J. 2016. Reliability of

dissimilarity measures for multi-voxel pattern analysis. *Neuroimage*.

doi:10.1016/j.neuroimage.2015.12.012

Wilson RC, Takahashi YK, Schoenbaum G, Niv Y. 2014. Orbitofrontal cortex as a cognitive

map of task space. *Neuron* **81**:267–279. doi:10.1016/j.neuron.2013.11.005

Woolgar A, Thompson R, Bor D, Duncan J. 2011. Multi-voxel coding of stimuli, rules, and

responses in human frontoparietal cortex. *Neuroimage*.

doi:10.1016/j.neuroimage.2010.04.035

Zeithamova D, Dominick AL, Preston AR. 2012. Hippocampal and ventral medial prefrontal

activation during retrieval-mediated learning supports novel inference. *Neuron*

75:168–179. doi:10.1016/j.neuron.2012.05.010

Zeithamova Dagmar, Schlichting ML, Preston AR. 2012. The hippocampus and inferential

reasoning: Building memories to navigate future decisions. *Front Hum Neurosci*.

doi:10.3389/fnhum.2012.00070

Zhou J, Montesinos-Cartagena M, Wikenheiser AM, Gardner MPH, Niv Y, Schoenbaum G.

2019. Complementary Task Structure Representations in Hippocampus and

Orbitofrontal Cortex during an Odor Sequence Task. *Curr Biol*.

doi:10.1016/j.cub.2019.08.040

1100

1101

Table 1. Sum of negative log-likelihood for four alternative models across participants and fraction of participants where each model was lowest in this measure in parentheses, for each group and session

	Conjunctive associative retrieval	Independent associative retrieval	Latent state	Hierarchical latent state
fMRI Group – Session 1	3537.78 (1/16)	3227.38 (2/16)	3428.23 (0/16)	3061.04 (13/16)
fMRI Group – Session 2	3849.60 (0/16)	3413.20 (4/16)	3569.10 (0/16)	3264.13 (12/16)
Behavioral Group – Session 2	2063.65 (0/9)	1851.76 (0/9)	1921.61 (0/9)	1713.73 (9/9)