What the Phage: A scalable workflow for the identification and analysis of phage sequences

Mike Marquet[1,7], Martin Hölzer[3], Mathias W. Pletz[1], Adrian Viehweger[2], Oliwia Makarewicz[1], Ralf Ehricht[4,5,6], Christian Brandt[1]

[1] Institute for Infectious Diseases and Infection Control, Jena University Hospital, Jena, 07747, Germany

[2] Institute for Medical Microbiology and Epidemiology of Infectious Diseases, University Hospital Leipzig, Leipzig, 04103, Germany

[3] RNA Bioinformatics and High-Throughput Analysis, Friedrich Schiller University Jena, Leutragraben 1, 07743 Jena, Germany

[4] Leibniz Institute of Photonic Technology (Leibniz-IPHT), Jena, Germany

[5] InfectoGnostics Research Campus, Jena, Germany

[6] Institute of Physical Chemistry, Friedrich-Schiller-University Jena, Jena, Germany

[7] Center of Sepsis Control and Care (CSCC), Jena, Germany

Abstract

Phages are among the most abundant and diverse biological entities on earth. Identification from sequence data is a crucial first step to understand their impact on the environment. A variety of bacteriophage identification tools have been developed over the years. They differ in algorithmic approach, results and ease of use. We, therefore, developed "What the Phage" (WtP), an easy-to-use and parallel multitool approach for phage identification combined with an annotation and classification downstream strategy, thus, supporting the user's decision-making process when the phage identification tools are not in agreement to each other. WtP is reproducible and scales to thousands of datasets through the use of a

24   workflow manager (Nextflow). WtP is freely available under a GPL-3.0 license

25   (https://github.com/replikation/What_the_Phage).

26   Introduction

Bacteriophages (phages) are viruses that infect prokaryotes and replicate by utilizing the

metabolism of the host (1). They are among the most abundant and diverse organisms on the

planet and inhabit almost every environment (2). Phages drive and maintain bacterial diversity

by perpetuating the coevolutionary interactions with their bacterial prey, facilitating horizontal

gene transfer, and nutrient turnover through continuous cycles of predation and coevolution

(3,4). They have a direct impact on the microbiome e.g. the human gut and can influence

human health (5). However, despite having considerable impacts on microbial ecosystems

such as the human gut, they remain one of the least understood members of complex

communities (6).

The sequencing of the entire DNA of environmental samples (metagenomics) is an essential

approach to gain insights into the microbiome and functional properties. It should be noted

that due to the small genome size of phages (5 kbp to 300 kbp) (7), their entire genome can

be sequenced assembly-free via long-read technologies (e.g., Oxford Nanopore

Technologies or PacBio) (8). This facilitates phage genome recovery in their natural habitat,

without the need to culture their hosts to isolate the phages (2). However, the identification

of phages from metagenomes in general and their differentiation from prophages remains a

challenge as there is no established computational gold standard (9).

Existing identification tools rely on direct comparison of sequence similarity (10,11), sequence

composition (12,13), and models based on these features derived through learning algorithms

(10,11,14,15).

The performance of each identification method varies greatly depending on the sample type

or material, the sequencing technology, and the assembly method, which makes the correct

choice for any given sample difficult without having to install and test several tools.

To further complicate matters, the user can choose from many tools based on different

calculation strategies and based on different software dependencies and databases. While

working with these phage identification tools, we observed various installation issues and

conflicts making a multi-tool screening approach unnecessary complex and time-consuming.

To overcome these obstacles and issues we developed "What the Phage" (WtP), a

reproducible, accessible and scalable workflow utilizing the advantages of multiple

identification tools in parallel to detect and annotate phages.

57 Design and Implementation

WtP was implemented in Nextflow, a portable, scalable, and parallelizable workflow manager

(16). At the time of writing, twelve different approaches to identify phage sequences are

included in WtP besides other programs for further annotation and classification. WtP uses

so-called containers (Docker or Singularity) for an installation-free workflow execution without

dependency or operating system conflicts for each of the currently over 21 programs included.

All containers are pre-build, version-controlled, online available at dockerhub.com and

automatically downloaded if used. Additionally, all nine different databases/datasets used by

the workflow are automatically managed. The modular code structure and functionalities of

Nextflow and Docker/Singularity allow easy integration of other phage prediction tools and

additional analysis steps in future releases of the pipeline. The workflow consists of two main

steps which are executed subsequently or, if specified, individually (see Figure 1):

1.   Identification: The identification of putative phage sequences

2.   Annotation & Taxonomy: The gene annotation and taxonomic classification of phage

sequences

Figure 1: Simplified DAG chart of the "What the Phage" workflow. Sequence input (yellow) can

either be first-run through the "Identification" and subsequently "Annotation & Taxonomy" as

a whole or used directly as an input for the "Annotation & Taxonomy" only. Each of the multiple

phage identification tools can be individually controlled if needed (tool control).

Identification and Visualization

The first step takes a multi fasta file as input (e.g. a metagenome assembly), formats it to the

demands of each tool and filters sequences below a user-defined length threshold (1,500 bp

by default) via SeqKit v0.10.1 (17). Sequences which are too small usually generate false-

positive hits as observed by Gregory *et al.* (18). The phage identification process is performed

by nine different tools in parallel: VirFinder v1.1 (13), PPR-Meta v1.1 (15), VirSorter v1.0.6

(with and without virome mode) (11), DeepVirFinder v1.0 (19), Metaphinder with no release

version (using default database and own database) (20), MARVEL v0.2 (14), sourmash v2.0.1

(12), Vibrant v1.2.1 (with and without virome mode) (10), and VirNet v0.1 (21). Positive

identifications are collected, filtered by adjustable parameters (Table 1), and the results are

summarized via a detailed heat map (Figure 3 A) that serves as a general identification

performance overview of each input sample. In addition, and because standard Venn and

Euler diagrams are an inadequate solution for quantitative visualization of multiple (n > 4)

intersections, we used an R package to generate UpSet plots (22) as a scalable alternative

for visualizing intersecting sets and their properties (Figure 2).

Table 1: Overview of the default criteria for "What the Phage" to determine a phage positive

contig by the raw output results of each tool. VirSorter and Vibrant are executed in default and

virome mode. MetaPhinder is executed with the default database and an own database based

on Zheng *et al.* (23).

Tool	Criteria	Filter
MARVEL	probability according to Random Forest algorithm	> 75 %
VirFinder	p-value	> 0.9
PPR-Meta	contig classification	"Phage"
VirSorter & VirSorter_virome	Category of detection (1, 2 or 3: intact, incomplete or questionable)	Category 1 & 2
MetaPhinder & MetaPhinder-own-DB	A) contig classification & B) average nucleotide identity %	A) Phage & B) > 50
DeepVirFinder	p-value	> 0.9
Vibrant & Vibrant_virome	contig classification	Virus
Virnet	p-value (as median across all hits per contig)	> 0.5
Sourmash	Similarity score	> 0.5

Annotation & Taxonomy

For this step, phage positive contigs are used and either automatically retrieved from the identification step or directly via user input. Prodigal v2.6.3-1 (22) is used in metagenome mode to predict ORFs and HMMER v3.3 (24) to identify homologs via the pVOG-database (25). All annotations are summarized in an interactive HTML file via chromoMap (26) (see Figure 3 B). Additionally, WtP classifies positive matches via sourmash and thus provides a taxonomic classification of already known phages.

Other features

All mandatory databases and containers are automatically downloaded when the workflow is started and stored for following executions. Additionally, the workflow can be pre-setup in order to subsequently analyse sequences offline. To support a transparent and reproducible mode of operation, the raw output of each tool is provided. Maximum execution stability is ensured by automatically excluding phage identification tools that cannot analyse the input data without failing the workflow (e.g. file too large, not the scope of an individual tool).

Dependencies and version control

WtP requires only the workflow management software Nextflow (16) and either Docker or Singularity (27) installed and configured on the system. The pipeline was tested on Ubuntu 16.04 LTS, Ubuntu 18.04 LTS and Windows 10 (via Windows Subsystem for Linux 2 using Docker). The installation process is described in detail at https://github.com/replikation/What_the_Phage. Each workflow release specifies the Nextflow version the code was tested on to avoid any version conflicts between the workflow code and the workflow manager at any time. A specific Nextflow version can always be directly downloaded as an executable file from https://github.com/nextflow-io/nextflow/releases.

121 Additionally, each container used in the workflow is tagged by the accompanying tool version,

122 pre-build and stored on hub.docker.com.

Results

To demonstrate the utility and performance of WtP, we analysed a described metagenome

data set (ENA Study PRJEB6941) using a local desktop machine (24 threads, 60 GB RAM,

Ubuntu 18.04.4 LTS) and WtP release v0.8.0. In this study (28), Kleiner *et al.* sequenced an

artificial microbiome sample which was produced via bacteria and phage cultures in mice

faeces (germ-free C57BL/6 J mice). The samples contained six different phages: P22, T3, T7,

φ6, M13 and φVPE25.

The raw read data set composed of eight samples was downloaded from the ENA server and

individually assembled via metaSPAdes v3.14 using the default settings (29). The resulting

eight assembly files (available at https://github.com/mult1fractal/WtP_test-

data/tree/master/01.Phage_assemblies) were analysed with WtP (release v0.8.0, default

settings). As WtP uses multiple tools for phage identification, an UpSet plot summarizes for

each sample the performance of all approaches executed successfully (see Figure 2 for

sample ERR575692 and Supplementary Dataset for all samples).

Figure 2: UpSet plot summarizing the identification performance of each tool for the sample

ERR575692. The total amount of identified phage-contigs per tool is shown in blue bars on

the left. Black bars visualize the number of contigs that each tool or tool combination has

uniquely identified. Each tool combination is shown below the barplot as a dot matrix.

The workflow was able to detect contigs that correspond to the phages P22, T3, T7 and VPE25

in all eight samples. In addition, the phage for the internal Illumina control (phiX174) was also

identified. The M13 phage (27) could not be identified as it was not assembled via

metaSPAdes due to the low read-abundance and low coverages (below 0.55x, determined by

Kleiner *et. al* (27)). The same applies to phage ϕ6 which was not detectable by Kleiner *et. al*

(27).

Unknown or novel phages, false-positive hits and tool disagreements are all plausible results

during the phage identification step. Therefore, WtP generates for each positive contig a visual

plot highlighting the identified phage genes and additionally a heatmap to visualize tool

agreements for each contig. While for some contigs all tools agreed, in many cases, only a

handful (e.g. 6 out of 12 in case of VPE25) could identify the phage positive contig (Figure 3

A). VPE25 was initially not taxonomically classified by WtP as it was not represented in the

taxonomic database at this time, however, the corresponding positive contig was annotated

with multiple different essential phage genes (Figure 3 B). Therefore, this unclassified but

positive contig was compared via blastn and matched against the genome sequence of VPE25

(PRJEB13004).

Figure 3: (A) Modified heatmap for assembly ERR575692 visualising the tool agreements per

phage positive contig and (B) a visual annotation of phage contigs and annotated protein-

coding genes via chromoMap. Annotations are coloured based on the categories of capsid

genes (orange), tail genes (red) and other phage genes (blue). Other contigs without either

capsid or tail genes have been removed for better readability. All unedited figures for each

sample can be found in the Supplementary Dataset.

WtP streamlines the detection of phage sequences across multiple tools and thus balancing

some drawbacks of tools (e.g. relying on updated databases, only identifying known phages).

This issue is best highlighted in Figure 3 A: P22 could not be identified by either VirNet or

DeepVirFinder and VPE25 could not be identified by DeepVirFinder, MetaPhinder (both

databases), sourmash, VirFinder and VirSorter without the virome option. However, besides

other phage genes (e.g. DNA ligase, helicase), capsid and tail genes could be clearly

annotated for both (Figure 3 B: P22 and VPE25). Furthermore, CheckV determined a phage

completeness score of over 99.99 for both P22 and VPE25 (Table 2).

In addition to the above-mentioned phages, WtP identified two more large contigs with capsid

and tail annotations and a taxonomic assignment pointing to a phage of *Salmonella enterica*

(contig NODE_5 and NODE_8). However, both contigs are labelled as prophages via CheckV

with an estimated completeness of over 99.99 %. These phage positive contigs match to

prophages *Salmonella enterica* (additionally confirmed via blastn search on NCBI) and they

were identified in six out of eight samples.

Table 2: Summary of the CheckV output for the sample ERR575692. All contigs with a

completeness > 10 % and a length > 5,000 bp are shown.

Phage name	Contig_id	Gene count	CheckV quality	Completeness	contig length [bp]
unknown1	NODE_5	107	Complete	100.0	114,288
unknown2	NODE_8	71	High-quality	100.0	63,147
VPE25	NODE_6	137	High-quality	99.99	86,514
phiX174	NODE_30	8	Medium-quality	89.31	5,441
T3	NODE_14	43	High-quality	93.36	37,380
T7	NODE_13	53	Complete	99.46	39,820
P22	NODE_12	67	Complete	100.0	41,715

Some limitations must be noted. No specialised phage assembly strategy or any cleanup step

were included during the assembly step. Therefore, some smaller mice host contigs (below

5,000 bp) produced false positive hits. However, these contigs were clearly distinguishable

after the "Annotation & Taxonomy" step both in CheckV and due to the lack of typical genes

related to e.g. capsid or tail proteins, showing the application of WtP also for contaminated

datasets

193 Conclusion

With the rise of metagenomics and the application of machine learning principles for virus

detection, several phage identification tools have been released over the last few years. All

these tools utilize different identification approaches, all with advantages and limitations. The

choice of the user of a certain tool often depends strongly on its usability and less on its

performance. While some tools already come with a packaging system such as Conda or a

containerized environment, there exists no general framework for their execution and

different filter parameters, database dependencies, and installation issues prevent many

potential users from using certain tools. At least one multitool approach was implemented

on a smaller scale by Ann C. Gregory *et al.* (comprising only VirFinder and VirSorter) (20).

The overarching goal of WtP is to identify positive phage sequences via a comprehensive

and extendable multitool approach that is easy to use across different platforms. After a WtP

run, the user is provided with sufficient processed data (such as tool performance

comparisons, taxonomic assessments, and annotation maps) to reliably work with the

identified sequences. The results support the decision-making process of the user if different

identification tools are not in agreement with each other (e.g.: see reported results for VPE25

phage). Thus, WtP streamlines the identification of phage sequence recognition across

multiple tools in a reproducible and scalable workflow to allow researchers to concentrate on

their scientific questions instead of software implementations.

212 Future directions

WtP is a workflow project that will be improved and extended as the modular approach and

containerisation simplify the integration of new tools. Besides the intended main application of

the workflow - the identification of phages - the workflow can be used to benchmark current

and novel virus detection tools in a continuous manner. The predictive scope of WtP can be

extended to other viruses (such as RNA viruses) and prophages by including future tools

specifically designed for such use cases and by adjusting filter and annotation steps.

Furthermore, we plan to support the input of raw long reads as an alternative to assemblies.

The versioning of WtP represents a well-functioning approach with tested and up-to-date

versions of the workflow. Thus, the correct functioning of the workflow is always guaranteed

and allows a reliable and fast identification of phage sequences.

223 Declarations

224 Availability

225 Source code: https://github.com/replikation/What_the_Phage

Supplementary Dataset: https://github.com/mult1fractal/WtP_test_profile_results

Sequence data used in this work is available at: https://github.com/mult1fractal/WtP_test-
data

Competing interest

None to declare.

Funding

This study was supported by the Federal Ministry of Education and Research (BMBF), Germany, grant numbers 01EO1502 and 13GW0423B.

Acknowledgements

We thank Michael Shamash towards helping to properly test and validate WtP on a SLURM based HPC with Singularity.

References

1. G MTP, B LS, L MES. Bacteriophage Genome Sequencing: A New Alternative to Understand Biochemical Interactions between Prokaryotic Cells and Phages. J Microb Biochem Technol. 2017;9(4):1–5.

2. Clokie MR, Millard AD, Letarov AV, Heaphy S. Phages in nature. Bacteriophage. 2011;1(1):31–45.

3. De Sordi L, Lourenço M, Debarbieux L. The Battle Within: Interactions of Bacteriophages and Bacteria in the Gastrointestinal Tract. Cell Host Microbe. 2019 13;25(2):210–8.

4. Reyes A, Semenkovich NP, Whiteson K, Rohwer F, Gordon JI. Going viral: next-generation sequencing applied to phage populations in the human gut. Nat Rev Microbiol. 2012 Sep;10(9):607–17.

5. Divya Ganeshan S, Hosseinidoust Z. Phage Therapy with a Focus on the Human Microbiota. Antibiotics [Internet]. 2019 Aug 27 [cited 2020 May 25];8(3). Available from: https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6783874/

6. Sutton TDS, Hill C. Gut Bacteriophage: Current Understanding and Challenges. Front Endocrinol [Internet]. 2019 [cited 2020 May 23];10. Available from: https://www.frontiersin.org/articles/10.3389/fendo.2019.00784/full

7. Hatfull GF, Hendrix RW. Bacteriophages and their Genomes. Curr Opin Virol. 2011 Oct 1;1(4):298–303.

8. Beaulaurier J, Luo E, Eppley J, Uyl PD, Dai X, Turner DJ, et al. Assembly-free single-molecule nanopore sequencing recovers complete virus genomes from natural microbial communities [Internet]. Microbiology; 2019 Apr [cited 2020 Jun 10]. Available from: http://biorxiv.org/lookup/doi/10.1101/619684

9. Overholt WA, Hölzer M, Geesink P, Diezel C, Marz M, Küsel K. Inclusion of Oxford Nanopore long reads improves all microbial and phage metagenome-assembled genomes from a complex aquifer system. bioRxiv. 2019 Dec 19;2019.12.18.880807.

10. Kieft K, Zhou Z, Anantharaman K. VIBRANT: Automated recovery, annotation and

curation of microbial viruses, and evaluation of virome function from genomic
sequences. bioRxiv. 2019 Nov 26;855387.

11. Roux S, Enault F, Hurwitz BL, Sullivan MB. VirSorter: mining viral signal from microbial
genomic data. PeerJ. 2015 May 28;3:e985.

12. Brown C, Irber L. sourmash: a library for MinHash sketching of DNA. J Open Source
Softw. 2016 Sep 14;1(5):27.

13. Ren J, Ahlgren NA, Lu YY, Fuhrman JA, Sun F. VirFinder: a novel k-mer based tool for
identifying viral sequences from assembled metagenomic data. Microbiome. 2017 Jul
6;5(1):69.

14. Amgarten D, Braga LPP, da Silva AM, Setubal JC. MARVEL, a Tool for Prediction of
Bacteriophage Sequences in Metagenomic Bins. Front Genet [Internet]. 2018 [cited
2020 May 1];9. Available from:
https://www.frontiersin.org/articles/10.3389/fgene.2018.00304/full

15. Fang Z, Tan J, Wu S, Li M, Xu C, Xie Z, et al. PPR-Meta: a tool for identifying phages
and plasmids from metagenomic fragments using deep learning. GigaScience [Internet].
2019 Jun 20 [cited 2020 May 1];8(6). Available from:
https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6586199/

16. Di Tommaso P, Chatzou M, Floden EW, Barja PP, Palumbo E, Notredame C. Nextflow
enables reproducible computational workflows. Nat Biotechnol. 2017 11;35(4):316–9.

17. Shen W, Le S, Li Y, Hu F. SeqKit: A Cross-Platform and Ultrafast Toolkit for FASTA/Q
File Manipulation. PLoS ONE [Internet]. 2016 Oct 5 [cited 2020 Jun 10];11(10). Available
from: https://www.ncbi.nlm.nih.gov/pmc/articles/PMC5051824/

18. Gregory AC, Zayed AA, Conceição-Neto N, Temperton B, Bolduc B, Alberti A, et al.
Marine DNA Viral Macro- and Microdiversity from Pole to Pole. Cell. 2019
May;177(5):1109-1123.e14.

19. Ren J, Song K, Deng C, Ahlgren NA, Fuhrman JA, Li Y, et al. Identifying viruses from
metagenomic data by deep learning. ArXiv180607810 Q-Bio [Internet]. 2018 Jun 20
[cited 2020 May 1]; Available from: http://arxiv.org/abs/1806.07810

20. Jurtz VI, Villarroel J, Lund O, Larsen MV, Nielsen M. MetaPhinder—Identifying
Bacteriophage Sequences in Metagenomic Data Sets. PLOS ONE. 2016 Sep
29;11(9):e0163111.

21. Abdelkareem AO, Khalil MI, Elaraby M, Abbas H, Elbehery AHA. VirNet: Deep attention
model for viral reads identification. In: 2018 13th International Conference on Computer
Engineering and Systems (ICCES). 2018. p. 623–6.

22. Hyatt D, Chen G-L, LoCascio PF, Land ML, Larimer FW, Hauser LJ. Prodigal:
prokaryotic gene recognition and translation initiation site identification. BMC
Bioinformatics. 2010 Mar 8;11(1):119.

23. Zheng T, Li J, Ni Y, Kang K, Misiakou M-A, Imamovic L, et al. Mining, analyzing, and
integrating viral signals from metagenomic data. Microbiome. 2019 Mar 19;7(1):42.

24. Wheeler TJ, Eddy SR. nhmmer: DNA homology search with profile HMMs.
Bioinformatics. 2013 Oct 1;29(19):2487–9.

25. Grazziotin AL, Koonin EV, Kristensen DM. Prokaryotic Virus Orthologous Groups
(pVOGs): a resource for comparative genomics and protein family annotation. Nucleic
Acids Res. 2017 Jan 4;45(D1):D491–8.

26. chromoMap-An R package for Interactive Visualization and Annotation of Chromosomes
[Internet]. [cited 2020 May 7]. Available from: https://cran.r-
project.org/web/packages/chromoMap/vignettes/chromoMap.html

27. Boettiger C. An introduction to Docker for reproducible research. ACM SIGOPS Oper
Syst Rev. 2015 Jan 20;49(1):71–79.

28. Kleiner M, Hooper LV, Duerkop BA. Evaluation of methods to purify virus-like particles
for metagenomic sequencing of intestinal viromes. BMC Genomics. 2015 Jan 22;16:7.

29. Nurk S, Meleshko D, Korobeynikov A, Pevzner PA. metaSPAdes: a new versatile
metagenomic assembler. Genome Res. 2017 May;27(5):824–34.