MacaquePose: A novel 'in the wild' macaque monkey pose dataset for markerless motion capture

Rollyn Labuguen[1*], Jumpei Matsumoto[2*], Salvador Negrete[1], Hiroshi Nishimaru[2], Hisao
Nishijo[2], Masahiko Takada[3], Yasuhiro Go[4,5], Ken-ichi Inoue[3], Tomohiro Shibata[1*]

[1]Department of Human Intelligence Systems, Graduate School of Life Science and Systems
Engineering, Kyushu Institute of Technology, Kitakyushu City, Fukuoka, Japan

[2]Systems Emotional Science, University of Toyama, Toyama, Japan

[3]Systems Neuroscience Section, Department of Neuroscience, Primate Research Institute, Kyoto
University, Inuyama, Aichi, Japan

[4]Cognitive Genomics Research Group, Exploratory Research Center on Life and Living Systems
(ExCELLS) National Institutes of Natural Sciences, Okazaki, Aichi, Japan

[5]Department of System Neuroscience, National Institute for Physiological Sciences, Okazaki, Aichi,
Japan

* Correspondence:
Rollyn Labuguen
labuguen-rollyn@edu.brain.kyutech.ac.jp

Jumpei Matsumoto
jm@med.u-toyama.ac.jp

Tomohiro Shibata
tom@brain.kyutech.ac.jp

Keywords: non-human primate, deep learning, pose estimation, large-scale dataset, behavior
analysis

Abstract

Video-based markerless motion capture permits quantification of an animal's pose and motion, with
a high spatiotemporal resolution in a naturalistic context, and is a powerful tool for analyzing the
relationship between the animal's behaviors and its brain functions. Macaque monkeys are excellent
non-human primate models, especially for studying neuroscience. Due to the lack of a dataset
allowing training of a deep neural network for the macaque's markerless motion capture in the
naturalistic context, it has been challenging to apply this technology for macaques-based studies. In
this study, we created MacaquePose, a novel open dataset with manually labeled body part positions
for macaques in naturalistic scenes, consisting of >13,000 images, refined by researchers. We show
that the pose estimation performance of an artificial neural network trained with the dataset is close
to that of a human-level. The MacaquePose will provide a platform for innovative behavior analysis
for non-human primate.

1   Introduction

Behavior analyses are fundamental for understanding brain functions and malfunctions (Datta et al.,
2019). Motion capture technologies allow the quantification of animal's pose and motion with a high
spatiotemporal resolution enabling the study of the relationship between various brain functions and
behaviors (Vargas-Irwin et al., 2008; Nagasaka et al., 2011; Mathis et al., 2020). However, attaching
the physical markers for the motion capture is often not practical for animal studies, as the markers
themselves disturb/change the subject's behavior (Nakamura et al., 2016; Mathis et al., 2018; Berger
et al., 2020). Thanks to recent advances in machine vision using deep learning, the video-based
markerless motion capture has been developed to a level permitting practical use (Mathis et al.,
2020), in which an artificial neural network predicts the location of body parts in a video without the
requirement for physical markers, and enabled successful behavioral studies in rodents (e.g., Dooley
et al., 2020; Cregg et al., 2020; Mathis et al., 2020). Macaque monkeys are an important non-human
primate model, particularly in the field of neuroscience (Kalin et al., 2006; Capitanio et al., 2008;
Nelson et al., 2008; Watson et al., 2012). The robust markerless motion capture using deep learning
will allow studying various complex naturalistic behaviors in detail, and permit investigation of
relationship between naturalistic behaviors and brain functions (Datta et al., 2019; Mathis et al.,
2020). Analyzing naturalistic behavior is crucial in brain-science, since the brain evolved from
natural behaviors, and various behaviors, such as complex social behaviors, can be observed only in
the natural situations (Datta et al., 2019; Mathis et al., 2020). The deep neural networks usually
require manually labeled body parts positions in thousands of pictures to learn prediction of the body
parts positions in an arbitrary picture. However, such a large labeled dataset for macaque monkeys in
the naturalistic scene has not been developed. The lack of this dataset limits the markerless motion
capture technology applications for macaque studies (Berger et al., 2020; Bala et al., 2020)

To overcome this limitation, we created a novel open dataset of the manually labeled body part
positions (keypoints) for macaques in naturalistic scenes, consisting of greater than 13,000 pictures.
We also validated the usefulness of the dataset by training and evaluating an artificial neural network
with the dataset. The results revealed that the keypoint estimation performance of the trained network
was close to that of a human level. Our dataset will provide basis for markerless motion capture on
the naturalistic behaviors.

2   Materials and Methods

2.1   Image Data Collection

A total of 13,083 images of macaque monkeys were obtained from the internet or were captured in
zoos or the Primate Research Institute of Kyoto University. Images on the internet were obtained
through Google Open Images (https://storage.googleapis.com/openimages/web/index.html) by
searching for images with a 'macaque' tag. Pictures zoos were acquired from the outside of the
breeding areas, with granted permission provided by the zoos. Images in the Primate Research
Institute of Kyoto University were taken in the breeding fields without causing any specific
interventions to the monkeys. The photo capturing in the institute was approved by the Animal
Welfare and Animal Care Committee of the Primate Research Institute of Kyoto University and
conducted in accordance with the Guidelines for the Care and Use of Animals of the Primate
Research Institute, Kyoto University.

2.2   Image Data Annotation

The positions of 17 keypoints (nose and left and right ears, eyes, shoulders, elbows, wrists, hips,
knees, and ankles) and instance segmentation for each monkey in each of the pictures were first
annotated by non-researchers employed by Baobab Inc. (Chiyoda-ku, Japan). As further expertise

was required for high-quality monkey annotation, the keypoint labels were then further refined with
eight researchers working with macaques at Kyoto University and the University of Toyama, using a
custom-made Python script. The keypoints were labeled according to the following guidelines: 1)
The keypoints of the limbs (shoulder, elbow, wrist, hip, knee, and ankle) should be located at the
center of the joint rotation. 2) Ear, eye, and nose keypoints should be located at the entrance of the
ear canal, the center of eye ball, in the middle position between the entrances of the two nostrils,
respectively. 3) A keypoint was annotated, if its position was predictable despite being occluded,
except for ears, eyes, and nose facing the back side of the picture. The resultant labels were
compatible with the Microsoft COCO Keypoint Dataset (Lin et al., 2014).

2.3   Performance evaluation of an artificial neural network trained with the present dataset

To validate the present dataset, we trained an artificial neural network estimating keypoint positions
by using the DeepLabCut algorithm (Mathis et al., 2018). Briefly, DeepLabCut is a versatile and
straightforward algorithm in which the 50-layer ResNet pre-trained for the ImageNet object
recognition task (He et al., 2016) is transferred for the keypoint estimation by replacing the
classification layer at the output of the ResNet with the deconvolutional layers. DeepLabCut is a
widely used algorithm in the field of neuroscience as it requires a relatively small number of training
data, has user-friendly interface associated with the algorithm, and has a proven good performance
(Nath et al., 2019). Due to DeepLabCut (version 2.1.6) currently not supporting the estimation of
keypoints in multiple animals in a picture, we first generated single monkey images by masking the
monkeys in the images except for one monkey and used these masked images as the input. Some
monkey images in the dataset were excluded due to technical reasons (e.g., a keypoint of one monkey
is covered by the mask of the other monkeys). Then, the images were resized to adjust the length to
640 pixels while maintaining the images aspect ratio, before inputting it into the network. In total,
15,476 single monkey images were generated. Among the images, 14,697 single monkey images
were used to train the network and the rest (779 images) were used to evaluate the trained network.
The network is trained up to a million iterations. The training took 20 hours to complete on a Nvidia
GTX 1080 Ti graphics processing unit workstation.

The keypoint prediction by the trained network was evaluated. A predicted keypoint with confidence
level > 0.4 was defined to be detected. First, minor cases showing the keypoint(s) detected outside
the monkey segment were eliminated. True positive, true negative, false positive, and false negative
detections were counted. A keypoint was defined as a correct detection by the network (true positive
detection) if there was the corresponding ground truth keypoint in the same image, regardless of its
location in the image. For true positive cases, the Euclidean distance between the predicted and
ground truth position was calculated as the error of position estimation. The error value represented
the normalized value with respect to the length of the monkey's bounding box due to variations in the
size of the monkey in the images. To check the accuracy of the predicted pose, the root-mean-square
error (RMSE) was also calculated with all keypoints in each image (Mathis et al.2018). To evaluate
the error values of the keypoint position predictions, we investigated human variability by calculating
the errors between the keypoint positions annotated by two humans. Finally, among the true positive
cases, numbers of limb keypoints misattributed as the homologous keypoint on another limb (e.g.,
left wrist misattributed as right wrist, left ankle, or right ankle) are also counted. Specifically, i-th
keypoint were defined as being misattributed to a homologous j-th keypoint on another limb, if the
keypoint satisfies both of the following two conditions: 1) the normalized position error of the i-th
keypoint was > 20%; 2) the ground truth positions of j-th keypoint was closest to the predicted
position of i-th keypoint among the ground truth positions of homologous keypoints.

3   Results

In total, the present data set contains keypoints and instance segmentation of 16,393 monkeys in 13,083 pictures. Each picture captures 1 to 5 monkeys; 10,630 pictures with a single monkey and 2453 pictures with multiple monkeys (Figure 1).

To validate the dataset, we trained an artificial network with 14,697 single monkey images in the dataset using the DeepLabCut algorithm (Mathis et al.2018). The performance of the keypoint prediction of the trained network was evaluated on 779 test images unseen during training. Figure 2 shows examples of the keypoint predictions (also see Supplementary Video 1 for keypoint prediction in videos). Among 779 images, 24 images had keypoint(s) detected outside the target monkey. Most of them (17 images) were due to imperfect masks of the other monkeys in the picture (Supplementary Figure 1). The 'out of monkey' cases were removed from the analysis.

We investigated the performance of keypoint detection (judging whether a keypoint exists anywhere in the picture or not) of the trained network (Supplementary Table 1). Both precision and recall of the keypoint detection were approximately 90% in most of the keypoints, suggesting good detection performance.

To further investigate the accuracy of the detected keypoints, the error of predicted position was calculated for each keypoint (Figure 3, gray bar). The prediction's RMSE values ($6.02 \pm 0.18\%$; mean $\pm$ s.e.m) were comparable to those between the positions manually labeled by two different people ($5.74 \pm 0.16\%$; $p = 0.250$, student's t-test), suggesting that the trained network's performance in the keypoint position estimation was close to the human level. The effect of the label refinement by researchers was also examined. The error values for the dataset before the refinement were calculated as previously mentioned. The analyses revealed that the averaged RMSE values after the refinement ($6.02 \pm 0.18\%$) were significantly smaller than the one before the refinement ($7.83 \pm 0.23\%$; $p = 9.13 \times 10^{-10}$, Student's t-test; see Supplementary Figure 2 for the error value of each keypoint). The result suggests that the network trained with the dataset refined by the researchers predicted the keypoint more consistently.

In some cases, we observed that the predicted positions of monkey's keypoints on a limb were located on homologous keypoints on another limb (Figure 2h, see also Supplementary Video 1).

We then quantified the frequency of such misattribution errors (Table 2). The misattribution errors were relatively frequent in the distal keypoints (elbow, knee, wrist, and ankle), especially on the hind limbs. The total number of images having at least one misattribution error was 114 (15%). The result shows that there is still room for improvement, although the RMSE indicates human-level performance.

4   Discussions

In this study, we created a novel large dataset of labeled keypoints of macaque monkeys (Figure 1, Table 1). The keypoint estimation performance of the neural network trained with the dataset was close to that of human level (Figure 2, Figure 3, and Supplementary Video 1), demonstrating the usefulness of the present dataset. We also found a significant improvement of the network prediction after the label refinement by researchers using macaques (Supplementary Figure 2), suggesting that the refinement successfully enhanced the quality of the dataset. Although we tested only single monkey images due to the limitation of the algorithm, the present dataset should be useful to train/test the network for multi-animal motion capture. The label formats in the present dataset are

compatible with those used in the COCO dataset for humans (Lin et al., 2014), allowing users to try a
direct application of algorithms developed for human motion capture. A recent study also proposed a
similarly sized labeled dataset of rhesus monkeys (Bala et al., 2020). In the study, they captured
freely moving monkeys in a 2.5 m cubic cage with 62 cameras surrounding the cage. The multi-
camera system allows to reconstruct 3D pose after manually labeling images simultaneously captured
from 3-4 views. Interestingly, the reconstructed 3D pose is projected to the other around 60 views
and enables automatically labeling the images from all the views. This cross-view data augmentation
allowed them to get labels of around 200,000 monkey images with 33,192 images labeled manually.
The critical difference between the two datasets is that pictures in their dataset were taken in a single
laboratory environment, our dataset consists of pictures taken in many different naturalistic
environments. Thanks to the `in-the-wild' aspect of the collected pictures, the present data set has rich
variations in pose, body shape, lighting, and background in naturalistic contexts. The rich variation
will help to train and test artificial neural networks with high generalizability (Mathis et al., 2019).
Thus, the two datasets will compensate each other to train or test better neural networks in future
studies. As the dataset formats (i.e., which keypoints are labeled) were slightly different among the
two datasets, some additional efforts are necessary to combine or compare these two datasets
directly.

To understand how the brain generates our behavior, analyzing naturalistic behaviors is crucial. The
brain evolved from natural behaviors, and various behaviors, such as complex social behaviors, can
be observed only in the natural situations (Datta et al., 2019; Mathis et al., 2020). The high-resolution
spatiotemporal data obtained with the markerless motion capture will also aid in understanding brain
dynamics underlying the behavior (Berger et al., 2020). Specific posture and motion are informative
for studying animals' emotions and intension (Nakamura et al., 2016), and the motor functions
(Berger et al., 2020). Furthermore, the automatic and long-term analyses of naturalistic behavior from
a large number of subjects permit new data-driven approaches to find unusual behaviors,
personalities and, underlying genetic and neural mechanisms (Vogelstein et al., 2014; De Chaumont
et al., 2018). For instance, the recently discovered autistic traits exhibited by macaque monkeys
(Yoshida et al., 2016) was identified by such a behavioral observation. Thus, the markerless motion
capture for macaque monkeys developed based on the present dataset will be of great use for many
neuroscience studies.

The performance evaluation of the network trained with the present dataset revealed that there is still
room for improvement regarding the misattribution of the limb keypoints (Figure 2h, Table 2),
although the RMSE indicates the human-level performance (Figure 3). The DeepLabCut algorithm
(Mathis et al., 2018) used in the present evaluation does not explicitly utilize the prior knowledge
about the animal's body, whereas the other algorithms were suggested to use the connection between
keypoints (Insafutdinov et al., 2016; Cao et al., 2017) or 3D shape of the subject (Biggs et al., 2018;
Zuffi et al., 2019). Such utilization of the prior knowledge may help to improve the estimation.
However, even the state-of-the-art human motion capture algorithms also have difficulties in
analyzing the pictures with severe occlusion or crowded people (Mathis et al., 2020). Due to severe
occlusions more frequently being observed in naturalistic behaviors in monkeys than in humans,
better algorithms may be required in the future. An alternative approach for the improvement will be
enriching the dataset itself. Although we tried to capture many different poses in various contexts, the
sampling was biased to the frequently observed poses. Adding data selectively for the rarely
observed poses may improve the performance of the trained network. Combining with the other
monkey datasets made for laboratory environments (Berger et al., 2020; Bala et al., 2020) or transfer
learning of the network trained with the human dataset (Sanakoyeu et al., 2020) are also interesting
approaches. Nevertheless, in practice, the performance of the network shown in the present study

may be sufficient for many applications, after appropriate temporal filtering of the motion data
(Berman et al., 2014; Nath et al., 2019) and additional training with the labels made on the pictures in
the target experiment (Mathis et al., 2019).

The keypoint position estimation in a 2D video is not the aim of the behavior analysis. In addition,
the researchers would need to reconstruct the 3D pose and motion of the animals (Nath et al., 2019;
Bala et al., 2020) and label the behaviors that the animals are exhibiting (Datta et al., 2019). The
post-processing methods for converting the high-dimensional motion data into meaningful and
interpretable behavioral events and parameters of a single animal or interacting animals are still
under active developments (Berman et al., 2014; Datta et al., 2019; Dviwedi et al., 2020). The present
dataset will permit simple access to motion data of macaques in various environments. Furthermore,
this could accelerate the development of post-processing method by accumulating the motion data
associated with various natural behaviors.

5   Conclusion

225 We created a novel large open dataset of keypoint labels of macaques in naturalistic scenes. The
226 dataset will be instrumental to train/test the neural networks for markerless motion capture of the
227 macaques and developments of the algorithms for the networks, contributing to the establishment of
228 an innovative platform of behavior analysis for non-human primates for neuroscience and medicine,
229 as well as the other fields using macaques (Carlsson et al., 2004).

6   Conflict of Interest

231 The authors declare that the research was conducted in the absence of any commercial or financial
232 relationships that could be construed as a potential conflict of interest.

7   Author Contributions

234 RL, TS, JM, KI, YG, HNishij, and HNishim designed this research. JM, KI, TS, RL, and MT created
235 the dataset. RL, SN, JM, TS evaluated the performance of the neural network trained with the dataset.
236 All the authors discussed the results and commented on the manuscript, read and approved the final
237 manuscript.

8   Funding

239 This work was supported by the Cooperative Research Program of Primate Research Institute, Kyoto
240 University, the Grant-in-Aid for Scientific Research from Japan Society for the Promotion of Science
241 (No. 16H06534 and 19H04984), and the grant of Joint Research by the National Institutes of Natural
242 Sciences (NINS) (NINS Program No. 01111901).

9   Acknowledgments

244 We would like to thank Yu Yang, Yang Meng, Kei Kimura, Yukiko Otsuka, Andi Zheng, Jungmin
245 Oh, Gaoge Yan, and Yuki Kinoshita for manually labeling and refining the keypoints.

10   References

Bala PC, Eisenreich BR, Yoo SBM, Hayden BY, Park HS, Zimmermann J (2020)
OpenMonkeyStudio: Automated Markerless Pose Estimation in Freely Moving Macaques. bioRxiv.

Berger M, Agha NS, Gail A (2020) Wireless recording from unrestrained monkeys reveals motor
goal encoding beyond immediate reach in frontoparietal cortex. Elife. 2020 May 4;9. pii: e51322.
doi: 10.7554/eLife.51322.

Berman GJ, Choi DM, Bialek W, haevitz JW (2014) Mapping the stereotyped behaviour of freely-
moving fruit flies. J R Soc Interface. 2014 Oct 6;11(99). pii: 20140672. doi: 10.1098/rsif.2014.0672.

Biggs B, Roddick T, Fitzgibbon A, Cipolla R (2018) Creatures great and SMAL: Recovering the
shape and motion of animals from video. ACCV 2018: 14th Asian Conference on Computer Vision.
pp 3-19

Cao Z, Simon T, Wei SE, Sheikh Y (2017). Realtime multi-person 2d pose estimation using part
affinity fields. In Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition
(pp. 7291-7299).

Capitanio JP, Emborg ME (2008) Contributions of non-human primates to neuroscience research.
Lancet. 2008 Mar 29;371(9618):1126-35. doi: 10.1016/S0140-6736(08)60489-4.

Carlsson HE, Schapiro SJ, Farah I, Hau J (2004). Use of primates in research: a global overview. Am
J Primatol. 2004;63(4):225‐237. doi:10.1002/ajp.20054

de Chaumont F, Ey E, Torquet N, Lagache T, Dallongeville S, Imbert A, Legou T, Le Sourd AM,
Faure P, Bourgeron T, Olivo-Marin JC (2019). Live Mouse Tracker: real-time behavioral analysis of
groups of mice. Nat Biomed Eng 3, 930–942 (2019). https://doi.org/10.1038/s41551-019-0396-1

Cregg JM, Leiras R, Montalant A, Wanken P, Wickersham IR, Kiehn O. Brainstem neurons that
command mammalian locomotor asymmetries [published online ahead of print, 2020 May 11]. Nat
Neurosci. 2020;10.1038/s41593-020-0633-7. doi:10.1038/s41593-020-0633-7.

Datta SR, Anderson DJ, Branson K, Perona P, Leifer A (2019) Computational Neuroethology: A Call
to Action. Neuron. 2019 Oct 9;104(1):11-24. doi: 10.1016/j.neuron.2019.09.038.

Dooley JC, Glanz RM, Sokoloff G, Blumberg MS. Self-Generated Whisker Movements Drive State-
Dependent Sensory Input to Developing Barrel Cortex [published online ahead of print, 2020 May
6]. Curr Biol. 2020; S0960-9822(20)30559-5. doi:10.1016/j.cub.2020.04.045

Dviwedi SK, Ngeo JG, Shibata T (2020) Extraction of Nonlinear Synergies for Proportional and
Simultaneous Estimation of Finger Kinematics. IEEE Transactions on Biomedical Engineering,
IEEEXplore early access page, 2020.1.16

He K, Zhang X, Ren S, Sun, J (2016) Deep residual learning for imagerecognition. in Proceedings of
the IEEE Conference on Computer Vision and Pattern Recognition 770–778. (IEEE, Piscataway, NJ,
USA, 2014)

Insafutdinov E, Pishchulin L, Andres B, Andriluka M, Schiele B (2016) DeeperCut: a deeper,
stronger, and faster multi-person pose estimation model. in European Conference on Computer
Vision 34–50 (Springer, New York, 2016).

Kalin NH, Shelton SE (2006) Nonhuman primate models to study anxiety, emotion regulation, and
psychopathology. Ann N Y Acad Sci. 2003 Dec;1008:189-200.

Lin TY, Maire M, Belongie S, Hays J, Perona P, Ramanan D, et~al. (2014) Microsoft coco: Common
objects in context. In: European conference on computer vision. Springer; 2014. pp 740-755

Mathis A, Mamidanna P, Cury KM, Abe T, Murthy VN, Mathis MW, Bethge M (2018)
DeepLabCut: markerless pose estimation of user-defined body parts with deep learning. Nat
Neurosci. 2018 Sep;21(9):1281-1289. doi: 10.1038/s41593-018-0209-y. Epub 2018 Aug 20.

Mathis MW, Mathis A (2020) Deep learning tools for the measurement of animal behavior in
neuroscience. Curr Opin Neurobiol. 2020 Feb;60:1-11. doi: 10.1016/j.conb.2019.10.008. Epub 2019
Nov 29.

Mathis A, Yüksekgönül M, Rogers B, Bethge M, Mathis MW (2019) Pretraining boosts out-of-
domain robustness for pose estimation. arXiv:1909.11229

Nagasaka Y, Shimoda K, Fujii N (2011) Multidimensional recording (MDR) and data sharing: an
ecological open research and educational platform for neuroscience. PLoS One. 2011;6(7):e22561.
doi: 10.1371/journal.pone.0022561. Epub 2011 Jul 21.

Nakamura T, Matsumoto J, Nishimaru H, Bretas RV, Takamura Y, Hori E, Ono T, Nishijo H (2016)
A Markerless 3D Computerized Motion Capture System Incorporating a Skeleton Model for
Monkeys. PLoS One. 2016 Nov 3;11(11):e0166154. doi: 10.1371/journal.pone.0166154. eCollection
2016.

Nath T, Mathis A, Chen AC, Patel A, Bethge M, Mathis MW (2019) Using DeepLabCut for 3D
markerless pose estimation across species and behaviors. Nat Protoc. 2019 Jul;14(7):2152-2176. doi:
10.1038/s41596-019-0176-0. Epub 2019 Jun 21.

Nelson EE, Winslow JT (2008) Non-human primates: model animals for developmental
psychopathology. Neuropsychopharmacology. 2009 Jan;34(1):90-105. doi: 10.1038/npp.2008.150.
Epub 2008 Sep 17.

Sanakoyeu A, Khalidov V, McCarthy MS, Vedaldi A, Neverova N (2020) Transferring Dense Pose
to Proximal Animal Classes. arXiv preprint arXiv:200300080. 2020

Vargas-Irwin CE, Shakhnarovich G, Yadollahpour P, Mislow JM, Black MJ, Donoghue JP (2008)
Decoding complete reach and grasp actions from local primary motor cortex populations. J Neurosci.
2010 Jul 21;30(29):9659-69. doi: 10.1523/JNEUROSCI.5443-09.2010.

Vogelstein JT, Park Y, Ohyama T, Kerr RA, Truman JW, Priebe CE, Zlatic M (2014) Discovery of
brainwide neural-behavioral maps via multiscale unsupervised structure learning. Science. 2014 Apr
25;344(6182):386-92. doi: 10.1126/science.1250298. Epub 2014 Mar 27.

Watson KK, Platt ML (2012) Of mice and monkeys: using non-human primate models to bridge
mouse- and human-based investigations of autism spectrum disorders. J Neurodev Disord. 2012 Jul
30;4(1):21.

Yoshida K, Go Y, Kushima I, Toyoda A, Fujiyama A, Imai H, Saito N, Iriki A, Ozaki N, Isoda M
(2016) Single-neuron and genetic correlates of autistic behavior in macaque. Sci Adv. 2016 Sep
21;2(9):e1600558. eCollection 2016 Sep.

Zuffi S, Kanazawa A, Berger-Wolf T, Black MJ (2019) Three-D Safari: Learning to Estimate Zebra
Pose, Shape, and Texture from Images "In the Wild". International Conference on Computer Vision,
October 2019

Data Availability Statement

The dataset for this study will be released when the manuscript is accepted.

Figures

Figure 1. Examples of pictures and labels in the present dataset

Figure 2. Examples of test image predictions. Test images (left), the ground truth keypoint positions
(center) and the position predicted by the artificial neural network trained with the present dataset
using the DeepLabCut algorithm (right; a-h). The inset (top right corner) shows color codes of the
keypoints. Red arrows in h indicate a misattribution error.

Figure 3. Averaged error of predicted (gray) and manual labeled (white) positions of each keypoint
comparing with the ground truth positions. Error bars represent standard error of the mean (s.e.m.)

Tables

Table 1. The number of pictures and monkeys in the present dataset from each source.

Source	Monkey Species	No. of Pictures	No. of Monkeys
Toyama Municipal Family Park Zoo	Japanese Macaque	3784	4952
Itozu no Mori Zoological Park	Japanese Macaque	1312	1622
Primate Research Institute	Japanese Macaque	1641	2131
Inokashira Park Zoo	Rhesus Macaque	2747	3203
Tobu Zoo	Rhesus Macaque	2461	2755
Google Open Images	Various	1138	1730
Total		13083	16393

339   Table 2. Number of the misattribution errors. L-R incorrect referring to left or right predicted
340   keypoint was incorrect; F-H switch, forelimb or hindlimb label was incorrect.

Keypoint pairs	Correct	L-R incorrect	F-H incorrect	L-R and F-H incorrect	Total
Shoulder	1225	5	1	3	9
Hip	1062	7	2	3	12
Elbow	1134	11	5	4	20
Knee	1066	45	11	3	59
Wrist	1049	14	7	6	27
Ankle	1045	29	11	5	45

Input	Ground truth	Prediction