١

٦ **Adaptive learning through temporal dynamics of state representation**

٨ Niloufar Razmi[1,2], Matthew R. Nassar[1,2]

١٠ [1]Robert J. & Nancy D. Carney Institute for Brain Science, Brown University, Providence RI 02912-1821, USA

١١ [2]Department of Neuroscience, Brown University, Providence RI 02912-1821, USA

Acknowledgments

We thank Linda Yu, Robert Wilson, Olga Lositsky, Romy Frömer and Cristian Buc Calderon for helpful
discussion and comments. This work was supported by R00AG054732 to M.R.N.

Competing interests

The authors declare that no competing interests exist.

Corresponding Author: Matthew Nassar (matthew_nassar@brown.edu)

Abstract

People adjust their learning rate rationally according to local environmental statistics and calibrate such
adjustments based on the broader statistical context. To date, no theory has captured the observed range of
adaptive learning behaviors or the complexity of its neural correlates. Here, we attempt to do so using a
neural network model that learns to map an internal context representation onto a behavioral response via
supervised learning. The network shifts its internal context upon receiving supervised signals that are
mismatched to its output, thereby changing the "state" to which feedback is associated. A key feature of
the model is that such state transitions can either increase learning or decrease learning depending on the
duration over which the new state is maintained. Sustained state transitions that occur after changepoints
facilitate faster learning and mimic network reset phenomena observed in the brain during rapid learning.
In contrast, state transitions after one-off outlier events are short-lived, thereby limiting the impact of
outlying observations on future behavior. State transitions in our model provide the first mechanistic
interpretation for bidirectional learning signals, such the p300, that relate to learning differentially
according to the source of surprising events and may also shed light on discrepant observations regarding
the relationship between transient pupil dilations and learning. Taken together, our results demonstrate that
dynamic latent state representations can afford normative inference and provide a coherent framework for
understanding neural signatures of adaptive learning across different statistical environments.

Significance Statement:

How humans adjust their sensitivity to new information in a changing world has remained largely an open
question. Bridging insights from normative accounts of adaptive learning and theories of latent state
representation, here we propose a feed-forward neural network model that adjusts its learning rate online
by controlling the speed of transitioning its internal state representations. Our model proposes a mechanistic
framework for explaining learning under different statistical contexts, explains previously observed
behavior and brain signals, and makes testable predictions for future experimental studies.

Introduction

People and animals are often required to update behavior in the face of new information. While standard
supervised learning or reinforcement learning models have shown great success in performing particular
tasks and explaining general trends in behavior, they lack the flexibility of biological systems, which seem
to adjust the influence of new information dynamically, especially in environments that evolve over time
(Behrens, Woolrich, Walton, & Rushworth, 2007; Donahue & Lee, 2015; Farashahi, Donahue, Hayden,
Lee, & Soltani, 2019; Li, Nassar, Kable, & Gold, 2019; Massi, Donahue, & Lee, 2018; Nassar & Gold,
2010). Recent advances in understanding these adaptive learning behaviors have relied on probabilistic
modeling to better understand the computational problems that organisms face for survival in their everyday
life (Soltani & Izquierdo, 2019).

Bayesian probability theory has been extensively applied to describing adaptive learning algorithms in
changing environment to provide normative accounts for learning behavior. Probabilistic models prescribe
learning that is more rapid during periods of environmental change and slower during periods of stability

(Adams & MacKay, 2007; Behrens et al., 2007; Nassar & Gold, 2010; Wilson, Nassar, & Gold, 2010).
These models have provided insight into why people seem to adjust learning according to their level of
uncertainty (Browning, Behrens, Jocham, O'Reilly, & Bishop, 2015; Muller, Mars, Behrens, & O'Reilly,
2019) and the probability with which an observation reflects a changepoint (Adams & MacKay, 2007;
Nassar, Wilson, Heasly, & Gold, 2010). In this framework, the human brain is viewed as implementing an
optimal learning algorithm that embodies the statistical properties of the world it operates in (Meyniel &
Dehaene, 2017; O'Reilly, 2013).

While probabilistic modeling provides an ideal observer account for many of the adjustments in learning
rate observed in humans and animals (Behrens et al., 2007; Nassar, Bruckner, & Frank, 2019; Nassar &
Gold, 2010), it has thus far failed to clarify the underlying neural mechanisms. One issue is that exact
Bayesian inference can be closely approximated by many qualitatively different algorithms (Bernacchia,
Seo, Lee, & Wang, 2011; Farashahi et al., 2017; Iigaya, 2016; Mathys, Daunizeau, Friston, & Stephan,
2011; Nassar et al., 2010; Wilson, Nassar, & Gold, 2013; A. J. Yu & Dayan, 2005). One such approximation
that relies on a single dynamic learning rate can capture behavior across a wide range of statistical
environments (Nassar, Waltz, Albrecht, Gold, & Frank, 2021). However, direct implementation of this
model requires a dynamic learning rate signal that is invariant to statistical context – that is to say, if
adaptive learning is accomplished through adjustments of a learning rate, then some brain signal must
reflect the "learning rate" – and do so across all statistical contexts. Such a learning rate signal has yet to
be observed in the brain, despite several attempts to do so across different statistical contexts (D'Acremont
& Bossaerts, 2016; Li et al., 2019; Nassar, Bruckner, et al., 2019). In contrast, brain signals that predict
more learning in discontinuously changing environments (Behrens et al., 2007; Jepma et al., 2016;
McGuire, Nassar, Gold, & Kable, 2014; Nassar et al., 2012; O'Reilly et al., 2013), do not do so consistently
across different statistical conditions (D'Acremont & Bossaerts, 2016). For example, feedback locked P300
signals, which positively correlate with learning in discontinuously changing environments (Jepma et al.,
2018, 2016) , negatively correlate with learning in environments that contain occasional outlier (oddball)
events (Nassar, Bruckner, et al., 2019). These observations run contrary to models that implement learning
rate adjustments: if the brain adjusts a latent variable that controls "learning rate", this signal should
correlate with learning in any context with measurable adjustments of learning – for example, when the
signal is stronger, consistently indicate more learning. Other approximations to normative learning have
been more closely connected to specific neural signals, but fail to capture the range of behaviors displayed
by people, for example the ability to immediately discount past experience after a changepoint (Bernacchia
et al., 2011; Farashahi et al., 2017; Mathys et al., 2011), or the ability to calibrate learning across different
statistical environments (Behrens et al., 2007). In sum, while previous models have explored the potential
neural mechanisms for adaptive learning, no algorithm has captured the range of human behavior and its
neural correlates across generative structures.

Here we build such a generalized framework based on the idea that adaptive learning is accomplished by
controlling internal representations according to environmental structure (L. Q. Yu, Wilson, & Nassar,
2021). We implement this idea with a feed-forward neural network model that maps an internal context
representation (which can be thought of as its "mental context" and serves to organize learning across events
much like the state in a reinforcement learning model) onto a continuous action space in order to perform
a predictive inference task. We show that the effective learning rate of the model is proportional to the rate
at which its internal context evolves in time, and that better model performance can be achieved when
context transitions are discontinuous and elicited by surprising events. Furthermore, we show that context
transitions can speed learning after changepoints, or slow them after oddball events, assuming appropriate
state transitions occur between trials (L. Yu, Wilson, & Nassar, 2020). Our model produces these behaviors
without an explicit representation of learning rate, and instead relies on an *internal context* that transitions

rapidly after surprising events much like patterns of activity previously observed in prefrontal cortex
(Karlsson, Tervo, & Karpova, 2012; Nassar, McGuire, et al., 2019).

Furthermore, it requires *context transition signals* that bidirectionally affect learning according to statistical
context (changepoint versus oddball), providing a mechanistic explanation for feedback-locked P300
signals that show the same complex relationship to learning (Nassar, Bruckner, et al., 2019), and potentially
shedding light on discrepant relationships between pupil diameter and learning that have been reported
(compare Nassar et al., 2012 to O'Reilly et al., 2013). Taken together, our results support the idea that
adaptive learning behavior emerges through abrupt transitions in mental context. Under this view, we argue
that learning rate dynamics emerge as a consequence of changes in the internal representations to which
learning is bound, and that the brain has no need to represent a global learning rate signal directly.

Methods

Experimental task:

We examine human and model behavior in a predictive inference task that has been described previously
(McGuire et al., 2014; Nassar & Troiani, 2020). The predictive inference task is a computerized task in
which an animated helicopter drops bags in an open field. In the pre-training session, human subjects
learned to move a bucket with a joystick beneath the helicopter to catch bags that could contain valuable
contents. During the main phase of the experiment, the helicopter was occluded by clouds and the
participants were forced to infer its position based on the locations of bags it had previously dropped.

Our initial simulations focus on dynamic environments in which surprising events often signal a change in
the underlying generative structure (changepoint condition; figures 1-5). In the chanagepoint condition, bag
locations were drawn from a distribution centered on the helicopter with a fixed standard deviation of 25
(unless otherwise specified in the analysis). The helicopter remained stationary on most trials, but
occasionally and abruptly changed its position to a random uniform horizontal screen location. The
probability of moving to a new location on a given trial is controlled by the hazard rate ($H = 0.1$). Unless
otherwise noted, our modeling results are presented with 32 simulated subjects, to correspond to the sample
size in (McGuire et al., 2014).

We also considered a complementary generative environment in which surprising events were unrelated to
the underlying generative structure (oddball condition; figure 6)(Nassar & Troiani, 2020). In the oddball
condition, the helicopter would gradually move in the sky according to a Gaussian random walk (drift rate
$(DR) = 10$). In the oddball condition bags were typically drawn from a normal distribution centered on the
helicopter as described above, but on occasion a bag would be dropped in random location unrelated to the
position of the helicopter. The location of an oddball bag was sampled from a uniform distribution that
spanned the entire screen. The probability of an oddball event was controlled by a hazard rate ($H = 0.1$).

Normative learning model:

A simple delta rule can perform the predictive inference by incrementally updating beliefs about the
helicopter location according to prediction errors:

١٥٥
$$B_{t+1} = B_t + \alpha\delta \quad (1)$$

١٥٦
$$\delta = Bag\ Position(t) - B_t(t) \quad (2)$$

here B is belief about the helicopter position on each trial, δ is the prediction error observed on that trial,
and α is the learning rate. With a constant α, the model assigns the same weight to all predictions and

outcomes. Previous work has shown that Bayesian optimal inference can be reduced to a delta rule learning
under certain approximations, leading to normative prescriptions for learning rate that are adjusted
dynamically (Nassar, Bruckner, et al., 2019; Nassar et al., 2010). The resulting normative learning model
takes information which human subjects would normally obtain during the pre-training sessions including
Hazard rate and standard deviation, but also computes two latent variables, by using the trial-by-trial
prediction error: 1) changepoint probability which is computed after an outcome is observed and indicates
the probability that the observed outcome has reflected a change in the helicopter location, and 2) relative
uncertainty which is computed before making the next prediction and indicates the models uncertainty
about the location of the helicopter. Detailed information regarding how CPP and RU are calculated can be
found in previous work (Nassar, Bruckner, et al., 2019).

In the changepoint condition the normative learning rate α_t is defined by:

١٧٠
$$\alpha_t = CPP + RU - CPP \times RU \quad (3)$$

Where CPP is changepoint probability and RU is relative uncertainty. Using these two latent variables,
which both track the prediction error, but with different temporal dynamics (McGuire et al., 2014), the
model computes a dynamic learning rate that increases after a changepoint and gradually decreases in the
following stable period after a changepoint.

The same approximation to Bayesian inference can be applied in the oddball condition to produce a
normative learning model that relies on oddball probability and relative uncertainty to guide learning. While
the latent variables and form of the model mimic that in the changepoint condition, the learning rate differs
in that it is reduced, rather than enhanced, in response to outcomes that are inconsistent with prior
expectations:

١٨٠
$$\alpha_t = RU - OBP \times RU \quad (4)$$

Where OBP is the models posterior probability estimate that an outcome was an oddball event and RU
reflects the model's uncertainty about the current helicopter location. Thus, normative inference in the
oddball condition requires decreasing learning according to the probability of an extreme event (oddball),
whereas normative inference in the changepoint condition required increasing it.

Neural network models:

In order to better understand how normative learning principles might be applied in a neural network we
created a series of neural network models that use supervised learning rules to generate predictions in the
predictive inference task. Specifically, we created a two-layer feed forward neural network that can perform
the predictive inference task.

Network architecture includes two layers:

The input layer is composed of N neurons with responses characterized by a von Mises (circular)
distribution with mean m and fixed concentration equal to 32 We implemented several versions of this
model depending on how the mean m changes on a trial-by-trial basis.

The output layer contains neurons corresponding to spatial location of the bucket on the screen. The
response of output layer neurons was computed by the weighted sum of input layer:

١٩٧
$$r_j = \sum_{i=1}^{N_{in}} x_i w_{ij} \quad (5)$$

١٩٨ Where x_i is the activation of neuron i in the input layer, r_j is the response of neuron j in the output layer
١٩٩ and w_{ij} is the connection weight between neuron i and neuron j. The bucket position chosen by the model
٢٠٠ on each trial was computed as a linear readout of the output layer:

٢٠١
$$estimate = \sum_{j=1}^{N_{out}} L_j \, r_j \quad (6)$$

٢٠٢ Where L_j is the location encoded by each corresponding unit r_j in the output layer. Weight matrix is
٢٠٣ randomly initialized with a uniform distribution of mean zero and SD equal to 5×10^{-4}. The network is
٢٠٤ then trained on each trial by modifying the weight matrix according to:

٢٠٥
$$w_{ij} = (1 - \eta)w_{ij} + \eta y_j x_i \quad (7)$$

Where y_j is the probability on a normal distribution centered on the observed outcome evaluated at L_j with
standard deviation of 25 (equal to the standard deviation of the outcome generative process), and η is a
constant synaptic learning rate controlling the weight changes of the neural network and was set to 0.1 for
all model simulations. Although this value was chosen somewhat arbitrarily, additional simulations using
network learning rates in the range of [0.01 – 0.6] did not change the qualitative predictions of the model.

Fixed context shift models:

In the first models we consider, *fixed context shift* models, the mean m is the variable that controls the
position of the most active neuron in the input layer and is computed on each trial as follows:

٢١٥
$$m_{(t+1)} = m_{(t)} + \Delta m_f \quad (8)$$

Here, Δm_f takes a fixed value for all trials throughout the simulation (figure 2b&c). We considered 50
different Δm_f values ranging from 0 to 2 in order to study the effect of context shifts on model performance.
The word "context" refers to the subpopulation of input layer neurons that are firing above the threshold
(here 0.0001 although the results are robust if using a range of values between 0.001-0.00001) on each trial.
As m increases from one trial to the next, the activity bump in the input layer shifts clockwise (Figure 2b
& c) which can be thought of as the associative context being changed to some degree (Δm_f) on each trial.
The architecture of the input layer is arranged in a circle so that hypothetically the context would be able to
shift clockwise indefinitely, and thus context shifts are reported in radians. In order to minimize interference
from previous visits to a set of context neurons we implemented weight decay (WD) on each time step
according to the following rule:

٢٢٦
$$W_{t+1}(x_t < threshold) = W_t(x_t < threshold) \times WD \quad (9)$$

٢٢٧
$$WD = 0.1$$

Note that this weight decay is not intended as a biological assumption, but rather a convenient simplification
to allow the model to represent a large number of contexts with a small pool of neurons.

Therefore, on each trial, first the model would make a prediction based on weighted sum of the active input,
observe an outcome, shift the context by the assigned context shift and store the supervised signal in the
new context. This new context is in turn used at the beginning of the next trial to produce a response.

Table 1- Summary of the parameters used for simulation of the probabilistic inference task and neural network training.

Neural Network Parameter:	**Value**	**Description**
Number of neurons in the input layer (N_{in})	63	Equally-spaced points between $[-\pi. +\pi]$ incrementing by 0.1
Concentration (κ)	32	Concentration of the von Mises pdf used in the input layer
Number of neurons in the output layer (N_{out})	41	Equally-spaced points between -50 and 350 , incrementing by 10
Synaptic learning Rate (η)	0.1	
Weight Decay Threshold	0.01	
Weight Decay Rate (*WD*)	0.1	
Model Hazard Rate	0.6	The model uses a higher value compared to the actual hazard rate for optimal performance
Input Layer Threshold	0.0001	Neurons firing above this threshold constitute the active "context" on each trial.
Task Parameter:		
Hazard Rate (*H*)	0.1	Probability of a changepoint/oddball trial
Noise (σ_N)	25	Standard Deviation of random process generating outcomes
Standard Deviation of Drift Rate (σ_{drift})	10	Standard Deviation of the random process generating drift rate in oddball condition

Table 1. List of all parameters used in the current neural network modeling simulations as well as the
original task parameters used in a previous behavioral study involving the same task (McGuire et al., 2014).

Ground Truth context shift model:

To leverage the benefits of different context shifts which we observed in the fixed context shifts models we
designed a model that would use a context shift optimized for each trial. The ground truth context shift
model has the same design of a fixed context shift model except instead of the constant term Δm, the model
computes Δm in a manner that depends on whether the current trial is a changepoint:

$$\Delta m = \begin{cases} max(\Delta m_f). & if \ t \ is \ changepoint \\ 0. & otherwise \end{cases} \quad (10)$$

Dynamic context shift models:

The ground truth context shift model assumes full knowledge of changepoint locations, whereas humans
and animals must infer changepoints based on the data. Here we build plausibility into the ground truth
model by controlling context shifts according to subjective estimates of changepoint probability (CPP) that
are based on the observed trial outcomes:

٢٥٣
$$\Delta m = f(CPP) \quad (11)$$

The function, f, provides a fixed level of context shift according to the estimated changepoint probability
by inverting the relationship between context shift and effective learning rate observed in the fixed context
shift models and plotted in figure 2d. Thus, on each trial, the model will choose a context shift belonging
to a fixed context shift model that has the closest effective learning rate to CPP. Thus, more surprising
outcomes that yield higher values of CPP will consistently result in larger context shifts, with a changepoint
probability of one resulting in the maximal context shift and a changepoint probability of zero resulting in
no context shift at all.

CPP was computed either using the Bayesian normative model described above (Bayesian context shift) or
from an approximation derived from the neural network itself (Network-based context shift). In the
network-based version, the probability of a state transition is subjectively computed by the following
equation:

٢٦٥
$$\frac{H/41}{H/41 + r_{X_t}(1-H)} \quad (12)$$

which can be interpreted as a network-based approximation to Bayesian CPP estimation (For more details
see supplementary information: *https://github.com/learning-memory-and-decision-*
lab/dynamicStatesLearning) or in terms of a non-linear activation over prediction errors such as has been
proposed in various conflict models (Botvinick, Braver, Barch, Carter, & Cohen, 2001; Cockburn & Frank,
2013). H can be thought of in Bayesian terms as a hazard rate, or in neural network terms, as controlling
the threshold of the activation function, and r_{X_t} is the firing rate of the output unit corresponding to the
location X_t, which can be thought of as providing a readout of the outcome probability based on a Bayesian
population code. The 41 reflects the total number of output units in our population, and since outcomes
could occur that were in between the tuning of these units, in practice we used linear interpolation to
estimate r_{X_t} based the two output units closest to the actual outcome location. The hazard rate H was set to
0.6 for the changepoint condition to optimize performance (i.e. minimize prediction errors). While hazard
rate in our model was selected to optimize predictions, it also is consistent with human participants'
behavior, which when fit with the model yielded higher hazard rates than the generative hazard rate in our
experiment (see supplementary figure 1: *https://github.com/learning-memory-and-decision-*
lab/dynamicStatesLearning).

Mixture Model:

We also considered a model that uses context shifts intermediate between our fixed- and dynamic-context
shift models. Specifically, this model shifted context according to a weighted mixture of the context shift
from the best performing fixed context shift model and the network-based context shift model as follows:

285
$$contetx\ shift = mixture\ \times fixed\ context\ shift + (1 - mixture) \times dynamic\ context\ shift \quad (13)$$

Quantitative model fitting:

We fit the behavior of human subjects from a previous study (McGuire et al., 2014) with five different
models: 1) the Network-based context shift model with a single free parameter (hazard rate), 2) a fixed
context shift model with one parameter (i.e. fixed context shift) and 3) A mixture model in which context
shifts are a weighted mixture of best fixed context shift model (fixed context shift = 0.4) and network-based
dynamic context shift where the mixture weight is one free parameter (eq. 13) 4) a mixture model as above,
but with the fixed context shift fit as a second free parameter, 5) a mixture model as above, but with both
the fixed context shift and hazard rate fit as additional free parameters (in addition to mixture weight).
Parameters that minimized sum of squared errors were attained through a grid search over the parameter
space ([0 1] for fixed context shift, mixture weight and hazard rate). Model comparison used Bayesian
information criteria (BIC) to penalize for differential complexity across our model set, as BIC provided the
most reliable model recovery for synthetic data.

Extension of network models to the oddball condition:

To test our proposed models in a variation of the task where prediction errors are not indicative of a change
in context i.e. oddball condition we use the same design of neural network but with a simple modification
in temporal dynamics of context shifts.

The task involved the same paradigm described above, but with outcomes (i.e. bag locations) determined
by a different generative structure. In particular, the helicopter location gradually changed its position in
the sky with a constant drift rate, and bags were occasionally sampled from a uniform distribution spanning
the range of possible outcomes, rather than being "dropped" from the helicopter itself (Nassar & Troiani,
2020; Nassar et al., 2021).

The ground truth neural network model was modified to incorporate the alternate generative structure of
the oddball condition. In particular, on each trial, input activity mean m was changed by 1) maximally
context shifting in response to oddballs at the time of feedback, 2) "returning" from the oddball induced
context shift at the end of the feedback period, prior to the subsequent trial, and 3) adding a constant value
(0.05) proportional to the fixed drift rate of the random walk process prior to making the prediction (for
choosing this constant drift rate, we ran simulations with different values of drift rate and chose one that
produced optimal behavior). Thus, after a prediction is made on trial context mean changes according to:

314
$$\Delta m_1 = \begin{cases} max(\Delta m_f), & if\ t\ is\ oddball \\ 0 & otherwise \end{cases} \quad (14)$$

316
$$m_{t+1} = m_t + \Delta m_1 \quad (15)$$

317 But, after the model receives the supervised signal (represented by a normal distribution which is centered
318 on the bag position with standard deviation corresponding to standard deviation of bag drops) and stores
319 it in a new context, the context transitions back to:

320
$$m_{t+1} = m_t - \Delta m_1 + \Delta m_2 \quad (16)$$

Where Δm_2 is a constant (here 0.05) proportional to the drift rate of the random walk process. This leads
the information from oddball trial to be stored in a different context that will not influence the upcoming
prediction of the model.

The dynamic context shift models were constructed to follow the same logic, but using subjective measures
of oddball probability rather than perfect knowledge about whether a trial is an oddball. Specifically, we
updated context upon observing feedback according to the probability that the feedback reflects an oddball
(OP):

$$\Delta m_1 = f(OP) \ \ (17)$$

$$m_{t+1} = m_t + \Delta m_1 \ \ \ (18)$$

۳۳۰ And prior to making a prediction for the subsequent trial returned to the previous context except with a
۳۳۱ slight shift modeling to account for the drift in the helicopter position due to the random walk:

$$m_{t+1} = m_t - \Delta m_1 + \Delta m_2 \ (19)$$

This model captures the intuition that if an outcome is known to be an outlier, it should be partitioned from
knowledge that pertains to the helicopter location, rather than combined with it. To accomplish this, the
model changes the context first according to the oddball probability or Δm_1 in above equation and after
storing the supervised learning signal in the new context, the model transition back to its previous context
by subtracting the first context shift term Δm_1. It then moves the context according to a constant shift
proportional to the drift rate Δm_2. The Δm_1 term causes significant shifts on oddball trials, but after that
the model transition back to previous context and shifts according to the Δm_2 which would not be
influenced by oddball trials. Similar to the changepoint condition, here, we also made a version of the
dynamic Bayesian context shift model, which used network output layer activity to compute subjective
measures of oddball probability.

Representational similarity analysis:

We computed a trial-by-trial dissimilarity matrix where each cell in the matrix represents the number
corresponding to the dissimilarity between the input layer activity on two trials. The dissimilarity matrix
(*D*) of the dynamic context shifts model uses Euclidean distance and is computed by:

$$D_{ij} = \sqrt{\sum_{q=1}^{N_{in}}(Act_{(i.q)} - Act_{(j.q)})^2} \ (20)$$

Behavioral analysis:

Behavioral analyses are aimed at understanding the degree to which we revise our behavior in response to
new observations. In order to quantify this, we define an "effective learning rate" as the slope of the
relationship between trial-to-trial predictions errors (i.e. the difference between the bucket position and bag
position) and trial-to–trial updates (i.e. the change in bucket position from one trial to the next). The
adjective "effective" is chosen here so that this learning rate won't be mistaken by the reader with two other
learning rates used in this paper: 1) the fixed synaptic learning rate of the neural network 2) the normative
learning rate prescribed by the reduced Bayesian model. To measure effective learning rate, we regressed
updates (UP) onto the prediction errors (PE) that preceded them:

$$UP = \beta_0 + \beta_1 \times PE \ (21)$$

The resulting slope term, β_1 captures the effective learning rate, or the amount of update expected for a
given prediction error. We also performed a more extensive regression analysis that included terms for 1)
prediction error 2) prediction error times changepoint probability 3) prediction error times relative
uncertainty (figure 4d).

Comparison to P300 analysis:

To analyze the effect of trial-to-trial variability in context shifts from the dynamic context shift model on
effective learning rate produced by that model, we fit the regression model above to simulated predictions
for the dynamic context shift models, but did so while splitting data into quartiles according to the size of
the context shift size that the model underwent on a given trial. The corresponding figure (figure 6e) of
P300 signal and learning rate are from ref. (Nassar, Bruckner, et al., 2019).

Pupil Response Simulation:

We modeled 480 trials of a predictive inference task for each of the two conditions (oddball, changepoint).
We created synthetic pupil traces by defining time points for feedback-locked context shifts, which occurred
400ms after oddball or changepoint, and pre-prediction context shifts at 900ms after oddball events (see eq.
10 & 13). We used measurements of context shift for the respective changepoint and oddball trials (see eq.
11 & 16) at these time points and convolved these measurements with a gamma distribution to create
simulated time courses of a pupil response under the assumption that the pupil signal reflects the need for
a context shift. We analyzed this signal with a regression model that was applied to all synthetic data in
sliding windows of time. Explanatory variables in our model included surprise (changepoint/oddball
probability computed from normative model) and learning (trial-by-trial learning rate computed from the
normative model).

Results

In order to test whether changes to latent state representations can facilitate adaptive learning behavior we
modeled a predictive inference task designed to measure adaptive learning in humans (figure 1) (McGuire
et al., 2014). In the task a helicopter, which is hidden behind clouds, drops visible bags containing valuable
contents from the sky (figure 1a, right). On each trial, the subject moves a bucket to the location where they
believe the helicopter to be, such that they can catch potentially valuable bag contents. Subjects can move
the bucket to a new position on each trial to update and improve their prediction (figure 1a, left; figure 1b
orange arrow). In the "changepoint" variant of the task, bag locations were sampled from a Gaussian
distribution centered on the helicopter, which occasionally relocated to a new position on the screen. Such
abrupt transitions in helicopter location led to changes in the statistical context defining the bag locations
(context shifts), which could be inferred by monitoring the size of prediction errors (figure 1b, red arrow).
Therefore, the helicopter position is a dynamic latent variable that must be inferred from noisy observations
(i.e. dropped bags) on each trial to yield optimal task performance. Previous work has shown that human
behavior can be captured by a normative learning model that relies on a dynamic "learning rate" adjusted
from trial-to-trial according to changepoint probability (CPP) and uncertainty (RU) (figure1b&c), but
failures to identify neural signals that reflect this dynamic learning rate consistently across conditions cast
doubt on its biological relevance (D'Acremont & Bossaerts, 2016; Nassar, Bruckner, et al., 2019; Nassar
et al., 2012; O'Reilly et al., 2013). Here we explore whether normative learning may instead be achieved
in the brain by a neural network that undergoes dynamic transitions in the mental context to which
associates are bound, thereby adjusting where information is stored, rather than the degree to which storage
occurs.

Figure 1: Predictive inference task to measure dynamics of adaptive learning.

A) Schematic Illustration (left) and screenshots of the predictive inference task (right). Human subjects place a bucket at horizontal location on the bottom of the screen to catch a bag of coins that will be subsequently dropped from a hidden helicopter. After observing the bag location (outcome) at the end of each trial, along with their prediction error (distance between bucket and outcome), the subject could improve their response by adjusting their bucket position (update). In the changepoint condition, the helicopter typically remains stationary but occasionally moves to a completely new location. B) The sequence of bag locations (outcome; ordinate) is plotted across trials, which are segmented into discrete contexts reflecting periods with a stationary mean. Context transitions (dotted vertical lines) reflect changepoints in the position of the helicopter. Bucket placements made by a subject (pink) and normative model (navy) are shown with a representation of an example prediction error and outcome. [Prediction error = outcome (t) – estimate (t) and Update = estimate (t+1) – estimate (t)]. (C) The learning rate, which defines the degree to which the normative model updates the bucket in response to a given prediction error, depends on two factors, changepoint probability (CPP; red) and relative uncertainty (RU; blue), which combine to prescribe learning that is highest at changepoints (CPP) and decays slowly thereafter (RU).

A neural network test bed for exploring adaptive learning

To examine how normative updating could be implemented in a neural network, we devised a two-layer feedforward neural network in which internal representations of context are mapped onto bucket locations by learning weights using a supervised learning rule (figure 2b; see methods). Units in the output layer of the network represent different possible bucket locations in the predictive inference task and a linear readout of this layer is used to guide bucket placement, which serves as a prediction for the next trial. After each trial, a supervised learning signal corresponding to the bag location is provided to the output layer and weights corresponding to connections between input and output units are updated accordingly.

The input layer of our model is designed to reflect the mental context to which learned associations are formed, and its activity is given by a Gaussian activity bump with a mean denoting the position of the neuron with the strongest activity and a standard deviation denoting the width of the activity profile. The primary goal of this work is to understand how changes to the mean of the activity bump, across trials, affect learning within our model. Since the input layer of the network reflects mental context, it does not receive any explicit sensory information, and we can manipulate its activity across trials to provide a flexible test bed for how different task representations (i.e. mental context dynamics) might affect performance of the model. In particular, we examine how displacing the mean of the activity bump in the input layer across trials affects the rate and dynamics of the networks learning behavior. In the simplest case, a non-dynamic network, the mean of the activity bump in the input layer is constant across all trials - - reflecting learning onto a fixed "state". A slightly more complex mental context might be one that drifts slowly over time, such that the mean of the activity bump changes a fixed amount from one trial to the next leading trials occurring close in time to be represented more similarly. In this case, learning would occur onto an evolving temporal state representation. In a more complex (but maybe more intuitive) case, the subset of active neurons in the input layer could correspond to the current "helicopter context" (figure 1b), or period of helicopter stability. In this case, the mean of the activity bump would only transition on trials where the helicopter changes position and thus could be thought of as representing the underlying latent state of the helicopter (e.g. this is the third unique helicopter position I have encountered) – albeit without any explicit encoding of its position.

Context shifts facilitate faster learning

We first examined performance of models in which the mean of the input activity bump transitioned by
some fixed amount on each trial. This set included 0 (fixed stimulus representation), small values in which
nearby trials had more similar input activity profiles (timing representation) and extreme cases where there
was no overlap between the input layer representations on successive trials (individuated trial
representation). We defined the fixed shift in the mean of the activity profile as the "context shift" of our
model. This shift is depicted in figure 2c as the nodes shown in "hot colors" (i.e. active neurons) in the
input layer of the neural network moving to the right; Note how the size of rightward shift in the schematic
neural network is constant in all four trials shown. We used increments starting from zero (the same input
layer population) to a number corresponding to a complete shift (completely new population) in each trial.
Learning leads to fine tuning of the weights by strengthening connections between active input neurons and
the output neurons nearby the outcome location (bag position) on each trial. We observed that moderate
shifts of in the input layer (context shifts) led to the best performance in our task (figure 2e), and that the
effective learning rate describing the model's behavior monotonically scaled with context shift (figure 2d).
We also compared the performance of these models to a delta-rule equipped with learning rates matched to
those empirically observed in each fixed context shift model (figure2d). Performance of fixed-context shift
networks mirrored that of delta-rule models, both in terms of overall performance and the advantage
conferred to moderate context shifts in the network (figure 2e, black), or learning rates in the delta rule
(figure 2e, red). Together, these results support the notion that context shifts could be used to enhance the
sensitivity of behavior to new observations, analogous to adjusting the learning rate in a delta rule.

Figure 2: A neural network with fixed context shifts can approximate any constant learning rate. A-C) Network
 structure and weight updates for two fixed context shift models (B, C) are depicted across four example trials of a
 predictive inference task (A). For all networks, feedback was provided on each trial corresponding to the observed
 bag position (circle in panel A, red arrow in B&C) and weights of network were updated using supervised learning.
 Only a subset of neurons (circles) and connections between them (lines) are shown in neural network schematic.
 Activation in the input layer was normally distributed around a mean value that was constant in (B) and shifted by a
 fixed amount on each trial in (C) (context shift). Learned weights (colored lines) were all assigned to the same input
 neuron when context shift was set to zero (B) but assigned to different neurons when the context shift was substantial
 (C). D) The effective learning rate (ordinate), characterizing the influence of an unpredicted bag position on the
 subsequent update in bucket position, increased when the model was endowed with faster internal context shifts
 (abscissa). E) Mean absolute prediction error (ordinate) was minimized by neural network models (black line) that
 incorporated a moderate level of context shift from one trial to the next (abscissa). Mean error of a simple delta rule
 model using various learning rates is shown in red (x-axis values indicate the context shift equivalent to the fixed delta

rule learning rate derived from panel D). For each simulated delta rule model we plotted the x position according to the amount of context shift that yielded the corresponding learning rate from that fixed context shift model, thus the position on the x-axis reflects the same amount of average learning of the two models but the mechanics of how learning is generated differs across the two models. Note that neural networks with fixed context shifts achieve similar task performance to more standard delta-rule models that employ a constant learning rate.

Dynamic context shifts can improve task performance

The higher performance of moderate context shift models (figure2e) might be thought of intuitively as navigating the classic trade-off between flexibility and stability. A higher learning rate, which can be effectively produced by a larger context shift, promotes flexibility and leads to better performance in response to environmental changes that render past observations irrelevant to future ones (figure 3c). In contrast, smaller learning rates, which are effectively produced by smaller context shifts, yield stable predictions that facilitate a performance advantage in stable but noisy environments by averaging over the noise (figure3d). More concretely, when the helicopter remains in the same location, small context shifts improve performance by pooling learning over a greater number of bag locations to better approximate their mean, but large context shifts can improve performance after changes in helicopter location by reducing the interference between outcomes before and after the helicopter relocation. Inspired by the observed relationship between context shift and accuracy, we next modified the model to dynamically adjust context shifts to optimize performance. In principle, based on the intuitions above, we might improve on our fixed context shift models by only shifting the activity profile of the input layer at a true context shift in the task (i.e. allow the input layer to represent the latent state). Since such a model requires pre-existing knowledge of changepoint timings we refer to it as the ground truth model (figure 3, top). Indeed, we observed that the ground truth model performs as well as the best fixed context shift model after changepoints (figure 3c), and better than the best fixed context shift model during periods of stability (figure 3d), yielding overall performance better than any fixed context shift model (figure 3e).

Needless to say, the brain does not have access to perfect information regarding whether a given trial is a changepoint or not. Is it possible to make a more realistic version of this optimal model, utilizing information that the brain does have access to? To answer this question, we built models that infer changepoint probability based on experienced prediction errors. We built two versions of this model, one that computed changepoint probability (CPP) explicitly according to Bayes rule (Nassar & Gold, 2010), and one that approximated CPP according to the mismatch between output activity in the network and the observed outcome (i.e. supervised signal). In both cases, hazard rates necessary for computing CPP were optimized for performance, resulting in model hazard rates exceeding their experimental values (See Supplementary figure 1 at https://github.com/learning-memory-and-decision-lab/dynamicStatesLearning). Both models achieved good performance after changepoints by elevating context shifts (figure 3c) and during periods of stability by reducing context shifts (figure 3d), yielding overall performance better than any fixed context shift model, and only slightly worse than the ground truth model (figure 3e&f). These results were consistent across different noise conditions (See supplementary figure 2 at *https://github.com/learning-memory-and-decision-lab/dynamicStatesLearning*).

Figure 3

Figure -3: Dynamic context shifts facilitate better task performance. A) Schematic diagram of ground truth model network (left) which is provided with objective information about whether a given trial is changepoint or not (right) and uses that knowledge to shift the context only on changepoint trials. B) The dynamic context shift network uses a subjective estimate of changepoint probability based a statistical model (Bayesian) or the network output (Network-based) to adjust its context shift on each trial. All of these models shift context to a greater degree on changepoint trials (bottom row) than on non-changepoint trials (top 3 rows). C) Performance on trials immediately following a changepoint was best for models employing the largest context shifts. Mean error on trials following a changepoint (ordinate) is plotted as a function of context shift (abscissa) for fixed (line/shading) and dynamic (points) context shift models. The ground truth model (blue point) minimized error after changepoints through large context shifts, and the dynamic context shift models, which made moderately large context shifts after changepoints, also approached this level of performance (yellow & pink). Note that since the optimal policy on changepoint trials is to use a learning rate of one, any model with a large enough context shift would be able to achieve optimal performance on this subset of trials (note performance of highest fixed context shift models). D) Smallest errors on trials during periods of stability (> 5 trials after changepoint; ordinate) were achieved by models that made smaller context shifts (abscissa). All dynamic context shift models (ground truth, Bayesian, network-based) made relatively small context shifts for stable trials, yielding good performance. E) Across all trials, subjective dynamic context shift models yielded better average performance than the best fixed context shift model and approached the performance of the ground truth model. F) Average Error for individual simulations showing the Bayesian (yellow) and network-based (pink) context shift models beat the best fixed context shift model (green) consistently across simulated task sessions. Note that on some occasions the ground truth model yields higher errors than the network-based context shift model. Exhaustive simulations with larger numbers of trials revealed that these apparent performance failures of the ground truth model simply reflected the probabilistic nature of our task, and that as the number of trials is increased, the ground truth model always achieved better performance than all other models (see supplementary figure 3 https://github.com/learning-memory-and-decision-lab/dynamicStatesLearning)($Bayesian\ Context\ Shift: t = 21.9. df = 31. p < 10^{-16}$ Network $-$ Based Context Shift: $t = 20.48. df = 31. p < 10^{-16}$).

Dynamic context shifts capture key behavioral and neural signatures of adaptive learning in humans.

Not only was the dynamic context shift model able to outperform fixed context shift models, it did so by capturing behaviors that are observed in people. The model updated predictions according to prediction errors, but relied more heavily on prediction errors from certain trials (figure 4a). We can quantify the effective learning rate as the slope of the relationship between the model's bucket update and its previously observed prediction error in order to compare the behavior of different models (figure 4a). To look more closely at the relationship between our proposed model and human behavior, we first created a mixture model that updated context as a linear mixture of those prescribed by the network-based dynamic model and those prescribed by the best fixed context shift model (see methods for a more detailed description). We then fit five different models to human subjects' data 1) the Network-based context shift model with a single free parameter (hazard rate), 2) a fixed context shift model with one parameter (i.e. fixed context shift) and 3) A mixture model in which context shifts are a weighted mixture of those used by the "best" fixed context shift model and those used by the "best" network-based context shift model with one free parameter (mixture weight), 4) the mixture model described above, but with the fixed context shift fit as a second free parameter, 5) the mixture model as above, but with the fixed context shift and hazard rate fit as additional free parameters (in addition to the mixture weight).

Comparing the five models described above, we observed that human subject data was best described by the most complex model, which included aspects of both fixed and dynamic context shifts (Figure 4b). The winning model assumes that context shifts as a mixture of network-based dynamics (with hazard rate as a free parameter) and a fixed level on each trial (controlled by a fixed context shift parameter). The relative contribution of these two influences is controlled by the mixture weight – such that the model can model

 participants who adjust learning dramatically at changepoints, but also model participants who learn
relatively consistently. A summary of the fitted parameters for the winning model (the model with three
free parameters) is shown in table 2. The participants also used higher hazard rate than the true hazard rate
of the task but close to the hazard rate used by our network-based dynamic context shift model. It is
noteworthy that the fixed context shift model provided the worst quantitative fit to participant data,
suggesting that dynamics played a critical role in matching participant behavior.

Table 2 A summary of the fitted parameters for the best model.

Fitted Parameter	Fixed Context Shift	Mixture Weight	Hazard Rate
Mean	0.49	0.65	0.48
Standard Deviation	0.28	0.24	0.28

Table 2. Mean and standard deviation of the fitted parameters for the model with three free parameters
(fixed context shift, mixture weight and hazard rate) across all human participants.

Simulated data from our fit models reproduced the key behavioral hallmarks of human adaptive learning.
In particular, the winning model used higher effective learning rates immediately after changepoints,
recapitulating human learning dynamics, whereas the fixed context shift model used the same effective
learning rate across all trials (Figure 4c). Previous work has captured human learning dynamics using a
regression model that includes separate parameters to model fixed learning (β_1), increased learning after
likely changepoints (β_2), and increased learning during periods of uncertainty (β_3)(McGuire et al., 2014).
Here we performed posterior predictive checks on our winning model using this same approach and found
that our best fitting model, which mixed dynamic and fixed-context shifts, could reproduce key hallmarks
of learning (figure 4d; red points). In addition, the model could reproduce the impressive heterogeneity in
learning behavior across participants, in part through different mixtures of fixed and dynamic context shifts
(figure 4d; gray points). Taken together, these results suggest that a network that includes a mixture of
dynamic and fixed context shifts can reproduce hallmarks of human adaptive learning behavior.

These context adjustments provide a potential explanation for rapid changes in activity patterns, or
"network resets", that have been observed during periods of rapid learning in rodent mPFC and human
OFC (Karlsson et al., 2012; Nassar, McGuire, et al., 2019). Rodent studies previously identified neural
population activity changes that occurred during periods of uncertainty when animals were rapidly shifting
behavioral policies (Karlsson et al., 2012). Human neuroimaging work took a similar approach to identify
patterns of activity that changed more rapidly during periods of rapid learning following changepoints, after
controlling for other factors(Nassar, McGuire, et al., 2019). An important open question raised by these
studies is why such representations exist at all; in both cases the representations were not reflecting the
behavioral policy, and their dynamics would not be necessary for implementing existing models of adaptive
learning (Nassar et al., 2012, 2010). Given that our dynamic context shift model accomplishes adaptive
learning by dynamically changing the context representations, we asked whether our input layer might give
rise to population dynamics similar to the phenomena observed in these previous studies.

To do so, we used an RSA approach to create a dissimilarity matrix reflecting differences in the input layer
activation across pairs of trials for our dynamic context shift model (figure 5a). By using the activity profile
of the input layer the dynamic context shift model we were able to obtain a pattern of dissimilarity across

all pairs of trials for each simulated task session (figure 5b). Examining this dissimilarity matrix reveals
abrupt representational shifts at changepoints (dotted lines in figure 5b). To quantify the observed changes
in activity pattern, we computed the dissimilarity across adjacent pairs of trials, and examined how this
adjacent trial similarity was affected by changepoints in the task. Consistent with empirical data, we found
that representations in our context layer shifted more rapidly immediately after a changepoint (figure 5c;
mean dissimilarity for changepoint/non changepoint trials = 0.73/0.22, t = -54.54, df = 31, p $<10^{-16}$). In
some sense, this is not surprising, given that we built our model to achieve faster learning after changepoints
by shifting the activity pattern in the input layer. Nonetheless, our model provides a potential normative
explanation for why "network reset" phenomena are observed during periods of rapid learning: in our
model, such changes in activity optimize behavior by providing a clean slate for learning after
environmental change.

FIGURE 4 Dynamic context shifts describe quantitative and qualitative patterns in human learning
behavior. A) Single trial updates from dynamic context shift model (ordinate) are plotted against prediction
errors (abscissa) for each single trial of a simulated session with points colored according to the normative
changepoint probability. Note that large absolute prediction errors, corresponding to high changepoint
probabilities, tend to lead to updates on the unity line, corresponding to an effective learning rate of one.
B) Relative BIC (abscissa) is plotted for 5 models that were fit to human behavioral data (ordinate): Fixed
CS: model with the fixed context shift as a free parameter. Mixture weight: model that mixes fixed context
shift with network-based dynamic context shift in which mixture weight is the only free parameter. HR:
dynamic network-based context shift model with hazard rate as a free parameter. Mixture+fixed CS: model

with mixture weight and fixed context shift as two free parameters. Mixture + fixed CS + HR: model with mixture weight, fixed context shift and hazard rate as three free parameters. C) Effective learning rate (ordinate) is plotted for trials that differ in their alignment to the most recent changepoint (abscissa). The best fitting model (Mixture + fixed CS + HR ; purple) resembles qualitative behavior of human subjects (light blue) D) Coefficients from a regression model (top equation) fit to single trial updates to characterize the degree of overall learning (β_1: fixed LR), adjustments in learning at likely changepoints (β_2: CPP Driven Learning), and adjustments in learning according to normative uncertainty (β_3: RU driven learning). Grey circles represent fits to individual human subjects (left) and simulated data from the best model (right), whereas red circles reflect mean coefficients across individuals.

Figure 5: Input layer representations change rapidly at changepoints. A) Dissimilarity in the input representation between pairs of trials was computed according to the Euclidean distance between those trials in the space of population activity (here exemplified in terms of three trials, where trial t is an example changepoint). Note that the cyan activity bump corresponding to trial t is shifted relative to the green bump corresponding to trial t-1 (green). B) A dissimilarity matrix representing the dissimilarity in input layer activity for each pair of trials in a simulated task session. Dotted lines reflect changepoints, and thus trials between the dotted lines occurred in the same task context (helicopter position). Note that trials within the same context (i.e. trial t and trial t+1) are more similar

than for consecutive trials belonging to two different contexts (trial t-1 and trial t). C) Mean/SEM (dotted line/shading)
dissimilarity between adjacent trials (ordinate) is plotted across trials relative to changepoint events (abscissa) for 32
simulated sessions. Note the rapid change in input layer activity profiles (i.e. high adjacent trial dissimilarity) at the
changepoint event, reminiscent of previously observed "network reset" phenomena that have been linked to periods
of rapid learning in both rodents and humans.

Dynamic context shifts can reduce learning from oddballs

In order to understand how dynamic context shifts might be employed to improve learning in an alternate
statistical environment we considered a set of "oddball" generative statistics that have recently been
employed to investigate neural signatures of learning (D'Acremont & Bossaerts, 2016; Nassar, Bruckner,
et al., 2019). In the oddball condition, the mean of the output distribution does not abruptly change but
instead gradually drifts according to a random walk. However, on occasion a bag is dropped at a random
location uniformly sampled across the width of the screen with no relationship to the helicopter, constituting
an outlier unrelated to both past and future outcomes. In the presence of such oddballs, large prediction
errors should lead to less, rather than more, learning. This normative behavior has been observed in adult
human subjects (D'Acremont & Bossaerts, 2016; Nassar, Bruckner, et al., 2019; Nassar & Troiani, 2020).

To examine whether dynamic context transitions could afford adaptive learning in the oddball condition
we created a network analogous to the ground truth model described above, but active input units were
adjusted according to the oddball condition transition structure (figure 6a). Specifically, on each trial, the
model would shift the context with a small constant rate, corresponding to the drift rate in the generative
process (i.e. the helicopter position slowly drifting from trial to trial). On oddball trials, the model would
undergo a large context shift, ensuring that the oddball outcome would be associated with a non-overlapping
set of input layer neurons, in much the same way as for changepoint observations in our previous model.
However, the model was also endowed with knowledge of the transition structure of the task, which
includes that oddballs are typically followed by non-oddball trials, and as such, the input layer activity
bump would transition to its previous non-oddball location subsequent to learning from the oddball outcome
(L. Q. Yu et al., 2021). Consequently, the learned associations from oddball trials would not be stored in
the same context as the ordinary trials, and predictions were always made from the previous "non-oddball"
context – thereby minimizing the degree to which oddballs contribute to behavior.

Like in the changepoint condition, we also created versions of the model in which oddballs were inferred
probabilistically using either a Bayesian inference model or the activity profile of the output units. Oddball
probabilities (computed either from the normative model or the network's output activity itself) were then
used to guide transitions of the active input layer units (figure 6b). In these models the probability of an
oddball event drove immediate transitions of the active input layer units to facilitate storage of information
related to oddballs in a separate location, but subsequent predictions were always made from the input units
corresponding to the most recent non-oddball event (plus a constant expected drift). These models achieved
significantly better overall performance than the best fixed context shift model and similar performance to
the ground truth context shift model (figure 6c&d). The advantage conferred through dynamic context shifts
was specific to the oddball structural assumptions, as a model that employed dynamic context shifts based
on the changepoint generative structure yielded worse performance than fixed context shift models (figure
6c&d, red). It is noteworthy that, given the appropriate structural representation, the dynamic context shift
model produced normative behavior in changepoint condition, where it increased learning by sustaining the
newly activated context, but produced normative learning in the oddball context (decreasing learning on
oddball trials) by immediately abandoning the new context in favor of the more "typical" one.
٧٠٢

Dynamic context shifts explain bidirectional learning signals observed in the brain

A primary objective in this study was to identify the missing link between the algorithms that afford adaptive learning in dynamic environments and their biological implementations. One key challenge to forging such a link has been the contextual sensitivity of apparent "learning rate" signals observed in the brain. For example, in EEG studies the P300 associated with feedback onset positively predicts behavioral adjustments in static or changing environments (Fischer & Ullsperger, 2013; Jepma et al., 2018, 2016), but negatively predicts behavioral adjustments in the oddball condition that we describe above (Nassar, Bruckner, et al., 2019). These bidirectional relationships are strongest in people who adjust their learning strategies most across conditions, and persist even after controlling for a host of other factors related to behavior, suggesting that they are actually playing a role in learning, albeit a complex one (Nassar, Bruckner, et al., 2019).

Here we propose an alternative mechanistic role for the P300: that it reflects the need for a context shift. Our model provides an intuition for why such a signal might yield the previously observed bidirectional relationship to learning. A stronger P300 signal, corresponding to a larger context shift, would result in a stronger partition between current learning and previously learned associations. In changing environments, this could effectively increase learning, as it would decrease the degree to which prior experience is reflected in the weights associated with the currently active input units. In the oddball environment, where context changes *prevent* oddball events from affecting weights of the relevant input layer units, we would make the opposite prediction. We tested this idea directly in our model by measuring the effective learning rate in the dynamic context shift model for bins of trials sorted according to the magnitude of context shift that was used for them. The results of this analysis revealed a positive relationship between the context shift employed by the model and its effective learning rate in the changepoint condition, but a negative relationship between context shift and learning rate in the oddball condition (figure 6e). This result is qualitatively similar to empirically observed bidirectional relationships between learning and the P300 (figure 6f). Thus, our results are consistent with the possibility that the P300 relates to learning indirectly, by signaling or promoting transitions in a mental context representation that effectively partition learning across context boundaries, including changepoints and oddballs.

Relationship between context shifts and pupil diameter response:

One major theory of learning has suggested that adaptive learning is facilitated by fluctuations in arousal mediated by the LC/NE system (A. J. Yu & Dayan, 2005). This idea has been supported by evidence from transient pupil dilations, which in animals are linked to LC/NE signaling (Joshi & Gold, 2020; Reimer et al., 2016), and are positively related to learning in changing environments (Nassar et al., 2012). Nonetheless, these results are difficult to interpret in light of another study that employed both changepoints and oddballs and observed the opposite relationship between pupil dilation and learning (O'Reilly et al., 2013). The contextual link between pupil diameter and learning may have a common biological origin to that of the P300 signal explored above, as the signals share a host of common antecedents and have both been proposed to reflect transient LC/NE signaling (Joshi & Gold, 2020; Nieuwenhuis, De Geus, & Aston-Jones, 2011; Vazey & Aston-Jones, 2014). In contrast to learning theories, another prominent theory has suggested that the LC/NE system plays a role in resetting ongoing context representations (Network reset hypothesis; Bouret & Sara, 2005), which maps well onto the context shift signals that our model requires to adjust effective learning rates.

Here we formalize the network reset hypothesis in terms of context transitions in our model, and explore the predictions of this formalization for the relationship between pupil diameter and learning. Specifically,

we consider the possibility that LC/NE system is related to the instantaneous context shifts in our model, and that pupil dilations occur as a delayed and temporally smeared version of this LC/NE signal (see methods). In this framework we might consider two distinct influences on the pupil diameter. First, the context shifts elicited by observations that deviate substantially from expectations, which might reflect either changepoints or oddballs depending on the statistical context (figure 7a, purple observation highlighted in green box). Second, the context shift required to "return" to the previous context after a likely oddball event, which must occur after processing feedback from a given trial, but before the start of the next trial (figure 7a, red box). Jointly considering transitions at these two discrete timepoints yields the prediction that both changepoints and oddball events should lead to pupil dilations, but that these dilations should be prolonged in the oddball condition (figure 7b). We regressed these pupil signals onto an explanatory matrix that included model-derived measures of learning (trial-wise empirically derived learning rate) and surprise (estimated changepoint/oddball probability) to better understand their relationship to behavior. The results from this simulation yielded a positive relationship between our modeled pupil signal and surprise, but a late negative relationship between pupil diameter and learning (Fig 7c). These results are generally in agreement with O'Reilly 2013, and support the possibility that pupil diameter reflects a temporally extended indicator of the context transitions predicted by our model. We suggest that this idea can be empirically tested in future studies involving pupillometry in predictive inference tasks with two distinct generative structures (oddball, changepoint) where our predictions state that pupil dilations would be observed during both conditions but with different temporal profiles: the changepoint condition with a pupil response corresponding to only one initial context shift but the oddball condition including two responses for each respective context shift.

A — Ground Truth Model — Oddball

B — Dynamic Context Shift Model — Oddball Probability

C

- ● Dynamic (Changepoint) Context Shifts
- ● Dynamic (Bayesian) Context Shifts
- ● Dynamic (Network-Based) Context Shifts
- ● Fixed Context Shifts
- ● Ground Truth Model

Model Simulations

Empirical Data (Nassar et al 2019)

Figure 6 – Dynamic context shifts facilitate adaptive learning in presence of oddballs. A) Schematic representation of the ground truth model for the oddball environment, which has a constant context shift proportionate to the environmental drift. On oddball trials (third row) there is a large context shift, but context on next trial returns to its pre-oddball activity pattern. B) Schematic of the dynamic context shift model for the oddball task, which on each trial shifts the context according to oddball probability (OBP), but after receiving the supervised learning signal from the outcome, returns to its pre-oddball context, plus a small shift to account for the constant drift in helicopter position. Thus, context representations drift slowly on each trial, much as the helicopter position drifts. However, a trial with high oddball probability will cause the supervised signal to be stored in a completely separate context, and since context is reset to the previous value before the subsequent trial, any learning done from probable oddball events will not affect behavior on the subsequent trial. C) Example predictions of the two dynamic context shift models (pink & yellow) across 60 trials of the oddball condition compared to with the changepoint version of dynamic context shift model (red). Note that the oddball dynamic context shift models (pink &yellow) do not react to deviant outcomes (gray points) whereas the model that employs changepoint generative assumption (red) completely adjusts predictions after experiencing a deviant outcome. D) The dynamic context shift models had better aggregate performance than the best fixed context shift model ($Bayesian\ Context\ Shift\ Model: t = 9.22.\ df = 31.\ p = 2.13 \times 10^{-10}. Network - Based\ Model: t = 7.85.\ df = 31.\ p = 7.2 \times 10^{-9}$), and approached the performance of the ground truth model. E) Effective learning rate for the network-based context shift model (ordinate) was computed for subsets of simulated trials selected according to the magnitude of context shifts on those trials (abscissa) separately for changepoint (yellow) and oddball (blue) tasks. Note that larger context shifts in the changepoint condition correspond with greater learning, but in the oddball correspond with less learning. F) Effective learning rate computed for human participants (ordinate; Nassar 2019) in binned according to the magnitude of feedback-locked P300 EEG signal on that trial (abscissa) separately for changepoint (blue) and oddball (yellow) task conditions. Note qualitative similarity between the empirical observations related to the P300 signal and our models predictions regarding context shift magnitude.

A

Outcome

- Oddball Condition
- ChangePoint Condition
- ChangePoint/Oddball Trial

Trial

B ×10⁻³

Predicted Pupil Response

Early Feedback Window

Late Feedback Window

- Oddball Trial
- ChangePoint Trial
- Neutral Trial

C ×10⁻³

time

coefficinets

SURPRISE

Learning

time

Figure 7 -- Pupil responses simulated to reflect context shifts at multiple timepoints within a trial positively
reflect surprise and negatively reflect learning across changepoint and oddball conditions. A) An example set of
outcomes (ordinate) over trials (abscissa) is depicted to demonstrate the key difference between the changepoint
(orange) and oddball (cyan) generative structures. Based our dynamic and network-based context shift models
predictions, a surprising outcome is accompanied by a context shift in both the changepoint and oddball conditions
(green box). A second context shift is predicted to happen only in the oddball condition in the inter-trial interval after
experiencing an oddball event (red box), corresponding to the expected return to the more typical context (cyan points).
B) Predicted pupil responses (ordinate) are plotted over time (abscissa) for three trial types (colors). Pupil responses
were simulated as the convolution of a gamma function with the expected context shift on each trial at two discrete
time points. The first occurred at 400 ms after observing the outcome, and context shifts at this time point were
proportional to changepoint probability/oddball probability in our model; the second time point was at 900ms after
the outcome when subjects would be expected to begin preparing a prediction for the next trial outcome, the context
shifts at this time point were proportional to the inter-trial-interval context shifts necessary to return to the "typical"
context after an oddball trial. Based on predictions of our model, a context shift should occur at the first time point in
both changepoint and oddball trials while a context shift at the second timepoint should only to happen at the oddball
condition. C) Simulated pupil responses positively reflect surprise early after feedback (light gray) but negatively
reflect learning during a later time window (dark gray). Coefficients for learning and surprise were obtained by
regressing simulated pupil responses onto an explanatory matrix that contained regressors capturing surprise
(changepoint/oddball probability) and learning (dynamic trial-by-trial learning rate) as estimated by a reduced
Bayesian model.
٨٢٥
٨٢٦

Discussion
Existing models of adaptive learning have failed to capture the range of behaviors in humans across
different statistical environments and their underlying neural correlates. To address this issue, we
considered experimental findings that were not consistent with the existing models of adaptive learning and
developed a neural network framework that could account for them. Within this framework we demonstrate
that abrupt transitions in context, triggered by unexpected outcomes, can facilitate improved performance
in two different statistical environments that differ in the sort of adaptive learning that they require, and do
so in a manner that mimics human behavior. Specifically, we showed that human participants behavior in
a predictive inference task can be explained by a mixture of fixed and dynamic context shifts. The neural
network model that we proposed underwent context transitions that depended on the likelihood of the
observed outcome and the hazard rate. The hazard rate that optimized performance and matched participant
behavior in our simulations, was considerably higher than the true rate of changepoints in the task (0.1),
calling to question whether it should really be interpreted as a hazard rate. One alternative interpretation
would be to think of this parameter as controlling the threshold of a nonlinear activation function that
monitors conflict in the output layer the network, which is the mechanistic role that it plays in our network.

Context representations from this dynamic model provide a mechanistic interpretation of cortical activity
patterns that abruptly change during periods of rapid learning(Karlsson et al., 2012; Nassar, McGuire, et
al., 2019). The context shift signal, which allows the model to adjust context representations dynamically
in order to afford adaptive learning behaviors, provides a mechanistic interpretation for feedback locked
P300 signals that conditionally predict learning, and may also resolve a contradiction in different studies
examining the relationship between pupil dilation and learning(Nassar, Bruckner, et al., 2019). Taken
together, our results provide a mechanistic explanation for adaptive learning behavior and the signals that
give rise to it, and furthermore suggest that apparent adjustments in "how much" to learn may actually
reflect the dynamics controlling "where" learning takes place. The true test of this model will come from
future experiments to validate the new predictions of the current model.

The input layer that our model employs for flexible learning builds on the notion of latent states for
representation learning. Through this lens, our work can be thought of as an extension to a larger body of

research on structure learning, much of which has focused on identifying commonalities across stimulus
categories (A. G. E. Collins & Frank, 2013; Gershman & Niv, 2010). In cases where temporal dynamics
have been explored, the focus has been on the degree to which latent states allow efficient pooling of
information across similar contexts that are separated in time (A. G. E. Collins & Frank, 2013; Gershman,
Blei, & Niv, 2010; Wilson, Takahashi, Schoenbaum, & Niv, 2014). Here we highlight another advantage
of using temporal dynamics to control active state representations: efficient partitioning of information in
time to prevent interference. In addition to highlighting this advantage, our results highlight a shared
anatomical basis for state representations across different types of tasks. Patterns of input layer activity in
our model transition rapidly after changepionts to facilitate adaptive learning, much like network reset
phenomena that have been observed in medial prefrontal cortex in rodents and orbitofrontal cortex (OFC)
in humans(Karlsson et al., 2012; Nassar, Bruckner, et al., 2019). Rapid transitions in OFC are particularly
interesting given that this area has been suggested to represent latent states for sharing knowledge across
common structures (Schuck, Cai, Wilson, & Niv, 2016; Wilson et al., 2014). The existence of coordinated
changes in neural activity patterns in brain regions thought to reflect provides support for our assumption
that associations are controlled through changes in the pattern of active input units over time (e.g. figure 3),
rather than alternative accounts in which associations are selectively attributed to only a subset of active
units through synchronization (Verbeke & Verguts, 2019), although these two mechanisms need not be
mutually exclusive.

Our model description shares some mechanistic similarities with temporal context models (TCM) of
episodic and sequential memory recall. (DuBrow, Rouhani, Niv, & Norman, 2017; Franklin et al., 2020;
Howard & Kahana, 2002; Kornysheva et al., 2019; Polyn, Norman, & Kahana, 2009; Shankar, Jagadisan,
& Howard, 2009). In temporal context models, there is a gradual change in context activity that occurs
through passage of time or a through learned linear mapping of the stimuli to contexts, however our dynamic
model relies on discontinuous changes in context more analogous to the underlying latent state dynamics
and provides a normative rationale for such abrupt transitions at surprising events, namely that such
transitions promote pooling of relevant information within a context (figure 3d) and partitioning of
information across contexts (figure 3c) in order to improve inference in complex and dynamic environments
(figure 3e & figure 6d). These modeling assumptions allowed us to capture prediction behavior in
changepoint and oddball conditions – but to capture a more general set generative statistics – our model
would also need to incorporate the possibility of returning to a previous context, and thus considering a
hybrid between the assumptions in our model and those of the temporal context models might be an
interesting avenue for future study.

More recently, extensions of the temporal context models have suggested the existence of event boundaries
which cause discontinuity in temporal context (Zacks, Speer, Swallow, Braver, & Reynolds, 2007). The
emergence of these boundaries has been attributed to errors in predictions which, analogous to detected
outliers in our model, cause the subsequent observations to be stored in a different context (DuBrow &
Davachi, 2013; Rouhani, Norman, Niv, & Bornstein, 2020). Such segmented events also lead to more
dissociable representations in fMRI (Antony et al., 2020; Baldassano et al., 2017; Lositsky et al., 2016).
While these interpretations of discontinuity in memory are closely related to our model, we take a step
further by assigning a key role to such segmentations. In particular, our model shows that it is useful to
segment internal context representation after a surprising event in order to improve predictions.

An important question here is how to quantitatively control the transition to new contexts, particularly when
such context transitions are not overtly signaled. In previous computational models of event segmentation,
surprise has been suggested as the main factor controlling such transition probabilities (Schapiro, Rogers,
Cordova, Turk-Browne, & Botvinick, 2013). Our dynamic context shift model uses surprise, as indexed by

the probability of an unexpected event (changepoint/oddball), to control context shifts. Such probabilities
can be inferred using a Bayesian learning model calibrated to the environmental structure, however, we
show that they could also be estimated from output layer of our network itself. Previous work has suggested
that changepoint and oddball probability are reflected by BOLD activations in both cortical and subcortical
regions (D'Acremont & Bossaerts, 2016; Kao et al., 2020; McGuire et al., 2014; Meyniel & Dehaene, 2017;
Nassar, McGuire, et al., 2019; Nassar et al., 2012; O'Reilly et al., 2013; A. J. Yu & Dayan, 2005). While
such signals have previously been interpreted as early-stage computations performed in the service of
computing a learning rate, our work suggests that they serve another purpose, namely in signaling the need
to change the active context representation. This interpretation would be consistent with the observation
that in at least one case, BOLD responses to surprising events look quite similar across behavioral contexts
in which such events should be either learned from, or ignored (D'Acremont & Bossaerts, 2016).

The need for knowledge of transition structure in our model also raises the question of where this
information comes from. We speculate that, in the brain, this transition structure might be provided by a
separate set of neural systems that includes the medial temporal lobe (MTL). This speculation is based on
1) the observation that our context representations mirror the dynamics of representations in orbitofrontal
cortex (figure 5), 2) that OFC receives strong inputs from the medial temporal lobe (MTL) (Wikenheiser
& Schoenbaum, 2016), and 3) the important role played by the MTL in model based learning and
planning (Mattar & Daw, 2018; Schuck & Niv, 2019; Vikbladh et al., 2019). However, future work
examining adaptive learning behavior in the face of ambiguous transition structures may help to tease
apart the functional roles of different brain signals that occur at surprising task events (Bakst & McGuire,
2020).

Of particular interest in this regard is the feedback-locked P300 signal, an EEG-based correlate of surprise
in humans (Kolossa, 2016; Kopp et al., 2016; Mars et al., 2008). A recent study showed that this signal
positively related to learning in a changing environment and negatively related to learning in one containing
oddballs (Nassar, Bruckner, et al., 2019). Here we show that the context shift variable in our dynamic model
has the exact same bidirectional relationship to learning. In our model this reflects a causal relationship,
whereby context transitions that persist in the changepoint condition lead new observations to have greater
behavioral impact (i.e. more learning; figure 6e), and transient context transitions in the oddball condition
limit the behavioral impact of oddball events by associating them with a different context from the one in
which predictions are generated (i.e. less learning; figure 6e). We note that this distinction relies in part on
our definition of learning. In reality, our model makes the same sorts of weight adjustments for both
situations, yet the situations differ in the degree to which those weight adjustments impact future
predictions.

This bidirectional adjustment of learning rate is a key prediction of our model. We also predict that other
physiological measures of surprise that have previously been related to learning, such as pupil diameter,
should also provide similar results in environments with different sources of surprising outcomes. However,
a key difference of pupil dilation predictions is that given the slow time course of the pupil signal, we
predict that it will aggregate multiple state transitions that can occur on an oddball trial (i.e. the transition
away from the original state to a new one, and the transition back to the original state). This aspect of the
signaling predicts heightened pupil dilations on oddball relative to changepoint trials, which agrees
qualitatively with previous observations (O'Reilly et al., 2013), and may help to resolve confusion in the
existing literature regarding the relationship between pupil dilations and behavioral adjustment (Nassar et
al., 2012; O'Reilly et al., 2013). Our model predicts that such a signal should also drive changes in state
representations in OFC. This prediction, at least in part, is consistent with another recent experiment on
neuromodulatory control of uncertainty (Muller et al., 2019), in which the strength of pupil dilation predicts

the level of uncertainty regarding the current state of the environment, represented in medial orbitofrontal
cortex. Our model predicts that these relationships should also depend on the task structure, with state
transitions driving OFC representations toward an alternative state in reversal tasks (Muller et al., 2019)
toward a completely new persisting state in changepoint tasks (Nassar, McGuire, et al., 2019) and toward
a transient state after oddball events. These relationships between state transition signals and neural
representations have yet to be measured across the range of contexts that would be necessary to fully test
our models predictions, and thus is an interesting avenue for future empirical work.

A major implication of our findings is that behavioral markers of learning rate adjustment may be produced
by a network that relies on a fixed learning rate (the rate of synaptic weight changes), so long as that network
adjusts its own internal representations according to the structure of the environment. This is also what
distinguishes our model from other accounts of behavior (Nassar et al., 2012, 2010) that adjust learning rate
directly, or from computational models that have used surprise detection signals to control learning rate at
the synaptic level (Iigaya, 2016). By introducing context shifts in our model we were able to build a
mechanistic role for surprise in a learning algorithm that can explain the conditional nature of heretofore
identified learning rate signals: they are actually signaling state transitions, rather than learning per se.

Our model opens the door for a number of future investigations. We catered our analysis to the behavioral
experiments of Nassar et al 2019 (Nassar, Bruckner, et al., 2019; Nassar, McGuire, et al., 2019), and
therefore only considered changepoint and oddball conditions but did not study the case where context
could either shift to a new context or return to a previous context it has learned before. Recognizing that a
new observation actually comes from a previously learned context would involve additional pattern
recognition and memory retrieval mechanisms (Redish, Jensen, Johnson, & Kurth-nelson, 2007), which
might be thought of as part of a more general model-based inference framework as described above
(Franklin, Norman, Ranganath, Zacks, & Gershman, 2020; Whittington et al., 2019). That is to say, in order
to solve all types of real-world problems, our model would be required to know not only that an observation
is different from the recent past, but also which previously encountered state would provide the best
generalization to this new situation. Doing so effectively would require organization of states based on
similarity, such that similar states shared learning to some degree, in the same way that states which occur
nearby in time pool learning in our current model.

Model limitations

The design of our network has several limitations that would need to be overcome to fully realize the
potential of our overarching framework. The first is that our network was endowed with knowledge of the
task transition structure – raising an important question for future work as to how this structure could be
learned directly from observations. In our tasks the transition structure differed between changepoints and
oddballs, with changepoints promoting persisting state representations and oddballs promoting an
immediate transition back to the previous state, however real-world learning occurs in a much more
diverse set of environments, where simultaneously learning transition structure and applying it to guide
behavioral adjustment would be challenging to say the least.

A second set of limitations stems from our simplified ring organization of the input (context) layer of our
network. This simplification causes potential issues for the oddball condition we model, in that future
contexts could rely on the same input units that were previously associated with oddball events. In our
simplified network we solved this problem through slow weight decays that slowly turn unused input
units into blank slates for future learning. However, we suspect that the brain uses a different solution,
namely a more complex organization of context representations – for example if the input layer were two

dimensional, with one dimension corresponding to slow drifts and the other corresponding to oddball
events, an oddball context could never be encountered with any amount of drift.

Another set of limitations would emerge if our model were required to re-use previously encountered
input representations to transfer knowledge about a repeated context. This situation would present two
main challenges to our current network design. The first is that the weight decay mechanisms in our
network would erase memories from previously visited contexts. This limitation could be overcome by
eliminating weight decay mechanisms and instead equipping the network with a relatively large number
of input units to prevent interference (see supplementary figure 5 at *https://github.com/learning-memory-*
and-decision-lab/dynamicStatesLearning). Although increasing the number of input units provides a
reasonable solution for our toy problems, this solution may not scale for life-long learning, where the
number of unique contexts may approach the number of unique mental context representations – raising
an important question for future research. A second challenge for our model in repeating contexts would
be to identify the input units that should be active in response to a previously encountered state. Our
model was given transition structure for the environments we examined (changepoints/oddballs), and this
transition structure controlled how input layer activations were updated in each environment. In
principle, state update rules could be derived for repeating contexts in much the same way, by first
deriving Bayesian estimates of context probability(A. Collins & Koechlin, 2012) and then approximating
these values using the network output (analogous to our network-based context shift model). We hope
that our model inspires future work to examine this idea in more detail.

١٠٠٦

١٠٠٧   Summary

١٠٠٨

In summary, we suggest that flexible learning emerges from dynamic internal context representations that
are updated in response to surprising observations in accordance with task structure. Our model requires
representations consistent with those that have previously been observed in orbitofrontal cortex as well as
state transition signals necessary to update them. We suggest that biological signals previously thought to
reflect "dynamic learning rates" actually signal the need for internal state transitions, and our model
provides the first mechanistic explanation for the context-dependence with which these signals relate to
learning. Taken together, our results support the notion that adaptive learning behaviors may arise through
dynamic control of representations of task structure

١٠١٧

١٠١٨   **Data Availability**

١٠١٩   All analysis and modeling code (including code for generating the figures) has been made available on
١٠٢٠   GitHub: https://github.com/learning-memory-and-decision-lab/dynamicStatesLearning

١٠٢١

١٠٢٢

١٠٢٣   **References:**

١٠٢٤   Adams, R. P., & MacKay, D. J. C. (2007). *Bayesian Online Changepoint Detection*. Retrieved from
١٠٢٥   http://arxiv.org/abs/0710.3742

Antony, J. W., Hartshorne, T. H., Pomeroy, K., Gureckis, T. M., Hasson, U., McDougle, S. D., & Norman, K. A. (2020). Behavioral, physiological, and neural signatures of surprise during naturalistic sports viewing. *BioRxiv*, 2020.03.26.008714. https://doi.org/10.1101/2020.03.26.008714

Bakst, L., & McGuire, J. (2020). Eye movements reflect adaptive predictions and predictive precision. *Journal of Experimental Psychology: General*. https://doi.org/10.1037/xge0000977

Baldassano, C., Chen, J., Zadbood, A., Pillow, J. W., Hasson, U., & Norman, K. A. (2017). Discovering Event Structure in Continuous Narrative Perception and Memory. *Neuron*, *95*(3), 709-721.e5. https://doi.org/10.1016/j.neuron.2017.06.041

Behrens, T. E. J., Woolrich, M. W., Walton, M. E., & Rushworth, M. F. S. (2007). *Learning the value of information in an uncertain world*. *10*(9), 1214–1221. https://doi.org/10.1038/nn1954

Bernacchia, A., Seo, H., Lee, D., & Wang, X.-J. (2011). A reservoir of time constants for memory traces in cortical neurons. *Nature Neuroscience*, *14*(3), 366–372. https://doi.org/10.1038/nn.2752

Botvinick, M. M., Braver, T. S., Barch, D. M., Carter, C. S., & Cohen, J. D. (2001). Conflict monitoring and cognitive control. *Psychological Review*, Vol. 108, pp. 624–652. https://doi.org/10.1037/0033-295X.108.3.624

Bouret, S., & Sara, S. J. (2005). Network reset: a simplified overarching theory of locus coeruleus noradrenaline function. *Trends in Neurosciences*, *28*(11), 574–582. https://doi.org/10.1016/j.tins.2005.09.002

Browning, M., Behrens, T. E., Jocham, G., O'Reilly, J. X., & Bishop, S. J. (2015). Anxious individuals have difficulty learning the causal statistics of aversive environments. *Nature Neuroscience*, *18*(4), 590–596. https://doi.org/10.1038/nn.3961

Cockburn, J., & Frank, M. (2013). Reinforcement Learning, Conflict Monitoring, and Cognitive Control: An Integrative Model of Cingulate-Striatal Interactions and the ERN. *Neural Basis of Motivational and Cognitive Control*, 310–331. https://doi.org/10.7551/mitpress/9780262016438.003.0017

Collins, A. G. E., & Frank, M. J. (2013). Cognitive control over learning: creating, clustering, and generalizing task-set structure. *Psychological Review*, *120*(1), 190–229. https://doi.org/10.1037/a0030852

Collins, A., & Koechlin, E. (2012). Reasoning, learning, and creativity: Frontal lobe function and human decision-making. *PLoS Biology*, *10*(3). https://doi.org/10.1371/journal.pbio.1001293

D'Acremont, M., & Bossaerts, P. (2016). Neural Mechanisms behind Identification of Leptokurtic Noise and Adaptive Behavioral Response. *Cerebral Cortex*, *26*(4), 1818–1830. https://doi.org/10.1093/cercor/bhw013

Donahue, C. H., & Lee, D. (2015). Dynamic routing of task-relevant signals for decision making in dorsolateral prefrontal cortex. *Nature Neuroscience*, *18*(2), 295–301. https://doi.org/10.1038/nn.3918

DuBrow, S., & Davachi, L. (2013). The influence of context boundaries on memory for the sequential order of events. *Journal of Experimental Psychology: General*, *142*(4), 1277–1286. https://doi.org/10.1037/a0034024

Farashahi, S., Donahue, C. H., Hayden, B. Y., Lee, D., & Soltani, A. (2019). Flexible combination of reward information across primates. *Nature Human Behaviour*, *3*(11), 1215–1224. https://doi.org/10.1038/s41562-019-0714-3

Farashahi, S., Donahue, C. H., Khorsand, P., Seo, H., Lee, D., & Soltani, A. (2017). Metaplasticity as a
Neural Substrate for Adaptive Learning and Choice under Uncertainty. *Neuron*, *94*(2), 401-414.e6.
https://doi.org/10.1016/j.neuron.2017.03.044

Fischer, A. G., & Ullsperger, M. (2013). Real and Fictive Outcomes Are Processed Differently but
Converge on a Common Adaptive Mechanism. *Neuron*, *79*(6), 1243–1255.
https://doi.org/10.1016/j.neuron.2013.07.006

Franklin, N. T., Norman, K. A., Ranganath, C., Zacks, J. M., & Gershman, S. J. (2020). Structured Event
Memory: A neuro-symbolic model of event cognition. *Psychological Review*, *127*(3), 327–361.
https://doi.org/10.1037/rev0000177

Gershman, S. J., Blei, D. M., & Niv, Y. (2010). Context, Learning, and Extinction. *Psychological Review*,
Vol. 117, pp. 197–209. Retrieved from
https://nivlab.princeton.edu/sites/default/files/nivlab/files/gershmanetal2009.pdf

Gershman, S. J., & Niv, Y. (2010). Learning latent structure: Carving nature at its joints. *Current Opinion*
in Neurobiology, *20*(2), 251–256. https://doi.org/10.1016/j.conb.2010.02.008

Iigaya, K. (2016). Adaptive learning and decision-making under uncertainty by metaplastic synapses
guided by a surprise detection system. *ELife*, *5*, e18073. https://doi.org/10.7554/eLife.18073

Jepma, M., Brown, S. B. R. E., Murphy, P. R., Koelewijn, S. C., de Vries, B., van den Maagdenberg, A.
M., & Nieuwenhuis, S. (2018). Noradrenergic and Cholinergic Modulation of Belief Updating.
Journal of Cognitive Neuroscience, *30*(12), 1803–1820. https://doi.org/10.1162/jocn_a_01317

Jepma, M., Murphy, P. R., Nassar, M. R., Rangel-Gomez, M., Meeter, M., & Nieuwenhuis, S. (2016).
Catecholaminergic Regulation of Learning Rate in a Dynamic Environment. *PLOS Computational*
Biology, *12*(10), e1005171. Retrieved from https://doi.org/10.1371/journal.pcbi.1005171

Joshi, S., & Gold, J. I. (2020). Pupil Size as a Window on Neural Substrates of Cognition. *Trends in*
Cognitive Sciences, *24*(6), 466–480. https://doi.org/10.1016/j.tics.2020.03.005

Kao, C.-H., Khambhati, A. N., Bassett, D. S., Nassar, M. R., McGuire, J. T., Gold, J. I., & Kable, J. W.
(2020). Functional brain network reconfiguration during learning in a dynamic environment. *Nature*
Communications, *11*(1), 1682. https://doi.org/10.1038/s41467-020-15442-2

Karlsson, M. P., Tervo, D. G. R., & Karpova, A. Y. (2012). Network Resets in Medial Prefrontal Cortex
Mark the Onset of Behavioral Uncertainty. *Science*, *338*(6103), 135 LP – 139.
https://doi.org/10.1126/science.1226518

Kolossa, A. (2016). *A New Theory of Trial-by-Trial P300 Amplitude Fluctuations*.
https://doi.org/10.1007/978-3-319-32285-8_3

Kopp, B., Seer, C., Lange, F., Kluytmans, A., Kolossa, A., Fingscheidt, T., & Hoijtink, H. (2016). P300
amplitude variations, prior probabilities, and likelihoods: A Bayesian ERP study. *Cognitive,*
Affective, & Behavioral Neuroscience, *16*(5), 911–928. https://doi.org/10.3758/s13415-016-0442-3

Li, Y. S., Nassar, M. R., Kable, J. W., & Gold, J. I. (2019). Individual Neurons in the Cingulate Cortex
Encode Action Monitoring, Not Selection, during Adaptive Decision-Making. *The Journal of*
Neuroscience, *39*(34), 6668 LP – 6683. https://doi.org/10.1523/JNEUROSCI.0159-19.2019

Lositsky, O., Chen, J., Toker, D., Honey, C. J., Shvartsman, M., Poppenk, J. L., … Norman, K. A. (2016).
Neural pattern change during encoding of a narrative predicts retrospective duration estimates.
ELife, *5*, e16070. https://doi.org/10.7554/eLife.16070

Mars, R. B., Debener, S., Gladwin, T. E., Harrison, L. M., Haggard, P., Rothwell, J. C., & Bestmann, S.
(2008). Trial-by-Trial Fluctuations in the Event-Related Electroencephalogram Reflect Dynamic
Changes in the Degree of Surprise. *The Journal of Neuroscience*, *28*(47), 12539 LP – 12545.
https://doi.org/10.1523/JNEUROSCI.2925-08.2008

Massi, B., Donahue, C. H., & Lee, D. (2018). Volatility Facilitates Value Updating in the Prefrontal
Cortex. *Neuron*, *99*(3), 598-608.e4. https://doi.org/https://doi.org/10.1016/j.neuron.2018.06.033

Mathys, C., Daunizeau, J., Friston, K. J., & Stephan, K. E. (2011). A bayesian foundation for individual
learning under uncertainty. *Frontiers in Human Neuroscience*, *5*, 39.
https://doi.org/10.3389/fnhum.2011.00039

Mattar, M. G., & Daw, N. D. (2018). Prioritized memory access explains planning and hippocampal
replay. *Nature Neuroscience*, *21*(11), 1609–1617. https://doi.org/10.1038/s41593-018-0232-z

McGuire, J. T., Nassar, M. R., Gold, J. I., & Kable, J. W. (2014). Functionally dissociable influences on
learning rate in a dynamic environment. *Neuron*, *84*(4), 870–881.
https://doi.org/10.1016/j.neuron.2014.10.013

Meyniel, F., & Dehaene, S. (2017). Brain networks for confidence weighting and hierarchical inference
during probabilistic learning. *Proceedings of the National Academy of Sciences of the United States*
of America, *114*(19), E3859–E3868. https://doi.org/10.1073/pnas.1615773114

Muller, T. H., Mars, R. B., Behrens, T. E., & O'Reilly, J. X. (2019). Control of entropy in neural models
of environmental state. *ELife*, *8*, 1–30. https://doi.org/10.7554/eLife.39404

Nassar, M. R., Bruckner, R., & Frank, M. J. (2019). Statistical context dictates the relationship between
feedback-related EEG signals and learning. *ELife*, *8*, 1–26. https://doi.org/10.7554/eLife.46975

Nassar, M. R., & Gold, J. I. (2010). *Supplementary Material for : Bayesian On-line Learning of the*
Hazard Rate in Change-Point Problems. 22(9), 2452–2476.

Nassar, M. R., McGuire, J. T., Ritz, H., & Kable, J. W. (2019). Dissociable forms of uncertainty-driven
representational change across the human brain. *Journal of Neuroscience*, *39*(9), 1688–1698.
https://doi.org/10.1523/JNEUROSCI.1713-18.2018

Nassar, M. R., Rumsey, K. M., Wilson, R. C., Parikh, K., Heasly, B., & Gold, J. I. (2012). Rational
regulation of learning dynamics by pupil-linked arousal systems. *Nature Neuroscience*, *15*(7), 1040–
1046. https://doi.org/10.1038/nn.3130

Nassar, M. R., & Troiani, V. (2020). The stability flexibility tradeoff and the dark side of detail.
Cognitive, Affective, & Behavioral Neuroscience. https://doi.org/10.3758/s13415-020-00848-8

Nassar, M. R., Waltz, J. A., Albrecht, M. A., Gold, J. M., & Frank, M. J. (2021). All or nothing belief
updating in patients with schizophrenia reduces precision and flexibility of beliefs. *Brain*.
https://doi.org/10.1093/brain/awaa453

Nassar, M. R., Wilson, R. C., Heasly, B., & Gold, J. I. (2010). An approximately Bayesian delta-rule
model explains the dynamics of belief updating in a changing environment. *Journal of*
Neuroscience, *30*(37), 12366–12378. https://doi.org/10.1523/JNEUROSCI.0822-10.2010

Nieuwenhuis, S., De Geus, E. J., & Aston-Jones, G. (2011). The anatomical and functional relationship
between the P3 and autonomic components of the orienting response. *Psychophysiology*, *48*(2),
162–175. https://doi.org/10.1111/j.1469-8986.2010.01057.x

O'Reilly, J. X. (2013). Making predictions in a changing world-inference, uncertainty, and learning.

Frontiers in Neuroscience, *7*(7 JUN), 1–10. https://doi.org/10.3389/fnins.2013.00105

O'Reilly, J. X., Schüffelgen, U., Cuell, S. F., Behrens, T. E. J., Mars, R. B., & Rushworth, M. F. S.
(2013). Dissociable effects of surprise and model update in parietal and anterior cingulate cortex.
Proceedings of the National Academy of Sciences of the United States of America, *110*(38).
https://doi.org/10.1073/pnas.1305373110

Redish, A. D., Jensen, S., Johnson, A., & Kurth-nelson, Z. (2007). *Reconciling Reinforcement Learning*
Models With Behavioral Extinction and Renewal : Implications for Addiction , Relapse , and
Problem Gambling. *114*(3), 784–805. https://doi.org/10.1037/0033-295X.114.3.784

Reimer, J., McGinley, M. J., Liu, Y., Rodenkirch, C., Wang, Q., McCormick, D. A., & Tolias, A. S.
(2016). Pupil fluctuations track rapid changes in adrenergic and cholinergic activity in cortex.
Nature Communications, *7*(1), 13289. https://doi.org/10.1038/ncomms13289

Rouhani, N., Norman, K. A., Niv, Y., & Bornstein, A. M. (2020). Reward prediction errors create event
boundaries in memory. *Cognition*, *203*, 104269.
https://doi.org/https://doi.org/10.1016/j.cognition.2020.104269

Schapiro, A. C., Rogers, T. T., Cordova, N. I., Turk-Browne, N. B., & Botvinick, M. M. (2013). Neural
representations of events arise from temporal community structure. *Nature Neuroscience*, *16*(4),
486–492. https://doi.org/10.1038/nn.3331

Schuck, N. W., Cai, M. B., Wilson, R. C., & Niv, Y. (2016). Human Orbitofrontal Cortex Represents a
Cognitive Map of State Space. *Neuron*, *91*(6), 1402–1412.
https://doi.org/10.1016/j.neuron.2016.08.019

Schuck, N. W., & Niv, Y. (2019). Sequential replay of nonspatial task states in the human hippocampus.
Science, *364*(6447), eaaw5181. https://doi.org/10.1126/science.aaw5181

Soltani, A., & Izquierdo, A. (2019). Adaptive learning under expected and unexpected uncertainty.
Nature Reviews Neuroscience, *20*(10), 635–644. https://doi.org/10.1038/s41583-019-0180-y

Vazey, E. M., & Aston-Jones, G. (2014). Designer receptor manipulations reveal a role of the locus
coeruleus noradrenergic system in isoflurane general anesthesia. *Proceedings of the National*
Academy of Sciences of the United States of America, *111*(10), 3859–3864.
https://doi.org/10.1073/pnas.1310025111

Verbeke, P., & Verguts, T. (2019). Learning to synchronize: How biological agents can couple neural
task modules for dealing with the stability-plasticity dilemma. *PLOS Computational Biology*, *15*(8),
e1006604. Retrieved from https://doi.org/10.1371/journal.pcbi.1006604

Vikbladh, O. M., Meager, M. R., King, J., Blackmon, K., Devinsky, O., Shohamy, D., … Daw, N. D.
(2019). Hippocampal Contributions to Model-Based Planning and Spatial Memory. *Neuron*, *102*(3),
683-693.e4. https://doi.org/10.1016/j.neuron.2019.02.014

Whittington, J. C. R., Muller, T. H., Mark, S., Chen, G., Barry, C., Burgess, N., & Behrens, T. E. J.
(2019). The Tolman-Eichenbaum Machine: Unifying space and relational memory through
generalisation in the hippocampal formation. *BioRxiv*, 770495. https://doi.org/10.1101/770495

Wikenheiser, A., & Schoenbaum, G. (2016). Over the river, through the woods: cognitive maps in the
hippocampus and orbitofrontal cortex. *Nature Reviews Neuroscience*, *17*.
https://doi.org/10.1038/nrn.2016.56

Wilson, R. C., Nassar, M. R., & Gold, J. I. (2010). Bayesian online learning of the hazard rate in change-
point problems. *Neural Computation*, *22*(9), 2452–2476. https://doi.org/10.1162/NECO_a_00007

Wilson, R. C., Nassar, M. R., & Gold, J. I. (2013). A mixture of delta-rules approximation to bayesian
inference in change-point problems. *PLoS Computational Biology*, *9*(7), e1003150–e1003150.
https://doi.org/10.1371/journal.pcbi.1003150

Wilson, R. C., Takahashi, Y. K., Schoenbaum, G., & Niv, Y. (2014). Orbitofrontal cortex as a cognitive
map of task space. *Neuron*, *81*(2), 267–279. https://doi.org/10.1016/j.neuron.2013.11.005

Yu, A. J., & Dayan, P. (2005). Uncertainty, neuromodulation, and attention. *Neuron*, *46*(4), 681–692.
https://doi.org/10.1016/j.neuron.2005.04.026

Yu, L. Q., Wilson, R. C., & Nassar, M. R. (2021). Adaptive learning is structure learning in time.
Neuroscience & Biobehavioral Reviews, *128*, 270–281.
https://doi.org/https://doi.org/10.1016/j.neubiorev.2021.06.024

Yu, L., Wilson, R., & Nassar, M. (2020). *Adaptive learning is structure learning in time*.
https://doi.org/10.31234/osf.io/r637c

Zacks, J. M., Speer, N. K., Swallow, K. M., Braver, T. S., & Reynolds, J. R. (2007). Event perception: A
mind-brain perspective. *Psychological Bulletin*, Vol. 133, pp. 273–293.
https://doi.org/10.1037/0033-2909.133.2.273

١٢٠٦