RNA secondary structure prediction using deep learning with thermodynamic integration

Kengo Sato[1], Manato Akiyama[1] & Yasubumi Sakakibara[1]

[1]*Department of Biosciences and Informatics, Keio University, 3–14–1 Hiyoshi, Kohoku-ku, Yokohama 223–8522, Japan*

RNA secondary structure prediction is one of the key technologies for revealing the essential roles of functional non-coding RNAs. Although machine learning-based rich-parametrized models have achieved extremely high performance in terms of prediction accuracy, the risk of overfitting for such models has been reported. We propose a new algorithm for predicting RNA secondary structures that uses deep learning with thermodynamic integration, thereby enabling robust predictions. Our algorithm computes folding scores for the nearest-neighbor loop using a deep neural network. Similar to our previous work, the folding scores are integrated with traditional thermodynamic parameters to enable robust predictions. Then, Zuker-style dynamic programming is employed to find an optimal secondary structure that maximizes the folding score. We also propose a new regularization, called thermodynamic regularization, for training our deep neural network without overfitting it to the training data. Our algorithm (MXfold2) archived the most robust and accurate predictions in the computational experiments designed for newly discovered non-coding RNAs. Our algorithm (MXfold2) achieved the most robust and accurate predictions in the computational experiments that included novel types of non-coding RNAs.

Recent studies have revealed that functional non-coding RNAs (ncRNAs) play essential roles, including transcriptional regulation and guiding modification, participating in various biological processes ranging from development to cell differentiation, with defective functionality being involved in various diseases[1]. Because it is well-known that the functions of ncRNAs are deeply related to their structures rather than their primary sequences, discovering the structures of ncRNAs can elucidate the functions of ncRNAs. However, there are major difficulties in determining RNA tertiary structures through experimental assays such as nuclear magnetic resonance and X-ray crystal structure analysis, because of the high experimental costs and resolution limits on measurements of RNA. Therefore, instead of conducting such experimental assays, we frequently perform computational prediction of RNA secondary structures, defined as sets of base-pairs with hydrogen bonds between the nucleotides.

The most popular approach for predicting RNA secondary structures is based on thermodynamic models, such as Turner's nearest-neighbor model[2,3], in which a secondary structure is decomposed into several characteristic substructures, called nearest-neighbor loops, such as hairpin loops, internal loops, bulge loops, base-pair stackings, multi-branch loops, and external loops, as shown in Fig. 1. The free energy of each nearest-neighbor loop can be calculated by summing the free energy parameters that characterize the loop. The free energy parameters have been determined in advance by experimental methods such as optical melting experiments[2]. The free energy of an entire RNA secondary structure is calculated by summing the free energy of the decomposed nearest-neighbor loops. We can employ dynamic programming to find an optimal secondary structure that minimizes the free energy of a given RNA sequence. A number of tools,

Figure 1: An RNA secondary structure can be decomposed into several types of nearest-neighbor loops, including hairpin loops (e.g., bases 11–19), internal loops (e.g., bases 25–29 and 43–47), bulge loops (e.g., bases 4–5 and 57–62), base-pair stackings (e.g., bases 23–24 and 48–49), multi-branch loops (e.g., bases 7–9, 21–23, and 49–55), and external loops (e.g., bases 1–2 and 64–66). This diagram was drawn using VARNA[14].

including Mfold/UNAfold[4,5], RNAfold[6,7], and RNAstructure[8,9], have adopted this approach.

An alternative approach utilizes machine learning techniques, which train scoring parameters for decomposed substructures from reference structures, rather than experimental techniques. This approach has successfully been adopted by CONTRAfold[10,11], ContextFold[12], and other methods, and has enabled us to more accurately predict RNA secondary structures. However, rich parameterization can easily cause overfitting to the training data, thus preventing robust predictions for a wide range of RNA sequences[13].

Hybrid methods that combine thermodynamic and machine learning-based approaches to

compensate for each other's shortcomings have been developed. SimFold[15,16] more accurately estimates thermodynamic parameters from training data, including RNA sequences and their known secondary structures as well as the free energy of their known secondary structures. We previously proposed MXfold[17], which combines thermodynamic energy parameters and rich-parameterized weight parameters. The model learns more precise parameters for substructures observed in training data and avoids overfitting rich-parameterized weight parameters to the training data by resorting to the thermodynamic parameters for assessing previously unobserved substructures.

In recent years, deep learning has made remarkable progress in a wide range of fields, including bioinformatics and life sciences. SPOT-RNA[18] and E2Efold[19] have been developed for RNA secondary structure prediction using deep neural networks (DNNs). Both algorithms formulated RNA secondary structure prediction as multiple binary classification problems that predict whether each pair of nucleotides forms a base pair or not, using a deep neural network trained with a large amount of training data. As with the other machine learning-based methods described above, concerns about overfitting due to rich parameterization remain.

Inspired by MXfold and the DNN-based RNA secondary structure prediction methods, in this paper, we propose a new algorithm for predicting RNA secondary structures using deep learning. Similar to MXfold, we integrate the folding scores, which are calculated by a deep neural network, with Turner's nearest-neighbor free energy parameters. The deep neural network is trained by the max-margin framework with thermodynamic regularization, which is proposed in this paper to make our model robust. These two techniques, the thermodynamic-integrated fold-

ing scores and the thermodynamic regularization, are referred to as thermodynamic integration. To confirm the robustness of our algorithm, we conducted the computational experiments on two types of cross-validation; sequence-wise cross-validation with test datasets structurally similar to training datasets, and family-wise cross-validation with test datasets structurally dissimilar to training datasets. The resulting method, called MXfold2, achieved the best prediction accuracy based not only on the sequence-wise cross-validation, but also the family-wise cross-validation, indicating the robustness of our algorithm. In addition, the computational experiment on a dataset with sequence-structure-energy triplets shows a high correlation between folding scores predicted by MXfold2 and the free energy derived from optical melting experiments.

Results

Overview of our algorithm. Our algorithm computes four types of folding scores for each pair of nucleotides by using a deep neural network, as shown in Fig. 2. The folding scores are used to calculate scores of the nearest-neighbor loops. Similar to MXfold, we integrate the folding scores, which are calculated by a deep neural network, with Turner's nearest-neighbor free energy parameters. Then, our algorithm predicts an optimal secondary structure that maximizes the sum of the scores of the nearest-neighbor loops using Zuker-style dynamic programming. The deep neural network is trained by the max-margin frame work, also known as structured support vector machine (SSVM), to minimize the structured hinge loss function with thermodynamic regularization.

Figure 2: The network structure of our algorithm, where act. indicates the activation function and norm. indicates the normalization function. The network calculates four types of folding scores for each pair of nucleotides (i, j) from a given RNA sequence of length L.

Effectiveness of the thermodynamic integration. To investigate the effectiveness of the thermo-dynamic integration, which is the main contribution of this study, we conducted an experiment to compare the cases with and without the novel thermodynamic integration. We implemented a base model that employs only the deep neural network to compute the folding score; that is, it does not use the thermodynamic parameters for the folding score and the subsequent thermodynamic regularization. Then, we compared the base model with the use of the thermodynamic-integrated folding score and/or the thermodynamic regularization. For this experiment, we employed Train-SetA, TestSetA, and TestSetB, which have been established by Rivas *et al.*[13]. Note that TrainSetA and TestSetB are structurally dissimilar, whereas TrainSetA and TestSetA have some structural similarity. All the models were trained with TrainSetA and were then evaluated using TestSetA and TestSetB. The results in Table 1 and Fig. S1 show that the base model achieved extremely high accuracy for TestSetA, but quite poor accuracy for TestSetB, suggesting that the base model might be categorized as being prone to heavy overfitting. In contrast, the model using the complete novel thermodynamic integration showed much better accuracy for TestSetB compared with the base model, indicating that the thermodynamic integration enables robust predictions.

Comparison with the existing methods. We compared our algorithm with eight available folding algorithms: MXfold version 0.0.2[17], LinearFold-V (committed on Feb 5, 2020)[20], CONTRAfold version 2.02[10,11], ContextFold version 1.00[12], CentroidFold version 0.0.16[21,22], RNAfold in Vienna RNA package version 2.4.14[6,7], SimFold version 2.1[15,16], and RNAstructure version 6.2[8,9]. The parameters of three trainable algorithms, namely, MXfold, CONTRAfold, and ContextFold, trained their parameters with TrainSetA. For the other algorithms, default parameters were used.

Table 1: Comparison of the accuracy of the secondary structure prediction between the base model and the use of thermodynamic integration. (+int. = the use of the thermodynamic-integrated folding scores; +reg. = the use of thermodynamic regularization.)

	TestSetA			TestSetB		
	PPV	SEN	F	PPV	SEN	F
base model	0.794	0.824	0.804	0.461	0.545	0.494
+int.	0.799	0.825	0.808	0.500	0.571	0.527
+reg.	0.765	0.796	0.776	0.542	0.647	0.583
final model	0.754	0.778	0.761	0.571	0.650	0.601

Figures 3a and 3b show PPV-SEN plots of prediction accuracy for TestSetA and TestSetB, respectively. The maximum expected accuracy (MEA)-based secondary structure predictions, CONTRAfold and CentroidFold, can control PPV and SEN through the parameter γ, and therefore, their accuracies are shown as the curves for multiple $\gamma \in \{2^n \mid -5 \leq n \leq 10\}$.

For the predictions on TestSetA, our algorithm, MXfold2 achieved the best accuracy ($F = 0.761$), followed by ContextFold ($F = 0.759$), MXfold ($F = 0.739$), and CONTRAfold ($F = 0.719$ at γ=4.0). However, for the predictions on TestSetB, which is structurally dissimilar from TrainSetA, we observe that ContextFold achieved the worst accuracy ($F = 0.502$), as Rivas *et al.*[13] have pointed out that ContextFold might be prone to overfitting. In contrast, we do not observe heavy overfitting as with ContextFold for MXfold2 ($F = 0.601$), MXfold ($F = 0.581$), and CONTRAfold ($F = 0.573$ at γ=4.0).

Figure 3: Positive predictive value (PPV) and sensitivity (SEN) plots for (a) TestSetA, (b) TestSetB, and (c) the combined dataset with TestSetA and TestSetB. (d) F-values of the combined test data for all the methods.

Figures 3c and 3d show the PPV-SEN plot and the distribution of F-values, respectively, on the combined dataset comprising TestSetA and TestSetB. These results indicate that MXfold2 ($F = 0.693$) achieved the best accuracy, followed by the trainable methods, namely, MXfold ($F = 0.673$), CONTRAfold ($F = 0.658$ at γ=4.0), and ContextFold ($F = 0.651$), which outperformed the thermodynamics-based methods.

Comparison with DNN-based methods. We compared our algorithm, MXfold2, with two recently published DNN-based methods: SPOT-RNA[18] and E2Efold[19]. We trained MXfold2 using their available training datasets and tested the prediction accuracy on their test datasets for direct comparison. Furthermore, because their datasets were designed only for sequence-wise cross-validation, we developed bpRNA-new dataset for family-wise cross-validation that does not contain any families present in their training datasets.

Table 2 and Fig. S2 show the comparison of the prediction accuracy between MXfold2, SPOT-RNA, ContextFold, and RNAfold, in which MXfold2 and ContextFold were trained on the TR0 dataset, which is a subset of bpRNA-1m dataset[23]. In contrast, SPOT-RNA used the pre-trained model trained on the TR0 dataset and an additional dataset for transfer learning. All of these methods were tested using the TS0 dataset, which is also a subset of bpRNA-1m dataset, for sequence-wise cross-validation, after which the bpRNA-new dataset was used for family-wise cross-validation.

We observe that MXfold2 performs slightly worse in sequence-wise cross-validation relative to SPOT-RNA but is more accurate in terms of family-wise cross-validation. In addition, as shown

Table 2: Comparison of the accuracy of the secondary structure prediction between MXfold2, SPOT-RNA, ContextFold, and RNAfold on TS0 for sequence-wise cross-validation (CV) and the bpRNA-new dataset for family-wise CV. All trainable methods were trained with TR0.

	Sequence-wise CV			Family-wise CV		
	PPV	SEN	F	PPV	SEN	F
MXfold2	0.520	0.682	0.575	0.585	0.710	0.632
SPOT-RNA	0.652	0.578	0.597	0.599	0.619	0.596
ContextFold	0.583	0.595	0.575	0.595	0.539	0.554
RNAfold	0.446	0.631	0.508	0.552	0.720	0.617

in Fig. S3, MXfold2 is, on average, approximately 15 and 36 times faster than SPOT-RNA when using GPU and CPU, respectively.

We also compared MXfold2 with E2Efold, ContextFold, and RNAfold (Table S2 and Fig. S4), in which E2Efold used the pre-trained model trained on a subset of the RNAStrAlign dataset[24], and MXfold2 and ContextFold were trained on the same dataset. All of these methods were tested on a subset of the ArchiveII dataset[25] for sequence-wise cross-validation and the bpRNA-new dataset for family-wise cross-validation. These results show that E2Efold almost completely failed to predict secondary structures for unseen families (F=0.0361), whereas MXfold2 accurately predicted their secondary structures (F=0.628).

Correlation with free energy. We investigated the correlation between the free energy and the predicted folding score using the T-Full dataset[16], which contains sequence-structure-energy triplets.

Table 3: Comparison of the accuracy of the secondary structure prediction, the root mean squared error (RMSE, measured in kcal/mol) and the Spearman's rank correlation coefficient (ρ) between the folding score and free energy for the T-Full dataset. (*MXfold2 without the thermodynamic regularization.)

	PPV	SEN	F	RMSE	ρ
MXfold2	0.984	0.978	0.980	3.260	0.833
MXfold2 w/o th.*	0.980	0.972	0.973	3.607	0.538
CONTRAfold	0.963	0.639	0.643	5.781	0.736
RNAfold	0.979	0.964	0.963	2.868	0.909

Table 3 shows the root mean squared error (RMSE) and the Spearman's rank correlation coefficient (ρ) between the free energy of the reference structure and the folding score of the predicted structure for MXfold2 with and without thermodynamic regularization compared with CONTRAfold and RNAfold. The folding score of MXfold2 is highly correlated with the true free energy, though it is not as high as that of RNAfold. In contrast, even though MXfold2 without thermodynamic regularization is able to predict secondary structures as accurately as MXfold2 with thermodynamic regularization, its folding score is not highly correlated with the true free energy. This suggests that high accuracy in the secondary structure prediction does not directly lead to the reliable evaluation of thermodynamic stability.

Discussion

Our experiments showed that several methods with rich parameterization achieved excellent performance for test datasets structurally similar to training datasets, but poor performance for test datasets structurally dissimilar from training datasets. Rivas *et al.*[13] have already pointed out that rich-parameterized methods might easily tend towards overfitting. Such secondary structure prediction methods would be useful if we could know a priori whether the sequence we want to predict is a member of a family included in the training data. However, if we have knowledge about the family of the sequences whose structures are to be predicted, homology searches for RNA sequences, such as Infernal[26], are a better choice. In other words, the lack of prior knowledge about sequences is a major reason the prediction of secondary structures from single sequences is an important goal. In principle, regardless of whether a given sequence is within a family included in a training dataset or not, robust methods should be able to properly predict its secondary structure because its secondary structure is formed under the same physical laws. In general, machine learning-based methods can be expected to improve prediction accuracy by increasing the number of training samples. Although the development of sequencing techniques has made it easier to obtain sequence data, it is still not easy to increase the amount of training data because of the significant effort required to obtain those empirically determined secondary structures. Therefore, it is impractical to predict secondary structures of newly discovered sequences using methods that are not generalizable to a wide variety of sequences, such as those methods that rely on only memorizing sequences and their secondary structures within a large number of neural network parameters. We designed our experiments to predict secondary structures of newly discovered RNAs using test

datasets structurally dissimilar from training datasets, e.g., TestSetB for TrainSetA (originally developed by Rivas *et al.*[13]) and the bpRNA-new dataset for TR0. These conditions are among the most important situations for RNA secondary structure prediction from single sequences, and our method, which is able to achieve high accuracy under these conditions, is useful in practice.

Estimation of free energies is important for applications other than structure prediction, such as small interfering RNA selection using hybridization thermodynamics[27]. Table 3 indicates that RNAfold and MXfold2 with thermodynamic regularization can calculate folding scores that are highly correlated with true free energy estimates, at least for sequences for which secondary structures can be predicted with high accuracy. Given that MXfold2 is more accurate in secondary structure prediction compared with RNAfold, as mentioned above, MXfold2 can be expected to evaluate thermodynamic stability with high accuracy for more sequences compared with RNAfold.

Methods

Using a deep neural network to compute folding scores. Figure 2 shows the overview of our deep neural network, which is used to calculate four types of folding scores for each pair of nucleotides in a given sequence: helix stacking, helix opening, helix closing, and unpaired region.

The input of the network is an RNA sequence of length L. Each base (A, C, G, or U) is encoded into d-dimensional embeddings using a trainable embedding function.

The $L \times d$-dimensional sequence embedding is entered into 1D convolution blocks (Block 1) repeated N_1 times. Each 1D convolution block consists of two convolutional layers, each with a

kernel size of 5 and 3, respectively, and a depth of d. The layer normalization[28] and continuously differentiable exponential linear units (CELU) activation functions[29] are employed. A dropout rate of 50 % is used to avoid overfitting[30]. To efficiently train deep neural networks, a residual connection[31] that skips each layer is employed.

The next block (Block 2) contains N_2 layers of the bidirectional long short-term memory (LSTM) network[32]. The number of hidden units in each direction of the LSTM network is $d/2$. Each LSTM layer is followed by the layer normalization and CELU activation functions. A dropout rate of 50 % is also used in LSTM layers.

The $L \times d$ matrix obtained so far is divided into two matrices of size $L \times d/2$; one of the two matrices expands in the column direction and the other in the row direction, and then the two matrices are concatenated into an $L \times L \times d$ matrix. This matrix is entered into 2D convolution blocks (Block 3) N_3 times. Each 2D convolution block consists of two convolutional layers, each with a kernel size of 5×5 and 3×3, respectively, and a depth of d. The layer normalization and CELU functions with a dropout rate of 50 % are again utilized.

Finally, four types of folding scores for each pair of i-th and j-th nucleotides are calculated by 3-layer multilayer perceptron with h hidden units.

We used the following values for the above hyperparameters: $d = 64$, $N_1 = 4$, $N_2 = 2$, $N_3 = 4$, and $h = 32$.

Using dynamic programming to predicting RNA secondary structure. Similar to traditional folding methods, such as RNAfold and CONTRAfold, our algorithm adopts the nearest-neighbor model[3,33] as an RNA secondary structure model without pseudoknots. As an alternative to the thermodynamic parameters, our algorithm calculates the free energy of the nearest-neighbor loops using four types of folding scores computed by the deep neural network described in the previous section. The four types of the folding scores are helix stacking scores, helix opening scores, helix closing scores, and unpaired region scores (Fig. 2). For example, the folding score of the internal loop consisting of bases 25–29 and 43–47 in Fig. 1 is calculated by summing the helix closing score for (25, 47), the helix opening score for (28, 44), and the unpaired region scores for (26, 28) and (44, 46). Similarly, the folding score of the base-pair stacking consisting of 23–24 and 48–49 in Fig. 1 is calculated from the helix stacking score for (23, 49).

Similar to MXfold, we integrate our model with the thermodynamic model by adding the negative value of the Turner free energy[3] to the folding scores calculated by the deep neural network for each nearest-neighbor loop. We define our scoring function of a secondary structure y given an RNA sequence x as

$$f(x, y) = f_T(x, y) + f_W(x, y), \tag{1}$$

where $f_T(x, y)$ is the contribution of the thermodynamic parameters (i.e., the negative value of the free energy of y) and $f_W(x, y)$ is the contribution of the deep neural network, which is calculated as the sum of the folding scores over the decomposed nearest-neighbor loops as described above. Zuker-style dynamic programming can be applied to find an optimal secondary structure that maximizes the scoring function (1).

Training parameters with the max-margin framework. To optimize the network parameters λ, we employed a max-margin framework called the structured support vector machine (SSVM)[34]. Given a training dataset $\mathcal{D} = \{(x^{(k)}, y^{(k)})\}_{k=1}^{K}$, where $x^{(k)}$ is the k-th RNA sequence and $y^{(k)}$ is the reference secondary structure for the k-th sequence $x^{(k)}$, we aim to find a set of parameters λ that minimizes the objective function:

$$\mathcal{L}(\lambda) = \sum_{(x,y) \in \mathcal{D}} \left\{ \left(\max_{\hat{y} \in \mathcal{S}(x)} [f(x, \hat{y}) + \Delta(y, \hat{y})] - f(x, y) \right) + C_1 [f(x, y) - f_T(x, y)]^2 + C_2 ||\lambda||_2 \right\}, \tag{2}$$

where $\mathcal{S}(x)$ is a set of all possible secondary structures of x. The first term is the structured hinge loss function[34]. Here, $\Delta(y, \hat{y})$ is a margin term of $\hat{y}$ for y defined as

$$\Delta(y, \hat{y}) = \delta^{\text{FN}} \times (\text{\# of false-negative base pairs}) + \delta^{\text{FP}} \times (\text{\# of false-positive base pairs}),$$

where δ^{FN} and δ^{FP} are tunable hyperparameters that control the trade-off between sensitivity and specificity for learning the parameters. We used $\delta^{\text{FN}} = 0.5$ and $\delta^{\text{FP}} = 0.005$ by default. The margin term for structured models enables robust predictions by maximizing the margin between $f(x, y)$ and $f(x, \hat{y})$ for $y \neq \hat{y}$. We can calculate the first term of Eq. (2) using Zuker-style dynamic programming modified by the loss-augmented inference[34]. The second and third terms of Eq. (2) are regularization terms that penalize parameter values that are extreme relative to a postulated distribution. The second term is our proposed thermodynamic regularization, which prevents the folding score of the secondary structure from differing significantly from the free energy of the thermodynamic parameters. The third term of Eq. (2) is the ℓ_2 regularization term. We used $C_1 = 0.125$ and $C_2 = 0.01$ by default. To minimize the objective function (2), we employ the Adam optimizer[35].

Datasets. To evaluate our algorithm, we performed computational experiments on several datasets. Table S1 shows a summary of the datasets used in our experiments.

The first dataset, which has been carefully established by Rivas *et al.*[13], includes TrainSetA, TestSetA, TrainSetB, and TestSetB. TrainSetA and TestSetA were collected from the literature[10, 15, 16, 36–38]. TrainSetB and TestSetB, which contain 22 families with 3D structure annotations, were extracted from Rfam 10.0[39]. The sequences in Train/TestSetB share less than 70 % sequence identity with the sequences in TrainSetA. We excluded a number of sequences that contain pseudoknotted secondary structures in the original data sources from all four sub-datasets since all algorithms evaluated in this study were designed for predicting RNA secondary structures without pseudoknots. It is important to note that literature-based TrainSetA and Rfam-based TestSetB are structurally dissimilar, whereas TrainSetA and TestSetA have some structural similarity.

To compare our algorithm with SPOT-RNA[18], we employed the same dataset extracted from the bpRNA-1m dataset[23], which is based on Rfam 12.2[40] with 2,588 families. After removing redundant sequences based on sequence identity, the bpRNA-1m dataset was randomly split into three sub-datasets, namely, TR0, VL0, and TS0, for training, validation, and testing, respectively. Note that this partition is not family-wise, but sequence-wise. SPOT-RNA performed the initial training and validation using TR0 and VL0, which was followed by testing using TS0 and then transfer learning using other PDB-based datasets.

To confirm the robustness against "unseen" families, we built a new dataset that includes new families from the most recent Rfam database, Rfam 14.2[41]. Since the release of Rfam 12.2, from

which bpRNA-1m is derived, the Rfam project has been actively collecting about 1,500 new RNA families, including families detected by new techniques[42]. We first extracted these new families. Then, as with SPOT-RNA, we removed redundant sequences by CD-HIT-EST[43], with a cutoff threshold of 80 %, and discarded sequences whose lengths exceeded 500 bp. Our new dataset is referred to as bpRNA-new.

We also compared our algorithm with E2Efold[19], using the same experimental conditions in which the RNAStrAlign dataset[24] and the ArchiveII dataset[25] were employed for training and testing, respectively. Note that this setting is also not family-wise, but sequence-wise, because both datasets contain the same families.

To investigate the correlation between folding score and free energy, we employed the T-Full dataset, which was compiled by Andronescu *et al.*[16]. Each sequence in the T-Full dataset has a corresponding reference secondary structure as well as its free energy change derived from optical melting experiments.

Performance measure. We evaluated the accuracy of predicting RNA secondary structures through the positive predictive value (PPV) and the sensitivity (SEN) of the base pairs, defined as

$$PPV = \frac{TP}{TP + FP}, \quad SEN = \frac{TP}{TP + TN},$$

where TP is the number of correctly predicted base pairs (true positives), FP is the number of incorrectly predicted base pairs (false positives), and FN is the number of base pairs in the reference structure that were not predicted (false negatives). We also used the F-value as the

balanced measure between PPV and SEN, which is defined as their harmonic mean:

$$F = \frac{2 \times SEN \times PPV}{SEN + PPV}.$$

For the experiment on the T-Full dataset, we evaluated the root mean squared error (RMSE)

$$RMSE = \sqrt{\frac{1}{N} \sum_{i=1}^{N} (e_i - \hat{e}_i)^2},$$

where e_i and $\hat{e}_i$ are the free energy of the reference secondary structure and the negative value of the folding score of the predicted secondary structure for the i-th sequence, respectively. We also evaluated the Spearman's rank correlation coefficient (ρ) between e and $\hat{e}$.

1. Hirose, T., Mishima, Y. & Tomari, Y. Elements and machinery of non-coding RNAs: toward their taxonomy. *EMBO Rep.* **15**, 489–507 (2014).

2. Schroeder, S. J. & Turner, D. H. Optical melting measurements of nucleic acid thermodynamics. *Methods Enzymol.* **468**, 371–387 (2009).

3. Turner, D. H. & Mathews, D. H. NNDB: the nearest neighbor parameter database for predicting stability of nucleic acid secondary structure. *Nucleic Acids Res.* **38**, D280–2 (2010).

4. Zuker, M. Mfold web server for nucleic acid folding and hybridization prediction. *Nucleic Acids Res.* **31**, 3406–3415 (2003).

5. Markham, N. R. & Zuker, M. UNAFold: software for nucleic acid folding and hybridization. *Methods Mol. Biol.* **453**, 3–31 (2008).

6. Hofacker, I. L. Vienna RNA secondary structure server. *Nucleic Acids Res.* **31**, 3429–3431 (2003).

7. Lorenz, R. *et al.* ViennaRNA package 2.0. *Algorithms Mol. Biol.* **6**, 26 (2011).

8. Mathews, D. H., Andre, T. C., Kim, J., Turner, D. H. & Zuker, M. An updated recursive algorithm for RNA secondary structure prediction with improved thermodynamic parameters (1997).

9. Reuter, J. S. & Mathews, D. H. RNAstructure: software for RNA secondary structure prediction and analysis. *BMC Bioinformatics* **11**, 129 (2010).

10. Do, C. B., Woods, D. A. & Batzoglou, S. CONTRAfold: RNA secondary structure prediction without physics-based models. *Bioinformatics* **22**, e90–8 (2006).

11. Foo, C.-S., Do, C. B. & Ng, A. Y. Efficient multiple hyperparameter learning for log-linear models. In Platt, J. C., Koller, D., Singer, Y. & Roweis, S. T. (eds.) *Advances in Neural Information Processing Systems 20*, 377–384 (Curran Associates, Inc., 2008).

12. Zakov, S., Goldberg, Y., Elhadad, M. & Ziv-Ukelson, M. Rich parameterization improves RNA structure prediction. *J. Comput. Biol.* **18**, 1525–1542 (2011).

13. Rivas, E., Lang, R. & Eddy, S. R. A range of complex probabilistic models for RNA secondary structure prediction that includes the nearest-neighbor model and more. *RNA* **18**, 193–212 (2012).

14. Darty, K., Denise, A. & Ponty, Y. VARNA: Interactive drawing and editing of the RNA secondary structure. *Bioinformatics* **25**, 1974–1975 (2009).

15. Andronescu, M., Condon, A., Hoos, H. H., Mathews, D. H. & Murphy, K. P. Efficient parameter estimation for RNA secondary structure prediction. *Bioinformatics* **23**, i19–28 (2007).

16. Andronescu, M., Condon, A., Hoos, H. H., Mathews, D. H. & Murphy, K. P. Computational approaches for RNA energy parameter estimation. *RNA* **16**, 2304–2318 (2010).

17. Akiyama, M., Sato, K. & Sakakibara, Y. A max-margin training of RNA secondary structure prediction integrated with the thermodynamic model. *J. Bioinform. Comput. Biol.* **16**, 1840025 (2018).

18. Singh, J., Hanson, J., Paliwal, K. & Zhou, Y. RNA secondary structure prediction using an ensemble of two-dimensional deep neural networks and transfer learning. *Nat. Commun.* **10**, 5407 (2019).

19. Chen, X., Li, Y., Umarov, R., Gao, X. & Song, L. RNA secondary structure prediction by learning unrolled algorithms. In *Proceedings of the 8th International Conference on Learning Representations* (2020).

20. Huang, L. *et al.* LinearFold: linear-time approximate RNA folding by 5'-to-3' dynamic programming and beam search. *Bioinformatics* **35**, i295–i304 (2019).

21. Hamada, M., Kiryu, H., Sato, K., Mituyama, T. & Asai, K. Prediction of RNA secondary structure using generalized centroid estimators. *Bioinformatics* **25**, 465–473 (2009).

22. Sato, K., Hamada, M., Asai, K. & Mituyama, T. CentroidFold: A web server for RNA secondary structure prediction. *Nucleic Acids Res.* **37**, 277–280 (2009).

23. Danaee, P. *et al.* bpRNA: large-scale automated annotation and analysis of RNA secondary structure. *Nucleic Acids Res.* **46**, 5381–5394 (2018).

24. Tan, Z., Fu, Y., Sharma, G. & Mathews, D. H. TurboFold II: RNA structural alignment and secondary structure prediction informed by multiple homologs. *Nucleic Acids Res.* **45**, 11570–11581 (2017).

25. Sloma, M. F. & Mathews, D. H. Exact calculation of loop formation probability identifies folding motifs in RNA secondary structures. *RNA* **22**, 1808–1818 (2016).

26. Nawrocki, E. P. & Eddy, S. R. Infernal 1.1: 100-fold faster RNA homology searches. *Bioinformatics* **29**, 2933–2935 (2013).

27. Lu, Z. J. & Mathews, D. H. Efficient siRNA selection using hybridization thermodynamics. *Nucleic Acids Res.* **36**, 640–647 (2008).

28. Ba, J. L., Kiros, J. R. & Hinton, G. E. Layer normalization. arXiv preprint arXiv:1607.06450 [stat.ML] (2016).

29. Barron, J. T. Continuously differentiable exponential linear units. arXiv preprint arXiv:1704.07483 [cs.LG] (2017).

30. Hinton, G. E., Srivastava, N., Krizhevsky, A., Sutskever, I. & Salakhutdinov, R. R. Improving neural networks by preventing co-adaptation of feature detectors. arXiv preprint arXiv:1207.0580 [cs.NE] (2012).

31. He, K., Zhang, X., Ren, S. & Sun, J. Deep residual learning for image recognition. arXiv preprint arXiv:1512.03385 [cs.CV] (2015).

32. Hochreiter, S. & Schmidhuber, J. Long short-term memory. *Neural Comput.* **9**, 1735–1780 (1997).

33. Tinoco, I., Jr *et al.* Improved estimation of secondary structure in ribonucleic acids. *Nat. New Biol.* **246**, 40–41 (1973).

34. Tsochantaridis, I., Joachims, T., Hofmann, T. & Altun, Y. Large margin methods for structured and interdependent output variables. *J. Mach. Learn. Res.* **6**, 1453–1484 (2005).

35. Kingma, D. P. & Ba, J. Adam: A method for stochastic optimization. In *Proceedings of the 3rd International Conference for Learning Representations* (2015).

36. Steinberg, S., Misch, A. & Sprinzl, M. Compilation of tRNA sequences and sequences of tRNA genes. *Nucleic Acids Res.* **21**, 3011–3015 (1993).

37. Dowell, R. D. & Eddy, S. R. Evaluation of several lightweight stochastic context-free grammars for RNA secondary structure prediction. *BMC Bioinformatics* **5**, 71 (2004).

38. Lu, Z. J., Gloor, J. W. & Mathews, D. H. Improved RNA secondary structure prediction by maximizing expected pair accuracy. *RNA* **15**, 1805–1813 (2009).

39. Gardner, P. P. *et al.* Rfam: Wikipedia, clans and the "decimal" release (2011).

40. Nawrocki, E. P. *et al.* Rfam 12.0: updates to the RNA families database. *Nucleic Acids Res.* **43**, D130–7 (2015).

41. Kalvari, I. *et al.* Rfam 13.0: shifting to a genome-centric resource for non-coding RNA families. *Nucleic Acids Res.* **46**, D335–D342 (2018).

42. Weinberg, Z. *et al.* Detection of 224 candidate structured RNAs by comparative analysis of specific subsets of intergenic regions. *Nucleic Acids Res.* **45**, 10811–10823 (2017).

43. Fu, L., Niu, B., Zhu, Z., Wu, S. & Li, W. CD-HIT: accelerated for clustering the next-generation sequencing data. *Bioinformatics* **28**, 3150–3152 (2012).

Acknowledgements This work was partially supported by a Grant-in-Aid for Scientific Research (B) (No. 19H04210) and Challenging Research (Exploratory) (No. 19K22897) from the Japan Society for the Promotion of Science (JSPS) to K.S. and a Grant-in-Aid for JSPS Fellows (No. 18J21767) from JSPS to M.A. This work was also supported by a Grant-in-Aid for Scientific Research on Innovative Areas "Frontier Research on Chemical Communications." The supercomputer system used for this research was provided by the National Institute of Genetics (NIG), Research Organization of Information and Systems (ROIS).

Authors Contributions K.S. conceived the study, implemented the algorithm, conducted experiments, and drafted the paper. K.S. and M.A. discussed the network architectures, designed the experiments, and collected the datasets. All authors read, contributed to the discussion, and approved the final paper.

Availability The source code of MXfold2 and the datasets used in the present experiments are available

at `https://github.com/keio-bioinformatics/mxfold2/`, and the web server of MXfold2

is working at `http://www.dna.bio.keio.ac.jp/mxfold2/`.

Competing Interests   The authors declare that they have no competing financial interests.

Correspondence   Correspondence and requests for materials should be addressed to K.S. (email: sato-ken@bio.keio.ac.jp).

Supplementary material of "RNA secondary structure prediction using deep learning with thermodynamic integration"

Kengo Sato[1,*], Manato Akiyama[1], and Yasubumi Sakakibara[1]

[1] Department of Biosciences and Informatics, Keio University, 3–14–1 Hiyoshi, Kohoku-ku, Yokohama 223–8522, Japan.
[*] To whom correspondence should be addressed.

Figure S1: F-values of the base model and the use of thermodynamic integration. (+int. = the use of the thermodynamic-integrated folding scores; +reg. = the use of thermodynamic regularization.)

Figure S2: *F*-values of MXfold2, SPOT-RNA, ContextFold, and RNAfold on TS0 for sequence-wise cross-validation (CV) and the bpRNA-new dataset for family-wise CV. All trainable methods were trained with TR0.

Figure S3: The running time for the lengths of input sequences in TestSetA measured on Linux OS v4.15.0 with Intel XeonE5-2698v4 (2.20 GHz) and NVIDIA Tesla V100.

Figure S4: *F*-values of MXfold2, E2Efold, ContextFold, and RNAfold using ArchiveII for sequence-wise cross-validation (CV) and the bpRNA-new dataset for family-wise CV. All trainable methods were trained using the RNAStrAlign dataset.

Table S1: The summary of datasets used in our experiments.

		# sequences	length	source
Rivas Dataset	TrainSetA	3,166	10–734	Rivas *et al.* [3]
	TestSetA	592	10–768	
	TestSetB	430	27–244	
bpRNA-1m	TR0	10,814	33–498	Danaee *et al.* [2]
	TS0	1,305	22–499	
bpRNA-new		5,401	33–489	the present study
RNAStrAlign	train	20,923	30–600	Tan *et al.* [5]
ArchiveII		3,966	28–1,800	Sloma *et al.* [4]
T-Full		1,291	9–55	Andronescu *et al.* [1]

Table S2: Comparison of the accuracy of the secondary structure prediction between MXfold2, E2Efold, ContextFold, and RNAfold using ArchiveII for sequence-wise cross-validation (CV) and the bpRNA-new dataset for family-wise CV. All trainable methods were trained using the RNAS-trAlign dataset.

	Sequence-wise CV			Family-wise CV		
	PPV	SEN	*F*	PPV	SEN	*F*
MXfold2	0.790	0.815	0.800	0.575	0.712	0.628
E2Efold	0.605	0.519	0.548	0.0474	0.0307	0.0361
ContextFold	0.770	0.771	0.768	0.559	0.506	0.522
RNAfold	0.551	0.613	0.577	0.552	0.720	0.617

References

[1] M. Andronescu, A. Condon, H. H. Hoos, D. H. Mathews, and K. P. Murphy. Computational approaches for RNA energy parameter estimation. *RNA*, 16(12):2304–2318, Dec. 2010.

[2] P. Danaee, M. Rouches, M. Wiley, D. Deng, L. Huang, and D. Hendrix. bpRNA: large-scale automated annotation and analysis of RNA secondary structure. *Nucleic Acids Res.*, 46(11):5381–5394, June 2018.

[3] E. Rivas, R. Lang, and S. R. Eddy. A range of complex probabilistic models for RNA secondary structure prediction that includes the nearest-neighbor model and more. *RNA*, 18(2):193–212, Feb. 2012.

[4] M. F. Sloma and D. H. Mathews. Exact calculation of loop formation probability identifies folding motifs in RNA secondary structures. *RNA*, 22(12):1808–1818, Dec. 2016.

[5] Z. Tan, Y. Fu, G. Sharma, and D. H. Mathews. TurboFold II: RNA structural alignment and secondary structure prediction informed by multiple homologs. *Nucleic Acids Res.*, 45(20):11570–11581, 2017.